

RESTRICTED

CLASS 48

**CAPACITORS
(ALL TYPES)**

Includes: Fixed, Variable, and Adjustable Capacitors,
With Air, Mica, Paper, Electrolytic, Ceramic,
Oil, Plastic, Etc., Dielectrics

NAVSHIPS 900,109 (A)

RESTRICTED

CLASS 48 TO NAVY TYPE

RESTRICTED

SHEET 48 - 2

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48001-B20	CAPACITOR, fixed: 12/22/31 NT-48001 w/100 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B101M	16-C-28564-6747	R16-C-9934-12	R16-C-9928-740		CD CAW CRV	9L-53010 1652L AF, FARADON	CRV	K-35485-4	TBS thru TBS-8
-48001-C2	CAPACITOR, fixed: 12/22/31 NT-48001 w/100 mmf p/m 2%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C101G	16-C-28549-2312		R16-C-9928-3		CD CAW	9L-53010 1652L			
-48001-C5	CAPACITOR, fixed: 12/22/31 NT-48001 w/100 mmf p/m 5%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C101J	16-C-28554-3792		R16-C-9928-200		CD CAW	9IST 1652IST	CSL	XMCW 2.5-31-5	
-48001-C10	CAPACITOR, fixed: 12/22/31 NT-48001 w/100 mmf p/m 10%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C101K	16-C-28559-4272		R16-C-9928-560		CD CAW	9L-53010 1652L			
-48001-C20	CAPACITOR, fixed: 12/22/31 NT-48001 w/100 mmf p/m 20%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C101M	16-C-28564-6752		R16-C-9928-770		CD CAW	9L-53010 1652L			
-48001-D2	CAPACITOR, fixed: 12/22/31 NT-48001 w/100 mmf p/m 2%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D101G	16-C-28549-2317		R16-C-9928-4		CD	9H-53010			
-48001-D5	CAPACITOR, fixed: 12/22/31 NT-48001 w/100 mmf p/m 5%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D101J	16-C-28554-3797		R16-C-9928-250		CD	9H-53010			
-48001-D10	CAPACITOR, fixed: 12/22/31 NT-48001 w/100 mmf p/m 10%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D101K	16-C-28559-4277		R16-C-9928-590		CD	9H-53010			
-48001-D20	CAPACITOR, fixed: 12/22/31 NT-48001 w/100 mmf p/m 20%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D101M	16-C-28564-6757		R16-C-9928-800		CD	9H-53010			
-48002	CAPACITOR, fixed: 12/22/31 mica dielectric; 400 mmf; 5000 max vdcw 4.0 amp at 3000 kc, 2.5 amp at 1000 kc, 1.0 amp at 300 kc, 0.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; 2 stud term top 1/2" h on 1 5/8" ctr; two 3/16" diam mtg holes on bottom on 2 5/8" mtg/c; add suffix indicating capacitor tolerance in per cent.	RE48A131 16C40										
-48002-A2	CAPACITOR, fixed: 12/22/31 NT-48002 w/400 mmf p/m 2%; temp coef ltr A.	RE48A131 16C40		16-C-29921-5638				CAW	1550-208	CDE		YF (4)
-48002-A5	CAPACITOR, fixed: 12/22/31 NT-48002 w/400 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-29926-7118				CD CRV	FL-283-6 Model 100-3103	CAY CRV CRV	M-7404262-1rev0 K-860215-5rev6 DL-500497-502 K-35256-1	GP GP-2
-48002-B2	CAPACITOR, fixed: 12/22/31 NT-48002 w/400 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-29921-5643				CAW	1550L	CDE	S-2378-4	YR (2) Con't

SHEET 48-2

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 3

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48002-B5	CAPACITOR, fixed: 12/22/31 Navy Type 48002 w/400 mmf p/m 5%; temp coef letter B. NOTE: TBK-17; TBK-19; TBL-4; TBL-8; TBL-9.	RE48A131 16C40		16-C-29926-7123	N16-C-10011			CD CRV CRV CRV	PL-283-6L UC3103 DL-500497-502 K-35356-1	K-860215-5 rev 3	TBK-8 TBK-10 TBK-12 TBK-14 SEE NOTE
-48003	CAPACITOR, fixed: 12/22/31 mica; 50,000 mmf; 1500 vdcw max 13 amp at 3000 kc, 15 amp at 1000 kc, 12 amp at 300 kc, 7 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term top 1/2" h on 1 5/8" c to c; two 3/16" diam mtg holes on bottom on 2 5/8" c to c.	RE48A131 16C40									
-48003-A5	CAPACITOR, fixed: 12/22/31 NT-48003 w/50,000 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-35227-5709	N16-C-10596			CD CRV	PL-118-6	CAY K-860215-23rev6 744-33	NT QCF
-48003-B5	CAPACITOR, fixed: 12/22/31 NT-48003 w/50,000 mmf p/m 5%; temp coef ltr B. NOTE: QCW; QCX; QCY; QCZ; TBK-8 (3); TBK-10 (3); TBK-12 (3); TBK-14 (3); TBK-17 (3); TBK-19 (3); TBL-4 (7); TBL-8 (7); TBL-9 (7); WEA.	RE48A131 16C40		16-C-35227-5714	N16-C-10596			CRV	UC-2990A	W-303346-11 K-860215-23 DL-500402-502	NM-3 RMB-1 QC-3 (2) SEE NOTE
-48004	CAPACITOR, fixed: 12/22/31 mica; 100 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 11/32" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40									
-48004-A10	CAPACITOR, fixed: 12/22/31 NT-48004 w/100 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-28558-3551				CD CAN	9-13010 A	CG P-7760498-10	RAF
-48004-B2	CAPACITOR, fixed: 12/22/31 NT-48004 w/100 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-28548-1591				CD	9-13010		
-48004-B10	CAPACITOR, fixed: 12/22/31 NT-48004 w/100 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-28558-3556	N16-C-9925			CD	9L-13010		
-48005	CAPACITOR, fixed: 12/22/31 mica; 150 mmf; 600 vdcw; 1000v DC test; case 1 13/16" lg x 1 11/32" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40									
-48005-A10	CAPACITOR, fixed: 12/22/31 NT-48005 w/150 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-28980-3951				CD	9-13015		
-48005-B2	CAPACITOR, fixed: 12/22/31 NT-48005 w/150 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-28970-1996				CD	9-13015		
-48005-B10	CAPACITOR, fixed: 12/22/31 NT-48005 w/150 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-28980-3956				CD	9L-13015		

SHEET 48-3

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 4

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48006	CAPACITOR, fixed: 12/22/31 mica; 200 mmf; 600 vdcw, 1000v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48006-A10	CAPACITOR, fixed: 12/22/31 NT-48006 w/200 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-29270-5351				CD	9-13020			
-48006-B2	CAPACITOR, fixed: 12/22/31 NT-48006 w/200 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-29260-3396	N16-C-9968			CD	9-13020			
-48006-B5	CAPACITOR, fixed: 12/22/31 NT-48006 w/200 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40		16-C-29265-4876				CD	9LS-13020	COL	910N320H	
-48006-B20	CAPACITOR, fixed: 12/22/31 NT-48006 w/200 mmf p/m 20%; temp coef ltr B.	RE48A112 16C40		16-C-29275-7836	N16-C-9967-100			CD	9L-13020			
-48007	CAPACITOR, fixed: 12/22/31 mica; 250 mmf; 600 vdcw, 1000v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48007-A10	CAPACITOR, fixed: 12/22/31 NT-48007 w/250 mmf p/m 10%; temp coef ltr A	RE48A112 16C40		16-C-29481-5551	N16-C-9975-4			CD	9-13025			
-48007-B2	CAPACITOR, fixed: 12/22/31 NT-48007 w/250 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-29471-3596	N16-C-9975-5	R16-C-9975-5		CD	9-13025			
-48007-B5	CAPACITOR, fixed: 12/22/31 NT-48007 w/250 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40		16-C-29476-5076			3D9250-16	CD CAN	9LS-13025 AF	COL CG	910N325H P-7760498-65	RAF
-48007-B10	CAPACITOR, fixed: 12/22/31 NT-48007 w/250 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-29481-5556	N16-C-9975-4			CAN	A-10	COL	910N325A	TCA
-48007-C10	CAPACITOR, FIXED: 10/29/48 Navy Type 48007 w/250 mmf p/m 10%; temp coef letter C.			16-C-29481-5564				CD	9LST	CG	7350590-P1213	TBJ
-48008	CAPACITOR, fixed: 12/22/31 mica; 300 mmf; 600 vdcw, 1000v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48008-A10	CAPACITOR, fixed: 12/22/31 NT-48008 w/300 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-29666-2353				CD	9-13030			
-48008-B2	CAPACITOR, fixed: 12/22/31 NT-48008 w/300 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-29655-9532	N16-C-9993			CD	9-13030			
-48008-B10	CAPACITOR, fixed: 12/22/31 NT-48008 w/300 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-29666-2358	N16-C-9993-2			CD	9L-13030			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-4

RESTRICTED

RESTRICTED

SHEET 48 - 5

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48009	CAPACITOR, fixed: 12/22/31 mica; 350 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48009-A10	CAPACITOR, fixed: 12/22/31 NT-48009 w/350 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-29798-1351				CD	9-13035			
-48009-B2	CAPACITOR, fixed: 12/22/31 NT-48009 w/350 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-29787-8396				CD	9-13035			
-48009-B10	CAPACITOR, fixed: 12/22/31 NT-48009 w/350 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-29798-1356	N16-C-10000			CD	9L-13035			
-48010	CAPACITOR, fixed: 12/22/31 mica; 400 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48010-A10	CAPACITOR, fixed: 12/22/31 NT-48010 w/400 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-29929-9351				CD	9-13040			
-48010-B2	CAPACITOR, fixed: 12/22/31 NT-48010 w/400 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-29919-7396				CD	9-13040			
-48010-B10	CAPACITOR, fixed: 12/22/31 NT-48010 w/400 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-29929-9356	N16-C-10008			CD	9L-13040			
-48011	CAPACITOR, fixed: 12/22/31 mica; 500 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48011-A10	CAPACITOR, fixed: 12/22/31 NT-48011 w/500 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-30167-3951	N16-C-10018-3			CD CAW	9-13050 1650	CDE	2374-2	YB-2 (2) YF
-48011-B2	CAPACITOR, fixed: 12/22/31 NT-48011 w/500 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-30157-1996	N16-C-10018-5			CD	9-13050	CG	P-7762664-P28	TCJ TCJ-1
-48011-B10	CAPACITOR, fixed: 12/22/31 NT-48011 w/500 mmf p/m 10%; temp coef ltr B. NOTE: TCM-1 (2); TCM-2; TCN (3); TCN-1 (3); TCU-1; TCU-2.	RE48A112 16C40		16-C-30167-3956	N16-C-10018-3		3D9500-13	CAN CD	A-10 9LS-13050	CG COL CG CG	P-7760498-59 91-4350A W-7350697-205 W-7350699-454 P-7761560-2	CAF TBR TBR(2) TCA TCM (2) SEE NOTE:
-48011-C2	CAPACITOR, fixed: 12/22/31 NT-48011 w/500 mmf p/m 2%; temp coef ltr C. NOTE: TBA-10; TBA-11; TBA-12; TBA-13; TBC-5.	RE48A112 16C40		16-C-30157-2001				CD	9L-13050	CG	P-7762165-1	TBA-6 TBA-8 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-5

RESTRICTED

RESTRICTED

SHEET 48 - 6

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48012	CAPACITOR, fixed: mica; 550 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	12/22/31 RE48A112 16C40										
-48012-A10	CAPACITOR, fixed: NT-48012 w/550 mmf p/m 10%; temp coef ltr A.	12/22/31 RE48A112 16C40		16-C-30272-8551				CD	9-13055			
-48012-B2	CAPACITOR, fixed: NT-48012 w/550 mmf p/m 2%; temp coef ltr B.	12/22/31 RE48A112 16C40		16-C-30262-6596				CD	9-13055			
-48012-B10	CAPACITOR, fixed: NT-48012 w/550 mmf p/m 10%; temp coef ltr B.	12/22/31 RE48A112 16C40		16-C-30272-8556	N16-C-10030			CD	9L-13055			
-48013	CAPACITOR, fixed: mica; 600 mmf; 600 vdcw, 1,000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	12/22/31 RE48A112 16C40										
-48013-A10	CAPACITOR, fixed: NT-48013 w/600 mmf p/m 10%; temp coef ltr A.	12/22/31 RE48A112 16C40		16-C-30325-6351				CD	9-13060			
-48013-B2	CAPACITOR, fixed: NT-48013 w/600 mmf p/m 2%; temp coef ltr B.	12/22/31 RE48A112 16C40		16-C-30315-4396				CD	9-13060			
-48013-B10	CAPACITOR, fixed: NT-48013 w/600 mmf p/m 10%; temp coef ltr B.	12/22/31 RE48A112 16C40		16-C-30325-6356	N16-C-10040			CD	9L-13060			
-48014	CAPACITOR, fixed: mica; 650 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 11/32" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	12/22/31 RE48A112 16C40										
-48014-A10	CAPACITOR, fixed: NT-48014 w/650 mmf p/m 10%; temp coef ltr A.	12/22/31 RE48A112 16C40		16-C-30483-8751				CD	9-13065			
-48014-B2	CAPACITOR, fixed: NT-48014 w/ 650 mmf p/m 2%; temp coef ltr B.	12/22/31 RE48A112 16C40		16-C-30473-6796				CD	9-13065			
-48014-B10	CAPACITOR, fixed: NT-48014 w/ 650 mmf p/m 10%; temp coef ltr B.	12/22/31 RE48A112 16C40		16-C-30483-8756	N16-C-10060			CD	9L-13065			
-48015	CAPACITOR, fixed: mica; 700 mmf; 600 vdcw, 1,000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	12/22/31 RE48A112 16C40										
-48015-A10	CAPACITOR, fixed: NT-48015 w/700 mmf p/m 10%; temp coef ltr A.	12/22/31 RE48A112 16C40		16-C-30589-4351				CD	9-13070			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-6

RESTRICTED

Con't

RESTRICTED

SHEET 48 - 7

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48015-B2	CAPACITOR, fixed: 12/22/31 NT-48015 w/700 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-30579-2396				CD	9-13070			
-48015-B10	CAPACITOR, fixed: 12/22/31 NT-48015 w/700 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-30589-4356	N16-C-10068			CD	9L-13070			
-48016	CAPACITOR, fixed: 12/22/31 mica; 850 mmf; 600 vdcw, 1000v DC rest; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48016-A10	CAPACITOR, fixed: 12/22/31 NT-48016 w/850 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-30826-7951				CD	9-13085			
-48016-B2	CAPACITOR, fixed: 12/22/31 NT-48016 w/850 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-30816-5996	N16-C-10076			CD	9-13085			
-48016-B10	CAPACITOR, fixed: 12/22/31 NT-48016 w/ 850 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-30826-7956	N16-C-10076-80			CD	9L-13085			
-48017	CAPACITOR, fixed: 12/22/31 mica; 900 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48017-A10	CAPACITOR, fixed: 12/22/31 NT-48017 w/900 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-30905-9151				CD	9-13090			
-48017-B2	CAPACITOR, fixed: 12/22/31 NT-48017 w/900 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-30895-7196	N16-C-10080-1			CD	9-13090			
-48017-B10	CAPACITOR, fixed: 12/22/31 NT-48017 w/900 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-30905-9156	N16-C-10080			CD	9L-13090			
-48018	CAPACITOR, FIXED: 12/22/31 mica dielectric; 1000 mmf; 600 vdcw; 1 3/4" lg x 1 5/16" wd x 7/16" h case; molded phenolic case; low loss; one #6-32 NC tapped hole on end, 1 1/4" c to c; term mtg; add suffix indicating capacity tolerance in per cent.	RE48A112 16C40										
-48018-A10	CAPACITOR, fixed: 12/22/31 NT-48018 w/1000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-31090-5951				CD	9-12010			
-48018-B2	CAPACITOR, fixed: 12/22/31 NT-48018 w/1000 mmf p/m 2%; temp coef ltr B. NOTE: SC-4 (4); SK-2 (4); SK-3 (4); TBC-5.	RE48A112 16C40		16-C-31080-3996	N16-C-10085	R16-C-10085		CD	9-12010	CG	7762664-34	SC-2 (4) SC-3 (4) SEE NOTE:
-48018-B5	CAPACITOR, fixed: 12/22/31 NT-48018 w/1000 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40		16-C-31085-5478				CAN	AZLS-1210	CFT		YA-1 YA-2
-48018-B10	CAPACITOR, fixed: 12/22/31 NT-48018 w/1000 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-31090-5956				CD	9L-12010			
-48018-B20	CAPACITOR, FIXED: 7/5/48 Navy Type 48018 w/1000 mmf p/m 20%; temp coef ltr B.	RE48A112 16C40		16-C-31095-8439				CD	9-12010			

SHEET 48.7

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 8

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48019	CAPACITOR, fixed: 12/22/31 mica; 1200 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48019-A10	CAPACITOR, fixed: 12/22/31 NT-48019 w/1200 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-31275-2751						CD	9-12012	
-48019-B2	CAPACITOR, fixed: 12/22/31 NT-48019 w/ 1,200 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-31264-9796						CD	9-12012	
-48019-B10	CAPACITOR, fixed: 12/22/31 NT-48019 w/ 1,200 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-31275-2756	N16-C-10163-11					CD	9L-12012	
-48020	CAPACITOR, fixed: 12/22/31 mica; 1500 mmf, 1000v DC test; 600 vdcw; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48020-A10	CAPACITOR, fixed: 12/22/31 NT-48020 w/1,000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-31512-6351						CD	9-12015	
-48020-B2	CAPACITOR, fixed: 12/22/31 NT-48020 w/1,500 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-31502-4396						CD	9-12015	
-48020-B10	CAPACITOR, fixed: 12/22/31 NT-48020 w/1,500 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-31512-6356	N16-C-10180					CD	9L-12015	
-48021	CAPACITOR, fixed: 12/22/31 mica; 2000 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48021-A10	CAPACITOR, fixed: 12/22/31 NT-48021 w/2,000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-31802-7751						CD	9-12020	
-48021-B2	CAPACITOR, fixed: 12/22/31 NT-48021 w/2,000 mmf p/m 2%; temp coef ltr B. NOT : TBA-10(23); TBA-8; BA-11; TBA-6(22); TBC-5(22).	RE48A112 16C40		16-C-31792-5796	N16-C-10241-5	R16-C-10241-5				CD CNA	9LS-12020	CG P-7762664-37 TAJ-13 TAQ-10 SEE NO E
-48021-B10	CAPACITOR, fixed: 12/22/31 NT-48021 w/2,000 mmf p/m 10%; temp coef ltr B. NOTE:TBA-12 (24); TBA-13 (24); TCB-1; TCB-2; TCC (2); TDE; TDE-1 ; TDE-2; TDE-3.	RE48A112 16C40		16-C-31802-7756	N16-C-10241-15	R16-C-10241-8	3DA2-89			CD C N	9LS-12020 A-10	COL 910 2201 20 rev0 COL 910 2208 20 rev0 CG 7764888-37 CG 7761560-19 CAT 7608226-67 TAQ-6 (12) TAQ-5 (12) TAQ-10(13) TBA-8 (23) TBA-11(23) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-8

RESTRICTED

RESTRICTED

SHEET 48 - 9

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48022	CAPACITOR, fixed: 12/22/31 mica; 2,500 mmf; 600 vdcw, 1000V DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bake- lite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48022-A10	CAPACITOR, fixed: 12/22/31 NT-48022 w/2,500 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-32013-7951				CD CAW	9-12025 1650	CDE		YF
-48022-B9	CAPACITOR, fixed: 12/22/31 NT-48022 w/2,500 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40		16-C-32008-7476	N16-C-10314			CD	9-12025			
-48022-B10	CAPACITOR, fixed: 12/22/31 NT-48022 w/2,500 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-32013-7956	N16-C-10315	R16-C-10314		CD	9L-12025			
-48023	CAPACITOR, fixed: 12/22/31 mica; 5,000 mmf; 600 vdcw, 1000V DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bake- lite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48023-A10	CAPACITOR, fixed: 12/22/31 NT-48023 w/5,000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-32699-6351				CD CAW	9-12050 1650	CDE	2374-4	YB-2 (10) YF (6)
-48023-B5	CAPACITOR, fixed: 7/9/48 Navy Type 48023 w/5000 mmf p/m 5%; temp coef letter B.			16-C-32694-5879				CD CAW	9LS-12050 1650-LS	CFW CFW	208110 100152	TZU
-48023-B10	CAPACITOR, fixed: 12/22/31 NT-48023 w/5,000 mmf p/m 10%; temp coef ltr B. NOTE: TCK-2 (10); TCK-3 (10); TCK-4 (10); TCK-5 (10); TCK-6 (10); TCK-7 (10); TCK (10); TCK-1 (10); YR (2).	RE48A112 16C40		16-C-32699-6356	N16-C-10405	R16-C-10405		CD CAW	9L-12050 1650	CG CDE	P-7764888-46 S-2369-8	TC(2) TC-1(2) SEE NOTE:
-48023-B20	CAPACITOR, fixed: 12/22/31 NT-48023 w/5,000 mmf p/m 20%; temp coef ltr B.	RE48A112 16C40		16-C-32704-8836	N16-C-10405-21			CD	9L-12050			
-48024	CAPACITOR, fixed: 12/22/31 mica; 4000 mmf; 600 vdcw, 1000V DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48024-A10	CAPACITOR, fixed: 12/22/31 NT-48024 w/4000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-32462-2751				CD	9-12040			
-48024-B10	CAPACITOR, fixed: 12/22/31 NT-48024 w/4000 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-32462-2756	N16-C-10373			CD	9L-12040			
-48024-B20	CAPACITOR, fixed: 12/22/31 NT-48024 w/4000 mmf p/m 20%; temp coef ltr B.	RE48A112 16C40		16-C-32467-5236	N16-C-10373-4			CD	9L-12040			

SHEET 48-9

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48-10

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CON. FACTOR	CONTRACTOR'S CWG OR PART NO	EQUIPMENT USED IN
-48025	CAPACITOR, fixed: 12/22/31 mica; 6000 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded mica case; two #6-32 tapped holes 1/4" c to c for term and mtg.	RE48A112 16C40										
-48025-A10	CAPACITOR, fixed: 12/22/31 NI-48025 w/6000 mmf p/m 10%; temp coef ltr A. NOTE: NM-12; NMA; NMB-2; NMC-1; MN-13; MN-13A; WCA; W CA-1; WCA-3.	RE48A112 16C40		16-C-32857-8751				CD CSL	9-12060 XMW.6-26-10	CBM	744-92	NM-9 NM-9a SEE NOTE
-48025-B2	CAPACITOR, fixed: 12/22/31 NI-48025 w/6,000 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-32847-6796	N16-C-10447			CD	9-12060			
-48025-B5	CAPACITOR, fixed: 12/22/31 NI-48025 w/6000 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40						CD	918-12060	COL	910N260H	TCA-1
-48025-B10	CAPACITOR, fixed: 12/22/31 NI-48025 w/6000 mmf p/m 10%; temp coef ltr B. NOTE: TCC (5); TCC-2 (5); WDA; WDA-1.	RE48A112 16C40		16-C-32857-8756	N16-C-10447-4			CD CAN	9L-12060 A-10	COL CBM	910 2601 10 744-92	TCA TCA-1 (5) SEE NOTE
-48025-B20	CAPACITOR, fixed: 12/22/31 NI-48025 w/6000 mmf p/m 20%; temp coef ltr B.	RE48A112 16C40		16-C-32863-2236				CD CSL CAN CAN CAW	9L-12060 XMB-6-26 A2-1260 A2-10	COL	910 2601 40rev1	TDB TDB-3
-48025-C10	CAPACITOR, fixed: 12/22/31 NI-48025 w/6000 mmf p/m 10%; temp coef ltr C. NOTE: NM-14b; NM-14c.	RE48A112 16C40		16-C-32857-8761				CAN	A-10	CBM	744-184	NM-14 NM-14a SEE NOTE
-48026	CAPACITOR, fixed: 12/22/31 mica; 8000 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1/4" c to c for term and mtg.	RE48A112 16C40										
-48026-A10	CAPACITOR, fixed: 12/22/31 NI-48026 w/8000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-33227-2351				CD	9-12060			
-48027	CAPACITOR, fixed: 12/22/31 mica; 10000 mmf; 600 vdcw, 1000v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1/4" c to c for term and mtg.	RE48A112 16C40										
-48027-A10	CAPACITOR, fixed: 12/22/31 NI-48027 w/10000 mmf p/m 10%; temp coef ltr A. NOTE: TBK-9(11); TBK-11(10); TBK-13(11); YB-2(2).	RE48A112 16C40		16-C-33622-8351			3DA10-247 3D306	CD CAN CAW	9-11010 A-10 1650	CAY CAY CAY CAY CAY CDE	M-7406194-8 M-7406181-3 7406181-5 T-7607280-18 T-7607093-18 T-7609847-24 2374-10	TBM-4 (11) TBM-5 (10) thru TBM-8 (10) TBK-5 (11) TBK-6 (11) TBK-7 (11) SEE NOTE Con't

SHEET 48-10

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 11

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48027-B2	CAPACITOR, fixed: 12/22/31 NT-48027 w/10,000 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-33612-6396			3DA10-63.2	CD CSL	9LS-11010 4LSE	COL	910N110Hrev0	TCC-1(2)
-48027-B10	CAPACITOR, fixed: 12/22/31 NT-48027 w/10,000 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-33622-8356	N16-C-10496	R16-C-10496-20	3DA10-12	CAN CD CRV	A-10 9LS-11010 Model F	COL CG CBM CRV CC CC	910N110Arev0 P-7761560-13 rev17 744-79 K-35482-54 P-7762664-52 P-7764888-52	QCA (2) QCB (2) QCE (2) QCF (2) QCK (2) QCL (2) QCN (3)
	NOTE: TAJ-6 (2); TAQ-5 (8); TBA-10; TBL-2 (8); TCB-2 (8); WCA-3; WEB (2).											SEE NOTE
-48027-B20	CAPACITOR, fixed: 12/22/31 NT-48027 w/10,000 mmf p/m 20%; temp coef ltr B.	RE48A112 16C40		16-C-33628-1836	N16-C-10496-1			CD CAN CRV	9L-11010 A-10 BF	COL CRV	910 1101 40rev0 K-361720504rev5	TDH-4 (3) TDO (3)
-48028	CAPACITOR, fixed: 12/22/31 mica: 15,000 mmf; 600 vdcw, 1000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48028-A10	CAPACITOR, fixed: 12/22/31 NT-48028 w/15,000 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A153K	16-C-34044-8751		R16-C-10529-16		CD	9-11015			
-48028-A20	CAPACITOR, fixed: 12/22/31 NT-48028 w/15,000 mmf p/m 20%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A153M	16-C-34050-2231		R16-C-10529-28		CD	9-11015			
-48028-B2	CAPACITOR, fixed: 12/22/31 NT-48028 w/15,000 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B153G	16-C-34034-6796		R16-C-10529-2-200		CD	9-11015			
-48028-B10	CAPACITOR, fixed: 12/22/31 NT-48028 w/15,000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B153K	16-C-34044-8756	N16-C-10529	R16-C-10529-18	3K5515321	CD	9L-11015			
-48028-B20	CAPACITOR, fixed: 12/22/31 NT-48028 w/15,000 mmf p/m 20%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B153M	16-C-34050-2236		R16-C-10529-30		CD	96-11015			
-48028-C2	CAPACITOR, fixed: 12/22/31 NT-48028 w/15,000 mmf p/m 2%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C153G	16-C-34034-6801		R16-C-10529-3		CD	9L-11015			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVYSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-11

RESTRICTED

RESTRICTED

SHEET 48 - 12

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48028-C10	CAPACITOR, fixed: NT-48028 w/15,000 mmf p/m 10%; temp coef ltr C.	12/22/31 REF48A112 JAN-C-5	CM55C153K	16-C-34044-8761		R16-C-10529-20		CD	9L-11015			
-48028-C20	CAPACITOR, fixed: NT-48028 w/15,000 mmf p/m 20%; temp coef ltr C.	12/22/31 REF48A112 JAN-C-5	CM55C153M	16-C-34050-2241		R16-C-10529-32		CD	9L-11015			
-48028-D2	CAPACITOR, fixed: NT-48028 w/15,000 mmf p/m 2%; temp coef ltr D.	12/22/31 REF48A112 JAN-C-5	CM55D153C	16-C-34034-6906		R16-C-10529-3-800		CD	9H-11015			
-48028-D10	CAPACITOR, fixed: NT-48028 w/15,000 mmf p/m 10%; temp coef ltr D.	12/22/31 REF48A112 JAN-C-5	CM55D153K	16-C-34044-8766		R16-C-10529-22		CD	9H-11015			
-48028-D20	CAPACITOR, fixed: NT-48028 w/15,000 mmf p/m 20%; temp coef ltr D.	12/22/31 REF48A112 JAN-C-5	CM55D153M	16-C-34050-2246		R16-C-10529-34	3K5515324					
-48028-E2	CAPACITOR, fixed: NT-48028 w/15,000 mmf p/m 2%; temp coef ltr E.	12/31/31 REF48A112 JAN-C-5	CM55E153G	16-C-34034-6811		R16-C-10529-4-600						
-48028-E10	CAPACITOR, fixed: NT-48028 w/15,000 mmf p/m 10%; temp coef ltr E.	12/22/31 REF48A112 JAN-C-5	CM55E153K	16-C-34044-8771		R16-C-10529-24						
-48028-E20	CAPACITOR, fixed: NT-48028 w/15,000 mmf p/m 20%; temp coef ltr E.	12/22/31 REF48A112 JAN-C-5	CM55E153M	16-C-34050-2251		R16-C-10529-36						
-48029	CAPACITOR, fixed: mica; 20,000 mmf; 600 vdcv, 1000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and atg.	12/22/31 REF48A112 JAN-C-5										
-48029-A5	CAPACITOR, fixed: NT-48029 w/20,000 mmf p/m 5%; temp coef ltr A.	12/22/31 REF48A112 JAN-C-5	CM55A203J	16-C-34329-9671	N16-C-10552-3	R16-C-10532-110		CD CRV	9-11020	CRV	DW-300213-168	TAF-4 (4)
-48029-A10	CAPACITOR, fixed: NT-48029 w/20000 mmf p/m 10%; temp coef ltr A.	12/22/31 REF48A112 JAN-C-5	CM55A203K	16-C-34335-1151			3DA20-37	CAW	1650	CDE	4151-14	YB-2 (2)
-48029-A20	CAPACITOR, fixed: NT-48029 w/20000 mmf p/m 20%; temp coef ltr A.	12/22/31 REF48A112 JAN-C-5	CM55A203M	16-C-34340-3631				CD	9-11020	CRV	K-35478-52rev9	QC-3 (12)
-48029-B5	CAPACITOR, fixed: NT-48029 w/20000 mmf p/m 5%; temp coef ltr B.	12/22/31 REF48A112 JAN-C-5	CM55B203J	16-C-34329-9676	N16-C-10552	R16-C-10532-290		CD CAN	9-11020 21S-1120	CFT		YA-1 (7) YA-2 (7)
-48029-B10	CAPACITOR, fixed: NT-48029 w/20000 mmf p/m 10%; temp coef ltr B.	12/22/31 REF48A112 JAN-C-5	CM55B203K	16-C-34335-1156	N16-C-10552-3	R16-C-10533-10		CD CRV	9L-11020 HF	CRV	W-303083-155 K-30172-505 K-35482-52rev6 K-36172-505 W-303086-214	NB-3 (12) NMB-1 (5) QBH (3) QCJ-8 (12) QJW (3) SEE NOTE
-48029-B20	CAPACITOR, fixed: NT-48029 w/20,000 mmf p/m 20%; temp coef ltr B.	12/22/31 REF48A112 JAN-C-5	CM55B203M	16-C-34340-3636	R16-C-10552-2			CD	9L-11020			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-12

RESTRICTED

RESTRICTED

SHEET 48 - 13

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48029-C2	CAPACITOR, fixed: 12/22/31 NT-48029 w/20,000 mmf p/m 2%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C203G	16-C-34324-8201		R16-C-10532-4		CD	9L-11020			
-48029-C5	CAPACITOR, fixed: 12/22/31 NT-48029 w/20,000 mmf p/m 5%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C203J	16-C-34329-9681		R16-C-10532-470		CD	9L-11020			
-48029-D2	CAPACITOR, fixed: 12/22/31 NT-48029 w/20,000 mmf p/m 2%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D203G	16-C-34324-8206		R16-C-10532-6		CD	9H-11020			
-48029-D5	CAPACITOR, fixed: 12/22/31 NT-48029 w/20,000 mmf p/m 5%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D203J	16-C-34329-9686		R16-C-10532-650		CD	9H-11020			
-48029-E2	CAPACITOR, fixed: 12/22/31 NT-48029 w/20,000 mmf p/m 2%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E203G	16-C-34324-8211		R16-C-10532-8						
-48029-E5	CAPACITOR, fixed: 12/22/31 NT-48029 w/20,000 mmf p/m 5%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E203J	16-C-34329-9691		R16-C-10532-830						
-48030	CAPACITOR, fixed: 12/22/31 mica; 30,000 mmf; 600 vdcv, 1000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48030-A5	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 5%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A303J	16-C-34725-6671		R16-C-10549-700		CD	9-11030			
-48030-A10	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A303K	16-C-34730-7151	N16-C-10575-1			CD CAW	9-11030 1650	CDE	2374-3	YB-2 (3) YF
-48030-B2	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B303G	16-C-34720-5196		R16-C-10548-900		CD	9-11030			
-48030-B5	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B303J	16-C-34725-6676		R16-C-10549-900		CD	9-11030			
-48030-B10	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B303K	16-C-34730-7156	N16-C-10575-1	R16-C-10551		CD	9L-11030	CRR CAY CAY	QB15275-18-F alt 0 T-7607321-8 T-7609144-8	TBU thru TBU-4
-48030-C2	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 2%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C303G	16-C-34720-5201		R16-C-10549-100		CD	9L-11030			
-48030-C5	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 5%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C303J	16-C-34725-6681				CD	9L-11030			
-48030-D2	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 2%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D303G	16-C-34720-5206		R16-C-10549-300		CD	9H-11030			
												Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-13

RESTRICTED

RESTRICTED

SHEET 48 - 14

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USE IN
-48030-B5	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55D303J	16-C-34725-6686		R16-C-10550-300		CD	9E-11030			
-48030-B2	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 2%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E303G	16-C-34720-5211		R16-C-10549-500						
-48030-B5	CAPACITOR, fixed: 12/22/31 NT-48030 w/30,000 mmf p/m 5%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E303G	16-C-34725-6691								
-48031	CAPACITOR, fixed: 12/22/31 mica; 4.0 mmf; 600 vdcv, 1,000v DC test; case 1 13/16" lg x 1 11/32" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48031-A10	CAPACITOR, fixed: 12/22/31 NT-48031 w/40 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-27397-6951				CD	9-14040			
-48031-B2	CAPACITOR, fixed: 12/22/31 NT-48031 w/40 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-27387-4991				CD	9-14040			
-48031-B5	CAPACITOR, fixed: 12/22/31 NT-48031 w/40 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40		16-C-27392-6471	N16-C-9843-53			CD	9L-14040			
-48031-B10	CAPACITOR, fixed: 12/22/31 NT-48031 w/40 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-27397-6956	N16-C-9843-55			CD	9L-14040			
-48032	CAPACITOR, fixed: 12/22/31 mica; 1000 mmf; 1200 vdcv, 2500v DC test; case 1 13/16" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48032-A10	CAPACITOR, fixed: 12/22/31 NT-48032 w/1,000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-31091-1237				CD CAW CAN	9AL-22010 1651 AL2210	CRV CDB	L61014-13 rev 1 2374-7	YB-2(15)
-48032-B2	CAPACITOR, fixed: 12/22/31 NT-48032 w/1,000 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-31080-8282	N16-C-10092	R16-C-10092		CRV	Model F	CRV	K-35484-54 rev9	
-48032-B10	CAPACITOR, fixed: 12/22/31 NT-48032 w/1,000 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-31091-1242	N16-C-10092-7	R16-C-10092-10		CD CAW CAN	9AL-22010 1651L A2L2210	CRV	L61014-13 rev 1	TET (8)
-48033	CAPACITOR, fixed: 12/22/31 mica; 4,000 mmf; 1200 vdcv, 2500v DC test; case 1 25/32" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										Cont

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-14

RESTRICTED

RESTRICTED

SHEET 48 - 15

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48033-A10	CAPACITOR, fixed: 12/22/31 NT-48033 w/4,000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-32462-7037	N16-C-10376-1			CD	9-22040			
-48033-B5	CAPACITOR, fixed: 12/22/31 NT-48033 w/4,000 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40		16-C-32457-6562	N16-C-10376			CD CAW	9-22040 1651-L	CRR	A26201-2	TAJ-8 (2)
-48033-B10	CAPACITOR, fixed: 12/22/31 NT-48033 w/4,000 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-32462-7042	N16-C-10376-1			CD CRV	9L-22040 F	CRV	K-35482-45	BL-4 TBL-8 TBL-9
-48034	CAPACITOR, fixed: 12/22/31 mica; 8000 mmf; 1200 vdcw, 2500v DC test; case 1 25/32" lg max x 1 11/32" wd max x 1 5/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48034-A10	CAPACITOR, fixed: 12/22/31 NT-48034 w/8000 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A802K	16-C-33227-6639				CD	9-22080			
-48034-B10	CAPACITOR, fixed: 12/22/31 NT-48034 w/8000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B802K	16-C-33227-6642	N16-C-10475	R16-C-10475		CD CRV	9L-22080 F	CRV	K-35482-48	TBL-4 TBL-8 TBL-9
-48034-B20	CAPACITOR, fixed: 12/22/31 NT-48034 w/3000 mmf p/m 20%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B802M	16-C-33232-9122	N16-10475-1			CD	9L-22080			
-48035	CAPACITOR, fixed: 12/22/31 mica; 10,000 mmf; 1200 vdcw, 2500v DC test; 1 25/32" lg max x 1 11/32" wd max x 1 5/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48035-A5	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 5%; temp coef ltr A.	RE48A112 JA -C-5	CM55A103J	16-C-33618-3157		R16-C-10503-3-181		CD	9-21010			
-48035-A10	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 10%; temp coef ltr A. NOTE: TBK-7 (3); TBK-9 (2); TBM-4 (2).	RE48A112 JAN-C-5	CM55A103K	16-C-33623-3637			3E5510311	CD	9-21010	CAY CAY	M-7406194-7 M-7406194-1	TRK-5 (3) TRK-6 (3) SEE NO E.
-48035-A20	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 20%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A103M	16-C-33628-6117		R16-C-10504-21		CD	9-21010			
-48035-B2	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B103G	16-C-33613-1682		R16-C-10503-1-198	3E5510323	CD	9-21010			
-48035-B5	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B103J	16-C-33618-3142	N16-C-10503-57	R16-C-10504-19	3E5510322	CD	9-21010			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-15

RESTRICTED

RESTRICTED

SHEET 48 - 16

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-48035-B10	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B103K	16-C-33623-3642	R16-C-10504-2	R16-C-10504	3K5510321	CD CRV CD	9L-21010 F 9L	CG CRV CAY CG CG CG CRV CAY CAY CAY CAY CRV CRV	P-7761560-15 rev17 W-303033-154 T-7606683-6 7761891-C105 P-7762664-53 P-7764888-53 K-35482-49 7607280-33 7607470-30 M-7406194-7 7607093-33 P-7761560-3 T-7605847-26 W-7350697-208 W-7350699-457	NMB-1 (5) QCL-8 (5) QCL (5) QCL-7 (5) TAB-5 (2) TAB-6 (2) TAB-7 (2) TAJ-7 (18) TAJ-9 (16) TAQ-5 (10) TAQ-6 (10) TBL (17) TBL-1 TBL-1 TBM (11) TBM (12) TCJ (3) SEE NOTE:
-48035-a20	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 20%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B103M	16-C-33628-6122	R16-C-10504-3	R16-C-10504-22	3K5510324	CD CRV CSF	9L-21010 F S-6742	CRV CRV CRV	K-35478-19rev9 00-767	TAJ-4 (8) TCS-6
-48035-C2	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 2%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C103G	16-C-33613-1687		R16-C-10503-1-396		CD	9L-21010			
-48035-C5	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 5%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C103J	16-C-33618-3167		R16-C-10503-3-724		CD	9L-21010			
-48035-C10	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 10%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C103K	16-C-33623-3647		R16-C-10504-2		CD	9L-21010			
-48035-C20	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 20%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C103M	16-C-33628-6127		R16-C-10504-23		CD	9L-21010			
-48035-D2	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 2%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D103G	16-C-33613-1692		R16-C-10503-1-544		CD	9E-21010			
-48035-D5	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 5%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D103J	16-C-33618-3172		R16-C-10503-4-86	3K5510342	CD	9E-21010			
-48035-D10	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 10%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D103K	16-C-33623-3652		R16-C-10504-4		CD	9E-21010			
-48035-D20	CAPACITOR, fixed: 12/22/31 NT-48035 w/10,000 mmf p/m 20%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D10 M	16-C-33628-6132				CD	9E-21010			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-16

RESTRICTED

RESTRICTED

SHEET 48 - 17

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-48035-E5	CAPACITOR, fixed: NT-48035 w/10,000 mmf p/m 5%; temp coef ltr E.	12/22/31 RE48A112 JAN-C-5	CM55E103J	16-C-33618-3177		R16-C-10503-4-44							
-48035-E10	CAPACITOR, fixed: NT-48035 w/10,000 mmf p/m 10%; temp coef ltr E.	12/22/31 RE48A112 J N-C-5	CM55E103K	16-C-33623-3657		R16-C-10504-6							
-48035-F20	CAPACITOR, fixed: NT-48035 w/10,000 mmf p/m 20%; temp coef ltr E.	12/22/31 RE48A112 J N-C-5	CM55E103M	16-C-33628-6137		R16-C-10504-25-500							
-48036	CAPACITOR, fixed: mica; 1000 mmf; 2500 vacw, 5000v DC test; case l 25/32" lg max x l 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes l 1/4" c to c for term and mtg.	12/22/31 RE48A112 JAN-C-5											
-48036-A5	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 5%; temp coef ltr A.	12/22/31 RE48 112 JAN-C-5	CM55A102J	16-C-31086-6182		R16-C-10095-180		CD			9-52010		
-48036-A10	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 10%; temp coef ltr A.	12/22/31 RE48A112 JAN-C-5	CM55A102K	16-C-31091-6660		R16-C-10096-140		CD CAW		9-52010 1652	CBS CDE	2374-8 TAZ-1 (6) YB-2	
-48036-A20	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 20%; temp coef ltr A.	12/22/31 RE48A112 JAN-C-5	CM55A102M	16-C-31096-9142	N16-C-10094-4	R16-C-10097-120		CD			9-52010		
-48036-B2	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 2%; temp coef ltr B. NOTE: TBL-4 (2); TBL-8 (2); TBL-9 (2); YE (4); YE-1 (4); YE-2 (4).	12/22/31 RE48A112 JAN-C-5	CM55B102G	16-C-31081-4707	N16-C-10094	R16-C-10094-300		CD CRV		9L-52010 Model F	CG CRV	P-7761560-22 rev17 E-35484-40rev9 TAQ-5 TAQ-6 TAQ-10 SEE NOTE	
-48036-B5	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 5%; temp coef ltr B.	12/22/31 RE48A112 JAN-C-5	CM55B102J	16-C-31086-6187	N16-C-10092-20	R16-C-10095-300	3E5510222	CD			9L-52010		
-48036-B10	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 10%; temp coef ltr B.	12/22/31 RE48A112 JAN-C-5	CM55B102K	16-C-31091-6667	N16-C-10094-3	R16-C-10096-150	3E5510221	CD			9L-52010	CRR	QB15273-6-Faito
-48036-C2	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 2%; temp coef ltr C.	12/22/31 RE48A112 JAN-C-5	CM55C102G	16-C-31081-4712		R16-C-10094-500		CD			9L-52010		
-48036-C5	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 5%; temp coef ltr C.	12/22/31 RE48A112 JAN-C-5	CM55C102J	16-C-31086-6192		R16-C-10095-420	3E5510232	CD			9L-52010		
-48036-C10	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 10%; temp coef ltr C.	12/22/31 RE48A112 JAN-C-5	CM55C102K	16-C-31091-6672		R16-C-10096-420	3E5510231	CD			9L-52010		
-48036-C20	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 20%; temp coef ltr C.	12/22/31 RE48A112 JAN-C-5	CM55C102M	16-C-31096-9152		R16-C-10097-400	3E5510234						
-48036-D2	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 2%; temp coef ltr D.	12/22/31 RE48A112 JAN-C-5	CM55D102G	16-C-31081-4717		R16-C-10094-600	3E5510243	CD			9H-52010		
-48036-D5	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 5%; temp coef ltr D.	12/22/31 RE48 112 JAN-C-5	CM55D102J	16-C-31086-6197		R16-C-10095-540	3E5510242	CD			9H-52010		
-48036-D10	CAPACITOR, fixed: NT-48036 w/1,000 mmf p/m 10%; temp coef ltr D.	12/22/31 RE48A112 JAN-C-5	CM55D102K	16-C-31091-6877		R16-C-10096-560		CD			9H-52010		

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-17

RESTRICTED

Con't

RESTRICTED

SHEET 48 - 18

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48036-D20	CAPACITOR, fixed: 12/31/48 Navy Type 48036 w/1,000 mmf p/m 20%; temp coef letter D.	JAN-C-5	CM55D102M	16-C-31096-9159								TS-89/AP
-48036-E2	CAPACITOR, fixed: 12/22/31 NT-48036 w/1,000 mmf p/m 2%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E102G	16-C-31081-4722		R16-C-10094-800						
-48036-E5	CAPACITOR, fixed: 12/22/31 NT-48036 w/1,000 mmf p/m 5%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E102J	16-C-31086-6202		R16-C-10095-660						
-48036-E10	CAPACITOR, fixed: 12/22/31 NT-48036 w/1,000 mmf p/m 10%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E102K	16-C-31091-6682		R16-C-10096-700						
-48036-E20	CAPACITOR, fixed: 12/22/31 NT-48036 w/1,000 mmf p/m 20%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E102M	16-C-31096-9162		R16-C-10097-680						
-48037	CAPACITOR, fixed: 12/22/31 mica; 2000 mmf; 2500 vdcw, 5000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48037-A5	CAPACITOR, fixed: 12/22/31 NT-48037 w/2000 mmf p/m 5%; temp coef ltr A	RE48A112 JAN-C-5	CM55A202J	16-C-31798-7982		R16-C-10247-90		CD	9-52020			
-48037-A10	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 10%; temp coef ltr A. NOTE: TBK-7(5); TBK-9(6); TEM-4(6).	RE48A112 JAN-C-5	CM55A202K	16-C-31803-8462				CD	9-52020	CHS CAY	M-7406194-9 M-7406181-3	TAZ-1(6) TBK-5(5) TBK-6(5) SEE NOTE
-48037-B2	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 2%; temp coef ltr B. NOTE: TBA-10(2); TBL-3(3); TBL-1(3); TBL-2(5); TBL-3(5); TBL-4(5); TBL-5(5); TBL-6(5); TBL-7(5); TBL-8(5); TBL-9(5); TBL-10(5); TBL-11(5); TBL-12(5); TBL-13(5).	RE48A112 JAN-C-5	CM55B202G	16-C-31793-6507	N16-C-10242	R16-C-10242		CRV CD	Model "F" 9LS-52020	CRV CAY	K-35484-43rev9 P-7762664-39 7607470-29	GP (6) GP-2(6) TBA-6(2) SEE NOTE
-48037-B5	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B202J	16-C-31798-7987	N16-C-10241-80	R16-C-10247-100	3K5520222	CD	9-52020			
-48037-B10	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B202K	16-C-31803-8467	N16-C-10241-70	R16-C-10247-110		CD CAW CAN	9L-52020 1652LS A-50	CRV CG CAY CAY CAY COL	K-866919-1rev1 P-7764888-39 7607280-26 M-7406194-9 T-7607093-26 T-7609847-25 950N220A	SD SD-a SD-1 SD-2 SD-3 SD-4 TBA-8(2)
-48037-B20	CAPACITOR, fixed: 3/24/49 Navy Type 48037 w/2000 mmf p/m 20%; temp coef letter B. NOTE: TBA-11(2); TBA-12(2); TBA-13(2); TBK-11(6); TBK-13(5); TBK-15(6); TBK-16(6); TEM-5(5); TEM-6(6); TEM-7(5); TEM-8(6); TEM-12(6); TCA-(2).			16-C-31809-1950				CAN	A	CYV	12-45	TBA SEE NOTE Con't

SHEET 48-18

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 19

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48037-C2	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 2%; temp coef ltr C.	RE48A112 JAN-C-5	CM59C202G	16-C-31793-6512		R16-C-10247-45		CD	9L-52020			
-48037-C5	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 5%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C202J	16-C-31798-7992		R16-C-10247-105-888	3K5520232	CD	9L-52020			
-48037-D2	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 2%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D202G	16-C-31793-6517		R16-C-10247-55	3DA2-62	CD	9E-52020			
-48037-D5	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 5%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D202J	16-C-31798-7997		R16-C-10247-106-776	3K5520242	CD	9E-52020			
-48037-E2	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 2%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E202G	16-C-31793-6522		R16-C-10247-65						
-48037-E5	CAPACITOR, fixed: 12/22/31 NT-48037 w/2,000 mmf p/m 5%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E202J	16-C-31798-8002		R16-C-10247-107-664						
-48038	CAPACITOR, fixed: 12/22/31 mica; 50 mmf; 2500 vacv, 5000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; moulded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48038-A10	CAPACITOR, fixed: 12/22/31 NT-48038 w/50 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A500K	16-C-27636-2262				CD	9-54050			
-48038-B2	CAPACITOR, fixed: 12/22/31 NT-48038 w/ 50 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B500G	16-C-27625-9307	N16-C-9843-128	R16-C-9844		CRV	Model "F"	CRV	K-35484-33 rev 3	TBR (2)
								CD	9LS-54050	CG	W-7350697-207	TBP-1 (2)
-48038-B5	CAPACITOR, fixed: 12/22/31 NT-48038 w/50 mmf p/m 5%; temp coef ltr B. NOTE: TCM-2(2); TCN (2); TCN-1(2); TCV-2(2).	RE48A112 JAN-O-5	CM55B500J	16-C-27631-1787	N16-C-9844-1			CD	9LS-54050	CG	P7761560-10rev9	TCM(2) TCN-1(2) SEE NOTE
-48038-B10	CAPACITOR, fixed: 12/22/31 NT-48038 w/50 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B500K	16-C-27636-2267	N16-C-9844-3			CD	9L-54050			
-48038-B20	CAPACITOR, fixed: 12/22/31 NT-48038 w/ 50 mmf p/m 20%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B500M	16-C-27641-4747	N16-C-9844-4 N16-C-9844-7			CD CAN CRV	9L-54050 A-50 AF, FARADON	CRZ CRV COL	00-766-A rev A2 K-35485-3 990 4501 40	TBS thru TBS-8 TCS-6 thru TCS-12
-48039	CAPACITOR, fixed: 12/22/31 mica; 70 mmf; 2500 vacv, 5000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; moulded phenolic case; one #6-32 tapped holes 1 1/4" c to c; add suffix indicating capacity tolerance in per cent.	RE48A112 JAN-C-5										
-48039-A10	CAPACITOR, fixed: 12/22/31 NT-48039 w/70 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A700K	16-C-28098-2662				CD	9-54070	CAY CAY	P-7705830-3 7705830-4	TBK-6 TBK-7 Con't

SHEET 48-19

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 20

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48039-B2	CAPACITOR, fixed: 12/22/31 NT-48039 w/ 70 mmf p/m 2%; temp coef ltr B. NOTE: TBL-5; TBL-6; TBL-7; TBL-10; TBL-11; TBL-12; TBL-13	RE48A112 JAN-C-5	CM55B700G	16-C-28047-9702	N16-C-9875	R16-C-9879-800		CD	9-54070		TBL-2 TBL-3 SEE NOTE
-48039-B5	CAPACITOR, fixed: 12/22/31 NT-48039 w/70 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B700J	16-C-28053-2182	N16-C-9875-1			CD	9-54070		
-48039-B10	CAPACITOR, fixed: 12/22/31 NT-48039 w/70 mmf p/m 10%; temp coef ltr B. NOTE: TBM-5 thru TBM-8.	RE48A112 JAN-C-5	CM55B700K	16-C-28058-2667	N16-C-9875-3			CD	9L-54070	F-7705830-4 T-7607280-29 T-7607093-29 T-7605847-27	TBK-11 TBK-13 TBK-15 TBK-16 SEE NOTE:
-48039-B20	CAPACITOR, FIXED: 2/10/38 Navy Type 48039 w/70 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5		16-C-28063-5147				CD	9L-54070		
-48039-A	CAPACITOR, fixed: 2/10/38 CANCELLED: for replacement use NT-481078.	RE48A112						CD	9FL-64070		TBL-3
-48040	CAPACITOR, fixed: 12/22/31 mica; 150 mmf; 2500 vdc; 5000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; moulded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5									
-48040-A10	CAPACITOR, fixed: 12/22/31 NT-48040 w/150 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A151K	16-C-28981-4662				CD	9-53015		
-48040-B2	CAPACITOR, fixed: 12/22/31 NT-48040 w/ 150 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B151G	16-C-28971-2707	N16-C-10187-51	R16-C-9956		CD CRV	9-53015 Model "F"	CRV	X-35484-35 rev9
-48040-B5	CAPACITOR, fixed: 12/22/31 NT-48040 w/150 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B151J	16-C-28976-4187	N16-C-9955-46			CD	9L-53015		
48040-B10	CAPACITOR, fixed: 12/22/31 NT-48040 w/150 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B151K	16-C-28981-4667	N16-C-9956-1		3K5515121	CD	9L-53015		

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-20

RESTRICTED

RESTRICTED

SHEET 48 - 21

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48041	CAPACITOR, fixed: 12/22/31 mica; 100 mmf; 600 vdcw, 1000 vdc; case 1 3/16" lg max x 3/4" wd max x 5/16" thk max; moulded bakelite case; two tab term ea w/ one 0.144" diam mtg hole, 1 3/4" c to c.	RE48A220 16C40										
-48041-A20	CAPACITOR, fixed: 12/22/31 NF-48041 w/100 mmf p/m 20%; temp coef ltr A.	RE48A220 16C40		16-C-28563-5380								
-48041-B2	CAPACITOR, fixed: 12/22/31 NF-48041 w/100 mmf p/m 2%; temp coef ltr B.	RE48A220 16C40		16-C-28547-9945	H16-C-9924-14	R16-C-9926-5						
-48041-B5	CAPACITOR, fixed: 12/22/31 NF-48041 w/100 mmf p/m 5%; temp coef ltr B.	RE48A220 16C40		16-C-28553-2425	H16-C-9925-4							
-48042	CAPACITOR, fixed: 12/22/31 mica; 1000 mmf; 600 vdcw, 1000 vdc; case 1 3/16" lg max x 3/4" wd max x 5/16" thk max; moulded bakelite case; two tab term ea w/ one 0.144" diam mtg hole, 1 3/4" c to c.	RE48A220 16C40										
-48042-A20	CAPACITOR, fixed: 12/22/31 NF-48042 w/1000 mmf p/m 20%; temp coef ltr A.	RE48A220 16C40		16-C-31095-7780								
-48042-B10	CAPACITOR, fixed: 12/22/31 NF-48042 w/ 1000 mmf p/m 10%; temp coef ltr B. NOTE: DO-2 (5); DO-3 (5); DP (5); DP-1 (5); DP-2 (5); DP-3 (5); RAZ; RAZ-1.	RE48A220 16C40		16-C-31090-5301				CAN	B-10	CRV CRN	K-80149-7	DO (5) DO-1 (5) SEE NOTE
-48043	CAPACITOR, fixed: 12/22/31 mica; 2000 mmf; 600 vdcw, 1000 vdc; case 1 3/16" lg max x 3/4" wd max x 5/16" thk max; moulded bakelite case; two tab term ea w/ one 0.144" diam mtg hole, 1 3/4" c to c.	RE48A220 16C40										
-48043-A20	CAPACITOR, fixed: 12/22/31 NF-48043 w/2000 mmf p/m 20%; temp coef ltr A.	RE48A220 16C40		16-C-31807-9580		R16-C-10241-14						
-48044	CAPACITOR, fixed: 6/27/32 mica; 1250 mmf; 5000 vdcw, 10.5 amp at 3000 kc, 10 amp at 1000 kc, 5 amp at 300 kc, 2.5 amp at 100 kc; case 2 1/2" lg x 2 1/2" wd x 1 15/16" h; potted in metal case; one screw term on ea side 3/4" h; two mtg fl on bottom, four 0.0173" diam holes on 2" x 3" mtg/c.	RE48A250 16C40										
-48044-B5	CAPACITOR, fixed: 6/27/32 NF-48044 w/1250 mmf p/m 5%; temp coef ltr B.	RE48A250 16C40		16-C-31324-7442				CRV	UC-2953, case #356	CRV CAY	K-35405 rev 1 P-7704120	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-21

RESTRICTED

RESTRICTED

SHEET 48 - 22

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD STOCK NO	NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48045	CAPACITOR, fixed: 7/12/32 mica; 50,000/50,000/100,000 mmf; 1,000/1,000/2,000 vdcw; case 4" lg x 3" wd x 3 5/16" h; potted in metal case; four screw term 15/16" h, ctr 3/4" h x 1" wd; four mtg ft on bottom, ea w/a 0.257" diam mtg hole on 2 1/8" x 4 5/8" mtg/c.	REF48A251 16C40											
-48045-B5	CAPACITOR, fixed: 7/12/32 NT-48045 w/50,000/50,000/100,000 mmf p/m 5%; temp coef ltr B.	REF48A251 16C40		16-C-39440-5069	N16-C-12693-1				CRV CD	UC-2852K, case #251 SEN464	CRV CD	K-35769 sub 0 4510 rev 0	
-48046	CAPACITOR, fixed: 7/12/32 mica; 2000 mmf; 8000 vdcw, 8 amp at 1000 kc, 5 amp at 300 kc, 3 amp at 100; case 4 1/2" lg x 1 3/4" wd x 1 5/8" h; potted in cast metal case; two pillar term 1 1/16" h on ea end; two through holes 0.206" diam 1 7/16" c to c.	REF48A252 16C40											
-48046-B5	CAPACITOR, fixed: 7/12/32 NT-48046 w/ 2,000 mmf p/m 5%; temp coef ltr B.	REF48A252 16C40		16-C-31800-2354					CRV	UC-2693, case #303	CRV	K-35770 sub 0	
-48047	CAPACITOR, FIXED: 7/12/32 mica; 60000/60000 mmf; 2000 vdcw on sect, 20 amp at 2500 kc on sect; case dimen 4" lg x 3 1/2" wd x 4" h; potted in cast metal case; 2 solder lug term near bottom 2 1/2" c to c; 4 holes #10-24 thd x 5/16" d in bottom (2 1/2" lg x 1 13/16" wd mtg/c); add suffix indicating capacity tolerance in per cent.	REF48A239 16C40											
-48047-B5	CAPACITOR, fixed: 7/12/32 NT-48047 w/60,000/60,000 mmf p/m 5%; temp coef ltr B.	REF48A239 16C40		16-C-39433-1821					CRV	UC-2563, case #209	CRV	K-35398 sub 0	
-48048	CAPACITOR, fixed: 1/28/32 mica; 500 mmf; 500 vdcw, 1000v DC test; case 1 1/4" lg x 5/8" wd x 1 1/4" thk; moulded low-loss bakelite case; two solder lug term; two 9/64" diam holes in case 1 1/4" mtg/c.	REF48A217 16C40											
-48048-B10	CAPACITOR, fixed: 1/28/32 NT-48048 w/500 mmf p/m 10%; temp coef ltr B. NOTE: RAA-3; RAA-4.	REF48A217 16C40		16-C-30167-2560	N16-C-10016-12				CAW	1461	CRV	K-30088-1 rev 2	RAA RAA-2 SEE NOTE

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-22

RESTRICTED

RESTRICTED

SHEET 48 - 23

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USE IN
-48049	CAPACITOR, fixed: 1/28/32 paper dielectric; three sect; 1.5 mf/1.5 mf/1.5 mf minus 10 plus 25%; 300 vdcw ea sect; metal can; 3" h x 3 1/4" wd x 2 7/16" thk; asphalt compound impr and filled; four flex wire term 16" lg from bottom of case; no int gnd connections; mts by four 0.177" diam holes on 1 5/8" x 3 5/8" mtg/c. NOTE: RAB (2); RAB-1 (2).	RE13A488		16-C-54688-5900	N16-C-11453			CRV	MI-2359	CRV	M-66005-1	RAA R A-2 RAA-3 RAA-4(10) RAB-4(2) RAB-2(2) RAB-3(2) SEE NOTE:
-48049-A	CAPACITOR, fixed: 6/17/40 paper dielectric; three sect; 1.5 mf/1.5 mf/1.5 mf plus 10 minus 25%; 400/400/400 vdcw; metal can; 3" h x 3 1/4" wd x 2 7/16" thk; asphalt compound impr and filled; four flex wire term 16" lg out of bottom ctr; no int gnd connections; two integral mtg fl at bottom w/ four 0.177" diam holes 1 5/8" x 3 5/8" c to c; same as NT-48049 except 400 vdcw instead of 300 vdcw.	RE48A165 RE13A488		16-C-54687-4690				CRV	MI-2359	CRV	M-66005-1	
-48049-A10	CAPACITOR, fixed: 6/17/40 NT-48049-A w/1.5 mf p/m 10% ea sect.	RE48A165 RE13A488		16-C-54688-6203	N16-C-11455							
-48050	CAPACITOR, VARIABLE: 1/28/32 dielectric; compression type, single sect; 10 to 60 mmf; 1 31/32" lg x 1 5/16" wd x 3/4" h; solder lug term; 2 mtg holes in base 3/4" c to c; slotted screw adj; fixed plated coated w/vitreous enamel.	XA-8173		16-C-57500-4125				CRV		CRV	K-806789-01 rev 6	RAA RAB RAA-2 RAA-3 RAA-4 (5)
-48051	CAPACITOR, fixed: 2/1/32 mica; 10,000 mmf; 600 vdcw, 1000 vdcw; case 1 3/16" lg max x 3/4" wd max x 5/16" thk max; molded bake- lite case; two tab term ea w/ one 0.144" diam mtg hole, 1 3/4" c to c.	RE48 220 16C40										
-48051-A20	CAPACITOR, fixed: 2/1/32 NT-48051 w/10,000 mmf p/m 20%; temp coef ltr A.	RE48A220 16C40		16-C-33628-1181								
-48051-B10	CAPACITOR, fixed: 2/1/32 NT-48051 w/ 10,000 mmf p/m 10%; temp coef ltr B. NOTE: DP (4) thru DP-3 (4); TCP (3) thru TCP-2 (3); TCP-3.	RE48A220 16C40		16-C-33622-7701	N16-C-10498-1	R16-C-10498		CAN	B-1110	CRM	X-801494-5 rev 2 CA-175	DO (4) thru E-3 (4) SEE NOTE
-48051-B20	CAPACITOR, fixed: 2/1/32 NT-48051 w/10,000 mmf p/m 20%; temp coef ltr B.	RE48A220 16C40		16-C-33628-1183	N16-C-10498							

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-23

RESTRICTED

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48052	CAPACITOR, fixed: 2/1/32 mica; 500 mmf; 600 vdcw, 1000 vdet; case 1 3/16" lg max x 3/4" wd max x 5/16" thk max; moulded bakelite case; two tab term ea w/ one 0.144" diam mtg hole, 1 3/4" c to c.	RE48A220 16C40									
-48052-A20	CAPACITOR, fixed: 2/1/32 NT-48052 w/500 mmf p/m 20%; temp coef ltr A.	RE48A220 16C40		16-C-30172-5780							
-48052-B10	CAPACITOR, fixed: 2/1/32 NT-48052 w/500 mmf p/m 10%; temp coef ltr B. NOTE: DP thru DP 3.	RE48A220 16C40		16-C-30167-3301	N16-C-10016-14			CAN		CRV K-801494-6rev2	DO thru DO-3 SEE NOTE
-48053	CAPACITOR, fixed: 2/1/32 mica; 250 mmf; 600 vdcw, 1000 vdet; case 1 3/16" lg max x 3/4" wd max d 5/16" thk max; moulded bakelite case; two tab term ea w/ one 0.144" diam mtg hole, 1 3/4" c to c.	RE48A220 16C40									
-48053-A20	CAPACITOR, fixed: 2/1/32 NT-48053 w/250 mmf p/m 20%; temp coef ltr A.	RE48A220 16C40		16-C-20486-7380							
-48053-B10	CAPACITOR, fixed: 2/1/32 NT-48053 w/250 mmf p/m 10%; temp coef ltr B. NOTE: DO-2; DO-3; DP; DP-1; DP-2; DP-3.	RE48A220 16C40		16-C-29481-4901				CAN		CRV K-801494-9rev2	DO DO-1 SEE NOTE
-48054	CAPACITOR, fixed: 2/5/32 mica; 2,000/2,000 mmf; 2500 vdcw ea sect, 5 amp at 1000 kc, 3.5 amp at 300 kc, 2 amp at 100 kc; case 3 1/2" lg x 2 1/4" wd x 2 3/4" h; potted in cast metal case; two stud term on top 1 1/4" h on 1 1/4" ctr, one side of ea sect int gnd; four mtg feet on bottom w/ 0.144" hole, on 4" x 1 13/16" mtg/c.	RE48A104 16C40									
-48054-B5	CAPACITOR, fixed: 2/5/32 NT-48054 w/2,000/2,000 mmf p/m 5%; temp coef ltr B.	RE48A104 16C40		16-C-39427-7701				CRV	UC-1868		
-48055	CAPACITOR, fixed: 2/5/32 mica; 2,000/2,000 mmf; 7000 vdcw, 8 amp at 1000 kc, 5 amp at 300 kc, 3 amp at 100 kc; case 3 1/2" lg x 2 1/4" wd x 2 3/4" h; potted in cast metal case; two stud term on top 1 1/4" h on 1 1/4" ctr, one side of ea sect int gnd; four mtg feet on bottom w/ 0.144" hole, on 4" x 1 13/16" mtg/c.	RE48A104 16C40									
-48055-B5	CAPACITOR, fixed: 2/5/32 NT-48055 w/2,000/2,000 mmf p/m 5%; temp coef ltr B.	RE48A104 16C40		16-C-39427-7901				CRV	UC-1879		

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 25

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48056	CAPACITOR, fixed: 2/5/32 mica; 2,000 mmf; 15,000 vdcw 22 amp at 1000 kc, 15 amp at 300 kc, 9 amp at 100 kc; case 5 3/4" lg x 5 3/4" wd x 5 5/8" h; potted in cast metal case; one stud term on top 11/16" h ctr other term gnd to case; two mtg ears opposite sides w/ 11/32" diam mtg holes 8" c to c.	RE48A105 16C40										
-48056-B10	CAPACITOR, fixed: 2/5/32 NT-48056 w/2,000 mmf p/m 10%; temp coef ltr A.	RE48A105 16C40		16-C-31805-8920				CRV	UC-1804			
-48057	CAPACITOR, fixed: 2/6/32 mica; 1,000 mmf; 10,000 vdcw, 16 amp at 1000 kc, 9 amp at 300 kc, 3 amp at 100 kc; case 5 3/4" lg x 5 3/4" wd x 5 5/8" h; potted in cast metal case; one stud term on top 11/16" h ctr other term int gnd; two mtg ears opposite sides w/ 11/32" diam mtg holes 8" c to c.	RE48A105 16C40										
-48057-B5	CAPACITOR, fixed: 2/6/32 NT-48057 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A105 16C40		16-C-31088-2535	N16-C-10099-7			CRV	UC-1809			
-48058	CAPACITOR, fixed: 2/6/32 mica; 500 mmf; 10,000 vdcw. 12 amp at 1000 kc, 5 amp at 300 kc, 2 amp at 100 kc; case 5 3/4" lg x 5 3/4" wd x 5 5/8" h; potted in cast metal case; one stud term on top 11/16" h ctr other term int gnd; two mtg ears opposite sides w/ 11/32" diam mtg holes 8" c to c.	RE48A105 16C40										
-48058-B5	CAPACITOR, fixed: 2/6/32 NT-48058 w/500 mmf p/m 5%; temp coef ltr B.	RE48A105 16C40		16-C-30164-9545				CRV	UC-1840			
-48059	CAPACITOR, fixed: 2/6/32 mica; 500 mmf; 15,000 vdcw, 9 amp at 1000 kc, 6 amp at 300 kc, 3 amp at 100 kc; case 5 3/4" lg x 5 3/4" wd x 6 13/16" max h; potted in cast metal case; one stud term on top 11/16" h ctr, other term int gnd; two mtg ears opposite sides w/ 11/32" diam mtg holes 8" c to c.	RE48A105 16C40										
-48059-B5	CAPACITOR, fixed: 2/6/32 NT-48059 w/500 mmf p/m 5%; temp coef ltr B.	RE48A105 16C40		16-C-30165-3604				CRV	UC-1865			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-25

RESTRICTED

RESTRICTED

SHEET 48 - 26

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48060	CAPACITOR, fixed; 2/6/32 mica; 20,000 mmf; 2500 vdcw, 15 amp at 3000 kc, 18 amp at 1000 kc, 12 amp at 300 kc, 7 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48060-B5	CAPACITOR, fixed; 2/6/32 NT-48060 w/20,000 mmf p/m 5%; temp coef 1tr B; for replacement use NT-481288-B5.	RE48A108 16C40		16-C-34331-1584				CRV	UC-2256			
-48061	CAPACITOR, fixed; 2/6/32 mica; 20,000 mmf; 3000 vdcw, 18 amp at 3000 kc, 21 amp at 1000 kc, 14 amp at 300 kc, 8 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48061-B5	CAPACITOR, fixed; 2/6/32 NT-48061 w/20,000 mmf p/m 5%; temp coef 1tr B; for replacement use NT-481288-B5.	RE48A108 16C40		16-C-34331-2396				CRV	UC-1821			
-48062	CAPACITOR, fixed; 2/6/32 mica; 15,000 mmf; 2,500 vdcw, 16 amp at 3000 kc, 13 amp at 1000 kc, 9 amp at 300 kc, 5 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48062-B5	CAPACITOR, fixed; 2/6/32 NT-48062 w/15,000 mmf p/m 5%; temp coef 1tr B.	RE48A108 16C40		16-C-34040-9184	N16-C-10541-11			CRV	UC-2255			
-48063	CAPACITOR, fixed; 2/6/32 mica; 10,000 mmf; 2,500 vdcw, 12 amp at 3000 kc, 9 amp at 1000 kc, 6 amp at 300 kc, 3.5 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes on base 3 1/4" c to c.	RE48A108 16C40										
-48063-B5	CAPACITOR, fixed; 2/6/32 NT-48063 w/10,000 mmf p/m 5%; temp coef 1tr B.	RE48A108 16C40		16-C-33618-8788				CRV	UC-2267			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-26

RESTRICTED

RESTRICTED

SHEET 48 - 27

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48064	CAPACITOR, fixed: 2/6/32 mica; 10,000 mmf; 3,000 vdcw, 8 amp at 1000 kc, 5.2 amp at 300 kc, 0.3 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base on 3 1/4" c to c.	RE48A108 16C40										
-48064-A5	CAPACITOR, fixed: 2/6/32 NT-48064 w/10,000 mmf p/m 5%; temp coef ltr A; for replacement use NT-481287.	RE48A108 16C40		16-C-33618-9591	116-C-10521			CRV	UC-2267			
-48064-B5	CAPACITOR, fixed: 2/6/32 NT-48064 w/10,000 mmf p/m 5%; temp coef ltr B; for replacement use NT-481287.	RE48A108 16C40		16-C-33618-9596				CRV	UC-2294			
-48065	CAPACITOR, fixed: 2/6/32 mica; 5,000 mmf; 3,000 vdcw, 11 amp at 3000 kc, 7.5 amp at 1000 kc, 5 amp at 300 kc, 3 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48065-B5	CAPACITOR, fixed: 2/6/32 NT-48065 w/5,000 mmf p/m 5%; temp coef ltr B; for replacement use NT-481286.	RE48A108 16C40		16-C-32695-7596				CRV	UC-1852			
-48066	CAPACITOR, fixed: 2/6/32 mica; 4,000 mmf; 3,000 vdcw, 9 amp at 3,000 kc, 6 amp at 1,000 kc, 4 amp at 300 kc, 2.5 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48066-B5	CAPACITOR, fixed: 2/6/32 NT-48066 w/4,000 mmf p/m 5%; temp coef ltr B; for replacement use NT-481285.	RE48A108 16C40		16-C-32458-3996				CRV	UC-1885			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-27

RESTRICTED

RESTRICTED

SHEET 48 - 28

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48067	CAPACITOR, fixed: 2/6/32 mica; 4,000 mmf; 5,000 vdcw, 15 amp at 3,000 kc, 9 amp at 1,000 kc, 6 amp at 300 kc, 3.5 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40									
-48067-B5	CAPACITOR, fixed: 2/6/32 NT-48067 w/4,000 mmf p/m 5%; temp coef 1tr B; for replacement use NT-481285.	RE48A108 16C40		16-C-32458-9596	N16-C-10385			CRV	UC-1842		
-48068	CAPACITOR, fixed: 2/6/32 mica; 3,000 mmf; 3,000 vdcw, 15 amp at 3,000 kc, 12 amp at 1,000 kc, 8 amp at 300 kc, 4 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40									
-48068-B5	CAPACITOR, fixed: 2/6/32 NT-48068 w/3,000 mmf p/m 5%; temp coef 1tr B.	RE48A108 16C40		16-C-32194-5996				CRV	UC-2295		
-48069	CAPACITOR, fixed: 2/6/32 mica; 2,500 mmf; 2,500 vdcw, 8 amp at 3,000 kc, 4 amp at 1,000 kc, 2.7 amp at 300 kc, 1.5 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40									
-48069-B5	CAPACITOR, fixed: 2/6/32 NT-48069 w/2,500 mmf p/m 5%; temp coef 1tr B; for replacement use NT-481284.	RE48A108 16C40		16-C-32009-8384	N16-C-10318			CRV	UC-2253		
-48070	CAPACITOR, fixed: 2/5/32 mica; 2,000 mmf; 6,000 vdcw, 12 amp at 3,000 kc, 7.5 amp at 1,000 kc, 5 amp at 300 kc, 3 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40									
-48070-B5	CAPACITOR, fixed: 2/6/32 NT-48070 w/2,000 mmf p/m 5%; temp coef 1tr B; for replacement use NT-481283-B5.	RE48A108 16C40		16-C-31799-6876	N16-C-10284-3		3DA2-6	CRV	UC-2231		

SHEET 48-28

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 29

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48071	CAPACITOR, fixed: 2/6/32 mica; 1,000 mmf; 4,000 vdcv, 10 amp at 3,000 kc, 6 amp at 1,000 kc, 4 amp at 300 kc, 1.5 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48071-B5	CAPACITOR, fixed: 2/6/32 NT-48071 w/1,000 mmf p/m 5%; temp coef ltr B; for replacement use NT-48832-B5.	RE48A108 16C40		16-C-31087-2255				CRV	UC-1884	CRV	T-602221-16	TAJ-4
-48072	CAPACITOR, fixed: 2/6/32 mica; 100 mmf; 5,000 vdcv, 3 amp at 3,000 kc, 2 amp at 1,000 kc, 0.8 amp at 300 kc, 0.2 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term on top 2" h shielded, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48072-B5	CAPACITOR, fixed: 2/6/32 NT-48072 w/100 mmf p/m 5%; temp coef ltr B.	RE48A108 16C40		16-C-28555-1391	N16-C-9940		3D9100-1	CRV	UC-1808			
-48072-B10	CAPACITOR, fixed: 2/6/32 NT-48072 w/100 mmf p/m 10%; temp coef ltr B.	RE48A108 16C40		16-C-28560-1876	N16-C-9940-7		3D9100-1	CRV	UC-1808			
-48073	CAPACITOR, fixed: 2/6/32 mica; 7,000 mmf; 3,000 vdcv, 17 amp at 3,000 kc, 15 amp at 1,000 kc, 10 amp at 300 kc, 6 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48073-B5	CAPACITOR, fixed: 2/6/32 NT-48073 w/7,000 mmf p/m 5%; temp coef ltr B.	RE48A108 16C40		16-C-33117-7996				CRV	UC-2391			
-48074	CAPACITOR, fixed: 2/6/32 mica; 500 mmf; 3,000 vdcv, 7 amp at 3,000 kc, 3.3 amp at 1000 kc, 2 amp at 300 kc, 0.8 amp at 100 kc; case 3 9/16" lg x 2 9/16" wd x 2 15/16" h; cast metal case; one pillar term w/ shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48074-B5	CAPACITOR, fixed: 2/6/32 NT-48074 w/500 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-30163-5416	N16-C-10023-18			CRV	UC-1851K	CRV CRV	T-602221-15 DL-501619-502	TAJ-4 TBL TBL-1

SHEET 48-29

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 30

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48075	CAPACITOR, fixed: 2/6/32 sulphur; 50 mmf; 3000 vdcv, 3.5 amp at 10000 kc; case dimen 2 1/2" wd x 2 1/4" d x 4" h; cast metal case; 1 pillar term on top 2" h centered, other term int gnd; two 1/4" diam mtg holes in base 3 1/4" c to c; add suffix indicating capacity tolerance in per cent.	RE48A108										
-48075-5	CAPACITOR, fixed: 2/6/32 NT-48075 w/50 mmf p/m 5%.	RE48A108		16-C-56456-6261	N16-C-11800			CRV	UC-2535			
-48076	CAPACITOR, fixed: 2/6/32 mica; 60,000 mmf; 700 vdcv, 18 amp at 3,000 kc, 50 amp at 1,000 kc, 34 amp at 300 kc, 19 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48076-B5	CAPACITOR, fixed: 2/6/32 NT-48076 w/60,000 mmf p/m 5%; temp coef 1tr B.	RE48A108 16C40		16-C-35385-2342	N16-C-10596-105			CRV	UC-2205			
-48077	CAPACITOR, fixed: 2/6/32 mica; 40,000 mmf; 700 vdcv; 18 amp at 3,000 kc, 33 amp at 1,000 kc, 22 amp at 300 kc, 12 amp at 100 kc, case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48077-B5	CAPACITOR, fixed: 2/6/32 NT-48077 w/40,000 mmf p/m 5%; temp coef 1tr B.	RE48A108 16C40		16-C-34989-5342	N16-C-10583			CRV	UC-2206K			
-48078	CAPACITOR, fixed: 2/6/32 mica; 300 mmf; 5,000 vdcv, 3 amp at 3,000 kc, 1 amp at 1,000 kc, 0.7 amp at 300 kc, 0.4 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2", one side gnd to case; two 1/4" diam holes in base 3 1/4" c to c.	RE48A108 16C40										
-48078-B5	CAPACITOR, fixed: 2/6/32 NT-48078 w/300 mmf p/m 5%; temp coef 1tr B; for replacement use NT-481202.	RE48A108 16C40		16-C-29662-9196				CRV	UC-2320			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-30

RESTRICTED

RESTRICTED

SHEET 48 - 31

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48079	CAPACITOR, fixed: 2/6/32 mica; 1,500 mmf; 4,000 vdcw, 11 amp at 3,000 kc, 8 amp at 1,000 kc, 4 amp at 300 kc, 2 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 3 1/4" c to c.	RE48A108 16C40										
-48079-B5	CAPACITOR, fixed: 2/6/32 NT-48079 w/1,500 mmf p/m 5%; temp coef ltr B; for replacement use NI-48834.	RE48A108 16C40		16-C-31509-2652	N16-C-10189			CRV	UC-2641K			
-48080	CAPACITOR, fixed: 2/6/32 mica; 14,000 mmf; 2,000v max working, 16 amp at 3,000 kc, 18 amp at 1,000 kc, 12 amp at 300 kc, 7 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shield on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48080-B5	CAPACITOR, fixed: 2/6/32 NI-48080 w/14,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-33987-9836				CRV	UC-2322			
-48081	CAPACITOR, fixed: 2/6/32 mica; 40,000 mmf; 1,500 vdcw, 25 amp at 3,000 kc, 37 amp at 1,000 kc, 25 amp at 300 kc, 14 amp at 100 kc; case 3 9/16" wd x 2 9/16" dx 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48081-B5	CAPACITOR, fixed: 2/6/32 NT-48081 w/40,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-35755-1989				CRV	UC-2298			
-48082	CAPACITOR, fixed: 2/6/32 mica; 60,000 mmf; 1,500 vdcw, 20 amp at 3,000 kc, 50 amp at 1,000 kc, 40 amp at 300 kc, 30 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48082-B5	CAPACITOR, fixed: 2/6/32 NT-48082 w/60,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-35384-4309				CRV	UC-1898			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-31

RESTRICTED

RESTRICTED

SHEET 48 - 32

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48083	CAPACITOR, fixed: 2/6/32 mica; 40,000 mmf; 1,500 vdcw, 20 amp at 3,000 kc, 50 amp at 1,000 kc, 40 amp at 300 kc, 25 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48083-B5	CAPACITOR, fixed: 2/6/32 NT-48083 w/40,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-34990-2389				CRV	UC-1897A			
-48084	CAPACITOR, fixed: 2/6/32 mica; 20,000 mmf; 1,500 vdcw, 22 amp at 3,000 kc, 30 amp at 1,000 kc, 20 amp at 300 kc, 12 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48084-B5	CAPACITOR, fixed: 2/6/32 NT-48084 w/20,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-34330-7389				CRV	UC-1896			
-48085	CAPACITOR, fixed: 2/6/32 mica; 10,000 mmf; 1,500 vdcw; 14 amp at 3,000 kc, 15 amp at 1,000 kc, 10 amp at 300 kc, 6 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48085-B5	CAPACITOR, fixed: 2/6/32 NT-48085 w/10,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-33618-5589				CRV	UC-1894			
-48086	CAPACITOR, fixed: 2/6/32 mica; 10,000 mmf; 3,000 vdcw, 18 amp at 3,000 kc, 30 amp at 1,000 kc, 20 amp at 300 kc, 10 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48086-B5	CAPACITOR, fixed: 2/6/32 NT-48086 w/10,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-33618-9816				CRV	UC-1849			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-32

RESTRICTED

RESTRICTED

SHEET 48 - 33

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48087	CAPACITOR, fixed: 2/6/32 mica; 3,000 mmf; 5,000 vdcw, 12 amp at 1,000 kc, 8.5 amp at 300 kc, 5 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48087-B5	CAPACITOR, fixed: 2/6/32 NT-48087 w/3,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-32195-2889	N16-C-10329			CRV	UC-1850A			
-48088	CAPACITOR, fixed: 2/6/32 mica; 4,000 mmf; 2,000 vdcw, 16 amp at 3,000 kc, 15 amp at 1,000 kc, 10 amp at 300 kc, 6 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48088-B5	CAPACITOR, fixed: 2/6/32 NT-48088 w/4,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-32458-1636				CRV	UC-2529			
-48089	CAPACITOR, fixed: 2/6/32 mica; 2,000 mmf; 5,000 vdcw, 10 amp at 600 kc, 12 amp at 1,000 kc, 7 amp at 300 kc, 3.5 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, other term int gnd; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48089-B5	CAPACITOR, fixed: 2/6/32 NT-48089 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-31799-5885				CRV	UC-2859			
-48089-B10	CAPACITOR, fixed: 2/6/32 NT-48089 w/2,000 mmf p/m 10%; temp coef ltr B.	RE48A109 16C40		16-C-31804-6369				CRV	UC-2859			
-48090	CAPACITOR, fixed: 2/6/32 mica; 2,000 mmf; 3,000 vdcw, 12 amp at 3,000 kc, 10 amp at 1,000 kc, 6.5 amp at 300 kc, 3 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h, one side gnd to case; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48090-B5	CAPACITOR, fixed: 2/6/32 NT-48090 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-31798-9632				CRV	UC-2318			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-33

RESTRICTED

RESTRICTED

SHEET 48 - 34

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFG	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48091	CAPACITOR, fixed: 2/6/32 mica; 500 mmf; 2,500 vdcw, 7.5 amp at 1,000 kc, 2.3 amp at 300 kc, 0.8 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; two pillar terminals shielded on top 2" h, other term int gnd; two 1/4" diam mtg holes in base 4 1/4" c to c.	RE48A109 16C40										
-48091-B5	CAPACITOR, fixed: 2/6/32 NT-48091 w/500 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-30163-4431				CRV	UC-2503A			
-48092	CAPACITOR, fixed: 2/6/32 mica; 5,000 mmf; 2,000 vdcw, 16 amp at 3,000 kc, 15 amp at 1,000 kc, 10 amp at 300 kc, 6 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; incl term cast metal case; 1 stud term on top; 2 mtg holes 1/4" diam, 4 1/4" mtg/c; add suffix indicating capacity tolerance in per cent.	RE48A109 16C40										
-48092-B5	CAPACITOR, fixed: 2/6/32 NT-48092 w/5,000 mmf p/m 5%; temp coef ltr B.	RE48A109 16C40		16-C-32695-5236				CRV	UC-2223			
-48092-R20	CAPACITOR, FIXED: 2/18/49 Navy Type 48092 w/5000 mmf p/m 20%; temp coef ltr B.	RE48A109E		16-C-32705-8337								
-48093	CAPACITOR, fixed: 2/6/32 CANCELLED: for replacement use NT-48093-A.	RE48A110						CRV	UC-490A			
-48093-A	CAPACITOR, fixed: 9/6/36 paper dielectric; 1.0 mfd, plus 10 minus 3%; 1,000 vdcw; HS metal can; 4 1/2" h x 2 1/2" wd x 2" d; two stud term 1/2" h located on top, spaced 1" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-48799-8637								
-48093-A10	CAPACITOR, fixed: 9/6/36 NT-48093-A w/1.0 mfd p/m 10%.	RE48A110 RE13A488		16-C-48820-8632	N16-C-11424-11							
-48094	CAPACITOR, fixed: 2/6/32 paper dielectric; 500,000 mmf plus 10 minus 3%; 1,000 vdcw; HS metal can; 4 1/2" h x 2 1/2" wd x 1" thk; oil impr and filled; two stud and nut term 1/2" h 1" c to c on top; no int gnd connections.	RE48A110		16-C-47279-8642				CRV	UC-489A			
-48094-A	CAPACITOR, fixed: 9/6/36 paper dielectric; 500,000 mmf plus 10 minus 3%; 1,000 vdcw; HS metal can; 4 1/2" h x 2 1/2" wd x 1" d; two stud term 1/2" h located on top, spaced 1" c to c; no int gnd connections; same as NT-48094 except it complies with RE13A488.	RE48A110 RE13A488		16-C-47279-8642	N16-C-11360			CRV	UC-489A			

SHEET 48-34

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 35

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E B O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48095	CAPACITOR, fixed: 2/8/32 mica; 100,000 mmf; 3,000 vdcw, 40 amp at 3,000 kc, 50 amp at 1,000 kc, 35 amp at 300 kc, 20 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" diam mtg holes, two lugs on one end ea w/ two holes, mtg/c 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48095-B5	CAPACITOR, fixed: 2/8/32 NT-48095 w/100,000 mmf p/m 5%; temp coef ltr B.	RE48A111 16C40		16-C-36151-3546	N16-C-10702-76			CRV	UC-1892			
-48096	CAPACITO, fixed: 2/8/32 mica; 10,000 mmf; 5,000 vdcw, 30 amp at 3,000 kc, 40 amp at 1,000 kc, 27 amp at 300 kc, 15 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/ two holes ea, mtg/c 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE 5A111 16C40										
-48096-B5	CAPACITOR, fixed: 2/8/32 NT-48096 w/10,000 mmf p/m 5%; temp coef ltr B.	RE48A111 16C40		16-C-33619-6783				CRV	UC-2288			
-48097	CAPACITOR, fixed: 2/8/32 mica; 4,000 mmf; 12,500 vdcw, 13 amp at 3,000 kc, 15 amp at 1,000 kc, 10 amp at 300 kc, 6 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/ two holes ea, mtg/c 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48097-B5	CAPACITOR, fixed: 2/8/32 NT-48097 w/4,000 mmf p/m 5%; temp coef ltr B.	RE48A111 16C40		16-C-32460-1908				CRV	UC-1822A			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-35

RESTRICTED

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48098	CAPACITOR, fixed: 2/8/32 mica; 5,000 mmf; 5,500 vdcw; 15 amp at 3,000 kc, 20 amp at 1,000 kc, 14 amp at 300 kc, 8 amp at 10 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/ two holes ea, mtg/c 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48098-B5	CAPACITOR, fixed: 2/8/32 NT-48098 w/5,000 mmf p/m 5%; temp coef ltr B.	RE48A111 16C40		16-C-32696-5222				CRV	UC-1875			
-48099	CAPACITOR, fixed: 2/8/32 mica; 15,000 mmf; 5,000 vdcw, 25 amp at 3000 kc, 35 amp at 1000 kc, 24 amp at 300 kc, 14 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/ two holes ea, mtg/c, 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48099-B5	CAPACITOR, fixed: 2/8/32 NT-48099 w/15,000 mmf p/m 5%; temp coef ltr B.	RE48A111 16C40		16-C-34041-7153				CRV	UC-1877			
-48100	CAPACITOR, fixed: 2/8/32 mica; 2,500 mmf; 12,000 vdcw, 15 amp at 3,000 kc, 20 amp at 1,000 kc, 14 amp at 300 kc, 8 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/ two holes ea, mtg/c 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48100-B5	CAPACITOR, fixed: 2/8/32 NT-48100 w/2,500 mmf p/m 5%; temp coef ltr B.	RE48A111 16C40		16-C-32011-5111				CRV	UC-1874			
-48100-B10	CAPACITOR, fixed: 2/8/32 NT-48100 w/2,500 mmf p/m 10%; temp coef ltr B.	RE48A111 16C40		16-C-32016-5591	N16-C-10320-3			CRV	UC-1874			

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 37

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48101	CAPACITOR, fixed: 2/8/32 mica; 1,000 mmf; 15,000 vdcw, 5 amp at 3,000 kc, 7 amp at 1,000 kc, 5 amp at 300 kc, 3 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case: one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/two holes ea, mtg/c 3/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48101-B5	CAPACITOR, fixed: 2/8/32 NT-48101 w/1,000 mmf p/a 5%; temp coef ltr B.	RE48A111 16C40		16-C-31088-6143					2C4101454	CRV	UC-2216	
-48102	CAPACITOR, fixed: 2/8/32 mica; 500 mmf; 12,000 vdcw, 8 amp at 3,000 kc, 10 amp at 1,000 kc, 4 amp at 300 kc, 2 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case: one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/two holes ea, mtg/c 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48102-B5	CAPACITOR, fixed: 2/8/32 NT-48102 w/500 mmf p/a 5%; temp coef ltr B.	RE48A111 16C40		16-C-30165-1111						CRV	UC-2316	
-48103	CAPACITOR, fixed: 2/8/32 mica; 1,000 mmf; 12,000 vdcw, 16 amp at 3000 kc, 12 amp at 1000 kc, 8 amp at 300 kc, 4.5 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case: one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/two holes ea, mtg/c 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48103-B5	CAPACITOR, fixed: 2/8/32 NT-48103 w/1,000 mmf p/a 5%; temp coef ltr B.	RE48A111 16C40		16-C-31088-3112	N16-C-10099-12					CRV	UC-1886	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-37

RESTRICTED

RESTRICTED

SHEET 48 - 38

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48104	CAPACITOR, fixed: 2/8/32 mica; 7,000 mmf; 7,500 vdcw, 18 amp at 3000 kc, 20 amp at 1000 kc, 14 amp at 300 kc, 8 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/ two holes w/ mtg/c 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48104-B5	CAPACITOR, fixed: 2/8/32 NT-48104 w/7,000 mmf p/m 5%; temp coef ltr B.	RE48A111 16C40		16-C-33118-8800				CRV	UC-2262			
-48105	CAPACITOR, fixed: 2/8/32 mica; 2,000 mmf; 12,000 vdcw; 18 amp at 3,000 kc, 20 amp at 1,000 kc, 12 amp at 300 kc, 6 amp at 100 kc; case 5 1/2" wd x 4 1/8" d x 4 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; four mtg lugs on top, six 17/64" mtg holes, two lugs on one end w/two holes w/mtg/c 3 1/4" d x 6 7/8" wd for inside holes and 7 7/16" wd for outside holes.	RE48A111 16C40										
-48105-B5	CAPACITOR, fixed: 2/8/32 NT-48105 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A111 16C40		16-C-31800-4911	N16-C-10241-65			CRV	UC-2614			
-48106	CAPACITOR, fixed: 2/8/32 mica; 1,000 mmf; 15,000 vdcw, 16 amp at 3000 kc, 16 amp at 1000 kc, 9 amp at 300 kc, 3 amp at 100 kc; case 5" diam x 4" h; ceramic case; two cast aluminum end term 6 1/2" lg x 5" wd, one on top and one on bottom, ea term has two 3/8" diam holes 5 3/4" c to c.	RE48A116 16C40										
-48106-B5	CAPACITOR, fixed: 2/8/32 NT-48106 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-31088-5902				CRV	UC-2325			
-48107	CAPACITOR, fixed: 2/8/32 sulphur dielectric; 150 mmf; 6,000 vdcw, 18 amps at 6,000 kc, 12 amps at 4,000 kc; case 5 3/4" h x 5" diam; low loss ceramic case; two elliptical cast aluminum end cap term, ea w/ two 0.377" diam holes 5 3/4" c to c.	RE48A237										
-48107-5	CAPACITOR, fixed: 2/8/32 NT-48107 w/150 mmf p/m 5%.	RE48A237		16-C-56537-7341	N16-C-11810			CRV	UC-2536	CRV	X-35246-111rev1	

SHEET 48-38

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 39

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48108	CAPACITOR, fixed: 2/8/32 mica; 2,000 mmf; 8,000 vdcw max, 15 amp at 3000 kc, 12 amp at 1000 kc, 8 amp at 300 kc, 4.5 amp at 100 kc; case 5" diam x 4" h; ceramic case; two cast aluminum end term 6 1/2" lg x 5" wd, one on top and one on bottom ea term w/two 3/8" diam holes 5 3/4" c to c.	RE48A116 16C40										
-48108-B5	CAPACITOR, fixed: 2/8/32 NT-48108 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-31800-2301				CRV	UC-2371			
-48108-B10	CAPACITOR, fixed: 2/8/32 NT-48108 w/2,000 mmf p/m 10%; temp coef ltr B.	RE48A116 16C40		16-C-31805-3784	N16-C-10287-1							
-48109	CAPACITOR, fixed: 2/8/32 mica; 800 mmf; 3,000 vdcw, 16 amp at 3,000 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end 5 3/4" c to c.	RE48A116 16C40										
-48109-B5	CAPACITOR, fixed: 2/8/32 NT-48109 w/800 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-30691-1571	N16-C-10074			CRV	UC-2509			
-48110	CAPACITOR, fixed: 2/8/32 mica; 400 mmf; 14140 vacw effective, 20,000 vdcw 11 amp at 3,000 kc, 7 amp at 1,000 kc, 4 amp at 300 kc; 2 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48110-B5	CAPACITOR, fixed: 2/8/32 NT-48110 w/400 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-29928-2175				CRV	UC-2356			
-48111	CAPACITOR, fixed: 2/8/32 mica; 600 mmf; 35,000 vdcw, 13.5 amp at 3000 kc, 12 amp at 1000 kc, 7 amp at 300 kc, 4 amp at 100 kc; case 5 3/4" h x 5" diam; low loss ceramic case; two elliptical cast aluminum end cap term, ea w/two 0.377" diam holes 5 3/4" c to c.	RE48A237 16C40										
-48111-B5	CAPACITOR, fixed: 2/8/32 NT-48111 w/600 mmf p/m 5%; temp coef ltr B.	RE48A237 16C40		16-C-30324-3051				CRV	UC-2425			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-39

RESTRICTED

RESTRICTED

SHEET 48 - 40

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY BWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48112	CAPACITOR, fixed: 2/8/32 mica; 1,250 mmf; 10,000 vdcw, 12 amp at 3000 kc, 13 amp at 1000 kc, 7 amp at 300 kc, 4 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48112-B5	CAPACITOR, fixed: 2/8/32 NT-48112 w/1250 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-31325-5652				CRV	UC-2517			
-48113	CAPACITOR, fixed: 2/8/32 mica; 1,700 mmf; 15,000 vdcw, 19 amp at 3000 kc, 18 amp at 1000 kc, 12 amp at 300 kc, 5 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48113-B5	CAPACITOR, fixed: 2/8/32 NT-48113 w/1700 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-31631-3953				CRV	UC-2597			
-48113-B10	CAPACITOR, fixed: 2/8/32 NT-48113 w/1700 mmf p/m 10%; temp coef ltr B.	RE48A116 16C40		16-C-31631-3966				CRV	UC-2597			
-48114	CAPACITOR, fixed: 2/8/32 mica; 3,000 mmf; 9,000 vdcw, 20 amp at 3,000 kc, 18 amp at 1,000 kc, 12 amp at 300 kc, 6.5 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48114-B5	CAPACITOR, fixed: 2/8/32 NT-48114 w/3,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-32195-9220				CRV	UC-2372			
-48115	CAPACITOR, fixed: 2/8/32 mica; 4,000 mmf; 12,000 vdcw, 27 amp at 3,000 kc, 23 amp at 1,000 kc, 16 amp at 300 kc, 8 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48115-B5	CAPACITOR, fixed: 2/8/32 NT-48115 w/4,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-32459-8871	W16 C-10392-1			CRV	UC-2360A			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-40

RESTRICTED

RESTRICTED

SHEET 48 - 41

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48116	CAPACITOR, fixed: 2/8/32 mica; 800 mmf; 20,000 vdcw, 16 amp at 3,000 kc, 11 amp at 1,000 kc, 7 amp at 300 kc, 4 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48116-B5	CAPACITOR, fixed: 2/8/32 NT-48116 w/800 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-30693-1388	N16-C-10074-44			CRV	UC-2355			
-48117	CAPACITOR, fixed: 2/8/32 mica; 450 mmf; 15,000 vdcw, 14 amp at 3,000 kc, 11 amp at 1,000 kc, 7 amp at 300 kc, 4 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48117-A5	CAPACITOR, fixed: 2/8/32 NT-48117 w/450 mmf p/m 5%; temp coef ltr A.	RE48A116 16C40		16-C-30086-2588	N16-C-10015-1			CRV	UC-2682			
-48117-B5	CAPACITOR, fixed: 2/8/32 NT-48117 w/450 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-30086-2593	N16-C-10015-1			CRV	UC-2682			
-48118	CAPACITOR, fixed: 2/8/32 mica; 6,000 mmf; 6,000 vdcw, 20 amp at 1000 kc, 12 amp at 300 kc, 7 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48118-B5	CAPACITOR, fixed: 2/8/32 NT-48118 w/6,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-32854-8512				CRV	UC-2648			
-48119	CAPACITOR, fixed: 2/8/32 mica; 2,000 mmf; 12,000 vdcw, 21 amp at 3,000 kc, 20 amp at 1,000 kc, 12 amp at 300 kc, 7 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end 5 3/4" c to c.	RE48A116 16C40										
-48119-B5	CAPACITOR, fixed: 2/8/32 NT-48119 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-31800-4871				CRV	UC-2366			
-48119-B10	CAPACITOR, fixed: 2/8/32 NT-48119 w/2,000 mmf p/m 10%; temp coef ltr B.	RE48A116 16C40		16-C-31805-6453	N16-C-10289			CRV	UC-2366			

SHEET 48-41

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 42

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48120	CAPACITOR, fixed: 2/8/32 mica; 5,000 mmf; 5,656 vacw effective, 30 amp at 3,000 kc, 30 amp at 1,000 kc, 20 amp at 300 kc, 10 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48120-B2	CAPACITOR, fixed: 2/8/32 NT-48120 w/5,000 mmf p/m 2%; temp coef ltr B. NOTE: TAB-7 (2).	RE48A116 16C40		16-C-32691-8424				CD	181-51	CAY	T-7606683-30	TAB-5 (2) TAB-6 (2) SEE NOTE
-48120-B5	CAPACITOR, fixed: 2/8/32 NT-48120 w/5,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-32696-9570				CRV	UC-2663			
-48121	CAPACITOR, fixed: 2/8/32 mica; 1,500 mmf; 12,000 vdcw max, 16 amp at 3,000 kc, 12 amp at 1,000 kc, 8 amp at 300 kc, 4.5 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48121-B5	CAPACITOR, fixed: 2/8/32 NT-48121 w/1,500 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-31510-3471				CRV	UC-2365			
-48122	CAPACITOR, fixed: 2/8/32 mica; 3,000 mmf; 15,000 vdcw, 22 amp at 3,000 kc, 25 amp at 1,000 kc, 16 amp at 300 kc, 9 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48122-B5	CAPACITOR, fixed: 2/8/32 NT-48122 w/3,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-32196-4772	N16-C-10341			CRV CD C N	UC-2374 PL-204-91B	CG	M-7463524-2	TAQ-5(4) TAQ-6(4) TAQ-10(4)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-42

RESTRICTED

RESTRICTED

SHEET 48 - 43

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48123	CAPACITOR, fixed: 2/8/32 mica; 2,500 mmf; 12,000 vdcw, 20 amp at 3,000 kc, 20 amp at 1,000 kc, 14 amp at 300 kc, 8 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48123-B5	CAPACITOR, fixed: 2/8/32 NT-48123 w/2,500 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-32011-5071	N16-C-10320			CRV CB	UC-2369 PL-212-518	CG	M-7463524-1	TAQ-5 TAQ-6 TAQ-10
-48124	CAPACITOR, fixed: 2/8/32 mica; 500 mmf; 20,000 vdcw, 8 amp at 300 kc; case 5 3/4" h x 5" diam; low loss ceramic case; two elliptical cast aluminum end cap term, ea w/ two 0.377" diam holes 5 3/4" c to c.	RE48A237 16C40										
-48124-B5	CAPACITOR, fixed: 2/8/32 NT-48124 w/500 mmf p/m 5%; temp coef ltr B.	RE48A237 16C40		16-C-30165-5950				CRV	UC-2699			
-48125	CAPACITOR, fixed: 2/8/32 mica; 1,000 mmf; 20,000 vdcw, 18 amp at 3,000 kc, 17 amp at 1,000 kc, 10 amp at 300 kc, 4.5 amp at 100 kc; case 5 3/4" x 5" diam; low loss ceramic case; two elliptical cast aluminum end cap term, ea w/two 0.377" diam holes 5 3/4" c to c.	RE48A237 16C40										
-48125-B5	CAPACITOR, fixed: 2/8/32 NT-48125 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A237 16C40		16-C-31088-7336				CRV	UC-3075			
-48126	CAPACITOR, fixed: 2/8/32 mica; 1,600 mmf; 15,000 vdcw max, 19 amp at 3,000 kc, 18 amp at 1,000 kc, 12 amp at 300 kc, 5 amp at 100 kc; case 5" diam x 4" h; ceramic case; one case aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48126-B5	CAPACITOR, fixed: 2/8/32 NT-48126 w/1,600 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-31616-1905				CRV	UC-2392			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-43

RESTRICTED

RESTRICTED

SHEET 48 - 44

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48127	CAPACITOR, fixed: 2/8/32 mica; 500 mmf; 20,000 vdcw max, 12 amp at 3,000 kc, 9 amp at 1,000 kc, 6 amp at 300 kc, 3 amp at 100 kc; case 5" diam x 4" h; ceramic case; one cast aluminum elliptical term 6 1/2" lg x 5" wd on top and one on bottom, ea term has one 3/8" diam hole ea end, holes 5 3/4" c to c.	RE48A116 16C40										
-48127-B5	CAPACITOR, fixed: 2/8/32 NT-48127 w/500 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-30165-5875	N16-C-10024-98			CRV	UC-2344	CRV	DL-500455-502	TBL TBL-1
-48127-B10	CAPACITOR, fixed: 2/8/32 NT-48127 w/500 mmf p/m 10%; temp coef ltr B.	RE48A116 16C40		16-C-30170-7215	N16-C-16024-100 N16-C-10014-100			CRV	UC-2344			
-48128	CAPACITOR, fixed: 2/8/32 mica; 350 mmf; 20,000 vdcw, 11 amp at 3,000 kc, 7 amp at 1,000 ka, 4 amp at 300 kc, 2 amp at 100 kc; case 5" diam x 4" h; ceramic case; one fl elliptical end term at ea end, two 3/8" diam holes in ea term 5 3/4" c to c.	RE48A116 16C40										
-48128-B5	CAPACITOR, fixed: 2/8/32 NT-48128 w/350 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-29796-2707				CRV	UC-2523K			
-48129	CAPACITOR, fixed: 2/8/32 mica; 250 mmf; 20,000 vdcw, 9 amp at 3,000 kc, 4 amp at 1,000 kc, 2 amp at 300 kc, 0.7 amp at 100 kc; case 5" diam x 4" h; ceramic case; one fl elliptical end term at ea end, two 3/8" diam holes in ea term 5 3/4" c to c.	RE48A116 16C40										
-48129-B5	CAPACITOR, fixed: 2/8/32 NT-48129 w/250 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-29479-6870				CRV	UC-2461			
-48130	CAPACITOR, fixed: 2/8/32 paper dielectric; 500,000 mmf plus 10 minus 3%; 1800 vdcw; IS metal can; 4 27/32" lg x 3" h x 2 1/16" wd; oil impr and filled; two stud and nut term 1" c to c on side; no int end connections; integral mtg bkt w/two 1/4" diam holes 5 11/16" c to c; superseded by NT-48130-A.	RE48A117		16-C-47282-9600	N16-C-11365			CG	DL-2927771			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-44

RESTRICTED

RESTRICTED

SHEET 48 - 45

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48130-A	CAPACITOR, fixed: 4/27/37 paper dielectric; 500,000 mfd plus 10 minus 3%; 1800 vdcw; HS metal can; 4 27/32" lg x 3" h x 2 1/16" wd; oil impr and filled; two screw type term #10-32 thd x 9/16" h located on side; no int gnd connections; mtg bkt 6 3/8" lg x 5/8" wd w/ two mtg holes 1/4" diam x 5 11/16" c to c; same as NT-48130 except it complies with REL3A488.	RE48A117 REL3A488		16-C-47282-9610	N16-C-11365			CC	DL-2927771			
-48131	CAPACITOR, fixed: 2/8/32 paper dielectric; 1 mfd plus 10 minus 3%; 1,200 vdcw; HS metal can; 4 27/32" lg x 3 1/32" h x 2 3/32" wd; oil impr and filled; two stud and nut term 1" c to c on side; no int gnd connections; integral mtg bkt w/ two 1/4" diam holes 5 11/16" c to c; superseded by NT-48131-A.	RE48A117		16-C-48801-3190				CRV	UC-2209E			
-48131-A	CAPACITOR, fixed: 4/27/37 paper dielectric; 1 mfd plus 10 minus 3%; 1,200 vdcw; HS metal can; 4 27/32" lg x 3 1/32" h x 2 3/32" wd; oil impr and filled; two screw type term #10-32 thd x 9/16" h located on side; no int gnd connections; mtg bkt 6 3/8" lg x 5/8" wd w/ two mtg holes 1/4" diam x 5 11/16" c to c; same as NT-48131 except it complies with REL3A488.	RE48A117 REL3A488		16-C-48801-3190								
-48131-A10	CAPACITOR, fixed: 4/27/37 NT-48131-A w/ 1 mfd p/m 10%; same as NT-48131 except it complies with REL3 488.	RE48A117 REL3A488		16-C-48822-2470	N16-C-11430			CRV	UC-2209E			
-48132	CAPACITOR, fixed: 2/8/32 paper dielectric; 700,000 mfd plus 10 minus 3%; 1500 vdcw; HS metal can; 4 27/32" lg x 3" h x 2 1/16" wd; oil impr and filled; two screw type term #10-32 thd x 9/16" h located on side; no int gnd connections; integral mtg bkt w/ two 1/4" diam holes 5 11/16" c to c; superseded by NT-48132-A.	RE48A117		16-C-48042-1421								

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-45

RESTRICTED

RESTRICTED

SHEET 46 - 46

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48132-A	CAPACITOR, fixed; 4/27/37 paper dielectric; 700,000 mfd plus 10 minus 3%; 1500 vdcw; BS metal can; 4 27/32" lg x 2 1/16" wd x 3" h; oil impr and filled; two screw type term #10-32 thd x 9/16" h located on side; no int gnd connections; mtg hkt 6 3/8" lg x 5/8" wd w/two mtg holes 1/4" diam 5 11/16" c to c; same as NT-48132 except it complies w/REL34488.	RE48A117 REL34488		16-C-48042-1421				CRV	64965-502	CRV	64965-502	TBL (2) TBL-1 (2)
-48133	CAPACITOR, fixed; 2/8/32 paper dielectric; one mfd plus 10 minus 3%; 600 vdcw; BS metal can; 4 27/32" lg x 2 9/32" h x 1 17/32" wd; oil impr and filled; two screw type term #10-32 thd x 9/16" h located on side; no int gnd connections; integral mtg hkt w/two 1/4" diam holes 5 11/16" c to c; superseded by NT-48133-A.	RE48A117		16-C-48797-6974	N16-C-11420			CRV	UC-2210A			
-48133-A	CAPACITOR, fixed; 4/27/37 paper dielectric; one mfd plus 10 minus 3%; 600 vdcw; BS metal can; 4 27/32" lg x 2 9/32" h x 1 17/32" wd; oil impr and filled; two screw type term #10-32 thd x 9/16" h located on side; no int gnd connections; mtg hkt 6 3/8" lg x 5/8" wd w/two mtg holes 1/4" diam x 5 11/16" c to c; same as NT-48133 except it complies w/REL34488.	RE48A117 REL34488		16-C-48797-6974				CRV	UC-2210A			
-48134	CAPACITOR, fixed; 2/8/32 paper dielectric; 1 mfd plus 10 minus 3%; 600 vdcw; BS metal can; 4 1/2" h x 1 7/16" wd x 1 3/4" thk; oil impr and filled; two stud term 1/2" h located on top, spaced 1" c to c; no int gnd connections; superseded by NT-48134-A.	RE48A110		16-C-48796-2952				CRV	UC-488A	CBM	744-615	QGA (2)
-48134-A	CAPACITOR, fixed; 9/8/36 paper dielectric; 1 mfd plus 10 minus 3%; 600 vdcw; BS metal can; 4 1/2" h x 1 3/4" wd x 1 7/16" d o/a; two stud term 1/2" h located on top, spaced 1" c to c; no int gnd connections; same as NT-48134 except complies with REL34488.	RE48A110 REL34488		16-C-48796-2952				CRV	UC-488A	CBM	744-615	
-48134-A10	CAPACITOR, fixed; 9/8/36 NT-48134-A w/1 mfd p/m 10%.	RE48A110 REL34488		16-C-48817-2872	N16-C-11410							

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 46-46

RESTRICTED

RESTRICTED

SHEET 48 - 47

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTORS DWG OR PART NO	EQUIPMENT USED IN
-48135	CAPACITOR, fixed: 2/8/32 paper dielectric; 500,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; 4 1/2" h x 1 3/4" wd x 1" thk; oil impr and filled; two stud and nut term 1" c to c on top; no int gnd connections; superseded by NT-48135-A	RE48A110		16-C-47276-2867				CRV	UC-487A			
-48135-A	CAPACITOR, fixed: 9/8/36 paper dielectric; 500,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; 4 1/2" h x 1 3/4" wd x 1" d; two stud term 1/2" h located on top, spaced 1" c to c; no int gnd connections; same as NT-48135 except complies w/REL3A488.	RE48A110 REL3A488		16-C-47276-2867	N16-C-11353-1							
-48135-A10	CAPACITOR, fixed: 9/8/36 NT-48135-A w/500,000 mmf p/m 10%.	RE48A110 REL3A488		16C-47297-2877	N16-C-11351-6			CRV	UC-487A			
-48136	CAPACITOR, fixed: 2/8/32 paper dielectric; two sect; 200,000 mmf/200,000 mmf plus 10 minus 3%; 150/150 vdcw; HS metal can; 2 5/16" lg x 2 1/16" wd x 13/16" thk; oil impr and filled; three ins stud and nut term ea 1/2" c to c on end; one side of ea sect is common but no int gnd connections; two mtg ft ea w/a 0.154" diam hole whose ctr are in diagonal corners of rectangle 2 11/32" x 1"; superseded by NT-48136-A.	RE48A119		16-C-53234-9143								
-48136-A	CAPACITOR, fixed: 3/29/37 paper dielectric; two sect; 200,000 mmf plus 10 minus 3% ea sect; 400 vdcw ea sect; HS metal can; 2 5/16" lg x 2 1/16" wd x 13/16" thk; oil filled; three screw type term 3/8" h on end spaced 1/2" c to c; no int gnd connections; two mtg ft 1/2" lg x 11/32" wd x 1/32" thk, ea w/one 0.154" diam hole in diagonal corners of rectangle 2 11/32" x 1"; same as NT-48136 except complies w/Navv Spec REL3A488.	REL3A488 RE48A119		16-C-53235-6650								

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-47

RESTRICTED

RESTRICTED

SHEET 48 - 48

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48137	CAPACITOR, fixed: 2/8/32 paper dielectric; two sect; 500,000/500,000 mmf plus 10 minus 3%; 150/150 vdcw; ES metal can; 2 5/16" lg x 2 1/16" wd x 13/16" thk; oil impr and filled; three ins stud and nut term ea 1/2" c to c on end 3/8" h; one side of ea sect is common; but no int gnd connection; two mtg ft ea w/one 0.154" diam hole in diagonal corners of rectangle 2 11/32" x 1"; superseded by NT-48137-A.	RE18A119		16-C-53559-5704								
-48137-A	CAPACITOR, fixed: 3/29/37 paper dielectric; two sect; 500,000 mmf plus 10 minus 3% ea sect; 400 vdcw ea sect; ES metal can; 2 5/16" lg x 2 1/16" wd x 13/16" thk; oil filled; three screw type term 3/8" h on end spaced 1/2" c to c; no int gnd connections; two mtg ft 1/2" lg x 11/32" wd x 1/32" thk ea w/one 0.154" diam hole in diagonal corners of rectangle 2 11/32" x 1"; same as NT-48137 except complies w/Navy Spec RE13A488.	RE13A488 RE48A119		16-C-53570-4400								
-48137-A15	CAPACITOR, fixed: 3/29/37 NT-48137-A w/500,000 mmf p/m 15% ea sect.	RE48A119 RE13A488		16-C-53676-4947	N16-C-11376							
-48138	CAPACITOR, fixed: 2/8/32 paper dielectric; 1 mfd plus 10 minus 3%; 150 vdcw; ES metal can; 2 5/16" lg x 2 1/16" wd x 13/16" thk; oil impr and filled; two ins stud and nut term 1" c to c on side; no int gnd connections; two mtg ft ea w/one 0.154" diam hole in diagonal corners of rectangle 2 11/32" x 1"; superseded by NT-48138-A.	RE48A119		16-C-48788-5978								
-48138-2	CAPACITOR, FIXED: 2/6/50 Navy Type 48138 w/1 mfd p/m 20%.			16-C-48842-9710								
-48138-A	CAPACITOR, fixed: 3/29/37 paper dielectric; 1 mf plus 10 minus 3%; 400 vdcw; ES metal can; 2 5/16" lg x 2 1/16" wd x 13/16" thk; oil filled; two screw type term 3/8" h on side spaced 1" c to c; no int gnd connections; two mtg feet 1/2" lg x 11/32" wd x 1/32" thk ea w/one 0.154" diam hole in diagonal corners of rectangle 2 11/32" x 1"; same as NT-48138 except complies w/Navy spec RE13A488.	RE13A488 RE48A119		16-C-48793-2421	N16-C-11385							

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-48

RESTRICTED

RESTRICTED

SHEET 48 - 49

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48139	CAPACITOR, fixed: 2/8/32 mica; 4,000 mmf; 9,000 vdcw, 8 amp at 3000 kc, 11 amp at 1000 kc, 7.5 amp at 300 kc, 4.0 amp at 100 kc; case 3 5/8" lg x 3 3/8" wd x 5 11/16" h; cast metal case; one screw term 11/16" h on top; mtg plates on ea side located 1 1/2" from bottom, make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate 6" c to c.	RE48A120 16C40										
-48139-B5	CAPACITOR, fixed: 2/8/32 NT-48139 w/4,000 mmf p/m 5%; temp coef 1tr B.	RE48A120 16C40		16-C-32458-9263			206726B/1	CRV	UC-1837			
-48139-B20	CAPACITOR, fixed: 2/8/32 NT-48139 w/4,000 mmf p/m 20%; temp coef 1tr B.	RE48A120 16C40		16-C-32469-2923	N16-C-10395-14		206726B/5	CRV	UC-1837			
-48140	CAPACITOR, fixed: 2/8/32 mica; 6,000 mmf; 9,000 vdcw, 15 amp at 3,000 kc, 17 amp at 1,000 kc, 11 amp at 300 kc, 6 amp at 100 kc; case 3 5/8" lg x 3 3/8" wd x 5 11/16" h; cast metal case; one screw term 11/16" h on top; mtg plates on ea side located 1 1/2" from bottom make lg of capacitor 7", one mtg hole 11/32" diam in ea plate on 6" mtg/c.	RE48A120 16C40										
-48140-B4	CAPACITOR, fixed: 2/8/32 NT-48140 w/6,000 mmf p/m 4%; temp coef 1tr B.	RE48A120 16C40		16-C-32351-9992				CRV	UC-2570			
-48140-B5	CAPACITOR, fixed: 2/8/32 NT-48140 w/6,000 mmf p/m 5%; temp coef 1tr B.	RE48A120 16C40		16-C-32854-6963				CRV	UC-2570			
-48140-B10	CAPACITOR, fixed: 2/8/32 NT-48140 w/6,000 mmf p/m 10%; temp coef 1tr B.	RE48A120 16C40		16-C-32859-7443	N16-C-10450			CRV	UC-2570			
-48141	CAPACITOR, fixed: 2/8/32 mica; 3,000 mmf; 5,000 vdcw, 13 amp at 3,000 kc, 15 amp at 1,000 kc, 10 amp at 300 kc, 5 amp at 100 kc; case 3 5/8" lg x 3 3/8" wd x 5 11/16" h; cast metal case; one screw term 11/16" h on top; mtg plates on ea side located 1 1/2" from bottom make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate 6" c to c.	RE48A120 16C40										
-48141-B5	CAPACITOR, fixed: 2/8/32 NT-48141 w/3,000 mmf p/m 5%; temp coef 1tr B.	RE48A120 16C40		16-C-32195-2963	N16-C-10330	N16-C-10336		CRV	UC-2520			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48 - 9

RESTRICTED

RESTRICTED

SHEET 48 - 50

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL COR S STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48142	CAPACITOR, fixed: 2/8/32 mica; 1,700 mmf; 5,000 vdcw, 7 amp at 300 kc, 9 amp at 100 kc, 6 amp at 300 kc, 3.5 amp at 100 kc; case 3 5/8" lg x 3 3/8" wd x 5 11/16" h; cast metal case; one screw term 11/16" h on top; mtg plates on ea side located 1 1/2" from bottom, make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate on 6" mtg/c.	RE48A120 16C40										
-48142-B5	CAPACITOR, fixed: 2/8/32 NT-48142 w/1,700 mmf p/m 5%; temp coef ltr B.	RE48A120 16C40		16-C-31631-3923	N16-C-10220			CRV	UC-2571			
-48143	CAPACITOR, fixed: 2/8/32 mica; 1,200 mmf; 5,000 vdcw, 6 amp at 3,000 kc, 8 amp at 1,000 kc, 5.5 amp at 300 kc, 3.0 amp at 100 kc; case 3 5/8" lg x 3 3/8" wd x 5 11/16" h; cast metal case; one screw term 11/16" h on top; mtg plates on ea side located 1 1/2" from bottom make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate on 6" mtg/c.	RE48A120 16C40										
-48143-B5	CAPACITOR, fixed: 2/8/32 NT-48143 w/1,200 mmf p/m 5%; temp coef ltr B.	RE48A120 16C40		16-C-31271-9963	N16-C-10170			CRV	UC-2572			
-48144	CAPACITOR, fixed: 2/8/32 mica; 800 mmf; 5,000 vdcw, 5 amp at 3000 kc, 6 amp at 1000 kc; 3 amp at 300 kc, 1 amp at 100 kc; case 3 5/8" lg x 3 3/8" wd x 5 11/16" h; cast metal case; one screw term 11/16" h on top; mtg plates on ea side located 1 1/2" from bottom, make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate on 6" mtg/c.	RE48A120 16C40										
-48144-B4	CAPACITOR, fixed: 2/8/32 NT-48144 w/800 mmf p/m 4%; temp coef ltr B.	RE48A120 16C40		16-C-30688-9023	N16-C-10074-17			CRV	UC-2573			
-48144-B5	CAPACITOR, fixed: 2/8/32 NT-48144 w/800 mmf p/m 5%; temp coef ltr B.	RE48A120 16C40		16-C-30691-7163	N16-C-10074-14			CRV	UC-2573			
-48144-B10	CAPACITOR, fixed: 2/8/32 NT-48144 w/800 mmf p/m 10%; temp coef ltr B.	RE48A120 16C40		16-C-30696-7643	N16-C-10074-15			CRV	UC-2573			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-50

RESTRICTED

RESTRICTED

SHEET 48 - 51

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48145	CAPACITOR, fixed: 2/8/32 mica; 6,000 mmf; 15000 vdcw, 20 amp at 1000 kc, 14 amp at 300 kc, 8 amp at 100 kc; case 3 3/4" lg x 3 5/8" wd x 7 3/8" h; cast metal case; one screw term 5/8" lg on top; mtg plates on ea side 7/16" thk located 1 25/32" from bottom make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate on 6" mtg/c.	RE48A121 16C40										
-48145-B4	CAPACITOR, fixed: 2/8/32 NT-48145 w/6,000 mmf p/m 4%; temp coef ltr B.	RE48A121 16C40		16-C-32851-9992				CRV	UC-2566			
-48145-B5	CAPACITOR, fixed: 2/8/32 NT-48145 w/6,000 mmf p/m 5%; temp coef ltr B.	RE48A121 16C40		16-C-32855-8666				CRV	UC-2566			
-48146	CAPACITOR, fixed: 2/8/32 mica; 1,600 mmf; 15,000 vdcw, 11 amp at 3,000 kc, 13 amp at 1,000 kc, 9 amp at 300 kc, 4 amp at 100 kc; case 3 3/4" lg x 3 3/8" wd x 7 3/8" h; cast metal case; one screw term 5/8" h on top; mtg plates on ea side 7/16" thk located 1 25/32" from bottom make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate 6" c to c.	RE48A121 16C40										
-48146-B5	CAPACITOR, fixed: 2/8/32 NT-48146 w/1600 mmf p/m 5%; temp coef ltr B.	RE48A121 16C40		16-C-31616-1867				CRV	UC-2568			
-48147	CAPACITOR, fixed: 2/8/32 mica; 3,000 mmf; 15,000 vdcw, 17 amp at 3,000 kc, 20 amp at 1,000 kc, 13 amp at 300 kc, 6 amp at 100 kc; 3 3/4" lg x 3 5/8" wd x 7 3/8" h; cast metal case; one screw term 5/8" h on top; mtg plates on ea side 7/16" thk located 1 25/32" from bottom make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate on 6" mtg/c.	RE48A121 16C40										
-48147-B4	CAPACITOR, fixed: 2/8/32 NR-48147 w/3,000 mmf p/m 4%; temp coef ltr B.	RE48A121 16C40		16-C-32192-5157				CRV	UC-2567			
-48147-B5	CAPACITOR, fixed: 2/8/32 NT-48147 w/3,000 mmf p/m 5%; temp coef ltr B.	RE48A121 16C40		16-C-32196-4667	16-C-10341-40			CRV	UC-2567			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-51

RESTRICTED

RESTRICTED

SHEET 48 - 52

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48148	CAPACITOR, fixed: 2/8/32 mica; 1,000 mmf; 15,000 vdcw, 10 amp at 3,000 kc, 12 amp at 1,000 kc, 8 amp at 300 kc, 4.5 amp at 100 kc; case 3 3/4" lg x 3 5/8" wd x 7 3/8" h; cast metal case; one screw term 5/8" h on top; mtg plates on ea side 7/16" thk located 1 25/32" from bottom make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate on 6" mtg/c.	RE48A121 16C40										
-48148-B5	CAPACITOR, fixed: 2/8/32 NT-48148 w/1000 mmf p/m 5%; temp coef ltr B.	RE48A121 16C40		16-C-31098-5865	N16-C-10099-24			CRV	UC-2498			
-48149	CAPACITOR, fixed: 2/8/32 mica; 750 mmf; 15,000 vdcw, 8 amp at 3,000 kc, 9 amp at 1,000 kc, 6 amp at 300 kc, 2 amp at 100 kc; case 3 3/4" lg x 3 5/8" wd x 7 3/8" h; cast metal case; one screw term 5/8" h on top; mtg plates on ea side 7/16" thk located 1 25/32" from bottom make o/a lg of capacitor 7", one mtg hole 11/32" diam in ea plate c to c.	RE48A121 16C40										
-48149-A	CAPACITOR, fixed: 2/8/32 NT-48149 w/750 mmf p/m 4%; temp coef ltr B.	RE48A121 16C40		16-C-30662-5623				CRV	UC-2569			
-48149-B5	RESISTOR, fixed: 2/8/32 NT-48149 w/750 mmf p/m 5%; temp coef ltr B.	RE48A121 16C40		16-C-30666-5463				CRV	UC-2569			
-48150	CAPACITOR, fixed: 2/8/32 mica; 150 mmf; 10,000 vdcw, 5.0 amp at 3,000 kc, 3.8 amp at 1,000 kc, 2.5 amp at 300 kc, 1.3 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; two flanged elliptical end term w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48150-B5	CAPACITOR, fixed: 2/8/32 NT-48150 w/150 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-28977-8870				CRV	UC-2602			
-48151	CAPACITOR, fixed: 2/8/32 mica; 350 mmf; 10,000 vdcw, 8.0 amp at 3,000 kc, 5.0 amp at 1,000 kc, 2.0 amp at 300 kc, 0.6 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end cap term ea end, two 9/32" diam mtg holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48151-B5	CAPACITOR, fixed: 2/8/32 NT-48151 w/350 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-29795-6271				CRV	UC-2603			

SHEET 48-52

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 53

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48152	CAPACITOR, fixed: 2/8/32 mica; 650 mmf; 10,000 vdcw. 10 amp at 3,000 kc, 6.0 amp at 1,000 kc, 3.5 amp at 300 kc, 1.3 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/one 17/64" diam hole in ea end of term 4 1/4" c to c.	RE48A122 16040										
-48152-B5	CAPACITOR, fixed: 2/8/32 NT-48152 w/650 mmf p/m 5%; temp coef ltr B.	RE48A122 16040		16-C-30481-4662	N16-C-10061-75			CRV	UC-2604			
-48153	CAPACITOR, fixed: 2/8/32 mica; 500 mmf; 10,000 vdcw, 9 amp at 3,000 kc, 6 amp at 1,000 kc, 3 amp at 300 kc, 1 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term on ea end w/one 17/64" diam hole in ea end of term 4 1/4" c to c.	RE48A122 16040										
-48153-B5	CAPACITOR, fixed: 2/8/32 NT-48153 w/500 mmf p/m 5%; temp coef ltr B.	RE48A122 16040		16-C-30164-8871				CRV	UC-2617			
-48153-B10	CAPACITOR, fixed: 2/8/32 NT-48153 w/500 mmf p/m 10%; temp coef ltr B.	RE48A122 16040		16-C-30169-9351	N16-C-10024-54			CRV	UC-2617			
-48154	CAPACITOR, fixed: 2/8/32 mica; 940 mmf; 6,000 vdcw, 9.0 amp at 3,000 kc, 6.0 amp at 1,000 kc, 4.2 amp at 300 kc, 2.4 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term on ea end w/one 17/64" diam hole in ea end of term 4 1/4" c to c.	RE48A122 16040										
-48154-B5	CAPACITOR, fixed: 2/8/32 NT-48154 w/940 mmf p/m 5%; temp coef ltr B.	RE48A122 16040		16-C-31008-3952				CRV	UC-2582			
-48155	CAPACITOR, fixed: 2/8/32 mica; 250 mmf; 10,000 vdcw, 6 amp at 3,000 kc, 3 amp at 1,000 kc, 2 amp at 300 kc, 1 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term on ea end w/ 9/32" diam mtg hole in ea end term 4 1/4" c to c.	RE48A122 16040										
-48155-B5	CAPACITOR, fixed: 2/8/32 NT-48155 w/250 mmf p/m 5%; temp coef ltr B.	RE48A122 16040		16-C-29479-1471				CRV	UC-2581			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-53

RESTRICTED

RESTRICTED

SHEET 48 - 54

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48156	CAPACITOR, fixed: mica; 4,000 mmf; 6,000 vdcw, 14.0 amp at 3,000 kc, 17.0 amp at 1,000 kc, 11.5 amp at 300 kc, 6.5 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term on ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	2/8/32 RE48A122 16C40										
-48156-B5	CAPACITOR, fixed: NT-48156 w/4,000 mmf p/m 5%; temp coef ltr B.	2/8/32 RE48A122 16C40		16-C-32459-2076	N16-C-10388			CRV	UC-2579	CRV	M-402386-5	TAJ-4 (2)
-48157	CAPACITOR, fixed: mica; 1200 mmf; 5,000 vdcw, 13.0 amp at 3,000 kc, 8.0 amp at 1,000 kc, 5.5 amp at 300 kc, 3.0 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	2/8/32 RE48A122 16C40										
-48157-B5	CAPACITOR, fixed: NT-48157 w/1,200 mmf p/m 5%; temp coef ltr B.	2/8/32 RE48A122 16C40		16-C-31271-9715	N16-C-10171-7			CRV	UC-2577			
-48158	CAPACITOR, fixed: mica; 4,500 mmf; 5,000 vdcw, 16.0 amp at 3,000 kc, 17.0 amp at 1,000 kc, 11.5 amp at 300 kc, 6.0 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	2/8/32 RE48A122 16C40										
-48158-B5	CAPACITOR, fixed: NT-48158 w/4,500 mmf p/m 5%; temp coef ltr B.	2/8/32 RE48A122 16C40		16-C-32617-3189				CRV	UC-2583			
-48159	CAPACITOR, fixed: mica; 10,000 mmf; 3,000 vdcw, 20.0 amp at 3,000 kc, 22.0 amp at 1,000 kc, 15.0 amp at 300 kc, 8.5 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	2/8/32 RE48A122 16C40										
-48159-B5	CAPACITOR, fixed: NT-48159 w/10,000 mmf p/m 5%; temp coef ltr B.	2/8/32 RE48A122 16C40		16-C-33618-9687				CRV	UC-2580			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-54

RESTRICTED

RESTRICTED

SHEET 48 - 55

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E B O STOCK NO	A B O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48160	CAPACITOR, fixed: 2/8/32 mica; 15,000 mmf; 2,000 vdcv, 20.0 amp at 3,000 kc, 17.0 amp at 1,000 kc, 11.5 amp at 300 kc, 6.5 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48160-B5	CAPACITOR, fixed: 2/8/32 NT-48160 w/15,000 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-34040-7452				CRV	UC-2578	CRV	T-602220-15 M-402386-3	TAJ-4(2)
-48161	CAPACITOR, fixed: 2/8/32 mica; 20,000 mmf; 1,500 vdcv, 20 amp at 3,000 kc, 10 amp at 1,000 kc, 7 amp at 300 kc, 4 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two axial wire leads 5" lg; two mtg ft both on same side at bottom, ea w/ one 0.173" diam hole on 1 1/4" mtg/c.	RE48A225 16C40										
-48161-B5	CAPACITOR, fixed: 2/8/32 NT-48161 w/20,000 mmf p/m 5%; temp coef ltr B.	RE48A225 16C40		16-C-34330-7140	N16-C-10555-24		3DA20-1	CRV	UC-2311			
-48162	CAPACITOR, fixed: 2/8/32 mica; 1,000 mmf; 3,000 vdcv, 2.5 amp at 3,000 kc, 1.3 amp at 1,000 kc, 0.9 amp at 300 kc, 0.3 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two axial wire leads 5" lg; two mtg ft both on same side at bottom, ea w/ one 0.173" diam hole on 1 1/4" mtg/c.	RE48A225 16C40										
-48162-B5	CAPACITOR, fixed: 2/8/32 NT-48162 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A225 16C40		16-C-31086-7161				CRV	UC-1870			
-48163	CAPACITOR, fixed: 2/8/32 mica; 4,000 mmf; 3,000 vdcv, 6.5 amp at 3000 kc, 4.0 amp at 1,000 kc, 2.6 amp at 300 kc, 1.4 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two axial wire leads 5" lg; two mtg ft both on same side at bottom, ea w/one 0.173" diam hole on 1 1/4" mtg/c.	RE48A225 16C40										
-48163-B5	CAPACITOR, fixed: 2/8/32 NT-48163 w/4,000 mmf p/m 5%; temp coef ltr B.	RE48A225 16C40		16-C-32458-3962	N16-C-10380			CRV	UC-2309			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-55

RESTRICTED

RESTRICTED

SHEET 48 - 56

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48164	CAPACITOR, fixed: 2/8/32 mica; 100,000 mmf; 500 vdcw, 20 amp at 3,000 kc, 20 amp at 1,000 kc, 13 amp at 300 kc, 7 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two axial wire leads 5" lg; two mtg ft both on same side at bottom, ea w/one 0.173" diam hole on 1 1/4" mtg/c.	RE48A225 16C40										
-48164-B5	CAPACITOR, fixed: 2/8/32 NT-48164 w/100,000 mmf p/m 5%; temp coef ltr B.	RE48A225 16C40		16-C-36149-9258	N16-0-10633			CRV	UC-2422			
-48165	CAPACITOR, fixed: 2/8/32 mica; 15,000 mmf; 1,500 vdcw, 12 amp at 3,000 kc, 10 amp at 1,000 kc, 7 amp at 300 kc, 4 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two axial wire leads 5" lg; two mtg ft both on same side at bottom, ea w/one 0.173" diam hole on 1 1/4" mtg/c.	RE48A225 16C40										
-48165-B5	CAPACITOR, fixed: 2/8/32 NT-48165 w/15,000 mmf p/m 5%; temp coef ltr B.	RE48A225 16C40		16-C-34040-5740				CRV	UC-2214K			
-48166	CAPACITOR, fixed: 2/8/32 mica; 2,000 mmf; 3,000 vdcw, 5 amp at 3,000 kc, 2.0 amp at 1,000 kc, 1.3 amp at 300 kc, 0.7 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two axial wire leads 5" lg; two mtg ft both on same side at bottom, ea w/one 0.173" diam hole on 1 1/4" mtg/c.	RE48A225 16C40										
-48166-B5	CAPACITOR, fixed: 2/8/32 NT-48166 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A225 16C40		16-C-31798-8961				CRV	UC-1014			
-48167	CAPACITOR, fixed: 2/8/32 mica; 500 mmf; 5,000 vdcw, 4 amp at 3000 kc, 2 amp at 1000 kc, 1.30 amp at 300 kc, 0.75 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two axial wire leads 5" lg; two mtg ft both on same side at bottom, ea w/one 0.173" diam hole 1 1/4" c to c.	RE48A225 16C40										
-48167-B5	CAPACITOR, fixed: 2/8/32 NT-48167 w/ 500 mmf p/m 5%; temp coef ltr B.	RE48A225 16C40		16-C-30164-1749				CRV	UC-2230			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-56

RESTRICTED

RESTRICTED

SHEET 48 - 57

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48168	CAPACITOR, fixed: mica; 20,000 mmf; 4,000 vdcw, 15 amp cur at 4,000 to 20,000 kc; case 3" lg x 2 7/16" wd x 2 7/8" h; cast metal case; two screw term 1" h on top spaced 1 7/16" c to c connected to one side of capacitor, other side gnd to case; three mtg ft on bottom ea w/ 17/64" diam hole, two on one side spaced 1 5/8" c to c and 3" from ctr of mtg hole on other side.	2/8/32 RE48A124 16C40										
-48168-B5	CAPACITOR, fixed: NT-48168 w/20,000 mmf p/m 5%; temp coef ltr B.	2/8/32 RE48A124 16C40		16-C-34331-6533	N16-C-10566-54		3DA20-2	CRV	UC-2534			
-48169	CAPACITOR, fixed: mica; 100,000 mmf; 2,000 vdcw, 20 amp at 4,000 kc to 20,000 kc; case 3" lg x 2 7/16" wd x 2 7/8" h; cast metal case; two screw term 1" h on top spaced 1 7/16" c to c connected to one side of capacitor, other side gnd to case; three mtg ft on bottom ea w/ 17/64" diam hole, two on one side spaced 1 5/8" c to c and 3 9/16" from ctr of mtg hole on other side.	2/8/32 RE48A124 16C40										
-48169-B5	CAPACITOR, fixed: NT-48169 w/100,000 mmf p/m 5%; temp coef ltr B.	2/8/32 RE48A124 16C40		16-C-36151-1354	N16-C-10702-65		3DA100-1	CRV	UC-2533			
-48170	CAPACITOR, fixed: mica; 100,000/ 100,000 mmf; 250 vdcw, 18 amp at 3,000 kc, 20 amp at 1,000 kc, 15 amp at 300 kc, 10 amp at 100 kc; case 2 3/16" lg x 2" wd x 1 19/32" h; cast metal case; two screw term 21/32" lg on side spaced 1" c to c, one side of ea sect int gnd; two mtg fl on sides ea w/two 0.196" diam holes on 1 1/4" x 2 13/16" mtg/c.	2/8/32 RE48A125 16C40										
-48170-B5	CAPACITOR, fixed: NT-48170 w/100,000/ 100,000 mmf p/m 5%; temp coef ltr B.	2/8/32 RE48A125 16C40			N16-C-10702-100		3DA100-3	CRV	UC-1839			
-48170-B10	CAPACITOR, fixed: NT-48170 w/100,000/ 100,000 mmf p/m 10%; temp coef ltr B.	2/8/32 RE48A125 16C40						CD	109-21	CAY	T-7606683-11	TAB-5(2) TAB-6(2) TAB-7

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-57

RESTRICTED

RESTRICTED

SHEET 48 - 58

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48171	CAPACITOR, fixed: 2/8/32 mica; 150 mmf; 4,000 vdcw, 5 amp at 4,000 kc; case 2 1/2" lg x 2 1/2" wd x 1 9/16" h; sheet metal case; one tab term 1" lg at ea end w/ one 0.196" diam hole 4" c to c; two mtg ft on bottom ea w/ two 0.201" diam holes on 2" x 3" mtg/c.	RE48A253 16C40										
-48171-B5	CAPACITOR, fixed: 2/8/32 NT-48171 w/150 mmf p/m 5%; temp coef ltr B.	RE48A253 16C40		16-C-28976-9280				CRV	UC-2806 Case 309	CRV	E-35796	GI
-48172	CAPACITOR, fixed: 2/8/32 mica; 400 mmf; 10,000 vdcw, 9.0 amps at 3,000 kc, 6.5 amps at 1,000 kc, 3.5 amps at 300 kc, 1.2 amps at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48172-B5	CAPACITOR, fixed: 2/8/32 NT-48172 w/400 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-29927-5271				CRV	UC-3150			
-48173	CAPACITOR, fixed: 2/8/32 mica; 2,000 mmf; 6,000 vdcw, 5 amps at 300 kc; case 2 1/2" lg x 2 1/2" wd x 1 9/16" h; metal case; two screw term 3/4" lg, #10-32 thd, one on front, one on back; two mtg fl on sides ea w/two 0.173" diam holes on 3" x 2" mtg/c.	RE48A254 16C40										
-48173-B5	CAPACITOR, fixed: 2/8/32 NT-48173 w/2000 mmf p/m 5%; temp coef ltr B.	RE48A254 16C40		16-C-31799-6901				CRV	UC-2642A Case 334	CRV	K-35405sub1	
-48174	CAPACITOR, fixed: 2/8/32 mica; 375 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	RE48A126 16C40										
-48174-10	CAPACITOR, fixed: 2/8/32 NT-48174 w/375 mmf p/m 10%.	RE48A126 16C40		16-C-29063-2300				CRV	T			
-48175	CAPACITOR, fixed: 2/8/32 mica; 10,000 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	RE48A126 16C40										
-48175-10	CAPACITOR, fixed: 2/8/32 NT-48175 w/10,000 mmf p/m 10%. NOTE: RAA-4; RAB; RAB-1; RAB-2; RAB-3; RAB-4.	RE48A126 16C40		16-C-33622-6677	N16-C-10495-30			CRV	T	CRV	P-32170-13rev10	RAA-2 RAA-3 SEE NOTE

SHEET 48-58

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 59

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48176	CAPACITOR, fixed: mica; 150 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	2/8/32 RE48A126 16C40										
-48176-10	CAPACITOR, fixed: NT-48176 w/150 mmf p/m 10%.	2/8/32 RE48A126 16C40		16-C-28980-2277				CRV	T			
-48177	CAPACITOR, fixed: mica; 6,000 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	2/8/32 RE48A126 16C40										
-48177-10	CAPACITOR, fixed: NT-48177 w/6,000 mmf p/m 10%.	2/8/32 RE48A126 16C40		16-C-32857-7080	N16-C-10440-1			CRV	T			
-48178	CAPACITOR, fixed: mica; 1,500 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	2/8/32 RE48A126 16C40										
-48178-10	CAPACITOR, fixed: NT-48178 w/1500 mmf p/m 10%.	2/8/32 RE48A126 16C40		16-C-31512-4677				CRV	T			
-48179	CAPACITOR, fixed: mica; 500 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	2/8/32 RE48A126 16C40										
-48179-10	CAPACITOR, fixed: NT-48179 w/500 mmf p/m 10%.	2/8/32 RE48A126 16C40		16-C-30167-2277				CRV	T			
-48180	CAPACITOR, fixed: mica; 250 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	2/8/32 RE48A126 16C40										
-48180-10	CAPACITOR, fixed: NT-48180 w/250 mmf p/m 10%.	2/8/32 RE48A126 16C40		16-C-29481-3877				CRV	T	CRV	P-32170-15rev10	
-48181	CAPACITOR, fixed: CANCELLED: same as NT-48228.	2/8/32 RE48A126 16C40						CRV	T			
-48182	CAPACITOR, fixed: CANCELLED: same as NT-48229.	2/8/32 RE48A126 16C40						CRV	T			
-48183	CAPACITOR, fixed: CANCELLED: same as NT-48230.	2/8/32 RE48A126 16C40						CRV	T			
-48184	CAPACITOR, fixed: CANCELLED: same as NT-48231.	2/8/32 RE48A126 16C40						CRV	T			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-59

RESTRICTED

RESTRICTED

SHEET 48-60

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48185	CAPACITOR, fixed: 2/8/32 CANCELLED: name as NT-48232.	RE48A126 16C40						CRV	T			
-48186	CAPACITOR, fixed: 2/8/32 mica; 50,000 mmf; 1,500 vdcw, 9 amp at 3,000 kc, 12 amp at 1,000 kc, 8 amp at 300 kc, 4 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft, ea w/0.173" diam hole, mtg holes 1 1/4" c to c.	RE48A123 16C40										
-48186-B5	CAPACITOR, fixed: 2/8/32 NT-48186 w/50,000 mmf p/m 5%; temp coef ltr B.	RE48A123 16C40		16-C-35227-5735	N16-C-10595			CRV	UC-2592			
-48186-B10	CAPACITOR, fixed: 2/8/32 NT-48186 w/50,000 mmf p/m 10%; temp coef ltr B.	RE48A123 16C40		16-C-35232-6233	N16-C-10595-7			CRV	UC-2592			
-48187	CAPACITOR, fixed: 2/8/32 mica; 2,000 mmf; 5,000 vdcw, 8 amp at 3000 kc, 4.5 amp at 1000 kc, 2.5 amp at 300 kc, 1.5 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft, ea w/0.173" diam hole, mtg holes 1 1/4" c to c.	RE48A123 16C40										
-48187-B5	CAPACITOR, fixed: 2/8/32 NT-48187 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A123 16C40		16-C-31799-5554				CRV	UC-2219			
-48188	CAPACITOR, fixed: 2/8/32 mica; 1,000 mmf; 5,000 vdcw, 4 amp at 3,000 kc, 2.5 amp at 1,000 kc, 1.5 amp at 300 kc, 0.5 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft, ea w/0.173" diam hole, mtg holes 1 1/4" c to c.	RE48A123 16C40										
-48188-B5	CAPACITOR, fixed: 2/8/32 NT-48188 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A123 16C40		16-C-31087-3754				CRV	UC-1805			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-60

RESTRICTED

RESTRICTED

SHEET 48 - 61

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48189	CAPACITOR, fixed; 2/8/32 mica; 3,750 mmf; 2,000 vdcw, 10 amp at 3000 kc, 7.5 amp at 1000 kc, 4.0 amp at 300 kc, 1.5 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft, ea w/0.173" diam hole, mtg holes 1 1/4" c to c.	RE48A123 16C40										
-48189-B5	CAPACITOR, fixed; 2/8/32 NF-48189 w/3,750 mmf p/m 5%; temp coef ltr B.	RE48A123 16C40		16-C-32395-5932	N16-C-10346			CRV	UC-2894			
-48190	CAPACITOR, fixed 2/8/32 mica; 10,000 mmf; 2,000 vdcw, 8 amp at 3,000 kc, 7.5 amp at 1,000 kc, 4.0 amp at 300 kc, 1.5 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft, ea w/0.173" diam hole, mtg holes 1 1/4" c to c.	RE48A123 16C40										
-48190-B5	CAPACITOR, fixed; 2/8/32 NF-48190 w/10,000 mmf p/m 5%; temp coef ltr B.	RE48A123 16C40		16-C-33618-6717	N16-C-10505			CRV	UC-2882			
-48191	CAPACITOR, fixed; 2/8/32 mica; 140 mmf; 5,000 vdcw, 0.7 amp at 3,000 kc, 0.5 amp at 1,000 kc, 0.3 amp at 300 kc, 0.1 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft, ea w/0.173" diam hole, mtg holes 1 1/4" c to c.	RE48A123 16C40										
-48191-B5	CAPACITOR, fixed; 2/8/32 NF-48191 w/140 mmf p/m 5%; temp coef ltr B.	RE48A123 16C40		16-C-28924-3953				CRV	UC-2326			
-48192	CAPACITOR, fixed; 2/8/32 mica; 5,000 mmf; 2,000 vdcw, 6 amp at 3000 kc, 4.0 amp at 1000 kc, 2.6 amp at 300 kc, 1.5 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft, ea w/0.173" diam hole, mtg holes 1 1/4" c to c.	RE48A123 16C40										
-48192-B5	CAPACITOR, fixed; 2/8/32 NF-48192 w/5,000 mmf p/m 5%; temp coef ltr B.	RE48A123 16C40		16-C-32695-4717				CRV	UC-1857			

SHEET 48-61

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 63

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48196-A10	CAPACITOR, fixed: 11/23/36 NT-48196-A w/100,000 mmf p/m 10%; for replacement use NT-481001.	RE13A488 RE48A128		16-C-45773-9450			3DA100-289.2 3DA100-327	CD	VC-1039	CAY	P-7706376-2	TBK-7
-48196-A20	CAPACITOR, fixed: 11/23/36 NT-48196-A w/100,000 mmf p/m 20%; for replacement use NT-481001.	RE13A488 RE48A128		16-C-45805-7096			3DA100-133.5 3DA100-318	CSL	XDMRTW-1-20	CW	ESX-638975-106 ESX-654024-26	QBF (3) QJA (3)
-48197	CAPACITOR, fixed: 2/8/32 paper dielectric; 100,000 mmf plus 10 minus 3%; 400 vdcw; HB metal case; 1 13/16" lg x 15/16" wd x 3/4" h; dykanol filled; two solder lug term 5/16" h on side, spaced 7/8" c to c; no int gnd connections; two mtg ft 3/8" wd w/ 3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A129		16-C-45752-9445	N16-C-11309-10			CD	DH-4010	CFT CAY	F-36434-1 P-7706012-3	DAK-2 DAK-2 D K-4 GP-3 GP-4
-48197-10	CAPACITOR, fixed: 2/8/32 NT-48197 w/100,000 mmf p/m 10%.	RE13A488 R 48A129		16-C-45773-9445	N16-C-11297			CD	DH-4010			
-48197-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 100,000 mmf plus 10 minus 3%; 600 vdcw; HB metal can; 1 13/16" lg x 15/16" wd x 3/4" h; dykanol filled; two solder lug term 5/16" h on side, spaced 7/8" c to c; no int gnd connections; two mtg ears 3/8" wd w/ 3/16" diam mtg holes spaced 2 1/8" c to c.	RE48A129 RE13A488		16-C-45756-3119	N16-C-11309-950		3DA100-121	CD CSF	DYR-6010 PX24A	CG CRF CHZ CDE	M-7444514-2 0A-30879-2 rev C 00-828 2381-6	LS (3) NGA (4) OAP OAP-1 YB-2 (2) MK-33(17)
-48197-A10	CAPACITOR, fixed: 11/23/36 NT-48197-A w/100,000 mmf p/m 10%.	RE118A129 RE13A488		16-C-45777-3119	N16-C-11310		3DA100-90.1	CD CSF CAW CSL CGF CTD CBV	DYR-6010 2528-1 630-1 XDMRW6-1-10 7501 RLO-610 12M-2-20	CAY COL CAY CAY CRP CEM CML CHZ CRP CEM CAY CEM	T-7606286-2 956 2014 20 T-7609856-17 T-7606591-17 35-5273 744.622 24167 00-827 35-5049 744-247 ES-682063-52 744-199	IS-1 (3) OAP (2) OAP-1 (2) SF (18) SF-1 (18) SG (16) SG-1 (19) SG-16 (19) SG-25 (19) SJ-1 (3) SL SLA SEE NOTE
	NOT : SL-1; SO-1; SO-12M; SO-12N; SP-4; SU; SU-1; SV (6); TBK-1 3 (2); TEM-5 thru TEM-8; TEM-10; TEM-12; TCB-1 (4); TCB-2 (4); TCC-1; TCC-2; TCC-3; VD (5); VD-1 (5); WF; WCA; WCA-1 thru WCA-3 (5); WPA (14); MK-8 Mod 4; MK-8 Mod 1; MK-10 Mod 4; MK-12 Mod 3; MK-16 (5); MK-27 (3); MK-28 (3); MK-29 Mod 2 (3); MK-34 Mod 4; MK-33.											Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-63

RESTRICTED

RESTRICTED

SHEET 48 - 64

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48197-B	CAPACITOR, fixed: 12/17/41 paper dielectric; 100,000 mmf plus 10 minus 3%; 1000 vdcw; ES metal ca; 1 3/16" lg x 1" wd x 3/4" h; mineral oil impr and filled; two solder lug term 5/16" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48197-C.	RE13A488 RE48A129		16-C-45759-7092				CD CSL CAW	DYR-10010 XDMRW10-.1 1030	CFR CIP CPV	OA-30879-15 rev C ES-13103 M-422765-2	SA-3 (6) SJ
-48197-B5	CAPACITOR, fixed: 12/17/41 NT-48197-B w/100,000 mmf p/m 5%.	RE13A488 RE48A129		16-C-45738-7092			3DKA100-180	CD CSL CAW	DYR-10010 XDMRW10-.1-5 1030	CFR CIP	OA-30879-15revC ES-13103	
-48197-B10	CAPACITOR, fixed: 12/17/41 NT-48197-B w/100,000 mmf p/m 10%. NOTE: SG-1 (3); SG-2S (3); MK-12 Mod 1 (2); MK-22.	RE13A488 RE48A129		16-C-45780-7092	N16-C-11310-14		3DKA100-190 3DA100-397	CD CSL CAW	DYR-10010 XDMRW10-.1-10 1030-.1	CFR CIP CPT CRP CWI CYP	OA-30879-15revC ES-13103 F-36434-1 35-5013 GU-1899 270.154	DAK DAK-1 DAK-3 QBG (2) QBG-1 QBH (2) SEE NOTE
-48197-B15	CAPACITOR, fixed: 12/17/41 NT-48197-B w/100,000 mmf p/m 15%.	RE48A129 RE13A488		16-C-45796-8652				CD CSL CAW	DER-10010 XDMRW10-.1-15 1030	CAY	T-7610979-5	SR SR-5
-48197-C	CAPACITOR, fixed: 12/17/41 paper dielectric; 100,000 mmf plus 10 minus 3%; 1500 vdcw; ES metal c; 1 13/16" lg x 1" wd x 3/4" h; mineral oil im r and filled; two solder lug term 5/16" h on sides, spaced 1" c to c; no int gnd con- nections; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A129		16-C-45761-6300				CD CAW	DYR-15010 630			SJ
-48197-C10	CAPACITOR, fixed: 12/17/41 N -48197-C w/100,000 mmf p/m 10%.	RE13A488 RE48A129		16-C-45782-6347	N16-C-11324-93			CD CAW	DYR-15010 630	CDU CW	3-381 ESL-682055-1	
-48197-C20	CAPACITOR, fixed: 12/17/41 NT-48197-C w/100,000 mmf p/m 20%.	RE13A488 RE48A129		16-C-45811-1346				CD CAW	DYR-15010 630	COL COL	930 0012 00rev0 756 2018 40	TCZ (2) TDH-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-64

RESTRICTED

RESTRICTED

SHEET 48 - 65

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48198	CAPACITOR, fixed: 2/8/32 paper dielectric; 500,000 mmf plus 10 minus 3%; 200 vdcw; ES metal can; 7/8" h x 1 3/4" wd x 1" thk; oil impr and filled; two solder lug term 1" c to c on top; no int gnd connections; two integral mtg ears on bottom horiz ctr line w/two 3/16" diam holes 2 1/8" c to c; superseded by NT-48198-A.	RE48A128 RE13A488		16-C-47269-3454								
-48198-10	CAPACITOR, fixed: 2/8/32 NT-48198 w/500,000 mmf p/m 10%; superseded by NT-48198-A10.	RE48A128 RE13A488		16-C-47290-3444								
-48198-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 500,000 mmf plus 1% minus 3%; 400 vdcw; ES metal can; 1 3/4" lg x 1" wd x 7/8" h o/a; oil impr and filled; two solder lug term 5/16" h on top, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/two 3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-481002.	RE48A128 RE13A488										
-48198-A10	CAPACITOR, fixed: 11/23/36 NT-48198-A w/500,000 mmf p/m 10%; for replacement use NT-481002-10.	RE13A488 RE48A128		16-C-47293-9198			3DA500-37 3DA500-281.1	CAW CD	430	CRR CRR CDE CDE	C-59592-4-H A-201-2 S-2370-5 S-2380-2	LD-4 (3) YB-2 (5) YR (2)
-48199	CAPACITOR, fixed: 2/8/32 paper dielectric; 1 mf plus 10 minus 3%; 200 vdcw; ES metal can; case dimen 2" lg x 1 3/4" wd x 7/8" h; oi: impr; two solder lug term 3/8" lg on one end 1" c to c; no int gnd connections; two mtg ft on bottom, ea w/one 3/16" diam hole 2 3/8" c to c; superseded by NT-48199-A.	RE13A488 RE48A133		16-C-48789-4227	N16-C-11381-16-1		3DB1.2	CAW	261	CG	M-8461405-23	LD-1 (3)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-65

RESTRICTED

RESTRICTED

SHEET 48 - 66

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MEGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48199-A	CAPACITOR, fixed: 1/30/37 paper dielectric; 1 mf plus 10 minus 3%; 400 vdcw; HS metal can; case dimen 2" lg x 1 3/4" wd x 7/8" h; oil impr; 2 solder lug term 7/16" lg on one end 1" c to c; no int gnd connections; two mtg ft ea w/ one 3/16" diam hole 2 3/8" c to c; superseded by NT-48199-B.	RE48A133 RE13A488		16-C-48793-1194							
-48199-B	CAPACITOR, fixed: 2/21/41 paper dielectric; 1 mf plus 10 minus 3%; 600 vdcw; HS metal can; 2" lg x 1 3/4" wd x 13/16" h ; oil impr; two solder lug term 7/16" h on end 1" c to c; no int gnd connections; two mtg ft 3/8" wd, flush w/bottom w/3/16" diam mtg holes on 2 3/8" ctr.	RE48A133 RE13A488		16-C-48796-3862							
-48199-B10	CAPACITOR, fixed: 2/21/41 NT-48199-B w/1 mf p/m 10%.	RE48A133 RE13A488		16-C-48817-3890	N16-C-11415		3DB1.6100K				
-48200	CAPACITOR, fixed: 2/8/32 paper dielectric; 9.12 mfd plus 10 minus 3%; 1265 vdcw; HS metal can; 13 1/2" lg x 4 3/16" wd x 12 1/32" h; oil impr and filled; two screw type term 3" h located on top, spaced 6 3/4" c to c on four pillars; no int gnd connection; no mtg bkt incl.	RE48A139		16-C-51706-4970			3DB9	OG	DI-2928908	OG	M-2972828 rev 4
-48201	CAPACITOR, fixed: 3/16/32 mica; 250 mmf; 600 vdcw; case 1 1/4" lg x 1 1/4" wd x 11/32" d; molded bakelite case; two lug term ea w/one 3/16" diam hole on 1 3/4" ctr; two mtg holes in back of case 5/32" diam on 1 1/2" mtg/c.	RE48A215 16C40									
-48201-A10	CAPACITOR, fixed: 3/16/32 NT-48201 w/250 mmf p/m 10%; temp coef ltr A.	RE48A215 16C40		16-C-29481-5151				CAW	1455	CRV	X-30090-1
-48201-B10	CAPACITOR, fixed: 3/16/32 NT-48201 w/250 mmf p/m 10%; temp coef ltr B.	RE48A215 16C40		16-C-29481-5156	N16-C-9975-10			CAW	1455L		RAB RA -1 thru RAB-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-66

RESTRICTED

RESTRICTED

SHEET 48 - 67

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48202	CAPACITOR, fixed: mica; 2,000 mmf; 600 vdcw, 1000v DC test; case 1 1/4" lg x 1 1/4" wd x 5/16" thk; molded bakelite case; two solder lug term ea w/one 3/16" hole on 1 3/4" mtg/c.	3/16/32 RE48A216 16C40										
-48202-A1	CAPACITOR, fixed: NT-48202 w/2000 mmf p/m 10%; temp coef ltr A. NOTE: RAA-3; RAA-4; RAB thru RAB-4.	3/16/32 RE48A216 16C40		16-C-31802-7351			3DA2-86	CAW	1450	CRV	K-30095-1rev1	RAA RAA-2 SEE NOTE
-48203	CAPACITOR, fixed: mica; 150 mmf; 3,500v working peak, 7.0 amp at 27,000 kc, 1.5 amp at 4,000 kc; case 2 9/16" diam x 1 1/16" d; ceramic case; two elliptical end plates ea w/two 0.196" diam holes 3" c to c on sides.	4/12/32 RE48A255 16C40										
-48203-B5	CAPACITOR, fixed: NT-48203 w/150 mmf p/m 5%; temp coef ltr B.	4/12/32 RE48A255 16C40		16-C-28976-6504	N16-C-9956-7			CD	PL-432-54			TBA TBB TBC
-48204	CAPACITOR, fixed: mica; 15,000 mmf; 2,000 max vdcw, 12 amp at 3000 kc, 10 amp at 1000 kc, 7 amp at 300 kc, 4 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two 1/2" lg stud term on top 1 5/8" c to c; two mtg feet ea w/one 0.180" diam hole 2 5/8" c to c.	4/20/32 RE48A131 16C40										
-48204-A5	CAPACITOR, fixed: NT-48204 w/15,000 mmf p/m 5%; temp coef ltr A.	4/20/32 RE48A131 16C40		16-C-34040-7081				CD	PL-140-6	CAY	7705832-9	TBA-1 TBK-5 TBL-6
-48204-B5	CAPACITOR, fixed: NT-48204 w/15,000 mmf p/m 5%; temp coef ltr B.	4/20/32 RE48A131 16C40		16-C-34040-7086	N16-C-10537			CRV CRV	UC-3183 UC-2915	CRV CRV	W-303346-12 DL-501617-502	NBM-1 TBL TBL-1
-48204-D2	CAPACITOR, fixed: NT-48204 w/15,000 mmf p/m 2%; temp coef ltr D. NOTE: TBL-3 thru TBL-7; TBL-10 thru TBL-13; TEM-4 thru TEM-8; TEM-11; TEM-12.	4/20/32 RE48A131 16C40		16-C-34035-5616	N16-C-10536			CD CAW	PL-140-6L 1550-H-311	CAY CAY CAY CAY	P-7705832-76 7607280-21 7607470-20 T-7607093-21 T-7605847-97	TBK-9 TBK-11 TBK-15 TBK-16 TBL-2 SEE NOTE
-48204-D5	CAPACITOR, fixed: NT-48204 w/15,000 mmf p/m 5%; temp coef ltr D.	4/20/32 RE48A131 16C40		16-C-34040-7096				CD	PL-140-6HB	CAY	P-7705832-6	TBK-7

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-67

RESTRICTED

RESTRICTED

SHEET 48 - 68

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48205	CAPACITOR, fixed: 4/25/32 paper dielectric; 500,000 mmf plus 10, minus 3%; 200 vdcw; BS metal can; 3/4" h x 1 13/16" wd x 1 1/4" thk; oil impr and filled; two solder lug term 1" c to c on side; no int gnd connections; two integral mtg ears on bottom horiz ctr line w/twe 11/64" diam holes 2 1/8" c to c; superseded by NT-48205-A.	RE48A129 RE13A488		16-C-47269-3641	W16-C-11344-102							
-48205-10	CAPACITOR, fixed: 4/25/32 NT-48205 w/500,000 mmf p/m 10%; superseded by NT-48205-A10.	RE48A129 RE13A488		16-C-47290-3656				CD		CBS	RA-158	RAG (2) RAG-1 (2) RAH RAH-1
-48205-A	CAPACITOR, fixed: 8/22/36 paper dielectric; 500,000 mmf plus 10 minus 3%; 400 vdcw; BS metal can; 1 13/16" lg x 15/16" wd x 13/16" h; oil filled; two solder lug term 7/8" h on side spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c; for replacement used NT-481223. NOTE: TBL; TBL-2; TBL-3; TBL-5; TBU; TBU-2; TBU-3; TC	RE13A488 RE48A129		16-C-47267-1110				CD CAW	DE-4050-A 430 .	CRR CRR CAY CDE CG CRP	N-27551-97 A-17491 7706012-6 2381-2 T-7659573-216 35-5052	GP-3 DAH (3) GP-4 LJ-1 (2) LS SO-2 (2) TR-2 (10) YF (2) SEE NOTE
-48205-A10	CAPACITOR, fixed: 8/22/36 NT-48205-A w/500,000 mmf p/m 10%.	RE13A488 RE48A129		16-C-47293-9445	N16-C-11345			CSF CD	2528-2 DE-4050A	CEM CAY CML CAY CRP CAY CAY CAY CDE CRR	744-584 7608226-33 24165 T-7606570-13 5-5052 T-7611054-12 7607470-56 T-7607094-74 T-7606591-3 2381-2 A17471	LS-1 SO-1 SO-2 SO-1 SP SU TB-2 (2) TAB-7 (7) TAB-8 (7) TBK-2 (2) TBL-5 SEE NOTE
	NOTE: TBL-6; TBM-6 (3); TCE; TCE-1; TCE-2; TCE-3; TDE (7); ME-29 Mod 2; MK-33.	B-2 (3).										

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-68

RESTRICTED

RESTRICTED

SHEET 48 - 69

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48206	CAPACITOR, fixed: 5/17/32 mica; 100/100 mmf; 6,000 vdcw, 7.5 amp at 3000 kc, 29 amp at 18000 kc, 18 amp at 8000 kc; case 5" lg x 3 1/2" wd x 4 1/4" h; metal case; four screw term 5/8" lg 1/4"-20 thd, two on ea side of capacitor 1 1/2" c to c; two mtg ft, one in front, one in back, ea w/two 1/4" diam holes on 4" x 4 1/4" mtg/c.	RE48A256 16C40										
-48206-B5	CAPACITOR, fixed: 5/17/32 NF-48206 w/100/100 mmf p/m 7/8; temp coef ltr B.	RE48A256 16C40		16-C-39423-7831				CRV	UC-2952	CRV	K-35489-revo	GK-1
-48207	CAPACITOR, variable: 5/28/32 mica; compression type, single sect; 30 mmf max, 5 mmf min; 1.78" lg x 7/8" wd x 1 1/16" h; two mtg ft ea w/ 0.136" diam hole 1.53" c to c, also used as term; slotted screw adj; Grade E ins matl.	RA48F202		16-C-64651-9801	N16-C-12600							
-48208	CAPACITOR, variable: 5/28/32 mica; compression type, single sect; 50 mmf max, 7 mmf min; 1.78" lg x 7/8" wd x 1 1/16" h; two mtg ft ea w/0.136" diam hole 1.53" c to c, also used as term; slotted screw adj; Grade E ins matl.	RA48F202		16-C-64692-1901	N16-C-12615	R16-C-12615						
-48209	CAPACITOR, variable: 5/28/32 mica; compression type, single sect; 100 mmf max, 5 mmf min; 1.78" lg x 7/8" wd x 1 1/16" h; two mtg ft ea w/ 0.136" diam hole 1.53" c to c, also used as term; slotted screw adj; Grade E ins matl.	RA48F202		16-C-64774-3501	N16-C-12620							
-48210	CAPACITOR, variable: 5/28/32 mica; compression type, single sect; 200 mmf max, 5 mmf min; 1.78" lg x 7/8" wd x 1 1/16" h; two mtg ft ea w/0.136" diam hole 1.53" c to c, also used as term; slotted screw adj; Grade E ins matl.	RA48F202		16-C-64806-2351								
-48211	CAPACITOR, variable: 5/28/32 mica; compression type, single sect; 300 mmf max, 5 mmf min; 1.78" lg x 7/8" wd x 1 1/16" h; two mtg ft ea w/ 0.136" diam hole 1.53" c to c, also used as term; slotted screw adj; Grade E ins matl.	RA48F202		16-C-64843-2801								

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-69

RESTRICTED

RESTRICTED

SHEET 48 - 70

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48212	CAPACITOR, variable: mica; compression type, single sect; 500 mmf max, 5 mmf min; 1.78" lg x 7/8" wd x 1 1/16" h; two mtg ft ea w/ 0.136" diam hole 1.53" c to c, also used as term; slotted screw adj; Grade E ins matl.	5/28/32 RA48202		16-C-64895-1541								
-48213	CAPACITOR, fixed: mica; 20,000/2,000/2,000/500/1,000 mmf; 1,000 vdcw ea sect, 10 amp at 1,000 kc; case 3 1/16" lg x 2 7/16" wd x 2 13/16" h; cast metal case, potted; 6 solder lug term 3/8" h on top; three mtg ft, one on one side, two on the other, ea w/one 0.257" diam hole, on 1 5/8" x 3 9/16" mtg/c; add suffix indicating capacity tolerance in per cent.	6/16/32 RE48A260 16C40										
-48213-B5	CAPACITOR, fixed: NT-48213 w/20,000/2000/2000/500/1000 mmf p/m 5%; temp coef ltr B.	6/16/32 RE48A260 16C40		16-C-39444-3001				CRV	UC-2944K	CRV	K-35470 sub0	TBA-1a
-48214	CAPACITOR, oil: CANCELLED: for replacement use NT-48335-A.	6/16/32						CG	9CE1A22	CG	H-3931073-3	TBA-1a
-48215	CAPACITOR, fixed: mica; 800 mmf; 600 vdcw; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	7/29/32 RE48A112 16C40										
-48215-A10	CAPACITOR, fixed: NT-48215 w/800 mmf p/m 10%; temp coef ltr A.	7/29/32 RE48A112 16C40		16-C-30694-8951				CD	9L-13080			MF-2 MB-3
-48215-B2	CAPACITOR, fixed: NT-48215 w/800 mmf p/m 2%; temp coef ltr B.	7/29/32 RE48A112 16C40		16-C-30684-6996								
-48215-B10	CAPACITOR, fixed: NT-48215 w/800 mmf p/m 10%; temp coef ltr B.	7/29/32 RE48A112 16C40		16-C-30694-8956				CD	9L-13080			
-48216	CAPACITOR, fixed: CANCELLED: for replacement use NT-48352.	9/22/32										
-48217	CAPACITOR, fixed: paper dielectric; two sect; 7 mf/7mf plus 10, minus 3%; 1300 vdcw; HS metal can; 12" h x 13 1/2" wd x 4 1/8" thk; mineral oil impr and filled; three stud and nut term 2" h on for pillars each 3 3/8" c to c on top; no int and connections.	7/18/32 RE48A176 RE13A405		16-C-54235-4620	N16.C-11623-150			CD	PL-184-6	CG	M-2943341 rev3	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109 (A)
SUPPLEMENT # 1

SHEET 48-70

RESTRICTED

RESTRICTED

SHEET 48 - 71

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48218	CAPACITOR, fixed: 9/22/32 mica; 4,000 mmf; 3000 max vdcw, 11 amp at 3,000 kc, 8.5 amp at 1,000 kc, 5.5 amp at 300 kc, 2.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; two stud term on top 1/2" h on 1 5/8" centers; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-481289.	RE48A131 16C40										
-48218-A	CAPACITOR, fixed: 9/22/32 CANCELLED: for replacement use NT-481289. NOTE: TBK-9; TBK-16; TEM-4.	RE48A131 16C40		16-C-32458-3881		R16-C-10378		CD	PL-184-6	CAY	T-760584-7-15 T-7604831-11 7604831-27 7607280-58	TAJ-3 TBK-5 TBK-6 TBE-7 SEE NOTE
-48218-B2	CAPACITOR, fixed: 9/22/32 NT-48218 w/4,000 mmf p/m 2%; temp coef 1tr B.	RE48A131 16C40		16-C-32453-2405			3DA4-85	CSL	XSBW-3-24-2	CAY	T-7606683-25	TAB-5 (2) TAB-6 (4) TAB-7 (2)
-48218-B5	CAPACITOR, fixed: 9/22/32 NT-48218 w/4,000 mmf p/m 5%; temp coef 1tr B. NOTE: TBL (2); TBL-1 (2); TBK-11; TBK-15.	RE48A131 16C40		16-C-32458-3886	N16-C-10381			CRV CRV CSL CD	UC-3038 UC-2918 XSBW-3-24-5 PL-184A-6LS	CRV CRV CAY CG CAY CAY CAY	K-856829-2rev8 DL-UC-2918RG-2 T-7606683-37 P-702259-15 7660607-124 7607470-64 T-7607280-58	TAB-5 (2) TAB-6 (2) TAB-7 (2) TAJ-4 (2) TAJ-7 (2) TBL-2 TBL-13 SEE NOTE
-48218-B15	CAPACITOR, fixed: 9/22/32 NT-48218 w/4,000 mmf p/m 15%; temp coef 1tr B.	RE48A131 16C40		16-C-32466-4950				CD		CAY	T-760584-7-15	TEM-5 TBM-7 TBK-13
-48218-D5	CAPACITOR, FIXED: 12/14/48 Navy Type 48218 w/4000 mmf p/m 5%; temp coef letter D.	RE48AA131C		16-C-32458-3896				CD	LS	CAY	T-7604831-10 P34	TBK-7
-48219	CAPACITOR, fixed: 7/19/32 paper dielectric; 7 mf plus 10 minus 3%; 300 vdcw; HS metal can; 5" h x 4 7/16" wd x 1 9/16" thk; wax impr and filled; two ins solder lug term 3/4" c to c on top; no int gnd connections.	RE48A177 RE134888		16-C-51072-1920				CG	DL-2593228	CG	M-2576829-101 rev8	
-48220	CAPACITOR, fixed: 7/19/32 paper dielectric; 500,000 mmf plus 10 minus 3%; 20,000 vdcw; HS metal can; 12" h x 13 1/2" wd x 4 1/8" thk; oil impr and filled; two stud and nit term 3 7/8" h on por pillars 5 1/4" c to c on top; no int gnd connections; one 1/4"-20 thd stud 3" from term for gnd case.	RE48A139		16-C-47286-5293				CG	DL-3932062	CG	K-3912212rev 5	

SHEET 48-71

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 72

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48221	CAPACITOR, fixed: CANCELLED for replacement use NT-48146.	7/19/32 RE48A106 16C40										
-48222	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 500 vdcw; HS metal can; 5" h x 4 1/4" wd x 1 1/2" thk; oil impr and filled; two ins stud and nut term 2" c to c on top; no int gnd connections; superseded by NT-48222-A.	7/20/32 RE48A110 RE13A488		16-C-49935-4138	N16-C-11547			CAY	512723	CRV	WG-15-ED	TAB-2
-48222-A	CAPACITOR, fixed: paper dielectric; 4 mfd plus 10 minus 3%; 600 vdcw; HS metal can; 5" h x 4 1/4" wd x 1 1/2" d; oil impr and filled; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	4/11/38 RE48A110 RE13A488		16-C-49937-4147				CAY	512723-WG-15-ED			
-48223	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 300 vdcw; HS metal can; 4 1/2" h x 2 3/4" wd x 5/8" thk; oil impr and filled; two ins stud and nut term 1" c to c on top; no int gnd connections; superseded by NT-48223-A	7/20/32 RE48A110 RE13A488		16-C-49171-8922				CAY	552844			TAJ
-48223-A	CAPACITOR, fixed: paper dielectric; 2 mfd plus 10 minus 3%; 400 vdcw; HS metal can; 4 1/2" h x 2 3/4" wd x 5/8" d c/a; oil impr and filled; two stud term 1/2" h located on top, spaced 1" c to c; no int gnd connections.	1/18/37 RE48A110 RE13A488		16-C-49173-4150	N16-C-11470							
-48224	CAPACITOR, fixed: paper dielectric; 9 mf plus 10 minus 3%; 550 vacw HS metal can; 4 13/16" h x 3 3/4" lg x 4 9/16" wd; oil impr and filled; two ins stud and nut term 2" c to c on top; no int gnd connections; superseded by NT-48224-A.	7/22/32 RE48A110 RE13A488		16-C-51645-6350				CG	9CE1A55	CG	R-3931073-3rev1	TAQ-3
-48224-A	CAPACITOR, fixed: paper dielectric; 9 mfd plus 10 minus 3%; 1,600 vdcw; HS metal can; 4 13/16" h x 4 9/16" wd x 3 3/4" lg; oil impr and filled; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	1/28/38 RE48A110 RE13A488		16-C-51652-7863								

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-72

RESTRICTED

RESTRICTED

SHEET 48 - 73

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48225	CAPACITOR, fixed: 43 paper dielectric; five sect; 2/2/2/2 mf plus 10 minus 3%; 150/150/150/150 vdcw; BS metal can; 5" h x 2 3/4" lg x 2 1/4" wd; wax impr and filled; One black and five red ins flex wire term 6" lg out of top; no int gnd connections, one side of all sections is common.	RE48A178 RE13A488		16-C-54978-5996				CG	DL-C-2593244	CG	M-2576856rev4	
-48225-20	CAPACITOR, fixed: Aug 43 NT-48225 w/2/2/2/2 mf p/m 20%.	RE48A178 RE13A488		16-C-54983-5817	N16-C-11497-20							
- 8226	CAPACITOR, fixed: 8/22/32 mica; 30,000 mmf; 2,000 vdcw, 18 amp at 3,000 kc, 40 amp at 1,000 kc, 35 amp at 300 kc, 19 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; two 1/4" mtg holes in base 3 1/4" mtg/c.	RE48A108 16C40										
-48226-B5	CAPACITOR, fixed: NT- 226 w/30,000 mmf p/m 5%; temp coef ltr B.	RE48A108 16C40		16-C-34726-5596	N16-C-10577			CRV	UC-2785			
-48227	CAPACITOR, fixed: 8/22/32 mica; 5,000 mmf; 200 vacw; case 2" lg x 1" wd x 3/8" thk; potted in sheet metal case; two axial wire leads RC; two mtg tabs on bottom ea w/one 0.10" diam mtg holes 1 1/4" mtg/c.	RE48A106 16C40										
-48227-B3	CAPACITOR, fixed: 8/22/32 NT-48227 w/5,000 mmf p/m 3%; temp coef ltr B; for replacement use NT-481295-B3.	RE48A106 16C40		16-C-32693-5423				CRV	UC-2909	CRV	K-35900rev0	RAA RAB RAA-2 RAA-3
-48228	CAPACITOR, fixed: 8/22/32 mica; 10 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c; add suffix indicating capacity tolerance in per cent.	RE48A126 16C40										
-48228-10	CAPACITOR, fixed: 8/22/32 NT-48228 w/10 mmf p/m 10%. NOTE: RAA-2; RAA-3; RAA-4.	RE48A126 16C40		16-C-26025-8477				CRV	T	CRV	P-32170-1rev10	RAA RAB SEE NOTE
-48228-20	CAPACITOR, FIXED: 4/9/58 Navy Type 48228 w/10 mmf p/m 20%.	RE48A154 RE48A126		16-C-26031-1962	N16-C-9791-35			CRV	T			

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-73

RESTRICTED

RESTRICTED

SHEET 48 - 74

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48229	CAPACITOR, fixed: 8/22/32 mica; 30 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term on w/one 3/32" diam hole, 1 3/16" o to c.	RE48A126 16C40										
-48229-10	CAPACITOR, fixed: 8/22/32 NT-48229 w/30 mmf p/m 10%.	RE48A126 16C40		16-C-27133-7277				CRV	T	CRV	P-32170-2rev10	RAA RAB
-48230	CAPACITOR, FIXED: 8/22/32 mica dielectric; 85 mmf; 500 vdcw; 7/8" lg x 7/8" wd x 1/4" thk case; metal case; 2 axial solder lug term; one 0.140" mtg hole in ctr; add suffix indicating capacity tolerance in per cent.	RE48A126E 16C40 RE48A154										
-48230-5	CAPACITOR, fixed: 8/22/32 NT-48230 w/85 mmf p/m 5%. NOTE: RAA-2; RAA-3; RAA-4.	RE48A126 16C40		16-C-28289-3397	N16-C-9923			CRV	T	CRV	P-32170-3rev10	RAA RAB SEE NOTE
-48230-10	CAPACITOR, fixed: 8/22/32 NT-48230 w/85 mmf p/m 10%.	RE48A126 16C40		16-C-28294-3877	N16-C-9923-10			CRV	T			
-48230-20	CAPACITOR, FIXED: 6/24/48 Navy Type 48230 w/85 mmf p/m 20%.	RE48A126E RE48A154		16-C-28299-6362				CRV	T			
-48230-85	CAPACITOR, FIXED: 6/28/48 Navy Type 48230 w/85 mmf p/m 5%; temp coef 1tr B.	RE48A126 RE48A154		16-C-28289-3402	N16-C-9923			CRV	T	CRV	P-32170-3	RAA
-48231	CAPACITOR, fixed: 8/22/32 mica; 10,000 mmf; 500 vdcw; 7/8" lg x 7/8" wd x 1/4" thk; metal clad; one lug term at one end w/one 3/32" diam hole and one lug term bent back over top of capacitor fastened down w/eyelet 0.14" diam.	RE48A228 16C40										
-48231-5	CAPACITOR, fixed: 8/22/32 NT-48231 w/10,000 mmf p/m 5%. NOTE: RBP; RBP-1.	RE48A228 16C40		16-C-33617-6153				CRV	T	CRV	P-713881-14	RAA RAB SEE NOTE:
-48231-10	CAPACITOR, fixed: 8/22/32 NT-48231 w/10,000 mmf p/m 10%. NOTE: RAA thru RAA-4; RAB (3) thru RAB-4(3); RAL; RAL-1; RAL-5; RAL-6; RAL-7; RBP; TDQ; YE-1; YE-2.	RE48A228 16C40		16-C-33622-6632	N16-C-10497			CRV	T	CRV	P-32170-11	DO thru DO-3 SEE NOTE
-48232	CAPACITOR, FIXED: 8/22/32 mica; 42 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" h; metal case; 1 solder lug term 1 end other end 1 lug term bent back over top of case secured w/eyelet 0.140" diam; term mtg; add suffix indicating capacity tolerance in per cent.	RE48A228 RE48A154										
-48232-5	CAPACITOR, fixed: 8/22/32 NT-48232 w/42 mmf p/m 5%.	RE48A228 16C40		16-C-27445-2478	N16-C-9843-72			CRV	T	CRV	P-32170-512	YE-1 YE-2
-48232-10	CAPACITOR, fixed: 8/22/32 NT-48232 w/42 mmf p/m 10%. NOTE: RAB-1; RAB-3; RAB-4; YE-2.	RE48A228 16C40		16-C-27450-2959				CRV	T	CRV	P-32170-12	RAA RAB SEE NOTE

SHEET 48-74

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48-75

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48232-20	CAPACITOR, FIXED: Navy Type 48232 w/42 mmf p/m 20%.	5/8/48 RE48A228 RE48A134		16-C-27455-5562				CRV	T			
-48233	CAPACITOR, FIXED: paper dielectric; 3 sect; 100000 mmf plus 10 minus 3% ea sect; 300 vdcw ea sect; HS metal can; 2 11/16" h x 1 7/8" lg x 5/8" wd, not incl mtg ft or term; parolite impr and sealed; 3 solder lug term on side of case 7/16" h, 9/16" from c to c; all sect int grnd; 2 mtg ft 7/16" lg integral w/bottom of case w/two 0.154" diam mtg holes on 2 3/16" ctr, mtg ft extend horiz from bottom of case.	8/22/32 RE13A488 RE48A134 alt A		16-C-54429-3355				CRV	CP-96	CRV	M-64575-01	RAA RAB RAB-1 RAB-2 (5) RAB-3 (5)
-48233-10	CAPACITOR, FIXED: Navy Type 48233 w/100000 mmf p/m 10% ea sect.	8/22/32 RE13A488 RE48A134 alt A		16-C-54442-0432				CRV	CP-96	CRV	M-64575-01	RAB-4 (5)
-48233-A	CAPACITOR, FIXED: paper dielectric; 3 sect; 100000 mmf plus 10 minus 3% ea sect; 400 vdcw ea sect; HS metal can; 2 11/16" h x 1 7/8" lg x 5/8" wd, not incl mtg ft or term; parolite impr and sealed; 3 solder lug term on side of case 7/16" h, 9/16" from c to c; all sect int grnd; 2 mtg ft 7/16" lg integral w/bottom of case w/two 0.154" diam mtg holes on 2 3/16" ctr, mtg ft extend horiz from bottom of case.	2/2/38 RE13A488 RE48A134 alt B		16-C-54429-6164	M16-C-1333-149			CRV	M-64575-01			
-48233-A10	CAPACITOR, FIXED: Navy Type 48233 w/100000 mmf p/m 10% ea sect.	2/2/38 RE13A488 RE48A134 alt B		16-C-54442-2405				CRV	M-64575-01			
-48234	CAPACITOR, FIXED: paper dielectric; 3 sect; 100000 mmf plus 10 minus 3% ea sect; 300 vdcw ea sect; HS metal can; 2 11/16" h x 1 7/8" lg x 5/8" wd, not incl mtg ft or term; parolite impr and sealed; 3 solder lug term on side of case 7/16" h, 9/16" from c to c; all sect int grnd; 2 mtg ft extending 7/16" beyond end of case, ea w/one 0.154" diam mtg hole in ea, mtg ft extend vert from bottom of case and are spaced 1 15/16" apart; same as Navy Type 48233 except mtg ft bent at right angles.	8/22/32 RE13A488 RE48A134 alt A		16-C-54429-3335	M16-C-11333-119			CRV	CP-97	CRV	M-64575-02	RAA RAB RAB-1 RAB-2 (2) RAB-3
-48234-10	CAPACITOR, FIXED: Navy Type 48234 w/100000 mmf p/m 10% ea sect.	8/22/32 RE13A488 RE48A134 alt A		16-C-54442-5412				CRV	CP-97	CRV	M-64575-02	RAB-4 (2)

SHEET 48-75

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 76

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48234-A	CAPACITOR, FIXED: 12/22/36 paper dielectric; 3 sect; 100000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; HS metal can; 2 11/16" h x 1 7/8" lg x 5/8" wd, not incl mtg ft or term; parolite impr and sealed; 3 solder lug term on side of case 7/16" h, 9/16" from c to c; all sect int gnd; 2 mtg ft extending 7/16" beyond end of case, ea w/one 0.154" diam mtg hole in ea, mtg ft extend vert from bottom of case and are spaced 1 15/16" apart.	RE13A488 RE48A134 alt B		16-C-54429-6144								
-48234-A10	CAPACITOR, FIXED: 12/22/36 Navy Type 48234 w/100000 mmf p/m 10%.	RE13A488 RE48A134 alt B		16-C-54443-2415				CRV	M-64575-2			
-48235	CAPACITOR, FIXED: 8/22/32 paper dielectric; 2 sect; 100000 mmf plus 10 minus 3% ea sect; 300 vdcv ea sect; HS metal can; 2 11/16" h x 1 7/8" lg x 5/8" wd, not incl mtg ft or term; parolite impr and sealed; 3 solder lug term on side of case 7/16" h, 9/16" c to c; both sect int gnd; 2 mtg ft 7/16" lg integral w/bottom of case w/two 0.154" diam mtg holes on 2 3/16" ctr, mtg ft extend horiz from bottom of case; for replacement use Navy Type 48235-A.	RE13A488 RE48A134 alt A		16-C-53103-9577	N16-C-11330-100			CRV	CP-98	CRV	M-66000-C1	RAA RAB RAB-1 RAB-2 (2) RAB-3 (4)
-48235-10	CAPACITOR, fixed: 8/22/32 NT-48235 w/100,000 mmf p/m 10% ea sect.	RE48A134 RE13A488		16-C-53147-9385	N16-C-11330-100			CRV	CP-98	CRV	M-66000-1 sub0	RAB-4 (4)
-48235-A	CAPACITOR, fixed: 2/2/38 paper dielectric; 2 sect; 10,000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; HS metal can; 2 21/32" h x 1 15/16" wd x 19/32" thk; parolite impr and sealed; two solder lug term on side of case 7/16" h from bottom 1" c to c; all sect int gnd; two mtg ft 1/2" lg integral w/bottom of case w/two 0.154" diam mtg holes 2 3/16" c to c; for replacement use NT-48236-A.	RE48A134 RE13A488		16-C-53104-9345	N16-C-11332			CRV				
-48235-A10	CAPACITOR, fixed: 2/2/38 NT-48235-A w/100,000 mmf p/m 10% ea sect.	RE48A134 RE13A488		16-C-53148-7794				CRV				

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-76

RESTRICTED

RESTRICTED

SHEET 48 - 77

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48236	CAPACITOR, fixed: 8/22/32 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 300 vdcv ea sect; ES metal can; 2 21/32" h x 1 15/16" wd x 19/32" thk; parolite impr and sealed; three solder lug term on side of case 7/16" h from bottom 1/2" from c to c; both sect int gnd; two mtg ft 1/2" lg integral w/bottom case w/two 0.154" diam mtg holes on same axis 1 7/8" apart; for replacement use NT-48236-A.	RE48A134 RE13A488		16-C-53103-9560	N16-C-11330-100			CRV	CP-99	CRV	M-66000-2 sub0	RAA RAB RAB-1 RAB-2 (3) RAB-3(4)
-48236-10	CAPACITOR, fixed: 8/22/32 NT-48236 w/100,000 mmf p/m 10% ea sect.	RE48A134 RE13A488		16-C-53147-9382	N16-C-11330-100			CRV	CP-99	CRV	M-66000-2 sub0	RAB-4 (2)
-48236-A	CAPACITOR, fixed: 12/22/36 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; ES metal can; 2 21/32" h x 1 15/16" wd x 19/32" thk; parolite impr and sealed; two solder lug term on side of case 7/16" h from bottom 1" c to c; all sect int gnd; two mtg ft 1/2" lg integral w/bottom of case w/two 0.154" diam mtg holes on same axis 1 7/8" apart.	RE48A134 RE13A488		16-C-53104-9335	N16-C-11331			CRV				
-48236-A10	CAPACITOR, fixed: 12/22/36 NT-48236-A w/100,000 mmf p/m 10% ea sect.	RE48A134 RE13A488		16-C-53148-7784				CRV				
-48237	CAPACITOR, fixed: 8/22/32 paper dielectric; 50,000 mmf plus 10 minus 3%; 300 vdcv; ES metal can; 2 21/32" h x 1 15/16" wd x 19/32" thk; parolite impr and sealed; two solder lug term on front of case 7/16" h from bottom 1" c to c; no int gnd connections; two mtg ft 1/2" lg integral with bottom of case w/two 0.154" diam mtg holes 2 13/16" c to c; for replacement use NT-48238-A.	RE48A134 RE13A488		16-C-44231-7960	N16-C-11153							
-48237-10	CAPACITOR, fixed: 8/22/32 NT-48237 w/50,000 mmf p/m 10%. NOTE: RAA-2; RAA-3; RAA-4.	RE48A134 RE13A488		16-C-44252-7960	N16-C-11153			CRV	CP-100	CRV	M-66000-1 sub1	RAA RAB SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-77

RESTRICTED

RESTRICTED

SHEET 48 - 78

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48237-A	CAPACITOR, fixed: 2/2/38 paper dielectric; 50,000 mmf plus 10 minus 3%; 400 vdcw; HS metal can; 2 21/32" h x 1 15/16" wd x 19/32" thk; parolite impr and sealed; two solder lug term on front of case 7/16" h from bottom 1" c to c; no int gnd connection; two mtg ft 1/2" lg integral w/bottom of case w/two 0.154" diam mtg holes 2 13/16" c to c; for replacement use NT-48238-A.	RE48A134 RE13A488		16-C-44232-9944	N16-C-11153-600			CRV				
-48237-A10	CAPACITOR, fixed: 2/2/38 NT-48237-A w/50,000 mmf p/m 10%.	RE48A134 RE13A488		16-C-44253-9944				CRV				
-48238	CAPACITOR, fixed: 8/22/32 paper dielectric; 50,000 mmf plus 10 minus 3%; 300 vdcw; HS metal can; 2 21/32" h x 1 15/16" wd x 19/32" thk; parolite impr and sealed; two solder lug term on front of case 7/16" h from bottom 1" c to c; no int gnd connections; two mtg ft 1/2" lg integral w/top of case w/two 0.154" diam mtg holes on same axis 1 7/8" c to c; for replacement use NT-48238-A.	RE48A134 RE13A488		16-C-44231-9005				CRV	CP-101			RAA RAB
-48238-10	CAPACITOR fixed: 8/22/32 NT-48238 w/50,000 mmf p/m 10%. NOTE: RAB-3; RAB-4.	RE48A134 RE13A488		16-C-44252-7995				CRV	CP-101	CRV	M-56002-G-2 sub1	RAB RAB-1 SEE NOTE
-48238-A	CAPACITOR, fixed: 12/22/36 paper dielectric; 50,000 mmf plus 10 minus 3%; 400 vdcw; HS metal can; 2 21/32" h x 1 15/16" wd x 19/32" thk; parolite impr and sealed; two solder lug term on front of case 7/16" h from bottom 1" c to c; no int gnd connections; two mtg ft 1/2" lg integral w/bottom of case w/two 0.154" diam mtg holes on same axis 1 7/8" c to c.	RE48A134 RE13A488		16-C-44232-9939				CRV				
-48238-A10	CAPACITOR, fixed: 12/22/36 NT-48238-A w/50,000 mmf p/m 10%.	RE48A134 RE13A488		16-C-42253-9939	N16-C-11155			CRV				

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-78

RESTRICTED

RESTRICTED

SHEET 48 - 79

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48239	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 300 vdcw; HS metal can; 2 21/32" h x 2 3/8" wd x 1" thk; parolite impr and sealed; two solder lug term on front of case 7/16" h from bottom 1" c to c; no int gnd connection; two mtg ft 13/16" lg integral w/top of case w/two 0.154" diam mtg holes 2 3/4" c to c; for replacement use NT-48240-A. NOTE: DP-2 (7); DP-3 (7); NM-3.	8/22/32 RE48A134 RE13A488		16-C-48791-8478	N16-C-11384-12							RAA RAB DO (7) DO-1 (7) SO-2 (7) DO-3 (7) DP (7) MP-1 (7) SEE NOTE
-48239-10	CAPACITOR, fixed: NT-48239 w/1 mf p/m 10%. NOTE: RAA-3; RAA-4 (2); RAB (2); RAB-1 (2); RAB-2 (3); RAB-3 (3); RAB-4 (3).	8/22/32 RE48A134 RE13A488		16-C-48812-8478				CRV	CP-102	CRV	M-66003-1 sub1	RAA RAA-2 SEE NOTE
-48239-A	CAPACITOR, fixed: paper dielectric; 1 mf plus 10, minus 3%; 400 vdcw; HS metal can; 2 21/32" lg x 2 3/8" wd x 1" h; parolite impr and sealed; two solder lug term on front of case 7/16" h from bottom 1" c to c; no int gnd connection; two mtg ft 13/16" lg integral w/ top of case w/two 0.154" diam mtg holes 2 3/4" c to c; for replacement use NT-48240-A.	2/2/38 RE48A134 RE13A488		16-C-48793-2678	N16-C-11397			CRV				
-48239-A10	CAPACITOR, fixed: NT-48239-A w/1 mf p/m 10%.	2/2/38 RE48A134 RE13A488		16-C-48814-2668				CRV				
-48240	CAPACITOR, fixed: paper dielectric; 1 mfd plus 10 minus 3%; 300vdcw; HS metal can; 2 21/32" h x 2 3/8" wd x 1" thk; parolite impr and sealed; two solder lug term on front of case 7/16" h f on bottom 1/2" c to c; no int gnd connections; two mtg ft 13/16" lg integral w/top of case w/two 0.154" diam mtg holes on same axis 2 3/8" apart; for replacement use NT-48240-A10.	8/22/32 RE48A134 RE13A488		16-C-48791-8483	N16-C-11384-14			CRV				RAA RAB
-48240-10	CAPACITOR, fixed: NT-48240 w/1 mf p/m 10%.	8/22/32 RE48A134 RE13A488		16-C-48812-8483						CRV	M-66003-2 sub1	RAB RAB-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-79

RESTRICTED

RESTRICTED

SHEET 48 - 80

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48240-A	CAPACIT R, fixed: 12/22/36 paper dielectric; 1 mf plus 10, minus 3%; 400 vdcw; HS metal can; 2 21/32" h x 2 3/8" wd x 1" thk; paralite impr and sealed; two solder lug term on front of case 7/16" h from bottom 1" c to c; no int gnd connections; two mtg ft 13/16" lg integral w/top of case w/two 0.154" diam mtg holes in same axis 2 3/8" c to c.	RE48A134 RE13A488		16-C-48793-2668				CRV				
-48240-A10	CAPACITOR, fixed: 12/22/36 NT-48240-A w/ 1 mfd p/m 10%.	RE13A488 RE48A134		16-C-48812-8478	N16-C-11398			CRV				
-48241	CAPACITOR, fixed: 8/22/32 paper dielectric; two sect; 2 mf/2 mf plus 10 minus 3%; 300/300 vdcw; HS metal can; 4 13/16" h x 2 15/16" wd x 1 5/16" thk; wax impr and filled; two red and one black ins flex wire term out of side near bottom 6" lg; no int gnd connections, one side of each section is common; four ears integral with bottom of can with four 0.154" diam mtg holes 2 3/16" x 1 19/32" mtg/c.	RE48A179 RE13A488		16-C-53988-8441				CRV	CP-92			HAA RAB
-48241-10	CAPACITOR, fixed: 8/22/32 NT-48241 w/2 mf/ 2 mf p/m 10%.	RE48A179 RE13A488		16-C-54020-1801				CRV	CP-92	CRV	P-64918-1 sub1	
-48242	CAPACITOR, fixed: 8/22/32 paper dielectric; 100,000 mmf plus 10 minus 3%; 1,000 vdcw; HS metal can; 2 1/2" h x 2 3/8" wd x 1" thk; oil impr and filled; two flex ins wire leads 6" lg on bottom; no int gnd connections; two integral mtg ft on bottom w/two 0.154" diam holes 2 3/4" c to c; superseded by NT-48242-A.	RE48A136		16-C-45759-8352				CRV	CP-93			HAA RAB
-48242-10	CAPACITOR, fixed: 8/22/32 NT-48242 w/100,000 mmf p/m 10%. NOTE: RAA-3; RAA-4; RAB; RAB-1; RAB-2; RAB-4(2); UA-2.	RE48A136		16-C-45780-8352	N16-C-11324			CRV	CP-93	CRV	M-64573-1 sub1	HAA RAA-2 SEE NOTE:

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-80

RESTRICTED

RESTRICTED

SHEET 48 - 81

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48242-A	CAPACITOR, fixed: 12/22/36 Paper dielectric; 100,000 mmf plus 10 minus 3%; 1000 vdcw; HS metal can; 2 3/4" h x 2 3/8" wd x 1" thk; wax impr and sealed; two ins wire leads on end of case in ctr extending 6" from cover w/ 5/16" of length bare; no int gnd connections; two mtg ft 13/16" lg integral w/bottom of case w/two 0.154" diam mtg holes 2 3/4" c to c.	RE48A136 RE13A488		16-C-45759-8342				CRV				
-48242-A10	CAPACITOR, fixed: 12/22/36 NT-48242-A w/100,000 mmf p/m 10%.	RE48A136 RE13A488		16-C-45780-9192	N16-C-11324-1			CRV				
-48243	CAPACITOR, fixed: 8/22/32 paper dielectric; 10 mf plus 10 minus 3%; 400 vdcw; HS metal can; 4 19/32" lg x 2 1/4" wd x 5 5/16" h; wax impr and sealed; two solder lug term 3/8" h on bottom of case 1 1/4" from c to c; no int gnd connection; two mtg fl 2 1/4" lg integral w/bottom of case w/four 0.242" diam mtg holes on 5 3/32" ctr; for replacement use NT-48243-B.	RE48A137 RE13A488		16-C-51834-2436	N16-C-11685			CRV	CP-94			RAA RAB
-48243-10	CAPACITOR, fixed: 8/22/32 NT-48243 w/10 mf p/m 10%.	RE48A137 RE13A488		16-C-51855-2437				CRV	CP-94	CRV	P-64919-1	RAA RAA-2 RAA-3
-48243-A	CAPACITOR, fixed: 12/1/34 paper dielectric; 10 mf plus 10 minus 3%; 400 vdcw; HS metal can; 4 19/32" lg x 2 1/4" wd x 5 5/16" h; wax impr and sealed; two solder lug term 3/8" h on bottom of case 1 1/4" from c to c; no int gnd connection; two mtg fl 2 1/4" lg integral w/bottom of case w/ four 0.242" diam mtg holes on 5 3/32" ctr; for replacement use NT-48243-B.	RE48A137 RE13A488		16-C-51834-2436				CRV	ES6-A-1			RAA RAB
-48243-A10	CAPACITOR, fixed: 12/1/34 NT-48243-A w/10 mf p/m 10%. NOTE: RAB-2 (2); RAB-3 (2); UA-2 (2).	RE48A137 RE13A488		16-C-51855-2437				CRV	ES6-A-1	CRV	P-72014-2 P-64919-1	RAB RAB-1 SEE NOTE:

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-81

RESTRICTED

RESTRICTED

SHEET 48 - 82

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48243-B	CAPACITOR, fixed: 12/22/36 paper dielectric; 10 mf plus 10 minus 3%; 400 vdcw; HS metal can; 4 19/32" lg x 2 1/4" wd x 5 5/16" h; wax impr and sealed; two solder lug term 3/8" h on bottom of case 1 1/4" from c to c; no int gnd connection; two mtg fl 2 1/4" lg integral w/bottom of case w/four 0.242" diam mtg holes on 5 3/32" ctr.	RE48A137 RE13A488		16-C-51834-2436	N16-C-11685			CRV	MI-2393-2			
-48243-B10	CAPACITOR, fixed: 12/22/36 NT-48243-B w/10 mf p/m 10%.	RE48A137 RE13A488		16-C-51855-2437				CRV	MI-2393-2	CRV	P-72014-502	RAA-4 (2)
-48244	CAPACITOR, fixed: 8/22/32 paper dielectric; 2 mf plus 10 minus 3%; 300 vdcw; HS metal can; 3 17/64" h x 2 15/16" wd x 1 5/16" thk; oil impr asphalt compound filled; two flex wire leads 6" lg on top; no int gnd connections; no mtg holes, no mtg bkts supplied; superseded by NT-48256-A.	RE48A135		16-C-49171-9154	N16-C-11469-25			CRV CRV	CP-95 MI-2394-1	CRV	M-64574-1	RAA RAB
-48244-10	CAPACITOR, fixed: 8/22/32 NT-48244 w/2 mf p/m 10%; superseded by NT-48244-A10. NOTE: RAA; RAA-2; RAA-3; RAA-4 (4); RAB; RAB-1; RAB-2; RAB-3; RAB-4.	RE48A135		16-C-49192-9154	N16-C-11469-25			CRV	MI-2394-1	CRV	M-64574-1	NM-3 (4) QC-3 (4) SEE NOTE:
-48244-A	CAPACITOR, fixed: 12/22/36 paper dielectric; 2 mfd plus 10 minus 3%; 400 vdcw; HS metal can; 2 15/16" lg x 1 5/16" wd x 3 17/64" h; wax impr and sealed; two ins wire leads on top of case in ctr extending 6" outside of cover plus 5/16" bare wire; no int gnd connections; four mtg fl 3/8" wd integral w/top of case w/four 0.154" diam mtg holes 2 3/16" c to c; for replacement use NT-48256-A.	RE48A135 RE13A488		16-C-49173-4891	N16-C-11475			CRV				
-48244-A10	CAPACITOR, fixed: 12/22/36 NT-48244-A w/2 mf p/m 10%; for replacement use NT-48256-A10.	RE48A135 RE13A488		16-C-49194-4891				CRV				

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48 82

RESTRICTED

RESTRICTED

SHEET 48 - 83

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48245	CAPACITOR, fixed: mica; 100 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	8/22/32 RE48A126 16C40										
-48245-10	CAPACITOR, fixed: NT-48245 w/100 mmf p/m 10%.	8/22/32 RE48A126 16C40		16-C-28558-1882				CRV	T			MF-2 MB-3
-48246	CAPACITOR, fixed: CANCELLED: for replacement use NT-48223-A.	8/29/32 RE48A110						CAY	9552814			
-48247	CAPACITOR, fixed: mica; 400 mmf; 5,000 vdcw, 10 amp at 4,000 kc; case 2 1/2" lg x 2 1/2" wd x 1 9/16" h; sheet metal case; one tab term 1" lg at ea end w/one 0.196" diam hole 4" c to c; two mtg ft on bottom ea w/two 0.201" diam holes on 2" x 3" mtg/c.	9/1/32 RE48A253 16C40										
-48247-B5	CAPACITOR, fixed: NT-48247 w/400 mmf p/m 5%; temp coef 1tr B.	9/1/32 RE48A253 16C40		16-C-29926-7220				CRV	UC-2722-A	CRV	7600624	GH-1
-48248	CAPACITOR, fixed: paper dielectric; 12 mf plus 10 minus 3%; 825 vdcw; HS metal can; 4 13/16" h x 3 3/4" wd x 2 1/2" thk; oil impr and filled; two ins stud and nut term 2" c to c on top ctr line; no int gnd connections; superseded by T-48248-A.	9/12/32 RE48A110		16-C-51899-8245				CG	9CE1A32	CG	H-3931073-3rev1	TBA-1
-48248-A	CAPACITOR, fixed: paper dielectric; 12 mf plus 10 minus 3%; 800 vdcw; HS metal can; 4 13/16" h x 3 3/4" wd x 2 1/2" d; oil impr and filled; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections; same as NT-48248 except 800 vdcw and complies w/RE13A488.	1/27/38 RE48A110T RE13A488		16-C-51899-8248								
-48249	CAPACITOR, fixed: mica; 1,000 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	9/16/32 RE48A126 16C40										
-48249-10	CAPACITOR, fixed: NT-48249 w/1,000 mmf p/m 10%.	9/16/32 RE48A126 16C40		16-C-31090-4265				CRV	T			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-83

RESTRICTED

RESTRICTED

SHEET 48 - 84

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48250	CAPACITOR, fixed: 9/16/32 mica; 4,000 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam hole, 1 3/16" c to c.	RE48A126 16C40										
-48250-10	CAPACITOR, fixed: 9/16/32 NT-48250 w/4,000 mmf p/m 10%.	RE48A126 16C40		16-C-32462-1077				CRV	T			
-48251	CAPACITOR, fixed: 9/16/32 mica; 6,000 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 5/16" max thk; metal clad; two solder lug term one at ea end, ea w/one 3/32" diam hole on 1 3/16" ctr and one elliptical slot 9/16" x 7/32".	RE48A227 16C40										
-48251-5	CAPACITOR, fixed: 9/16/32 NT-48251 w/ 000 mmf p/m 5%.	RE48A227 16C40		16-C-32652-6523				CRV	T	CAY	7809542-1	GP-3
-48251-10	CAPACITOR, fixed: 9/16/32 NT-48251 w/6000 mmf p/m 10%.	RE48A227 16C40		16-C-32857-7003	N16-C-10445			CRV	T-3	CRV	K-36185-551	SB(2)
-48252	CAPACITOR, fixed: 9/22/32 mica; 8,000 mmf; 3,000 vdcw, 15 amp at 3,000 kc, 15 amp at 1,000 kc, 9 amp at 300 kc, 5 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48252-B5	CAPACITOR, fixed: 9/22/32 NT-48252 w/8,000 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-33223-3687	N16-C-10478-250			CRV	UC-2892-K	CRV	K-802265-12	TAJ-3
-48253	CAPACITOR, fixed: 9/27/32 mica; 1,000 mmf; 5,000 vdcw, 4.0 amp at 3,000 kc, 2.5 amp at 1,000 kc, 1.5 amp at 300 kc, 0.5 amp at 100 kc; case 2 11/32" lg x 1 5/8" wd x 27/32" h; metal case; two screw term #6-32 thd w/ ins 15/16" lg on ea end.	RE48A257 16C40										
-48253-B5	CAPACITOR, fixed: 9/27/32 NT-48253 w/1000 mmf p/m 5%; temp coef ltr B.	RE48A257 16C40		16-C-31087-3769				CRV	UC-2737	CRV	K-2101627WS	MB-2 MB-3
-48254	CAPACITOR, fixed: 9/27/32 mica; 1,000 mmf; 5,000 vdcw, 4.0 amp at 3,000 kc, 2.5 amp at 1,000 kc, 1.5 amp at 300 kc, 0.5 amp at 100 kc; case 2 11/32" lg x 1 5/8" wd x 27/32" h; metal case; two screw term #6-32 thd w/ ins 3/4" lg on ea end.	RE48A257 16C40										
-48254-B5	CAPACITOR, fixed: 9/27/32 NT-48254 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A257 16C40		16-C-31087-3768				CRV	UC-2738	CRV	K-2101627WS	MB-3 MB-2

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-84

RESTRICTED

RESTRICTED

SHEET 48 - 85

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48255	CAPACITOR, fixed: mica; 40 mmf; 2,500 vdcw; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	10/6/32 RE48A112 JAN-C-5										
-48255-A10	CAPACITOR, fixed: NT-48255 w/40 mmf p/m 10%; temp coef ltr A.	10/6/32 RE48A112 JAN-C-5	CM55A400K	16-C-27398-7662				CD	9-54040			
-48255-B2	CAPACITOR, fixed: NT-48255 w/40 mmf p/m 2%; temp coef ltr B.	10/6/32 RE48A112 JAN-C-5	CM55B400G	16-C-27388-5707	N16-C-9843-68			CSL CRV	KMW2.5-44-2 "P"	CRV	K-35484-32rev9	CK-1
-48255-B5	CAPACITOR, fixed: NT-48255 w/40 mmf p/m 5%; temp coef ltr B.	10/6/32 RE48A112 JAN-C-5	CM55B400J	16-C-27393-7187	N16-C-9843-69			CD	9L-54040			CK-1
-48255-B10	CAPACITOR, fixed: NT-48255 w/40 mmf p/m 10%; temp coef ltr B.	10/6/32 RE48A112 JAN-C-5	CM55B400K	16-C-27398-7667	N16-C-9843-70			CD	9L-54040			
-48256	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 300 vdcw; HS metal can; 3 1/4" h x 2 15/16" wd x 1 5/16" thk; oil impr and filled; two ins flex wire leads 12" lg at ctr of top; no int gnd connections; four integral mtg ft at the top corners w/ four 3/8" diam holes on 2 3/16" x 1 5/8" mtg/c; superseded by NT-48256-A.	10/7/32 RE48A135		16-C-49171-9144	N16-C-11469-50			CRV	CP-95	CRV	M-64574-2 K-802265-14	
-48256-10	CAPACITOR, fixed: NT-48256 w/2 mf p/m 10%; superseded by NT-48256-A10.	10/7/32 RE48A135		16-C-49192-9144				CRV	CP-95	CRV	P-702260-7	TAJ-4 (3)
-48256-A	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 400 vdcw; HS metal can; 2 15/16" lg x 1 5/16" wd x 3 17/64" h o/a; wax impr and sealed; two ins wire leads on top of case in ctr extending 6" outside of cover plus 5/16" bare wire; four mtg ft 3/8" wd integral w/ top of case w/ four 0.154" diam mtg holes 2 3/16" c to c; same as NT-48256 except 400 vdcw and complies with RE13A488.	12/19/40 RE48A135 RE13A488		16-C-49173-4891								
-48256-A10	CAPACITOR, fixed: NT-48256-A w/2 mf p/m 10%.	12/19/40 RE48A135 RE13A488		16-C-49194-4891	N16-C-11474							

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-85

RESTRICTED

RESTRICTED

SHEET 48 - 86

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48257	CAPACITOR, fixed: 10/7/32 paper dielectric; 500,000 mmf minus 10 plus 25%; 400 vdcw; ES metal can; 2 15/16" lg x 1 5/16" wd x 3 17/64" h; wax impr and filled; two lns wire leads on top of case in ctr extending 12" lg outside of cover plus 5/16" bare wire; no int gnd connections; four mtg ft 3/8" wide integral w/ top of case w/ four 0.154" diam mtg holes on 2 3/16" x 1 9/32" mtg/c.	RE48A135 RE13A488		16-C-47335-1107				CRV	CP			TAJ-3
-48257-10	CAPACITOR, fixed: 10/7/32 NT-48257 w/500,000 mmf p/m 10%.	RE48A135 RE13A488		16-C-47294-4891				CRV	CP	CRV	P-702260-8	TAJ-4
-48258	CAPACITOR, fixed: 10/7/32 paper dielectric; 3.5 mf minus 10 plus 25%; 3000 vdcw; ES metal can; 5 5/8" h x 9 1/2" wd x 4 5/8" thk; filled w/ asphalt compound; two stud and nut term on per pillars 1 1/8" h x 3" c to c on top; no int gnd connections; two integral mtg ft on bottom w/three 1/4" diam holes 4 1/2" c to c and 3 1/2" c to c in ea ft w/ 5.092" c to c from ft to ft.	RE48A180 RE13A488		16-C-49805-1610				CRV	XA8415	CRV	P-64966 rev 0	TAJ-3
-48258-10	CAPACITOR, fixed: 10/7/32 NT-48258 w/ 3.5 mf p/m 10%.	RE48A180 RE13A488		16-C-49775-7287				CRV	XA8415			
-48259	CAPACITOR, fixed: 10/7/32 CANCELLED: for replacement use NT-48131-A.	RE48A117										TAJ-3
-48260	CAPACITOR, fixed: 10/7/32 CANCELLED: for replacement use NT-48132-A.	RE48A117										TAJ-3
-48261	CAPACITOR, fixed: 10/7/32 CANCELLED: for replacement use NT-48360-A.	RE48A134						CRV		CRV	P-66123-1	TAJ-3
-48262	CAPACITOR, fixed: 10/13/32 mica; 3,000 mmf; 600 vdcw, 1000v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48262-A10	CAPACITOR, fixed: 10/13/32 NT-48262 w/3,000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-32198-4751				CD	9L-12030	CBM	744-316	NMC-1
-48262-B10	CAPACITOR, fixed: 10/13/32 NT-48262 w/3,000 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-32198-4756	N16-C-10327	R16-C-10327		CD	9L-12030			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-86

RESTRICTED

RESTRICTED

SHEET 48 - 87

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48263	CAPACITOR, fixed: 10/17/32 mica; 10,000 mmf; 1,000 vdcw, 8 amp at 3,000 kc, 5.0 amp at 1,000 kc, 3.5 amp at 300 kc, 2.0 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft, ea w/ 0.173" diam hole, mtg holes 1 1/4" c to c.	RE48A123 16C40										
-48263-B5	CAPACITOR, fixed: 10/17/32 NT-48263 w/10,000 mmf p/m 5%; temp coef ltr B.	RE48A123 16C40		16-C-33618-1155				CRV	UC-2233			TAU-1
-48264	CAPACITOR, fixed: 10/31/32 CANCELLED: for replacement use NT-48268.	RE48A221 16C40						CD				TAU-1
-48265	CAPACITOR, fixed: 10/31/32 mica; 2,000 mmf; 6,000 vdcw, 9.0 amp at 3000 kc, 5.0 amp at 1,000 kc, 3.0 amp at 300 kc, 1.8 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two axial wire leads 5" lg; two mtg ft both on same side at bottom, ea w/ one 0.173" diam hole on 1 1/4" mtg/c.	RE48A225 16C40										
-48265-B5	CAPACITOR, fixed: 10/31/32 NT-48265 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A225 16C40		16-C-31799-6851								
-48266	CAPACITOR, fixed: 10/31/32 mica; 50,000 mmf; 1,000 vdcw, 20 amp at 3,000 kc, 25 amp at 1,000 kc, 25 amp at 300 kc, 15 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/ two 17/64" diam hole in ea 4 1/4" c to c.	RE48A122 16C40										
-48266-B5	CAPACITOR, fixed: 10/31/32 NT-48266 w/50,000 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-35227-1869	N16-C-10592			CD	PL-507-50			TAU-1
-48267	CAPACITOR, fixed: 10/31/32 mica; 12,500 mmf; 1,000 vdcw, 18 amp at 3,000 kc, 18 amp at 1,000 kc, 15 amp at 300 kc, 9 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/ two 17/64" diam hole in ea 4 1/4" c to c.	RE48A122 16C40										
-48267-B5	CAPACITOR, fixed: 10/31/32 NT-48267 w/12,500 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-33855-5065				CD	PL-510-50			TAU-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-87

RESTRICTED

RESTRICTED

SHEET 48 - 88

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48268	CAPACITOR, fixed: 10/31/32 mica; 30,000 mmf; 1,000 vdcw, 20 amp at 3,000 kc, 22 amp at 1,000 kc, 22 amp at 300 kc, 15 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/ two 17/64" diam hole 4 1/4" c to c.											
-4 268-B5	CAPACITOR, fixed: 10/31/32 NT-48268 w/30,000 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-34725-9265	N16-C-10575-10			CD	PL-509-50			
-48269	CAPACITOR, fixed: 10/31/32 mica; 40,000 mmf; 1,000 vdcw, 20 amp at 3,000 kc, 25 amp at 1,000 kc, 22 amp at 300 kc, 15 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/ two 17/64" diam hole in ea 4 1/4" c to c.											
48269-B5	CAPACITOR, fixed: 10/31/32 NT-48269 w/40,000 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-34989-7265	N16-C-10589-1			CD	PL-508-50			TAU-1
-48270	CAPACITOR, fixed: 10/31/32 mica; 200 mmf; 10,000 vdcw, 5.0 amp at 3,000 kc, 1.6 amp at 1,000 kc, 0.5 amp at 300 kc, 0.16 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/ two 17/64" diam hole in ea 4 1/4" c to c.	RE48A122 16C40										
-48270-B5	CAPACITOR, fixed: 10/31/32 NT-48270 w/200 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-29268-1271	N16-C-9972-14			CD	PL-308-50			TAU-1
-48271	CAPACITOR, fixed: 10/31/32 mica; 600 mmf; 5000 vdcw, 10 amp at 3000 kc, 7 amp at 1000 kc, 4 amp at 300 kc, 1.5 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48271-B5	CAPACITOR, fixed: 10/31/32 NT-48271 w/600 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-30322-4326	N16-C-10050-2			CD	PL-499-50			TAU-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-88

RESTRICTED

RESTRICTED

SHEET 48 - 89

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48272	CAPACITOR, fixed: 10/31/32 mica; 400 mmf; 5000 vdcw, 8 amp at 3000 kc, 6 amp at 1000 kc, 3 amp at 300 kc, 1.5 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/ two 17/64" diam hole in ea 4 1/4" c to c.	RE48A122 16C40										
-48272-B5	CAPACITOR, fixed: 10/31/32 T-48272 w/400 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-29926-7326	N16-C-10011-1			CD	PL-506-50			TAU-1
-48273	CAPACITOR, fixed: 10/31/32 mica; 90 mmf; 6,000 vdcw, 4.0 amp at 3000 kc, 2.0 amp at 1000 kc, .6 amp at 300 kc, .2 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/ two 17/64" diam hole in ea 4 1/4" c to c.	RE48A122 16C40										
-48273-B5	CAPACITOR, fixed: 10/31/32 NT-48273 w/90 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-28370-6056	N16-C-10489-2 N16-C-9923-15-4			CD	PL-501-50			TAU-1
-48274	CAPACITOR, fixed: 10/31/32 mica; 950mmf; 5000 vdcw, 15 amp at 3000 kc, 15 amp at 1000 kc, 8 amp at 300 kc, 3 amp at 100 kc; case 5" diam x 4" h; ceramic case; one fl elliptical end term ea end w/ two 3/8" diam holes in ea term 5 3/4" c to c.	RE48A116 16C40										
-48274-B5	CAPACITOR, fixed: 10/31/32 NT-48274 w/950mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-31023-8989	N16-C-10081-23			CD	PL-505-51			TAU-1
-48275	CAPACITOR, fixed: 10/31/32 mica; 250 mmf, 30,000 vdcw, 14.0 amp at 3000 kc, 10.0 amp at 1000 kc, 4.0 amp at 300 kc, 1.5 amp at 100 kc; case 5 3/4" h x 5" diam; low-loss ceramic case; two elliptical cast aluminum end cap term, ea w/ two 0.377" diam holes 5 3/4" c to c.	RE48A237 16C40										
-48275-B5	CAPACITOR, fixed: 10/31/32 NT-48275 w/250 mmf p/m 5%; temp coef tr B.	RE48A237 16C40		16-C-29479-9800				CD	PL-516-52			TAU-1
-48276	CAPACITOR, fixed: 11/7/32 mica; 50 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" d; metal clad; two axial lug term ea w/one 3/32" diam holes, 1 3/16" c to c.	RE48A126 16 40										
-48276-10	CAPACITOR, fixed: 11/7/32 NT-48276 w/50 mmf p/m 10%.	RE48A126 16C40		16-C-27634-8877				CRV	T			LE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-89

RESTRICTED

RESTRICTED

SHEET 48 - 90

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48277	CAPACITOR, fixed: 11/8/32 mica; 250 mmf; 1000 vdcw, 1 amp at 3000 kc, 0.4 amp at 1000 kc, 0.15 amp at 300 kc, 0.06 amp at 100 kc; case 2 1/8" lg x 1" wd x 3/8" thk; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom w/ two 0.1" diam mtg holes on 1 1/4" mtg/c.	RE48A106 16C40										
-48277-B5	CAPACITOR, fixed: 11/8/32 NT-48277 w/250 mmf p/m 5%; temp coef ltr B.	RE48A106 16C40		16-C-29476-7257				CD	577			MB-3 MF-2
-48278	CAPACITOR, fixed: 11/8/32 mica; 10000 mmf; 1000 vdcw max, 9 amp at 3000 kc, 5 amp at 1000 kc, 3.5 amp at 300 kc, 2 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term 7/16" lg on top 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48392.	RE48A131 16C40										
-48278-A5	CAPACITOR, fixed: 11/8/32 NT-48278 w/10,000 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-33618-1109				CD	PL-150-6			TAU-1
-48279	CAPACITOR, fixed: 11/8/32 mica; 2000 mmf; 6000 vdcw, 9 amp at 3000 kc, 5 amp at 1000 kc, 3 amp at 300 kc, 1.8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/ two mtg holes 3/16" diam 2 5/8" c to c.	RE48A131 16C40										
-48279-B2	CAPACITOR, fixed: 11/8/32 NT-48279 w/2,000 mmf p/m 3%; temp coef ltr B. NOTE: TAB-6 (2); TAB-7.	RE48A131 16C40		16-C-31794-5341				CSL	XSEW-6-22	CAY	T-7606683-24	TAU-1 TAB-5 SEE NOTE:
-48279-B5	CAPACITOR, fixed: 11/8/32 NT-48279 w/2,000 mmf p/m 5%; temp coef ltr B. NOTE: TRA-8; TBA-10; TBA-11; TBC-5 (7); TBU-1; TBU-2; TBU-3; TBU-4.	RE48A131 16C40		16-C-31799-6825	PL6-C-10284			CD CSL	PL-217-6LS XSEW-6-22-5	CAY CAY CG CAY	T-7609144-39 T-7606683-40 P-7762751-21 P-7762166-1 T-7607321-47	TAB-5 TAB-6 TAB-7 TAQ-10(2) TBA-6 SEE NOTE
-48279-C5	CAPACITOR, fixed: 11/8/32 NT-48279 w/2000 mmf p/m 5%; temp coef ltr C.	RE48A131 16C40		16-C-31799-6830				CD	PL-217-6L	CG	P-7762166-1	TAQ-5 (2) TAQ-6 (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-90

RESTRICTED

RESTRICTED

SHEET 48 - 91

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48280	CAPACITOR, fixed; 11/8/32 paper dielectric; 4 mf plus 10 minus 3%; 2500 vdcw; HS metal can; case 5 5/16" lg x 3 11/16" wd x 9 1/4" h; oil impr and filled; two ceramic ins screw type term 2" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 1/4" diam mtg holes ctr 5 7/8" x 2 1/4" mtg/c; for replacement use only.	RE48A159 RE13A488		16-C-49944-3480				CD	PL-50950	CD	4529 rev 0	TAU-1
-48281	CAPACITOR, fixed; 11/8/32 paper dielectric; 500,000 mmf plus 10 minus 3%; 1000 vdcw; HS metal can; case 3 3/4" lg x 1 1/4" wd x 5" h; oil impr and filled; two ceramic ins screw type term 1 5/8" h located on top 1 1/2" c to c; no int gnd connections; two mtg fl on bottom of case, ea with two 0.166" diam mtg holes ctr 4 1/4" x 7/8" mtg/c; for replacement use only.	RE48A159 RE13A488		16-C-47280-2442				CCA	DA-14			TAU-1
-48282	CAPACITOR, fixed; 11/8/32 paper dielectric; 500,000 mmf plus 10 minus 3%; 2500 vdcw; HS metal can; case 3 3/4" lg x 2 1/2" wd x 5" h; oil impr and filled; two ceramic ins screw type term 1 5/8" h located on top 1 1/2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 0.166" diam mtg holes ctr 4 1/4" c to c.	RE48A159 RE13A488		16-C-47280-2698				CCA	DA-15			TAU-1
-48283	CAPACITOR, fixed; 11/8/32 paper dielectric; 4 mf plus 10 minus 3%; 500 vdcw; HS metal can; case 3 3/4" lg x 1 3/4" wd x 5" h; oil impr and filled; two screw type term 9/16" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl 1" wd on side of case, ea w/two 0.166" diam holes on 4 1/4" x 1 1/4" mtg/c.	RE48A158 RE13A488		16-C-49935-3546				CCA	DA-16			TAU-1
-48284	CAPACITOR, fixed; 11/8/32 paper dielectric; 150,000 mmf plus 10 minus 3%; 2500 vdcw; HS metal can; case 3 3/4" lg x 1 1/4" wd x 5" h; oil impr and filled; two ceramic ins screw type term 1 5/8" h located on top 1 1/2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 0.166" diam mtg holes 7/8" apart ctr 4 1/4" c to c.	RE48A159 RE13A488		16-C-49954-2698				CCA	DA-18			TAU-1
-48284-2	CAPACITOR, Fixed; Navy Type 48284 w/150000 mmf p/m 2%.	RE48A159 RE13A488	6/10/49	16-C-49916-1100	N16-C-11338-85			CCA	DA-18			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-91

RESTRICTED

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-48285	CAPACITOR, fixed: 11/9/32 mica; 100,000 mmf; 3000 vdcw, 20 amp at 1000 kc, 15 amp at 300 kc, 10 amp at 100 kc; case 3 3/16" lg x 2 5/8" wd x 3" h; cast metal case; one screw term #4-14 thd under top plate, opening for connection in front; one mtg fl on bottom sides ea w/one 5/16" diam hole on 4 1/8" mtg/c.	RE48A259 16040										
-48285-B5	CAPACITOR, fixed: 11/9/32 NT-48285 w/100,000 mmf p/m 5%; temp coef 1tr B.	RE48A259 16040		16-C-36151-3106				CRV	00-1827			
-48286	CAPACITOR, fixed: 11/12/32 paper dielectric; 1 mfd plus 10 minus 3%; 200 vdcw; HS metal can; 2" lg x 1 3/4" wd x 13/16" h; oil filled; two solder lug term 5/16" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 7/16" c to c; for replacement use NT-48286-A.	RE13A488		16-C-48790-4232				CD	BW-30		TAU-1	
-48286-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 1 mfd plus 10 minus 3%; 400 vdcw; HS metal can; 2" lg x 1 3/4" wd x 13/16" h; oil filled; two solder lug term 5/16" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 7/16" c to c.	RE48A129 RE13A488		16-C-48793-1196	N16-C-11397-13			CD CSL	DE-4100 YDREW-1	QWI CRV CML	24168 K-866451-23	LS LS-1 SD (2) SDa (2)
-48286-A20	CAPACITOR, fixed: 11/23/36 NT-48286-A w/1 mfd p/m 20%.	RE48A129 RE13A488		16-C-48845-7552				CD	DE-4100	CRV	Q815257-H	
-48287	CAPACITOR, fixed: 11/12/32 paper dielectric; 500,000 mmf plus 10 minus 3%; 400 vdcw; HS metal can; 2" lg x 1 3/4" wd x 13/16" h; oil filled; two solder lug term 5/16" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 7/16" c to c; for replacement use NT-48287-A.	RE13A488		16-C-47273-1186				CD	BW-28		TAU-1	
-48287-A5	CAPACITOR, FIXED: 11/4/47 Navy Type 48287-A w/500,000 mmf p/m 5%.			16-C-47255-3109				CD	DYR-6050-13	CEM	744-544	QGA QGA-1

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 93

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48287-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 500,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; 2" lg x 1 3/4" wd x 13/16" h; oil filled; two solder lug term 5/16" h on side spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 7/16" c to c.	RE13A488 RE48A129		16-C-47276-3890	N16-C-11358		3DA500-97.22	CD CD	PC-891 DYR-6050	CBM	744-190	MK-1 MK-2
-48287-A10	CAPACITOR, fixed: 11/23/36 NT-48287-A w/500,000 mmf plus 10%. NOT : WFA; SP (3); SP-1M (3).	RE13A488 RE48A129		16-C-47297-3880	N16-C-11358			CD CSF	DYR-6050 2528-4	CBM CBM CG	744-294 744-190 83017	NGA MK-7 NGA (6) SEE NOTE
-48287-A20	CAPACITOR, fixed: 11/23/36 NT-48287-A w/500,000 mmf p/m 20%.	RE48A129 RE13A488		16-C-47327-7935				CD CD	PC-891 DYR-6050	CRR	QB15258-H	
-48287-B	CAPACITOR, fixed: 3/31/42 paper dielectric; 500,000 mmf plus 10 minus 3%; 1000 vdcw, 1000v DC test; HS metal can; 2" lg x 1 3/4" wd x 13/16" h; oil filled; two solder lug term 5/16" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, with 3/16" diam mtg holes spaced 2 3/8" c to c.	R 13A488 RE48A129		16-C-47279-7522			3DA500-104	CD	DYR-10050			
-48287-B10	CAPAC OR, fixed: 3/31/42 NT-48287-B w/500,000 mmf p/m 10%.	RE13A488 RE48A129		16-C-47300-7522	N16-C-11361			CD CAW CGF CBV CSL CSF CTD	DYR-10050 1030M-.5 7517 12M-18-20 XDMRW10-.5-10 PBTS-414A RL0-1050	CW CW	ESL-682055-2rev2 ES-682063-71	MK-9 SJ-1 SV MK-18 MK-27 MK-28 MK-10Mod5

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109 (A)
SUPPLEMENT # 1

SHEET 48-93

RESTRICTED

RESTRICTED

SHEET 48 - 94

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48288	CAPACITOR, fixed: 11/12/32 paper dielectric; 250,000 mmf plus 10 minus 3%; 200 vdcw; BS metal can; 1 13/16" lg x 1" wd x 3/4" h; dykanol filled; two solder lug term 3/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48288-B.	RE13A488 RE48A129		16-C-46319-3641				CD	DYR-60025			
-48288-10	CAPACITOR, fixed: 11/12/32 NT-48288 w/250,000 mmf p/m 10%; for replacement use NT-48288-B10. NOTE: RAH; RAH-1.	RE48A129 RE13A488		16-C-46340-3641				CD	DYR-60025	CBS	RA-161	TAU-1 RAG (4) RAG-1 (4) SEE NOTE
-48288-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 250,000 mmf plus 10 minus 3%; 600 vdcw; BS metal can; 1 13/16" lg x 1" wd x 15/16" h; oil impr and filled; two solder lug term 1/2" h on side spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c. NOTE: QFD (4); SD (8); SD-a (8); SD-1 (8); SD-2 (8); SD-3 (8); SD-4 (8); SR-2; TAJ-8; EC (6).	RE13A488 R 48A129		16-C-46326-3119		R16-C-11338-27		CD CD CSF CAW	PC-1267 DYR-6025 2528-5 630	CRV CBM CJ CRB C V	K-866920-1 sub 1 744-149 116-164 A26203-1 14-1	L.P. L-1 LP-2 LP-3 LP-4 NJ-3 NJ-9 SEE NOTE
-48288-A5	CAPACITOR, fixed: 11/23/36 NT-48288-A w/250,000 mmf p/m 5%.	RE48A129 RE13A488		16-C-46305-3109			3DA250-21.8	CSL C F CAW	XDRM6-.25-5 2528 630	CBV	M-422765-5rev7	SA-2 SA-3 (9)
-48288-A10	CAPACITOR, fixed: 11/23/36 NT-48288-A w/250,000 mmf p/m 10%.	RE13A488 RE48A129		16-C-46347-3144	N16-C-11341-40		3DA250-60.1 3DA250-63.1 3DA250-171 3DA250-183	CD CGV C D CD CBV CAW CSF CD CD	PC-1267 12-M-3-20 RLO-625 DYR-6025-2 7502 630 2528-5 XDRM6-.25-10 PBT8-398A	COL CBM CB CRP CW CG	95N505U 744-149 744-291 35-5121 ES-682063-52 83009	NJ-4 NJ-7 SF-1 SJ-1 SL SL-a SL-1 SM-1 SO-1 SO-8 SEE NOTE
-48288-A20	CAPACITOR, fixed: 11/23/36 NT-48288-A w/250,000 mmf p/m 20%.	RE13A488 RE48A129		16-C-46377-7470			3DA250-107 3DA250-163	CD CD CAW	PC-1267 DYR-6025 630	COL COL	956 2058 40 956N505Y	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-94

RESTRICTED

RESTRICTED

SHEET 48 - 95

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48288-B	CAPACITOR, fixed: paper dielectric; 250,000 mmf plus 10 minus 3%; 1000 vdcw; HS metal can; 1 13/16" lg x 1" wd x 3/4" h; oil impr and filled; two solder lug term 5/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c.	12/17/41 RE13A488 RE48A129		16-C-46329-7092				CD CTD CGG CSL	DTR-10025 RLO-1025-SP 8A103913 XIMRW10-.25	CW CRR	ES-682028 iss 4 0A30879-16 rev C	
-48288-B5	CAPACITOR, fixed: NT-48288-B w/250,000 mmf p/m 5%.	12/17/41 RE13A488 RE48A129		16-C-46308-7092				CD CTD CGG CSL	DTR-10025 RLO-1025-SP 8A103913 XIMRW10-.25-5	CAY	T-7610979-6	ST SR SR-5
-48288-B10	CAPACITOR, fixed: NT-48288-B w/250,000 mmf p/m 10%.	12/17/41 RE13A488 RE48A129		16-C-46350-7092	N16-C-11342		3DA250-157.1	CD CTD CGG CSL	DTR-10025 RLO-1025-SP 8A103913 XIMRW10-.25-10	CAJ CW CRR	77180revC ESA-682063-70 0A30879-16revC	SM (3) SM-1 (3) SP (3) MK-22 (2) SEE NOTE:
-48289	CAPACITOR, fixed: mica; 100,000 mmf; 500 vdcw max 17 amp at 3000 kc, 20 amp at 1000 kc, 15 amp at 300 kc, 8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	11/14/32 RE48A131 16C40										
-48289-A5	CAPACITOR, fixed: NT-48289 w/100,000 mmf p/m 5%; temp coef 1tr A.	11/14/32 RE48A131 16C40		16-C-36149-9227				CD	FL-111-6			
-48290	CAPACITOR, fixed: mica; 1000 mmf; 600 vdcw, 1000v DC test; case 1 1/4" lg x 1 1/4" wd x 5/16" thk; molded bakelite case; two solder lug term ea w/one 3/16" hole on 1 3/4" mtg/c.	12/13/32 RE48A216 16C40										
-48290-A10	CAPACITOR, fixed: NT-48290 w/1,000 mmf p/m 10%; temp coef 1tr A.	12/13/32 RE48A216 16C40		16-C-31090-5551				CAW	1450	CRV	K-30095-2	RAE UA-2
-48291	CAPACITOR, variable: mica; compression type, 2 sect; 10 to 60 mmf ea sect; 2 7/16" lg x 2 7/32" wd x 1" h; solder lug term; two mtg holes 1 3/4" c to c; slotted screw adj; ceramic base.	1/6/33 16C40		16-C-65123-1901				CRV		CRV	K-806783-1rev0	RAA RAB DO (3) DO-1 (3) DO-2 (3) SEE NOTE:
	NOTE: DO-3 (3); DP (3); DP-1 (3); DP-2 (3); DP-3 (3); RAB-1; RAB-2; RAB-3; RAB-4											

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-95

RESTRICTED

RESTRICTED

SHEET 48 - 96

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USE# IN
-48292	CAPACITOR, variable: 1/6/33 mica; compression type, single sect; 10 to 60 mmf; 2 7/16" lg x 2 7/32" wd x 1" h; solder lug term; two mtg holes in base 1 3/4" c to c; slotted screw adj; ceramic base.	16040		16-C-64711-5501	N16-C-12590			CRV		CRV	K-806783-2rev0	RAA RAB (14) RAB-1 (14) RAB-2 (14) RAB-3 (14) RAB-4 (14)
-48293	CAPACITOR, variable: 1/6/33 mica; compression type, dual sect; 4 to 25 mmf ea sect 2 7/16" lg x 2 7/32" wd x 1" h; solder lug term; two mtg holes in base 1 3/4" c to c; slotted screw adj; ceramic base;	16040		16-C-65109-5465	N16-C-12591			CRV		CRV	K-806783-3rev0	RAA RAB (6) RAB-1 (6) RAB-2 (6) RAB-3 (6) RAB-4 (6)
-48294	CAPACITOR, variable: 1/6/33 mica; compression type, single sect; 4 to 25 mmf; 2 7/16" lg x 2 7/32" wd x 1" h; solder lug term; two mtg holes in base 1 3/4" c to c; slotted screw adj; ceramic base.	16040		16-C-64643-5321	N16-C-12592			CRV		CRV	K-806783-4rev0	RAA RAB (18) RAB-1 (18) RAB-2 (18) RAB-3 (18) RAB-4 (18)
-48295	CAPACITOR, variable: 1/6/33 mica; compression type, dual sect; 4 to 25 mmf sect one, 8 to 60 mmf sect two; 2 7/16" lg x 2 7/32" wd x 1" h; solder lug term; two mtg holes in base 1 3/4" c to c; slotted screw adj; ceramic base.	16040		16-C-65123-1001				CRV		CRV	K-806783-1rev0	RAA RAB (4) RAB-1 (4) RAB-2 (4) RAB-3 (4) RAB-4 (4)
-48296	CAPACITOR, variable: 1/6/33 mica; compression type, dual sect; 8 to 60 mmf sect one, 4 to 25 mmf sect two; 2 7/16" lg x 2 7/32" wd x 1" h; solder lug term; two mtg holes in base 1 3/4" c to c; slotted screw adj; ceramic base.	16040		16-C-65123-1021				CRV		CRV	K-806784-2rev0	RAA RAB (6) RAB-1 (6) RAB-2 (6) RAB-3 (6) RAB-4 (6)
-48297	CAPACITOR, variable: 1/6/33 mica; compression type, 3 sect; sect one and two 8 to 60 mmf ea sect, sect three 3 to 10 mmf; 2 7/16" lg x 2 7/32" wd; solder lug term; two mtg holes in base 1 3/4" c to c; slotted screw adj; ceramic base; third sect is var air, three plates, uses var mica capaci- tor term.	16040		16-C-65206-4601	N16-C-12655	R16-C-12655		CRV		CRV	K-806784-3rev0	RAA RAB (4) RAB-1 (4) RAB-2 (4) RAB-3 (4) RAB-4 (4)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-96

RESTRICTED

RESTRICTED

SHEET 48 - 97

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48298	CAPACITOR, variable: mica; compression type, 3 sect; sect one and two h to 25 mmf ea sect, sect three 3 to 10 mmf; 2 7/16" lg x 2 7/32" wd; solder lug term; two mtg holes in base 1 3/4" c to c; slotted screw adj; ceramic base; third sect is var air, three plates. uses var mica capacitor term.	1/6/33 16C40		16-C-65203-1901				CRV		CRV	X-806784-4rev0	RAA RAB-1 (4) RAB-2 (4) RAB-3 (4) RAB-4 (4)
-48299	CAPACITOR, FIXED: mica dielectric; 2500 mmf; 2500 vdcw; 1 25/32" lg x 1 11/32" wd x 15/32" thk case; molded phenolic case, low loss; one #6-32 NC tapped hole ea end, 1 1/4" c to c; add suffix indicating capacity tolerance in per cent.	6/8/33 RE48A112 JAN-C-5										
-48299-A10	CAPACITOR, fixed: NT-48299 w/2500 mmf p/m 10%; temp coef ltr A.	6/8/33 RE48A112 JAN-C-5	CN55A252K	16-C-32014-8662				CD	9-52025	CHS	X-806790-501	PC RAA-4 (9) TAZ-1 (3)
-48299-B5	CAPACITOR, FIXED: Navy Type 48299 w/2500 mmf p/m 5%; temp coef ltr B.	6/19/48 RE48A112 JAN-C-5		16-C-32009-8190				CSL	XMBW			
-48299-B10	CAPACITOR, fixed: NT-48299 w/2500 mmf p/m 10%; temp coef ltr B.	6/8/33 RE48A112 JAN-C-5	CN55B252K	16-C-32014-8667	N16-C-10317			CD	9L-52025			
-48300	CAPACITOR, fixed: mica; 1,800 mmf; 8,000 vdcw, 14.7 amp at 3000 kc, 12 amp at 1000 kc, 7 amp at 300 kc, 2.9 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam in ea 4 1/4" ctr.	6/8/33 RE48A122 16C40										
-48300-B5	CAPACITOR, fixed: NT-48300 w/1,800 mmf p/m 5%; temp coef ltr B.	6/8/33 RE48A122 16C40		16-C-31668-3155				CRV	UC-2970	CRV	T-602220-37	TAJ-4
-48301	CAPACITOR, variable: air; plate meshing type single sect; 6 to 100 mmf; SLC; 0.0245" air gap; 1 27/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 3/8" lg bushing 3/8" lg x 3/8"-32 thd; round shaft; fourteen dull nickel pl brass plates; clockwise rotation; isolantite ins; lug term; base mtg by two mtg feet ea w/one #6-32 tapped hole on 1 13/32" mtg/c.	1/31/33		16-C-60652-3381	N16-C-12450	R16-C-12450		CHC	MC-100-S	CRV	X-806726-1 rev6	RAA RAB RAA-2 RAA-3 RAB-3 RAB-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-97

RESTRICTED

RESTRICTED

SHEET 48 - 98

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48302	CAPACITOR, variable: 1/31/33 air; plate meshing type single sect; 6 to 100 mmf; SLO: 0.0245" air gap; 1 1/4" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 1/2" lg bushing 3/8" lg x 3/8"-32 thd; rounded shaft; fourteen dull nickel pl brass plates; clockwise rotation; isolantite ins; lug term for stator, rotor grounded; single hole mtg by 3/8" diam mtg bushing. NOTE: NM-15; NMA; NMB-2; NMC-1; RAB-1; RAB-2; RAB-3; RAB-4; WCA; WCA-1; WCA-2; WEB.			16-C-60652-3281	N16-C-18490-7			CBC	MC-100-S modified	CRV	K-811656-1 sub0	RAA RAB NM-9 NM-9a NM-11 NM-12 NM-13 NM-13a SEE NOTE
-48303	CAPACITOR, fixed: 1/31/33 mica; 300 mmf; 250 vdcw; case 2" lg x 1" wd x 3/8" thk; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom w/two 0.10" mtg holes 1 1/4" mtg/c.	RE48A106		16C40								
-48303-B5	CAPACITOR, fixed: 1/31/33 WT-48303 w/300 mmf p/m 2%; temp coef ltr B. NOTE: RAA-2; RAA-3; RAA-4.	RE48A106		16-C-29660-6241				CRV	UC-2903A	CRV CRV	K-359001 rev0 DL-UC2903A-1	RAA RAB SEE NOTE
-48304	CAPACITOR, fixed: 1/31/33 mica; 1200 mmf; 250 vdcw; case 2" lg x 1" wd x 3/8" thk; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom w/two 0.1" diam mtg holes on 1 1/4" mtg/c.	RE48A106		16C40								
-48304-B2	CAPACITOR, fixed: 1/31/33 WT-48304 w/1200 mmf p/m 2%; temp coef ltr B. NOTE: RAA-2; RAA-3; RAA-4.	RE48A106		16-C-31264-5166	N16-C-10158-24			CRV	UC-2905A	CRV CRV	K-35900rev0 DL-UC2905A-1	RAA RAB SEE NOTE
-48305	CAPACITOR, fixed: 1/31/33 mica; 1580 mmf; 250 vdcw; case 2" lg x 1" wd x 3/8" thk; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom w/two 0.1" mtg holes 1 1/4" mtg/c.											
-48305-B 1 1/2	CAPACITOR, fixed: 1/31/33 WT-48305 w/1580 mmf p/m 1 1/2%; temp coef ltr B. NOTE: RAA-2; RAA-3; RAA-4.	RE48A106		16-C-31602-5548				CRV	UC-2904A	CRV CRV	K-35900rev0 DL-UC2904A-1	RAA RAB SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-98

RESTRICTED

RESTRICTED

SHEET 48 - 99

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48306	CAPACITOR, fixed: mica; 900 mfm; 250 vdcw; case 2" lg x 1" wd x 3/8" thk; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom w/two 0.10" mtg holes 1 1/4" mtg/c.	1/31/33 RE48A106 16C40										
-48306-B3	CAPACITOR, fixed: mica; 900 mfm; 250 vdcw; case 2" lg x 1" wd x 3/8" thk; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom w/two 0.10" mtg holes 1 1/4" mtg/c.	1/31/33 RE48A106 16C40		16-C-30899-8223	N16-C-10077-200			CRV	UC-2902A	CRV CRV	K-35900rev0 DL-UC2902A-501	RAA RAB SEE NOTE
-48307	CAPACITOR, fixed: mica; 3200 mfm; 250 vdcw; case 2" lg x 1" wd x 3/8" thk; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom w/two 0.10" mtg holes 1 1/4" mtg/c.	1/31/33 RE48A106 16C40										
-48307-B3	CAPACITOR, fixed: mica; 3200 mfm; 250 vdcw; case 2" lg x 1" wd x 3/8" thk; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom w/two 0.10" mtg holes 1 1/4" mtg/c.	1/31/33 RE48A106 16C40		16-C-32237-2861				CRV	UC-2908A	CRV CRV	K-35900rev0 DL-UC2908A-501	RAA RAB SEE NOTE
-4830P	CAPACITOR, fixed: paper dielectric; 20 mf plus 10 minus 3%; 200 vdcw; ES metal can; 5 5/16" lg x 3 11/16" wd x 4 3/8" h; oil impr and filled; two screw type term 3/8" h located on top 2" c to c; no int gnd connections; two mtg fl on side of case ea w/two 1/4" diam mtg on 5 7/8" x 2 1/4" mtg/c.	2/2/33 RE48A158 RE13A488		16-C-52210-5127								GK-1
-48309	CAPACITOR, fixed: paper dielectric; 500,000 mfm plus 10 minus 3%; 200 vdcw; ES phenolic case; case 1 3/16" h x 1 3/4" wd x 1 5/16" thk; wax impr and filled-pitch sealed; two stud and nut term 1" c to c on top; no int gnd connections; two integral mtg feet with two 5/32" diam holes 2 1/8" c to c along bottom longitudinal ctr line.	2/2/33 RE48A181 RE13A488		16-C-47269-3444				CAW	250	CRV	K-815704-4	GK-1 TBM-5(3) TBM-7(3) TBR-13(3)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-99

RESTRICTED

RESTRICTED

SHEET 48 - 100

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48310	CAPACITOR, fixed: mica; 30,000 mmf; 600 vdcw, 1000v Dc test; case 1 1/4" lg x 1 1/4" wd x 3/8" h; molded bakelite case; two mtg holes in back of case 5/32" diam on 1 1/2" mtg/c; two lug term ea w/one 3/16" diam holes on 1 3/4" ctr.	2/2/33 RE43A215 16C40										
-48310-A10	CAPACITOR, fixed: NT-48310 w/30,000 test mmf p/m 10%; temp coef ltr A. NOTE: NM-13a; NM-15.	2/2/33 RE48A215 16C40		16-C-34730-6951				CAW	1455	CBM	p/o 562BB & BE	GK-1 NM-13 SEE NOTE
-48310-B10	CAPACITOR, fixed: NT-48310 w/30,000 mmf p/m 10% temp coef ltr B. NOTE: JKA-2 (2); JKA-3 (2); JKA-4 (2); JKA-5 (2); JKA-5a (2); WDA-1; WDA-1; WEB.	2/2/33 RE48A215 16C40		16-C-34730-6956	W16-C-10575-5			CAW	1455L	CBM CBP	p/o 744 & 744A 6828-74	JKA (2) JKA-1 (2) SEE NOTE
-48311	CAPACITOR, fixed: mica; 1000 mmf; 3000 vdcw max, 6 amp at 3000 kc, 2 amp at 1000 kc, 0.9 amp at 300 kc, 0.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded loss bakelite case; three stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	2/2/33 RE43A131 16C40										
-48311-A5	CAPACITOR, fixed: NT-48311 w/1,000 mmf p/m 5%; temp coef ltr A.	2/2/33 RE43A131 16C40		16-C-31086-7081				CD	PL-245-6			
-48312	CAPACITOR, fixed: paper dielectric; two sections; 100,000 mmf/100,000 mmf plus 10 minus 3%; 200/200 vdcw; ES metal case; 3/4" h x 1 13/16" wd x 1" thk; oil impr and filled; three solder lug term 3/8" h each 1/2" c to c along top ctr line; no int gnd connections one side of each sect common; two integral mtg fl on bottom ends w/two 3/16" diam holes 2 1/8" c to c; superseded by NT-48312-B.	2/16/33 RE13A488		16-C-53097-1160								GK-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-100

RESTRICTED

RESTRICTED

SHEET 48 - 101

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFCR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S BWG ON PART NO	EQUIPMENT USED IN
-48312-A	CAPACITOR, fixed: 11/23/36 paper dielectric; two sections; 100,000 muf/100,000 mmf plus 10 minus 3%; 400/400 vdcw; ES metal can; 3/4" h x 1 13/16" wd x 1" thk; oil impr and filled; three solder lug term 3/8" h ea 1/2" c to c along top ctr line; no int gnd connections; two integral mtg fl on bottom ends w/ two 3/16" diam holes 2 1/8" c to c; superseded by NT-48312-B.	RE48A128 RE13A488		16-C-53104-9305	N16-C-11331-1			CSL	2XIMRTW-4-1	CW CW	ESX-638975-107 ESX-654024-13	
-48312-A10	CAPACITOR, fixed: 11/23/36 NT-48312-A w/100,000 mmf/100,000 mmf p/m 10% superseded by NT-48312-B10.	RE48A128 RE13A488		16-C-53148-7744			3DA100-118.2 3DA100-317	CD	DYRT-4011	COL	954 4016 20	DAB DAB-1 EAB-2
-48312-A15	CAPACITOR, fixed: 11/23/36 NT-48312-A w/100,000 mmf/100,000 mmf p/m 15%.	RE48A128 RE13A488		16-C-53187-4867				CSL	2XIMRTW-4-1-15	CW CW	ESX-638975-107 ESX-654024-13	QBF QJA
-48312-A20	CAPACITOR, fixed: 11/23/36 NT-48312-A w/100,000 mmf/100,000 mmf p/m 20%; superseded by NT-48312-B20.	RE48A128 RE13A488		16-C-53209-3752	N16-C-11331-45		3DA100-348 3DA100-349	CSF CD	DYRT-4011	COL CHEZ CGR	CO-11421 CO-776-B B-6994	TCS-15(3)
-48312-B	CAPACITOR, fixed: 12/3/40 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 600 vdcw ea sect; ES metal can; 1 13/16" lg x 1" wd x 3/4" h o/a; oil impr and filled; three rivet lug term 3/8" h on top, spaced 1/2" c to c; no int gnd connections, one side of ea sect common; two mtg ft 3/8" wd flush w/bottom, w/two 3/16" diam mtg holes spaced 2 1/8" c to c; same as NT-48312-A except 600 vdcw.	RE13A488 RE48A128		16-C-53115-6212			3DXA100-186	CD CSF CSL CSF	DYTR-6011 2527-9 2XDRW6-1 PBTT566	COL CHEZ COL CIP	956ND01Wrev0 CO-806revB 956 0008 00 dated 6/21/44 ES-11739	
-48312-B5	CAPACITOR, fixed: 12/3/40 NT-48312-B w/100,000 mmf p/m 5% ea sect.	RE48A128 RE13A488		16-C-53071-6853				CD CSF CSL	DYTR-6011 2527-9 2XDRTM	COL CHEZ	956ND01W-Krev0 CO-806revB	
-48312-B10	CAPACITOR, fixed: 12/3/40 NT-48312-B w/100,000 mmf p/m 10% ea sect.	RE48A128 RE13A488		16-C-53159-5460	N16-C-11333-1		3DA100-133.10 3DXA100-179	CD CSF CSL	DYTR-6011 2527-9 2XDRTM	COL CHEZ COL	956ND01W-Krev0 CO-806revB 956 4012 20	
-48312-B15	CAPACITOR, fixed: 12/3/40 NT-48312-B w/100,000 mmf/100,000 mmf p/m 15%.	RE48A128 RE13A488		16-C-53192-8237			3DA100-272					
-48312-B20	CAPACITOR, fixed: 12/3/40 NT-48312-B w/100,000 mmf p/m 20% ea sect.	RE48A128 RE13A488		16-C-53214-7507			3DA100-168.3 3DA100-347	CD CD CSF CSL CSF	P-9451 DYTR-6011 2527-9 2XDRTM PBTT566	CHEZ COL	CO-806revB 956 4016 40	TCS(3) TCS-6(2) TCS-13 TCS-14 TDH-3

SHEET 48-101

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 102

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48313	CAPACITOR, fixed: paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 300 vdcv ea sect; ES metal can; case 1 13/16" lg x 1" wd x 5/8" h; oil filled; three stud term 5/16" h on side, spaced 1/2" c to c; no int gnd connections, one side of ea sect common; two mtg ft 3/8" wd flush w/bottom, w 3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48313-B.	2/16/33 RE13A488		16-C-53115-6152	N16-C-11330					CG	T-7659573-210	CK-1 LJ-1 (2)
-48313-10	CAPACITOR, fixed: NT-48313 w/100,000 mmf p/m 10% ee sect;	2/16/33 RE13A488		16-C-53140-8450				CD		CHS CBE	D-50W-263 RA-156	RAG RAG-1 FAH RAH-1
-48313-A	CAPACITOR, fixed: paper dielectric; two sect; 100,000 mmf plus 10% minus 3%; 400/400 vdcv; ES metal can; case 1 13/16" lg x 1" wd x 5/8" h o/s; oil filled; three stud term 3/8" h on side, spaced 1/2" c to c; no int gnd connections, one side of ea sect common; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c; superseded by NT-48313-B	11/23/36 RE48A129 RE13A488		16-C-53104-9265								
-48313-A15	CAPACITOR, fixed: NT-48313-A w/100,000 mmf/100,000 mmf p/m 10%.	11/23/36 RE48A129 RE13A488		16-C-53187-4857	N16-C-11330-8			CD	DYRS-6011	COL	T-7606408-33	TCB-2
-48313-B	CAPACITOR, fixed: paper dielectric; two sect; 100,000 mmf plus 10 minus 3%; 600/600 vdcv; ES metal can; case 3/4" h x 1 13/16" lg x 1" wd; oil filled; three solder lug term 5/16" h on side; no int gnd connections, one side ea sect is common; two mtg ft 3/8" wd flush w/bottom w/ 3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48313-C.	12/9/40 RE48A129 RE13A488		16-C-53115-6152			3DKA100-186	CTD CD CID	RLO-6210 DYR-6011 RLO-2210	CFE CFE CFE CIP CGG	10.70rev0 CO-630rev0 FBTS-580-E ES-117391ae2 8A103138	SU (2)
-48313-B10	CAPACITOR, fixed: NT-48313-B w/100,000 mmf p/m 10% ea sect; for replacement use NT-48313-C. NOTE: SU-1; WFA.	12/9/40 RE13A488 RE48A129		16-C-53159-5420	N16-RC-13922			CTD CGF CIE CD	RLO-6210 7507 GR11 DYR-6011-4	CEM CFE CEM CZC	744-675 10.70 744-363 8220	DAS-1(2) DAS-3(2) RCK(2) RDO(2) SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-102

RESTRICTED

RESTRICTED

SHEET 48 - 103

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48313-B15	CAPACITOR, fixed: 12/9/40 NT-48313-B w/100,000 mmf p/m 15% ea sect; replaced by NT-48313-C. NOTE: MK-8 Mod 2 (2); MK-13 Mod 0 (4); MK-16; MK-18(6); MK-19 (4); MK-22; MK-27; MK-28 (9); MK-29 Mod 2; MK-34 Mod 3 (3); MK-34 Mod 4 (3); MK-34 Mod 2 (6).	RE48A129 RE13A488		16-C-53192-8217	N16-C-11332-47			CD CSL CSF CAW CBV COF CTD	DYR-6011 2MMRW6-.1-15 PBTS-5800 630-.1-.1 12M-8-30 7507 RLO-6210	CW CAY	ES-682063-581aa1 7608226-.5	SJ-1(2) TDE TDE-1 TDE-2 TDE-3 MK-8 MK-8 Mod1
-48313-B20	CAPACITOR, fixed: 12/9/40 NT-48313-B w/100,000 mmf/100,000 mmf p/m 20%; for replacement use NT-48313-C20.	RE48A129 RE13A488		16-C-53214-7497	N16-C-11332-48		3DA100-168.3 3DA100-347	CD CTD	DYRS-6011 RLO-6210	CIF COF COL	ES-11739-2 PF-2619-1-1 956 4016 40	DAV DAV-1 TDB-4 (2)
-48313-C	CAPACITOR, fixed: 5/5/42 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 1000 vdc ea sect; HS metal can; case. 1 13/16" lg x 1" wd x 3/4" h; dykanol impr and filled; three solder lug term 3/8" h on side, spaced 1/2" c to c; no int gnd connections, one side ea sect is common; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c; same as NT-48313 except 1000 vdc.	RE13A488 RE48A129		16-C-53132-8720				CD	DYR-10011	CRF	h6993	MK-8
-48313-C10	CAPACITOR, fixed: 5/5/42 NT-48313-C w/100,000 mmf p/m 10% ea sect.	RE13A488 RE48A129		16-C-53176-6707	N16-C-11333-3			CD	DYR-10011			
-48313-C15	CAPACITOR, fixed: 5/5/42 NT-48313-C w/100,000 mmf p/m 15% ea sect.	RE13A488 RE48A129		16-C-53201-3916	N16-C-11333-4			CD CAW CTD CSF	DYR-10011 1030-.1-.1 RLO-10210-3 PBTS-4200	CW CW	ES-682029-21aa3 ES-682063-74	SS SV-1 MK-5 Mod2(2) MK-5 Mod 3
-48314	CAPACITOR, fixed: 2/16/33 paper dielectric; 200,000 mmf plus 10 minus 3%; 200 vdc; HS metal can; case 1 13/16" lg x 15/16" wd x 1/2" h; oil filled; two solder lug term 3/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48435-A.	RE13A488 RE48A129		16-C-46129-1831						CAY CAY	32-D-442 rev 5 987261	GK-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-103

RESTRICTED

RESTRICTED

SHEET 48 - 104

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48315	CAPACITOR, fixed: 2/16/33 paper dielectric; two sect; 50,000 mmf plus 10 minus 3% ea sect; 300 vdcw ea sect; BS metal can; 1 13/16" lg x 1" wd x 5/8" h; oil filled; three solder lug term 3/8" h on side, spaced 1/2" c to c; no int gnd connections, one side ea sect common; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48315.	RE13A488 RE48A129		16-C-52938-8387				CD		CHS	DRA-172-1	GK-1 DAK-2 DAK-4 RAG-1 RAH-1
-48315-10	CAPACITOR, fixed: 2/16/33 NT-48315 w/50,000 mmf p/m 10% ea sect; for replacement use NT-48315-B10.	RE13A488 RE48A129		16-C-52970-1670						CHS	DRA-172-1	
-48315-A	CAPACITOR, fixed: 11/23/36 paper dielectric; two sect; 50,000 mmf plus 10 minus 3% ea sect; 400 vdcw ea sect; BS metal can; 1 13/16" lg x 1" wd x 5/8" h; oil filled; three solder lug term 3/8" h on side, spaced 1/2" c to c; no int gnd connections, one side ea sect common; two mtg feet 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48315-B.	RE13A488 RE48A129		16-C-52939-5545						CPT	F-36434-1	DAK DAK-1
-48315-A10	CAPACITOR, fixed: 11/23/36 NT-48315-A w/50,000 mmf p/m 10% ea sect.	RE13A488 RE48A129		16-C-52970-8220			3DA50-143					
-48315-B	CAPACITOR, fixed: 12/9/40 paper dielectric; two sect; 50,000 mmf plus 10 minus 3% ea sect; 600 vdcw ea sect; BS metal can; 1 13/16" lg x 1" wd x 3/4" h; oil impr and filled; three solder lug term 5/8" h on side, spaced 1/2" c to c; no int gnd connections, one side ea sect common; two mtg feet 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A129		16-C-52947-1860			3DA50-73	CSF CD	CFBTS-57 DYR-60055	CHZ CFE	CO-626 isa B 10.74rev0	ABK(2) ABK-1(2) ABK-2(2) ABK-3(2) ACK-4(2) thru ABK-7(2)
-48315-B10	CAPACITOR, fixed: 12/9/40 NT-48315-B w/50,000 mmf p/m 10% ea sect. NOTE: RCK(2); RDO(2).	RE13A488 RE48A129		16-C-52978-4969	N16-C-11175-1		3DA50-132 3DA50-156	GSF CD CGF CIE CQU CIE	CFBTS-57 DYR-60055 7506 AH121 55-1 7571	CZC CFE CTJ CIE CCS	5067 10.74rev0 CP126M 6BA0505 6-492	DAS-1 DAS-3(2) PH RBO-1(5) RBO-2(5) RCH(5) SEE NOTE
-48315-B15	CAPACITOR, fixed: 12/9/40 NT-48315-B w/50,000 mmf p/m 15% ea sect.	RE48A129 RE13A488		16-C-53002-4330			3DA50-125	CD	DYR-60055	CPT	F-36431-1	DAK-3 DAH

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-104

RESTRICTED

RESTRICTED

SHEET 48 - 105

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48316	CAPACITOR, fixed: mica; 400 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	2/17/33 RE48A238 16C40										
-48316-B2	CAPACITOR, fixed: NT-48316 w/400 mmf p/m 2%; temp coef ltr B.	2/17/33 RE48A238 16C40		16-C-29919-5692	N16-C-10005-4			CRV	H	CRV CRV	K-35913-1rev0 M-86016-501	RAA RAB RAB-4
-48317	CAPACITOR, fixed: mica; 154 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" h; thermo-plastic case; two wire leads.	2/17/33 RE48A236 16C40										
-48317-B2	CAPACITOR, fixed: NT-48317 w/154 mmf p/m 2%; temp coef ltr B. NOTE: RAB-4; NM-3.	2/17/33 RE48A238 16C40		16-C-28996-3692	N16-C-9963			CRV	H	CRV CRV	K-35913-2 M-86016-502	RAA RAB SEE NOTE
-48317-D2	CAPACITOR, fixed: NT-48317 w/154 mmf p/m 2%; temp coef ltr D.	2/17/33 RE48A238 16C40		16-C-28996-3702	N16-C-9963			CRV	H			
-48318	CAPACITOR, fixed: mica; 540 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam lam phenolic case; two ins wire leads ea 4" lg.	2/17/33 RE48A219 16C40										
-48318-B5	CAPACITOR, fixed: NT-48318 w/540 mmf p/m 5%; temp coef ltr B. NOTE: RAB-1; RAB-2; RAB-3; RAB-4(3).	2/17/33 RE48A219 16C40		16-C-30241-3412				CRV	G	CRV	K-35912-1rev0	RAA RAB SEE NOTE
-48319	CAPACITOR, fixed: mica; 500 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins wire leads ea 4" lg.	2/17/33 RE48A219 16C40										
-48319-B5	CAPACITOR, fixed: NT-48319 w/500 mmf p/m 5%; temp coef ltr B.	2/17/33 RE48A219 16C40		16-C-30162-2212				CRV	G	CRV	K-35912-2	RAA RAB RAB-4
-48320	CAPACITOR, fixed: mica; 400 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins wire leads ea 4" lg.	2/17/33 RE48A219 16C40										
-48320-B5	CAPACITOR, fixed: NT-48320 w/400 mmf p/m 5%; temp coef ltr B.	2/17/33 RE48A219 16C40		16-C-29924-7612				CRV	G	CRV	K-35912-3	RAA RAB RAB-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-105

RESTRICTED

RESTRICTED

SHEET 48 - 106

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	COM. TRACION	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48321	CAPACITOR, fixed: mica; 345 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins wire leads ea 4" lg.	2/17/33 RE48A 19 16C40										
-48321-B5	CAPACITOR, fixed: NT-48321 w/345 mmf p/m 5%; temp coef ltr B.	2/17/33 RE48A219 16C40		16-C-29766-5212				CRV	G	CRV	K-35912-4rev0	RAA R B RAB-4(2)
-48322	CAPACITOR, fixed: mica; 220 mmf ; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins wire leads ea 4" lg.	2/17/33 RE48A219 16C40										
-48322-B2	CAPACITOR, fixed: NT-48322 w/220 mmf p/m 2%; temp coef ltr B.	2/17/33 RE48A219 16C40		16-C-29364-6732				CRV	G	CRV	K-35912-5	RAA RAB RAB-4(4)
-48322-D2	CAPACITOR, fixed: NT-48322 w/220 mmf p/m 2%; temp coef ltr D.	2/17/33 RE48A219 16C40		16-C-29365-6 42	N16-C-9973-3			CRV	G			
-48323	CAPACITOR, fixed: mica; 155 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins wire lead ea 4" lg.	2/17/33 RE48A219 16C40										
-48323-B5	CAPACITOR, fixed: NT-48323 w/155 mmf p/m 5%; temp coef ltr B. NOTE: RM-3 (2); QC-3 (2); RAB-4 (7).	2/17/33 RE48A219 16C40		16-C-29027-9012				CRV	G	CRV	K-35912-6	RAA RAB SEE NOTE
-48324	CAPACITOR, fixed: mica; 130 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins wire leads ea 4" lg.	2/17/33 RE48A219 16C40										
-48324-B5	CAPACITOR, fixed: NT-48324 w/130 mmf p/m 5%; temp coef ltr B.	2/17/33 RE48A219 16C40		16-C-28816-8812				CRV	G	CRV	K-35912-7	RAA RAB R B-4
-48325	CAPACITOR, fixed: mica; 125 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins wire leads ea 4" lg.	2/17/33 RE48A219 16C40										
-48325-B5	CAPACITOR, fixed: NT-48325 w/125 mmf p/m 5%; temp coef ltr B.	2/17/33 RE48A219 16C40		16-C-28790-5410				CRV	G	CRV	K-35912-8	RAA RAB RAB-4(5)
-48326	CAPACITOR, fixed: mica; 110 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins wire leads ea 4" lg.	2/17/33 RE48 219 16C40										
-48326-B5	CAPACITOR, fixed: NT-48326 w/110 mmf p/m 5%; temp coef ltr B.	2/17/33 RE48A219 16C40		16-C-26858-6412	N16-C-9947-1			CRV	G	CRV	K-35912-9	RAA RAB RAB-4

SHEET 48-106

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 45 - 107

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48327	CAPACITOR, FIXED: 2/17/33 mica dielectric; 70 mmf; 500 vdcw; 1 3/4" lg x 9/16" diam case; lam phenolic case; 2 axial ins wire leads ea 4" lg; add suffix indicating capacity tolerance in per cent.	RE48A219 16C40										
-48327-B5	CAPACITOR, fixed: 2/17/33 NT-48327 w/70 mmf p/m 5%; temp coef ltr B.	RE48A219 16C40		16-C-28051-9212				CRV	G	CRV	K-35912-10	RAA RAB RAB-4
-48327-B20	CAPACITOR, FIXED: 6/10/48 Navy Type 48327 w/70 mmf p/m 20%; temp coef ltr B.	RE48A219 16C40		16-C-28062-3172	N16-C-9970-3			CPV	G			
-48328	CAPACITOR, fixed: 2/17/33 mica; 40 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins wire leads ea 4" lg.	RE48A219 16C40										
-48328-B5	CAPACITOR, fixed: 2/17/33 NT-48328 w/40 mmf p/m 5%; temp coef ltr B.	RE48A219 16C40		16-C-27392-5207	N16-C-9843-48			CRV	G	CRV	K-35912-11	RAA RAB RAB-4
-48329	CAPACITOR, fixed: 2/17/33 mica; 35 mmf; 500 vdcw; case 1 3/4" lg x 9/16" diam; lam phenolic case; two ins axial wire leads ea 4" lg; add suffix indicating capacity tolerance in per cent.	RE48A219 16C40										
-48329-B5	CAPACITOR, fixed: 2/17/33 NT-48329 w/35 mmf p/m 5%; temp coef ltr B. NOTE: AA-2; RAA-3; RAB-4 (5).	RE48A219 16C40		16-C-27260-6212	N16-C-9842-1			CRV	G	CRV	K-35912-12	RAA RAB SEE NOTE
-48329-B10	CAPACITOR, fixed: 2/17/33 NT-48329 w/ 35 mmf p/m 10%; temp coef ltr B.	RE48A219 16C40		16-C-27265-6687	N16-C-9842							
-48329-B20	CAPACITOR, FIXED: 5/7/48 Navy Type 48329 w/35 mmf p/m 20%; temp coef ltr B.	RE48A219 16C40		16-C-27270-9172	N16-C-9842-2			CRV	C			
-48330	CAPACITOR, fixed: 2/18/33 mica; 250 mmf; 2,500 vdcw, 5000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term end mtg.	RE48A112 JAN-C-5										
-48330-A10	CAPACITOR, fixed: 2/18/33 NT-48330 w/250 mmf p/m 10%; temp coef ltr A. NOTE: TBK-6; TBK-7; TBK-9; TBK-4.	RE48A112 JAN-C-5	CM55A251K	16-C-29482-6262				CD	9-53025	CES	M-7406187-4	TAZ-1(2) TBK-5 SEE NOTE
-48330-B2	CAPACITOR, fixed: 2/18/33 NT-48330 w/250 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B251G	16-C-29472-4307	N16-C-9978	R16-C-9978						

SHEET 48-107

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 108

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S B/WG OR PART NO	EQUIPMENT USED IN
-48330-B10	CAPACITOR, fixed: 2/18/33 NT-48330 w/ 250 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM59B251K	16-C-29486-6267	N16-C-9978-2			CD	9L-53023	CRR CAY CAY CAY	C-55564-66188G 7607280P36 M-7406187P4 T-7607093E36 T-7605847P33	TBK-11 TBK-13 TBK-15 TBK-16 TBM-5 SEE NOTE:
-48331	CAPACITOR, fixed: 3/8/33 paper dielectric; 4 mfd plus 10 minus 3%; 300 vdcw; HS metal can; 4 1/2" h x 2 3/4" wd x 1 1/8" thk; oil impr and filled; two solder lug term 1" c to c on top; no int gnd connections; superseded by NT-48331-A.	RE48A110 RE13A488		16-C-49931-8922				CRV	UC-2305-72			
-48331-A	CAPACITOR, fixed: 3/8/33 paper dielectric; 4 mfd plus 10 minus 3%; 400 vdcw; HS metal case; 4 1/2" h x 2 3/4" wd x 1 1/8" thk; oil impr and filled; two solder lug term 1" c to c on top; no int gnd connections; same as NT-48331 except 400 vdcw.	RE48A110 RE13A488		16-C-49933-4150	N16-C-11545			CRV	UC-2305-72			
-48332	CAPACITOR, FIXED: 3/21/33 mica; 500 mmf; 5000 vdcw max, 6 amp at 3000 kc, 3 amp at 1000 kc, 2 amp at 300 kc, 0.6 amp at 100 kc; case 3 1/8" lg x 1 1/4" wd x 1 31/16" h; molded low-loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48754; add suffix indicating capacity tolerance in per cent.	RE48A131 16C40										
-48332-B5	CAPACITOR, fixed: 3/21/33 NT-48332 w/500 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-30164-1721	N16-C-10024-17			CRV CD CRV CD	UC-3095B PL-466-6H Paradon 272-6LS	CAY CRV CBM CAY	T-7607321-33 K-860215-7rev6 744-186 T-7609144-44	TBF QCL-9 QCL-1(2) QCL-2(2) QCL-8 SEE NOTE:
-48333	CAPACITOR, fixed: 3/21/33 mica; 2,000 mmf; 3,000 vdcw max, 6 amp at 3,000 kc, 2.5 amp at 1,000 kc, 1.5 amp at 300 kc, 0.8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-481040.	RE48A131 16C40										
-48333-A5	CAPACITOR, fixed: 3/21/33 NT-48333 w/2,000 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-31798-8881				CD CD	PL-215-6 PL-452-6			TBF

SHEET 48-108

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 109

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFOR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48334	CAPACITOR, fixed: 3/21/33 mica; 250 mmf; 5,000 vdcw max, 5 amp at 3,000 kc, 2.5 amp at 1,000 kc, 1 amp at 300 kc, 0.3 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48749.	RE48A131 16C40										
-48334-A2	CAPACITOR, fixed: 3/21/33 NT-48334 w/250 mmf p/m 2%; temp coef 1tr A.	RE48A131 16C40		16-C-29473-1B3B	N16-C-9979	R16-C-9988		CD	PL-364A-6			TBF
-48334-B5	CAPACITOR, fixed: 3/21/33 NT-48334 w/250 mmf p/m 5%; temp coef 1tr B.	RE48A131		16-C-29478-3325				CRV	Model UC-3178	CRV CRV	DI-500571-502 K-35356-1	GP(2) GP-2(2)
-48335	CAPACITOR, fixed: 3/21/33 mica; 250,000 mmf; 1250 vdcw, 20 amp at 3,000 kc, 40 amp at 1,000 kc, 30 amp at 300 kc, 10 amp at 100 kc; case 2 1/2" lg x 2 1/8" wd x 2 1/2" h; cast metal case; one screw term #20-18 thd on top 13/16" h; two mtg ft on bottom ea w/ one 0.196" diam hole on 3 5/16" mtg/c.	RE48A261 16C40										
-48335-B5	CAPACITOR, fixed: 3/21/33 NT-48335 w/250,000 mmf p/m 5%; temp coef 1tr B.	RE48A261 16C40		16-C-37073-8950	N16-C-10715			CRV	UC-1832			TBF
-48336	CAPACITOR, fixed: 3/21/33 CANCELLED: for replacement use NT-48135-A.											TBF
-48337	CAPACITOR, FIXED: 3/21/33 mica; 1000 mmf; 5000 vdcw max, 3925 vacw effective, 7 amp at 3000 kc, 4 amp at 1000 kc, 2 amp at 300 kc, 1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low-loss bakelite case; 2 stud term on top 7/16" h on 1 5/8" mtg/c; two 3/16" mtg holes on bottom on 2 5/8" mtg/c; for replacement use Navy Type 48737.	RE48A131 16C40										
-48337-A5	CAPACITOR, fixed: 3/21/33 NT-48337 w/1,000 mmf p/m 5%; temp coef 1tr A. NOTE: QCL-5 (2); QCN-3 (2); QCO-2 (2); THK-5(2); THK-6 (2); TB K-7 (2); THK-9 (2); THM-4.	RE48A131 16C40		16-C-31087-3718	N16-C-10096-3	R16-C-10126		CD CRV	PL-246-6 Faradon	CG CRV CBM CAY CAY CAY	P-7761566-18rev4 K-860215-13rev6 744-117 T-7603026-347 T-7605024-9 7605024-69	TBF QCJ QCJ-5(2) QCJ-6(2) QCX(2) QCL-4(2) SEE NOTE: Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-109

RESTRICTED

RESTRICTED

SHEET 48 - 110

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48337-BP	CAPACITOR, fixed: 3/21/33 NT-48337 w/1000 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-31082-2243	N16-C-10096-1			CRV CRV	UC-3300 Case 351	CRV	K-860215-11 revh	YG thru YG-2 YL
-48337-B5	CAPACITOR, fixed: 3/21/33 NT-48337 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-31087-3723	N16-C-10096-3			CD CAW	PL-246-6L 1550-L-116	CRV CG CRV	A26200-2 W-7350697-236 K-860215-13rev4	TAJ-8(14) TBR TBR-1
-48337-B10	CAPACITOR, fixed: 3/21/33 NT-48337 w/1,000 mmf p/m 10%; temp coef ltr B.	RE48A131 16C40		16-C-31092-5203	N16-C-10096			CD	PL-246-6L			
-48337-C5	CAPACITOR, fixed: 3/21/33 NT-48337 w/1,000 mmf p/m 5%; temp coef ltr C.	RE48A131 16C40		16-C-31087-3728	N16-C-10096-3			CD CAN	PL-246-6LS	CG CBM	P-7761566-18 rev13 744-117	QCJ-3(2) QCJ-4(2) QCN-1(2) SEE NOTE
-48337-D2	CAPACITOR, fixed: 3/21/33 NT-48337 w/1,000 mmf p/m 2%; temp coef ltr D.	RE48A131 16C40		16-C-31082-2253	N16-C-10096-1			CD CAW CAW	PL-246-6LS 1550-H-116 1550LS	CAY CAY CAY	7607470-71 T-7609144-12 T-7607321-12	TBL-2(2) TBL-3(2) TBL-5(2) SEE NOTE:
-48337-E2	CAPACITOR, FIXED: 3/21/33 CANCELLED: use Navy Type 48337-D2.	RE48A131 16C40		16-C-31082-2253				CD CAW	PL-246-6E 1550-H-116	CAY CAY CAY	760747-71 T-7609144-12 T-7607321-12	
-48338	CAPACITOR, fixed: 3/21/33 paper dielectric; 4 mf plus 10 minus 3%; 1250 vdcw; ES metal can; case 6" lg x 2 1/4" wd x 6 7/8" h, o/a; oil impr and filled; two stud term 2" h located on top, spaced 3" c to c on por pillows; no int gnd connection; strap mtg not supplied.	RE48A139		16-C-4994-14420	N16-C-11564-1			CAY	S#624414			TBF
-48339	CAPACITOR, fixed: 3/21/33 paper dielectric; two sect; 4 mfd/4 mfd plus 10 minus 3%; 2200/2200 vdcw; ES metal can; 8 3/4" h x 9" wd x 4 1/2" thk; "INERTEN" mineral oil impr and filled; three stud and nut term on por pillars 1 3/4" h x 2 1/2" c to c along top ctr line; no int gnd connec- tions one side of ea sect common; two 3/8"-16 remov- able mtg studs 7 3/4" c to c on bottom.	RE13A488		16-C-54093-8830	N16-C-11584-9			CAY	LD	CAY	S#700633-A	TBF
-48339-15	CAPACITOR, fixed: 3/21/33 NT-48339 w/ 4 mfd/4mfd p/m 15%.	RE48A234 RE13A488		16-C-54097-7170				CAY	LD	CAY CAY	S#700633-A 1-B-4371 chg 0	
-48340	CAPACITOR, fixed: 3/21/33 electrolytic; 500 mf; 15 vdcw; working temp range minus 20°C to plus 65°C; case 4 7/16" lg x 1 3/8" diam; tubr metal can; one stud term on top; neg term gnd internally; single hole mtg 3/4"-16 thd.	RE48A302 RE13A549		16-C-20654-8741	N16-C-9700	R16-C-9700		CD CAW	PL-5113-E G15-500	CAY CAY CAY	K-7809901 7606286-1 T-7609026-1 7609133-4	TBF TBM-13(4) TBM-5(4) TBM-6(10) TBM-7(4) SEE NOTE:
NOTE: TBM-8 (4); TBM-10 (6); TBM-12 (4); TDE (4); TDE-1 (4); TDE-2 (4); TDE-3 (4).												

SHEET 48-110

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 111

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48341	CAPACITOR, fixed: mica; 10,000 mmf; 600 vdcw, 1,000v DC test; case 1 1/4" lg x 1 1/4" wd x 3/8" h; molded bakelite case; two lug term ea w/ one 3/16" diam hole 1 3/4" c to c; two mtg holes in back of case 5/32" diam on 1 1/2" mtg/c.	4/7/33 RE48A215 16C40										
-48341-A10	CAPACITOR, fixed: NT-48341 w/10,000 mmf p/m 10%; temp coef ltr A. NOTE: QC-3; RAK (5); RAK-1 (5); RAK-2 (5); RAK-3 (5); RAK-4 (5); RAK-5 (5); RAK-6 (5); RAK-7 (5); RAL (3); RAL-1 (3); RAL-2 (3); RAL-4 (3); RAL-5(3); RAL-6(3); RAL-7(3) ..	4/7/33 RE48A215 16C40		16-C-33622-7951	NI6-C-10501-12			CAW	1455	CRV	K-30090-3	RAE NM-3 (2) SEE NOTE:
-48341-B10	CAPACITOR, fixed: NT-48341 w/10,000 mmf p/m 10%; temp coef ltr B.	4/7/33 RE48A215 16C40		16-C-33622-7956				CAW	1455L			
-48342	CAPACITOR, fixed: paper dielectric; two sect; 500,000/ 100,000 mmf plus 10 minus 3/4 ea section; 200/1,000 vdcw; ES metal can; case 2 5/16" lg x 2 1/4" wd x 2 15/32" h o/a; oil impr and filled; three wire lead term located on bottom; no internal gnd connections; two mtg r1 w/ four 0.154" diam mtg holes on 3 5/16" x 1 3/8" mtg/c.	5/23/33 RE48A167 RE13A488		16-C-53133-4820				CRV	CP-124	CRV	KX-280383	PC
-48343	CAPACITOR, fixed: mica; 150 mmf; 6,000 vdcw, 8 amp at 3,000 kc, 4.5 amp at 1,000 kc, 1.5 amp at 300 kc, 0.5 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; two 1/4" mtg holes in base on 4 1/4" mtg/c.	5/10/33 RE48A109 16C40										
-48343-B5	CAPACITOR, fixed: NT-48343 w/150 mmf p/m 5%; temp coef ltr B.	5/10/33 RE48A109 16C40		16-C-28977-3462				CRV	UC-2428			
-48344	CAPACITOR, fixed: mica; 1,400 mmf; 5,000 vdcw, 7.25 amp at 3,000 kc, 5.5 amp at 1,000 kc, 3.2 amp at 300 kc, 1.4 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	6/8/33 RE48A108 16C40										
-48344-B5	CAPACITOR, fixed: NT-48344 w/1,400 mmf p/m 5%; temp coef ltr B.	6/8/33 RE48A108 16C40		16-C-31456-6396				CRV	UC-2971	CRV	T-602221-38	TAJ-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-111

RESTRICTED

RESTRICTED

SHEET 48 - 112

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48345	CAPACITOR, fixed: mica; 2,800 mmf; 3,000 vdcw, 8.5 amp at 3,000 kc, 6.5 amp at 1,000 kc, 4 amp at 300 kc, 1.6 amp at 100 kc; case 2 1/2" lg x 2 1/4" wd x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side smd to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	6/8/33 RE48A108 16C40										
-48345-B5	CAPACITOR, fixed: NT-48345 w/2,800 mmf p/m 5%; temp coef ltr B.	6/8/33 RE48A108 16C40		16-C-32168-2596				CRV	UC-2972	CRV	T-602221-37	TAJ-4
-48346	CAPACITOR, fixed: mica; 100 mmf; 2,000 vdcw, 10 amp at 13,000 kc, 7 amp at 9,000 kc, 2 amp at 4,000 kc; case 2 1/2" lg x 2 1/2" wd x 1 9/16" h; metal case; two screw term 3/4" lg, #10-32 thd, one on front, one on back; two mtg ft on sides ea w/ two 0.173" diam holes on 3" x 2" mtg/c.	6/9/33 RE48A254 16C40										
-48346-B5	CAPACITOR, fixed: T-48346 w/100 mmf p/m 5%; temp coef ltr B.	6/9/33 RE48A254 16C40		16-C-28554-2021	N16-C-9927			CRV	UC-2707A			
-48347	CAPACITOR, fixed: mica; 2,000 mmf; 5,000 vdcw max, 8.5 amp at 3,000 kc, 6.5 amp at 1,000 kc, 4 amp at 300 kc, 2 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	6/19/33 RE48A131 16C40										
-48347-B5	CAPACITOR, fixed: NT-48347 w/2,000 mmf p/m 5%; temp coef ltr B. NOTE: QCL-8; NM-3; TAJ-4 (2); TB -8 (7); TEK-10 (7); THK-12 (7); THK-14 (7); THK-19 (7); TBL (6); TRL-1 (6); TRL-4 (9); TRL-8 (9); TRL-9 (9); TBU-1; TBU-4; WAA; WCA (2); WCA-1 (2); WRA.	6/19/33 RE48A131 16C40		16-C-31799-5523	N16-C-10262-1			CRV CRV CB	UC-3054-K-2 PL-217A-6S 6LS	CRV CRV CAY CAY CBM	K-860215-17rev6 P-702390-44 DL-500500-502 T-7609144-56 T-7607321-56 744-5	TAJ-4 QC-3 QCJ-5 QCJ-9 QCL-4 QCL-5 SEE NOTE:
-48347-B10	CAPACITOR, fixed: NT-48347 w/2,000 mmf p/m 10%; temp coef ltr B.	6/19/33 RE48A131 16C40		16-C-31804-5993	N16-C-10262			CD CD CD	BT-8D2 217-6L PL-217A-6LS	CBM CBM	744-476 744-5	WEB(14) WCA-3(2) WDA (2) WBA-1(2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-112

RESTRICTED

RESTRICTED

SHEET 48 - 113

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48347-B20	CAPACITOR, fixed: NT-48347 w/2,000 mmf p/m 20%; temp coef ltr B. NOTE: NMA; NMB-2 (2); NMC-1; QC-7; QCA; QCB; QCE; QCF; QCJ-5; QCK-6; QCL-2; QCM-1; QCN-1; QCO-3; QOQ; QOR; QOS; QOT.	6/19/33 R 48A131 16C40		16-C-31809-8483	N16-C-10262-14			CD CD	217-6L PL-217A-6LS	CG CRM	K-357758-1rev0 744-5	MN-13 NM-12 SEE NOTE:
-48348	CAPACITOR, fixed: mica; 20,000 mmf; 2,000 vdcw, 1 1/4 amp at 3,000 kc, 15 amp at 1,000 kc, 11 amp at 300 kc, 5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	6/22/33 RE48A131 16C40										
-48348-B2	CAPACITOR, FIXED: Navy Type 48348 w/20000 mmf p/m 2%; temp coef letter B.	12/15/47 RE48A131 RE48A154		16-C-34325-6996				CRV	DL502318-502	CRV	W-303083-224	QCB
-48348-B5	CAPACITOR, fixed: NT-48348 w/20,000 mmf p/m 5%; temp coef ltr B. NOTE: NMA (2); NMB-2 (2); QC-3; QCC (2); QCD (2); QCF; QCJ (2); QCK (2); QCO (2); QOQ (2); QOR (2); QOS-1 (2); QOT-1 (2); TAB -5; TBL (2); WAB (2) WCA (2).	6/22/33 RE48A131 16C40		16-C-34330-8478	N16-C-10558			CRV CAN CD	UC-2996-K-2 F3L-1512 6PL-131A-6S	CRV CBM	K-856829-11rev8 744-61	BC JE-5(2) NM-9 (2) SEE NOTE:
-48349	CAPACITOR, fixed: mica; 6,000 mmf; 3,000 vdcw, 13 amp at 3,000 kc, 10 amp at 1,000 kc, 6.5 amp at 300 kc, 3.0 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48740.	6/22/33 RE48A131 16C40										
-48349-A5	CAPACITOR, fixed: NT-48349 w/6,000 mmf p/m 5%; temp coef ltr A.	6/22/33 RE48A131 16C40		16-C-32853-9881	N16-C-10449-55			CRV CD	UC-3021-K-2 PL-439-6	CRV	K-860215-20rev6	TBC
-48349-B5	CAPACITOR, fixed: NT-48349 w/6,000 mmf p/m 5%; temp coef ltr B. NOTE: TBL-4(7); TBL-8(7); TBL-9(7).	6/22/33 RE48A131 16C40		16-C-32853-9886	N16-C-10449-55			CRV CD	UC-3021-K-2 PL-439-6L	CRV	DL-5004066-502	TBL (2) TBL-1 (2) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-113

RESTRICTED

RESTRICTED

SHEET 48 - 114

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL COR S STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-4 350	CAPACITOR, fixed: 6/22/33 mica; 2,000 mmf; 3,000 vdcw, 5.5 amp at 3,000 kc, 4 amp at 1,000 kc, 2.5 amp at 300 kc, 1.2 amp at 100 kc; case 2" lg x 1 5/16" wd x 1 1/2" h; molded low loss bakelite case; two screw term 7/16" h spaced 1 1/2" c to c on top; two mtg fl on bottom, ea w/one 0.15" diam hole on 2 3/8" mtg/c.	RE48A222 16C40										
-48350-A5	CAPACITOR, fixed: 6/22/33 NT-48350 w/2,000 mmf p/m 5%; temp coef ltr A.	RE48A222 16C40		16-C-31798-8825				CRV	UC-3053-K	CRV CRV	DL-500502-502 K-35356-2	TBG GP GP-2
-48350-D2	CAPACITOR, fixed: 6/22/33 NT-48350 w/2,000 mmf p/m 2%; temp coef ltr D.	RE48A222 16C40		16-C-31793-7348				CRV	UC-3053-K			
-48350-D5	CAPACITOR, fixed: 6/22/33 NT-48350 w/2,000 mmf p/m 5%; temp coef ltr D.	RE48A222 16C40		16-C-31798-8828				CRV	UC-3053-K			
-48351	CAPACITOR, fixed: 6/22/33 mica; 2,000 mmf; 5,000 vdcw, 13 amp at 3,000 kc, 10 amp at 1,000 kc, 6 amp at 300 kc, 3 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 5/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	RE48A108 16C40										
-48351-B5	CAPACITOR, fixed: 6/22/33 NT-48351 w/2,000 mmf p/m 5%; temp coef ltr B; for replacement use NT-481283.	RE48A108 16C40		16-C-31799-5596				CRV	UC-3055-K			TBG
-48352	CAPACITOR, fixed: 6/22/33 mica; 10,000 mmf; 2,000 vdcw max, 14 amp at 3,000 kc, 14 amp at 1,000 kc, 9 amp at 300 kc, 4 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48352-B2	CAPACITOR, FIXED: 12/16/47 Navy Type 48352 w/10000 mmf p/m 2%; temp coef letter B.			16-C-33613-9207				CRV	W-303083-151			QCJ-8 QCL-7
-48352-B5	CAPACITOR, fixed: 6/22/33 NT-48352 w/10,000 mmf p/m 5%; temp coef ltr B. NOTE: TBK-8 (3); TBK-10 (3); TBK-12 (3); TBK-14 (3); TBK-17 (3); TBK-19 (3); TBL-1; TBL-1; TBL-4 (2); TBL-8 (2); TBL-9(2); YE (3); YK-1 (3); YK-2 (3).	RE48A131 16C40		16-C-33618-6686	N16-C-10508			CRV CD	UC-3004-K-2 Case 351	CRV CRV CBM CRV	K-860215-21rev6 W-303056-12 720-84 DL-500404-502	TBG QCF QCJ-8 QCL-7 SEE NOTE:

SHEET 48-114

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 115

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48353	CAPACITOR, fixed: mica; 800 mmf; 5,000 vdcw, 9 amp at 3000 kc, 6 amp at 1000 kc, 3.5 amp at 300 kc, 1.4 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side end to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	6/22/33 RE48A108 16C40										
-48353-B5	CAPACITOR, fixed: NT-48353 w/800 mmf p/m 5%; temp coef 1tr B.	6/22/33 RE48A108 16C40		16-C-30691-6796				CRV	UC-3080K			TBG
-48354	CAPACITOR, FIXED: mica dielectric; 60 mmf; 5000 vdcw, 5.5 amp at 10000 kc, 1.7 amp at 3000 kc; 0.7 amp at 1000 kc; 2 5/16" lg x 1 17/64" wd x 1 27/32" h case; molded low loss phenolic case; 2 stud term on top, thd 7/16" h, 1 5/8" c to c; 2 mtg ft, 1 ea end, w/hole 0.150" diam 2 5/8" mtg/c; add suffix indicating capacity tolerance in per cent.	6/22/33 RE48A131 16C40										
-48354-B5	CAPACITOR, fixed: NT-48354 w/60 mmf p/m 5%; temp coef 1tr B.	6/22/33 RE48A131 16C40		16-C-27790-1728	N16-C-9853			CRV	UC-2974K	CRV CRV	M-402589-7 DL-501616-502	TBG TBL TBL-1
-48354-B20	CAPACITOR, FIXED: Navy Type 48354 w/60 mmf p/m 20%; temp coef 1tr B.	6/9/48 RE48A131 16C40		16-C-32706-7097				CRV	UC2974K			
-48355	CAPACITOR, fixed: paper dielectric; 10 mf plus 10 minus 3%; 1000 vdcw; ES metal can; 4 5/8" h x 3 3/4" wd x 1 3/4" thk; oil impr and filled; two stud end nut term 2" c to c on top; no int grd connections; mts by removable mtg bkt not incl; superseded by Navy Type 48355-A.	7/3/33 RE13A488 RE48A110		16-C-51840-2398				CG	9CE1A22	CRV	K-802520	TAJ-4 TBF-1
-48355-A	CAPACITOR, FIXED: paper dielectric; 10 mf plus 10 minus 3%; 1000 vdcw; ES metal can; 4 5/8" h x 3 3/4" wd x 1 3/4" d, o/a; 2 solder term 1/2" h located on top, spaced 2" c to c; no int grd connections; mts by removable mtg bkt CG dwg #56J-878-2; add suffix indicating capacity tolerance in per cent.	1/27/38 RE48A110U RE13A488		16-C-51840-2400	N16-C-11675		3DB10-37	CG CSF	25F686 674	CBZ CG	CG-662 K52J565-2 rev 0	YH (2)
-48355-A10	CAPACITOR, fixed: NT-48355-A w/10 mf p/m 10%.	1/27/38		16-C-51861-2437			3DB10-37	CD		CG	K-52J565-2 rev 2	UE-1 (5)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-115

RESTRICTED

RESTRICTED

SHEET 48 - 116

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48356	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 1650 vdcw; HS metal can; case 3 3/4" lg x 2 1/4" wd x 4 5/8" h; oil impr and filled; two screw type term 2" h located on top, spaced 2" c to c on por pillars; no int gnd connections; strap mtg not supplied.	7/3/33 RE48A139 RE13A488		16-C-49942-9600					CRV CRV CRV	W-300501-57 K-802521 W-300217-83 W-300289-123	TAJ-4(2) TRF-1 NM-3 (2) EC-3 (2) TBL-1
-48356-20	CAPACITOR, FIXED: Navy Type 48356 w/4 mfd p/m 20%.	11/11/49		16-C-49991-7787							
-48357	CAPACITOR, fixed: paper dielectric; 3.5 mf plus 10 minus 3%; 3300 vdcw; HS metal can; case 3 3/4" lg x 4 9/16" wd x 5 25/32" h; pyramol impr and filled; two screw type term 2" h located on top, spaced 2" c to c on por pillars; no int gnd connections; strap mtg not supplied.	7/3/33 RE48A139 RE13A488		16-C-49754-7470					CRV CRV	K-802519 W-300217-82	TAJ-4 TRF-1
-48358	CAPACITOR, fixed: mica; 175 mmf; 500 vdcw; case 7/16" lg x 1/4" diam; thermo-plastic case; two wire leads.	7/20/33 RE48AP46 16040									
-48358-B5	CAPACITOR, fixed: NT-48358 w/175 mmf p/m 5%; temp coef ltr B. NOTE: DP(7) thru DP-3(7).	7/20/33 RE48A246 16040		16-C-29106-5234	N16-C-9964-15				CRV	K-35976-1	DO(7) thru DO-3(7) SEE NOTE
-48359	CAPACITOR, fixed: paper dielectric; three sect; 4 mf minus 10 plus 25% ea sect; 300 vdcw ea sect; HS metal can; 4 19/32" lg x 2 11/32" wd x 5 5/16" h; oil impr and filled; four solder lug term 1/2" c to c on bottom; no int gnd connections; two mtg bkt welded to can ea w/two 0.242" diam holes 1 1/4" x 5 3/32" c to c.	7/22/33 RE48A171		16-C-54733-3185					CRV	P-64997-1 rev0	
-48359-10	CAPACITOR, fixed: NT-48359 w/4 mf p/m 10% ea sect.	7/22/33 RE48A171		16-C-54734-1163	N16-C-11584-12						DO thru DO-3
-48360	CAPACITOR, FIXED: paper dielectric; 2 sect; 100000 mmf minus 10 plus 25% ea sect; 300 vdcw ea sect; HS metal can; 2 11/16" h x 1 7/8" lg x 5/8" wd, not incl mtg ft or term; wax impr and sealed; 3 solder lug term on side of case 7/16" h; 9/16" from c to c; no int gnd connections; 2 mtg ft 7/16" lg integral w/bottom of case w/one 0.154" diam mtg hole in ea, mtg ft extend vert from bottom of case and are 1 7/8" apart; for replacement use Navy Type 48360-A.	7/22/33 RE13A488 RE48A134 alt A		16-C-53225-8000				CRV			DO thru DO-3 DP thru DP-3
-48360-10	CAPACITOR, FIXED: Navy Type 48360 w/100000 mmf p/m 10% ea sect.	7/22/33 RE13A488 RE48A134 alt A		16-C-53147-7410				CRV	M-66180-G1		

SHEET 48-116

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 117

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48360-A	CAPACITOR, FIXED: 12/22/36 paper dielectric; 2 sect; 100000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; HS metal can; 2 11/16" h x 1 7/8" lg x 5/8" wd, not incl mtg ft or term; wax impr and sealed; 3 solder lug term on side of case 7/16" h, 9/16" from c to c; no int gnd connections; 2 mtg ft 7/16" lg integral w/bottom of case w/one 0.154" diam mtg holes in ea, mtg ft extend vert from bottom of case and are 1 7/8" apart.	RE48A134 alt B RE13A488		16-C-53104-9355								
-48360-A10	CAPACITOR, FIXED: 12/22/36 Navy Type 48360-A w/100000 mmf p/m 10% ea sect.	RE13A488 RE48A134 alt B		16-C-53148-7804	W16-C-11332-9							
-48361	CAPACITOR, FIXED: 7/22/33 paper dielectric; 2 sect; 500000 mmf minus 10 plus 25% ea sect; 300 vdcv ea sect; HS metal can; 2 21/32" h x 2 3/8" wd x 51/64" h, not incl mtg ft or term; wax impr and sealed; 3 solder lug term on side of case 7/16" h, 1/2" from c to c; no int gnd connections; 2 mtg ft 13/16" lg integral w/top of case w/two 0.154" diam mtg holes 2 3/4" c to c; for replacement use Navy Type 48361-A.			16-C-53725-7680	W16-C-11375-88			CRV	M-66110-01			DO thru DP thru DP-3
-48361-10	CAPACITOR, fixed: 7/22/33 NT-48361 w/500,000 mmf p/m 10% ea sect.			16-C-53625-4146				CRV		CRV	M-66110-1	
-48361-A	CAPACITOR, FIXED: 12/22/36 paper dielectric; 2 sect; 500000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; HS metal can; 2 11/16" h x 2 5/16" lg x 1" wd, not incl mtg ft or term; wax impr and sealed; 3 solder lug term on side of case 7/16" h, 9/16" from c to c; no int gnd connections; 2 mtg ft 9/16" lg integral w/bottom of case w/one 0.154" diam mtg hole in ea, mtg ft extend vert from bottom of case and are 2 5/16" apart.	RE13A488 RE48A134 alt B		16-C-53570-4420								
-48361-A10	CAPACITOR, FIXED: 12/22/36 Navy Type 48361-A w/500000 mmf p/m 10% ea sect.	RE13A488 RE48A134 alt B		16-C-53626-7716								

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-117

RESTRICTED

RESTRICTED

SHEET 48 - 118

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
48362	CAPACITOR, FIXED: 7/22/33 paper dielectric; 1 mfd minus 10 plus 25%; 300 vdcw; HS metal can; 2 11/16" h x 2 5/16" lg x 1" wd, not incl mtg ft or term; wax impr and sealed; 2 solder lug term on side of case 1 1/8" c to c; no int gnd connections; 2 mtg ft 9/16" lg integral w/bottom of case w/two 0.154" diam mtg holes 2 3/4" c to c, mtg ft extend horiz from bottom of case; for replacement use Navy Type 48239-A.	RE13A488 RE48A134 alt A		16-C-48854-8780	N16-C-11384-1							DO(2) thru DO-3 (2) DP(2) thru DP-3 (2)
48362-10	CAPACITOR, FIXED: 7/22/33 Navy Type 48362 w/1 mfd p/m 10%.	RE13A488 RE48A134 alt A		16-C-48812-8493	N16-C-11384-1			CRV	M-66183-01			
48363	CAPACITOR, fixed: 7/24/33 paper dielectric; 2 mfd plus 10 minus 3%; 800 vdcw; HS metal can; 5 1/16" h x 2 5/16" wd x 2" d; two stud term 1/2" h located on top, spaced 1" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-49178-6279				CD	PL-5039			TAV-2
48364	CAPACITOR, fixed: 7/24/33 paper dielectric; 25 mfd plus 10 minus 3%; 120 vdcw; 60 cps, 0.114 kva; HS metal can; case 4 13/16" h x 3 3/4" wd x 2 1/2" thk; oil impr and filled; two stud and nut term 2" c to c on top; no int gnd connections.	RE13A488		16-C-52398-4800	N16-C-11695			CG	9CE1A31	CG	H-3931073-3 rev 1	
48364-A	CAPACITOR, fixed: 1/27/38 paper dielectric; 25 mfd plus 10 minus 3%; 350 vdcw; HS metal can; 4 13/16" h x 3 3/4" wd x 2 1/2" d; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-52402-3910	N16-C-11695-1							

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-118

RESTRICTED

RESTRICTED

SHEET 48 - 119

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48365	CAPACITOR, fixed: mica; 3,000 mmf; 3,000v AC RMS test, 10 amp at 3,000 kc, 8 amp at 1,000 kc, 5 amp at 300 kc, 2 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	7/24/33 RE48A131 16C40										
-48365-B2	CAPACITOR, fixed: NT-48365 w/3,000 mmf p/m 2%; temp coef ltr B.	7/24/33 RE48A131 16C40		16-C-32189-4406	N16-C-10328	R16-C-10328-5		CD	PL-655-6H 1550-H-225	CAY	7607280-16	TAV-2 TBK-16 (1)
-48365-B5	CAPACITOR, fixed: NT-48365 w/3,000 mmf p/m 5%; temp coef ltr B. NOTE: NM-12 (2); NM-15 (2); NMA (2); NMB-2 (2); QCM-WDA (2); WDA-1 (2).	7/24/33 RE48A131 16C40		16-C-32194-5885	N16-C-10328-4 N16-C-10328-24			CRV CD CD	UC-3046K-2 case351 PL-655-6L PL-655-6S	CRV CBM CG CRV	K-860215-18rev6 744-63 MC-7660174-54 DL-500409-502	NM-13 (2) NM-13a (2) NM-9 (2) NM-9a (2) SEE NOTE
-48365-D2	CAPACITOR, fixed: NT-48365 w/3,000 mmf p/m 2%; temp coef ltr D. NOTE: TBL-2; TBL-3; TBL-5; TBL-6; TBL-7; TBL-10; TBM-4; TBM-8; TBM-12; TBM-13.	7/24/33 RE48A131 16C40		16-C-32189-4416	N16-C-10328			CAW CD CD	1550K PL-655-6H 1550H-225	CAY CAY CAY CAY	T-7605497-48 7607280-16 7607470-19 T-7607093-16 T-7605847-100	TBK-7 TBK-9 TBK-11 TBK-13 TBK-15 SEE NOTE
-48366	CAPACITOR, fixed: CANCELLED: for replacement use NT-481105.	7/24/33 RE48A131 16C40						CD	PL-307-6			TAV-2
-48367	CAPACITOR, fixed: mica; 25 mmf; 10,000 vdcv, 3 amp at 3000 kc, 1 amp at 1000 kc, 0.3 amp at 300 kc, 0.1 amp at 100 kc; case 2 5/16" lg x 2 3/4" diam; cast metal case; one screw term #10-32 thd, 1 3/8" h incl ins on top; one screw term #10-32 thd on side of base; two 0.196" diam holes in front and back of base on 2 1/4" mtg/c.	8/1/33 RE48A262 16C40										
-48367-B5	CAPACITOR, fixed: NT-48367 w/25 mmf p/m 5%; temp coef ltr B.	8/1/33 RE48A262 16C40		16-C-26946-7886	N16-C-9810-1			CRV	UC-1803	CRV	K-35388rev0	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-119

RESTRICTED

RESTRICTED

SHEET 48 - 120

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48368	CAPACITOR, fixed: 8/3/33 paper dielectric; 5 mfd plus 10 minus 3%; 2,000 vdcw; HS metal can; case 5 3/8" lg x 3 3/4" wd x 6 1/16" h; oil impr and filled; two ceramic ins screw type term 1 1/4" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 1/4" diam mtg holes on 2 1/4" x 5 7/8" mtg/c.	RE48A159 RE13A488		16-C-50323-8013				CD	PL-55016	CEM CD	746-17 4545	TAZ-1 QCJ-5 QCJ-6 QCL-4 QCL-5 QCN-3 QCO-2
-48369	CAPACITOR, fixed: 8/3/33 paper dielectric; 2 mf plus 10 minus 3%; 3000 vdcw; HS metal can; case 5 3/8" lg x 3 3/4" wd x 9 5/16" h; oil impr and filled; two ceramic ins screw type term 2" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 1/4" diam mtg holes on 2 1/4" x 5 7/8" mtg/c.	RE48A159 RE13A488		16-C-49184-7060				CD	PL-5510G	CD	4545	TAZ-1
-48370	CAPACITOR, fixed: 8/3/33 paper dielectric; 2 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 4 1/8" h; oil impr and filled; two screw type term 1/2" h located on top 13/16" c to c; no int gnd connections; two mtg fl 15/16" wd on side of case, ea w/one 3/16" diam mtg hole 2 1/4" c to c.	RE48A147 RE13 488		16-C-49176-3275				CD	PL-5997G			TAZ-1
-48371	CAPACITOR, fixed: 8/3/33 mica; 50,000 mmf; 600 vdcw, 1000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 3/4" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48371-A10	CAPACITOR, fixed: 8/3/33 NT-48371 w/50,000 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM60A503K	16-C-35231-8931	N16-C-10591			CD CSL	9-11050 ZMW6 -15-10	CAY	7406203-5	TAZ-1 TBK-5 TBK-6
-48371-B5	CAPACITOR, fixed: 8/3/33 NT-48371 w/50,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B503J	16-C-35226-8456	N16-C-10591-3			CAW	1650-L	CRV	A26201-1	TAJ-8 (9)
-48371-B10	CAPACITOR, fixed: 8/3/33 NT-48371 w/50,000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B503K	16-C-35231-8936	N16-C-10591			CD CAW CSL CW	9L-11050 1650XM ZMBH-6-15-10 D160800	CRV CEM CAY CG CAY CAY	P720567-12rev34 744-27 T-7606683-7 P-776488-60 T-7609144-6 T-7607321-6	JK-3 (2) JKA (2) QC-7 (3) QCA (4) QCA-1 (4) QCB (4) SEE NOTE:
NOTE: QCB-1 (4); QCB-2 (4); QCB-3 (4); QCE (4); QCE-1 (4); QCE-2 (4); QCE-3 (4); QCF (4); QCO (3); QCI (4); QCJ-3 (4); QCJ-4 (4); QCJ-9 (4); QCK (4); QCL-1; QCL-2; QCM-1 (2); QCN-1; QCC-1 (4); QCR-1 (4); SA thru SA-4; TAB-5 (10); TBU-4 (8); WAB (4); WCA (13); WEB (4); WFA (5).												

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-120

RESTRICTED

RESTRICTED

SHEET 48 - 121

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48372	CAPACITOR, fixed: mica; 5,000 mmf; 2,500 vdcw, 5000v DC test; case 1 27/32" lg max x 1 11/32" wd max x 3/4" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	8/3/33 RE48A112 JAN-C-5										
-48372-A10	CAPACITOR, fixed: NT-48372 w/ 5,000 mmf p/m 10%; temp coef ltr A.	8/3/33 RE48A112 JAN-C-5	CM60A502K	16-C-32700-7062	N16-C-10412			CD CSL	9-52050 EMW2.5-25-10			TAZ-1(19)
-48372-B10	CAPACITOR, fixed: NT-48372 w/5,000 mmf p/m 10%; temp coef ltr B.	8/3/33 RE48A112 JAN-C-5	CM60B502K	16-C-32700-7067	N16-C-10412-48			CD	9L-52050	CG	P-7761560-20rev17	
-48372-D10	CAPACITOR, fixed: NT-48372 w/5,000 mmf p/m 10%; temp coef ltr D.	8/3/33 RE48A112 JAN-C-5	CM60D502K	16-C-32700-7077	N16-C-10412					CAY	7608226-43	TDE-1 thru TDE-3
-48373	CAPACITOR, fixed: paper dielectric; 10 mf minus 10 plus 25%; 900 vdcw; metal can; 4 1/4" lg x 2 1/4" wd x 5 3/4" h; two screw term on top of case 1 1/4" c to c; no int gnd connections; two mtg fl 2 1/4" lg integral w/top of case, w/four 0.154" diam mtg holes on 4 5/8" x 1 3/8" mtg/c.	8/9/33 RE48A137 REL13A488		16-C-51894-9510				CRV	CP-127	CRV	P-64994-1 rev 0	PC NM-3
-48373-10	CAPACITOR, fixed: NT-48373 w/10 mf p/m 10%.	8/9/33 RE48A137 REL13A488		16-C-51860-3010				CRV	CP-127			
-48374	CAPACITOR, fixed: paper dielectric; 2 mfd minus 10 plus 25%; 300 vdcw; metal can; 3 3/64" lg x 1 55/64" wd x 4 11/16" h; two solder lug term 3/8" h on top of case 3/4" from c to c; no int gnd connections; two mtg fl 2 1/4" lg integral w/top of case w/four 0.154" diam mtg holes on 3 7/16" x 1" mtg/c.	8/9/33 RE48A137 REL13A488		16-C-49234-9045				CRV	CP-132	CRV	P-64995-1 rev 0	PC NM-3
-48374-10	CAPACITOR, fixed: NT-48374 w/2 mf p/m 10%.	8/9/33 RE48A137 REL13A488		16-C-49192-9277				CRV	CP-132			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-121

RESTRICTED

RESTRICTED

SHEET 48 - 123

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48378-10	CAPACITOR, fixed: NT-48378 w/500,000/500,000/500,000/500,000mmf p/m 10%	8/9/33 RE48A184 REL3A488		16-C-54855-6633				CRV	CP-128			
-48379	CAPACITOR, fixed: mica; 50mmf; 5,000 vdcw max, 1.5 amp at 3,000 kc, 0.8 amp at 1000 kc, 0.2 amp at 300 kc, 0.07 amp at 100 kc; case 2 5/16" lg x 1 17/64" d x 1 27/32" h case; molded phenolic case, low loss; 2 stud term on top thd 7/16" h x 1 5/8" c to c; 2 mtg ft 1 ea end w/hole 3/16" diam x 2 5/8" mtg/c; for replacement use Navy Type 48740; add suffix indicating capacity tolerance in per cent.	8/14/33 RE48A131 16C40										
-48379-A5	CAPACITOR, fixed: NT-48379 w/50mmf p/m 5%; temp coef 1tr A.	8/14/33 RE48A131 16C40		16-C-27631-8221				CD CAW CRV	PL-390-6 1550-200 UC-3133A			TBF-1
-48379-B20	CAPACITOR, FIXED: Navy Type 48379 w/50 mmf p/m 20%/ temp coef 1tr B.	5/20/48 RE48A131 16C40		16-C-32706-7074				CD	6LS			
-48380	CAPACITOR, fixed: mica; 300 mmf; 10,000 vdcw, 7.5 amp at 3,000 kc, 5.0 amp at 1,000 kc, 3.0 amp at 300 kc, 1.0 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	8/14/33 RE48A122 16C40										
-48380-B5	CAPACITOR, fixed: NT-48380 w/300 mmf p/m 5%; temp coef 1tr B. NOTE: TCM; TCM-2; TCN; TCU-2.	8/14/33 RE48A122 16C40		16-C-29663-7262	N16-C-9997			CD CRV CAN	PL-763-50 UC-3111	CG CG	W-7350697-239 M-7462694-3	TBF-1 TBR TBR-1 SEE NOTE
-48381	CAPACITOR, FIXED: mica dielectric; 2000 mmf; 8000 vdcw peak, 16 amp at 3000 kc, 14 amp at 1000 kc, 8 amp at 300 kc, 3.5 amp at 100 kc; 3" h x 3 1/2" diam case; molded ceramic case; 2 fl type term, 1 ea end, w/2 holes ea 17/64" diam 4 1/4" c to c; add suffix indicating capacity tolerance in per cent.	8/14/33 RE48A122 16C40										
-48381-B5	CAPACITOR, fixed: NT-48381 w/2,000 mmf p/m 5%; temp coef 1tr B.	8/14/33 RE48A122 16C40		16-C-31800-2111	N16-C-10288-100			CRV	UC-3056			TBF-1
-48381-B20	CAPACITOR, FIXED: Navy Type 48381 w/2000 mmf p/m 20%; temp coef 1tr B.	7/15/48 RE48A121 16C40		16-C-31810-5076				CRV	UC3056			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-123

RESTRICTED

RESTRICTED

SHEET 48 - 124

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48382	CAPACITOR, fixed: 8/15/33 mica; 10,000 mmf; 2,500 vdcw; case 1 25/32" lg max x 1 11/32" wd max x 3/4" h; molded bakelite case; two #6-32 thd holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48382-A5	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 5%; temp coef ltr A.	RE48A112 JAN-C-5	CM60A103J	16-C-33618-8703		R16-C-10507-9-476		CD CAW CSL	9-51010 1652 XM2.5-11-5			
-48382-A10	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 10%; temp coef ltr A. NOTE: THK-7 (2); THK-9 (2); TDM-4 (2); ME-8 Mod 2.	RE48A112 JAN-C-5	CM60A103K	16-C-33623-9183	R16-C-10513	R16-C-10511		CD CAW CSL CAN CSF	9-51010 1652 XM2.5-11-10 A2-5110 2811-8	CKV CRP CAY CAY	L-61030-28rev2 35-5048 T-7606233-28 P-7705781-11 7705781-8	TAZ-1 (6) SG(3) thru SG-2 (3) THK-5 (2) THK-6 (2) SEE NOTE
-48382-A20	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 20%; temp coef ltr A.	RE48A112 JAN-C-5	CM60A103M	16-C-33629-2663	R16-C-10513-13	R16-C-10513-440		CD CAW CSL	9-51010 1652 XM2.5-11-10			
-48382-B2	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B103G	16-C-33613-7228		R16-C-10507-5-416		CD CAW CSL	9-51010 1652 XM2.5-11-2			
-48382-B5	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B103J	16-C-33618-8708		R16-C-10507-9-700		CD CAW CSL	9-51010 1652 XM2.5-11-5	CRM	744-186	QCQ-1 (2) QCR-1 (2) QCS (2) QCT (2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-124

RESTRICTED

RESTRICTED

SHEET 48 - 125

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-48382-B10	CAPACITOR, fixed: NI-48382 w/10,000 mmf p/m 10%; temp coef 1tr B.	8/15/33 RE48A112 JAN-C-5	CM60B103K	16-C-33623-9188	16-C-10513				CD	9L-51010	CAY	T-7609144-27	CO-1
									CSL	IMB2.5-11-16	CAY	T-7607321-27	CO-2
									CAW	1652	CAY	T-7606683-116	SA-1
									CAN	A-10	CAY	7607280-34	SA-2
											CAY	7607470-42	SA-3
											CAY	760233-28	SF (3)
											CAY	T-7607093-34	SF-1 (3)
									CEM	744-610		TAB-5 (3)	
									CEM	744-609		TAB-6 (3)	
									CW	SSO-611146-2		TAB-7 (3)	
									CW	ES-682066-141		TAJ-6 (24)	
									CRV	P-720567-13		TAJ-7 (8)	
									CRV	L-61030-28rev2		TAJ-10 (4)	
CG	R-7761560-7rev17		TAJ-11 (4)										
CG	ML-7761468-5		TAJ-13 (4)										
CG	7461899-106		thru										
CG	P-7762661-3		TAJ-19 (4)										
CG	P-7762664-54		TAJ-5 (4)										
CG	P-7764888-54		TAQ-6 (4)										
												SEE NOTE	
-48382-B20	CAPACITOR, fixed: NI-48382 w/10,000 mmf p/m 20%; temp coef 1tr B.	8/15/33 RE48A112 JAN-C-5	CM60B103M	16-C-33629-2668	16-C-10513-7			CD CRV	9L-51010 BF	CRV	K-36172-501	YG (3) YL (4)	
-48382-C2	CAPACITOR, fixed: NI-48382 w/10,000 mmf p/m 2%; temp coef 1tr C.	8/15/33 RE48A112 JAN-C-5	CM60C103G	16-C-33613-7233		R16-C-10507-6-248		CD CAW CSL	9L-51010 1652L IMB2.5-11-2				
-48382-C5	CAPACITOR, fixed: NI-48382 w/10,000 mmf p/m 5%; temp coef 1tr C.	8/15/33 RE48A112 JAN-C-5	CM60C103J	16-C-33618-8713		R16-C-10507-10		CD CAW CSL	9L-51010 1652L IMB2.5-11-5				
-48382-C10	CAPACITOR, fixed: NI-48382 w/10,000 mmf p/m 10%; temp coef 1tr C.	8/15/33 RE48A112 JAN-C-5	CM60C103K	16-C-33623-9193		R16-C-10510-90		CD CAW CSL	9L-51010 1652L IMB2.5-11-10				
-48382-C20	CAPACITOR, fixed: NI-48382 w/10,000 mmf p/m 20%; temp coef 1tr C.	8/15/33 RE48A112 JAN-C-5	CM60C103M	16-C-33629-2673		R16-C-10513-615		CD CAW	9L-51010 1652L				
-48382-D5	CAPACITOR, fixed: NI-48382 w/10,000 mmf p/m 5%; temp coef 1tr D.	8/15/33 RE48A112 JAN-C-5	CM60D103J	16-C-33618-8718		R16-C-10507-284		CD	9L-51010			Con't	

SHEET 48-125

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 126

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48382-D10	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 10%; temp coef ltr D. NOTE: TDN-3; TDN-4.	RE48A112 JAN-C-5	CM60D103K	16-C-33623-9198		R16-C-10513-170		CD CAN	9H-51010 .01-A50			TDN TDN-2 SEE NOTE
-48382-D20	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 20%; temp coef ltr D.	RE48A112 JAN-C-5	CM60D103M	16-C-33629-2678		R16-C-10513-705		CD	9H-51010			
-48382-E5	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 5%; temp coef ltr E.	RE48A112 JAN-C-5	CM60E103J	16-C-33618-8723		R16-C-10507-468						
-48382-E10	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 10%; temp coef ltr E.	RE48A112 JAN-C-5	CM60E103K	16-C-33623-9203		R16-C-10513-260						
-48382-E20	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 20%; temp coef ltr E.	RE48A112 JAN-C-5	CM60E103M	16-C-33628-2683		R16-C-10513-805						
-48382-F2	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 2%; temp coef ltr F.	RE48A112 JAN-C-5	CM60F103G	16-C-33613-7248		R16-C-10507-8-744						
-48382-F5	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 5%; temp coef ltr F.	RE48A112 JAN-C-5	CM60F103J	16-C-33618-8730		R16-C-10507-752						
-48382-F10	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 10%; temp coef ltr F.	RE48A112 JAN-C-5	CM60F103K	16-C-33623-9208		R16-C-10513-350						
-48382-F20	CAPACITOR, fixed: 8/15/33 NT-48382 w/10,000 mmf p/m 20%; temp coef ltr F.	RE48A112 JAN-C-5	CM60F103M	16-C-33629-2688		R16-C-10513-895						
-48383	CAPACITOR, fixed: 8/28/33 paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; ES metal can; case 3 3/4" lg x 1 1/4" wd x 4 7/8" h •/a; oil impr and filled; two ceramic ins screw type term 1 1/4" h located on top 2" c to c; no int and connections; two mtg fl on bottom of case, ea w/2• 3/16" diam mtg holes 1/2" apart ctr 4 1/4" c to c; for replacement use only.	RE48A159 REL3A488		16-C-49937-2076				CD	PL-5996G	CD	4547	TAZ-1
-48384	CAPACITOR, FIXED: 8/28/33 mica dielectric; 60 mmf; 600 vdcw; 1 3/16" lg x 3/8" wd x 5/16" thk case; molded low loss phenolic case; 2 axial solder lug term; add suffix indicating capacity tolerance in per cent.	RE48A220 16C40										
-48384-A20	CAPACITOR, fixed: 8/28/33 NT-48384 w/60 mmf p/m 20%; temp coef ltr A.	RE48A220 16C40		16-C-27798-5780								
-48384-B10	CAPACITOR, fixed: 8/28/33 NT-48384 w/60 mmf p/m 10%; temp coef ltr B. NOTE: BP thru BP-3.	RE48A220 16C40		16-C-27793-3301	N16-C-9849-165					CRV	E-801494-11rev2	BO thru D-3 SEE NOTE
-48384-B20	CAPACITOR, FIXED: 6/10/48 Navy Type 48384 w/60 mmf p/m 20%; temp coef ltr B.	RE48A220 16C40		16-C-27799-5785								

SHEET 48-126

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 127

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48385	CAPACITOR, fixed: mica; 690 mmf; 600 vdcw, 1,000 vdc; case 1 3/16" lg max x 3/4" wd max x 5/16" thk max; molded bakelite case; two tab term ea w/one 0.144" diam mtg holes, 1 3/4" c to c.	8/28/33 RE48A220 16C40										
-48385-A20	CAPACITOR, fixed: NT-48385 w/690 mmf p/m 20%; temp coef ltr A.	8/28/33 RE48A220 16C40		16-C-30568-2780								DO thru DP-3
-48386	CAPACITOR, fixed: mica; 40 mmf; 600 vdcw, 1000 vdc; case 1 3/16" lg max x 3/4" wd max x 5/16" thk max; molded bakelite case; two tab term ea w/one 0.144" diam mtg hole 1 3/4" c to c.	8/28/33 RE48A220 16C40										
-48386-A20	CAPACITOR, fixed: NT-48386 w/40 mmf p/m 20%; temp coef ltr A.	8/28/33 RE48A220 16C40		16-C-27402-8780								DO thru DP-3
-48386-B10	CAPACITOR, fixed: NT-48386 w/40 mmf p/m 10%; temp coef ltr B. NOTE: DP thru DP-3.	8/28/33 RE48A220 16C40		16-C-27397-6301	N16-C-9843-52				CMV		K-801494-16	DO thru DP-3 SEE NOTE
-48387	CAPACITOR, FIXED: mica; 1000 mmf; 500 vdcw; case 1 3/4" lg x 1/2" wd x 9/16" thk; lam phenolic case; 2 axial wire leads.	9/1/33 RE48A244 16C40										
-48387-B1 1/2	CAPACITOR, fixed: NT-48387 w/1000 mmf p/m 1 1/2%; temp coef ltr B. NOTE: DP thru DP-3.	9/1/33 RE48A244 16C40		16-C-31079-5285								DO thru DP-3 SEE NOTE
-48388	CAPACITOR, FIXED: mica; 2000 mmf; 500 vdcw; case 1 3/4" lg x 1/2" wd x 9/16" thk; lam phenolic case; 2 axial wire leads.	9/1/33 RE48A244 16C40										
-48388-B1	CAPACITOR, fixed: NT-48388 w/2,000 mmf p/m 1%; temp coef ltr B. NOTE: DP thru DP-3.	9/1/33 RE48A244 16C40		16-C-31791-6077								DO thru DP-3 SEE NOTE
-48389	CAPACITOR, FIXED: mica; 5100 mmf; 500 vdcw; case 1 3/4" lg x 1/2" wd x 9/16" thk; lam phenolic case; 2 axial wire leads.	9/1/33 RE48A244 16C40										
-48389-B1	CAPACITOR, fixed: NT-48389 w/5100 mmf p/m 1%; temp coef ltr B. NOTE: DP thru DP-3.	9/1/33 RE48A244 16C40		16-C-32714-5052								DO thru DP-3 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-127

RESTRICTED

RESTRICTED

SHEET 48 - 128

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48390	CAPACITOR, variable: 9/1/33 mica; compression type, single sect; 5 to 35 mmf; 500 vdc; 1 3/4" lg x 15/16" wd x 3/4" h; solder lug term; two mtg holes 0.144" diam 1 3/8" c to c; scdr adj; isolantite base.	16040		16-C-64671-4857				CEC	ICS-35	CRV	K-30061-3rev0	DO(6) thru DO-3(6) DP(6) thru DP-3(6)
-48391	CAPACITOR, variable: 9/5/33 mica; compression type, single sect; 10 to 70 mmf; 500 vdc; 1 3/4" lg x 15/16" wd x 3/4" h; solder lug term; two mtg holes 0.144" diam 1 3/8" c to c; scdr adj; isolantite base.	16040		16-C-64729-7457	N16-C-12580			CEC	ICS-70	CRV	K-30061-1rev0	DO(11) thru DO-3(11) DP(10) thru DP-3(10)
-48392	CAPACITOR, FIXED: 9/5/33 paper dielectric; 500000 mmf minus 10 plus 25%; 300 vdc; HS metal can; 2 21/32" h x 1 15/16" lg x 19/32" wd, not incl term; parolite impr and sealed; 2 solder lug term on side of case 7/16" h, 1" c to c; no int and connections; 2 mtg ft 1/2" lg integral w/bottom of case w/two 0.154" diam mtg holes on 2 3/16" c to c, mtg ft extend horiz from bottom of case; for replacement use Navy Type 48392-A.			16-C-47335-1105				CRV	CP-103	CRV	M-66002-03 rev 1	DO thru DO-3 DP thru DP-3
-48392-10	CAPACITOR, fixed: 9/5/33 NI-48392 w/500,000 mmf p/m 10%.			16-C-47292-7960				CRV	CP-103	CRV	M-66002-03	
-48392-A	CAPACITOR, FIXED: 12/22/36 paper dielectric; 500000 mmf plus 10 minus 3%; 400 vdc; HS metal can; 2 11/16" h x 1 7/8" lg x 5/8" wd, not incl mtg ft or term; parolite impr and sealed; 2 solder lug term on side of case 7/16" h, 1 1/8" c to c; no int and connections; 2 mtg ft 7/16" lg integral w/bottom of case w/two 0.154" diam mtg holes on 2 3/16" ctr, mtg ft extend horiz from bottom of case.	RE13A488 RE48AA134 alt B		16-C-47272-9939	N16-C-11347-2							
-48392-A1Q	CAPACITOR, FIXED: 12/22/36 Navy Type 48392-A w/500000 mmf p/m 10%.	RE13A488 RE48AA134 alt B		16-C-47293-9939	N16-C-11347							

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-128

RESTRICTED

RESTRICTED

SHEET 48 - 129

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48393	CAPACITOR, fixed: 9/5/33 paper dielectric; four sect; 1 mf minus 10 plus 25%; 300 vdcv ea sect; ES metal can; case 2 3/4" lg x 2 1/8" wd x 3 5/8" h; oil impr and filled; five solder lug term on bottom of case; no int gnd connections; two integral mtg fl 3/4" wd on side of case, ea w/ two 0.154" diam mtg holes and 2 1/2" x 1 3/8" mtg/c; for replacement use NT-48393-A.	RE48A137 RE13A488										
-48393-10	CAPACITOR, fixed: 9/5/33 NT-48393 w/1 mf p/m 10% ea sect. NOTE: M0-2; D0-3; IP; DP-1; DP-2; DP-3.	RE13A488 RE48A137		16-C-54870-1192	M16-C-11440			CRV	CP-107			DO DO-1 SEE NOTE:
-48393-A	CAPACITOR, fixed: 9/10/40 paper dielectric; four sect; 1 mf plus 10 minus 5% ea sect; 600 vdcv ea sect; ES metal can; case 2 3/4" lg x 2 1/8" wd x 2" h o/a; oil impr and filled; five solder lug term on bottom of case; no int gnd connections; two integral mtg fl 9/16" wd on side of case, ea w/two 0.154" diam mtg holes and 2 1/2" x 1 3/8" mtg/c; for replacement of NT-48393.	RE48A157 RE13A488		16-C-54867-9180								
-48393-A20	CAPACITOR, fixed: 9/10/40 NT-48393-A w/1 mf p/m 20% ea sect.	RE48A157 RE13A488		16-C-54874-9082	M16-C-11441							
-48394	CAPACITOR, FIXED: 9/7/33 mica dielectric; 50 mmf; 600 vdcv; 1 3/4" lg x 1 5/16" wd x 15/32" h; molded low loss phenolic body; one #6-32 NC tapped hole ea end 1 1/4" c to c; add suffix indicating capacity tolerance in per cent.	RE48A112 16C40										
-48394-A10	CAPACITOR, fixed: 9/7/33 NT-48394 w/50 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-27635-1551				CD	9-14050			TAV-2
-48394-B2	CAPACITOR, fixed: 9/7/33 NT-48394 w/50 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-27624-8591	M16-C-9843-112							
-48394-D5	CAPACITOR, fixed: 9/7/33 NT-48394 w/50 mmf p/m 5%; temp coef ltr D.	RE48A112 16C40		16-C-27630-1071	M16-C-9843-113			CD	9L-14050			
-48394-B20	CAPACITOR, FIXED: 5/14/48 Navy Type 48394 w/50 mmf p/m 20%; temp coef ltr B.	RE48A112 16C40		16-C-27640-4039				CSL	XMB-6-45			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-129

RESTRICTED

RESTRICTED

SHEET 48 - 130

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48395	CAPACITOR, fixed: mica; 50 mmf; 600 vdcw, 1000v DC test; case 1 1/4" lg x 1 1/4" wd x 3/8" h; moulded bakelite case; two lug term ea w/one 3/16" diam hole on 1 3/4" ctr; two mtg holes in back of case 5/32" diam on 1 1/2" mtg/c.	9/18/33 RB48A215 16C4C										
-48395-A10	CAPACITOR, fixed: MT-48395 w/50 mmf p/m 10%; temp coef ltr A.	9/18/33 RB48A215 16C40		16-C-27635-1351				CAW	1455			TAV-2
-48395-B10	CAPACITOR, fixed: MT-48395 w/50 mmf p/m 10%; temp coef ltr B.	9/18/33 RB48A215 16C40		16-C-27635-1355				CAW	1455L			
-48396	CAPACITOR, fixed: mica; 500 mmf; 600 vdcw, 1000v DC test; case 1 1/4" lg x 1 1/4" wd x 3/8" h; moulded bakelite case; two lug term ea w/one 3/16" diam hole on 1 3/4" ctr; two mtg holes in back of case 5/32" diam on 1 1/2" mtg/c.	9/18/33 RB48A215 16C4C										
-48396-A10	CAPACITOR, fixed: MT-48396 w/500 mmf p/m 10%; temp coef ltr A.	9/18/33 RB48A215 16C40		16-C-30167-3551	N16-C-10018-14			CAW	1455	CRV	K-30090-2	TAV-2 NM-3 QC-3
-48396-B10	CAPACITOR, fixed: MT-48396 w/500 mmf p/m 10%; temp coef ltr B.	9/18/33 RB48A215 16C40		16-C-30167-3556				CAW	1455L			
-48397	CAPACITOR, fixed: mica; 5000 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" h; metal clad; two axial lug term ea w/one 3/32" diam hole 1 3/16" c to c.	10/11/33 RB48A126 16C40										
-48397-10	CAPACITOR, fixed: MT-48397 w/5000 mmf p/m 10%.	10/11/33 RB48A126 16C40		16-C-32699-4677	N16-C-10403-11			CRV	T			
-48398	CAPACITOR, fixed: mica; 1500 mmf; 2500 vdcw; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	10/11/33 RB48A112 JAN-C-5										
-48398-A0	CAPACITOR, fixed: MT-48398 w/1500 mmf p/m 5%; temp coef ltr A.	10/11/33 RB48A112 JAN-C-5		CM55A152J	16-C-31508-6582			CD	9-52015			
-48398-A10	CAPACITOR, fixed: MT-48398 w/1500 mmf p/m 10%; temp coef ltr A.	10/11/33 RB48A112 JAN-C-5		CM55A152K	16-C-31513-7062			CD	9-52015	CRS		TAZ-1
-48398-A20	CAPACITOR, fixed: MT-48398 w/1500 mmf p/m 20%; temp coef ltr A.	10/11/33 RB48A112 JAN-C-5		CM55A152M	16-C-31518-9542	R16-C-10221-250		CD	9-52015			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-130

RESTRICTED

RESTRICTED

SHEET 48-131

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48398-B2	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B152G	16-C-31503-5107	N16-C-10187			CRV	Model "F"	CRV	X-35484-41rev9	TBL-4(2) TBL-8(2) TBL-9(2)
-48398-B5	CAPACITOR, fixed: 10/11/33 I-48398 w/1500 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B152J	16-C-31508-6587				CD	9-52015			
-48398-B10	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B152K	16-C-31513-7067	N16-C-10187-48			CD	9L-52015			
-48398-C2	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 2%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C152G	16-C-31503-5112				CD	9L-52015			
-48398-C5	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 5%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C152J	16-C-31508-6592		R16-C-10220		CD	9L-52015			
-48398-C10	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 10%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C152K	16-C-31513-7072				CD	9L-52015			
-48398-C20	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 20%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C152M	16-C-31518-9552		R16-C-10221-450		CD	9L-52015			
-48398-D2	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 2%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D152G	16-C-31503-5117		R16-C-10210-350		CD	9H-52015			
-48398-D5	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 5%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D152J	16-C-31508-6597		R16-C-10220-100		CD	9H-52015			
-48398-D10	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 10%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D152K	16-C-31513-7077				CD	9H-52015			
-48398-D20	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 20%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D152M	16-C-31518-9557		R16-C-10221-550		CD	9H-52015			
-48398-E5	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 5%; temp coef ltr E.	RE48A112 JA-C-5	CM55E152J	16-C-31508-6602		R16-C-10220-200						
-48398-E10	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 10%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E152K	16-C-31513-7082								
-48398-E20	CAPACITOR, fixed: 10/11/33 NT-48398 w/1500 mmf p/m 20%; temp coef ltr E.	RE48A112 JAN-C-5	CM55E152M	16-C-31518-9562		R16-C-10221-650						

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-131

RESTRICTED

RESTRICTED

SHEET 48 - 132

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48399	CAPACITOR, fixed: 10/11/33 mica; 3000 mmf; 2500 vdcw, 5000v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; moulded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48399-A2	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 2%; temp coef ltr A.	RE48A112 16C40		16-C-32189-3502				CD	9-52030			TAZ-1
-48399-A5	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 5%; temp coef ltr A.	RE48A112 16C40		16-C-32194-4982	N16-C-10327-49	R16-C-10328-2-825		CD	9-52030			
-48399-A10	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-32199-5462				CD CSL	9-52030 DMW2.5-23-10			TAZ-1
-48399-B2	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-32189-3507		R16-C-10328-2-165		CD	9-52030			
-48399-B5	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40		16-C-32194-4987	N16-C-10327-48	R16-C-10328-3		CD CAW	9-52030 1652L	CRR	A106555-302	ATD(2)
-48399-B10	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-32199-5467	N16-C-10327-50	R16-C-10335		CD CSL CRV	9L-52030 DMW2.5-23-10 Model "B"	CRV	K-35482-44	TBL-4 TBL-8 TBL-9
-48399-C2	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 2%; temp coef ltr C.	RE48A112 16C40		16-C-32189-3512		R16-C-10328-2-275		CD	9L-52030			
-48399-C5	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 5%; temp coef ltr C.	RE48A112 16C40		16-C-32194-4992		R16-C-10328-3-99		CD	9L-52030			
-48399-D2	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 2%; temp coef ltr D.	RE48A112 16C40		16-C-32189-3517		R16-C-10328-2-385		CD	9H-52030			
-48399-D5	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 5%; temp coef ltr D.	RE48A112 16C40		16-C-32194-4997		R16-C-10328-3-199	3DA3-11	CD	9H-52030			
-48399-E2	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 2%; temp coef ltr E.	RE48A112 16C40		16-C-32189-3522		R16-C-10328-2-495						
-48399-E5	CAPACITOR, fixed: 10/11/33 NT-48399 w/3000 mmf p/m 5%; temp coef ltr E.	RE48A112 16C40		16-C-32194-5002		R16-C-10328-3-299						
-48400	CAPACITOR, fixed: 10/11/33 mica; 3500 mmf; 2500 vdcw, 5000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; moulded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48400-A10	CAPACITOR, fixed: 10/11/33 NT-48400 w/3500 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A352K	16-C-32331-4462				CD	9-52035	CHS		TAZ-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-132

RESTRICTED

RESTRICTED

SHEET 48 - 133

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48401	CAPACITOR, fixed: 10/11/33 mica; 500 mmf; 2500 vdcw, 5000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded low loss bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48401-A10	CAPACITOR, fixed: 10/11/33 NT-48401 w/500 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A501K	16-C-30168-4662				CD	9-53050	CBS		TAZ-1
-48401-B2	CAPACITOR, fixed: 10/11/33 NT-48401 w/500 mmf p/m 2%; temp coef ltr B. NOTE: TAJ-10; TAJ-11; TAJ-13 thru TAJ-19; TBK-8; TBK-10; TBK-12; TBK-14; TBK-17; TBK-19; TEL-4; TEL-8; TEL-9.	RE48A112 JAN-C-5	CM55B501G	16-C-30158-2707	N16-C-10022			CRV CD	Model "F" 9ALS-53050	CRV CG CG CG	K-35484-38rev9 7761891-104 P-7762661-1 P-7762664-30	GP GP-2 TAJ-7 TAJ-9 SEE NOTE
-48401-B5	CAPACITOR, fixed: 10/11/33 NT-48401 w/500 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B501J	16-C-30163-4187	N16-C-10022-1			CD	9-53050			
-48401-E10	CAPACITOR, fixed: 10/11/33 NT-48401 w/500 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B501K	16-C-30168-4667	N16-C-10023			CD	9L-53050	COL CG	950 3501 20rev0 ML-7761468-4	TAJ-6
-48401-B20	CAPACITOR, fixed: 10/11/33 NT-48401 w/500 mmf p/m 20%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B501M	16-C-30173-7147				CRV	AF, FARADON	CRV	K-35485-8	TBS(4) thru TBS-8(4)
-48401-D5	CAPACITOR, fixed: 10/11/33 NT-48401 w/500 mmf p/m 5%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D501J	16-C-30163-4322				CSL	XM	CRZ	CO-684	BL-6
-48401-E10	CAPACITOR, FIXED: 12/6/38 Navy Type 48401 w/500 mmf p/m 10%; temp coef letter E.	RE48A112		16-C-30168-4685				CD CD	9RL-53050 9RL-53050			GO-4
-48402	CAPACITOR, fixed: 10/31/33 paper dielectric; 2 mf plus 10 minus 3%; 2000 vdcw; HS metal can; 3 3/4" lg x 1 1/4" w x 4 7/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/4" h located on top 2" c to c; no int grd connections; two mtg fl on bottom of case, four 3/16" diam mtg holes 1/2" x 4 1/4" c to c.	RE48A159 RE13A488		16-C-49183-5965				CD	PL-5483G	CD	4547	TAZ-1
-48403	CAPACITOR, fixed: 11/15/33 paper dielectric; 2 mf plus 10 minus 3%; 400 vdcw; HS metal can; case 1 1/3" h x 2" wd x 2" thk; halovax impr end filled; two stud and nut term 1" c to c on side; no int grd connections; two integral mtg ears on bottom ends w/two 3/16" diam holes 2 3/3" c to c; superseded by NT-48403-A.	RE13A488		16-C-49173-1186	N16-C-11479-1			CD CRV	DH-4200 UC-278	CAY CG CG	K-7809165-2 V-7350697-245 M-7462695-1	TBR(2) TBR-1(2) TCF TCM(2) TCM-2(2) TCN (2) TCQ-2(2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-133

RESTRICTED

RESTRICTED

SHEET 48 - 134

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48403-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 2 mf plus 20 minus 10%; 400 vdcw; HS metal can; case 1 1/8" h x 2" wd x 2" thk; halowax impr and filled; two solder lug term 1" c to c on side; no int gnd connections; two integral mtg ears on bottom ends w/two 3/16" diam holes 2 3/8" c to c; same as NT-48403 except solder lug term.	RE13A488		16-C-49221-9847		R16-C-11460		CD	DE-4200	CEZ	CO-646	BL-6
		RE48A129						CSL	XDREW4-2	CRP	CO-775AK-C	GP-3 (2)
-48403-A10	CAPACITOR, fixed: 11/23/36 NT-48403-A w/2 mf p/m 10%. NOTE: TCB-2(2); TCE (2) thru TCE-2 (2); TOS-15.	RE13A488		16-C-49194-1186	N16-C-11479			CD	DE-4200	CEZ	CO-646	TBL-2(2)
		RE48A129						CSL	XDREW4-2	CRP	CO-775AK-C	TBL-3(4)
								CAW	630	CRR	A6680-1	TBL-5(2)
								CD	VC-278C	CRP	CO-775AK-C	TBL-6(2)
										CAY	T-7606991-4	TBL-7(2)
-48403-A20	CAPACITOR, fixed: 11/23/36 NT-48403-A w/2 mf p/m 20%.	RE13A488		16-C-49225-7552	N16-C-11480							TBL-10
		RE48A129										TBL-11
-48403-B	CAPACITOR, fixed: 12/9/40 paper dielectric; 2 mf plus 10 minus 3%; 600 vdcw; HS metal can; 2" lg x 2" wd x 1 1/8" h o/a; oil impr and filled; two solder lug term 3/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 3/8" c to c.	RE13A488		16-C-49176-3880	N16-C-11489-3			CAW	630	CADY	1032	SD-3
		RE48A129						CD	DY-6200	CRV	K-866923-1	SD-4
								CSF	2537-6			SR-2(B)
-48403-B5	CAPACITOR, fixed: 12/9/40 NT-48403-B w/2 mf p/m 5%.	RE13A488		16-C-49155-3880				CAW	630	CRV	K-866923-2	QFN
		RE48A129						CD	DY-6200	CRP	35-5007	SO-5
								CSF	2527-13			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-134

RESTRICTED

RESTRICTED

SHEET 48 - 135

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	COM-TRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48403-B10	CAPACITOR, fixed: NT-48403-B w/2 mf p/m 10%. NOTE: SJ-1; SI-a(2); SI-1 (2); SO-1 (2); thru SO-3 (2); SP-1M (2); SR-5; ST; T DT; VD-1 (4); VE-1; VF (6); VG-1 (2); MK-16; MK-27; MK-18 (2); MK-19 (2); MK-28 (2); MK-29 Mod 2; MK-34 Mod 2	RE13A488 RE48A129		16-C-49197-3880	N16-C-11489-3	R16-C-11712-250	3DBE.6200-6	CAW	630	CFP	35-5007	DAH-2 (3)
								CD	DY-6200	COL	956 2442 00	D K-1 (3)
								CD	DYR-6200-5	CHZ	00-830-B	DAK-3 (3)
								CSF	2527-13	CGZ	F-031-16	OAN (2)
								CSF	2528-8	CEV	A-6724	OBV
								CQU	AB-100	CPT	F-36435-1	QBD (5)
								CTD	RLO-602	CALG	8198	RCK
								CSL	XDMRW6-2-10	CZC	K-866923-1.	RDO
								CSF	FETS-370A	CW	ES-682063-56	RDZ-1
										CAY	T-7610894-61	SL-a
										CG	K-47J668-8	SD-1
										CG	K-34J180-1	SD-2
										CKV	L-61013-20	SG-1 (6)
		CWT	CU-11421ee1A	SG-2 (6)								
		CG	K-35J448rev1	VG-3 (2)								
				SEE NOTE								
-48403-B20	CAPACITOR, fixed: NT-48403-B w/2 mf p/m 20%. NOTE: MK-34 Mod 3 (2); MK-34 Mod 4 (2).	RE13A488 RE48A129		16-C-49227-7935	N16-C-11489-7		3DBE.602-3 3DBE.370B	CAW CD CSF CSL	630-2 DY-6200 2527-13 XDMRW6-2-20	COL CHZ CW	956 2444 00 CG-775-B ESA-682063-66	TCS-6 MK-12 Mod1 SEE NOTE
-48404	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 400 vdcw; HS metal can; 13/16" h x 2" wd x 1 3/4" thk; oil impr and filled; two stud and nut term 1" c to c on top; no int gnd connections; two integral mtg ears on bottom at the ends w/two 3/16" diam holes 2 3/8" c to c; superseded by NT-48404-B.	RE13A488		16-C-48793-1216								
-48404-A	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 400 vdcw; HS metal can; case 13/16" h x 2" wd x 1 3/4" thk; oil impr and filled; two riveted solder lug term 1" c to c on top; no int gnd connections; two integral mtg ears on bottom at the end w/two 3/16" diam holes 2 3/8" c to c; same as NT-48404 except term.	RE48A128 RE13A488		16-C-48793-1201								
-48404-A10	CAPACITOR, fixed: NT-48404-A w/1 mf p/m 10%.	RE48A128 RE13A488		16-C-48814-1196	N16-C-11397-11			CSL CAW	XDMRTW-4-1 430T-1	CW	ESA-682063-189	QJB

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-135

RESTRICTED

RESTRICTED

SHEET 48 - 136

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S C STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48404-B	CAPACITOR, fixed: 12/3/40 paper dielectric; 1 mf plus 10 minus 3%; 600 vdcw; ES metal can; 2" lg x 1 3/4" wd x 13/16" h; dykenol filled; two rivet lug type term 5/16" h on top, spaced 1" c to c; no int grd connections; two mtg ft 3/8" wd flush w/bottom, w/mtg holes 3/16" diam spaced 2 3/8" c to c; same as NT-48404-A except 600 vdcw.	REL134488 RE48A128		16-C-48796-3882				CD	DYT-6100			
-48404-B10	CAPACITOR, fixed: 12/3/40 NT-48404-B w/1 mf p/m 10%.	RE48A128 REL134488		16-C-48817-3750	N16-RC-14235		3DB1.6108S	CAW CSL CD CTD	630-1 XDMRTW6-1 DYRT-6100 RLON-601	CW	ES-682063-5	SL (3) SL-a (3) SL-1 (3) ST
-48405	CAPACITOR, fixed: 12/1/33 mica; 150 mmf; 10,000 vdcw, 4.0 amp at 3,000 kc, 3.0 amp at 1000 kc, 1.5 amp at 300 kc, 0.35 amp at 100 kc; case 2 1/2" h x 2 11/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48405-B5	CAPACITOR, fixed: 12/1/33 NT-48405 w/150 mmf p/m 5%; temp coef 1tr B.	RE48A132 16C40		16-C-28977-8768				CD	PL-587-59	CD CBS	4560	TBF-a TAZ-1 (3)
-48406	CAPACITOR, fixed: 12/14/33 mica; 5,000 mmf; 3,000 vdcw max, 9 amp at 3000 kc, 6 amp at 1000 kc, 4 amp at 300 kc, 2 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48406-A5	CAPACITOR, fixed: 12/14/33 NT-48406 w/5,000 mmf p/m 5%; temp coef 1tr A.	RE48A131 16C40		16-C-32696-4081	N16-C-10414			CD CRV CAY	PL-474-6 Paradon, case 351 1550-160	CRV CAY CAY	K-856829-1 rev 8 7406407-3 T-7605600-23 T-7606591-19	GP-3 (4) GP-4 TCE-1
-48406-B5	CAPACITOR, fixed: 12/14/33 NT-48406 w/5,000 mmf p/m 5%; temp coef 1tr B.	RE48A131 16C40		16-C-32696-4086	N16-C-10414			CD CRV CSL CAW	474-61S UC-3030 1550-160	CRV CAY	K-856829-1 T-7609856-19	TBL-4 (2) TBL-8 (2) TBL-9 (2) TCE-2 SO-2 Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-136

RESTRICTED

RESTRICTED

SHEET 48 - 137

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTORS DWG OR PART NO	EQUIPMENT USED IN
-48406-B10	CAPACITOR, fixed: 12/14/33 NF-48406 w/5,000 mmf p/m 10%; temp coef ltr B.	RE38A131 16C40		16-C-32701-5450	N16-C-10414-3			CD CRV CAW	PL-474-6L Faradon 1550L			
-48406-D2	CAPACITOR, fixed: 12/14/33 NF-48406 w/5,000 mmf p/m 2%; temp coef ltr D.	RE48A131 16C40		16-C-32690-6016				CAW	1550K230			
-48407	CAPACITOR, fixed: 12/14/33 mica; 5,000 mmf; 5,000 vdcw, 15 amp at 3000 kc, 17 amp at 1000 kc, 13 amp at 300 kc, 7 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast, aluminum end, cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48407-B5	CAPACITOR, fixed: 12/14/33 NF-48407 w/5,000 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-32696-4242				CD	PL-547-59	CG	P-7763250-18rev1	RA2-1
-48408	CAPACITOR, fixed: 12/14/33 mica; 10,000 mmf; 5,000 vdcw, 16 amp at 3000 kc, 20 amp at 1000 kc, 15 amp at 300 kc, 8 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast, aluminum end, term 3 3/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48408-A10	CAPACITOR, fixed: 12/14/33 NF-48408 w/10,000 mmf p/m 10%; temp coef ltr A.	RE48A132 16C40		16-C-33624-6721	N16-C-10524-3							
-48408-B5	CAPACITOR, fixed: 12/14/33 NF-48408 w/10,000 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-33619-6179				CD	PL-548-59	CG CES	P-7763250-21rev1	TAZ-1
-48408-B10	CAPACITOR, fixed: 12/14/33 NF-48408 w/10,000 mmf p/m 10%; temp coef ltr B. NOTE: QCR-1; QCS-1; QCT; QCT-1.	R 48A132 16C40		16-C-33624-6723				CD	PL-548-59	CEM	744-111	QCF QCC-1 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-137

RESTRICTED

RESTRICTED

SHEET 48 - 138

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFG	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48409	CAPACITOR, fixed: 12/14/33 mica; 5,000 mmf; 1,200 vdcw, $\pm 500v$ DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48409-A10	CAPACITOR, fixed: 12/14/33 NT-48409 w/5,000 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A502K	16-C-32700-1637				CB CAW	9-22050 1651			YB-2(3) YF (3)
-48409-B5	CAPACITOR, fixed: 12/14/33 NT-48409 w/5,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B502J	16-C-32695-1362	N16-C-10408			CU	9-22050			
-48409-B10	CAPACITOR, fixed: 12/14/33 NT-48409 w/5,000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B502K	16-C-32700-1642	N16-C-10409		3DKA5-69	CD CRV CAN	9L-22050 Model "F"	CRR CG CRV CG CBM CBM CBM	C-55564-441eeG P-7761560-9rev17 K-35482-46 W-7350697-231 P-7764888-47 744-232 744-423	TBL-4 (3) TBL-8 (3) TBL-9 (3) TBR (4) TBR-1 (4) TCK (4) TCK-1 (4)
	NOTE: thru TCK-7 (4); TCU; TCJ-1; TCM (4); TCM-2 (4); TCH (4); TCU-2 (4); WCA; WCA-1 thru WCA-3; WEB; YE; YE-1; YE-2.											SEE NOTE
-48409-B20	CAPACITOR, fixed: 12/14/33 NT-48409 w/5,000 mmf p/m 20%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B502M	16-C-32705-4122				CRV	AF, Faradon	CRV	K-35485-16	TBS(8) thru TBS-8 (8)
-48409-C10	CAPACITOR, fixed: 12/14/33 NT-48409 w/5,000 mmf p/m 10%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C502K	16-C-32700-1647	N16-C-10409							
-48410	CAPACITOR, fixed: 12/14/33 mica; 6,000 mmf; 600 vdcw, 1000vdc; case 1 1/4" lg x 1 1/8" wd x 23/64" thk max; molded bakelite case; two lug term w/one 0.173" diam holes; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 JAN-C-5										
-48410-A10	CAPACITOR, fixed: 12/14/33 NT-48410 w/6,000 mmf p/m 10%; temp coef ltr A.	RE48A221 JAN-C-5	CM45A602K	16-C-32857-8151	N16-C-10447-20		3DKA6-65	CD CD CSL CAN CAW	4-12060 4466 XQ H 1445	CAY CAY CAY CAY CAY CAY CAY	T-7609856-11 T-7605025-291 T-7606591-11 T-7605025-13 7605025-286 7607280-24 7606286-4 T-7606408-15	TBK-5 (12) TBK-6 (12) TBK-7 TBK-9 (11) TBM-4 (11) TBM-10 TBM-12(16) TCB-2 (6)
	NOTE: TCE-1 (2); TCE-2 (2).											SEE NOTE
-48410-B2	CAPACITOR, fixed: 12/14/33 NT-48410 w/6,000 mmf p/m 2%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B602G	16-C-32847-6196	N16-C-10447-14			CD	4L			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-138

RESTRICTED

RESTRICTED

SHEET 48 - 139

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48410-B3	CAPACITOR, fixed: 12/14/33 -48410 w/6,000 mmf p/m 3%; temp coef ltr B.	RE48A221 16C40		16-C-32851-8100	N16-C-10447-18			CD	4L			
-48410-B5	CAPACITOR, fixed: 12/14/33 NT-48410 w/6,000 mmf p/m 5%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B602J	16-C-32852-7676	N16-C-10447-16			CD CAW CAN CSL	4LS 1445LS HL XQBW			
-48410-B10	CAPACITOR, fixed: 12/14/33 NT-48410 w/6,000 mmf p/m 10%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B602K	16-C-32857-8156	N16-C-10448			CD CAW CAN CSL	4LS 1445LS HL XQBW	CAY CAY CAY CAY CAY CAY	7607470-28 7608226-32 T-7605025-291 T-7607093-14 T-7606233-9 T-7606286-13 T-7609144-13 T-7607321-13	TBK-11 TBK-13 TBK-15 TBL-2 (13) TBL-3 (13) TBL-5 (11) TBL-6 (11) TBL-7 (11)
	NOTE: BL-10 (10); TBL-11 (10); TBL-12 (11); TBL-13 (11); TBM (8); TBM-5 (15); TBM-6 (10); TBM-7 (15); TBU (10); TBU-1 thru TBU-4 (10); TCE; TDE (6); TDE-1 (6) thru TDE-3 (6).											SEE NOTE
-48410-B20	CAPACITOR, fixed: 12/14/33 NT-48410 w/6,000 mmf p/m 20%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B602M	16-C-32863-1636	N16-C-10448-1			CD CAW CAN CSL	4LS 1445LS HL XQBW	COL	910 2603 40	
-48410-C2	CAPACITOR, fixed: 12/14/33 NT-48410 w/6,000 mmf p/m 2%; temp coef ltr C.	RE48A221 16C40		16-C-32847-6201	N16-C-10447-14			CSL	MCW-6-26-20	CRP	35-5108	VD VD-1
-48411	CAPACITOR, fixed: 12/14/33 Paper dielectric; 4 mf plus 10 minus 3%; 1250 vdcw; HS metal can; 4 3/4" h x 2 1/2" diam; pyranol impr and filled; two stud and nut term 1 1/4" c to c along top diam; no int gnd connections.	RE48A185 RE13A488		16-C-49941-4410				CD	PC-135	CD	4582	
-48412	CAPACITOR, fixed: 1/17/34 mica; compression type, single sect; 10 to 70 mmf; 500 vdcw; 1 5/8" lg x 1" wd x 3/4" h; solder lug term; two mtg holes for #8-32 screw 1 1/4" c to c; sodr adj; isolantite base. NOTE: DP-2; PF-3.	16C40		16-C-64729-7427				CHC	MICS-70	CRV	K-30055-2rev0	DO DO-1 thru DO-3 DP DP-1 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVYSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-139

RESTRICTED

RESTRICTED

SHEET 48 - 140

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48413	CAPACITOR, fixed: 1/31/34 mica; 550 mmf; 2500 vdcw, 5000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5									
-48413-A10	CAPACITOR, fixed: 1/31/34 NT-48413 w/550 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A551K	16-C-30273-9262				CD	9-53055		TBF
-48413-B2	CAPACITOR, fixed: 1/31/34 NT-48413 w/550 mmf p/m 2%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B551G	16-C-30263-7307				CRV	Model "F"	CRV	K-35484-56rev9
-48414	CAPACITOR, fixed: 2/9/34 mica; 50,000 mmf; 500 vdcw, 12 amp at 3000 kc, 10 amp at 1000 kc, 7 amp at 300 kc, 5 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft, ea w/0.173" diam hole, mtg holes 1 1/4" c to c.	RE48A123 16C40									
-48414-B5	CAPACITOR, fixed: 2/9/34 NT-48414 w/50,000 mmf p/m 5%; temp coef ltr B.	RE48A123 16C40		16-C-35226-7257				CRV	UC-2236		
-48415	CAPACITOR, fixed: 3/2/34 mica; 6,000 mmf; 5,000 vdcw, 20 amp at 3000 kc, 23 amp at 1000 kc, 14 amp at 300 kc, 8 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40									
-48415-B5	CAPACITOR, fixed: 3/2/34 NT-48415 w/ 6,000 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-32854-6715				CRV	UC-3023		TAY-1
-48416	CAPACITOR, fixed: 3/2/34 mica; 1,500 mmf; 5,000 vdcw, 14.0 amp at 3000 kc, 10.0 amp at 1000 kc, 6.0 amp at 300 kc, 3.5 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40									
-48416-B5	CAPACITOR, fixed: 3/2/34 NT-48416 w/1,500 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-31509-4315				CRV	UC-2820		TAY-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-140

RESTRICTED

RESTRICTED

SHEET 48 - 141

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48417	CAPACITOR, fixed: 3/2/34 mica; 800 mmf; 10,000 vdcw, 11 amp at 3000 kc, 8 amp at 1000 kc, 5 amp at 300 kc, 2 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48417-B5	CAPACITOR, fixed: 3/2/34 NT-48417 w/800 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-30692-4871				CRV	UK-3081			TAY-1
-48418	CAPACITOR, fixed: 3/2/34 mica; 375 mmf; 10,000 vdcw, 7.0 amp at 3000 kc, 5.0 amp at 1000 kc, 2.5 amp at 300 kc, 1.0 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48418-B5	CAPACITOR, fixed: 3/2/34 NT-48418 w/375 mmf p/m 5%; temp coef ltr B. NOTE: LP-1 thru LP-4.	RE48A122 16C40		16-C-29863-2278				CAG CRV	539-407-1 UK-2829	CAG	539-5D	TAY-1 LP SEE NOTE
-48418-B10	CAPACITOR, fixed: 3/2/34 NT-48418 w/375 mmf p/m 10%; temp coef ltr B.	RE48A122 16C40		16-C-29863-2330	N16-C-10004-14			CRV	UK-2829			
-48419	CAPACITOR, fixed: 3/2/34 paper dielectric; 3 mf plus 10 minus 3%; 2200 vdcw; metal can; 9" lg x 4 1/2" wd x 8 3/4" h; oil filled; two screw type term 2 1/2" h located on top, spaced 6" c to c on por pillars; no int gnd connections; strap mtg not supplied; oil filler hole on top of can with plug and seal.	RE48A139		16-C-49563-9670				CAY	S 695774			
-48420	CAPACITOR, fixed: 3/13/34 paper dielectric; 16 mf tapped ea 1/2 mf; 150 vdcw as sect.											GH GH-1
-48421	CAPACITOR, fixed: 3/31/34 mica; 75 mmf; 6,000 vdcw; case 3 1/2" lg x 2" diam; metal case; one screw term 3/4" lg on bottom; thd mtg neck 3/4" lg, 3/4"-16 thd w/hex nut.	RE48A247 16C40										
-48421-B5	CAPACITOR, fixed: 3/31/34 NT-48421 w/75 mmf p/m 5%; temp coef ltr B.	RE48A247 16C40		16-C-28133-2576				CD	PL-590-66	CD	4573	GO

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-141

RESTRICTED

RESTRICTED

SHEET 48 - 142

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48422	CAPACITOR, fixed: mica; 100 mmf; 5,000 vdcw; case 3 1/2" lg x 2" diam; metal case; one screw term 3/4" lg on bottom; thd mtg neck 3/4" lg, 3/4"-16 thd w/hex nut.	3/31/34 RE48A247 16C40										
-48422-B5	CAPACITOR, fixed: NT-48422 w/100 mmf p/m 5%; temp coef 1tr B.	3/31/34 RE48A247 16C40		16-C-28555-1611				CD	PL-601-66	CD	4573	GO
-48423	CAPACITOR, fixed: sulphur; 25 mmf; 10,000 vdcw, 3 amp at 3000 kc, 1 amp at 1000 kc, 0.3 amp at 300 kc, 0.1 amp at 100 kc; case 2" lg x 2" diam; metal case; one screw term #10-32 thd, 1" lg incl ins on top; two mtg ft on bottom, ea w/one 3/16" diam hole on 2 7/16" mtg/c; add suffix indicating capacity tolerance in per cent.	3/31/34 RE48A263 16C40										
-48423-5	CAPACITOR, FIXED: Navy Type 48423 w/25 mmf p/m 5%. NOTE: TEM-4 thru TEM-8; TEM-12.	3/31/34 RE48A263 16C40		16-C-26946-7826	N16-C-9810			CD CAW	PL-341-62	CD CAY CAY CAY	4591 T-7605024-118 7607280-71 T-7607093-71 T-7605847-23	GO TBK-9 TBK-11 TBK-15 TBK-16 SEE NOTE
-48423-10	CAPACITOR, FIXED: Navy Type 48423 w/25 mmf p/m 10%.	3/31/34 RE48A443 16C40		16-C-56453-8741	N16-C-9811		3D9025-83	CD	PL-341-62	CD CAY CAY	4591 T-7605024-9 7605024-118	TBK-5 thru TBK-7
-48424	CAPACITOR, fixed: CANCELLED: for replacement use NT-48332	3/31/34 RE48A131 16C40						PL	PL-272-6			GO
-48425	CAPACITOR, fixed: mica; 600 mmf; 5,000 vdcw max, 5 amp at 3000 kc, 3 amp at 1000 kc, 1.6 amp at 300 kc, 0.8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	3/31/34 RE48A131 16C40										
-48425-A5	CAPACITOR, fixed: NT-48425 w/600 mmf p/m 5%; temp coef 1tr A.	3/31/34 RE48A131 16C40		16-C-30322-4118				CD	PL-266-6			GO
-48425-B5	CAPACITOR, fixed: NT-48425 w/600 mmf p/m 5%; temp coef 1tr B. NOTE: TAJ-10; TAJ-11; TAJ-13 thru TAJ-19.	3/31/34 RE48A131 16C40		16-C-30322-4123	N16-C-10050-1			CD CAW CD	PL-266-6L 1550-L-115 266A-6LS	CC CHR CC CC	ML-7660185-112 A26200-1 P-7762166-5 P-7762757-6	TAJ-6 TAJ-7 TAJ-8 (2) TAJ-9 SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-142

RESTRICTED

RESTRICTED

SHEET 48 - 143

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48425-B10	CAPACITOR, fixed: NT-48425 w/600 mmf p/m 10%; temp coef ltr B.	3/31/34 RE48A131 16C40		16-C-30327-5603	N16-C-10050			CD	PL-266-6L			
-48425-D2	CAPACITOR, fixed: NT-48425 w/600 mmf p/m 2%; temp coef ltr D.	3/31/34 RE48A131 16C40'		16-C-30317-2653				CD	PL-266-6E	CBM	744-81	JX-3
-48426	CAPACITOR, fixed: mica; 300 mmf; 5,000 vdcw max, 5 amp at 3000 kc, 2.5 amp at 1000 kc, 1 amp at 300 kc, 0.3 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	3/31/34 RE48A131 16C40										
-48426-A5	CAPACITOR, fixed: NT-48426 w/300 mmf p/m 5%; temp coef ltr A.	3/31/34 RE48A131 16C40		16-C-29662-9120				CD CRV	PL-611-6 UC-3109K	CRV CRV	DL-500498-503 K-35356-1	GO GP GP-2
-48426-B5	CAPACITOR, fixed: NT-48426 w/300 mmf p/m 5%; temp coef ltr B. NOTE: TBU-1 thru TBU-4.	3/31/34 RE48A131 16C40		16-C-29662-9125	N16-C-9999-3			CD	PL-611-61S	CAY CAY CG	T-7609144-34 T-7607321-34 W-7350697-224	TBR TBR-1 TBU SEE NOTE
-48426-C5	CAPACITOR, fixed: NT-48426 w/300 mmf p/m 5%; temp coef ltr C. NOTE: TCU; TCU-2.	3/31/34 RE48A131 16C40		16-C-29662-9128				CD CAN	PL-611-61S	CG	P-7761566-16 rev13	TCM TCM-2 SEE NOTE
-48427	CAPACITOR, fixed: paper dielectric; 550,000 mmf plus 10 minus 3%; 275 vacw at 800 cycles; HS metal can; case 1 13/16" lg x 1 1/16" wd x 2 1/8" h; oil impr and filled; two screw type term 1/2" h located on top 13/16" c to c; no int gnd connections; two mtg fl on side of case, ea w/one 3/16" diam mtg hole, 2 1/4" c to c.	3/31/34 RE48A147 RE13A488		16-C-47461-6110				CD	MC-121	CD	4563	GO
-48428	CAPACITOR, fixed: mica; 20,000 mmf; 600 vdcw, 1000 vdcvt; case 1 1/4" lg x 1 1/8" wd x 29/64" thk max; molded bakelite case; two lug term w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	3/31/34 RE48A221										Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-143

RESTRICTED

RESTRICTED

SHEET 48 - 144

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48428-A10	CAPACITOR, fixed: 3/31/34 NT-48428 w/20,000 mmf p/m 10%; temp coef ltr A. NOTE: LM-4; LM-4a; LM-5; LM-6; LM-7; LM-15; LM-16; LM-17; LP (9); LP-1 (9); LP-2 (9); LP-3 (9); LP-4 (9); LR (20); LR-1 (20); LR-2 (20); LR-3 (20); SX (2); TBM-10; TBM-12.	RE48A221 JAN-C-5	CM50A203K	16-C-34334-9650				CD CD CD CD CAW	4T-11020 4-652 4466 4S 1445	CRR CRR CRR CG CAT	A1728-10 A1728-1 A26111-1 744-37 7606286-14	GO LD-4 (5) LM LM-1 LM-2 SEE NOTE
-48428-B1	CAPACITOR, FIXED: 1/14/48 Navy Type 48428 w/20000 mmf p/m 1%; temp coef letter B.			16-C-34323-8910				CAN	H	CAN	812360 alt 1	QFA-3 QFA-4
-48428-B2	CAPACITOR, FIXED: 11/1/48 Navy Type 48428 w/20000 mmf p/m 2%; temp coef letter B.	JAN-C-5	CM50B203G	16-C-34324-7693				CD	4LS	CJF	SP-918	NAVU-2
-48428-B5	CAPACITOR, fixed: 3/31/34 NT-48428 w/20,000 mmf p/m 5%; temp coef ltr B.	RE48A221 JAN-C-5	CM50B203J	16-C-34329-9175	N16-C-10552-8			CAW CD CAW	1445LS 4LS 1455L	CRR	A26202-1	TAJ-8 (9)
-48428-B10	CAPACITOR, fixed: 3/31/34 NT-48428 w/20,000 mmf p/m 10%; temp coef ltr B. NOTE: TBM-6; TBM-7; TBM-8; TCB-2 (9); TLE (10); TDE-1 (10); TDE-2 (10); TDE-3 (10); MK-28 (3); MK-29 Mod 2 (3); MK-34 Mod 2 (3).	RE48A221 JAN-C-5	CM50B203K	16-C-34334-9655	N16-C-10550			CD CAW CAN	4LS-11020 1445LS	CV CAY CAY	ES-611146-1 T-7606286-14 T-7606408-10 7608226-9	GO-1 (10) GO-2 (10) TBM-13 TBM-5 SEE NOTE
-48428-B20	CAPACITOR, fixed: 3/31/34 NT-48428 w/20,000 mmf p/m 20%; temp coef ltr B.	RE48A221 JAN-C-5	CM50B203M	16-C-34340-3135	N16-C-10552-7			CD CAW CBM	4LS 1445LS	CBM	744-556	SF SF-1
-48429	CAPACITOR, fixed: 3/31/34 electrolytic; 20 mf; 50 vdcw; working temp range minus 20°C to plus 65°C; case 2 1/2" lg x 1" diam; tubr metal case; one solder lug term on top; neg term gnd internally; thd mtg neck 1/2" lg x 3/4" diam, 3/4"-16 thd w/palnut.	RE48A338 RE13A549		16-C-19709-1551		R16-C-9676		CD	MA-111-44-PE	CD	4593	
-48430	CAPACITOR, fixed: 3/31/34 paper dielectric; 40,000 mmf plus 10 minus 3%; 200 vdcw; HS metal case; case 1 1/8" lg x 7/16" diam; oil impr and filled; two axial wire leads; no int gnd connections. NOTE: LM-6 (2); LM-7 (2); LM-15 (2); LM-16 (2); LM-17 (2).	RE48A163 RE13A488		16-C-43849-1474				CD	HC507	CKB	15-A3006-1	GO LM-2(2) LM-4(2) LM-4a(2) LM-5 (2) SEE NOTE
-48430-10	CAPACITOR, FIXED: 3/31/34 Navy Type 48430 w/40000 mmf p/m 10%.	RE48A163 RE13A488		16-C-43870-1474	N16-C-11110-500			CD	RC507	CRR CD	A212 alt 0 4592	LM (2) LM-1 (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-144

RESTRICTED

RESTRICTED

SHEET 48 - 145

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48431	CAPACITOR, fixed: 3/31/34 mica; 250 mmf; 600 vdcw, 1000 vdc; case 1 1/4" lg x 1 1/8" wd x 11/32" thk; molded bakelite case; two lug term w/two 0.173" diam holes 1 3/4" c to c; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48431-A2	CAPACITOR, fixed: 3/31/34 NT-48431 w/250 mmf p/m 2%; temp coef ltr A.	RE48A221 16C40		16-C-29471-2991	N16-C-9975-7			CD	4-13025	CRR	A13753-5	GO LD-4
-48431-A10	CAPACITOR, fixed: 3/31/34 NT-48431 w/250 mmf p/m 10%; temp coef ltr A. NOTE: LR-2; LR-3.	RE48A221 16C40		16-C-29481-4951			3D9250-77	CD	4-13025			LR LR-1 SEE NOTE
-48431-B2	CAPACITOR, fixed: 3/31/34 NT-48431 w/250 mmf p/m 2%; temp coef ltr B. letter B.	RE48A221 16C40		16-C-29471-2996	N16-C-9975-7			CD	4LS			
-48431-B10	CAPACITOR, FIXED: 4/1/48 Navy Type 48431 w/250 mmf p/m 10%; temp coef			16-C-29481-4957				CD	4-13025	CJF	ST-2267	TDM
-48432	CAPACITOR, fixed: 4/13/34 paper dielectric; 500,000 mmf plus 10 minus 3%; 2500 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 4 3/4" h o/a; oil impr and filled; two screw type term 1 1/4" h located on top, spaced 13/16" c to c on por pillars; no int gnd connection; strap mtg not supplied.	RE48A139		16-C-47284-1551				CD	PC175	CD	4597	GO
-4 433	CAPACITOR, fixed: 4/13/34 paper dielectric; five sect; 3 mf/3 mf/ 3 mf/1 mf/ 1 mf plus 10 minus 3%; 125/125/125/125 vacw, 800 cps; HS metal can; case 3" h x 4 7/8" lg x 3 1/8" wd; mineral oil impr and filled; six stud and nut term ea 1" c to c x 1" c to c in 2 rows of 3 per row; no int gnd connections one side of all sect common.	RE48A186 RE13A488		16-C-54966-6632				CD	MC-119	CD	4598	GO
-48434	CAPACITOR, fixed: 5/2/34 paper dielectric; 250,000 mmf plus 10 minus 3%; 400 vdcw; HS metal can; case 1 13/16" lg x 1" wd x 3/4" h o/a; dykanol impr and filled; two solder lug term 3/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48288-B.	RE13A488 RE48A129		16-C-46322-3910				CD	DE-4025	CAY	7604 041-51	TAX-1 TBR-6 (4)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-145

RESTRICTED

RESTRICTED

SHEET 48 - 146

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	Com. tractor	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48435	CAPACITOR, fixed: 5/2/34 paper dielectric; 200,000 mmf plus 10 minus 3%; 300 vdcw; HS metal can; case 1 13/16" lg x 15/16" wd x 5/8" h o/a; oil impr and filled; two solder lug term 3/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48435-A.	RE13A488		16-C-46131-7812				CD	260	CAY CAY	32-D-442-2 sub 5 987262	TAY-1
-48435-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 200,000 mmf plus 10 minus 3%; 400 vdcw; HS metal can; case 1 13/16" lg x 1" wd x 5/8" h o/a; oil impr and filled; two solder lug term 3/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A129		16-C-46132-9445								
-48436	CAPACITOR, fixed: 5/2/34 CANCELLED ; for replacement use NT-48205-A or NT-481223.	RE48A129										TAY-1
-48437	CAPACITOR, fixed: 5/2/34 mica; 175 mmf; 600 vdcw, 1000v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48437-A10	CAPACITOR, fixed: 5/2/34 NT-48437 w/175 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-29112-2951				CD	9-130175			TAY-1
-48437-B2	CAPACITOR, fixed: 5/2/34 NT-48437 w/175 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-29101-9996								
-48438	CAPACITOR, fixed: 5/2/34 paper dielectric; 8 mf plus 10 minus 3%; 500 vdcw; HS metal can; case 2" h x 4 9/16" wd x 3 5/16" thk; oil impr and filled; two stud and nut term 1" h and 2" c to c on top; no int gnd connections; for replacement use NT-48438-A.	RE13A488		16-C-51455-4508				CAT		CAY	K-7808483-1 sub 0	TAY-1
-48438-A	CAPACITOR, fixed: 1/27/38 paper dielectric; 8 mf plus 10 minus 3%; 500 vdcw; HS metal can; 2" h x 4 1/2" wd x 3 5/16" d; oil impr and filled; two stud and nut term 1/2" h located on top, spaced 2" c to c; no int gnd connections; same as NT-48438 except term.	RE48A110 RE13A488		16-C-51455-4434								

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-146

RESTRICTED

RESTRICTED

SHEET 48 - 147

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48439	CAPACITOR, fixed: 5/2/34 paper dielectric; 20 mf plus 10 minus 3%; 500 vdcw; HS metal can; case 5 1/4" h x 4 9/16" wd x 3 5/16" thk; oil impr and filled; two stud and nut term 1" h and 2" c to c on top; no int gnd connections; for replacement use NT-48439-A.	RE13A488		16-C-52215-4508				CAY	K-7808483-2 sub 1	CAY		TAY-1
-48439-A	CAPACITOR, fixed: 1/27/38 paper dielectric; 20 mf plus 10 minus 3%; 500 vdcw; HS metal can; case 5 1/4" h x 4 1/2" wd x 3 5/16" d o/a; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections; same as NT-48439 except term.	RE48A110 RE13A488		16-C-52215-4434								
-48440	CAPACITOR, fixed: 6/20/34 mica; 80 mmf; 600 vdcw, 1,000v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded low loss bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48440-A10	CAPACITOR, fixed: 6/20/34 NT-48440 w/80 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-28162-6551				CD	9-14080			
-48440-B2	CAPACITOR, fixed: 6/20/34 NT-48440 w/80 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-28152-4591								
-48440-B10	CAPACITOR, fixed: 6/20/34 NT-48440 w/80 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-28162-6561	N16-C-9900			CD	9L-14080			
-48441	CAPACITOR, fixed: 6/20/34 mica; 9,000 mmf; 600 vdcw, 1,000v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48441-A10	CAPACITOR, fixed: 6/20/34 NT-48441 w/9,000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-33438-2551				CD	9-12090			
-48441-B10	CAPACITOR, fixed: 6/20/34 NT-48441 w/9,000 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-33438-2556	N16-C-10485			CD	9L-12090			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-147

RESTRICTED

RESTRICTED

SHEET 48 - 148

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48442	CAPACITOR, fixed: 7/7/34 mica; 750 mmf; 5,000 vdcw; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48442-B5	CAPACITOR, fixed: 7/7/34 NT-48442 w/750 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-30665-3441				CD	PL-596-59			TAZ-1
-4 4 3	CAPACITOR, fixed: 7/7/34 mica; 500 mmf; 6,000 vdcw, 7 amp at 3,000 kc, 5 amp at 1,000 kc, 3 amp at 300 kc, 1 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48443-B5	CAPACITOR, fixed: 7/7/34 NT-48443 w/500 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-30164-3152				CD	PL-544-59	CG	P-7763250-8rev1	TAZ-1
-48443-B10	CAPACITOR, fixed: 7/7/34 NT-48443 w/500 mmf p/m 10%; temp coef ltr B.	RE48A132 16C40		16-C-30169-3632				CD	PL-544-59			
-48444	CAPACITOR, fixed: 7/7/34 mica; 350 mmf; 6,000 vdcw; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48444-B5	CAPACITOR, fixed: 7/7/34 NT-48444 w/350 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-29794-521				CD	PL-605-59	CBS		TAZ-1 (3)
-48445	CAPACITOR, fixed: 7/7/34 mica; 250 mmf; 6,000 vdcw, 6.0 amp at 3,000 kc, 5.0 amp at 1,000 kc, 2.0 amp at 300 kc, 0.6 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48445-B5	CAPACITOR, fixed: 7/7/34 NT-48445 w/250 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-29478-4752				CD	PL-586-59	CG CBS	P-7763250-5rev1	TAZ-1 (3)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-148

RESTRICTED

RESTRICTED

SHEET 48 - 149

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48446	CAPACITOR, fixed: 7/7/34 mica; 200 mmf; 6,000 vdcw, 5.0 amp at 3,000 kc, 4.0 amp at 1,000 kc, 1.5 amp at 300 kc, 0.4 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48446-B5	CAPACITOR, fixed: 7/7/34 NT-48446 w/200 mmf p/m 5%; temp coef 1tr B.	RE48A132 16C40		16-C-29267-4632				CD	PL-543-59	CG CHS	P-7763250-4rev1	TAZ-1
-48447	CAPACITOR, fixed: 7/7/34 mica; 3,000 mmf; 6,000 vdcw, 14 amp at 3,000 kc, 15 amp at 1,000 kc, 11 amp at 300 kc, 6 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48447-B5	CAPACITOR, fixed: 7/7/34 NT-48447 w/3,000 mmf p/m 5%; temp coef 1tr B.	RE48A132 16C40		16-C-32195-3952				CD	PL-595-59			TAZ-1
-48448	CAPACITOR, fixed: 7/7/34 mica; 1,000 mmf; 6,000 vdcw, 10 amp at 3,000 kc, 7 amp at 1,000 kc, 4 amp at 300 kc, 1.7 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48448-B5	CAPACITOR, fixed: 7/7/34 NT-48448 w/1,000 mmf p/m 5%; temp coef 1tr B. NOTE: TBU-2; TBU-3; TBU-4.	RE48A132 16C40		16-C-31087-5152				CD CAW	PL-545-59	CG CAI CAY	P-7763250-11rev1 T-7609144-44 T-7607321-44	TAZ-1 TBU TBU-1 SEE NOTE
-48449	CAPACITOR, fixed: 9/21/34 mica; 30,000 mmf; 2,000 vdcw, 20 amp at 3,000 kc, 40 amp at 600 kc, 33 amp at 300 kc, 19 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48449-B5	CAPACITOR, fixed: 9/21/34 NT-48449 w/30,000 mmf p/m 5%; temp coef 1tr B. NOTE: TAQ-6 (4); TAQ-10 (2).	RE48A122 16C40		16-C-34726-5852	N16-C-10578			CD CAN	PL-697-50 PL-551A-50S	CG	M-7462694-5	TAQ-4 TAQ-5 (4) SEE NOTE

SHEET 48-149

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 150

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48450	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 1,000 vdcw; ES metal can; case 1 3/4" lg x 1" wd x 2 1/4" h o/a; pyranol impr and filled; two screw type term 1 5/32" h located on top, spaced 13/16" c to c on por pillars; no int gnd connections; strap mtg not supplied.	9/21/34 RE48A139		16-C-48799-6952	N16-C-11424-1			CG CD	9CE5A76 TA10010	CG CBM	H-3984539 rev9/14/34 744-121	TAQ-4 JK-2b JK-5 QC QCD
-48450-10	CAPACITOR, fixed: NT-48450 w/1 mf p/m 10%.	9/21/34 RE48A139		16-C-48820-6937	N16-C-11424					OW		MK-3 (2) MK-4 (2)
-48451	CAPACITOR, fixed: paper dielectric; 12 mf plus 10 minus 3%; 2,000 vdcw; ES metal can; case 3 3/4" lg x 4 9/16" wd x 5 5/8" h o/a; pyranol impr and filled; two screw type term 1 5/32" h located on top, spaced 2" c to c on por pillars; no int gnd connection, strap mtg not supplied.	9/21/34 RE48A139		16-C-51899-8285	N16-C-11692-13			CG	9CE5A75	CG	H-3984539 rev9/14/34	TAQ-4 WFA
-48451-10	CAPACITOR, fixed: NT-48451 w/12 mfd p/m 10%.	9/21/34 RE48A139		16-C-51899-8545				CD	TJU-10120			WFA
-48452	CAPACITOR, fixed: paper dielectric; 28 mf plus 10 minus 3%; 1,000 vdcw; ES metal can; case 3 3/4" lg x 4 9/16" wd x 4 5/8" h o/a; pyranol impr and filled; two screw type term 1 5/32" h located on top, spaced 2" c to c on por pillars; no int gnd connections; strap mtg not supplied.	9/21/34 RE48A139		16-C-52561-2830	N16-C-11695-98			CG	9CE5A74	CG	H-3984539 rev9/14/34	TAQ-4
-48453	CAPACITOR, fixed: paper dielectric; 500,000 mmf plus 10 minus 3%; 20,000 vdcw; ES metal can; case 13 1/2" lg x 4 1/8" wd x 12" h o/a; pyranol impr and filled; two screw type term 4 1/8" h located on top, spaced 6 3/4" c to c on por pillars; no int gnd connections; strap mtg not supplied.	9/24/34 RE48A139		16-C-47286-6507				CG	9CI3B7	CG	H-3943793-1 rev11/14/34	TBJ
-48454	CAPACITOR, fixed: paper dielectric; 4 mf plus 10, minus 3%; 2000 vdcw; ES metal can; case 3 3/4" lg x 2 1/4" wd x 3 7/8" h o/a; pyranol impr and filled; two screw type term 1 5/32" h located on top, spaced 2" c to c on por pillars; no int gnd connections; strap mtg not supplied.	9/24/34 RE48A139		16-C-49943-5928				CG	9CE5A20	CG	H-3984539 rev6-15-34	TBJ

SHEET 48-150

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 151

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48455	CAPACITOR, fixed; 9/24/34 paper dielectric; 2 mf plus 10 minus 3/4; 12500 vdcw; HS metal can; 13 7/16" lg x 4 3/16" wd x 12 1/8" h; pyranol impr and filled; two screw type term 4 1/8" h located on top, spaced 6 3/4" c to c on por pillars; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-49185-9990				CG	9CL3B14	CG	H-3943793-1 rev 11/14/34	TBJ
-48456	CAPACITOR, fixed; 9/24/34 paper dielectric; 4 mf plus 10 minus 3/4; 1500 vdcw; HS metal can; 3 7/8" lg x 2 3/8" wd x 3 7/8" h; pyranol impr and filled; two screw type term 1 1/8" h located on top, spaced 2" c to c on por pillars; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-49941-9129				CG	9CE5A17	CG	H-3984539 rev 7/26/34	TBJ
-48457	CAPACITOR, fixed; 9/24/34 paper dielectric; 4 mf plus 10 minus 3/4; 5000 vdcw; HS metal can; 13 7/16" lg x 4 3/16" wd x 7 1/8" h; pyranol impr and filled; two screw type term 2" h located on top, spaced 6 3/4" c to c on por pillars; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-49945-3013				CG	9CL3B24	CG	H-3943793-1 rev 11/14/34	TBJ
-48458	CAPACITOR, fixed; 9/24/34 paper dielectric; 4 mf plus 10 minus 3/4; 1000 vdcw; HS metal can; 3 3/16" lg x 1 11/32" wd x 3 3/4" h; pyranol impr and filled; two screw type term 1 11/32" h located on top, spaced 1 1/2" c to c on por pillars; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-49940-1172				CG	9CE5B1	CG	H-3984539 rev 7/26/34	TBJ
-48459	CAPACITOR, fixed; 9/24/34 Paper dielectric; 8 mf plus 10 minus 3/4; 1500 vdcw; HS metal can; 3 3/4" lg x 4 9/16" wd x 3 7/8" h; pyranol impr and filled; two por ins screw type term 1 5/32" h located on top, spaced 2 c to c; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-51461-1043				CG	9CE5A18	CG	H-3984539 rev 9/14/34	TBJ
-48460	CAPACITOR, fixed; 9/24/34 paper dielectric; 2 mf plus 10 minus 3/4; 1000 vdcw; HS metal can; 1 3/4" lg x 1" wd x 3 7/8" h; pyranol impr and filled; two por ins screw type term 1 5/32" h, located on top, spaced 13/16" c to c; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-49179-5675	N16-C-11490-14			CG CAW	9CE5A16 1009	CG CEZ	H-3984539 rev 9/14/34 CO-697	TBJ

SHEET 48-151

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48-152

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48 61	CAPACITOR, fixed: 9/24/34 paper dielectric; 2 mf plus 10 minus 3%; 2000 vdcw; HS metal can; 3 3/4" lg x 1 1/4" wd x 3 7/8" h; pyranol impr and filled; two por ins screw type term 1 5/32" h located on top, spaced 2" c to c; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-49169-9748				CG	9C85A19	CG	H-3984539 rev9/14/34	TBJ
-48462	CAPACITOR, fixed: 9/24/34 paper dielectric; 1 mf plus 10 minus 3%; 20,000 vdcw; HS metal can; 13 1/8" h x 13 9/16" wd x 5 11/16" thk; oil impr and filled; one high voltage stud and nut term 4 1/4" h on a por pillar and one gnd screw term 6 3/4" v to c on top; one side int gnd to case.	RE48A187 RE13A488		16-C-48806-6520				CG	9CL1B7	CG	K-3977138rev0	TBJ
-48463	CAPACITOR, fixed: 9/24/34 paper dielectric; 250,000 mmf plus 10, minus 3%; 20,000 vdcw; HS metal can; 13 1/2" lg x 4 1/8" wd x 7" h; pyranol impr and filled; two por ins screw type term 4 1/8" h located on top, spaced 6 3/4" c to c; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-46336-6507				CG	9CL3B8	CG	H-3943793-1 rev 11/14/34	TBJ
-48464	CAPACITOR, fixed: 9/24/34 paper dielectric; 1 mf plus 10 minus 3%; 20,000 vdcw; HS metal can; 13 1/2" lg x 5 1/8" wd x 13 1/8" h; pyranol impr and filled; two screw type term 4 1/8" h located on top, spaced 6 3/4" c to c on por pillars; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-48806-6507	N16-C-11437-17			CG	9CL3B5	CG	H-3943793-1 rev 11/14/34 P-7766168-2	TBJ TBC-5 (8) TDP-1 (3)
-48465	CAPACITOR, fixed: 9/24/34 mica; 5000 mmf; 5000 vdcw, 15 amp at 3000 kc, 17 amp at 1000 kc, 13 amp at 300 kc, 7 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 3 1/16" h; cast metal case; one pillar term shielded on top 1 1/2" h ctr, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	RE48A108 16C40										
-48 65-B5	CAPACITOR, fixed: 9/24/34 NT-48 65 v/5000 mmf p/m 5%; temp coef ltr B; for replacement use NT-481286.	RE 8A108 16C40		16-C-32696-4196				CD	PI-176-40			TBJ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-152

RESTRICTED

RESTRICTED

SHEET 48 - 153

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48466	CAPACITOR, fixed: mica; 10,000 mmf; 5,000 vdcw, 16 amp at 3000 kc, 20 amp at 1,000 kc, 15 amp at 300 kc, 8 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 3 1/16" h; cast metal case; one pillar term shielded on top 1 1/2" h ctr; one side gnd to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	9/24/34 RE48A108 16C40										
-48466-B5	CAPACITOR, fixed: NT-48466 w/10,000 mmf p/m 5%; temp coef 1tr B.	9/24/34 RE48A108 16C40		16-C-33619-6196				CD	PL-154-40			TBJ
-48467	CAPACITOR, fixed: mica; 1000 mmf; 6,000 vdcw, 10 amp at 3,000 kc, 7 amp at 1,000 kc, 4 amp at 300 kc, 2 amp at 100 kc; case 3 9/16" wd x 2 9/16" d x 2 15/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; two 1/4" mtg holes in base on 4 1/4" mtg/c.	9/24/34 RE48A109 16C40										
-48467-B5	CAPACITOR, fixed: NT-48467 w/1,000 mmf p/m 5%; temp coef 1tr B.	9/24/34 RE48A109 16C40		16-C-31087-5476				CD	PL-249-41			TBJ
-48468	CAPACITOR, fixed: mica; 2,000 mmf; 40,000 vdcw, 30 amp at 3,000 kc, 40 amp at 1,000 kc, 27 amp at 300 kc, 13 amp at 100 kc; case 14" lg x 7 1/4" diam; low loss ceramic case; two cast aluminum end cap term ea w/three 9/16" diam holes spaced 120 deg apart on 4 1/2" rad.	9/24/34 RE48A264 16C40										
-48468-B5	CAPACITOR, fixed: NT-48468 w/2000 mmf p/m 5%; temp coef 1tr B.	9/24/34 RE48A264 16C40		16-C-31801-5370				CD	PL-676-57	CD	4493	TBJ
-48469	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 440 vacw; HS metal can; 2 7/8" h x 1 13/16" wd x 1 1/16" d; two stud term 1/2" h located on top, spaced 13/16" c to c; no int gnd connections.	9/24/34 RE48A110 RE13A488		16-C-48794-8550				CD	PC-304			TBJ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-153

RESTRICTED

RESTRICTED

SHEET 48 - 154

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48470	CAPACITOR, fixed: 9/24/34 mica; 8,000 mmf; 3,000 vdcv max, 10 amp at 3,000 kc, 7 amp at 1,000 kc, 5 amp at 300 kc, 3 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" p to c.	RE48A131 16C40										
-48470-A5	CAPACITOR, fixed: 9/24/34 NT-48470 w/8,000 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-33223-3481				CD	PL-162-6			TBJ
-48470-B5	CAPACITOR, fixed: 9/24/34 NT-48470 w/8,000 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-33223-3486				CSL	XBBW-3-28-5	CAT	T-7606683-38	TAB-5 (2) TAB-6 (2) TAB-7 (2)
-48471	CAPACITOR, fixed: 9/24/34 mica; 16,000 mmf; 0.85 amp at 12 kc, 3.52 amp at 50 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/ two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48471-B5	CAPACITOR, fixed: 9/24/34 NT-48471 w/16,000 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-34146-5977				CD	PL-613-59			TBJ
-48472	CAPACITOR, fixed: 9/24/34 mica; 32000 mmf; test voltage effective 2000v, 1400 vdcv, 1.7 amp at 12 kc, 7.04 amp at 50 kc; 2 1/2" h x 2 13/16" diam; low-loss ceramic case; 2 elliptical cast aluminum end cap term 3 13/16" lg ea w/two 17/64" diam holes on 3 1/4" mtg/c.	RE48A132 16C40										
-48472-B5	CAPACITOR, fixed: 9/24/34 NT-48472 w/32,000 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-34769-4470				CD	PL-614-59			TBJ
-48473	CAPACITOR, fixed: 9/24/34 mica; 63,000 mmf; 3.33 amp at 12 kc, 13.86 amp at 50 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/ two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48473-B5	CAPACITOR, fixed: 9/24/34 NT-48473 w/63,000 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-35491-5775				CD	PL-615-59			TBJ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-154

RESTRICTED

RESTRICTED

SHEET 48 - 155

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48474	CAPACITOR, fixed: 9/24/34 mica; 10,000 mmf; 10,000 vdcw, 30 amp at 3,000 kc, 37 amp at 1,000 kc, 25 amp at 300 kc, 15 amp at 100 kc; case 5" diam x 4" h; ceramic case; one fl elliptical end term ea end, two 3/8" diam holes in ea term 5 3/4" c to c.	RE48A116 16C40										
-48474-B5	CAPACITOR, fixed: 9/24/34 NT-48474 w/10000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-33620-4484				CRV	U-3188			TBJ
-48475	CAPACITOR, fixed: 10/1/34 mica; 100 mmf; 6,000 vdcw, 5.5 amp at 25,000 kc, 5.0 amp at 8,000 kc, 2.5 amp at 2,000 kc, 3.0 amp at 3,000 kc, 2.0 amp at 1,000 kc; 0.9 amp at 300 kc, 0.3 amp at 100 kc; case 2 1/2" lg x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/ two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 JAN-C-5										
-48475-B5	CAPACITOR, fixed: 10/1/34 NT-48475 w/100 mmf p/m 5%; temp coef ltr B.	RE48A132 JAN-C-5	CM75B101J	16-C-28555-2676				CD	PL-542-59	CG	P-7763250-1rev1	TBA-2
-48476	CAPACITOR, fixed: 10/1/34 mica; 1,500 mmf; 5,000 vdcw, 14 amp at 26,000 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/ two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48476-B5	CAPACITOR, fixed: 10/1/34 NT-48476 w/1,500 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-31509-4231				CD	PL-686-59			TBA-2
-48477	CAPACITOR, fixed: 10/22/34 mica; 750 mmf; 5,000 vdcw max, 5 amp at 3,000 kc, 3.5 amp at 1,000 kc, 2 amp at 300 kc, 1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes, 2 5/8" c to c.	RE48A131 16C40										
-48477-A5	CAPACITOR, fixed: 10/22/34 NT-48477 w/750 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-30665-3318				CD	PL-654-6	CAY	7604989-48	TBK TBK-5 (2) TBK-6 (2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-155

RESTRICTED

RESTRICTED

SHEET 48 - 156

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48477-B2	CAPACITOR, fixed: 10/22/34 NT-48477 w/750 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-30660-1843				CD	PL-654-6LS	CG	7350661-102	TAJ-7
-48477-B5	CAPACITOR, fixed: 10/22/34 NT-48477 w/750 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-30665-3323				CD	PL-654-6			
-48477-D2	CAPACITOR, fixed: 10/22/34 NT-48477 w/750 mmf p/m 2%; temp coef ltr D. NOTE: TBK-9(2); TBK-11(2); TBK-13; TBK-15(2); TBK-16(2); TBL-2(4); TBL-3(4); TBL-4(2); TBL-5; TBL-6(2); TBL-7; TBL-8(2); TBL-12(2);	RE48A131 16C40		16-C-30660-1853	N16-C-10071	R16-C-10039-500		CD CAW	PL-654-6L 1550-H-215	CG CAY CAY CAY CAY	7762166-3 T-7605497-47 T-7605497-3 7607280-15 7607470-16 T-7605847-99	TAJ-9 TAJ-10 TAJ-11 TAJ-13 thru TAJ-19 TBK-7(2) SEE NOTE
-48477-D5	CAPACITOR, fixed: 10/22/34 NT-48477 w/750 mmf p/m 5%; temp coef ltr D.	RE48A131 16C40		16-C-30665-3333				CD	PL-654-6H	CG	ML-7350609-2	TAJ-6
-48478	CAPACITOR, fixed: 10/22/34 mica: 100,000 mmf; 1,000 vdcv max, 18 amp at 3,000 kc, 15 amp at 1,000 kc, 12 amp at 300 kc, 7 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; moulded low loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg rt w/ two 3/16" diam mtg holes, 2 5/8" c to c.	RE48A131 16C40										
-48478-B5	CAPACITOR, fixed: 10/22/34 NT-48478 w/100,000 mmf p/m 5%; temp coef ltr B. NOTE: TBK-13; TBK-15; TBK-16; TBL-2; TBL-3; TBL-5; TBL-6; TBL-7; TBL-10 thru TBL-13; TBM-5 thru TBM-8; TBM-12.	RE48A131 16C40		16-C-36150-3514	N16-C-10701	R16-C-10652		CD	PL-406-6	CBM CAY CAY CAY CAY	744-84 7607280-20 7607470-27 T-7705829-5 T-7607093-20 T-7605847-96	TBK NM-11 thru NM-13a QCJ(2) QCK(2) TBK-11 SEE NOTE
-48478-C5	CAPACITOR, fixed: 10/22/34 NT-48478 w/100,000 mmf p/m 5%; temp coef ltr C.	RE48A131 16C40		16-C-36150-3519	N16-C-10701			CD	PL-406-6LS	CBM	744-84	JK-3 QC-7(2) QCG(2)
-48478-D5	CAPACITOR, fixed: 10/22/34 NT-48478 w/100,000 mmf p/m 5%; temp coef ltr D. NOTE: TBK-9; TBM-4.	RE48A131 16C40		16-C-36150-3524				CD	PL-406-6HB	CAY	P-7705829-5	TBK-6 TBK-7 SEE NOTE
-48479	CAPACITOR, fixed: 10/22/34 CANCELLED: for replacement use NT-48204.	RE48A131 16C40						CD	PL-140-6			TAJ-5 TBK

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-156

RESTRICTED

RESTRICTED

SHEET 48 - 157

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48480	CAPACITOR, fixed: 10/22/34 mica; 150 mmf; 10,000 vdcw, 7.5 amp at 4,525 kc, 5.0 amp at 3,000 kc, 4.2 amp at 2,000 kc, 3.8 amp at 1,000 kc, 3.5 amp at 300 kc, 1.3 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/ two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48480-B5	CAPACITOR, fixed: 10/22/34 NT-48480 w/150 mmf p/m 5%; temp coef 1tr B. NOTE: TBK-6; TBK-7.	RE48A122 16C40		16-G-28977-8871	N16-C-9961-4			CD	PL-315-50	CAY CAY	T-7605024-9 7605024-48	TBK TBK-5 SEE NOTE
-48481	CAPACITOR, fixed: 10/22/34 mica; 375 mmf; 5,000 vdcw max, 4 amp at 3,000 kc, 2.5 amp at 1,000 kc, 1 amp at 300 kc, 0.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48481-A5	CAPACITOR, fixed: 10/22/34 NT-48481 w/375 mmf p/m 5%; temp coef 1tr A.	RE48A131 16C40		16-C-29863-2225				CD	PL-656-6	CAY	7604989-47	TBK TBK-5 TBK-6
-48481-D2	CAPACITOR, fixed: 10/22/34 NT-48481 w/375 mmf p/m 2%; temp coef 1tr B. NOTE: TBL-2; TBL-3; TBL-5; TBL-6; TBL-7; TBL-10 thru TBL-13; TBM-4 thru TBM-6; TBM-8; TBM-11; TBM-12.	RE48A131 16C40		16-C-29863-2175	N16-C-10004			CD	PL-656-6L	CAY CAY CAY CAY	T-7605497-46 T-7605497-3 7607280-70 7607470-17 T-7607093-70 T-7605847-98	TBK-7 TBK-9 TBK-11 TBK-13 TBK-15 TBK-16 SEE NOTE
-48482	CAPACITOR, fixed: 10/22/34 mica; 12,000 mmf; 4,000 vdcw, 16 amp at 3,000 kc, 20 amp at 1,000 kc, 15 amp at 300 kc, 8 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/ two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48482-B5	CAPACITOR, fixed: 10/22/34 NT-48482 w/12,000 mmf p/m 5%; temp coef 1tr B.	RE48A132 16C40		16-C-33804-1485				CD	PL-663-59			TAJ-5

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-157

RESTRICTED

RESTRICTED

SHEET 48 - 158

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48483	CAPACITOR, fixed: 10/22/34 mica; 2,500 mmf; 5,000 vdcw max, 9 amp at 3,000 kc, 6 amp at 1,000 kc, 3.5 amp at 300 kc, 2 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; moulded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48483-A5	CAPACITOR, fixed: 10/22/34 NT-48483 w/2500 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-32010-5718				CD	PL-473-6			TAJ-5
-48484	CAPACITOR, fixed: 10/22/34 mica; 600 mmf; 6,000 vdcw, 8 amp at 3,000 kc, 6 amp at 1,000 kc, 3 amp at 300 kc, 1 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at ea end w/ two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48484-B5	CAPACITOR, fixed: 10/22/34 NT-48484 w/600 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-30322-5552	N16-C-10190-28			CD	PL-664-59			TAJ-5
-48485	CAPACITOR, fixed: 10/22/34 mica; 1,500 mmf; 5,000 vdcw max, 9 amp at 3,000 kc, 5.5 amp at 1,000 kc, 4 amp at 300 kc, 1.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48485-A5	CAPACITOR, fixed: 10/22/34 NT-48485 w/1,500 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-31509-4118				CD	PL-234-6			TAJ-5
-48485-B2	CAPACITOR, fixed: 10/22/34 NT-48485 w/1,500 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-31504-2643				CD	PL-234-6LS	CG	7350661-101	TAJ-7
-48485-B5	CAPACITOR, fixed: 10/22/34 NT-48485 w/1,500 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-31509-4123				CRV CD CD	UC-3062A PL-234-6 PL-234-6LS	CRV CG	K-860215-15rev6 7660185-111	TAJ-7
-48485-D2	CAPACITOR, fixed: 10/22/34 NT-48485 w/1,500 mmf p/m 2%; temp coef ltr D. NOTE: TAJ-11(2); TAJ-13(2) thru TAJ-19(2); TBL-2; TBL -3; TBL-5; TBL-6; TBL-7; TBL-10 thru TBL-13.	RE48A131 16C40		16-C-31504-2653	N16-C-10190			CD CAW	PL-234-6K 1550-H-319	CG CAY	P-7762166-2 7607470-72	TAJ-9(2) TAJ-10(2) SEE NOTE
-48485-D5	CAPACITOR, fixed: 10/22/34 NT-48485 w/1,500 mmf p/m 5%; temp coef ltr D.	RE48A131 16C40		16-C-31509-4133				CD	PL-234-6H	CG	ML-735069-1	TAJ-6

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-158

RESTRICTED

RESTRICTED

SHEET 48 - 159

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48486	CAPACITOR, fixed: 10/22/34 mica; 20,000 mmf; 1,200 vdcw, 2500v DC test; case 1 25/32" lg max x 1 11/32" wd max x 3/4" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48486-A10	CAPACITOR, fixed: 10/22/34 NT-48486 w/20,000 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM60A203K	16-C-34335-5593		R16-C- 10535-103-100		CD CSL	9-21020 DHW1.2-12-10			TAJ-5
-48486-B5	CAPACITOR, fixed: 10/22/34 NT-48486 w/20,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B203J	16-C-34330-5119	N16-C-10555-18	R16-C- 10535-101-950		CD	9L-21020			
-48486-B10	CAPACITOR, fixed: 10/22/34 NT-48486 w/20,000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B203K	16-C-34335-5594	N16-C-10555-19			CD	9L-21020			
-48486-B20	CAPACITOR, fixed: 10/22/34 NT-48486 w/20,000 mmf p/m 20%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B203M	16-C-34340-8079	N16-C-10555-20			CD	9L-21020			
-48487	CAPACITOR, fixed: 10/22/34 mica; 10,000 mmf; 600 vdcw, 1000 vdct; case 1 1/4" lg x 1 1/8" wd x 23/64" thk max; molded bakelite case; two lug term w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 JAN-C-5										
-48487-A2	CAPACITOR, fixed: 10/22/34 NT-48487 w/10,000 mmf p/m 2%; temp coef ltr A.	RE48A221 JAN-C-5	CM45A103G	16-C-33612-5791	N16-C-10500-25			CD	4-11010	CG	K-27J77-6	TAJ-5 SC-2
-48487-A5	CAPACITOR, fixed: 10/22/34 NT-48487 w/10,000 mmf p/m 5%; temp coef ltr A.	RE48A221 JAN-C-5	CM45A103J	16-C-33617-7271	N16-C-10501-1			CSL	IQW.6-11-5	CRP	35-5045	SG SG-1 SG-28
-48487-A10	CAPACITOR, fixed: 10/22/34 NT-48487 w/10,000 mmf p/m 10%; temp coef ltr A. NOTE: RAL-7; SG(19); SG-1(17); SG-28(17); TCE(2); TCE	RE48A221 JAN-C-5	CM45A103K	16-C-33622-7751	N16-C-10501-2			CAW CD CSL	1445-01 4-11010 IQW.6-11-10	CRV CGZ CRP CAY CCI CFT	P-720567-22 033 35-5008 T-7609856-7 M-7406466-9 T-7606991-7	GP-3(2) GP-4(2) LAG (4) LAG-1(4) LR thru IR-3 SEE NOTE
-48487-B2	CAPACITOR, fixed: 10/22/34 NT-48487 w/10,000 mmf p/m 2%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B103G	16-C-33612-5796	N16-C-10501			CSF CSL CAW CD	MX-12B IQW 1445LS 4SL-11010	CG CW	K-35J292-1 rev1	MK-9 (2) MK-10 (2) MK-10 Mod5 (2) MK-18 (2)
-48487-B5	CAPACITOR, fixed: 10/22/34 NT-48487 w/10,000 mmf p/m 5%; temp coef ltr B. NOTE: DAB-3(10); SC-2; SC-3; SK-2.	RE48A221 JAN-C-5	CM45B103J	16-C-33617-7276	N16-C-10501-7		3E4510322	CD CAN	4LS HL-1110	COL CG	910 1103 10 K-35J292-3;rev3	DAB (10) DAB-1 (10) SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-159

RESTRICTED

RESTRICTED

SHEET 48 - 160

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48487-B10	CAPACITOR, fixed: 10/22/34 NT-48487 w/10,000 mmf p/m 10%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B103K	16-C-33622-7756	N16-C-10501-3		3K4510321	CD CSL CAN CAW	41S11010 XQB6-11	CW CHZ CW OG CHZ CAY CGQ CAY CW	ES-611146-1 CO-778 ES0-609852-1 P-7762925-51rev0 7761328-16 CO-734 T-7606408-9 B-CO-734 760266-8 ES-682066-18	GO-2 (2) GP-1 (9) QH (3) QH-1 (3) SC-4 (4) SK-3 (4) SP-1M (4) TBO (2) TBO-1 (2) TRX-h (6) SEE NOTE
	NOTE: TRX-4a (6); TRX-5 (6); TRX-8 (2); TCB-2 (16); MK-10 Mod 5 (12); MK-15 (8); MK-18 (9); MK-28; MK-29	TCK-1 thru TCK-7; TCS-6 (2)	TCK-7; TCS-6 (2)	TDE-3 (14); V	C-1 (4); VG (4);	VG-1 (4); VG-3 (4);						
-48487-B20	CAPACITOR, fixed: 10/22/34 NT-48487 w/10,000 mmf p/m 20%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B103M	16-C-33622-1236	N16-C-10501-18		3K4510324	CD CAW	4EHS	CHZ CW	CO-667	SJ-1(5) YH(2) YH-1(2) SEE NOTE
	NOTE: MK-8 Mod 2 (5); MK-8 Mod 3 (5); MK-16 (5); MK-27 (5)											
-48488	CAPACITOR, fixed: 10/22/34 mica; 4,000 mmf; 2,500 vdcw, 5000 vdcw; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48488-A10	CAPACITOR, fixed: 10/22/34 NT-48488 w/4,000 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A402K	16-C-32463-3462		R16-C-10393		CD	9-52040			TAJ-5
-48488-B5	CAPACITOR, fixed: 10/22/34 NT-48488 w/4,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B402J	16-C-32458-2987	N16-C-10379-3			CD	9-52040			
-48488-B10	CAPACITOR, fixed: 10/22/34 NT-48488 w/4,000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B402K	16-C-32463-3467	N16-C-10379-12	R16-C-10367		CD	9L-52040	CW	ESQ-611146-2	GO-1 GO-2
-48488-B20	CAPACITOR, fixed: 10/22/34 NT-48488 w/4,000 mmf p/m 20%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B402M	16-C-32468-5947	N16-C-10379-13			CD	9L-52040			
-48489	CAPACITOR, fixed: 10/22/34 paper dielectric; 50 mf plus 10 minus 3%; 500 vdcw; HS metal can; 1 1/2" h x 4 5/8" wd x 3 3/8" d; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-52663-1600	N16-C-11698-24			CAY	S 831723	CAY	41-D-495-6 rev 4	TAJ-5 TBK
-48490	CAPACITOR, fixed: 10/22/34 paper dielectric; 12 mf plus 10 minus 3%; 1000 vdcw; HS metal can; 1 1/2" h x 4 5/8" wd x 3 3/8" d; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-51899-8280	N16-C-11692-9			CAY	S 835308	CAY	41-D-495-5 rev 4	TAJ-5 TBK

SHEET 48-160

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 161

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48491	CAPACITOR, fixed: 10/22/34 paper dielectric; 8 mf plus 10 minus 3/4; 1,500 vdcw; BS metal can; 10 1/2" h x 4 5/8" wd x 3 3/8" d; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-51462-1127	N16-C-11646-63			CAY	S-895310	CAY	41-D-495-6 rev 4	TAJ-5 TBK
-48492	CAPACITOR, fixed: 10/22/34 paper dielectric; 4.5 mf plus 10 minus 3/4; 1000 vdcw; BS metal can; 2 3/4" h x 4 5/8" wd x 3 3/8" d; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-50130-4392	N16-C-11587			CAY	S 881566	CAY	41-D-495-1 rev 4	TAJ-5 TBK
-48493	CAPACITOR, fixed: 10/22/34 paper dielectric; 4.5 mf plus 10 minus 3/4; 3,000 vdcw; BS metal can; 4 5/8" lg x 3 3/8" wd x 10 1/2" h; pyranol impr and filled; two screw type term 2 1/8" h located on top, spaced 2 1/8" c to c on per pillars; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-50134-6616				CAY	S 895309	CAY	41-D-496-6 rev 4	TAJ-5 TBK
-48494	CAPACITOR, fixed: 10/22/34 paper dielectric; 200,000 mmf plus 10 minus 3/4; 3,000 vdcw; BS metal can; 4 5/8" lg x 3 3/8" wd x 2 3/4" h; oil impr and filled; two por ins screw type term 2 1/8" h located on top, spaced 2 1/8" c to c; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-46144-6616	N16-C-11340-24			CAY	S 895311	CAY	41-D-496-1 rev 4	TAJ-5 TBK
-48495	CAPACITOR, fixed: 10/22/34 paper dielectric; 100,000 mmf plus 10 minus 3/4; 5,000 vdcw; BS metal can; 3 3/4" lg x 1 1/4" wd x 4 7/8" h; oil impr and filled; two ceramic ins screw type term 1 1/4" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 3/16" diam mtg holes 1/2" apart, 4 1/4" o to c.	RE48A159 RE13A488		16-C-45765-2249				CD	PC-331	CAY	K-7808801 sub 1	TAJ-5 TBK
-48496	CAPACITOR, fixed: 10/22/34 paper dielectric; 500,000 mmf plus 10 minus 3/4; 1,500 vdcw; BS metal can; 1 3/4" lg x 1" wd x 4" h; oil impr and filled; two screw type term 3/8" h located on top 3/4" c to c; no int gnd connections; two mtg fl 15/16" wd on sides of case, ea w/3/16" diam mtg hole 2 1/4" c to c.	RE48A147 RE13A488		16-C-47281-6263				CD	VO-263	CAY	K-7808799 sub 0	TAJ-5 TBK SX (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-161

RESTRICTED

RESTRICTED

SHEET 48 - 162

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
48497	CAPACITOR, fixed: 10/22/34 paper dielectric; 150,000 mf plus 10 minus 3%; 500 vdcw, 1000v DC test; BS metal can; 1 13/16" wd x 2 1/32" h x 2 1/8" lg; oil impr and filled; two solder lug term 3/8" on end of case 1" c to c; no int gnd connections; three 3/8" wd mtg ft on end ea w/0.154" diam mtg hole, two on one end 1 13/32" c to c 2 1/2" from hole on other end; for replacement use NT-48497-A.	REL3A488		16-C-45945-1622	N16-C-11336-105					CAY	K-7808834rev0	
48497-A	CAPACITOR, fixed: 5/6/38 paper dielectric; 150,000 mf plus 10 minus 3%; 500 vdcw, 1,000v DC test; BS metal can; 1 13/16" lg x 2 1/32" wd x 2 1/8" h; oil impr and filled; two solder lug term 3/8" h on end of case 1" c to c; no int gnd connections; three 3/8" wd mtg ft on end ea w/0.154" diam mtg hole, two on one end 1 13/32" c to c 2 1/2" from hole in other end.	RE48A145 REL3A488		16-C-45945-1622								
48498	CAPACITOR, fixed: 10/27/34 paper dielectric; 1 mf plus 10 minus 3%; 600 vdcw; metal can; 1 3/4" lg x 1" wd x 2 1/8" h; oil impr and filled; two screw type term 3/8" h located on top 3/4" c to c; no int gnd connections; two mtg fl on bottom of case 15/16" wd w/3/16" diam mtg hole 2 1/4" c to c; replace w/NT-48498-A. NOTE: NMB-2 (2); QCF (2); QCU-5 (2); QCU-6 (2); QCL-4 (2); QCL-5 (2); QCM-2 (2); QCM-3; QCM-4; QC N-2; QCO-2; QCO (2); QCR (2); QCR-1 (2); QCT (2).			16-C-48796-2932	N16-C-11416-5			CD	TD-6010	CEM CAY	744-42 K-7808812-1rev0	TRK MM-13 (2) MM-13a (2) MM-11 (2) MM-12 (2) MM-15 (2) NMA (2) SEE NOTE
48498-10	CAPACITOR, fixed: 10/27/34 NT-48498 w/1 mf p/m 10%.			16-C-48817-2837	N16-C-11416-6			CD	TDF-6010-1	CEM	744-42	WAB (2) WCA (2) WCA-1 (2)
48498-A	CAPACITOR, fixed: 3/20/37 paper dielectric; 1 mf plus 10 minus 3%; 600 vdcw; BS metal can; 1 3/4" lg x 1" wd x 2 1/8" h; oil impr and filled; two screw type term 3/8" h located on top 3/4" c to c; no int gnd connections; two mtg fl on bottom of case 15/16" wd w/3/16" diam mtg hole 2 1/4" c to c; same as NT-48498 except BS.	RE48A147 REL3A488		16-C-48796-2882		N16-C-11417		CD	TD-6010	CAY	T-7607321-10	GO-3 TBU thru TBU-3
48498-A10	CAPACITOR, fixed: 3/20/37 NT-48498-A w/1 mf p/m 10%.	RE48A147 REL3A488		16-C-48817-2837	N16-C-11416-6			CD	TD-6010	CAY CAY	T-7609144-10 T-7606408-40	TBU-4 TCB-2 (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-162

RESTRICTED

RESTRICTED

SHEET 48 - 163

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48499	CAPACITOR, fixed: 11/1/34 paper dielectric; 10 mf plus 10 minus 3%; 1,500 vdcw; HS metal can; case 3 7/8" lg x 4 5/8" wd x 4 5/8" h; oil impr and sealed; two por ins screw type term 1 1/8" h located on top, spaced 2" c to c; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-51841-9236				CG	90E5A77	CG	H-3984539 rev9/13/34	TAW-1
-48500	CAPACITOR, fixed: 11/1/34 paper dielectric; 15 mf plus 10 minus 3%; 5,000 vdcw; HS metal can; case 13 1/2" lg x 4 1/8" wd x 12" h o/a; pyranol impr and sealed; two por ins screw type term 3" h located on top, spaced 6 3/4" c to c; no int gnd connections; strap mtg not supplied.	RE48A139		16-C-52035-3013				CG	90L3B22	CG	H-3943793-1 rev11/14/34	TAW-1
-48501	CAPACITOR, fixed: 11/15/34 mica dielectric; 17,000 mmf; 12,500 vdcw 21 amp at 15 kc, 47 amp at 34 kc; 17 1/2" diam x 24" h; steel case, oil-filled; four mtg ears spaced 90 deg apart on bottom of case ea w/ one 9/16" diam hole on 12 3/4" x 12 3/4" mtg/c; spark gap protection from surge.	RE48A265 16C40		16-C-34189-1795				CD	PL-684-77 case 77	CD	4617B	TAW-1
-48502	CAPACITOR, fixed: 11/15/34 mica dielectric; c/o six capacitors stacks mtd as a unit, five units required for NT-48501.	RE48A265 16C40						CD	PL-684-78 case 77			TAW-1
-48503	CAPACITOR, fixed: 12/10/34 paper dielectric; 4 mf plus 10 minus 3%; 3,000 vdcw; HS metal can; case 3 3/4" lg x 4 9/16" wd x 5 11/16" h; pyranol impr and filled; two pillar ins screw type term 2" h, located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/3/16" diam mtg holes 4 3/8" c to c.	RE48A146 RE13A488		16-C-49944-6594				CG	90E5A6	CD	H-3943793-1	TAQ-4
-48504	CAPACITOR, fixed: 1/8/35 paper dielectric; 2 mf plus 10 minus 3%; 3,000 vdcw; HS metal can; case 3 3/4" lg x 3 3/16" wd x 4 11/16" h; pyranol impr and filled; two pillar ins screw type term 2" h, located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/ 3/16" diam mtg hole 4 3/8" c to c; replace w/NT-48504-A.	RE48A146		16-C-49184-6098				CG	90E5A5	CG CRV	X-823188rev0 W-300289-100	TBL TBL-1
-48504-10	CAPACITOR, fixed: 1/8/35 NT-48504 w/2 mf p/m 10%.	RE48A146		16-C-49205-6108	N16-C-11495-1		3DB2.200-1					

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-163

RESTRICTED

RESTRICTED

SHEET 48 - 164

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48504-A	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 3,000 vdcw; HS metal can; case 3 3/4" lg x 3 3/16" wd x 4 11/16" h; pyranol impr and filled; two per line screw type term 2" h, located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/ 3/16" diam mtg hole 4 3/8" c to c.	5/5/38 RE48A146 REL13A488		16-C-49184-6099	N16-C-11495							
-48504-A10	CAPACITOR, fixed: NT-48504-A w/2 mf p/m 10%.	5/5/38 RE48A146 REL13A488		16-C-49205-6108	N16-C-11495		3DB2-200-1	CRV	72014-507			NAL-5
-48505	CAPACITOR, fixed: paper dielectric; 15 mfd plus 10 minus 3%; 330 vdcw; HS metal can; 4 5/8" h x 3 3/4" wd x 2 1/2" d; two solder lug term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	1/8/35 RE48A110 REL13A488		16-C-52028-3920				CG	55X198	CG	X-823187 rev 0	TBL TBL-1
-48505-10	CAPACITOR, fixed: NT-48505 w/15 mf p/m 10%.	1/8/35 RE48A110 REL13A488		16-C-52043-3910				CG	55X198	CRV	W-300289-104	TBL-1 (2)
-48506	CAPACITOR, fixed: paper dielectric; 2 mfd minus 10 plus 25%; 300 vdcw; HS metal case; case 2 15/16" lg x 2 1/4" wd x 3 1/2" h; oil impr and filled; two screw-type term 9/16" h on top of case 1 1/4" c to c; no int gnd connections; two mtg bkt on both sides at bottom of case ea w/ two 0.199" diam mtg holes on 1 3/4" x 1 3/4" mtg/c.	1/8/35 RE48A172 REL13A488		16-C-49234-9035				CRV	GL-54-A1	CRV	M-68534-2 rev 1 M-421212-1 rev 1	TBL TBL-1
-48506-10	CAPACITOR, fixed: NT-48506 w/2 mf p/m 10%.	1/8/35 RE48A172 REL13A488		16-C-49192-9164	N16-C-11469-30			CRV	GL-54-A1			TBL (2) TBL-1 (2)
-48507	CAPACITOR, fixed: paper dielectric; 500,000 mmf plus 10 minus 3%; 800 vdcw; HS metal case; 2 15/16" lg x 1 3/16" wd x 3 1/2" h; oil impr and filled; two screw-type term 9/16" h on top of case 1 1/4" c to c; no int gnd connections; two mtg bkt on both sides at bottom of case ea w/ two 0.199" diam mtg holes on 1 3/4" x 1 3/4" mtg/c.	1/8/35 RE48A172 REL13A488		16-C-47278-7369				CRV	GL-58-A1			TBL TBL-1
-48507-10	CAPACITOR, fixed: NT-48507 w/500,000 mmf p/m 10%.	1/8/35 RE48A172 REL13A488		16-C-47299-7369								TBL(2) TBL-1(2)
-48507-15	CAPACITOR, fixed: NT-48507 w/200,000 mmf p/m 15%.	1/8/35 RE48A172 REL13A488		16-C-47312-1326				CRV	GL-58-A1	CRV CRV	M-68534-4 M-421212-2 sub 1	

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-164

RESTRICTED

RESTRICTED

SHEET 48 - 165

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48508	CAPACITOR, fixed: 1/8/35 paper dielectric; 100,000 mmf plus 10 minus 3%; 600 vdcw; HS metal case; case 1 5/16" lg x 3/4" wd x 1" h; mineral oil filled and impr; two rivet lug term on top 5/8" c to c; no int gnd connections; mtg strap across back w/ two 0.154" diam holes on 1 27/32" mtg/c.	RE48A161 RE13A488										TBL TBL-1
-48508-15	CAPACITOR, fixed: 1/8/35 NT-48508 w/100,000 mmf p/m 15%.	RE48A161 RE13A488		16-C-45794-6186						CRV	M-68536-1rev0	TBL TBL-1
-48509	CAPACITOR, fixed: 1/8/35 paper dielectric; 250,000 mmf plus 10 minus 3%; 800 vdcw; HS metal can; case 1 5/16" lg x 3/4" wd x 1 7/8" h; mineral oil impr end filled; two rivet lug term on top; no int gnd connections; mtg strap across back w/ two 0.154" diam holes on 1 27/32" mtg/c.	RE48A161 RE13A488										TBL TBL-1
-48509-10	CAPACITOR, fixed: 1/8/35 NT-48509 w/250,000 mmf p/m 10%.	RE48A161 RE13A488		16-C-46349-5516						CRV	M-68535-501	TBL(2) TBL-1
-48509-15	CAPACITOR, fixed: 1/8/35 NT-48509 w/ 250,000 mmf p/m 15%.	RE48A161 RE13A488		16-C-46366-2098			3DA250-56			CRV	M-68535-1 sub 4	
-48510	CAPACITOR, fixed: 1/9/35 CANCELLED 1,500 mmf; 3,000 vdcw, 5.5 amp at 3,000 kc, 3.5 amp at 1,000 kc, 2 amp at 300 kc, 1 amp at 100 kc.	RE48A131 16C40						CD	PL-671-6	CRV	UC-3061K-2	TBL TBL-1
-48511	CAPACITOR, fixed: 1/9/35 mica; 1,200 mmf; 5,000 vdcw max, 7.5 amp at 3,000 kc, 5 amp at 1,000 kc, 3.25 amp at 300 kc, 1.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48511-A10	CAPACITOR, fixed: 1/9/35 NT-48511 w/1,200 mmf p/m 10%; temp coef 1tr A.	RE48A131 16C40		16-C-31277-1998	N16-C-10171-4			CD	PL-630-6			TBL TBL-1 Cont

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-165

RESTRICTED

RESTRICTED

SHEET 48 - 166

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48511-B2	CAPACITOR, fixed: 1/9/35 NT-48511 w/1,200 mmf p/m 2%; temp coef ltr B. NOTE: TBL-1; TBL; TBL-4 (3); TBL-8 (3); TBL-9 (3).	RE48A131 16040		16-C-31266-8043	N16-C-10171-1			CRV CRV	UC-3147K-2 UC-3313	CRV CRM CRV	K-860215-27rev6 744-80 DL-500575-502	JK-3 QC-7 QCG SEE NOTE:
-48511-C5	CAPACITOR, fixed: 1/9/35 NT-48511 w/1,200 mmf p/m 5%; temp coef ltr C.	RE48A131 16040		16-C-31271-9528	N16-C-10171-3			CD CAN	PL-630-61S	CG	P-7761566-24 rev13	TAQ-5(2) TAQ-6(2) TAQ-10(2)
-48512	CAPACITOR, fixed: 1/9/35 mica; 30,000 mmf; 1,500 vdcv max, 14 amp at 3,000 kc, 20 amp at 1,000 kc, 15 amp at 300 kc, 7 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16040										
-48512-A5	CAPACITOR, fixed: 1/9/35 NT-48512 w/30,000 mmf p/m 5%; temp coef ltr A.	RE48A131 16040		16-C-34726-4109	N16-C-10576-95			CRV	UC-3185K-2	CRV	K-860215-22rev6	TBL TBL-1
-48512-B5	CAPACITOR, fixed: 1/9/35 NT-48512 w/ 30,000 mmf p/m 5%; temp coef ltr B.	RE48A131 16040		16-C-34726-4114				CRV	UC-3185	CRV	DL-500577-502	TBL (2) TBL-1 (2)
-48513	CAPACITOR, fixed: 1/9/35 mica; 1,200 mmf; 5,000 vdcv, 15 amp at 3,000 kc, 10 amp at 1,000 kc, 5 amp at 300 kc, 2 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side grd to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	RE48A108 1 C4										
-48513-B5	CAPACITOR, fixed: 1/9/35 NT-48513 w/1,200 mmf p/m 5%; temp coef ltr B.	RE48A108 16040		16-C-31271-9596				CRV	UC-3186K	CRV	DL-500598-502	TBL(2) TBL-1(2)
-48514	CAPACITOR, fixed: 1/9/35 CANCELLED: 350 mmf; 5,000v, 8 amp at 3,000 kc, 5 amp at 1,000 kc, 2 amp at 300 kc, 0.8 amp at 100 kc.	RE48A131 16040						CRV	UC-2418K			TBL TBL-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-166

RESTRICTED

RESTRICTED

SHEET 48 - 167

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48515	CAPACITOR, fixed: mica; 150 mmf; 5,000 vdcw max, 3 amp at 3,000 kc, 1.5 amp at 1,000 kc, 0.5 amp at 300 kc, 0.15 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg x 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	1/9/35 RE48A131 16C40										
-48515-A2	CAPACITOR, fixed: NT-48515 w/150 mmf p/m 2%; temp coef ltr A.	1/9/35 RE48A131 16C40		16-C-28971-9238	N16-C-9958	R16-C-9959-20		CRV CDL CD CAW	UC-3121 15508-174 39568	CAY CAY	T-7609856-62 T-7606591-44	TBL TBL-1 TCE-1(2) TCE-2(2)
-48515-A10	CAPACITOR, fixed: NT-48515 w/ 150 mmf p/m 10%; temp coef ltr A.	1/9/35 RE48A131 16C40		16-C-28982-3198		R16-C-9959		CRV	UC-3121			
-48515-B2	CAPACITOR, FIXED: Navy Type 48515 w/150 mmf p/m 2%; temp coef letter B.	2/18/48 RE48A131 RE48A131D		16-C-28971-9246				CD CAW	395-68 15508-174	CAY	T7606591-F44	TCE-1
-48515-B5	CAPACITOR, fixed: NT-48515 w/150 mmf p/m 2%; temp coef ltr B.	1/9/35 RE48A131 16C40		16-C-28977-1723				CRV CD	UC-3121 395-618	CG	F-7762757-5	TBC-5(2)
-48516	CAPACITOR, fixed: mica; 3 mmf; 400 vdcw; case 1 1/4" lg x 1/2" wd x 5/16" thk; metal case; two wire leads.	1/10/35 RE48A240 16C40										
-48516-B10	CAPACITOR, fixed: NT-48516 w/ 3 mmf p/m 10%; temp coef ltr B.	1/10/35 RE48 240 16C40		16-C-24601-4300				CRV	H	CRV	M-68581-1rev4	RAB-2A RAB-3(2) RAB-4(2)
-48517	CAPACITOR, fixed: mica dielectric; 1550 mmf; 11,500 vdcw, 1.6 amp at 15 kc, 3.5 amp at 34 kc; case 7 1/4" diam x 11" h; steel case, oil-filled; mtg fl on bottom of case with two 7/16" holes spaced 180 deg on 8 1/2" mtg/c, mtg fl on top of case w/ two 7/16" holes spaced 180 deg apart and 90 deg from holes on bottom, 8 1/2" c to c; air discharge gap for surge protection.	1/12/35 RE48 266 16C40		16-C-31575-1380				CD	PL-669-150	CD	4618-X	TBJ
-48518	CAPACITOR, fixed: mica dielectric; 27,500 mmf plus 10 minus 3%; 9500 vdcw, 25 amp at 15 kc, 55 amp at 34 kc; case 17 1/2" diam x 20" h; steel case, oil-filled; four mtg ears spaced 90 deg on bottom of case ea w/ one 9/16" diam hole on 12 3/4" x 12 3/4" mtg/c; spark gap protection from surge.	1/12/35 RE48A265 16C40		16-C-34690-3534				CD	PL-667-77	CD	4617	TBJ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-167

RESTRICTED

RESTRICTED

SHEET 48 - 168

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	COR. TRAFIC	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48519	CAPACITOR, fixed: mica dielectric; replacement stack for NT-48518 Capacitor in ES container.	1/12/35 RE48A265 16040						CD	PL674-78			TBJ
-48520	CAPACITOR, fixed: paper dielectric; 60,000 mmf plus 10 minus 3%; 440 vdcw; ES metal can; 1 27/32" lg x 21/32" h x 2 1/8" wd; oil impr and filled; two solder lug term 3/8" h, on end of case 3/4" c to c; no int and connections; three 3/8" wd mtg ft w/ 5/32" diam hole one at top on ctr line and two on bottom 1 13/32" c to c and and 2 1/2" from top hole.	1/14/35 RE48A145 RE13A488		16-C-44614-8550				CAY	CC127	CAY	7808878 iss 0	TEM TBN
-48521	CAPACITOR, fixed: mica; 5,000 mmf; 5,000 vdcw, 10 amp at 3,000 kc, 11 amp at 1,000 kc, 3 amp at 300 kc, 1.5 amp at 100 kc; case 3 1/8" lg x 1 1/4" wd x 2 1/4" h; molded low loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ 3/16" diam mtg holes 2 5/8" c to c.	1/14/35 RE48A131 16040										
-48521-A10	CAPACITOR, fixed: NT-48521 w/5,000 mmf p/m 10%; temp coef ltr A.	1/14/35 RE48A131 16040		16-C-32701-4648				CAW	1550	CDE	2375-2	TEM TBN TB-2(8)
-48521-B5	CAPACITOR, fixed: NT-48521 w/5,000 mmf p/m 5%; temp coef ltr B. NOTE: NM-11; NM-12; NM-15; NMA; NMB-2; QCC; QCD; QCU; QCV-3; QCJ-4; QCI-5; QCJ-6; QCJ-9; QCK; QCL-2; QCL-3; QCL-4; QCL-5; QCL-8; QCM-2; QCM-3; QCM-4; QCN-1 thru QCN-4; QCO; QCO-1; QCO-2; QCO; QCO-1; QCR; QCR-1; QCS; QCS-1; QCT; QCT-1; TAJ-6; TAJ-7; TAJ-9 thru TAJ-11; TAJ-13 thru TAJ-19; TBU; TBU-1; TBU-2; TBU-3; WAB; WCA; WCA-1; WDA; WDA-1.	1/14/35 RE48A131 16040		16-C-32696-4123	N16-C-10420			CD	PL-173A-6	CBM CAY CG CG CG CG	744-62 T-7609144-60 ML-7350609-C7 P-7762166-4 7350661-C108 T-7607321-60	JK-2 JE-5 MN-13 MN-13a NM-9 NM-9a SEE NOTE
-48521-B10	CAPACITOR, fixed: NT-48521 w/5,000 mmf p/m 10%; temp coef ltr B.	1/14/35 RE48A131 16040		16-C-32701-4650				CAW	1550L	CDE	S-2378-1	TR(6)
-48521-C5	CAPACIT , fixed: NT-48521 w/5,000 mmf p/m 5%; temp coef ltr C.	1/14/5 RE48A131 16040		16-C-32696-4128				CD	PL-173A-6LS	CG	P-7761566-23 rev13	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-168

RESTRICTED

RESTRICTED

SHEET 48 - 169

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48522	CAPACITOR, fixed: mica; 10,000 mmf; 5,000 vdcw max, 13.0 amp at 3,000 kc, 14.0 amp at 1,000 kc, 7.0 amp at 300 kc, 3.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	1/14/35 RE48A131 16C40										
-48522-B5	CAPACITOR, fixed: NT-48522 w/10,000 mmf p/m 5%; temp coef ltr B. NOTE: TBU-2(3); TBU-3 (3); TDE; TDE-1; TDE-2; TDE-3.	1/14/35 RE48A131 16C40		16-8-33619-6123	N16-C-10524	R16-C-10526		CD CAW	PL-404A-6	CAY CAY	T-7609144-61 T-7607321-61 7608226-20	TBU-4(3) TBU(3) TBU-1(3) SEE NOTE:
-48522-B10	CAPACITOR, fixed: NT-48522 w/10,000 mmf p/m 10%; temp coef ltr B.	1/14/35 RE48A131 16C40		16-C-33624-6603	N16-C-10524-1			CD	PL-404A-6L			
-48522-C5	CAPACITOR, fixed: NT-48522 w/10,000 mmf p/m 5%; temp coef ltr C.	1/14/35 RE48A131 16C40		16-C-33619-6128				CD CD	PL-404A-6LS PL-883-6LST	CG	P-7761566-22 rev13	TAQ-5 (4) TAQ-6 (4) TAQ-1 (3)
-48523	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 1,500 vdcw; ES metal can; case 3" lg x 1" wd x 4 5/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl 1" wd on side of case, w/0.190" diam mtg hole 3 1/2" c to c.	1/14/35 RE48A146 RE13A488		16-C-49181-7943				CAY	FL	CAY	M-7405797-1 sub 0	TMN TMN
-48524	CAPACITOR, fixed: paper dielectric; 5 mf plus 10 minus 3%; 1000 vdcw; ES metal can; case 3" lg x 1 1/4" wd x 4 5/8" h; oil impr and filled; two pillars ins screw type term 1 1/8" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case ea w/0.190" diam mtg hole 3 1/2" c to c.	1/14/35 RE48A146 RE13A488		16-C-50319-9752				CAY	FL	CAY	M-7405797-2sub 0	TMN TMN

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-169

RESTRICTED

RESTRICTED

SHEET 48 - 170

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48525	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 1000 vdcw; BS metal can; case 3" lg x 1" wd x 3 1/8" h; oil impr and filled; two pillar ins screw type term 1 1/8" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/ 0.190" diam mtg hole 3 1/2" c to c.	1/14/35 RE48A146 RE13A488		16-C-49179-9752				CAY	FL	CAY	M-7405797-4 sub0	TBM TBN
-48525-10	CAPACITOR, fixed: NT-48525 w/2 mf p/m 10%.	1/14/35 RE48A146 RE13A488		16-C-49200-9752	N16-C-11490-12							
-48526	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 3,000 vdcw; BS metal can; case 4 7/16" lg x 1 9/16" wd x 5 1/8" h; oil impr and filled; two pillar ins screw type term 1 1/2" h, located on top 2 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea with 0.190" diam mtg hole 4 15/16" c to c.	1/14/35 RE48A146 RE13A488		16-C-49184-6505	N16-C-11496			CAY	FL	CAY	M-7405797-5 sub0	TBM TBN
-48526-10	CAPACITOR, fixed: NT-48526 w/2 mf p/m 10%. NOTE: TBM-6(2); TBM-7(2); TBM-8(2); TBM-10(2); TBM-13(2).	1/14/35 RE48A146 RE13A488		16-C-49208-6505	N16-C-11496			CAY CAY	SO.38Y979 FL	CAY CAY	T-7606286-8 T-7606286-11	TBM-12(2) TBM-5(2) SEE NOTE
-48527	CAPACITOR, fixed: paper dielectric; 200,000 mmf plus 10 minus 3%; 3,000 vdcw; BS metal can; case 3 1/8" h x 3" wd x 1 1/4" thk; oil impr and filled; two stud and nut term 1 1/2" h on por pillars 1 1/4" c to c on top; no int gnd connections; two mtg ft on bottom w/two 0.19" diam holes 3 1/2" c to c along ctr line.	1/14/35 RE48A146 RE13A488		16-P-46144-5654				CAY	FL	CAY	M-7405797-6 sub0	TBM TBN
-48527-10	CAPACITOR, fixed: NT-48527 w/200,000 mmf p/m 10%.	1/14/35 RE48A146 RE13A488		16-C-46165-5654	N16-C-11340-28			CAY	S#1247096	CAY	7610037-13	TBL-10(2) TBL-11
-48528	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 3,000 vdcw; BS metal can; case 7" h x 6" wd x 1 3/4" thk; oil impr and filled; two stud and nut term 1 1/2" h on por pillars 3 1/4" c to c on top; no int gnd connections; two mtg ft on bottom w/two 0.19" diam holes 6 1/2" c to c along ctr line.	1/14/35 RE48A146 RE13A488		16-C-49944-7044				CAY	FL	CAY	M-7405797-7 sub0	TBM TBN

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-170

RESTRICTED

RESTRICTED

SHEET 48 - 171

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A B O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48529	CAPACITOR, fixed: paper dielectric; 8 mf plus 10 minus 3%; 1500 vdcw; BS metal can; case 4 7/16" lg x 2 3/4" wd x 5 1/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 2 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea v/two 7/32" diam mtr holes 1 3/4" apart, 4 15/16" c to c; for replacement only.	1/14/35 RE48A159 RE13A488		16-C-51461-9875				CAY	FL	CAY	E-7405798-3 sub0	TBM TBN
-48529-10	CAPACITOR, fixed: NT-48529 w/8 mf p/m 10%; for replacement only.	1/14/35 RE48A159 RE13A488		16-C-51482-9875				CAY CAY	FL 6#1247098	CAY	T-7609266-10	TAB-6 TAB-7 TBU-4
-48530	CAPACITOR, fixed: paper dielectric; 18 mf plus 10 minus 3%; 330 vacw; BS metal can; case 4 5/8" h x 3 3/4" wd x 3 3/16" d c/a; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	1/24/35 RE48A110 RE13A488		16-C-52181-2810				CG	55X199	CG	R-5173708 dated 1/9/35	TAW-1
-48531	CAPACITOR, fixed: mica; 3,000 mmf; 3,000 vdcw, 8 amp at 3,000 kc, 5.5 amp at 1,000 kc, 3.5 amp at 300 kc, 2.0 amp at 100 kc; case 2 3/8" lg x 7/8" wd x 1 11/16" h; sheet metal case; two screw term 15/16" lg incl ins on ea end; two mtg ft ea w/ 0.173" diam hole, mtg holes 1 1/4" c to c.	2/1/35 RE48A123 16C40										
-48531-B5	CAPACITOR, fixed: NT-48531 w/3,000 mmf p/m 5%; temp coef ltr B.	2/7/35 RE48A123 16C40		16-C-32194-5917				CRV	UC-2226			
-48532	CAPACITOR, fixed: mica; 3,500 mmf; 4,000 vdcw, 14 amp at 3,000 kc, 10 amp at 1,000 kc, 7 amp at 300 kc, 3 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; pillar term shielded on top 2" h ctr, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	3/1/35 RE48A108 16C40										
-48532-B5	CAPACITOR, fixed: NT-48532 w/3,500 mmf p/m 5%; temp coef ltr B.	3/1/35 RE48A108 16C40		16-C-32326-9050				CRV	UC-2317S			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-171

RESTRICTED

RESTRICTED

SHEET 48 - 172

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG DR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFOR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48533	CAPACITOR, fixed: air; 85.6 mmf; enclosed in aluminum case 3 1/2" lg x 2 1/2" wd x 1 5/8" h o/a; two stud term extending from top plate spacer, one on ea end; mtd in case, six mtg holes in base 0.228" diam on 9 3/4" x 22 1/8" mtg/c; ten aluminum plates; mycalex ins; used in conjunction w/type RW 47091 indicator unit to form duplex coupling unit.	3/7/35 RA48F218		16-C-15152-9181				RW				XZ-1
-48534	CAPACITOR, fixed: mica; 150 mmf; 20000 vdw, 10 amp at 6000 kc; case 5" diam x 4" h; ceramic case; one fl elliptical end term ea end two 3/8" diam holes in ea term 5 3/4" c to c.	3/15/35 BE48A116 16C40										
-48534-B5	CAPACITOR, fixed: NT-48534 w/150 mmf p/m 5%; temp coef ltr B.	3/15/35 BE48A116 16C40		16-C-28978-5359	N16-C-9962			CD CAW CSL	PL-316-51	CAY CAY CAY	T-7606117-486 7607280-68 7607093-68 T-7609847-95	TBM TBM TBK-9 TBK-11 SEE NOTE
-48535	CAPACITOR, fixed: mica; 150 mmf; 5,000 vdw, 7.5 amp at 4,500 kc, 6 amp at 3,000 kc, 2 amp at 1,000 kc; case 2 1/2" h x 2 13/16" diam; low-loss ceramic case; one elliptical cast aluminum end-cap term 3 13/16" lg at ea end w/ two 17/64" diam holes 3 1/4" c to c in ea end.	3/15/35 BE48A132 16C40										
-48535-B5	CAPACITOR, fixed: NT-48535 w/150 mmf p/m 5%; temp coef ltr B.	3/15/35 BE48A132 16C40		16-C-28977-1843	N16-C-9959			CD CAW CSL	PL-661-59	CAY CAY CAY CAY CAY	T-7609024-68 T-7606024-9 7609024-68 7607280-67 T-7607093-67 T-7609847-22	TBM TBM TBK-5 TBK-6 TBK-7 TBK-9 SEE NOTE
-48536	CAPACITOR, electrolytic: CANCELLED: same as NT-48340.	3/15/35						CD	PL-5113-E	CD	K-7808901	TBM TBM

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-172

RESTRICTED

RESTRICTED

SHEET 48 - 173

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48537	CAPACITOR, fixed: 3/19/35 paper dielectric; two sect; 500,000 mmf/500,000 mmf plus 10 minus 3%; 300/300 vdcw; HS metal can; case 1 7/8" h x 1 5/16" wd x 11/16" thk; oil impr and filled; two ine stud and nut term 5/8" c to c on top; one side of each sect is common and int grd to can; two integral mtg ft on bottom w/two 0.154" diam holes 1 11/16" c to c along ctr line.	RE48A147 RE13A488		16-C-53569-1716								NM-3 QC-3
-48537-15	CAPACITOR, fixed: 3/19/35 NT-48537 w/500,000 mmf/500,000 mmf p/m 15%.	RE48A147 RE13A488		16-C-53675-7103						CRV	K-73755-1 sub 0	
-48538	CAPACITOR, fixed: 3/19/35 paper dielectric; two sect; 500,000/5000 mmf p/m 15%/p/m 10%; 250/1650 vdcw; HS metal can; 1 5/16" lg x 1 11/16" wd x 1 7/8" h o/a; oil impr and filled; two screw type term 3/16" h located on top 5/8" c to c; both sect int grd; two mtg fl on bottom of case, ea w/ 0.154" diam mtg hole centered 1 11/16" c to c; for replacement use only.	RE48A147 RE13A488		16-C-52783-2850						CRV CRV	M-685520-1 M-80311-2 sub 1	
-48539	CAPACITOR, fixed: 3/19/35 paper dielectric; 100,000 mmf plus 10 minus 3%; 500 vdcw; HS metal can; case 1 7/8" lg x 5/8" diam; mineral oil impr and filled; one axial wire lead; neg term grd int; mtg strap w/one 0.154" diam hole 9/16" x 3/8" from ctr of capacitor.	RE48A162 RE13A488										NM-3 QC-3
-48539-20	CAPACITOR, fixed: 3/19/35 NT-48539 w/100,000 mmf p/m 20%.	RE48A162 RE13A488		16-C-45806-9771						CRV CRV	M-407154-3 K-77015-1 sub 3	NM-3 (12) QC-3 (13)
-48540	CAPACITOR, fixed: 3/19/35 paper dielectric; three sect; 3 mf plus 10 minus 3% ea sect; 400 vdcw ea sect; HS metal can; case 4 19/32" lg x 2 11/32" wd x 5 5/16" h; oil impr and filled; four screw-type term 3/8" h on bottom of case, spaced 1/2" c to c; no int grd connections; two mtg fl on both sides ea w/two 0.213" diam holes 1 1/4" x 5 3/32" c to c.			16-C-54729-7434	N16-C-11535		3083.10	CRV	ER-50-A-1	CRV	M-407204-1	NM-3 QC-3 RAK RAK-1
-48540-1	CAPACITOR, fixed: 3/19/35 NT-48540 w/3 mf p/m 10% ea sect. NOTE: RAK-4; RAL thru RAL-4.			16-C-54730-4685	N16-C-11536			CRV	72014-501	CRV	P-72014-501 rev2	RAK-2 RAK-3 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-173

RESTRICTED

RESTRICTED

SHEET 48 - 174

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48540-A	CAPACITOR, fixed: 12/22/36 paper dielectric; three sect; 3 mf plus 10 minus 3% ea sect; 400 vdcw ea sect; HS metal can: h 19/32" lg x 2 11/32" wd x 5 5/16" h; oil impr and filled; four screw type term 3/8" h on bottom of case, spaced 1/2" c to c; no int gnd connections; two mtg fl on both sides ea w/two 0.213" diam holes 1 1/4" x 5 3/32" c to c.	RE48A171		16-C-54729-7434	N16-C-11536							
-48540-A10	CAPACITOR, fixed: 12/22/36 NT-48540-A w/3 mf p/m 10% ea sect. NOTE: RAK-8; RAL-7; RAL-8.	RE48A171		16-C-54730-4685	N16-C-11536			CRV CBV	72014-507	CRV CMX	P-72014-507 B-250100	RAK-6 RAK-7 SEE NOTE
-48541	CAPACITOR, variable: 3/19/35 air dielectric; plate meshing type single sect; 10 to 90 mmf; SLC; 1 13/32" lg x 15/16" wd x 1 1/4" h shaft completely encl in brg 1/4" diam x 5/16" lg o/a; acdr adj; twenty-seven white nickel pl brass plates; 360 deg rotation; isolantite ins; post term for stator, lug term for rotor on top; two mtg studs w/#4-36 tap on 21/32" mtg/c.			16-C-60502-5139				CEC	APC-100	CRV	K-815703-1rev0	NM-3 (8) QC-3 (9)
-48542	CAPACITOR, variable: 3/19/35 air dielectric; plate meshing type, single sect; 3 to 10 mmf; SLC; 0.0245" air gap; 1 23/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 1 1/2" lg bushing 1/2" lg x 3/8"-32 thd; round shaft adj; nickel pl brass plates; 360 deg rotation; isolantite ins; solder lug term; two mtg ft ea w/one #6-32 tapped holes 1 7/32" c to c.			16-C-58287-2801				CEC CMC	ATT-3-10 MC-10	CRV	K-815702-1rev0	NM-3 QC-3
-48543	CAPACITOR, fixed: 3/19/35 mica; 2,000 mmf; 600 vdcw; case 1 1/4" lg x 1 1/4" wd x 3/8" h; molded bakelite case; two lug term ea w/one 3/16" diam hole 1 3/4" c to c; two mtg holes in back of case 5/32" diam on 1 1/2" mtg/c.	RE48A215 16C40										
-48543-A10	CAPACITOR, fixed: 3/19/35 NT-48543 w/2,000 mmf p/m 10%; temp coef ltr A. NOTE: RAK; RAK-1; RAK-6; RAK-7.	RE48A215 16C40		16-C-31802-7381				CAW	1455	CRV	K-30090-5	NM-3 QC-3 SEE NOTE
-48543-B10	CAPACITOR, fixed: 3/19/35 NT-48543 w/2,000 mmf p/m 10%; temp coef ltr B.	RE48A215 16C40		16-C-31802-7556	N16-C-10241			CAW	1455-L			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-174

RESTRICTED

RESTRICTED

SHEET 48 - 175

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48544	CAPACITOR, fixed: 3/19/35 mica; 100 mmf; 500 vdcw, 1000v DC test; case 1 1/4" lg x 5/8" wd x 1/4" thk; molded low-loss bakelite case; two term; two 9/64" diam holes in case 1 1/4" mtg/c.	RE48A217 16C40										
-48544-B10	CAPACITOR, fixed: 3/19/35 NT-48544 w/100 mmf p/m 10%; temp coef ltr B.	RE48A217 16C40		16-0-28558-2160				CAW	1461	CRV	K-30088-2rev2	NM-3 (2) QC-3 (2)
-48544-B20	CAPACITOR, FIXED: 6/28/48 Navy Type 48544 w/100 mmf p/m 20%; temp coef ltr B.	RE48A217 16C40		16-0-28563-4640				CAW	1461 LS			
-48545	CAPACITOR, fixed: 3/19/35 mica; 40 mmf; 500 vdcw, 1000v DC test; case 1 1/4" lg x 5/8" wd x 1/4" thk; molded low-loss bakelite case; two solder lug term; two 9/64" diam holes in case 1 1/4" mtg/c.	RE48A217 16C40										
-48545-A10	CAPACITOR, fixed: 3/19/35 NT-48545 w/40 mmf p/m 10%; temp coef ltr A.	RE48A217 16 40		16-0-27397-5555				CAW	1461	CRV	K-30088-3rev2	NM-3 (2) QC-3 (2)
-48546	CAPACITOR, fixed: 3/19/35 mica; 250 mmf; 500 vdcw, 1000v DC test; case 1 1/4" lg x 5/8" wd x 1/4" thk; molded low-loss bakelite case; two solder lug term; two 9/64" diam holes in case 1 1/4" mtg/c.	RE48A217 16 40										
-48546-A10	CAPACITOR, fixed: 3/19/35 NT-48546 w/250 mmf p/m 10%; temp coef ltr A.	RE48A217 16C40		16-0-29481-4155			3D9250-4	CAW	1461	CRV	K-30088-4rev2	NM-3 (2) QC-3 (2)
-48547	CAPACITOR, fixed: 3/19/35 paper dielectric; 500,000 mmf plus 10 minus 3%; 400 vdcw; molded phenolic case; case 1 3/4" h x 1 3/4" wd x 15/16" thk; wax impr and filled, sealed w/pitch; two stud and nut term 1 1/16" c to c on top; no int gnd connections; two integral mtg ft on bottom ends w/two 0.173" diam holes 2 1/8" c to c.	RE48A181		16-0-47272-9198				CAW	450			
-48547-10	CAPACITOR, fixed: 3/19/35 NT-48547 w/500,000 mf p/m 10%.	RE48A181		16-0-47293-9183	N16-C-11346			CAW	450	CRV	K-815704-30	NM-3 QC-3
-48548	CAPACITOR, fixed: 3/22/35 paper dielectric; 2 mf plus 10 minus 3%; 300 vdcw; BS metal can; case 2 7/8" h x 1 3/4" wd x 1" d o/s; two stud term 1/2" h located on top, spaced 1" c to c; no int gnd connections.	RE48A110 REL3A488		16-0-49171-7738				CD	VC-338	CAY	K-7808928 sub 0	TBK
-48548-10	CAPACITOR, fixed: 3/22/35 NT-48548 w/2 mf p/m 10%.	RE48A110 REL3A488		16-0-49192-7738	N16-C-11469			CD	VC-338			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-175

RESTRICTED

RESTRICTED

SHEET 48 - 176

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48549	CAPACITOR, FIXED: mica dielectric; 100 mmf; 500 vdcw; 7/8" lg x 7/8" wd x 1/4" thk case; metal case; 1 solder lug term 1 end, other end, 1 lug term bent back over top of case secured w/eyelet 9/64" diam.	4/10/35 RE48A228										
-48549-5	CAPACITOR, FIXED: Navy Type 48549 w/100 mmf p/m 5%.	4/13/48 RE13A389M RE48A228A		16-C-28553-1402				CRV	T	CRV	P-713881-512 rev 8 P-713881-516 rev 8	BBP
-48549-10	CAPACITOR, fixed: NT-48549 w/100 mmf p/m 10%.	4/10/35 RE48A228 16C40		16-C-28558-1877	N16-C-9923-23			CRV	T	CRV	P-713881-518 P-713881-522 P-32170-518	RAK thru RAK-6 RAL SEE NOTE
-48549-20	CAPACITOR, FIXED: Navy Type 48549 w/100 mmf, p/m 20%.	6/28/48 RE48A228 16C40		16-C-28563-4362				CRV	T			
-48550	CAPACITOR, fixed: mica; 50 mmf; 500 vdcw; case 7/8" lg x 7/8" wd x 1/4" thk; metal clad; one lug term at one end w/one 3/32" diam hole, and one term over top fastened w/eyelet 0.14" diam.	4/10/35 RE48A228 16C40										
-48550-5	CAPACITOR, FIXED: Navy Type 48550 w/50 mmf p/m 5%.	12/26/47 RE48A228 16C40		16-C-27629-8407				CRV	T	CRV	P-32170-519	RAL-4
-48550-10	CAPACITOR, fixed: NT-48550 w/50 mmf p/m 10%.	4/10/35 RE48A228 16C40		16-C-27634-8758	N16-C-9843-103			CRV	T	CRV	P-32170-519	RAL (2) RAL-1 (2) SEE NOTE
-48551	CAPACITOR, fixed: CANCELLED same as NT-48540, for replacement use NT-48540-A.	4/10/35 RE48A171						CRV	ER50-A-1	CRV	P-72014-1	RAK-1 RAL-1
-48552	CAPACITOR, fixed: CANCELLED superseded by NT-48552-A.	4/10/35						CRV	72039-507	CRV	P-721074-1 sub3	RAL RAK
-48552-A	CAPACITOR, fixed: paper dielectric; 100,000 mmf plus 10 minus 3%; 500 vdcw; HS metal can; case 1 5/16" lg x 1 1/16" wd x 1 5/16" h o/a; oil impr and filled; two solder post term 13/32" h located on top 5/8" c to c; no int gnd connections; two mtg fl on bottom of case w/ 5/32" wd mtg slot 1 15/16" c to c.	12/29/39 RE48A160 RE13A488		16-C-45754-9670	N16-C-11304			CG	9CB6A2	CG	K-7875547-2rev1	SC-2 (2) SC-4 (2) SK-2 (2) SK-3 (2) SM (2) SM-1 (2) TCD
-48552-A2 1/2	CAPACITOR, fixed: NT-48552-A w/100,000 mmf p/m 2 1/2%.	12/29/39 RE48A160 RE13A488		16-C-45726-1215				CG	9CB6A2	CG	P-7763475-7rev10	SC-3 (2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-176

RESTRICTED

RESTRICTED

SHEET 48 - 177

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48552-B	CAPACITOR, fixed: 4/24/44 paper dielectric; 100,000 mmf plus 20 minus 10%; 600 vdcw; HS metal can; case 1 5/16" lg x 11/16" wd x 1 5/16" h; oil impr and filled; two solder lug term on top 5/8" c to c; no int gnd connections; two mtg lkt at bottom on both sides ea w/one 5/32" slot 1 15/16" c to c.	RE48A160 REL3A488		16-C-45801-9410				CSF	P-9722	CRZ	CO-973-C	
-48552-E10	CAPACITOR, fixed: 4/24/44 NT-48552-B w/100,000 mmf p/m 10%. NOTE: BG; BO-1.	RE48A160 REL3A488		16-C-45775-9660				CSF	P-9722			EM thru EM-2 SEE NOTE
-48553	CAPACITOR, fixed: 4/10/35 paper dielectric; 1 mf plus 10 minus 3%; 250 vdcw; HS metal can; case 1 5/16" lg x 11/16" wd x 1 15/16" h o/s; oil impr and filled; two solder post term 13/32" h located on top 5/8" c to c; no int gnd connections; two mtg fl on bottom of case w/a 5/32" wd mtg slot 1 15/16" c to c; for replacement use NT-48829. NOTE: QGB; RAL-6; SG; TBA-6 (2); TBA-10 (2); TBA-11 (2); TBC-5; TBS-1 (2) thru TBS-8 (2); MK-26 Mod 3 (3); MK-26 Mod 4 (3).	RE48A160 REL3A488		16-C-48790-9420	N16-C-11383-1			CRV CG	P-72039-501 90E6A4	CRV CRV CRV CG CRV	P-721074-2alt3 M-420071-6 W-306605-45 P-7763475-5rev10 K-885477-22	DP-4 (7) thru DP-6 (7) DP-8 (7) DP-10 (7) thru DP-19 (7) QCC-2 SEE NOTE
-48553-2 1/2	CAPACITOR, fixed: 4/10/35 NT-48553 w/1 mf p/m 2 1/2%.	RE48A160 REL3A488		16-C-48766-1092				CG	90E6A4	CG	T-8007240-28	SM-1 (2)
-48553-5	CAPACITOR, fixed: 4/10/35 NT-48553 w/1 mf p/m 5%.	RE48A160 REL3A488		16-C-48769-9420				CG	90E6A4	CAY	T-7611797-6	SR (4) SR-5 (4)
-48553-10	CAPACITOR, fixed: 4/10/35 NT-48553 w/1 mf p/m 10%.	RE48A160 REL3A488		16-C-48811-9420	N16-C-11383-1			CG	90E6A4	CMX CRP CAY CAY	B250101-3 35-5056 T-7610944-7 T-7610944-12	RAK-8 (16) RAL-8 (11) SO-3 SR (4) SR-5 (4)
-48553-15	CAPACITOR, fixed: 4/10/35 NT-48553 w/1 mf p/m 15%. NOTE: RAL (11); RAL-1 (11); RAL-5 (11); RA -2 (16) thru RAL-4 (16); RBD (2); TCD; TCX (2); YE -1; YE-2.	RE48A160 REL3A488		16-C-48831-4946	N16-C-11383			CRV	72024-502	CRV CRV CG CG	W-303345-389 P-72024-502 K-7875547-4rev1 P-7763475-5rev10	NMB-1 RAY (16) thru RAK-4 (16) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-177

RESTRICTED

RESTRICTED

SHEET 48 - 178

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48554	CAPACITOR, fixed: 4/10/35 paper dielectric; two sect; 500,000 mmf ea sect plus 10 minus 3%; 250 vdcv ea sect; superseded by NT-48554-A. NOTE: DP-8 (4) thru DP-18 (4); RAK-1 thru RAK-4; RAL-2 thru RAL-4.							C V CRV	72039-503 72024-505	CRV CRV	P-721074-3alt3 M-420071-7rev8	RAK RAL DP-4 thru DP-6 SEE NOTE
-48554-15	CAPACITOR, fixed: 4/10/35 N-48554 w/500,000 mmf ea sect p/m 15%; superseded by NT-48554-A.							CRV		CMX	B250101-4	M-3 (5) QC-3 (3)
-48554-A	CAPACITOR, fixed: 12/20/40 paper dielectric; two sect; 500,000 mmf/500,000 mmf plus 10 minus 3%; 400/400 vdcv; HS metal can; case 1 3/8" lg x 3/4" wd x 1 15/16" h; oil impr and filled; two solder post term 13/32" h located on top 5/8" c to c; both sect int gnd; two mtg fl on bottom of case w/a 5/32" wd mtg slot 1 7/8" c to c.	RE48A160 RE13A488		16-C-53570-4310	N16-C-11377-12							
-48555	CAPACITOR, fixed: 4/10/35 paper dielectric; two sect; 125,000/125,000 mmf plus 10 minus 3% ea sect; 500 vdcv ea sect; HS metal can; case 1 5/16" lg x 3/4" wd x 1 7/8" h; mineral oil impr and filled; two forked lug term on end 5/8" c to c, 7/16" h max; both sect int gnd; mtg strap w/two 0.154" diam holes on 1 27/32" mtg/c.	RE48A161 RE13A488		16-C-53227-3360				CRV	72039-513	CRV	P-721074-6 sub3	RAL-6 (4)
-48555-10	CAPACITOR, fixed: 4/10/35 NT-48555 w/125,000/125,000 mmf p/m 10%.	RE48A161 RE13A488		16-C-53227-3560	N16-C-11336-7					CRV		
-48555-15	CAPACITOR, fixed: 4/10/35 NT-48555 w/125,000/125,000 mmf p/m 15%. NOTE: RAL; RAL-1.	RE48A161 RE13A488		16-C-53227-3660	N16-C-11336-10					CMX	B-250102-1	RAL-5 RAL-8 (4) SEE NOTE
-48556	CAPACITOR, fixed: 4/10/35 paper dielectric; two sect; 500,000/500,000 mmf plus 10 minus 3% ea sect; 250 vdcv ea sect; HS metal can; case 1 5/16" lg x 3/4" wd x 1 7/8" h; mineral oil impr and filled; two rivet lug term on end 7/16" h, 5/8" c to c; both sect gnd int; mtg strap w/two 0.154" diam holes on 1 27/32" mtg/c.			16-C-53569-1310						CRV CRV	P-721074-7alt3 P-72025-502	RAK RAL-1
-48556-10	CAPACITOR, fixed: 4/10/35 NT-48556 w/500,000/500,000 mmf p/m 10%.			16-C-53625-2810	N16-C-11375-84							Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-178

RESTRICTED

RESTRICTED

SHEET 48 - 179

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48556-15	CAPACITOR, fixed: NT-48556 w/500,000/500,000 mmf p/m 15%. NOTE: RAK-2 (4) RAK-3 (4); RAK-4 (4); RAK-8 (4); RAL-2 (4) thru RAL-4 (4)	4/10/35		16-C-53675-6515						CMX	B-250102-2	RAK (4) RAK-1 (4) SEE NOTE
-48556-A	CAPACITOR, fixed: paper dielectric; two sect; 500,000/500,000 mmf plus 10 minus 3% ea sect; 400 vdcw ea sect; HS metal can; case 1 5/16" lg x 3/4" wd x 1 7/8" h; mineral oil impr and filled; two rivet lug term on end; both sect int grd; mtg strap w/ two 0.154" diam holes on 1 27/32" mtg/c.	10/12/41 RE48A161 RE13A488		16-C-53570-4370	N16-C-11174-27							
-48557	CAPACITOR, fixed: mica; 1000 mmf; 600 vdcw; case 1 1/4" lg x 1 1/4" wd x 1 1/32" d; molded bakelite case; two lug term ea with one 3/16" diam holes on 1 3/4" c to c; two mtg holes in back of case 5/32" diam on 1 1/2" mtg/c.	4/10/35 RE48A215 16C40										
-48557-A10	CAPACITOR, fixed: NT-48557 w/1000 mmf p/m 10%; temp coef ltr A. NOTE: RAK; RAK-1; RAK-6; RAK-7 (2); RAL (2); RAL-1 (2); RAL-5 (2) thru RAL-7 (2)	4/10/35 RE48A215 16C40		16-C-31090-5553			206901/08	CAW	1455	CRV	K-30090-10	RAL RAL-1 SEE NOTE
-48557-B10	CAPACITOR, fixed: NT-48557 w/1000 mmf p/m 10%; temp coef ltr B.	4/10/35 RE48A215 16C40		16-C-31090-5556	N16-C-10087			CAW	1455LS	CRV	P-720567-11rev35	ARB
-48558	CAPACITOR, fixed: mica; 300 mmf; 500 vdcw, 1000v DC test; case 1 1/4" lg x 5/8" wd x 1 1/4" h; molded bakelite case; two solder lug term; two 9/64" diam holes in case 1 1/4" mtg/c.	4/10/35 RE48A217 16C40										
-48558-A10	CAPACITOR, fixed: NT-48558 w/300 mmf p/m 10%; temp coef ltr A.	4/10/35 RE48A217 16C40		16-C-29665-9955	N16-C-9992-11			CAW	1461	CRV	K-30088-5rev2	RAK RAK-1 RAK-6
-48559	CAPACITOR, fixed: mica; 400 mmf; 500 vdcw; case 1 1/4" lg x 5/8" wd x 7/32" thk; molded bakelite case; two solder lug term; two 9/64" diam holes in case on 1 1/4" mtg/c.	4/10/35 RE48A217 16C40										
-48559-A10	CAPACITOR, fixed: NT-48559 w/400 mmf p/m 10%; temp coef ltr A.	4/10/35 RE48A217 16C40		16-C-29929-7955				CAW	1461	CRV	K-30088-6 rev2	RAL RAL-1 RAL-6
-48559-B20	CAPACITOR, fixed: NT-48559 w/400 mmf p/m 20%; temp coef ltr B.	4/10/35 RE48A217 16C40		16-C-29935-1440	N16-C-10007			CAW	1461L			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-179

RESTRICTED

RESTRICTED

SHEET 48 - 180

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48560	CAPACITOR, fixed: 4/10/35 mica; 500 mmf; 500 vdcw; 2" max lg x 3/4" wd x 3/4" thk; lam phenolic case; two wire leads.	RE48A241 16C40									
-48560-B10	CAPACITOR, fixed: 4/10/35 NT-48560 w/500 mmf p/m 10%; temp coef ltr B. NOTE: RAK-4 (2) thru RAK-6 (2); RAL-1 (2); RAL-2 (2) thru RAL-4 (2)	RE48A241 16C40		16-C-30167-278	N16-C-10016-4			CRV	77055-5	K-77055-5	RAK (2) RAK-1 SEE NOTE
-48561	CAPACITOR, fixed: 4/10/35 mica; 250 mmf; 500 vdcw; case 2" lg max x 3/4" wd x 3/4" thk; lam phenolic case; two wire leads.	RE48A241 16C40									
-48561-B10	CAPACITOR, fixed: 4/10/35 NT-48561 w/250 mmf p/m 10%; temp coef ltr B. NOTE: RAL-5 (2); RAL-6 (2).	RE48A241 16C40		16-C-29481-4380	N16-C-9974-7			CRV	77055-6	K-77055-6	RAL RAL-1 SEE NOTE
-48562	CAPACITOR, fixed: 4/10/35 mica; 900 mmf; 500 vdcw; case 1 1/4" lg x 1/2" wd x 5/16" thk; metal case; two wire leads.	RE48A240 16C40									
-48562-B10	CAPACITOR, fixed: 4/10/35 NT-48562 w/900 mmf p/m 10%; temp coef ltr B. NOTE: RAK-2; RAK-3; RAK-4; RAK-6; RAK-7; RAL-1; RAL-2 thru RAL-4.	RE48A240 16C40		16-C-30905-7746				CRV	H CRV	M-68581-3 M-86016-533	RAK RAK-1 SEE NOTE
-48563	CAPACITOR, variable: 4/15/35 air; plate meshing type single sect; 4.5 to 140 mmf; SLC; 0.020" air gap; 2" lg x 1 7/16" wd x 1 11/32" h shaft 1/4" diam x 5/32" lg bushing 7/32" lg x 3/8"-32 thd locking type; scdr wd w/ #6-32 tap in ctr of shaft; twenty seven aluminum plates; 360 deg rotation; isolantite ins; lug term; single hole mtg by 3/8" diam mtg bushing or panel mtg by two 1/8" diam holes on 1 3/32" mtg/c.			16-C-61025-2001				CBK	RT-140	K-815872rev0 K-815211-108rev7	DP thru DP-3 DQ
-48564	CAPACITOR, fixed: 4/15/35 paper dielectric; 500,000 mmf plus 10 minus 3%; 500 vdcw; HS metal can; case 1 5/16" lg x 3/4" wd x 1 7/8" h; mineral oil impr and filled; two rivet lug term on top; no int gnd connections; mtg strap w/two 0.154" diam holes on 1 27/32" mtg/c.	RE48A161 RE13A488		16-C-47275-1336					CRV CRV CRV CRV	K-823293-2 P-72025-503 P-721074-8alt3 P-72039-515	NM-3 (5) QC-3 (5) TBK-8 thru TBK-10 TBK-12 TBK-14 TBK-17
-48564-15	CAPACITOR, fixed: 4/15/35 NT-48564 w/500,000 mmf p/m 15%.	RE48A161 RE13A488		16-C-47313-9771	N16-C-11350-85						

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-180

RESTRICTED

RESTRICTED

SHEET 48 - 181

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48565	CAPACITOR, fixed: paper dielectric; two sect; 500,000/500,000 mmf plus 10 minus 3%; 2500/2500 vdcw; BS metal can; case 5 3/4" h x 4 11/16" wd x 2 5/16" thk; oil impr and filled; three stud and nut term 1 1/4" h on top pillars each 1" c to c; no int gnd connections; two integral mtg ft on top w/two 0.242" diam holes on 5.093" x 1.25" mtg/c.	4/15/35 RE48A188 RE13A488		16-C-53610-7110				CRV	P-72026	CRV CRV	P-72354-90 KX-281233	NM-3 QC-3
-48566	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 400 vdcw; BS metal can; case 2 3/16" lg x 3/4" wd x 2" h, o/a; oil impr and filled; two screw type term 5/16" h located on top 1 1/2" c to c; no int gnd connections; two mtg fl 7/8" wd on side of case ea w/ 3/16" diam mtg hole, 2 5/8" c to c; superseded by NT-48566-A.	4/19/35 RE13A488		16-C-48793-1927				CD		CHS	RA-154	RAG RAG-1 RAH RAH-1
-48566-A	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 400 vdcw; BS metal can; case 2 3/16" lg x 3/4" wd x 2" h o/a; oil impr and filled; two screw type term 5/16" h located on top 1 1/2" c to c; no int gnd connections; two mtg fl 7/8" wd on side of case, ea w/3/16" diam mtg hole ctr 2 5/8" c to c.	11/23/36 RE48A147 RE13A488		16-C-48793-1927	N16-C-11387			CD				
-48567	CAPACITOR, variable: air; plate, meshing type, single sect; 62 to 88 mmf; SLC; 1 9/32" lg x 1 15/16" diam shaft 3/8" diam x 1/8" lg; round shaft adj; eleven nickel pl plates; 360° rotation; isolantite or por ins; post term for stator, lug term for rotor; two mtg holes w/ #6-32 tap 1 1/2" c to c.	4/20/35		16-C-60496-9238				CHC		CRV	M-401958-54aub7	NM-3 QC-3
-48568	CAPACITOR, fixed: mica; 805 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	4/25/35 RE48A238 16C40										
-48568-B5	CAPACITOR, fixed: NT-48568 w/805 mmf p/m 3%; temp coef 1tr B. NOTE: RAK-1 thru RAK-4; RAK-6; RAK-7; RAL-2 thru RAL-4.	4/25/35 RE48A238 16C40		16-C-30716-1172				CRV	H	CRV CRV	M-86016-503 K-35913-3	RAL RAK SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-181

RESTRICTED

RESTRICTED

SHEET 48 - 182

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48569	CAPACITOR, fixed: mica; 62 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	4/25/35 RE48A238 16C40										
-48569-B2	CAPACITOR, fixed: NT-48569 w/62 mmf p/m 2%; temp coef ltr B. NOTE: RAK-1 thru RAK-4; RAL-2 thru RAL-4.	4/25/35 RE48A238 16C40		16-C-27835-7091	N16-C-9855			CRV	E	CRV	K-35913-4 M-86016-504	RAK RAL SEE NOTE
-48570	CAPACITOR, fixed: mica; 45.4 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	4/25/35 RE48A238 16C40										
-48570-B2	CAPACITOR, fixed: NT-48570 w/45.4 mmf p/m 2%; temp coef ltr B NOTE: RAK-1; RAK-2; RAK-3; RAK-4; RAK-5; RAK-6; RAK-7; RAK-8; RAL-2; RAL-3; RAL-4.	4/25/35 RE48A238 16C40		16-C-27566-7548	N16-C-9843-74			CRV	H	CRV	M-86016-505 K-35913-5	RAK RAL SEE NOTE
-48571	CAPACITOR, fixed: mica; 500 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	4/25/35 RE48A238 16 40										
-48571-B10	CAPACITOR, fixed: NT-48571 w/500 mmf p/m 10%; temp coef ltr B. NOTE: RAL-1; RAL-5 thru RAL-7.	4/25/35 RE48A238 16C40		16-C-30167-2252	N16-C-10017-26			CRV	H	CRV	M-86016-506 K-35913-6	RAK RAL SEE NOTE
-48572	CAPACITOR, fixed: mica; 1190 mmf; 5000 vdcw; case 1 13/32" lg x 1/2" wd x 3/8" thk; thermoplastic case; two axial wire leads. NOTE: RAK-1 thru RAK-4; RAK-6; RAK-7; RAL-2; RAL-3; RAL-5.	4/25/35 RE48A248 16C40										SEE NOTE
-48572-B5	CAPACITOR, fixed: NT-48572 w/1190 mmf p/m 5%; temp coef ltr B.	4/25/35 RE48A248 16C40		16-C-31243-6506				CRV	H	CRV	M-86016-507 K-35913-7	RAK RAL
-48573	CAPACITOR, variable: air; plate meshing type single sect; 2 to 12 mmf; SLC; 0.0245" air gap; 15/16" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 4 11/16" lg bushing 3/8" lg x 3/8"-32 thd; rounded shaft; three dull nickel pl brass plates; clockwise rotation; ceramic ins; post term for stator, rotor grounded; single hole mtg by 3/8" diam mtg bushing or base mtg by mtg foot w/one #6-32 tap hole.	4/29/35		16-C-58374-9049	N16-C-12217-11			CBC	45-11737-1	CRV	K-815737-1 sub12	RAL RAL-1 RAL-5 thru RAL-8

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-182

RESTRICTED

RESTRICTED

SHEET 48 - 183

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48574	CAPACITOR, variable: 4/29/35 air; plate meshing type single sect; 2 to 10 mmf p/m 5%; SLC; 0.266" air gap; 1 21/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 4 11/16" lg bushing 3/8" lg x 3/8"-32 thd; rounded shaft; two dull nickel pl brass plates; clockwise rotation; ceramic ins; lug term; single hole mtg by 3/8" diam mtg bushing or base mtg by two mtg feet ea w/one 6-32 tap hole on 1 7/32" mtg/c.			16-C-58242-2801	N16-C-12217-7			CBC	45-11737-2	CRV	K-815737-2rev12	RAL RAL-1 RAL-6 thru RAL-8
-48575	CAPACITOR, variable: 4/29/35 air; plate meshing type single sect; 5.3 to 27 mmf p/m 5%; SLC; 0.0245" air gap; 1 21/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 4 11/16" lg bushing 3/8" lg x 3/8"-32 thd; rounded shaft; four cad pl brass plates; clockwise rotation; ceramic ins; lug term; single hole mtg by 3/8" diam mtg bushing or base mtg by two mtg feet ea w/one #6-32 tap hole on 1 7/32" mtg/c.			16-C-59255-5385	N16-C-12220-24			CBC	45-11736-2	CRV	K-815736-2 rev10	RAK RAK-1 thru RAK-4 RAK-6 RAK-7 RAL RAL-1 thru RAL-8
-48576	CAPACITOR, variable: 4/29/35 air; plate meshing type single sect; 5.5 to 35 mmf p/m 10%; SLC; 0.0245" air gap; 1 21/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 5/32" lg bushing 3/8" lg x 3/8"-32 thd w/lock nut; scdr adj; five cad pl brass plates; clockwise rotation, 180 deg; ceramic ins; lug term; base mtg by two mtg feet ea w/one #6-32 tap hole on 1 7/32" mtg/c.			16-C-59438-2441	N16-C-12235-18			CBC	45-11736-3	CRV	K-815736-3rev10	RAL RAL-1 RAL-5 (2) thru RAL-8 (2)
-48577	CAPACITOR, variable: 4/29/35 air; plate meshing type single sect; 6 to 50 mmf p/m 10%; SLC; 0.0245" air gap; 1 21/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 5/32" lg bushing 3/8" lg x 3/8"-32 thd w/locking nut; scdr adj; seven cad or nickel pl brass plates; clockwise rotation; ceramic ins; lug term; base mtg by two mtg feet ea w/one 6-32 tap hole on 1 7/32" mtg/c.			16-C-59851-9821	N16-C-12236-13			CBC	45-11736-4	CRV CRV	K-815736-4 rev10 K-856620-1 sub0	RAK (2) RAK-1 (2) thru RAK-4 (2) RAK-6 (2) RAK-7 (2) RAL-2 (2) RAL-3 (2) RAL-4 (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-183

RESTRICTED

RESTRICTED

SHEET 48 - 184

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STO K NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48578	CAPACITOR, variable: 4/29/35 air; plate meshing type single sect; 6 to 60 mmf p/m 10%; SLC; 0.0245" air gap; 1 17/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 5/16" lg bushing 9/16" lg x 3/8"-32 tap w/locking nut; scdr adj; eight cad pl brass plates; clockwise rotation; ceramic ins; lug term; base mtg by one mtg foot w/one #6-32 tap hole.			16-C-60106-6346	N16-C-12236-18			CHC	45-11736-5	CRV	K-815736-5 rev10	R K RAK-1 thru RAK-4 RAK-7 RAL-2 thru RAL-4
-48579	CAPACITOR, variable: 4/29/35 air; plate meshing type single sect; 7.5 to 80 mmf p/m 10%; SLC; 0.0245" air gap; 1 21/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 5/32" lg bushing 3/8" lg x 3/8"-32 thd w/locking nut; scdr adj; eleven cad pl brass plates; clockwise rotation, 180 deg; ceramic ins; lug term; base mtg by two mtg feet ea w/one #6-32 tapped holes on 1 7/32" mtg/c.			16-C-60423-3206	N16-C-12236-100			CHC	45-11736-6	CRV	K-815736-6 rev10	RAK (2) thru RAK-4 (2) RAK-6 (2) RAK-7 (2) RAL-2 (8) thru RAL-4 (2)
-48580	CAPACITOR, variable: 5/8/35 air; plate meshing type single sect; 2.7 to 75 mmf; SLC; 0.020" air gap; 1 3/8" lg x 1 7/16" wd x 1 11/32" h shaft 1/4" diam x 1/8" lg bushing 1/4" lg x 3/8"-32 thd locking type; scdr adj w/#6-32 tap in ctr of shaft; fifteen aluminum plates; 360 deg rotation; isolantite ins; lug term; single hole mtg by 3/8" diam mtg bushing or panel mtg by two 1/8" diam holes on 1 3/32" mtg/c.			16-C-60207-5164	N16-C-12236-37			CRK CBK	ZU-75-AS-211 RT-75	CRV	K-815211-105 rev7	RAK (2) RAK-1 (2) thru RAK-4 (2) RAL-2 (2) thru RAL-4 (2)
-48581	CAPACITOR, variable: 5/8/35 air; plate meshing type single sect; 3.7 to 118 mmf; SLC; 0.020" air gap; 1 21/32" lg x 1 7/16" wd x 1 11/32" h shaft 1/4" diam x 1/8" lg bushing 1/4" lg x 3/8"-32 thd locking type; scdr adj w/#6-32 tap in ctr of shaft; twenty-three aluminum plates; 360 deg rotation; isolantite ins; lug term; single hole mtg by 3/8" diam mtg bushing or panel mtg by two 1/8" diam holes on 1 3/32" mtg/c.			16-C-60974-3559	N16-C-12242-75			CRK CMK	ZU-118-AS-211 RT-118	CRV	K-815211-107 rev7	RAK (2) thru RAK-4 (2) RAL-2 (2) RAL-3 (2) RAL-4 (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-184

RESTRICTED

RESTRICTED

SHEET 48 - 185

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48582	CAPACITOR, variable: air; plate meshing type single sect; 1.2 to 10 mmf; SIC; 0.030" air gap; 2 1/32" lg x 1 7/16" wd x 1 11/32" h shaft 1/8" diam x 1/8" lg bushing 1/4" lg x 3/8"-32 thd locking type; sdr adj w/#6-32 tap in ctr of shaft; four aluminum plates; 360 deg rotation; isolantite ins; lug term; single hole mtg by 3/8" diam mtg bushing or panel mtg by two 1/8" diam holes on 1 3/32" mtg/c.	5/8/35		16-C-58213-1970	N16-C-12217-9			CRK	ZR-10-AS-211	CRV	K-815211-112rev7	RAK RAK-1 RAL RAL-1 RAL-6 (2) RAL-7 (2) R L-8
-48583	CAPACITOR, fixed: mica; 500 mmf; 3000 vdcw, 3 amp at 3000 kc, 2 amp at 1000 kc, 1 amp at 300 kc, 0.55 amp at 100 kc; case 2" lg x 15/16" wd x 1 1/2" h; molded low loss bakelite case; two screw term 7/16" h spaced 1 1/2" c to c on top; two mtg fl on bottom, ea w/one 0.15" diam hole on 2 3/8" mtg/c.	5/14/35	RE48A222 16C40									
-48583-B5	CAPACITOR, fixed: NT-48583 w/500 mmf p/m 5%; temp coef ltr B. NOTE: QCJ-8; QCL; QCI-7; TBC-4; TBL-8; TEL-9.	5/14/35	R 48A222 16C40	16-C-30163-5021	N16-C-10023-16			CRV	UC-3094 Case #352	CRV	W-303241-12 K-860215-6rev8	TBG QCJ-1 SEE NOTE
-48583-D2	CAPACITOR, fixed: NT-48583 w/500 mmf p/m 2%; temp coef ltr D.	5/14/35	RE48A222 16C40	16-C-30158-3543	N16-C-10023-14			CRV CL	UC-3094-X	COL	T-7606408-27	TCB-2
-48583-D5	CAPACITOR, fixed: NT-48583 w/500 mmf p/m 5%; temp coef ltr D.	5/14/35	RE48A222 16C40	16-C-30163-5026				CRV	UC-3094-X			
-48584	CAPACITOR, fixed: mica; 250 mmf; 3000 vdcw, 2.5 amp at 3000 kc, 2.5 amp at 1000 kc, 1 amp at 300 kc, 0.4 amp at 100 kc; case 2" lg x 15/16" wd x 1 1/2" h; low-loss bakelite case; two screw term 7/16" h spaced 1 1/2" c to c on top; two mtg fl on bottom, ea w/one 0.15" diam hole on 2 3/8" mtg/c.	5/14/35	RE48A222 16C40									
-485 4-B5	CAPACITOR, fixed: NT-48584 w/250 mmf p/m 5%; temp coef ltr B.	5/14/35	RE48A222 16C40	16-C-29477-6625	N16-C-9978-47			CD CRV	PL805-15L UC-320X	CG	F-7763754-6	TBG RBD TCX

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-185

RESTRICTED

RESTRICTED

SHEET 48 - 186

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48585	CAPACITOR, fixed: 6/18/35 mica; 150 mmf; 10,000 vdcw, 6 amp at 3000 kc, 4 amp at 1000 kc, 1.6 amp at 300 kc, 0.6 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48585-B5	CAPACITOR, fixed: 6/18/35 NT-48585 w/150 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-28977-8873	N16-C-9961	R16-C-9961		CRV	UC-3123	CRV	DL-500444-502	TBL TBL-1
-48585-B10	CAPACITOR, fixed: 6/18/35 NT-48585 w/150 mmf p/m 10%; temp coef ltr B.	RE48A122 16C40		16-C-28982-9351	N16-C-9961-1			CRV	UC-3123			
-48586	CAPACITOR, fixed: 7/8/35 paper dielectric; five sect; 7/4/2/1/1 mf plus 10 minus 3%; 600/600/600/600/600 vdcw; ES metal can; case 4 13/16" h x 3 3/4" lg x 2 1/4" wd; mineral oil impr and filled; six stud and nut term in two rows of three each, term 1" c to c and rows are 7/8" c to c apart; one side of all sect common ne int gnd connections.	RE48A186 RE13A488		16-C-54967-9200				CD	MC-108	CRV	M-409459 rev1	GP GP-2
-48587	CAPACITOR, fixed: 7/8/35 paper dielectric; 2 mf plus 10 minus 3%; 1000 vdcw; HS metal can; case 3 7/8" h x 1 3/4" wd x 1" d; two stud term 3/4" h located on top, spaced 13/16" c to c; no int gnd connections. NOTE: SP; TDP-1 (4).	RE48A110 RE13A488		16-C-49179-5670	N16-C-11490-11			CG CSF CG	9CE2A6 1076 23F106	CRV CHZ CG	K-823197 rev1 CO-1003-2 P-7763476-P6	GP BL-1 (2) thru BL-5 (2) SM-1 SEE NOTE
-48588	CAPACITOR, fixed: 7/8/35 paper dielectric; 3 mf plus 10 minus 3%; 1500 vdcw; ES metal can; case 3 7/8" h x 3 3/4" wd x 1 3/4" d o/a; two stud term 3/4" h located on top, spaced 2" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-49561-8951				CG	9CE2A11	CRV	M-409513 rev1	GP GP-2

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-186

RESTRICTED

RESTRICTED

SHEET 48 - 187

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48589	CAPACITOR, fixed: mica; 10,000 mmf; 300 vdcw, 600 vdc; case 1" lg x 5/8" wd x 5/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/hole 5/32" diam, holes 1 5/8" c to c.	7/8/35 RE48A149 16C40										
-48589-A10	CAPACITOR, fixed: NT-48589 w/10,000 mmf p/m 10%; temp coef ltr A.	7/8/35 RE48A149 16C40		16-C-33622-5340	N16-C-10492-1		3DA10-50	CD CAW	3L 1441	CFD CAG CDE	180-123-B 4886 2379-2	LX YB-2
-48589-B10	CAPACITOR, FIXED: Navy Type 48589 w/10,000 mmf p/m 10%; temp coef letter B NOTE: RAG-1; RAH (3); RAH-1 (3).	7/8/35		16-C-33622-5345				CD	3-IS	CAG CAG CAG	COM-41B N-COM-41B N-COM41-B	NOber- 43099 RAG SEE NOTE
-48589-D20	CAPACITOR, fixed: NT-48589 w/10,000 mmf p/m 20%; temp coef ltr D.	7/8/35 RE48A149 16C40		16-C-33627-7790				CD	3HL	CV	BSO-613080-21a	
-48590	CAPACITOR, fixed: mica; 10,000 mmf; 2,000 vdcw, 10 amp at 3,000 kc, 8 amp at 1,000 kc, 5 amp at 300 kc, 2.5 amp at 100 kc; case 2 1/16" lg x 61/64" wd x 1 17/32" h; molded bakelite case; two screw term 7/16" h spaced 1 1/2" c to c on top; two mtg fl on bottom ea w/one 0.15" diam hole on 2 3/8" mtg/c.	7/8/35 RE48A222 16C40										
-48590-A5	CAPACITOR, fixed: NT-48590 w/10,000 mmf p/m 5%; temp coef ltr A.	7/8/35 RE48A222 16C40		16-C-33618-6625				CRV	UC-3202	CRV	DL-500501-502 K-33356-2	GP GP-2
-48590-A20	CAPACITOR, fixed: NT-48590 w/10,000 mmf p/m 20%; temp coef ltr A.	7/8/35 RE48A222 16C40		16-C-33628-9585				CRV	UC-3202			
-48590-DR	CAPACITOR, fixed: NT-48590 w/ 10,000 mmf p/m 2%; temp coef ltr D.	7/8/35 RE48A222 16C40		16-C-33613-5151	N16-C-10509			CRV	UC-3202K			
-48591	CAPACITOR, fixed: mica; 25,000 mmf; 600 vdcw, 100 vdc; case 1 1/4" lg x 1 1/8" wd x 29/64" d max; molded bakelite case; two lug term w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	7/11/35 RE48A221 JAN-C-5										
-48591-A10	CAPACITOR, fixed: NT-48591 w/25,000 mmf p/m 10%; temp coef ltr A. NOTE: QCJ-8; QCL-7; TEM-10 (2); TEM-12 (2); WEA.	7/11/35 RE48A221 JAN-C-5	CM50A253K	16-C-34545-9851				CAW CSL CD	1445-.025 XQW 4-11025	CRV CAY CRV	P-720561-2 7606286-5 W-303284-213	TEM TEM ATB(2) SEE NOTE: cont

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-187

RESTRICTED

RESTRICTED

SHEET 48 - 188

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48591-B5	CAPACITOR, fixed: 7/11/35 NT-48591 w/25,000 mf p/m 5%; temp coef ltr B.	RE48A221 JAR-C-5	CM50B253J	16-C-34540-9396		R16-C-10535-125		CAW CAN CMR CSL	1445LS EL-1125 6 XQBW	CAY	7608012-148	RBS(4) RBS-1(4) RBS-2(4)
-48591-B10	CAPACITOR, fixed: 7/11/35 NT-48591 w/25,000 mf p/m 10%; temp coef ltr B. NOTE: TBM-12 (2); TBM-5 (2); TBM-6 (2); TBM-7 (2); TBM-8 (2).	RE48A221 JAR-C-5	CM50B253K	16-C-34545-9856	N16-C-10568			CAN CAW CMR CSL	EL-1125 1445LS 6 XQBW	CAY CAY	7608011-109 T-7606286-5	RBA(2) RBA-1(2) RBA-1 thru RBA-5 (2) SEE NOTE:
-48592	CAPACITOR, fixed: 7/11/35 CANCELLED: for replacement use NT-48752.	RE48A131 16C40						CD	PL-321-6			TBM TBN
-48593	CAPACITOR, fixed: 7/11/35 CANCELLED: 3,000 mf; 2,000 vdcw, 12 amp at 3,000 kc.	RE48A131 16C40						CD	PL-479-6			TBM TBN
-48594	CAPACITOR, fixed: CANCELLED: for replacement use NT-481215.											
-48595	CAPACITOR, fixed: 7/23/35 paper dielectric; 1 mf plus 10 minus 3%; 250 vdcw; HS metal can; case 1 7/8" h x 1 3/8" wd x 3/4" thk; oil impr and filled; two stud and nut term 5/8" c to c on top; no int gnd connections; no mtg holes, no mtg bkt supplied; superseded by NT-48595-A.	RE48A110 RE13A488		16-C-48790-9494						CRV CRV	K-77094-1 P-720555-11 sub27	GP(2) GP-2(2) NMB-1(6)
-48595-A	CAPACITOR, fixed: 7/11/40 paper dielectric; 1 mf plus 10 minus 3%; 400 vdcw, 100 vacw, 60 cps, 1200v DC test; case HS metal can; 1 7/8" h x 1 3/8" wd x 3/4" d; two stud term 1/2" h located on top, spaced 5/8" c to c; no int gnd connec- tions; bkt mtg not supplied; same as NT-48595 except 400 vdcw. NOTE: QGJ-B (6); QCL-7 (6); QCQ-2 (3); QCU (5); QFN (7); QGB (7); WEA (9); WE A-1 (5); ZOR (4); MK-26 Mod 3 (4); MK-26 Mod 4 (4).	RE48A110 RE13A488		16-C-48792-7716	N16-C-11398			CRV CRV	72053-508 P-720555-2	CRV CWT CWT	P-720555-2rev2 W-303335-30sub1 W-303090-33sub7	QCJ-2 QCL SA-3(2) SD-5(3) SG(7) MAR(4) RH(3) SEE NOTE
-48595-A10	CAPACITOR, fixed: 7/11/40 NT-48595-A w/1 mf p/m 10%. NOTE: RAK (16); RAL-7 (11); RBB (8); RBB-1 (8); RBB-2 (8); RBC (8); RBC-1 (8); RBC-2 (8); TDQ (4).	RE48A110 RE13A488		16-C-48813-7716	N16-C-11398-5	R16-C-11382-403		CRV	72053-558	CRV	P-720555-52rev2	ARJ ATJ(2) SEE NOTE:

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-188

RESTRICTED

RESTRICTED

SHEET 48 - 189

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48596	CAPACITOR, fixed: 7/23/35 paper dielectric; 100,000 mmf plus 10 minus 3%; 1,750 vdcw; HS metal can; 1 7/8" h x 1 3/8" lg x 3/4" wd; oil impr and filled; two stud and nut term 5/8" c to c on top; no int gnd connections; no mtg holes, no mtg bkt supplied; superseded by NT-48596-A.			16-C-45761-4210				CRV	72025-505	CRV	P-720555-6 sub27	GP
-48596-10	CAPACITOR, fixed: 7/23/45 NT-48596 w/ 100,000 mmf p/m 10%.			16-C-45762-4210	N16-C-11435-50	R16-C-11326		CRV CSF	P-72025-505 2525-2	CRV CRV CRP CG	K-77094-2 P-720555-56sub27 P-72025-505 35-5050 K-7896632-1	GP GP-2 SL SO-3 SO-4 SEE NOTE
	NOTE: SO-12M; SO-12N; RBB; RBB-1; RBB-2; RBC; RBC-1; RBC-2; TEK-8; TEK-10; TEK-12; TEK-14; TEK-17; TEK-19.											
-48596-A	CAPACITOR, fixed: 10/16/40 paper dielectric; 100,000 mmf plus 10 minus 3%; 1,750 vdcw, 700 vacw, 60 cps, 1,200v DC test; HS metal can; case 1 7/8" h x 1 3/8" wd x 3/4" d, o/a; oil impr and filled; two stud term 1/2" h located on top, spaced 5/8" c to c; no int gnd connections; bkt std; same as NT-48596 except 1750 vdcw.	RE48A110 RE13A488		16-C-45762-9600				CSF CRV	2526-2 72053-504	CRV CRP	P-720555-6 rev10 & 26	TBL-4 TEL-8 TBL-9 SG-2
-48596-A10	CAPACITOR, fixed: 10/16/40 NT-48596-A w/100,000 mmf p/m 10%.	RE48A110 RE13A488		16-C-45763-9600	N16-C-11325			CSF CRV	2526-2 72053-554	CRV CDM CRP CG CW	P-720555-56 rev10&26 744-582 35-5050	SG-1(3) SG-2(3) SM-1 SU SU-1 MK-29Mod2 MK-33
-48597	CAPACITOR, fixed: 8/2/35 paper dielectric; 20,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1" wd x 5/8" h, o/a; oil filled; two solder lug term 3/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/ bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48597-A.	RE13A488		16-C-43096-3109				CD				RAG RAH RAG-1 RAH-1
-48597-10	CAPACITOR, fixed: 8/2/35 NT-48597 w/20,000 mmf p/m 10%; for replacement use NT-48597-A.	RE13A488		16-C-43117-3109			3DA20-124			CHS	DRA-173-1	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-189

RESTRICTED

RESTRICTED

SHEET 48 - 190

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48597-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 20,000 mmf plus 10 minus 3%; 600 vdcw; ES metal can; case 1 13/16" lg x 1" wd x 3/4" h o/a; oil filled; two solder lug term 3/4" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/ bottom, w/ 3/16" diam mtg hole spaced 2 1/8" c to c.	RE13A488 RE48A129		16-C-43096-3114				CSF		CZC	CO-640	YH YH-1
-48597-A10	CAPACITOR, fixed: 11/23/46 NT-48597-A w/20,000 mmf p/m 10%.	RE13A488 RE48A129		16-C-43117-3114	N16-C-11023		3DA20-124	CIE CIE	7570 AB123	CZC	5066-2 1aa2	RBO-1(2) RBO-2(2) RCH
-48598	CAPACITOR, fixed: 8/2/35 paper dielectric; three sect; 4/ 4/ 4 mf plus 10 minus 3%; 600/600/600 vdcw; ES metal can; case 4 7/8" h x 3 7/8" lg x 2 1/4" wd; oil impr and filled; four lns solder lug term each 11/16" c to c on top; no int gnd connections; two integral mtg ft on bottom with mtg ctr 1 1/2" x 4 1/4".	RE48A189 RE13A488		16-C-54733-5124								
-48598-10	CAPACITOR, fixed: 8/2/35 NT-48598 w/4/4/4 mf p/m 10%.	RE48A189 RE13A488		16-C-54734-3212				CD		CES	C-RA-174-1	RAG-1 RAB-1
-48599	CAPACITOR, fixed: 8/6/35 mica; 40,000 mmf; 1,500 vdcw, 14 amp at 34 kc, 6 amp at 15 kc; case 5 3/4" h x 5" diam; low-loss ceramic case; two elliptical cast aluminum end cap term, ea w/two 0.377" diam holes 5 3/4" c to c.	RE48A237 16C40										
-48599-B5	CAPACITOR, fixed: 8/6/35 NT-48599 w/ 40,000 mmf p/m 5%; temp coef 1tr B.	RE48A237 16C40		16-C-34990-2735				CD	PL-523A-52			TBJ
-48600	CAPACITOR, fixed: 8/14/35 paper dielectric; 1 mf plus 10 minus 3%; 400 vdcw; ES metal can; case 2" lg x 1 3/4" wd x 13/16" h o/a; oil filled; two solder lug term 5/16" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 3/8" c to c; for replacement use NT-48600-A10.	RE13A488 RE48A129		16-C-48793-1186				CSL CAW	XIMRW4-1 430-1			
-48600-10	CAPACITOR, fixed: 8/14/35 NT-48600 w/ 1 mf p/m 10%.	RE13A488 RE48A129		16-C-48814-1186			3DB1.9-1	CSL CAW	XIMRW4-1-10 430-1	OW	ESA-682063-221 1aa15	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-190

RESTRICTED

RESTRICTED

SHEET 48 - 191

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-48600-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 1 mf plus 10%; 600 vdcw; BS metal can; 2" lg x 1 3/4" wd x 7/8" h.o/a; oil filled; two solder lug term 3/4" h on side, spaced 1 1/16" c to c; no int grd connections; two mtg feet 3/8" wd flush w/bottom, ea w/ 3/16" diam mtg holes spaced 2 3/8" c to c.	RE13A488		16-C-48796-3885	N16-C-11418-7			CAW	630	CBZ	CO-609	BL-1	
		RE48A129						CD	DYR-6100	CFT	RF-151-1A	BL-2	
								CIE	68A100	CDU	DD-5038-A-2	BL-3	
								CGF	2528-11	CBZ	CO-639revC	BN	
								CSL	XMM6-1	CQA	10169 rev 0	BN-1	
								CDU	3-383	CRH	OA30879-4 rev C	BN-2	
								CSF	P-8906	CFN	300447-5	DAH	
										CAT	7706012-2	DAV (2)	
	NOTE: DAV-1 (2); GP-3; GP-4; OAP; QJB; YH; YH-1; YJ (5); YJ-1 (5); YJ-2 (5).											SEE NOTE:	
-48600-A10	CAPACITOR, fixed: 11/23/36 NF-48600-A w/ 1 mf p/m 10%.	RE13A488		16-C-48817-3895	N16-C-11419-7	R16-C-11418	3DB1-601-4	CSF	P-8906	CBM	744-236	BL-1 thru	
		RE48A129						CIE	68A100	CFT	RF-151-1A	BL-3	
									CAW	630	CG	T-7606991-15	BN thru
									CSL	XMM6-1-10	CDU	DD-5038-A-2	BN-2
									CDU	3-383	CRP	35-5101	DAB (3)
									CGF	7504	CBZ	CO-639revC	DAK (2)
									CD	DYR-6100	CQA	10169	DAK-1 (2)
											CRH	OA30879revC	DAS-1 (5)
										CW	ES-682063-55		DAS-3 (5)
										CFN	300447-5		DAV
										CFE	10.66		DAV-1
										CAY	T-7609856-15		SF-1 (2)
	NOTE: SJ-1 (4); SS; SV (4); SX (6); TCB-1; TCE thru TCE-2; TDG; TDG-1; VD; VD-1 (2); WCA (6); WCA (6); WCA-1 (6); WCA-3 (6); AN/TPS-1B (3); ME-9 (6); ME-10 (6).											SEE NOTE	
-48600-A20	CAPACITOR, fixed: 11/23/36 NF-48600-A w/ 1 mf p/m 20%.	RE13A488		16-C-48847-7935		R16-C-11419-14	3DB1.630-4	CD	DYR-6100	CBZ		OAP-1	
		RE48A129						CIE	68A100				
									CAW	630			
									CSL	XMM6-1			
									CDU	3-383			
									CSF	P-8906			
							CGF	7504					
								CSF	2528-11				

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-191

RESTRICTED

RESTRICTED

SHEET 48 - 192

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S QWG OR PART NO	EQUIPMENT USED IN
-48601	CAPACITOR, fixed: mica; 250 mmf; 500 vdcv, 1000 vdcvt; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48601-A10	CAPACITOR, fixed: NT-48601 w/250 mmf p/m 10%; temp coef ltr A. NOTE: RAH(8); RAH-1(8).	RE48A149 16C40		16-C-29481-3891			204197/15	CD	3L-13025	CHS CHS	RA-189 D-50W-250-B alt0	RAG(2) RAG-1(2) SEE NOTE
-48601-B5	CAPACITOR, fixed: NT-48601 w/250 mmf p/m 5%; temp coef ltr B.	RE48A149 16C40		16-C-29476-3416				CD	3WLS	CW		TDG TDG-1
-48602	CAPACITOR, fixed: mica; 5000 mmf; 300 vdcv, 600 vdcvt; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48602-A10	CAPACITOR, fixed; NT-48602 w/5,000 mmf p/m 10%; temp coef ltr A. NOTE: RAH; LP thru LP-4.	RE48A149 16C40		16-C-32699-345				CD	3L-12050	CHS CHS	D-50W-250-C alt0 RA-190	RAG RAG-1 SEE NOTE
-48602-B10	CAPACITOR, fixed: NT-48602 w/5,000 mmf p/m 10%; temp coef ltr B.	RE48A149 16C40		16-C-32699-3457	N16-C-10401-50			CD	PL-3	CRV	K-823039-3alt3	
-48603	CAPACITOR, fixed: mica; 1000 mmf; 500 vdcv, 1000 vdcvt; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48603-A10	CAPACITOR, fixed: NT-48603 w/1000 mmf p/m 10%; temp coef ltr A.	RE48A149 16C40		16-C-31090-4290			204197/13	CD	3L-12010	CHS CFD	D-50W-250-D alt0 180-126-B	RAG
-48603-B10	CAPACITOR, fixed: NT-48603 w/1000 mmf p/m 10%; temp coef ltr B. NOTE: OR; OH-1; RAH-1 (2).	RE48A149 16C40		16-C-31090-4296				CD	3L-5D1	CHS CAG	RA-191	RAH (2) LX (3) SEE NOTE
-48604	CAPACITOR, fixed: mica; 3000 mmf; 500 vdcv, 1000 vdcvt; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48604-A10	CAPACITOR, fixed: NT-48604 w/3,000 mmf p/m 10%; temp coef ltr A.	RE48A149 16C40		16-C-32198-3085				CD CAN	3L-12030 R-50	CHS CRF	D-50W-250-E alt0	SG
-48604-B10	CAPACITOR, fixed: NT-48604 w/3,000 mmf p/m 10%; temp coef ltr B. NOTE: RAG-1; RAH-1.	RE48A149 16C40		16-C-32198-3086			3DXA3-23.2	CD	3LL	CHS CRR	RA-192 815277alt0	RAG RAH SEE NOTE

SHEET 48-192

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 193

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48605	CAPACITOR, fixed: 8/16/35 mica; 45,000 mmf; 600 vdcw, 1000 vact; case 1 1/4" lg x 1 1/8" wd x 29/64" d max; molded bakelite case; two lug term w/two 0.173" diam holes 1 3/4" c to c; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A 21 JAN-C-5									
-48605-A10	CAPACITOR, fixed: 8/16/35 NT-48605 w/45,000 mmf p/m 10%; temp coef ltr A.	RE48A221 JAN-C-5	CM50A453K	16-C-35152-7511				CD	4-11045	CBS CBS RA-184 D-50W-249-A	RAG (4) RAH RAG-1 (4)
-48606	CAPACITOR, fixed: 8/16/35 mica; 19,000 mmf; 600 vdcw, 1000 vact; case 1 1/4" lg x 1 1/8" wd x 29/64" thk max; molded bakelite case; two lug term w/ one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 JAN-C-5									
-48606-A2	CAPACITOR, fixed: 8/16/35 NT-48606 w/19,000 mmf p/m 2%; temp coef ltr A. NOTE: RAG-1; RAH-1.	RE48A221 JAN-C-5	CM50A193G	16-C-34271-9890				CD	4-11019	CBS CBS RA-185 D-50W-249-B	RAG RAH SEE NOTE
-48607	CAPACITOR, fixed: 8/16/35 CANCELLED: for replacement use NT-48610.							CD	4-12060	CBS D-50W-249-C	RAG RAH
-48608	CAPACITOR, fixed: 8/16/35 paper dielectric; two sect; 500,000/500,000 mmf plus 10 minus 3%; 300/300 vdcw; metal can; 1" h x 2" wd x 1 3/4" thk; asphalt compound impr and filled; three flex wire term 6" lg out of side; no int gnd connections; two integral mtg ears on bottom w/5/32" wd slot 2 3/8" c to c.	RE48A190 RE13A488		16-C-53569-1786							RAH
-48608-10	CAPACITOR, fixed: 8/16/35 NT-48608 w/500,000/500,000 mmf p/m 10%.	RE48A190 RE13A488		16-C-53625-4116				CD		CBS CBS RA-169 D-50W-257 alt0	RAG RAG-1
-48608-20	CAPACITOR, FIXED: 2/6/50 Navy Type 48608 w/500000/500000 mmf p/m 20%.			16-C-53702-3980	N16-C-11375-117			CBS			
-48609	CAPACITOR, fixed: 8/16/35 paper dielectric; two sect; 1 mfd/500,000 mmf plus 10 minus 3%; 300/300 vdcw; metal can; 1 3/4" h x 1 5/16" wd x 1 9/16" thk; asphalt compound impr and filled; three flex wire term 6" lg out of top; no int gnd connections 1 side common; two integral mtg ft with 1 15/16" mtg ctr on bottom.	RE13A488		16-C-53569-4131							
-48609-10	CAPACITOR, fixed: 8/16/35 NT-48609 w/1 mfd/500,000 mmf p/m 10%.	RE13A488		16-C-53625-6458				CD		CBS D-50W-253	
-48609-15	CAPACITOR, fixed: 8/16/35 NT-48609 w/1 mfd/500,000 mmf p/m 15%.	RE13A488		16-C-53886-8805							

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-193

RESTRICTED

RESTRICTED

SHEET 48 - 194

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48610	CAPACITOR, fixed: 8/21/35 paper dielectric; 13 mf plus 10 minus 3%; 1,000 vdcv; HS metal can; case 3" lg x 3" wd x 4 5/8" h o/a; oil impr and filled; two ceramic ins screw type term 13/16" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 7/32" diam mtg holes on 2" x 3 1/2" mtg/c.	RE48A159 RE13A488		16-C-51991-2810				CAY	FL	CAY	45-D-644-1 rev5	TBM TBN
-48611	CAPACITOR, fixed: 8/21/35 paper dielectric; 20 mf plus 10 minus 3%; 1500 vdcv; HS metal can; case 6" lg x 3 1/8" wd x 7" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/3" h located on top 3 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 7/32" diam mtg holes 2 1/8" apart ctr 6 1/2" c to c.	RE48A159 RE13A488		16-C-52222-1990				CAY	FL	CAY	45-D-644-4 rev3	TBM TBN
-48612	CAPACITOR, fixed: 8/21/35 paper dielectric; 800,000 mmf plus 10 minus 3%; 1500 vdcv; HS metal can; case 3" lg x 1" wd x 3 1/8" h; oil impr and filled; two pillar ins screw type term 1 1/8" h, located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/0.190" diam mtg hole 3 1/2" c to c.	RE48A146 RE13A488		16-C-48421-7943				CAY	FL	CAY	45-D-643-4 rev3	TBM TBN
-48613	CAPACITOR, fixed: 8/21/35 paper dielectric; 6 mf plus 10 minus 3%; 3000 vdcv; HS metal can; case 6" lg x 1 3/4" wd x 7" h; oil impr and filled; two pillar ins screw type term 1 1/2" h, located on top 3 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea with 0.190" diam mtg hole 6 1/2" c to c.	RE48A146 RE13A488		16-C-50704-6947				CAY	FL	CAY	45-D-643-7 rev3	TBM TBN
-48614	CAPACITOR, fixed: 8/21/35 paper dielectric; 1.75 mf plus 10 minus 3%; 600 vdcv; HS metal can; case 3" lg x 1" wd x 1 7/8" h; oil impr and filled; two pillar ins screw type term 13/16" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/0.190" diam mtg hole 3 1/2" c to c.	RE48A146 RE13A488		16-C-49081-7992				CAY	FL	CAY	45-D-643-8 rev3	TBM TBN

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-194

RESTRICTED

RESTRICTED

SHEET 48 - 195

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48615	CAPACITOR, fixed: 8/21/35 paper dielectric; 300,000 mmf plus 10 minus 3%; 1000 vdcw; HS metal can; case 2" lg x 1" wd x 1 7/8" h; oil impr and filled; two pillar ins screw type term 13/16" h located on top 1" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/0.190" diam mtg hole 2 1/2" c to c.	RE48A146 RE13A488		16-C-46517-7512				CAY	FL	CAY	45-D-643-9 rev3	TBM TBM
-48616	CAPACITOR, fixed: 8/21/35 paper dielectric; 500,000 mmf plus 10 minus 3%; 3000 vdcw; HS metal can; case 3" lg x 1" wd x 4 5/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/2" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl 1" wd on side of case, ea w/ 0.190" diam mtg hole ctr 3 1/2" c to c.	RE48A146 RE13A488		16-C-47284-5017				CAY	FL	CAY	45-D-643-10 rev3	TBM TBM
-48617	CAPACITOR, fixed: 9/3/35 paper dielectric; two sect; 4 mfd/2 mfd plus 10 minus 3%; 300/300 vdcw; HS metal can; 2 1/2" wd x 4 3/4" lg x 1 11/16" h; oil impr and filled; four ins solder lug term on one end; no int gnd connections; four integral mtg ft w/#6-32 nuts on 3 1/4" x 2 7/8" mtg/c.	RE48A192 RE13A488		16-C-53988-9255				CD	PC518	CD	25925 rev0	
-48617-10	CAPACITOR, fixed: 9/3/35 NT-48617 w/4 m/2 m/ p/m 10%.	RE48A192 RE13A488		16-C-54020-2610	N16-C-12725-100			CD	PC514	CBS CBS	RA-155 D-50W-258	RAG RAH SEE NOTE
-48618	CAPACITOR, fixed: 9/3/35 paper dielectric; two sect; 250,000 mmf plus 10 minus 3% ea sect; 300 vdcw ea sect; HS metal can; 1 13/16" lg x 3/4" h x 1 1/4" wd; three tab term spaced 1/2" apart on side; no int gnd connection; mts by two integral mtg ft w/ 11/64" diam hole in ea on 2 1/8" mtg/c; superseded by NT-48618-B.	RE13 488		16-C-53319-1692								RAG RAH
-48618-10	CAPACITOR, fixed: 9/3/35 NT-48618 w/250,000 mmf p/m 10% ea sect.	RE13A488		16-C-53375-4044				CD		CBS CBS	D-50W-265 RA-160	RAG RAG-1 SEE NOTE:

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-195

RESTRICTED

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48618-A	CAPACITOR, fixed: 11/23/36 paper dielectric; two sect; 250,000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; case 1 13/16" lg x 1 1/4" wd x 3/4" h o/a; oil impr and filled; three solder lug term 3/8" h on side, spaced 1/2" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c; superseded by NT-48618-B.	RE13A488 RE48A129		16-C-53320-3974				CAW	430	CIA	D5498.1B-146	DA6
-48618-A15	CAPACITOR, fixed: 11/23/36 NT-48618-A w/250,000 mmf p/m 15% ea sect; superseded by NT-48618-B15.	RE13A488 RE48A129		16-C-53426-4586	N16-C-11343-28			CAW	430			
-48618-B	CAPACITOR, fixed: 12/9/40 paper dielectric; two sect; 250,000 mmf plus 10 minus 3% ea sect; 600 vdcv ea sect; ES metal can; case 1 13/16" lg x 1 1/4" wd x 3/4" h o/a; oil impr and filled; three solder lug term 3/8" h on side, spaced 1/2" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w 3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A129		16-C-53334-1504		R16-C-11708-100 R16-C-11338-75		CD CSF	DTR-6022 CPSTS-59			DA6 ABK ABK-1 ABK-2 ABK-3 ABK-4 ABK-5 ABK-6 ABK-7
-48618-B10	CAPACITOR, fixed: 12/9/40 NT-48618-B w/250,000 mmf p/m 10% ea sect. NOTE: ABK-1 ABK-2; ABK-3; A K-4; ABK-5; ABK-6; ABK-7	RE13A488 RE48A129		16-C-53390-5629			3DA250-20.4	CD CSF	DTR-6022 CPSTS-59	CEZ CDU	CO-629 3-382	DA6 ABK SEE NOTE
-48618-B15	CAPACITOR, fixed: 12/9/40 NT-48618-B w/250,000 mmf p/m 15% ea sect. NOTE: SL-a (5); SV; AN/TPS-1B (4); MK-3 (6); ME-4 (6); MK-8 Mod 2; MK-16 (4); MK-18 (3); MK-19 (3); MK-22 (2); MK-27 (3); MK-28 (3); MK-29 Mod 2 (3); MK-34 Mod 2 (3); MK-34 Mod 3 (3); MK-34 Mod 4 (3).	RE13A488 RE48A129		16-C-53433-4154	N16-C-11343-60		3DA250-224 3DA250-255 3DA250-20.2	CD CGF CAW	DTR-6022 7508 630-.25-.25	CW	ES-682063-59	SJ-1 (4) SL (5) SL-1 (4) SEE NOTE
-48618-B20	CAPACITOR, fixed: 12/9/40 NT-48618-B w/250,000 mmf p/m 20% ea sect.	RE1 A488 RE48A129		16-C-53461-5706	N16-C-11343-52			CD CSF	DTR-6022 CPSTS-59	CFT CW	RF-2619-1-2 ES-682063-368	DAV DAV-1 SJ-1 (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 197

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48619	CAPACITOR, fixed: 9/3/35 paper dielectric; three sect; 250,000/250,000/ 250,000 mmf plus 10 minus 3%; 300/300/300 vdcw; metal can; case 2 5/8" h x 1 5/8" wd x 5/8" thk; asphalt compound impr and filled; four flex wire leads 6" lg out of top; no int gnd connections, one side of all sect common; mts by two #6-32 thd clinch nuts 1 9/16" c to c opposite corners of case.	RE48A193 RE13A488		16-C-54495-9554								RAG RAH
-48619-10	CAPACITOR, fixed: 9/3/35 NT-48619 w/250,000/250,000/250,000 mmf p/m 10%.	RE48A193 RE13A488		16-C-54513-4523				CD		CHS CHS	RA-168 D-50W-273 alt 0	RAG (3) RAG-1 (3)
-48620	CAPACITOR, fixed: 9/3/35 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 300 vdcw ea sect; HS metal can; case 2 1/8" h x 1 5/16" wd x 5/8" thk; wax impr and sealed; three ins wire leads on end of case in ctr extending 6" from grommet plus 5/16" bare wire; no int gnd connection; two mtg ft 5/8" wide integral w/bottom of case w/two 11/64" mtg holes on 1 5/8" ctr.	RE48A136 RE13A488		16-C-53103-9547				CD				RAG RAH
-48620-10	CAPACITOR, fixed: 9/3/35 NT-48620 w/100,000 mmf p/m 10% ea sect.	RE48A136 RE13A488		16-C-53147-7360	N16-C-11330-150			CD		CH CHS	D-50X-170 alt 0 RA-146	RAH (5) RAH-1 (5)
-48621	CAPACITOR, fixed: 9/3/35 paper dielectric; 12 mf plus 10 minus 3%; 300 vdcw; HS metal can; case 3 3/4" lg x 1 7/8" x 5" lg; oil filled; two solder lug term 5/8" h on end of case; no int gnd connections; four mtg ft w/#6-32 thd elastic stop nuts on h" x 4 1/4" mtg/c.	RE48A194 RE13A488		16-C-51899-8160								RAG RAH
-48621-10	CAPACITOR, fixed: 9/3/35 NT-48621 w/12 mf p/m 10%.	RE48A194 RE13A488		16-C-51899-8445	N16-C-11690-50			CD		CHS CD	RA-159 25926rev0	RAH RAH_1
-48622	CAPACITOR, variable: 9/11/35 air; plate meshing type single sect; 4 to 35 mmf p/m 2%; SLC; 0.0245" air gap; 7/8" lg x 1 3/4" wd x 1 11/16" h shaft 1/4" diam x 9/16" lg bushing 3/8" lg x 3/8"-32 thd; round shaft; five cad pl brass plates; clockwise rotation; isolantite ins; lug term for stator, rotor gnd; single hole mtg by 3/8" diam mtg bushing or base, mtg by one mtg ft w/#6-32 tapped hole.			16-C-54411-6041				CRC		CHS CHS	RA-112 D-50W-275 alt A	RAG RAG-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-197

RESTRICTED

RESTRICTED

SHEET 48 - 196

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
48623	CAPACITOR, variable: 9/11/35 air; plate meshing type single sect; 36 to 76 mmf p/m 2%; SLC; 31/32" lg x 15/16" wd x 1 7/32" h shaft completely encl in housing w/ bushing and lock nut 3/16" diam x 7/16" lg; scdr adj; twenty cad pl brass plates; 360° rotation; isolantite insulation; post term for stator, lug term for rotor on RH side; two mtg studs 3/32" lg w/#2-56 tap on 21/32" mtg/c.			16-C-60362-9047				CHC CRS	APC RA-139A	CHS	D-50W-280 alt 0	RAG(16) RAG-1(16)
48624	CAPACITOR, variable: 9/11/35 air; plate meshing type single sect; 4 to 25 mmf p/m 2%; SLC; 0.015" air gap; 9/16" lg x 15/16" wd x 1 7/32" h, shaft 9/32" diam x 3/32" lg; round shaft w/scdr adj; seven cad pl brass plates; 360 deg rotation; isolantite insulation; post term for stator; lug term for rotor on RH side; two mtg posts w/#2-56 tap 21/32" c to c.			16-C-59052-6351			3D9025-67	CHC	APC	CHS	D-50W-318 alt 0	RAG RAG-1
48625	CAPACITOR, variable: 9/11/35 air; plate meshing type single sect; 3 to 15 mmf p/m 2%; SLC; 0.015" air gap; 5/8" lg x 15/16" wd x 1 7/32" h, shaft 9/32" diam x 1/16" lg; round shaft w/scdr adj; cad pl brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor; two mtg posts w/#2-56 tap 21/32" c to c.			16-C-58479-2435				CHC	APC	CHS	D-50W-318 alt 0	RAG RAG-1
48626	CAPACITOR, variable: 9/11/35 air; plate meshing type single sect; 3 to 15 mmf; SLC; air gap 0.015"; 1" lg x 15/16" wd x 1 7/32" h shaft 5/32" diam bushing 9/32" diam x 5/16" lg; scdr adj; four cad pl brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RH side; single 9/32" hole for bushing, two mtg studs tapped for #2-56 screw in base on 21/32" mtg/c 31/64" from top.			16-C-58479-2455				CHC	APC	CHS	D-50X-169-A alt 0	RAH RAH-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-198

RESTRICTED

RESTRICTED

SHEET 48 - 199

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48627	CAPACITOR, variable: air; plate meshing type single sect; 3 to 15 mmf; SLC; 1" lg x 15/16" wd x 1 7/32" h shaft completely housed in housing 17/32" lg x 13/64" diam w/1/4"-32 thd x 3/16" lg bushing shoulder 9/32" diam x 3/32" lg; ecdr adj; four cad plated brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor RH side; single 9/32" hole for bushing, two mtg studs tapped for #2-56 screws in base on 21/32" mtg/c 31/64" from top.	9/11/35		16-C-58479-2475				CEC	APC	CHS	D-50X-166-A alt0	RAH (33) RAH-1 (33)
-48628	CAPACITOR, variable: air; plate meshing type single sect; 3 to 25 mmf; SLC; 0.015" air gap; 19/32" lg x 15/16" wd x 1 7/32" h; shaft completely housed in housing 17/32" lg x 13/64" diam w/ 1/4"-32 thd x 3/16" lg bushing, shoulder 9/32" diam x 3/32" lg; ecdr adj; seven cad pl brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor RH side; two mtg studs tapped for #2-56 screws on 21/32" mtg/c 31/64" from top.	9/11/35		16-C-58940-4000				CEC	APC-25-C	CHS	D-50X-166-B alt0	RAH(4) RAH-1(4) RAG(4) RAG-1(4) LP thru LP-4 LR thru LR-3
48628-A	CAPACITOR, variable: CANCELLED: same as NF-48628, 3 to 25 mmf. NOTE: LR thru LR-3.	5/9/39						CEC	APC-25-6	CAG	LC 1.	LP thru LP-4 SEE NOTE
-48629	CAPACITOR, variable: air; plate meshing type single sect; 5 to 50 mmf p/m 2%; SLC; 0.015" air gap; 1 1/16" lg x 15/16" wd x 1 7/32" h shaft completely encl in vrg 9/32" diam x 9/32" lg; ecdr adj; 14 cad pl brass plates; 360 deg rotation; isolantite insulation; post term for stator; lug term for rotor on RH side, two mtg studs 1/32" lg w/#2-56 tabs on 21/32" mtg/c.	9/11/35		16-C-59823-8201	N16-C-12226-13			CEC	APC	CHS CHS	RA-109A D-50X-167a1+0	RAG (4) RAG-1 (4)
-48630	CAPACITOR, variable: air; plate meshing type single sect; 3 to 10 mmf p/m 2%; SLC; 23/32" lg x 15/16" wd x 1 7/32" h shaft 1/4" diam x 2 9/16" lg; five cad pl brass plates; 360 deg rotation; isolantite insulation; post term stator, lug term for rotor on RH side; single 1/4" diam holes for shaft, two mtg holes tapped for #2-56 screws in base on 21/32" mtg/c 31/64" from top.	9/11/35		16-C-58290-2281				CEC	APC	CHS	D-50X-168-A alt0	RAH RAH-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-199

RESTRICTED

RESTRICTED

SHEET 48-200.1

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN																								
-48633	<p>CAPACITOR, fixed: 10/16/35</p> <p>mica; 450 mmf p/m 2%; seven flex leads for various capacities w/#2 lead grd to case:</p> <p>Capacity Measured Other term Capacity and</p> <table border="1"> <thead> <tr> <th>Between</th> <th>Connections</th> <th>Tolerance</th> </tr> </thead> <tbody> <tr> <td>1 and 2</td> <td></td> <td>197 mmf p/m 2%</td> </tr> <tr> <td>2 and 3</td> <td></td> <td>307 p/m 2%</td> </tr> <tr> <td>1 and 3</td> <td></td> <td>120 p/m 2%</td> </tr> <tr> <td>1 and 3</td> <td>3 to 4</td> <td>172 p/m 2%</td> </tr> <tr> <td>1 and 3</td> <td>3 to 4 and 5</td> <td>236 p/m 2%</td> </tr> <tr> <td>1 and 3</td> <td>3 to 4, 5 and 6</td> <td>332 p/m 2%</td> </tr> <tr> <td>1 and 3</td> <td>3 to 4, 5, 6 and 7</td> <td>450 p/m 2%</td> </tr> </tbody> </table> <p>2000 vdcw, 1.85 amp at 800 kc at 450 mmf; temp coef ltr B; case 2 9/16" lg x 2 13/32" wd x 2 3/8" h;</p> <p>sheet metal case; seven flex leads 6 1/2" min lg on top; one mtg fl on top front w/two 0.173" diam holes 1 1/2" c to c, one mtg ft on bottom 1 9/32" from back w/two holes 0.173" diam 1 7/8" c to c, one mtg block 5/8" lg x 3/8" h on top back w/one #6-32 tapped hole in front.</p>	Between	Connections	Tolerance	1 and 2		197 mmf p/m 2%	2 and 3		307 p/m 2%	1 and 3		120 p/m 2%	1 and 3	3 to 4	172 p/m 2%	1 and 3	3 to 4 and 5	236 p/m 2%	1 and 3	3 to 4, 5 and 6	332 p/m 2%	1 and 3	3 to 4, 5, 6 and 7	450 p/m 2%	RE48A243 16040						CRV	UC-3195	CRV K-35631-1	GP GP-2
Between	Connections	Tolerance																																	
1 and 2		197 mmf p/m 2%																																	
2 and 3		307 p/m 2%																																	
1 and 3		120 p/m 2%																																	
1 and 3	3 to 4	172 p/m 2%																																	
1 and 3	3 to 4 and 5	236 p/m 2%																																	
1 and 3	3 to 4, 5 and 6	332 p/m 2%																																	
1 and 3	3 to 4, 5, 6 and 7	450 p/m 2%																																	
-48633-B2	<p>CAPACITOR, FIXED: 5/12/49</p> <p>Navy Type 48633 w/450 mmf p/m 2%; temp coef ltr B.</p>	RF48A194		16-C-39445-3401				CRV CRV	UC-3195 K-35631		GP GP-2																								

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-200.1

RESTRICTED

RESTRICTED

SHEET 48-200.2

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
48634	<p>CAPACITOR, fixed: 10/16/35</p> <p>mica: 831 mmf p/m 2%; seven flex leads for various cap w/#2 lead and to case:</p> <p>Capacity Measured Other term Capacity and</p> <p> Between Connections Tolerance</p> <p> 1 and 2 378 mmf p/m 2%</p> <p> 2 and 3 663 p/m 2%</p> <p> 1 and 3 238 p/m 2%</p> <p> 1 and 3 3 to 4 316 p/m 2%</p> <p> 1 and 3 3 to 4 and 5 444 p/m 2%</p> <p> 1 and 3 3 to 4, 5 and 6 601 p/m 2%</p> <p> 1 and 3 3 to 4, 5, 6 and 7 831 p/m 2%</p> <p>2000 vdcw, 3.5 amp at 800 kc at 831 mmf; temp coef 1tr B; case 2 9/16" lg x 2 13/32" wd x 2 3/8" h; sheet metal case; seven flex leads 6 1/2" min lg on top; one mtg fl on top front w/two 0.173" diam holes 1 1/2" c to c, one mtg ft on bottom 1 9/32" from back w/two 0.173" diam holes 1 7/8" c to c, one mtg block 5/8" lg x 3/8" h on top back w/one #6-32 tapped hole in front.</p>	RE48A243 16040		16-0-39445-3425				CRV	UC-3219	CRV	K-35631-1	GP GP-2

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-200.2

RESTRICTED

RESTRICTED

SHEET 48 - 201

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S ^ STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48635	CAPACITOR, fixed: paper dielectric; 50 mfd plus 10 minus 3%; 1000 vacw; HS metal can; 6" lg x 4" wd x 7" h; oil impr and filled; two screw type term on ins top of case 15/16" h 3 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 7/32" diam mtg holes 3" apart ctr 6 1/2" c to c.	11/27/35 RE48A159 RE13A488		16-C-52663-1650				CAY	FL	CAY	45-D-644-5 rev5	TBN-1
-48636	CAPACITOR, variable: air; plate meshing type single sect; 12 to 325 mmf p/m 2%; SLC; 0.02k5" air gap; 2 13/16" lg x 1 3/4" wd x 1 11/16" h shaft 1/4" diam x 3/8" lg, bushing 1/2" diam x 5/8" lg w/hole for #6-32 set screw 1/8" from end for locking; round shaft; four plates; clock- wise rotation; isolantite ins; lug term; base mtg by two mtg ft ea w/one #6-32 tapped hole on 2 3/16"mtg/c.	12/23/35		16-C-61716-4601				CHC		CHS CHS	D-50W-261 alt 0 RA-104	RAG (2) RAG-1 (2)
-48637	CAPACITOR, variable: air; plate meshing type, single sect; 2 to 3.5 mmf; SLC; 1 1/2" lg x 15/16" wd x 1 7/32" h, shaft 9/32" diam x 1/16" lg; four cad-pl brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor; single hole 9/32" for shaft, two mtg studs tapped for #4-36 screw in base on 21/32" mtg/c 31/64" from top.	12/23/35		16-C-57989-6401				CHC	APC	CHS	D-50W-318alt0	RAG(3) RAG-1(3)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVYSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-201

RESTRICTED

RESTRICTED

SHEET 48 - 202

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48638	CAPACITOR, fixed: 12/23/35 paper dielectric; 1 mf sect A, 500,000 mmf sect B, plus 10 minus 3% ea sect; 300 vdcw ea sect; RS metal can; case 1 3/4" lg x 1 1/4" wd x 2 1/2" h o/a; oil filled; three solder lug term 3/8" h located on top; no int gnd connections; two mtg ft w/ #6-32 thd elastic stop nuts 2 1/8" c to c.	RE48A195 REL3A488		16-C-53569-4161							
-48638-10	CAPACITOR, fixed: 12/23/35 NT-48638 w/ 1 mf sect A, 500,000 mmf sect B, p/m 10% ea sect.	RE48A195 REL3A488		16-C-53625-6498				CD		CBS CUB CD RA-148A D-504-253B 25920rev0	RAG RAG-1 RAH RAH-1
-48638-15	CAPACITOR, fixed: 12/23/35 NT-48638 w/ 1 mf sect A, 500,000 mmf sect B p/m 10% ea sect.	RE48A195 REL3A488		16-C-53675-8308							
-48639	CAPACITOR, fixed: 12/31/35 mica; 4000 mmf; 600 vdcw. 1000 vdc; case 1 1/4" lg x 1 1/8" wd x 2 3/16" thk max; molded low-loss bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 JAN-C-5									
-48639-A2	CAPACITOR, fixed: 12/31/35 NT-48639 w/4,000 mmf p/m 2%; temp coef ltr A.	RE48A221 JAN-C-5	CM45A402C	16-C-32451-9190	N16-C-10373-150			CD	4-12040	CRR A13753-13	LD-4
-48639-B2	CAPACITOR, fixed: 12/31/35 NT-48639 w/4,000 mmf p/m 2%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B402C	16-C-32451-9195	N16-C-10373-150			CBL CD	XQCW.6-24-2 4L	CML CW ESA-609861ea1	JR-1
-48639-B10	CAPACITOR, fixed: 12/31/35 NT-48639 w/4,000 mmf p/m 10%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B402K	16-C-32462-2155	N16-C-10373-200			CD	4L	CW CW ES-611146-1 ES0-609852-1	GO-1(6) GO-2(6) GP-1(5)
-48639-B20	CAPACITOR, fixed: 12/31/35 NT-48639 w/4,000 mmf p/m 20%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B402M	16-C-32467-4636	N16-C-10373-202			CD	4L		

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-202

RESTRICTED

RESTRICTED

SHEET 48 - 203

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48640	CAPACITOR, fixed: 12/31/35 mica; 4,000 mmf; 1,200 vdcv, 2,500v DC test; case 1 1/4" lg x 1 1/8" wd x 29/64" thk; m'led low-loss bakelite case; two lug term w/two 0.173" diam holes 1 3/4" c to c; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48640-A10	CAPACITOR, fixed: 12/31/35 NT-48640 w/4,000 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-32462-6565				CD	4-22040			
-48640-B2	CAPACITOR, fixed: 12/31/35 NT-48640 w/4,000 mmf p/m 2%; temp coef ltr B.	RE48A221 16C40		16-C-32452-4610				CD	4L	CW	ESA-6089861#e1	
-48640-B10	CAPACITOR, fixed: 12/31/35 NT-48640 w/4,000 mmf p/m 10%; temp coef ltr B.	RE48A221 16C40		16-C-32462-6570	N16-C-10374			CD	4L	CW CW	ES-611146-1 ESO-609852-1	GO-1(2) GO-2(2) GP-1(4)
-48640-B20	CAPACITOR, fixed: 12/31/35 NT-48640 w/4,000 mmf p/m 20%; temp coef ltr B.	RE48A221 16C40		16-C-32467-9048	N16-C-10374-1			CD	4L			
-48641	CAPACITOR, fixed: 12/31/35 mica; 1,000 mmf; 1,200 vdcv, 2,500 vdot; case 1 1/4" lg x 1 1/8" wd x 11/32" thk; molded bakelite case; two lug term ea w/ one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48641-A2	CAPACITOR, fixed: 12/31/35 NT-48641 w/1,000 mmf p/m 2%; temp coef ltr A. NOTE: BL-3 (2); BL-5 (2).	RE48A221 16C40		16-C-31080-7648	N16-C-10089-50			CSL	XQM1.2-21-2	CHZ	CO-618	BL-1(2) BL-2(2) SEE NOTE:
-48641-A10	CAPACITOR, fixed: 12/31/35 NT-48641 w/1,000 mmf p/m 10%; temp coef ltr A. NOTE: IR-1(3) thru IR-3(3).	RE48A221 16C40		16-C-31090-9608	N16-C-10090-3			CD	4-22010	CW	ESO-609852-1	GP-1 IR(3) SEE NOTE
-48641-B2	CAPACITOR, fixed: 12/31/35 NT-48641 w/1,000 mmf p/m 2%; temp coef ltr B.	RE48A221 16C40		16-C-31080-7653				CD	4L	CW	ESO-611146-1	
-48641-B10	CAPACITOR, fixed: 12/31/35 NT-48641 w/1,000 mmf p/m 2%; temp coef ltr B. NOTE: TDD-2 (2); TDU thru TDE-4.	RE48A221 16C40		16-C-31090-9613	N16-C-10090-3			CD CD CAW CD	4L 4-6S1-LL 1446L-001 4L-22010	CW OG COL	ESA-608986 7761328-17 925 2107 20	TBO TBO-1 TCH TCH-1 SEE NOTE
-48641-B20	CAPACITOR, fixed: 12/31/35 NT-48641 w/1,000 mmf p/m 20%; temp coef ltr B.	RE48A221 16C40		16-C-31096-3093				CD CAW CAN CSL	4LS 1445LS EL XQBW	COL	925 2107 40	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-203

RESTRICTED

RESTRICTED

SHEET 48 - 204

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48642	CAPACITOR, FIXED: 12/31/35 mica; 2000 mmf; 1200 vdw; 1 1/4" lg x 1 1/8" wd x 23/64" thk; molded low-loss bakelite case; 2 lug terminals w/one 0.173" diam hole; 2 holes in front of case 0.144" diam on 1 5/16" mtg/c.	RB48A221 JAN-C-5										
-48642-A10	CAPACITOR, fixed: 12/31/35 NT-48642 w/2,000 mmf p/m 10%; temp coef ltr A.	RB48A221 JAN-C-5	CM45A202K	16-C-31803-2408				CD	4-22020	CW	880-609852-1	GP-1(2)
-48642-B2	CAPACITOR, fixed: 12/31/35 NT-48642 w/2,000 mmf p/m 2%; temp coef ltr B.	RB48A221 JAN-C-5	CM45B202G	16-C-31792-9452	N16-C-10241-45			CD	4L-22020	CG	F7762925P38rev0	RBU TCX
-48642-B5	CAPACITOR, FIXED: 7/26/49 Navy Type 48642 w/2000 mmf p/m 5%; temp coef letter B.		CM45B202J	16-C-31798-1933	N16-C-10241-60							MX-56
-48642-B10	CAPACITOR, fixed: 12/31/35 NT-48642 w/2,000 mmf; temp coef ltr B. NOTE: TDE; TDE-1; TDE-2; TDE-3.	RB48A221 JAN-C-5	CM45B202K	16-C-31803-2413	N16-C-10241-50		3DKA2-125	CD CAW CAW	4L-22020 1446LT	CAY CAY CAY CAY CAY CAY CAY	7406466-2 T-7605847-1 T-7609144-2 T-7606408-4 T-7607321-2 T-7609856-9 T-7606233-5 T-7606591-10 T-7608226-4	GP-3 GP-4 TBU TBU-1thru TBU-4 TCE-2(2) TCE TCE-1 TCE-2 SEE NOTE:
-48642-B20	CAPACITOR, fixed: 12/31/35 NT-48642 w/2,000 mmf p/m 20%; temp coef ltr B. NOTE: MK-29 Mod 2; MK-34 Mod 2 (4); MK-34 Mod 4 (5).	RB48A221 JAN-C-5	M45B202M	16-C-31808-4093	N16-C-10241-55			CD CAW	4LS 1446LS	CW		MX-18(4) MK-28 SEE NOTE:
-48642-C10	CAPACITOR, fixed: 12/31/35 NT-48642 w/2,000 mmf; temp coef ltr C.	RB48A221 16040		16-C-31803-2418				CD CAW	4LT-22020 1446LST	CAY CAY CAY CAY	7406466-6 T-7609856-2 T-7605847-1 T-7606591-12	GP-3(2) GP-4(2) TCE(2) TCE-1(2) TCE-2(2).

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-204

RESTRICTED

RESTRICTED

SHEET 48 - 205

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48643	CAPACITOR, fixed: 12/31/35 mica; 10,000 mf; 1200 vdcw, 2500 vdc; case 1 1/4" lg x 1 1/8" wd x 29/64" thk max; molded low-loss bakelite case; two lug term w/two 0.173" diam holes 1 3/4" c to c; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 JAN-C-5										
-48643-A10	CA ACITOR, fixed: 12/31/35 NT-48643 w/10,000 mf p/m 10%; temp coef ltr A. NOTE: TCE; TCE-1; TCE-2.	RE48A221 JAN-C-5	CM50A103K	16-C-33623-3165				CAW CD CBL	1446 4-21010	CAY CAY CR CAY CAY	T-7406466-3 E80-609852-1 35-5010 T-7609856-10 M-7406466-7 T-7606591-10	GP-1(6) GP-3 GP-4 SG(10) SG-1(8) SG-2S(8)
-48643-A20	CAPACITOR, fixed: 12/31/35 NT-48643 w/10,000 mf p/m 20%; temp coef ltr A.	RE48A221 JAN-C-5	CM50A103M	16-C-33628-5695	N16-C-10503-500		3DA10-167.1	CAN	H-2110	CG	K-8167086AA rev2	TBS-8
-48643-B2	CA ACITOR, fixed: 12/31/35 NT-48643 w/10,000 mf p/m 2%; temp coef ltr B.	RE 8A221 JAN-C-5	CM50B103G	16-C-33613-1210	N16-C-10504-6			CD CAW CSL CAN	4L 1445LS XQBW HL	CW CG	ESA-608986 K-35292-1rev3	SC-3
-48643-B10	CAPACITOR, fixed: 12/31/35 NT-48643 w/10,000 mf p/m 10%; temp coef ltr B. NOTE: WAB; WCA (6); WCA-1 (6); WDA (5); WDA-1 (5).	RE48A221 JAN-C-5	CM50B103K	16-C-33623-3170	N16-C-10504-7	R16-C-10504-5		CD CD CD	4L 4-1251-LL 4ALS-21-010	CW CG CBM	E80-611146-1 7761328-2 744-105	GO-1(3) GO-2(3) TBO(2) TBO-1(2)
-48643-B20	CAPACITOR, fixed: 12/31/35 NT-48643 w/10,000 mf p/m 20%; temp coef ltr B. NOTE: TBS-3; TBS-4; TBS-5; TCU (4).	RE48A221 JAN-C-5	CM50B103M	16-C-33628-5650	N16-C-10504-12	R16-C-10504-20-500		CD CG CG	4L V-5835319AA Model F	COL CRV	910 1107 40 M-427877-78	TBS TBS-1 TBS-2
-48644	CAPACITOR, fixed: 12/31/35 mica; 4000 mf; 2500 vdcw, 5000 vdc; case 1 1/4" lg x 1 1/8" wd x 29/64" thk max; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 JAN-C-5										Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-205

RESTRICTED

RESTRICTED

SHEET 48 - 206

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48644-A10	CAPACITOR, fixed: NT-48644 w/4,000 mmf p/m 10%; temp coef ltr A.	12/31/35 RE48A221 JAN-C-5	CM50A402K	16-C-32463-2973	N16-C-10379-1			CD CAN	4-52040 H-52408	CRP	35-5042	SC-1(2) SC-26(2)
-48644-B2	CAPACITOR, fixed: HT-48644 w/4,000 mmf p/m 2%; temp coef ltr B.	12/31/35 RE48A221 JAN-C-5	CM50B402G	16-C-32453-101A				CD	4L	CW	ESA-608996 Iss 1	
-48644-B10	CAPACITOR, fixed: NT-48644 w/4,000 mmf p/m 10%; temp coef ltr B.	12/31/35 RE48A221 JAN-C-5	CM50B402K	16-C-32463-2973	N16-C-10379-1	R16-C-10396		CD CD	4L6-22040 4L6-12050	CW CW CG CW	ES-611146-1 ES0-609852-1 P-7762925-46rev0 ES-682066-64	GP-1(11) GO-1(2) GO-2(2) SC-3 SEE NOTE:
-48645	CAPACITOR, fixed: mica; 1000 muf; 600 vdcw, 1000 vdc; case 1 1/4" lg x 1 1/8" wd x 11/32" thk; molten bakelite case; two lug terminals w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	12/31/35 RE48A221 16C40										
-48645-A2	CAPACITOR, fixed: NT-48645 w/1,000 mmf p/m 2%; temp coef ltr A.	12/31/35 RE48A221 16 40		16-C-31080-3391				CD	4-12010	CRR	A13753-B	LD-4(2)
-48645-A10	CAPACITOR, fixed: NT-48645 w/1,000 mmf p/m 10%; temp coef ltr A.	12/31/35 RE48A221 16C40		16-C-31090-5351				CD CD CAW	4-12010 4S 1445-A	CW CDE	ES0-609852-1 2427-1	GP-1 LP LP-1 SEE NOTE:
-48645-B2	CAPACITOR, fixed: NT-48645 w/1,000 mmf p/m 2%; temp coef ltr B.	12/31/35 RE48A221 16C40		16-C-31080-3396	N16-C-10087-62			CD	4L	CG	P7762925-34rev0	TBX RBD
-48645-B5	CAPACITOR, fixed: NT-48645 w/1,000 mmf p/m 5%; temp coef ltr B.	12/31/35 RE48A221 16C40		16-C-31085-4876	N16-C-10087-75		3DA1-106.1	CD CAN	4LSE-12010 HL-10	COL	910W210D-J	TCA-1(3) TCB-1(4) SEE NOTE:
-48645-B10	CAPACITOR, fixed: NT-48645 w/1,000 mmf p/m 10%; temp coef ltr B.	12/31/45 RE48A221 16C40		16-C-31090-5356	N16-C-10088			CSL CD CAW	IQBW.6-21 4L6-12010 1445E	CGQ CRR CBM CAY CDE CW	B"00-740A A26111-P 744-639 7608226-41 S-2365-1	LM-2 LM-4 LM-4a LM-5 LM-6 LM-7 SEE NOTE:
NOTE: SK-1 (2); SK-2; MK-16 (2); MK-18 (2); MK-19 (2); MK-27 (2); MK-28 (2); MK-29 Mod 2 (2); MK-34 Mod 2 (4); MK-34 Mod 3; MK-34 Mod 4.												
NOTE: LP-2; LP-3; LP-4; LR; LR-1; LR-2; LR-3; YB-2 (2); YF (2).												
NOTE: TCB-2 (3); TCC-1 (7); TCC-3 (6); TCC-4 (6).												
NOTE: LM-15; LM-16; LM-17; TBX (2); TBX-4 (2); TBX-4a (2); TBX-5 (2); TBE; MK-18.												

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-206

RESTRICTED

RESTRICTED

SHEET 48 - 207

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48646	CAPACITOR, fixed: mica; 80 mmf; 5,000 vdcw max, 2 amp at 3,000 kc, 0.9 amp at 1,000 kc, 0.3 amp at 300 kc, 0.1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	12/31/35 RE48A131 16C40										
-48646-A5	CAPACITOR, fixed: NT-48646 w/80 mmf p/m 5%; temp coef ltr A.	12/31/35 RE48A131 16C40		16-C-28159-4318				CD	PL-470-6			
-48646-B5	CAPACITOR, fixed: NT-48646 w/80 mmf p/m 5%; temp coef ltr B.	12/31/35 RE48A131 16C40		16-C-28159-4328	N16-C-9922-18	R16-C-9922		CW CD	D-96159 PL-470-6	CW CW CG	ESA-608987 1ea1 ESO-609850-4 P7762757-3	GP-1 RBD TCX
-48646-C5	CAPACITOR, fixed: NT-48646 w/80 mmf p/m 5%; temp coef ltr C; RSW immersion.	12/31/35 RE48A131 16C40		16-C-28159-4338				CD	PL-4706LS			
-48647	CAPACITOR, fixed: paper dielectric; two sect; 1.5 mf A sect, 1 mf B sect, plus 10 minus 3% ea sect; 650 vdcw A sect, 250 vdcw B sect; ES metal can; case 1 21/32" lg x 1 1/2" wd x 3 7/8" h o/a; oil impr and filled; three stand-off term 7/8" h located on top on 1 3/16" x 3/4" mtg/c; no int gnd connections; one 0.164"-32 thd mtg stud on top.	12/31/35 RE48A209 RE13A488										GP-1
-48647-15	CAPACITOR, fixed: NT-48647 w/1.5 mf "A" sect. 1 mf "B" sect p/m 15%.	12/31/35 RE48A209 RE13A488		16-C-53886-8205		R16-C-11383		CW	D-98545	CW CW	ESA-608993 1ea3 ESO-609850-3	
-48648	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 650 vdcw; ES metal can; case 1 21/32" lg x 1 1/2" wd x 3 29/32" h o/a; oil filled; two stand-off type term 7/8" h located on top spaced 3/4" c to c; no int gnd connections; two 7/16" lg #4-32 thd mtg studs 1" c to c on top of case.	12/31/35 RE48A210 RE13A488		16-C-49178-2930				CW	288A			GP-1
-48648-15	CAPACITOR, fixed: NT-48648 w/2 mf p/m 15%.	12/31/35 RE48A210 RE13A488		16-C-49215-9480				CW	288A	CW CW CW	IA-700372 1ea 11 ESA-609990 1ea 1 ESO-609850-2	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-207

RESTRICTED

RESTRICTED

SHEET 48 - 208

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	ES O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	COM. TRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48649	CAPACITOR, fixed: 12/31/35 paper dielectric; 700,000 mmf plus 10 minus 3%; 250 vdcw, 800v DC test; ES metal can; case 2 1/4" lg x 1 1/16" w x 2 1/4" wd; vegetable oil filled and impr; two forked lug term on top; no int gnd connections; mtg strap w/two 5/32" diam holes on 2 11/16" mtg/c.	RE48A161 RE13A488										
-48649-15	CAPACITOR, fixed: 12/31/35 NT-48649 w/700,000 mmf p/m 15%.	RE48A161 RE13A488		16-C-48071-5621				CW	D-97277	CW CW	ES0-609850-1 ESA-609024 10a1	GP-1
-48650	CAPACITOR, fixed: 12/31/35 mica; 125 mmf; 1250 vdcw; case 1 7/32" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug term 5/8" lg spaced 7/16" c to c on top; two mtg ft at bottom ea w/slot 5/32" wd, one located 13/64" in back of case ctr, one 13/64" in front slot ctr lines 1 9/32" apart.	RE48A214 16C40										
-48650-A5	CAPACITOR, fixed: 12/31/35 NT-48650 w/125 mmf p/m 5%; temp coef 1tr A.	RE48A214 16C40		16-C-28791-2930								
-48650-A10	CAPACITOR, fixed: 12/31/35 NT-48650 w/125 mmf p/m 10%; temp coef 1tr A.	RE48A214 16C40		16-C-28796-3410				CW	D-97408	CW CW	ES0-609851-3 ESA-609891a1a2	GP-1
-48651	CAPACITOR, fixed: 12/31/35 mica; 25 mmf; 1250 vdcw; case 1 7/32" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug term 5/8" lg 7/16" c to c on top; two mtg ft at bottom, w/slot 5/32" wd, one slot located 13/64" in back of case ctr, one 13/64" in front, slot ctr lines 1 9/32" apart.	RE48A214 16C40										
-48651-A5	CAPACITOR, fixed: 12/31/35 NT-48651 w/25 mmf p/m 5%; temp coef 1tr A.	RE48A214 16C40		16-C-26944-7933								
-48651-A10	CAPACITOR, fixed: 12/31/35 NT-48651 w/25 mmf p/m 10%; temp coef 1tr A.	RE48A214 16C40		16-C-26949-8413								GP-1(2)
-48651-A20	CAPACITOR, fixed: 12/31/35 NT-48651 w/25 mmf p/m 20%; temp coef 1tr A.	RE48A484 16C40		16-C-26955-1800				CW	D-7433	CW	ES0-609851-3	
-48652	CAPACITOR, fixed: 12/31/35 mica; 1250 vdcw; case 1 7/32" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug term 5/8" lg 7/16" c to c on top; two mtg ft at bottom ea w/slot 5/32" wd, one located 13/64" in back of case ctr one 13/64" in front, slot ctr lines 1 9/32" apart.	RE48A214 16C40										
-48652-A5	CAPACITOR, fixed: 12/31/35 NT-48652 w/50 mmf p/m 5%; temp coef 1tr A.	RE48A214 16C40		16-C-27630-6333								
-48652-A10	CAPACITOR, fixed: 12/31/35 NT-48652 w/50 mmf p/m 10%; temp coef 1tr A.	RE48A214 16C40		16-C-27635-6813				CW	D-97434	CW CW	ES0-609851-3 ESA-608980 10a3	GP-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-208

RESTRICTED

RESTRICTED

SHEET 48 - 209

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48653	CAPACITOR, fixed: 12/31/35 mica; 100 mmf; 1250 vdcw max, 2500v AC test at 60 cyc; case 1 7/32" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug term 5/8" lg 7/16" c to c on top; two mtg ft at bottom, ea w/ slot 5/32" wd, one located 13/64" in back of case ctr, one 13/64" in front, slot ctr lines 1 9/32" apart.	RE48A214 16C40										
-48653-A5	CAPACITOR, fixed: 12/31/35 NT-48653 w/ 100 mmf p/m 5%; temp coef ltr A.	RE48A214 16C40		16-C-28553-8330								
-48653-A10	CAPACITOR, fixed: 12/31/35 NT-48653 w/ 100 mmf p/m 10%; temp coef ltr A.	RE48A214 16C40		16-C-28558-8810				CW	D-97435	CW	ES0-609851-3 ESA-608989 1ea3	GP-1
-48654	CAPACITOR, fixed: 12/31/35 mica; 250 mmf; 1250 vdcw, 2500v AC test at 60 cyc; case 1 7/32" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug term 5/8" lg 7/16" c to c on top; two mtg ft at bottom, ea w/ slot 5/32" wd, one located 13/64" in back of case ctr, one 13/64" in front, slot ctr lines 1 9/32" apart.	RE48A214 16C40										
-48654-A5	CAPACITOR, fixed: 12/31/35 NT-48654 w/ 250 mmf p/m 5%; temp coef ltr A.	RE48A214 16C40		16-C-29477-1320								
-48654-A10	CAPACITOR, fixed: 12/31/35 NT-48654 w/ 250 mmf p/m 10%; temp coef ltr A.	RE48A214 16C40		16-C-29482-1800				CW	D-97431	CW	ES0-609851-3 ESA-608989 1ea3	GP-1
-48655	CAPACITOR, fixed: 12/31/35 mica; 500 mmf; 1250 vdcw, 2500v AC test at 60 cyc; case 1 7/32" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug terms 5/8" lg 7/16" c to c on top; two mtg ft at bottom ea w/ slot 5/32" wd, one located 13/64" in back of case ctr, one 13/64" in front, slots ctr lines 1 9/32" apart.	RE48A214 16C40										
-48655-A5	CAPACITOR, fixed: 12/31/35 NT-48655 w/ 500 mmf p/m 5%; temp coef ltr A.	RE48A214 16C40		16-C-30162-8733								
-48655-A10	CAPACITOR, fixed: 12/31/35 NT-48655 w/ 500 mmf p/m 10%; temp coef ltr A.	RE48A214 16C40		16-C-30167-9213				CW	D-97438	CW	ES0-609851-3 ESA-608989 1ea3	GP-1(3)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-209

RESTRICTED

RESTRICTED

SHEET 48 - 210

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CW-TRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48656	CAPACITOR, fixed: mica; 150 mmf; 1250 vdcw, 2500v AC test at 60 cyc; case 1 7/37" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug term 5/8" lg 7/16" c to c on top; two mtg ft at botton, ea w/ slot 5/32" wd, one located 13/64" in back of case ctr, one 13/64" in front, slot ctr lines 1 9/32" apart.	12/31/35 RE48A214 16C40										
-48656-A10	CAPACITOR, fixed: NT-48656 w/150 mmf p/m 10%; temp coef 1tr A.	12/31/35 RE48A214 16C40		16-C-26980-9214				CW	D-97590	CW CW	ESA-608989 1883 ESA-608851-3	GP-1
-48657	CAPACITOR, fixed: mica; 1000 mmf; 1250 vdcw, 2500v AC test at 60 cyc; case 1 27/32" lg x 1 3/32" wd x 2 1/32" h; sheet metal case; two lug term 15/32" lg on top; two mtg ft at botton en w/ slot 5/32" wd, one located 13/64" in back of case ctr, one 13/64" in front, slot ctr lines 27/32" apart.	12/31/35 RE48A214 16C40										
-48657-A10	CAPACITOR, fixed: NT-48657 w/1,000 mmf p/m 10%; temp coef 1tr A.	12/31/35 RE48A214 16C40		16-C-31091-2400				CW	D-97439	CW CW	ESO-609850-5 ESA-608788 1881	GP-1
-48658	CAPACITOR, fixed: paper dielectric; 2.3 mf plus 10 minus 3%; 1,500 vdcw; HS metal can; case 3 23/32" h x 4 15/16" wd x 1 1/2" dia; mineral oil impr and filled; two stud and nut term on por pillars 7/8" h x 1" c to c on top ctr line; no int gnd connections; two #8-32 thd mtg studs 3" c to c on top ctr line.	12/31/35 RE48A211 RE13A488		16-C-49331-2810				CW	D-96963			
-48658-15	CAPACITOR, fixed: NT-48658 w/2.3 mf p/m 10%.	12/31/35 RE48A211 RE13A488		16-C-49331-3010				CW	D-96963	CW CW	ESO-609851-1 ESA-608991 1881	GP-1
-48659	CAPACITOR, fixed: paper dielectric; four sect; 2.5 mf/2 mf/1 mf/500,000 mmf plus 10 minus 3% ea sect; 250 vdcw ea sect; 800v test; HS metal can; case 4 15/16" lg x 1 1/2" wd x 3 5/8" h o/a; oil filled; five solder lug term located on bottom of case, spaced 5/8" c to c; no int gnd connections; two thd mtg studs 7/16" h on bottom 4" c to c.	12/31/35 RE48A196 RE13A488		16-C-54851-9914				CW	D-98778	CW CW	ESO-609851-2 ESL-620143	GP-1
-48660	CAPACITOR, fixed: vacuum dielectric; 31 mmf p/m 5%; 6 amp at 9000v; 4 5/8" lg x 1 1/4" diam o/a glass case w/metal ends; two 1/4" lg x 1/4" diam axial term; mts w/term slipped into mtg clips; 1/2" lg exhaust pip 1" from end.	1/20/36		16-C-56769-7481				CRV CRV	K-35866 case 364			GP GP-2

SHEET 48-210

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 211

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48661	CAPACITOR, fixed: 1/20/36 paper dielectric; 1.75 mf plus 10 minus 3%; 50 vdcv, 5 vacv; HS metal can; case 1 7/8" h x 1 3/8" wd x 3/4" d o/a; two stud term 1/2" h located on top, spaced 5/8" c to c; no int gnd connections; bkt mtg not supplied.	RE48A110 RE48A488		16-C-49072-4474	R16-C-11458-1	R16-C-11451	3DK9001675	CRV	72053-510	CRV	P-720555-10 alt 10	ATB(2) ATA thru ATA-3
-48661-10	CAPACITOR, fixed: 1/20/36 NT-48661 w/1.75 mf p/m 10%.	RE48A110 RE13A488		16-C-49093-4474		R16-C-11452		CRV	72053-560	CRV	P-720555-60 alt 10	
-48661-20	CAPACITOR, fixed: 1/20/36 NT-48661 w/1.75 mf p/m 20%.	RE13A488 RE48A110		16-C-49127-3139						CRV	77094-3	GP(2) GP-2(2)
-48662	CAPACITOR, fixed: 1/22/36 paper dielectric; 100,000 mmf plus 10 minus 3%; 1000 vdcv; HS metal case; 1 13/16" lg x 1" wd x 3/4" h; oil filled; two screw term 5/16" h on top 1/2" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/ bottom w/ 3/16" diam mtg holes spaced 2 1/8" c to c; superseded by NT-48662-A.	RE13A488		16-C-45759-7102								TBM TBM
-48662-A	CAPACITOR, fixed: 11/23/36 paper dielectric; 100,000 mmf plus 10 minus 3%; 1000 vdcv; HS metal can; case 1 13/16" lg x 1" wd x 3/4" h o/a; oil filled; two screw type term 5/16" h on top, spaced 1/2" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A128		16-C-45759-7097								
-48662-A10	CAPACITOR, fixed: 11/23/36 NT-48662-A w/100,000 mmf p/m 10%.	RE13A488 RE48A128		16-C-45780-7097	N16-C-11310-16		3DA100-397 3DA100-398	CSF		CHZ	CO-829	YJ(3) thru YJ-2(3)
-48663	CAPACITOR, fixed: 2/17/36 mica; 350 mmf; 1250 vdcv, 2500v AC test at 60 cyc; case 1 7/32" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug term 5/8" lg, 7/16" c to c on top; two mtg ft at bottom, ea w/ slot 5/32" wd, one located 13/64" in back of case ctr, one 13/64" in front, slot ctr lines 1 9/32" apart.	RE48A214 16C40										
-48663-A5	CAPACITOR, fixed: 2/17/36 NT-48663 w/350 mmf p/m 5%; temp coef 1tr A.	RE48A214 16C40		16-C-29793-6130								
-48663-A10	CAPACITOR, fixed: 2/17/36 NT-48663 w/350 mmf p/m 10%; temp coef 1tr A.	RE48A214 16C40		16-C-29798-6610				CW	D-98784	CW CW	ESO-609851-3 ESA-60989 1ee 3	GP-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-211

RESTRICTED

RESTRICTED

SHEET 48 - 212

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48664	CAPACITOR, fixed: 3/10/36 paper dielectric; 5 m ² plus 10 minus 3%; 600 vdcw; MS metal can; case 1 13/16" lg x 1 1/16" wd x 4 3/4" h; vegetable oil impr and filled; two screw type term 1/2" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/3/16" diam mtg hole 2 1/4" c to c.	RE48A147 RE13A488		16-C-50316-3109				CD	TDF-6050	CAY	M-7406055	
-48665	CAPACITOR, fixed: 6/17/36 mica; 500 mmf; 600 vdcw, 1000 vdot; case 1 1/4" lg x 1 1/8" wd x 23/64" thk; molded bakelite case; two lug term ea w/ 0.173" diam holes; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48665-A10	CAPACITOR, fixed: 6/17/36 NT-48665 w/500 mmf p/m 10%; temp coef ltr A. NOTE: LP(3) thru LP-4(3); LR(5) thru LR-3(5).	RE48A221 16C40		16-C-30167-3351				CD	4-13050	CRR	A-13753-7	LD-3 LD-4 SEE NOTE
-48665-B2	CAPACITOR, fixed: 6/17/36 NT-48665 w/500 mmf p/m 2%; temp coef ltr B. NOTE: SK-3; SP-1M; SX.	RE48A221 16C40		16-C-30157-1396	N16-C-10018-6		3D9500-178	CD CG CAN	4LS-13050 C	CW CG	FSO-611146-1rev4 P-7762925-28rev0	SC-2 thru SC-4 SK-2 SEE NOTE
-48665-B10	CAPACITOR, fixed: 6/17/36 NT-48665 w/500 mmf p/m 10%; temp coef ltr B.	RE48A221 16C40		16-C-30167-3356	N16-C-10018-10		3D9500-28	CD	4LS-13050			
-48665-B20	CAPACITOR, fixed: 6/17/36 NT-48665 w/500 mmf p/m 20%; temp coef ltr B.	RE48A221 16C40		16-C-30172-5836	N16-C-10018-12			CD	4LS-13050			
-48666	CAPACITOR, fixed: 6/17/36 mica; 100 mmf, 1000 vdot; case 1 1/4" lg x 1 1/8" wd x 1 1/32" d; molded low-loss bakelite case; two lug term ea w/ one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48666-A10	CAPACITOR, fixed: 6/17/36 NT-48666 w/100 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-28558-2951				CD	4-13010			LD-3 LR thru LR-3
-48666-B2	CAPACITOR, fixed: 6/17/36 NT-48666 w/100 mmf p/m 2%; temp coef ltr B.	RE48A221 16C40		16-C-28547-9995			3D9100-196	CD GSL	4L-13010	CHZ CGQ	CO-751 B-CO-751	TBX-4 TBX-4a TBX-5
-48666-B5	CAPACITOR, FIXED: 1/12/49 Navy Type 48666 w/100 mmf p/m %; temp coef letter B.			16-C-28553-2477								AN/FGC-1 AN/FGC-1K
-48666-B10	CAPACITOR, fixed: 6/17/36 NT-48666 w/100 mmf p/m 10%; temp coef ltr B.	RE48A221 16C40		16-C-28558-2956	N16-C-9924-16			CD	4L-13010	CRR	A1728-15	OH OH-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-212

RESTRICTED

RESTRICTED

SHEET 48 - 213

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48667	CAPACITOR, FIXED: mica dielectric; 40 mmf; 600 vdcw; 1 1/4" lg x 1 1/8" wd x 1 1/32" h; molded low loss phenolic body; 2 axial tab terms; 2 mtg holes on 1 side 0.144" diam x 1 5/16" mtg/c.	6/17/36 RE48A221 16C40										
-48667-A10	CAPACITOR, fixed: NT-48667 w/40 mmf p/m 10%; temp coef ltr A.	6/17/36 RE48A221 16C40		16-C-27397-6351				CD	4L-14040			LD-3
-48667-B2	CAPACITOR, fixed: NT-48667 w/40 mmf p/m 2%; temp coef ltr B.	6/17/36 RE48A221 16C40		16-C-27387-4396	N16-C-9843-54			CD CAN	4L-14040	COL	T-7606408-65	TCB-2
-48667-B5	CAPACITOR, fixed: NT-48667 w/40 mmf p/m 5%; temp coef ltr B.	6/17/36 RE48A221 16C40		16-C-27392-5876	N16-C-9843-56			CD CAW	4L-14040	CAY	7608226-58	TDE thru TDE-3
-48667-B10	CAPACITOR, FIXED: Navy Type 48667 w/40 mmf p/m 10%; temp coef ltr B.	5/10/48 RE48A221 16C40		16-C-27397-6361				CD	4L-14040			
-48667-B20	CAPACITOR, fixed: NT-48667 w/40 mmf p/m 20%; temp coef ltr B.	6/17/36 RE48A221 16C40		16-C-27402-8836	N16-C-9843-59			CD	4L-14040			
-48668	CAPACITOR, FIXED: mica; 2000 mmf; 600 vdcw, 1000 vdcct; case 1 1/4" lg x 1 1/8" wd x 23/64" thk; molded low loss bakelite case; 2 lug term ea w/one 0.173" diam hole; 2 mtg holes in case 0.144" diam 1 5/16" c to c.	6/17/36 RE48A221 16C40										
-48668-A10	CAPACITOR, fixed: NT-48668 w/2,000 mmf p/m 10%; temp coef ltr A.	6/17/36 RE48A221 16C40		16-C-31802-7151				CD	4L-12020	CRR	A1728-17	LD-3
-48668-B2	CAPACITOR, fixed: NT-48668 w/2,000 mmf p/m 2%; temp coef ltr B. NOTE: SX-3; SP-1M; SX-1; WC-1; VG; VG-1; VG-3.	6/17/36 RE48A221 16C40		16-C-31792-5196	N16-C-10240-90		3DAZ-183	CD CG CAN C	4LS-12020	CG	P-7762925-37rev0	SC-2 thru SC-4 SK-2 SEE NOTE
-48668-B5	CAPACITOR, FIXED: Navy Type 48668 w/2000 mmf p/m 5%; temp coef ltr B.	1/12/49 RE48A221 16C40		16-C-31797-6677								
-48668-B10	CAPACITOR, fixed: NT-48668 w/2,000 mmf p/m 10%; temp coef ltr B.	6/17/36 RE48A221 16C40		16-C-31802-7156	N16-C-10240-102		3DAZ-35	CD CSL CAW	4LS-12020 XQBW6-31	CGQ CAY CAG	B-00-751 7608226-42	OH OH-1 TBX-8 TDE
-48668-B20	CAPACITOR, fixed: NT-48668 w/2,000 mmf p/m 20%; temp coef ltr B. NO E: MK-29 Mod2(4); MK-34 Mod2(4).	6/17/36 RE48A221 16C40		16-C-31807-9636	N16-C-10241-12			CD	4LS-12020	CW		MK-19(4) MK-28(4) SEE NOTE
-48668-C2	CAPACITOR, fixed: NT-48668 w/2,000 mmf p/m 2%; temp coef ltr C.	6/17/36 RE48A221 16C40		16-C-31792-5401	N16-C-10240-92			CD	4LTS-12020			LR thru LR-3

SHEET 48-213

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 214

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48669	CAPACITOR, fixed: 6/17/36 mica; 350 mmf; 600 vdcw, 100 vdet; case 1 1/4" lg x 1 1/8" wd x 11/32" d; molded bakelite case; two lug terms ea w/ one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	RE48A221 16C40										
-48669-A10	CAPACITOR, fixed: 6/17/36 NT-48669 w/350 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-29797-9751				CD	4-13035			LD-3
-48670	CAPACITOR, fixed: 6/17/36 paper dielectric; 1 mf plus 10 minus 3%; 300 vdcw; BS metal can; case 1 7/8" lg x 3/4" wd x 1 3/4" h; oil impr and filled; two screw type term 1/4" h located on top 7/8" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/0.140" diam mtg hole, 2 1/8" c to c.	RE13A488 RE48A147		16-C-48791-7886	N16-C-11384-21			CD	VC-571			
-48671	CAPACITOR, variable: 6/22/36 air; plate meshing type single sect; 2 to 25 mmf; SLF; 0.055" air gap; 1 3/4" wd x 2 1/2" h shaft 2 1/4" lg bushing; rounded shaft adj; nine polished aluminum plates; 270 deg rotation clockwise; isolantite ins; lug term; single hole mtg by mtg bushing.			16-C-59165-4901				CRA	SE-25			
-48672	CAPACITOR, fixed 6/24/36 mica; 6000 mmf; 300 vdcw; case 1 1/4" lg x 5/8" wd x 1/4" thk; molded bakelite case; two solder lug term; two 9/64" diam holes in case on 1 1/4" mtg/c.	RE48A217 16C40										
-48672-A5	CAPACITOR, fixed: 6/24/36 T-48672 w/6,000 mmf p/m 5%; temp coef ltr A.	RE48A217 16C40		16-C-32852-4849			3DA6-1	CAW	1461	CBY	P-91chg0	BU-5 ARA ATA
-48672-A20	CAPACITOR, fixed: 6/24/36 NT-48672 w/6,000 mmf p/m 20%; temp coef ltr A.	RE48A217 16C40		16-C-32862-8708	16-C-10436-36	R16-C-10436-30		CAW	1461			
-48672-B10	CAPACITOR, fixed: 6/24/36 NT-48672 w/6,000 mmf p/m 10%; temp coef ltr B.	RE48A217 16C40		16-C-32857-6234				CAW	1461	CBY	P91	GF-11(2) RU-16(2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-214

RESTRICTED

RESTRICTED

SHEET 48 - 215

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48673	CAPACITOR, fixed; mica; 250 mmf; 500 vdcw, 1000v DC test; case 21/32" lg x 21/32" wd x 3/16" thk; molded bakelite case; two solder lug term ea w/one 5/32" diam hole 1 5/16" c to c. 6/24/36	RE48A218 16C40										
-48673-A5	CAPACITOR, fixed; NT-48673 w/250 mmf p/m 5%; temp coef ltr A. 6/24/36	RE48A218 16C40		16-C-29476-3059				CAW	1465	CBY	P-221	FU-5 GF-11 RJ-16
-48673-A10	CAPACITOR, fixed; NT-48673 w/250 mmf p/m 10%; temp coef ltr A. 6/24/36	RE48A218 16C40		16-C-29481-3539		R16-C-9975-125		CAW	1465			LP(2)thru LP-4(2)
-48674	CAPACITOR, fixed; mica; 100 mmf; 500 vdcw; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads; mtg by term. 6/24/36	RE48A148										
-48674-A5	CAPACITOR, fixed; NT-48674 w/100 mmf p/m 5%; temp coef ltr A. 6/24/36 NOTE: RBG-2 (2); MK-28 (6); MK-29 Mod 2 (3).	RE48A148 JAN-C-5	CM20A101J	16-C-28553-1191		R16-C-9924-55	3K2010112	CD CAW CSL CMR CD	5W 1468 MO 0 5W5T1	CHC CBM CBY CW	6172 744-406 P-325chg0	FU-5 SU(3) SU-1(3) RBG(2) RBG-1 (2) SEE NOTE
-48674-A10	CAPACITOR, fixed; NT-48674 w/100 mmf p/m 10%; temp coef ltr A. 6/24/36 NOTE: SG-1; SG-25; SO-2; SO-3 (2); SO-4 (7); SO-7M; S-7N; SU-1; RAO-2; RAO-6; RAO-7; RAO-9; RBE-1; RBR-2; RBH-3; RBL-1 (7); RER.	RE48A148 JAN-C-5	CM20A101K	16-C-28558-1671	N16-C-9923-40	R 16-C-9924-59	3K2010111	CMR CAW CSL CD	0 1468 MO-1416-10 5W	CHZ CNA CPN CRP CBM	LO-633issF D-774rev0 C1055 35-5021 744-568	ABK(3) ABK-1(3) thru ABK-7(3) SG SEE NOTE
-48674-A20	CAPACITOR, fixed; NT-48674 w/100 mmf p/m 20%; temp coef ltr A. 6/24/36	RE48A148 JAN-C-5	CM20A101M	16-C-28563-4151	N16-C-9923-39		3K2010114	CD CAW CSL CMR	5W5T1 1468 MO 0	CFT		DAU(2) DAU-1(2)
-48674-B2	CAPACITOR, fixed; NT-48674 w/100 mmf p/m 2%; temp coef ltr B. 6/24/36	RE48A148 JAN-C-5	CM20B101G	16-C-28547-8716	N16-C-9923-32	R16-C-9924-56		CD CAW CSL CMR	5WL 1468L MOB OXM	CRR CRR CAY	B6992alt0 C56734-101 7606437-7rev16	RAP TBY (2) TBY-1 (2) TBY-2 (2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-215

RESTRICTED

RESTRICTED

SHEET 48 - 216

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48674-B5	CAPACITOR, fixed: 6/24/36 NT-48674 w/100 mmf p/m 5%; temp coef ltr B. NOTE: TCD(5); ZB-2.	RE48A148 JAN-C-5	CM20B101J	16-C-28553-1196	N16-C-9923-33	R16-C-9924-56-40	3K2010122	CD CAW CSL CMR CMF	5WL 1468L MOB-1416-5 OXM 503M	CPT CRR CG CZR	A293-3altA K-27J362-124rev6 22G185	DAK(6) RAP(5) SC-2 SO-7M(7) SO-7N(7) SEE NOTE
-48674-B10	CAPACITOR, fixed: 6/24/36 NT-48674 w/100 mmf p/m 10%; temp coef ltr B. NOTE: SB; SC-2(3); SD-1(6); SJ-1(3); TBX-8; WEA-1(5); AN/UPM-1; AN/UPM-1B; MK-1 6(5); MK-28(5); GQ.	RE48A148 JAN-C-5	CM20B101K	16-C-28558-1676	N16-C-9923-35-4 N16-C-9923-40	R16-C-9924-60	3K2010121	CER CD CSL CAN CAW CMR	M2K100 5WLS-13010 MOBW-1416-10 K-1310 1468-LS OXM	CHZ CW CRB CRV CBM CHZ CCT CG COQ CDE CBM CW CQA CPT CMF CRV	CO-10521aa0 ES-692527-11aa1 CD-1033-91aaC P-720592-10 744-28 B-CO-613 7608010-27 M-746393-10rev0 CO-725 2806-5 744-277 ES-682032-6 10166-rev1 15-A3018-1 P-720473-6rev19 W303314-343	BL-1 thru BL-6 DAK(9) DAK-1(9) IM-15 OAN(2) OCU(6) QBH(6) QCJ-8 QGA(2) RAB RBC RBS(6) RBM-1(13) thru RBM-5(13) SEE NOTE
-48674-B20	CAPACITOR, fixed: 6/24/36 NT-48674 w/100 mmf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B101M	16-C-28563-4156	N16-C-9924-1	R16-C-9924-105	3K2010124	CD CAW CMR CSL	5WL 1468L OXM MOB	CIA CPT CHE CHZ	D5498.1B-191 RF-4582-1-11aaA CO-769 CO-671	DAG TCS-6(3) YH(2) YH-1(2)
-48674-C2	CAPACITOR, fixed: 6/24/36 NT-48674 w/100 mmf p/m 2%; temp coef ltr C.	RE48A148 JAN-C-5	CM20C101G	16-C-28547-8721	N16-C-9923-35	R16-C-9924-38	3K2010133	CD CAW CSL CMR CMF	5R 1469 MOSCW PO CM20101	CBM	744-723	WFA(9) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-216

RESTRICTED

RESTRICTED

SHEET 48 - 217

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTORS DWG OR PART NO	EQUIPMENT USED IN
-48674-C5	CAPACITOR, fixed: NT-48674 w/100 mmf p/m 5%; temp coef ltr C.	6/24/36 RE48A148 JAN-C-5	CM20C101J	16-C-28553-1201	N16-C-9923-36-5	R16-C-9924-56-500	3K2010132 3K2010152	CD CAW CSL CMR CAN CMF	5R 1469 MOSCW-1416-5 PO E-1310C 503M	COL CZC CRP CZR	912 3103 10rev2 7133 35-5106 22G185	DAB DAB-1 DAB-3 RBO-2 SO(6) SO-2(7) SEE NOTE
-48674-C10	CAPACITOR, fixed: NT-48674 w/100 mmf p/m 10%; temp coef ltr C.	6/24/36 RE48A148 JAN-C-5	CM20C101K	16-C-28558-1681	N16-C-9923-355 N16-C-9923-35-5		3K2010131	CD CAW CSL CMR	5R 1469 MOSCW PO			
-48674-C20	CAPACITOR, fixed: NT-48674 w/100 mmf p/m 20%; temp coef ltr C.	6/24/36 RE48A148 JAN-C-5	CM20C101M	16-C-28553-4161		R16-C-9924-150	3K2010134	CD CAW CSL CMR	5R 1469 MOSCW PO	COL	912 3103 40rev2	
-48674-D2	CAPACITOR, fixed: NT-48674 w/100 mmf p/m 2%; temp coef ltr D.	6/24/36 RE48A148 JAN-C-5	CM20D101G	16-C-28547-8726	N16-C-9923-35	R16-C-9924-40		CD CAW CMR CSL	5R 1469 PO MOSDW	CRR	C-56316-1011seR	
-48674-D3	CAPACITOR, fixed: NT-48674 w/100 mmf p/m 3%; temp coef ltr D.	6/24/36 RE48A148 16040		16-C-28552-2623		R16-C-9924-56-25		CAW CD CMR CER CSL	1469 5RS PO M2K100 MOSDW	CRV	P-720537-2rev19	NMR-1
-48674-D5	CAPACITOR, fixed: NT-48674 w/100 mmf p/m 5%; temp coef ltr D.	6/24/36 RE48A148 JAN-C-5	CM20D101J	16-C-28553-1206	N16-C-9923-36	R16-C-9924-57	3K2010142	CAW CMR CER CD CSL CMF CAN CFW	1469 PO M2K100 5RS MOSDW 603M K-1310 2M	CRV CS CW CJ CG CZC COL CWI CWF CW	P-720538-7rev30 G11-31 ES0-677316-3 106-169 M-7463969-26rev3 7133 912 3103 10 24163 270-117.3R K80-677316-3	ARJ AYA AYA-1 DBE (8) LS IS-1 PF QBC-1 (3) QPO (3) RBO-1 SEE NOTE
-48674-E2	CAPACITOR, FLXED: Navy Type 48674 w/100 mmf p/m 2%; temp coef letter E.	11/4/47		16-C-28547-8731				CMF	603M	CBM	744-822	WFA-1 Con't

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-217

RESTRICTED

RESTRICTED

SHEET 48 - 218

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTORS DWG OR PART NO	EQUIPMENT USED IN
-48674-D10	CAPACITOR, fixed: NT-48674 w/100 mmf p/m 10%; temp coef ltr D. NOTE: MK-16; MK-28(3); MK-29 Mod2(3).	6/24/36 RE48A148 JAN-C-5	CM20D101K	16-C-28558-1686	N16-C-9923-37	R16-C-9924-58		CEB CAW CSL CMR CD	M2K100 1469 MOSDW PO SRS	CRV CG CRV CFN CFN	P-720592rev30 M-7463969-10rev3 W-30314-343 C-1074 C-1095	RAX-1 RCL(9) RBD(2) SJ-1 TCX-2 WEA SEE NOTE
-48674-D20	CAPACITOR, fixed: NT-48674 w/100 mmf p/m 20%; temp coef ltr D.	6/24/36 RE48A148 JAN-C-5	CM20D101M	16-C-28563-4166	N16-C-9923-47			CD CAW CSL	5R 1469 MOSDW			
-48675	CAPACITOR, fixed: mica; 200 mmf; 500 vdcw, 1000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads; mtg by term.	6/24/36 RE48A148 JAN-C-5										
-48675-A5	CAPACITOR, fixed: NT-48675 w/200 mmf p/m 5%; temp coef ltr A.	6/24/36 RE48A148 JAN-C-5	CM20A201J	16-C-29265-2991	N16-C-9967-11		3E2020112	CAW CD CSL CMR CAN	1468 5W MO DO K1320-5	CRP	35-5029	BU-5 SG-1(2) SG-2(2) VF
-48675-A10	CAPACITOR, fixed: NT-48675 w/200 mmf p/m 10%; temp coef ltr A.	6/24/36 RE48A148 JAN-C-5	CM20A201K	16-C-29270-3471				CSL CD CAW CMR CER	MO-1418 5W 1468 1468BT M3K200	CMD CRV CDE	4C4 P-720473-43rev19 2806-3	ARD-1 TB-2(2)
-48675-A20	CAPACITOR, fixed: NT-48675 w/200 mmf p/m 20%; temp coef ltr A.	6/24/36 RE48A148 JAN-C-5	CM20A201M	16-C-29275-5951	N16-C-9967-19		3D327	CD CSL CAW CMR CD	5W5T2 MO-1418 1468 0 5WS	CFT CMD CHK CW	4C4A 3096-6	ARD-2 DAU DAU-1 OBL MK-16
-48675-B2	CAPACITOR, fixed: NT-48675 w/200 mmf p/m 2%; temp coef ltr B.	6/24/36 RE48A148 JAN-C-5	CM20B201G	16-C-29260-1516	N16-C-9967	R16-C-10240-20		CAW CD CSL CMR	1468L 5WL MOB OXM	CRR CRP	B-6992alt0 056304-201	RAP (2)
-48675-B5	CAPACITOR, fixed: NT-48675 w/200 mmf p/m 5%; temp coef ltr B.	6/24/36 RE48A148 JAN-C-5	CM20B201J	16-C-29265-2996	N16-C-9967-9	R16-C-9967-5	2K2020122	CAW CD CSL CMR	1468L 5WL MOB OXM	CRN CG CBM	A-293-11altA K-27J362-131rev9 744-29alt1	WBA(2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-218

RESTRICTED

RESTRICTED

SHEET 48 - 219

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY OWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A B O STOCK NO	SIGNAL CORPS STOCK NO	MFOR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S OWG OR PART NO	EQUIPMENT USED IN
-48675-B10	CAPACITOR, fixed: 6/24/36 NT-48675 w/200 muf p/m 10%; temp coef ltr B. NOTE: QCC (2); QCD (2); QCL-8 (2); QCM-4; QCN-4 (2); WDA-1 (2); WFA (3); WOA (2); YF (2).	RE48A148 JAN-C-5	CM20B20IX	16-C-29270-3476	N16-C-9967-10	R16-C-9968-5	3K2020121	CSL CD CAW CMR CMR CD CER	MOBW-1418 5WLS-13020 1468LS OXM FO 5RS M3K200	CHZ CBM CRB CQA CRV CRP CDE CFT	00-6141000 744-29alt1 CD-1033-11100C 10168rev1 P-720473-7rev19 35-5026	BL-1 BL-6 (4) JK-2B (2) JK-5 JKA-4 LAB (2) LAF (2) OAB SEE NOTE
-48675-B20	CAPACITOR, fixed: 6/24/36 NT-48675 w/200 muf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B20IM	16-C-29275-5956	N16-C-9967-19			CD CMF CAW CSL CMR	5WLS 503-M 1468LS MOB-1418 OXM	CHZ CDU	3-212	BR LO-1 LO-2 LO-3 LO-4
-48675-C5	CAPACITOR, fixed: 6/24/36 NT-48675 w/200 muf p/m 5%; temp coef ltr C.	RE48A148 JAN-C-5	CM20C20IJ	16-C-29265-3001		R16-C-9967-20	3K2020132	CD CAW CSL CMR CMF	5R 1469 MOSOW FO CM12-201	CBM	744-724	WFA
-48675-D2	CAPACITOR, fixed: 6/24/36 NT-48675 w/200 muf p/m 2%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D20IG	16-C-29260-1526	N16-C-9967-1	R16-C-9966-90	3K2020143	CAW CD CSL CMR CER CD	1469 5RLS MOSOW FO M3K-200 SR	CRV CFT CW	P-720537-12rev1 ES-692527-210019	DAU DAU-1 NMB-1(2) SJ-1(2) MX-16 MX-28(2) MX-29 Mod2(2)
-48675-D3	CAPACITOR, fixed: 6/24/36 NT-48675 w/200 muf p/m 3%; temp coef ltr D.	RE48A148 16C40		16-C-29264-4423		R16-C-9967-40		CAW CMR CER CD CSL	1469 FO M3K200 5RS MOSOW	CRV	P-720537-5rev19	Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-219

RESTRICTED

RESTRICTED

SHEET 48 - 220

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USE IN
-48675-D5	CAPACITOR, fixed: NT-48675 w/200 mmf p/m 5%; temp coef ltr D.	6/24/36	RE48A148 JAN-C-5	CM20D201J	16-C-29265-3006	N16-C-9967-11 N16-C-9967-6	R16-C-9967-45	3X2020142	CER MJK200 CAW 1469 CSL MOSDW CMR PO CD 5RS CMF 603-M CSL MOSW-1418	CRV CRV CW CDL CG COQ	P-720538-15rev30 W-303314-345 B-8F-828revD P-7463969-28rev3 B-CO-10002	ARJ DAK(6) DAK-1(6) PF QCJ-8 QCL-7 TBX-8(2) WEA
-48675-D10	CAPACITOR, fixed: NT-48675 w/200 mmf p/m 10%; temp coef ltr D.	6/24/36	RE48A148 JAN-C-5	CM OD201K	16-C-29270-3486	N16-C-9967-13	R16-C-9968-10		CSL MOSDW CD 5R CAW 1469 CMR PO	CRB CG	CD-1034-11 188C M-7463969-12rev3	RAX-1 RED TCX
-48676	CAPACITOR, fixed: mica; 350 mmf; 500 vdcw; case 51/64" lg x 15/32" wd x 7/32" d max dimen; molded bakelite case; two axial wire leads.	6/24/36	RE48A148 JAN-C-5									
-48676-A5	CAPACITOR, fixed: NT-48676 w/350 mmf p/m 5%; temp coef ltr A.	6/24/36	RE48A1 8 JAN-C-5	CM20A351J	16-C-29792-7991				CD 5W CAW 1468 CSL MO CMR 0	CBY CBV	P-389chg0 4514-1-A	RU-5
-48676-A10	CAPACITOR, fixed: NT-48676 w/350 mmf p/m 10%; temp coef ltr A.	6/24/36	RE48A148 JAN-C-5	CM20A351K	16-C-29797-8471				CAW 1468 CD 5W CMR 0 CSL MO	CNA	D-774	RBL-2(2) RBL-2(2) RBL-5(2) RBL-5(2)
-48676-B2	CAPACITOR, fixed: NT-48676 w/350 mmf p/m 2%; temp coef ltr B.	6/24/36	RE48A148 JAN-C-5	CM20B351G	16-C-29787-6516		R16-C-10000-2	3DR9350-9	CD 5WLS CAW 1468LS CSL MOBW CMR OXM	CRR	B6992a1t0	
-48676-B5	CAPACITOR, fixed: NT-48676 w/350 mmf p/m 5%; temp coef ltr B.	6/24/36	RE48A148 JAN-C-5	CM20B351J	16-C-29792-7996		R16-C-10000-5		CD 5WLS CAW 1468LS CSL MOBW CMR OXM			
-48676-B10	CAPACITOR, fixed: NT-48676 w/350 mmf p/m 10%; temp coef ltr B.	6/24/36	RE48A148 JAN-C-5	CM20B351K	16-C-29797-8476	N16-C-9999-80			CAN K-1335 CD 5WLS CAW 1468LS CSL MOBW CMR OXM	CWQ	47X3361eeB	RBL-3(2) RBL-4(2)
												Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-220

RESTRICTED

RESTRICTED

SHEET 48 - 221

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	F S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48676-B20	CAPACITOR, fixed: 6/24/36 NT-48676 w/350 mmf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B351M	16-C-29803-1956	N16-C-9999-81			CD CAW CSL CMR	SWLS 1468LS MOBW ODM			
-48676-C5	CAPACITOR, fixed: 6/24/36 NT-48676 w/350 mmf p/m 5%; temp coef ltr C.	RE48A148 JAN-C-5	CM20C351J	16-C-29792-8001				CAN CD CSL CAW CMR	K-1335C 5RS MOBCW 1469 PO	CZC	7136	RBO-2
-48676-D5	CAPACITOR, fixed: 6/24/36 NT-48676 w/350 mmf p/m 5%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D351J	16-C-29792-8006	N16-C-9999-98			CAW CD CSL CMR	1469 5RS MOGDW PO			
-48676-D10	CAPACITOR, fixed: 6/24/36 NT-48676 w/350 mmf p/m 10%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D351K	16-C-29797-8486	N16-C-9999-100			CAW CD CSL CMR CER	1469 5R MOGDW PO M5E350	CRV CRV	W-303314-284 P-720473-20rev29	QCJ-8 QCL-7 WEA
-48677	CAPACITOR, fixed: 6/24/38 mica; 150 mmf; 500 vdcw; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143										
-48677-A20	CAPACITOR, fixed: 6/24/36 NT-48677 w/150 mmf p/m 20%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A151M	16-C-30172-4639				CD CAW CSL	1W 1467 MW-1217	CBY	P-266chg0	
-48677-B10	CAPACITOR, fixed: 6/24/36 NT-48677 w/150 mmf p/m 10%; temp coef ltr B. NOTE: QCL-4; QCL-5; QCN-2; QCN-3; QCQ; QCQ-1; QCQ-3; QCR; QCR-1; QCR-2; QCS; QCS-1; QCT; QCT-1	RE48A143 JAN-C-5	CM30B151K	16-C-28980-2164	N16-C-9950-44			CD	1WLSP	CBM	744-179	QCJ-5 QCJ-6 SEE N TE:
-48677-C2 1/2	CAPACITOR, fixed: 6/24/36 NT-48677 w/ 150 mmf p/m 2 1/2%; temp coef ltr C.	RE48A143 16040		16-C-28974-2356				CAW	1467L	CRR	B6985 alt 0	
-48677-C10	CAPACITOR, fixed: 6/24/36 NT-48677 w/150 mmf p/m 10%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C151K	16-C-28980-2169				CAN	C160670	CAN	817744alt2	
-48677-D5	CAPACITOR, FIXED: 3/10/48 Navy Type 48677 w/150 mmf p/m 5%; temp coef letter D.			16-C-28975-1695				CD	1RS	CADV	1391	TS-587/U TS-587A/U

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-221

RESTRICTED

RESTRICTED

SHEET 48 - 222

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48678	CAPACITOR, fixed: 6/24/36 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect, 1,200v DC test; HS metal can; case 1 3/4" lg x 7/8" wd x 3/4" h o/a; oil filled; two solder lug term 3/8" h on top, spaced 1" c to c; both sect int grd; two mtg ft 3/8" wd flush w/bottom, w/0.149" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A128		16-C-53104-9245		R16-C-11333		CSF	514			BL-1(2) BL-2(2) BL-3(2) BL-4(3)
-48678-10	CAPACITOR, fixed: 6/24/36 NT-48678 w/100,000 mmf p/m 10%.	RE13A488 RE48A128		16-C-53148-7694	R16-C-11332-6			CSF	514	CW	1572	RU-16(5) GF-11(5)
-48678-15	CAPACITOR, fixed: 6/24/36 NT-48678 w/ 100,000 mmf p/m 15% ea sect.	PE48A128 RE13A488		16-C-53187-4837				CSF	514	CMD CBY CHZ	4C17A 1560-1-B 00-607 rev 0	ARD-2 (2) BL-6
-48679	CAPACITOR, fixed: 6/24/36 paper dielectric; 500,000 mmf minus 10 plus 20%; 300 vdcv; HS metal can; 1 3/4" lg x 7/8" wd x 3/4" h; oil filled; two solder lug term 5/16" h on top spaced 1/2" c to c; no int grd connections; two mtg ft 3/8" wd flush w/ bottom, w/ 0.149" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A128		16-C-47321-9210	R16-C-11344-1562					CBY CBY	1573-1 change 6 1560-1-B	RU-5
-48679-10	CAPACITOR, fixed: 6/24/36 NT-48679 w/500,000 mmf p/m 10%.	RE13A488 RE48A128		16-C-47292-7738						CW	1573	
-48680	CAPACITOR, fixed: 6/24/36 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect, 1200v DC test; HS metal can; case 1 13/16" lg x 1" wd x 3/4" h; oil filled And impr; two solder lug term 5/8" h on bottom of case 1/2" c to c; int grd; two mtg ft ea w/one 3/16" diam holes on 2 1/8" mtg/c; superseded by NT-48680-A.			16-C-53104-9275				CD CBY		CBY CBY	1574-1-C chg 5 1560-1-B	RU-5 GF-11 (4) RU-16(4)
-48680-20	CAPACITOR, fixed: 6/24/36 NT-48680 w/100,000 mmf p/m 20% ea sect; superseded by NT-48680-A20.			16-C-53209-3747				OSL	2529-6	CBY	1560-1-A chg 2	AN/UPM-1(2) AN/UPM-1B (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-222

RESTRICTED

RESTRICTED

SHEET 48 - 223

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGN	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48680-A	CAPACITOR, fixed: paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 600 wdcv, 1200 v DC test; HS metal can; case 1 13/16" lg x 1" wd x 3/4" h o/a; oil impr and filled; two solder lug term 5/16" h on bottom of case 1/2" apart c to c; both sect int gnd; two mtg ears 3/8" wd integral w/bottom of case w/two 3/16" diam mtg holes 2 1/8" c to c.	1/17/41 RE48A138 RE13A488		16-C-53115-6092			3DEA100-186	CSF CSF	2529-4 2529-6	OMD	409	ARD-1
-48680-A10	CAPACITOR, fixed: NT-48680-A w/100,000 mmf p/m 10% ea sect.	1/17/41 RE48A138 RE13A488		16-C-53159-5350			3DA100-110.1	CSF CSF	2529-4 2529-6	CBY	1574-1-C	
-48680-A20	CAPACITOR, fixed: NT-48680-A w/100,000 mmf p/m 20% ea sect.	1/17/41 RE48A138 RE13A488		16-C-53214-7477	N16-C-11332-40			CSF CSF	2529-4 2529-6	CEZ	CO-10621aa0	
-48681	CAPACITOR, fixed: paper dielectric; two sect; 500,000 mmf plus 10 minus 3% ea sect; 300vdcv, ea sect, 800v DC test; HS metal can; case 1 13/16" lg x 7/8" wd x 1 1/2" h o/a; wax impr and filled; two solder lug term 5/16" h on bottom of case 1/2" apart c to c; both sect int gnd; two mtg ears 3/8" wd integral w/bottom of case w/two 3/16" diam mtg holes on 2 1/8" ctr.	6/24/36 RE48A138 RE13A488		16-C-53569-1766	N16-C-11375-122			CBY		CBY CBY	1575-1-C 1368-1-C	RU-5
-48681-10	CAPACITOR, fixed: NT-48681 w/500,000 mmf p/m 10% ea sect.	6/24/36 RE48A138 RE13A488		16-C-53625-4086		R16-C-11369-300		CSF CD	2529-7	CBY CBY CBM CW	1575-1-C 1368-1-C 744-619 1575	GF-11(3) RU-16(3) SU SU-1
-48682	CAPACITOR, fixed: paper dielectric; 4 sect; 800,000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; HS metal can; case 1 15/16" lg x 1 13/16" wd x 2 11/16" h, o/a; vegetol impr and filled; four solder lug term 3/8" h on top of case; int gnd; two mtg ft w/ 0.161" diam mtg holes, one on bottom, one on top on opposite side.	6/24/36 RE48A198 RE13A488		16-C-54862-9980		R16-C-11379-50						RU-5
-48682-10	CAPACITOR, fixed: NT-48682 w/800,000 mmf p/m 10% ea sect.	6/24/36 RE48A198 RE13 488		16-C-54863-1845						CBY	2933-2-A	
-48682-20	CAPACITOR, fixed: NT-48682 w/800,000 mmf p/m 20% ea sect.	6/24/36 RE48A198 RE13A488		16-C-54863-3035								

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-223

RESTRICTED

RESTRICTED

SHEET 48 - 224

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48683	CAPACITOR, fixed: 7/15/36 paper dielectric; 4 mf plus 10 minus 3%; 1,000 vdcw; HS metal can; case 3" lg x 1" wd x 4 5/8" h, o/a; oil impr and filled; two ceramic ins screw type term 1 1/2" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/ a 0.190" diam mtg hole 3 1/2" c to c; superseded by NT-48683-A.	RE48A146		16-C-49939-9757	N16-C-11560-1			CAY	FL	CAY	45-D-643-10 rev4	TBU
		RE13A488						CAY	S 1166910	CAY	T-7607321-25	TBU-1
										CAY	M-7409797-10	TBU-2
												TBU-3
-48683-10	CAPACITOR, fixed: 7/15/36 NT-48683 w/4 mf p/m 10%; superseded by NT-48683-A10.	RE48A146		16-C-49960-9757	N16-C-11560			CAY	FL	CAY	T-7605005-7	TBK-5
		RE13A488						CAY	S1166910	CAY	7607280-61sub24	TBK-6
										CAY	T-7607093-61	TBK-7
										CAY	T-7605848-5	TBK-9
										CAY	T-7609144-25	TBK-11
	NOTE: TBK-13; TBK-15; TBK-16; TBM-4; TBM-5; TBM-6; TBM-7; TBM-8; TBM-12; TBU-4.											SEE NOTE:
-48683-A	CAPACITOR, fixed: 12/20/40 paper dielectric; 4 mf plus 10 minus 3%; 1,000 vdcw; HS metal can; case 3" lg x 1" wd x 4 5/8" h, o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea with a 0.190" diam mtg hole 3 1/2" c to c; same as NT-48683 except reduced term h.	RE13A488		16-C-49939-9752				CAY	S 1166910	CAY	3-D-9478sub1	TAR-5
		RE48A146								CAY	T-7606683-59	
-48683-A10	CAPACITOR, fixed: 12/20/40 NT-48683-A w/4 mf p/m 10%; same as NT-48683-10 ex- cept reduced term height.	RE13A488		16-C-49960-9752	N16-C-11560			CAY	S 1247039	CAY	T-7606683-59	TAR-6
		RE48A146										TAR-7
-48684	CAPACITOR, fixed: 7/15/36 paper dielectric; 6 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 4 5/8" h x 3" wd x 1" thk; oil impr and filled; two stud and nut term 1 1/8" h on for pillars 1 1/4" c to c on top; no int gnd connections; two integral mtg ft on bottom w/ two 0.19" diam holes 3 1/2" c to c; superseded by NT-48684-A.	RE48A146		16-C-50696-7997	N16-C-11620-4			CAY	FL	CAY	45-D-643-10 rev 4	TBK-5
		RE13A488						CAY	S 1166911	CAY	T-7607321-38	TBK-6
												TBU
												TBU-1
												TBU-2
												TBU-3

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-224

RESTRICTED

RESTRICTED

SHEET 48 - 225

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48684-A	CAPACITOR, fixed: paper dielectric; 6.6 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 3" lg x 1" wd x 4 5/8" h; oil impr and filled; two stud and nut term 1 1/16" h on por pillars 1 1/4" c to c on top; no int gnd connections; two mtg fl on bottom of case 1/2" wd, ea w/0.190" diam mtg hole 3 1/2" c to c; same as NT-48684 except term height.	12/20/40 RE48A146 RE13A488		16-C-50696-7992				CAY CAY	FL-3-D-9478 S#1166911	CAY CAY	3-D-9478 T-7606683-60	TAB-5
-48684-A10	CAPACITOR, fixed: NT-48684-A w/6mf p/m 10%.	12/20/40 RE13A488 RE48A146		16-C-50717-7992	N16-C-11620			CAY CAY CAY CAY	1318746 FL S#1166911 S#1318746 S#1247100	CRV CAY CAY CAY CAY	95652-3 T-7610894-47 T-7609144-38 T-7605005-10 T-7606683-60 7607280-62 T-7607093-62 T-7605848-6	SR(2) SR-2(5) SR-5(2) TAB-6 TAB-7 TBK-5 TBK-6 TBK-7 SEE NOTE
-48685	CAPACITOR, fixed: CANCELLED: for replacement use NT-48528.	7/15/36 RE48A146		16-C-49965-6947				CAY	FLS1166912	CAY	45-D-643-7	TBK-5
-48686	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 2 1/8" h o/a; oil impr and filled; two ceramic ins screw type term 7/8" h located on top 13/16" c to c; no int gnd connections; two mtg fl 13/16" wd on side of case, ea w/a 3/16" diam mtg hole 2 1/4" c to c; superseded by NT-48686-A. NOTE: QCH-2 (2) thru QCH-4 (2); QCM (2); QCM-1 (2)	7/15/36 RE48A146 RE13A488		16-C-48796-3119	N16-C-11418-5			CG	9CE5A21	CBM CBM CAY	744-36 744-164 K-7809148-1 sub 1	JK-3 JKA (2) JKA-2 (2) JKA-3 (2) JKA-5 (2) JKA-5a(2) NK-1 NK-3 SEE NOTE
-48686-10	CAPACITOR, fixed: NT-48686 w/ 1 mf p/m 10%; superseded by NT-48686-A10.	7/15/36 RE48A146 RE13A488		16-C-48817-3114	N16-C-11418			CD CAW CSL	TJ-6010	CBM CAY CAY CAY CAY CAY	744-164 T-7605848-3 T-7605024-107 T-7607093-59 7705838-6 7705838-21 7607280-59	NJ-4 (3) NJ-7 (2) NK-7 TBK-5 thru TBK-7 (3) TBK-9 (3) TBK-11 (3) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-225

RESTRICTED

RESTRICTED

SHEET 48 - 226

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48686-A	CAPACITOR, fixed; 8/25/39 paper dielectric; 1 mf plus 10 minus 3%; 600 vdcw, 350 vacw at 800 cyc; BS metal can; case 1 13/16" lg x 1 1/16" wd x 2 1/8" h o/a; oil impr and filled; two ceramic ins screw type term 7/8" h located on top 13/16" c to c; no int gnd connections; two mtg fl 13/16" wd on side of case, ea w/a 3/16" diam mtg hole 2 1/4" c to c; same as NT-48686 except for 800 cyc rating.	RE48A146 RE13A488		16-C-48796-3119	N16-C-11418-1		3DB1.609-1	CD	PC-1349	CAY	T-7607321-15	TBU TBU-1 thru TBU-3
-48686-A3	CAPACITOR, fixed; 8/25/39 NT-48686-A w/1 mf p/m 3%.	RE48A146 RE13A488		16-C-48766-1152				CD	PC-1A349	CAY	T-7606683-56 T-760944-15	TAB-5 thru TAB-7 TBU-4
-48686-A10	CAPACITOR, fixed; 8/25/39 NT-48686-A w/1 mf p/m 10%; same as NT-48686-10 except for 800 cyc rating.	RE48A146 RE13A488		16-C-48817-3114		R16-C-11419-12-250	3DB1.6010-1 3DB1.6010-4 3DB1.6010G					
-48687	CAPACITOR, fixed; 7/15/36 paper dielectric; 2 mf plus 10 minus 3%; 600 vdcw; BS metal can; case 2 7/8" h x 1 13/16" wd x 1 1/16" thk; 'dykanol' or 'inerteen' impr and filled; two stud end nut term 13/16" h on por pillars 7/8" c to c on top; no int gnd connections; two integral mtg ft on bottom w/two 0.206" diam holes 2 1/4" c to c along ctr line.	RE48A146 RE13A488		16-C-49176-3184	N16-C-11490			CD	TJ-6020	CAY	K-7809148-2	
-48687-10	CAPACITOR, fixed; 7/15/36 NT-48687 w/2 mf p/m 10%.	RE48A146 RE13A488		16-C-49197-3135	N16-C-11490		3D374	CD CAY CAY CAY	TJ-6020 S#1166909 S#1173042 7605848-25	CAY CAY CAY CAY CAY	K-7809148-2 P-7705838-7 T-7607094-73 T-7607281-73 T-7606570-1 T-7605848-25sub	TAB-5 thru TAB-7 TBK-5 thru TBK-7 TBK-9 TBK-7 (3) SEE NOTE
	NOTE: TBK-11 (2); TBK-15 (2); TBK-16 (2); TBK-13 (3); TBL-10; TBL-11; TB -4; TBM-10 (2); TBM-12 (2); TBM-5 (3); TBM-6 (4); TBM-8 (4); TBU; TBU-1 thru TBU-4.											
-48688	CAPACITOR, fixed; 7/15/36 paper dielectric; 40 mf plus 10 minus 3%; 600 vdcw; BS metal can; case 4 7/16" lg x 3 3/8" wd x 5 1/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/2" h located on top 2 1/4" c to c; no int gnd connections; two mtg fl on bottom of case ea with two 7/32" diam mtg holes 2 3/8" apart 4 15/16" c to c.	RE48A159 RE13A488		16-C-52662-1282				CAY	FL	CAY CAY	45-D-644-8 rev 7605041-56	TBK-5 TBK-6 (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-226

RESTRICTED

RESTRICTED

SHEET 48 - 227

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48689	CAPACITOR, fixed: mica; 150 mmf; 500 vdcw, 1,000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" h max; molded low-loss bakelite case; two axial wire leads.	7/24/36 RE48A148										
-48689-A5	CAPACITOR, fixed: N-48689 w/150 mmf p/m 5%; temp coef 1tr A. NOTE: RBH-1 (2) thru RBH-3 (2).	7/24/36 RE48A148 JAN-C-5	CM20A151J	16-C-28975-1591	N16-C-9952		3K2015112	CMR CAW CD CSL	0 1468 5W MO-1417-5	CHZ CHA CBY	CO-631188F D-774rev0 P-380chg0	CF-3 ABK (2) ABK-1 thru ABK-7 SEE NOTE
-48689-A10	CAPACITOR, fixed: NF-48689 w/150 mmf p/m 10%; temp coef 1tr A.	7/24/36 RE48A148 JAN-C-5	CM20 151K	16-C-28980-2071			3K2015111	CD CAW CSL CMR	5W5T15 1468 MO-1417-10 0	CRM CRP	744-379 35-9084	SO-9 SU SU-1 (2)
-48689-B1	CAPACITOR, fixed: NF-48689 w/150 mmf p/m 1%; temp coef 1tr B.	7/24/36 RE48A148 16040		16-C-28969-2265				CD CAW CSL CMR	5WL 1468L MOBW-1417-1 0XM			
-48689-B2	CAPACITOR, fixed: NF-48689 w/150 mmf p/m 2%; temp coef 1tr B.	7/24/36 RE48A148 JAN-C-5	CM20B151G	16-C-28969-9116		R16-C-9954-5		CD CAW CSL CMR	5WL 1468L MOB-1417-2 0XM	C R	B-6992alt0	
-48689-B5	CAPACITOR, fixed: NF-48689 w/150 mmf p/m 5%; temp coef 1tr B.	7/24/36 RE48A148 JAN-C-5	CM20B151J	16-C-28975-1596	N16-C-9950-48	R16-C-9954-24-20	3K2015122	CAW CD CSL CMR	1468L 5WL MOBW-1417-5 0XM	CHZ CPR CG CHZ	CO-1114180 C56305-151 M7463930-27rev0 CO-1114	RAP TCD AN/UFM-1 AN/UFM-1B
-48689-B10	CAPACITOR, fixed: NF-48689 w/150 mmf p/m 10%; temp coef 1tr B. NOTE: MK-16 (3); MK-18; MK-27; MK-28; MK-29 Mod 2; MK-34 Mod 2	7/24/36 RE48A148 JAN-C-5	CM20B151K	16-C-28980-2076	N16-C-9952-1	R16-C-9954-25	3K2015121	CAW CD CSL CMR	1468LS 5WLS MOBW-1417-10 0XM	CRB CFE CBM CW CW	CD-1033-10 188C 15.107 744-379 ES-682069-161 ES0-677316-1	NGA OF-1 (4) SJ-1 WFA (2) ZB-3 (6) SEE NOTE
-48689-B20	CAPACITOR, fixed: NF-48689 w/150 mmf p/m 20%; temp coef 1tr B. NOTE: MK-34 Mod 3; MK-34 Mod 4.	7/24/36 RE48A148 JAN-C-5	CM20B151M	16-C-28985-4556	N16-C-9952-3	R16-C-9955-19	3K2015124	CD CMF CAW CSL CMR	5WLS15 503M 1468L MOB-1417 0XM	CRM	744.561	SU SEE NO 8 Cont

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-227

RESTRICTED

RESTRICTED

SHEET 48 - 228

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-48689-05	CAPACITOR, fixed: NT-48689 w/150 mmf p/m 5%; temp coef ltr C.	7/24/36	RE48A148 JAN-C-5	CM200151J	16-C-28975-1601		R16-C-9955-10	3K2015132	CAW	1469	CEM	744-626	WFA
-48689-D2	CAPACITOR, fixed: NT-48689 w/150 mmf p/m 2%; temp coef ltr B.	7/24/36	RE48A148 JAN-C-5	CM200151G	16-C-28969-9126	N16-C-9952-2	R16-C-9954-7		CAW CER CSL CD CMR	1469 M2K150 MOSIM-1417-2 5RS PO	CS CRV	012-35rev0 P-721081-5rev27	DBE QCW QCY QCZ
-48689-D5	CAPACITOR, fixed: NT-48689 w/150 mmf p/m 5%; temp coef ltr D.	7/24/36	RE48A148 JAN-C-5	CM200151J	16-C-28975-1606	N16-C-9954	R16-C-9954-24		CAW CMF CD CSL CMR	1469 603M 5RS MOSIM-1417 PO	CS CG CPN	011-35 M-7463969-27rev3 C-1075	DBE RCD (5) SJ-1 MK-16 MK-27
-48689-D10	CAPACITOR, fixed: NT-48689 w/150 mmf p/m 10%; temp coef ltr D.	7/24/36	RE48A148 JAN-C-5	CM200151K	16-C-28980-2086	N16-C-9954-9	R16-C-9954-30		CAW CD CSL CMR CER	1469 5RS MOSIM-1417-10 PO M2K150	CRV CG CPB CRV CEM	W-303314-346 M-7463969-11rev3 CD-1034-10rev0 P-720473-23rev19 744-338	QCC-8 (2) QCJ-8 (2) QFB RAV-1 (2) SB (6) WEA
-48690	CAPACITOR, fixed: mica; 250 mmf; 500 vdcw, 1,000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" & max; molded low-loss bakelite case; two axial wire leads.	7/24/36	RE48A148 JAN-C-5										
-48690-A5	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 5%; temp coef ltr A.	7/24/36	RE48A148 JAN-C-5	CM20A251J	16-C-29476-3191			3D9250-13 3D9250-3	CAW CSL CMR	545T25 1468 M0-1419 0	CFT CBY	P-381chg0	GF-3 DAU DAU-1 RAS-5
-48690-A10	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 10%; temp coef ltr A.	7/24/36	RE48A148 JAN-C-5	CM20A251K	16-C-29481-3671	N16-C-9974-11		3D9250-20	CAW CD CSL CMR CD CAW CD	1468 545T25 M0-1419-10 0 5W 1468ST 5WS	CWA CADV CPN CRP CRM CW CDE CRV	D-774-23 A-1226rev0 C1058 35-5084 744-129 2806-1 K-863187-10	RAO-1 (3) RAO-2 (3) RAO-7 (3) RAS RAS-1 thru RAS-5 RDK-2 (4) RBE-3 (4) SEE NOTE Con't
	NOTE: RBJ-3; SJ-1; SO-13; VD; VD-1; YB-2 (3); YG; YG		-1 (2); YG	-2 (2); MK-27; WCA-3.									

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-228

RESTRICTED

RESTRICTED

SHEET 48 - 229

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-48690-B2	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 2%; temp coef ltr B.	7/24/36 RE48A148 JAN-C-5	CM20B251G	16-C-29471-1716		R16-C-9975-4		CAW CD CSL CMR	1468L 5WL MOB-1419-2 OXM	CRR	B-6992a1+0	RAW	
-48690-B5	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 5%; temp coef ltr B.	7/24/36 RE48A148 JAN-C-5	CM20B251J	16-C-29476-3196	N16-C-9974-6			CAW CD CSL CMR CAN	1468L 5WL MOB-1419-5 OXM K-1325C	CZC CRR	7135 C-56305-251	RAP (2) RBO-P (3)	
-48690-B10	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 10%; temp coef ltr B.	7/24/36 RE48A148 JAN-C-5	CM20B251K	16-C-29481-3676	N16-C-9974-11	R16-C-9976	3D9250-20	CAW CMR CER CSL CAN CD	1468LS OXM M4E250 MOBW-1419 K-1325 5WLS	CRV CRR CER CG CWQ CPT CBM CW CG CRB CPN CBM CHZ CRV CGC CW	P-720473-34rev19 C56306-251 C1058 47X3561eeB A1727-3 744-649 P-7762067-3 ES0-613080-31eeC M-7463930-313 CD-1033-121eeC ES-692527-51ee1 744-250 00-670 K-063107-10 21R6662 ES-682069-163	AYA AYA-1 AYA-2 CPN DAH-2 (8) DAK-1 thru DAK-4 (8) RAO-3 thru RAO-5 (4) RBO-1 (3) RBO-2 (3) TCJ-1 TUX-1 thru TUX-7 WFA YR	SFE NOTE
-48690-B20	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 20%; temp coef ltr B.	7/24/36 RE48A148 JAN-C-5	CM20B251M	16-C-29486-6156	N16-C-9974-13	R16-C-9976-60		CD CAN CSL CAW CMR	5WL K MOB-1419 1468L OXM	CIA CRM	D5498.1B-192	DAG (2) MQ-1 (2)	
-48690-D2	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 2%; temp coef ltr D.	7/24/36 RE48A148 JAN-C-5	CM20D251G	16-C-29471-1726	N16-C-9973-90	R16-C-9975-6		CER CAW CD CSL CMR	M4E250 1469 5R MOBDW-1419-2 PO	CRV COL CRR CW	P-721081-19rev27 912 3253 70rev3 C56316-251 1eeR ES-692527-31ee1	QCH QCU Con't	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-229

RESTRICTED

RESTRICTED

SHEET 48 - 230

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E B O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48690-D9	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 5%; temp coef ltr D.	7/24/36 RE48A148 JAN-C-5	CM20D251J	16-C-29476-3206	N16-C-9974-1	R16-C-9975-15	3D9250-14	CAW CD CSL CMR CAN	1469 5RS MOSDW-1419 FO K-1325	CCI OPT CRY COL CG CZC CW CFN	81-019 2-1469, 00025 K-885477-4 912 3253 10rev3 M-7463969-25rev3 7135 ES-682032 C-1220	DAI DAU-2 (2) MAB (4) PF RBO-1 (3) ROD (3)
	NOTE: MK-26 Mod 3 (2); MK-26 Mod 4 (2).											SEE NOTE
-48690-D10	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 10%; temp coef ltr D.	7/24/36 RE48A148 JAN-C-5	CM20D251K	16-C-29481-3686	N16-C-9974-3			CAW CD CSL CMR CER CD	1469 IRS MOSDW-1419-10 FO M4K250 SR	CRV COL CG CRB CRV CW	W-303314-300 912 3253 20rev3 M-7463969-13rev3 CD-1034-121aaC P-720473-22rev19 ES-682069-163	QCJ-8 (3) QCL-7 (3) SJ-1 (2) WEA (2) MK-8 (3) ME-16 (2)
	NOTE: MK-18; MK-19; MK-27; MK-28; MK-6 Mod 1 (3); MK-29 Mod 2; MK-34 Mod 3; MK-34 Mod 4.											SEE NOTE
-48690-D20	CAPACITOR, fixed: NT-48690 w/250 mmf p/m 20%; temp coef ltr D.	7/24/36 RE48A148 JAN-C-5	CM20D251M	16-C-29486-6166	N16-C-9974-12			CD CAW CSL CMR	SR 1469 MOSDW-1419-20 FO			
-48691	CAPACITOR, FIXED: mica; 500 mmf; 500 vdcw; case 51/64" lg max 15/32" wd max x 7/32" d max; molded low loss bakelite case; 2 axial wire leads.	7/24/36 RE48A148										
-48691-A5	CAPACITOR, fixed: NT-48691 w/500 mmf p/m 5%; temp coef ltr A.	7/24/36 RE48A148 JAN-C-5	CM20A501J	16-C-30162-1591	N16-C-10016-2			CAN CD	K-1350-5 SW	CRP CW	35-9031 ESA-682069-166	GP-3 SQ-1
	NOTE: SG-28; SL (14); SL-1 (14); MK-28 (13); MK-34 Mod 2 (13); MK-34 Mod 3 (13); MK-34 Mod 4 (13).											SEE NOTE
-48691-A10	CAPACITOR, fixed: NT-48691 w/500 mmf p/m 10%; temp coef ltr A.	7/24/36 RE48A148 JAN-C-5	CM20A501K	16-C-30167-2071	N16-C-10016 N16-C-10015-125 N16-C-10403-10			CAW CD CSL CMR	1468 5W525 MO-1422-10 O	CRA CWI CML CEK CRR CJF CFN	D-774 24164 A26112-3 15-A3008-1 525-178 ST-1187chg0 C1060	IM-2 IM-4 IM-4a IM-5 thru IM-7 IM-15 IM-16
	NOTE: IM-17; IS (5); IS-1 (5); RBJ; RBL (2); RBL-1 (2); RBL-2 (2); RBL-5 (2); RBL-6 (2); REB (2).											SEE NOTE
												Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-230

RESTRICTED

RESTRICTED

SHEET 48 - 231

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48691-A20	CAPACITOR, fixed: 7/24/36 NT-48691 w/500 mmf p/m 20%; temp coef ltr A.	RE48A148 JAN-C-5	CM20A501M	16-C-30172-4551			3D9500-74	CD CSL CMR CAW	5W5T5 MO-1422 0 1468	CFT CCS CMD	6-485 4C5	ARD-1 (3) ARD-2 DAU DAU-1 SEE NOTE
	NOTE: PH; PJ.											
-48691-B2	CAPACITOR, fixed: 7/24/36 NT-48691 w/500 mmf p/m 2%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B501G	16-C-30156-9116		R16-C-10017-5-45		CD CAW CSL CMR	5W 1468L MOB-1422-2 0	CFR	B6992alt0	
-48691-B5	CAPACITOR, fixed: 7/24/36 NT-48691 w/500 mmf p/m 5%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B501J	16-C-30162-1596	N16-C-10016-2	R16-C-10017-46	3E2051122	CD CAW CSL CMR	5W 1468L MOB-1422 OIM	CG	M-7463930-32rev1	BT OAX (6) RAR (8) MK-16 (18)
-48691-B10	CAPACITOR, fixed: 7/24/36 NT-48691 w/500 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B501K	16-C-30167-2076	N16-C-10016	R16-C-10017-58		CSL CAW CFR CMR CD CAN CD	MOBW-1422-10 1468LS MTE500 OIM 5WLS K-1350 5W5T5	CHZ CFV CFM CWQ CG CRB CW CFT CFR CPN CPE CWT	00-615 P-720473-36rev19 744-193 47X3351eeB M-7463930-16rev1 CD-1033-151eeC ES-692527-41ee1 C56306-501 C-1060 20,018 CU-1144	ARJ (2) ATJ AXD AYD-2 AYD-3 BL-1 BL-2 BL-6 (3) QBD QBD (15) RAF RBA SEE NOTE
	NOTE: RBB; RCD (2); RDP (7); SJ-1 (3); MK-16 (4); MK-18 (3); MK-29 Mod 2; MK-34 Mod 3.											
-48691-B20	CAPACITOR, fixed: 7/24/36 NT-48691 w/500 mmf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B501M	16-C-30172-4556	N16-C-10016-9			CMF CD CSL CMR CAW	503-M 5WLS MOBW-1422 OIM 1468LS	CFM CML CHZ	744-560 47B1501F 00-669	LO-1 thru LO-4 RCF (2) SU (2) SU-1 (2) SEE NOTE
	NOTE: YH; YH-1; MK-16.											
-48691-05	CAPACITOR, fixed: 7/24/36 NT-48691 w/500 mmf p/m 5%; temp coef ltr C.	RE48A148 JAN-C-5	CM200501J	16-C-30162-1601				CSL CD CAW CMR	MOSCW-500 5R 1469 FO	CFT CFM	744-337	DAK-2 DAK-4 QFB QFB-1 Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-231

RESTRICTED

RESTRICTED

SHEET 48 232

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48691-D2	CAPACITOR, fixed: NT-48691 w/500 mmf p/m 2%; temp coef 1tr D.	7/24/36 RE48A148 JAN-C-5	CM20D501G	16-C-30156-9126	N16-C-10016-13			CD CAW CMR CSL	5 S 1469 PO MOSDW	CW	BS-692527-71aa1	
-48691-D3	CAPACITOR, fixed: NT-48691 w/500 mmf p/m 3%; temp coef 1tr D.	7/24/36 RE48A148 16040		16-C-30161-3755	N16-C-10016-1			CSL CD CAW CMR	MOSDW-500-3 SR 1469 PO	CIP CBM CBM	EC-744-2571aa2 744-244 744-28	NJ-3 (2) NJ-6 (2) NJ-7 (2) NJ-9 (2)
-48691-D5	CAPACITOR, fixed: NT-48691 w/500 mmf p/m 5%; temp coef 1tr D.	7/24/36 RE48A148 JAN-C-5	CM20D501J	16-C-30162-1606	N16-C-10016-3	R16-C-10017-47		CAW CMR CER CD CSL CMF	1469 PO MIX500 SR MOSW 603M	COL C V CCI CCI CPT CG CW	912 3503 10rev2 P-720538-47rev30 81-023 2-1469.0005 RF-4582-1-31aaA M-7463969-321aa3 BS-682032	AYA AYA-1 AYA-2 DAB DAB-1 DAB-3 DAK SEE NOTE
-48691-D10	CAPACITOR, fixed: NT-48691 w/500 mmf p/m 10%; temp coef 1tr D.	7/24/36 RE48A148 JAN-C-5	C 20D501K	16-C-30167-2086	N16-C-10016-7	R16-C-10017-60		CER CAW CSL CMR CD	MIX500 1469 MOSDW PO SR	CRV CRV CG CV CRB CW	P-720473-8rev19 W-303314-285 M-7463969-16rev3 ND23555chg0 CD-1034-15revC	ATJ (6) LS (2) OAA OAF OAO-1 QCL-7 SEE NOTE
-48692	CAPACITOR, fixed: paper dielectric; three sect; 800,000 mmf plus 10 minus 3% ea sect; 400 vdcw ea sect, flash test 1200v DC; BS metal can; 1 15/16"lg x 1 13/16"wd x 2 11/16" h; oil tmpr and filled; three solder lug term 3/8" h located on top, spaced 9/16" c to c; int gnd; two mtg ft w/0.611" diam mtg holes one on bottom, one on top on opposite side.	7/24/36 RE13A488		16-C-54626-8937				CD				CF-3 CF-11 (2) RU-16 (2)
-48692-10	CAPACITO , fixed: NT-48692 w/800,000 mmf p.m 10% ea sect.	7/24/36 RE13A488		16-C-54627-3429	N16-C-11379-10					CBY	1588-2-C chg 5	
-48692-20	CAPACITOR, fixed: NT-48692 w/800,000 mmf p/m 20% ea sect.	7/24/36 RE48 199 RE13A488		16-C-54627-8245								

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-232

RESTRICTED

RESTRICTED

SHEET 48 - 233

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48693	CAPACITOR, fixed: 7/30/36 paper dielectric; 150,000 mmf plus 10 minus 3%; 1,500 vdcw, 1,000 vacw at 60 cyc; ES metal can; case 2 1/8" h x 1 27/32" wd x 1 1/2" h; oil impr and filled; two solder lug term 1" c to c on top; no int gnd connections; one integral mtg ear at top ctr of one side, 2 integral mtg ears at bottom corners of same side, bottom ears with 0.154" diam holes 1 13/32" c to c and top ear with 0.154" diam holes 2 1/2" from ctr line of bottom holes; superseded by NT-48693-A.	RE13A488		16-C-45951-6767	N16-C-11337-20-1			CAY	X-7808834-1			
-48693-A	CAPACITOR, fixed: 5/6/38 paper dielectric; 150,000 mmf plus 10 minus 3%; 1,500 vdcw, 1,000 vacw at 60 cyc; ES metal can; case 2 1/8" h x 1 27/32" wd x 1 1/2" thk; oil impr and filled; two stud and nut term 1" c to c on top; no int gnd connections; one integral mtg ear at top ctr of one side, two integral mtg ears at bottom corners of same side, bottom ears w/0.154" diam holes 1 13/32" c to c and top ear w/0.154" diam hole 2 1/2" from ctr line of bottom holes; same as NT-48693 except it complies w/RE13A488.	RE13A488 RE13A485		16-C-45951-6767	N16-C-11337-20-1							
-48694	CAPACITOR, fixed: 8/1/36 mica; 10,000 mmf; 3500v DC test; case 1 3/4" lg x 1 3/8" wd x 7/16" h; molded bakelite case; two #6-32 thd holes, 1 1/4" c to c for term and mtg.	16C40										
-48694-B10	CAPACITOR, fixed: 8/1/36 NT-48694 w/10,000 mmf p/m 10%; temp coef ltr B.	16C40		16-C-33624-2399				CRV	Special F	CRV	X-36216rev2	GP GP-2

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-233

RESTRICTED

RESTRICTED

SHEET 48 - 234

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48695	CAPACITOR, fixed: 8/6/36 mica; 1,000 mmf; 500 vdcv, 1,000v DC test; case 1 1/4" lg x 5/8" wd x 1/4" thk; molded bakelite case; two solder lug term; two 3/64" diam holes in case on 1 1/4" mtg/c.	RE48A217 16C40										
-48695-A20	CAPACITOR, fixed: 8/6/36 NT-48695 w/1,000 mmf p/m 20%; temp coef ltr A.	RE48A217 16C40		16-C-31095-7035			3DA1-133	CAW	1461			GP-3
-48695-B5	CAPACITOR, fixed: 8/6/36 NT-48695 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A217 16C40		16-C-31085-4080			3DA1-61	CAW	1461	CBY	P-114	APA ATA
-48695-B10	CAPACITOR, fixed: 8/6/36 NT-48695 w/1,000 mmf p/m 10%; temp coef ltr B. NOTE: RAP; BU-16 (3).	RE48A217 16C40		16-C-31090-4586	N16-C-10085-1			CAW CD CAW	1461 55 1468	CBY CKB CRR	P-114 15-A3008-1 056306-500	GP-11 (3) LM-15 thru LM-17 SEE NOTE
-48696	CAPACITOR, fixed: 8/20/36 mica; 50 mmf; 3,000 vdcv, 1.2 amps at 3000 kc, 0.6 amp at 1000 kc, 0.15 amp at 300 kc, 0.05 amp at 100 kc; 2" lg x 1 5/16" wd x 1 1/2" h; welded bakelite case; two screw term 7/16" h spaced 1 1/2" c to c on top; two mtg fl on bottom, ea w/ one 0.15" diam hole on 2 3/8" mtg/c.	RE48A222 16C40										
-48696-B2	CAPACITOR, fixed: 8/20/36 NT-48696 w/50 mmf p/m 2%; temp coef ltr B.	RE48A222 16C40		16-C-27626-1140	N16-C-9847			CD CAW	1570L-204 FL-639-15L	CAY CAY	7406463-5 M-7406210-2	GP-3 GP-4 TCE-2 TCE-1
-48696-B5	CAPACITOR, fixed: 8/20/36 NT-48696 w/50 mmf p/m 5%; temp coef ltr B.	RE48A222 16C40		16-C-27631-2621	N16-C-9847-16	R16-C-9870-25	3D9050-1	CD	FL-639-15L			
-48696-C5	CAPACITOR, fixed: 8/20/36 NT-48696 w/50 mmf p/m 5%; temp coef ltr C.	RE48A222 16C40		16-C-27631-2627	N16-C-9847-16			CD	FL-639-15H			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-234

RESTRICTED

RESTRICTED

SHEET 48 - 235

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFOR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48697	CAPACITOR, fixed: 8/20/36 mica; 100 mmf; 3,000 vdcw, 2.2 amp at 3000 kc, 0.8 amp at 1000 kc, 0.3 amp at 300 kc, 0.1 amp at 100 kc; 2" lg x 1 5/16" wd x 1 1/2" h; molded bakelite case; two screw term 7/16" h spaced 1 1/2" c to c on top; two mtg fl on bottom, ea w/ one 0.15" diam hole on 2 3/8" mtg/c.	RE48A222 16C40										
-48697-A5	CAPACITOR, fixed: 8/20/36 NT-48697 w/100 mmf p/m 5%; temp coef ltr A.	RE48A222 16C40		16-C-28554-4620		R16-C-9931		CD	PL-583-15			
-48697-B2	CAPACITOR, fixed: 8/20/36 NT-48697 w/100 mmf p/m 2%; temp coef ltr B.	RE48A222 16C40		16-C-28549-3141	R16-C-9936			CD	PL-583-15L			GP-3
-48697-B5	CAPACITOR, fixed: 8/20/36 NT-48697 w/100 mmf p/m 5%; temp coef ltr B.	RE48A222 16C40		16-C-28554-4621				CD	PL-583-15L	COL CRV	907M310C K-860215-26	TCB-2 TCC-1
-48697-B10	CAPACITOR, fixed: 8/20/36 NT-48697 w/100 mmf p/m 10%; temp coef ltr B.	RE48A222 16C40		16-C-28559-5105				CD	PL-583-15L	CG COL	P-7762067-1rev2 907 3100 20	TCB-1
-48697-D2	CAPACITOR, fixed: 8/20/36 NT-48697 w/100 mmf p/m 2%; temp coef ltr D.	RE48A222 16C40		16-C-28549-3167		R16-C-9929		CD	PL-583-15H	CG	P-7762067-3rev2	
-48698	CAPACITOR, fixed: 8/20/36 mica; 250 mmf; 5000 max vdcw, 5 amp at 3000 kc, 2.5 amp at 1000 kc, 1 amp at 300 kc, 0.3 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low-loss bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48749.	RE48A131 16C40										
-48698-A2	CAPACITOR, fixed: 8/20/36 NT-48698 w/ 250 mmf p/m 2%; temp coef ltr A.	RE48A131 16C40		16-C-29473-1838				CD CAW	PL-364-6 1550-204	CAY	T-7606591-32	TCE-1 (2)
-48698-A5	CAPACITOR, fixed: 8/20/36 NT-48698 w/ 250 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-29478-3318				CD	PL-364-6	CAY CAY	7406467-7 T-7605847-7	GP-3 GP-4 (2)
-48698-C2	CAPACITOR, fixed: 8/20/36 NT-48698 w/ 250 mmf p/m 2%; temp coef ltr C.	RE48A131 16C40		16-C-29473-1848	R16-C-9979-3	R16-C-9986		CD CAW	PL-364-6LS	CAY	7608226-17	TDE TDE-1thru TDE-3

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-235

RESTRICTED

RESTRICTED

SHEET 48 - 236

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A B O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-486 9	CAPACITOR, FIXED: mica; 800 mmf; 3000 vdcw, 4.5 amp at 3000 kc, 2.5 amp at 1000 kc, 1.5 amp at 300 kc, 0.7 amp at 100 kc; potted molded low loss bakelite case; case dimen 2 1/16" lg x 61/64" wd x 1 17/32" h; 2 stud term #8-32 ths, 7/16" h located on top spaced 1 1/2" c to c; 2 tab mtg holes .150" diam located on bottom spaced 2 3/8" c to c; add suffix indicating capacity tolerance in per cent.	8/20/36 RE48A222 16C40										
-48699-B5	CAPACITOR, fixed: NT-48699 w/800 mmf p/m 5%; temp coef ltr B.	8/20/36 RE48A222 16C40		16-C-30691-1021				CD	PL-727-15L			GP-3
-48699-B20	CAPACITOR, FIXED: Navy Type 48699 w/800 mmf p/m 20%; temp coef letter B.	2/24/50 RE48A222 16C40		16-C-30702-3500	R16-C-10073-108							
-48700	CAPACITOR, fixed: mica; 1250 mmf; 2000 vdcw, 5.0 mp at 3000 kc, 3.0 amp at 1000 kc, 1.6 amp at 300 kc, 0.8 amp at 100 kc; case 2" lg x 15/16" wd x 1 1/2" h; molded low-loss bakelite case; two screw term 7/16" h spaced 1 1/2" c to c on top; two mtg fl on bottom, ea w/ one 0.15" diam hole on 2 3/8" mtg/c.	8/20/36 RE48A222 16C40										
-48700-A5	CAPACITOR, fixed: NT-48700 w/1,250 mmf p/m 5%; temp coef ltr A.	8/20/36 RE48A222 16C40		16-C-31323-7825				CD	PL-847-15			
-48700-D2	CAPACITOR, fixed: NT-48700 w/1,250 mmf p/m 2%; temp coef ltr D.	8/20/36 RE48A222 16C40		16-C-31318-6360	R16-C-10175-16	R16-C-10205		CAW CD	1507B-121 PL-847-15LST	CAY CAY CAY	7406468-1 T-7605847 P-10 T-7609856-32 T-7606591-30	GP-3 GP-4 TCE-1(2) TCE-2
-48701	CAPACITOR, fixed: mica; 2500 mmf; 2000 vdcw, 5.5 amp at 3000 kc, 4.0 amp at 1000 kc, 2.5 amp at 300 kc, 1.2 amp at 100 kc; case 2" lg x 15/16" wd x 1 1/2" h; molded bakelite case; two screw term 7/16" h spaced 1 1/2" c to c on top; two mtg fl on bottom, ea w/one 0.15" diam hole on 2 3/8" mtg/c.	8/20/36 RE48A222 16C40										
-48701-A5	CAPACITOR, fixed: NT-48701 w/2,500 mmf p/m 5%; temp coef ltr A.	8/20/36 RE48A222 16C40		16-C-32009-6225				CD	PL-828-15			
-48701-D2	CAPACITOR, fixed: NT-48701 w/2,500 mmf p/m 2%; temp coef ltr D.	8/20/36 RE48A222 16C40		16-C-32004-4748				CAW CD	1570B-122 PL-828-15H	CAY CAY CAY	7406468-2 T-7605847-11 T-7609856-25 T-7606591-24	GP-3 GP-4(2) TCE-1 TCE-2 (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-236

RESTRICTED

RESTRICTED

SHEET 48 - 237

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48702	CAPACITOR, fixed; mica; 5,000 mmf; 2000 vdcw, 8.5 amp at 3000 kc, 6.5 amp at 1000 kc, 4.0 amp at 300 kc, 2.0 amp at 100 kc; case 2" lg x 1 5/16" wd x 1 1/2" h; molded bakelite case; two screw term 7/16" h spaced 1 1/2" c to c on top; two mtg fl on bottom, ea w/one 0.15" diam hole on 2 3/8" mtg/c. 8/20/36	RE48A222 16C40										
-48702-A5	CAPACITOR, fixed; NF-48702 w/5,000 mmf p/m 5%; temp coef ltr A. 8/20/36	RE48A222 16C40		16-C-32695-4625				CD	PL-725-15			
-48702-D2	CAPACITOR, fixed; NT-48702 w/5,000 mmf p/m 2%; temp coef ltr D. 8/20/36	RE48A222 16C40		16-C-32690-3160	N16-C-10411-80	R16-C-10425		CD CAW	PL-725-15H 1570H-245	CAY CAY CAY CAY	7406468-4 T-7605847-12 T-7606408-2 T-7609856-26 T-7606591-25	GP-3 GP-4 TCB-2 TCE-1 TCE-2
-48703	CAPACITOR, fixed; paper dielectric; two sect; 100,000 mmf plus 10 minus 3/4 ea sect; 400 vdcw; ES metal can; case 1 13/16" lg x 1" wd x 3/4" h o/s; oil impr end filled; three solder lug term 5/16" h on bottom of case 1/2" c to c; no int gnd connections; two mtg ears 3/8" wd integral w/bottom of case w/two 3/16" diam holes on 2 1/8" ctr; superseded by NT-48703-A. 8/22/36	RE48A138 RE13A488		16-C-53104-9295				CD CAY	HC-1579 UC-887	CAY CW	F-7706012-4 7899166	GP-3 GP-4
-48703-A	CAPACITOR, fixed; paper dielectric; two sect; 100,000 mmf plus 10 minus 3/4 ea sect; 500 vdcw ea sect; ES metal can; case 1 13/16" lg x 1" wd x 3/4" h o/s; oil impr end filled; three solder lug term 5/16" h on bottom of case 1/2" from c to c; no int gnd connections; two mtg ears 3/8" wd integral w/bottom of case w/two 3/16" diam mtg holes on 2 1/8" ctr. 1/16/41	RE13A488 RE48A138		16-C-53115-6172	N16-C-11332-44-1		3DKA100-186	CSF CB CBV	A8136	CW CFW	F-7809166 300447-2rev9	BN(2) BN-1 BN-2(2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-237

RESTRICTED

RESTRICTED

SHEET 48 - 238

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S B/WG OR PART NO	EQUIPMENT USED IN
-48703-A10	CAPACITOR, fixed: 1/16/41 NT-48703-A w/100,000 mmf p/m 10% ea sect.	RE13A488 RE48A138		16-C-53159-5390	N16-C-11332-44-2		3DKA100-179	CSF CSL CBV CQU CQU	2529-2 2XDRBW6 A8136 AH124 7573	CBM CFP CZC CFN	744-616 F-39012-1 5069 3004472-2rev9	DAU DAU-1 RMG-1 (2) RBO-2 (2) SU(3) SU-1
-48703-A15	CAPACITOR, fixed: 1/16/41 NT-48703-A w/100,000 mmf p/m 15% ea sect. NOTE: EN-2 (2); UE-1 (2).	RE13A488 RE48A138		16-C-53192-8197			3DA100-272 3DA100-273	CBV	A8136	CG CFN	K-56J874-6rev1 300447-2rev9	BN (2) BN-1 SEE NOTE
-48704	CAPACITOR, fixed: 8/22/36 paper dielectric; 500,000 mmf plus 10 minus 3%; 400 vdcw; ES metal can; 1 13/16" lg x 1" wd x 7/8" h o/a; oil impr and filled; two solder lug term 5/8" h on bottom of case spaced 1" c to c; no int gnd connections; two mtg ft on bottom of case 3/8" wd ea w/a 3/16" diam mtg holes spaced 2 1/8" c to c; superseded by NT-48704-A NOTE: LM-15 thru LM-17; TCE.	RE48A138 RE13A488		16-C-47272-9449	N16-C-11349			CAW CD CD CIB	HC-1580 VC-888	CMD CAY CFN CEA	4C18A 7706012-5 A203-2 15-A3003-1	ARD-2 GP-3 GP-4 LM thru LM-2 LM-4 LM-4a thru LM-7 SEE NOTE
-48704-A	CAPACITOR, fixed: 1/16/41 paper dielectric; 500,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1" wd x 7/8" h; oil impr; two solder lug term 1/2" h on bottom of case 1" c to c; no int gnd connections; two mtg ears 3/8" wd integral w/bottom of case w/two 3/16" diam mtg holes 2 1/8" c to c.	RE48A138 RE13A488		16-C-47276-3124	N16-C-11355	R16-C-11709-290	3DA500-97.20	CSF CSL CD	2529-3 XDRBW6-5 DTB	CBM CG CRR	744-620 K-43J249-3rev3 A-114465-1revE	SU (2)
-48704-A10	CAPACITOR, fixed: 1/16/41 NT-48704-A w/500,000 mmf p/m 10% NOTE: FF; TCC-1 (3); MK-33.	RE48A138 RE13A 88		16-C-47297-3114	N16-C-11355		3DA500-97.17 3DA500-97.29	CG CSL CAW CD CD COF CTD	2529-3 XDRBW6-5-10 630 VC-888 DYRD-6050G 7503B RL0L-650	CRF CAY CAY CW CBM CG CRR CG	35-5093 T-7609856-2 T-7606591-2 E50-682063-85 744-620 K-43J249-3rev3 A-114465-1revE K-56J874-3	SO-12M(2) SO-12M(2) SM-1 TCE-2 TCE-1 MK-34 Mod2 (2) MK-13 Mod0 SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-238

RESTRICTED

RESTRICTED

SHEET 48 - 239

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48704-A20	CAPACITOR, fixed: NT-48704-A w/500,000 mmf p/m 20%.	1/16/41		16-C-47327-7478	N16-C-11354-100		3DA500-97.7 3DA500-131.1 3DA500-260 3DA500-260.1 3DA500-260.2	CSF CSL CD	2529-3 TIMBHW6-.5 DYB	CHZ	CO-106118a0	AN/UPM-1 (2) AN/UPM-1B (2)
-48705	CAPACITOR, fixed: mica; 720 mmf; 5000 vdcv max, 5 amp at 3000 kc, 3.5 amp at 1000 kc, 2 amp at 300 kc, 1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	8/29/36 RE48A131 16C40										
-48705-A2	CAPACITOR, fixed: NT-48705 w/720 mmf p/m 2%; temp coef ltr A.	8/29/36 RE48A131 16C40		16-C-30607-4038	N16-C-10070	R16-C-10035		CD CAW	PL-862-6 1550-139	CAY CAY CAY	7406467-10 T-7605847-8 7606591-27	GP-3 GP-4 TCE-1
-48705-A5	CAPACITOR, fixed: NT-48705 w/720 mmf p/m 2%; temp coef ltr A.	8/29/36 RE48A131 16C40		16-C-30612-5518				CD	PL-862-6			
-48706	CAPACITOR, fixed: mica; 1100 mmf; 5000 max vdcv, 7 amp at 3000 kc, 6 amp at 1000 kc, 3 amp at 300 kc, 1.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	8/29/36 RE48A131 16C40										
-48706-A2	CAPACITOR, fixed: NT-48706 w/1100 mmf p/m 2%; temp coef ltr A.	8/29/36 RE48A131 16C40		16-C-31187-6838				CD CAW	PL-846-6 1550-140	CAY	T-7606591-26	TCE-1
-48706-A5	CAPACITOR, fixed: NT-48706 w/1100 mmf p/m 2%; temp coef ltr A.	8/29/36 RE48A131 16C40		16-C-31192-8318				CD	PL-846-6	CAY	T-7605847-B	GP-4
-48706-B2	CAPACITOR, fixed: NT-48706 w/1100 mmf p/m 2%; temp coef ltr B.	8/29/36 RE48A131 16C40		16-C-31187-6843	N16-C-10155	R16-C-10152		CRV CRV CD CAW	UC case 351 UC 3299 PL-846-6H 1550-H-140	CRV CAY	K-860215-14rev6 7607470-70	TBK-17 TBK-8 TBK-10 TBK-12 SEE NOTE
-48706-D2	CAPACITOR, fixed: NT-48706 w/1100 mmf p/m 2%; temp coef ltr D.	8/29/36 RE48A131 16C40		16-C-31187-6853				CD	PL-848-6HB	CAY	7406467-9	GP-3

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVYSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-239

RESTRICTED

RESTRICTED

SHEET 48 - 240

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48707	CAPACITOR, fixed: paper dielectric; five sect; 8/5/4/2/1 mf plus 10 minus 3% ea sect; 600 vdcw ea sect, 250 vacw 600 to 800 cps; HS metal can; case 3 3/4" wd x 2 1/2" h x 4 13/16" lg w/a; dykanol impr and filled; 6 solder lug term 7/16" h located on end; no int gnd connections; two mtg straps w/four 0.154" diam mtg holes on 4 1/4" x 3 7/16" mtg/c soldered to case.	8/29/36 RE48A197 RE13A488		16-C-54968-1498				CD	PC-679	CAY CAY CAW	T-7605848-1 P-7705695-1 rev8 14271 rev 0	GP-3 GP-4
-48707-15	CAPACITOR, fixed: NT-48707 w/ 8/5/4/2/1 mf p/m 15% ea sect.	8/29/36 RE48A197 RE13A488		16-C-54973-1710	N16-C-12725							
-48707-20	CAPACITOR, fixed: NT-48707 w/ 8/5/4/2/1 mf p/m 20% ea sect.	8/29/36 RE48A197 RE13A488		16-C-54974-5731								
-48708	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 2,000 vdcw; HS can; case 3" lg x 1 1/4" wd x 4 5/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl 1" wd on side of case, ea w/ 7/32" diam mtg hole 3 1/2" c to c.	9/18/36 RE48A146 RE13A488		16-C-49183-4735	N16-C-11492			CAY	S949133	CAY	7809562-1	GP-3
-48708-10	CAPACITOR, fixed: NT-48708 w/2 mf p/m 10%. NOTE: TBL-5; TBL-6; TBL-7; TBL-10 thru TBL-13.	9/18/36 RE48A146 RE13A488		16-C-49204-4735						CAY	7607471-96	TBL-2 TBL-3 SEE NOTE
-48709	CAPACITOR, fixed: paper dielectric; 3 sect; 100,000 mmf plus 10 minus 3%; 400 vdcw; HS metal can; case 15/16" wd x 1 13/16" lg x 3/4" h; oil impr; three solder lug term 9/16" h on bottom of case 19/32" c to c; all sect int gnd; 2 mtg ears 3/8" wd integral w/bottom of case w/two 3/16" diam mtg holes 2 1/8" c to c; superseded by Navy Type 431846; add suffix indicating capacity tolerance in per cent.	9/24/36 RE48A138 RE13A488		16-C-54443-2296	N16-C-11335-10			CD CIE CSF	D 84282A	CRR CKE CBZ	A207-2 alt 0 15-A3004-1 CO-831	IM IM-1 SEE NOTE
-48709-10	CAPACITOR, fixed: NT-48709 w/100,000 mmf p/m 10%. NOTE: IM-2; IM-4; IM-4a; IM-5; IM-6; IM-7; IM-15; IM-16; IM-17; YJ (8); YJ-1(8); YJ-2(8).	9/24/36 RE48A138 RE13A488		16-C-54443-2296	N16-C-11335-10			CD CIE CSF	D 84282A	CRR CKE CBZ	A207-2 alt 0 15-A3004-1 CO-831	IM IM-1 SEE NOTE
-48709-A	CAPACITOR, fixed: CANCELLED: for replacement use NT-481846	1/16/44 RE48A138 RE13A488										

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-240

RESTRICTED

RESTRICTED

SHEET 48 - 241

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48710	CAPACITOR, fixed: mica; 10 mmf; 500 vdcw; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	9/24/36 RE48A148 JAN-C-5										
-48710-A5	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 5%; temp coef ltr A.	9/24/36 RE48A148 JAN-C-5	CM20A100J	16-C-26020-7791	N16-C-9790			CAN CAW CD CMR CSL	K-1410 1468 5MS 0 MO	CRP	35-5015	LM SG(9) SG-1 SG-2S
-48710-A10	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 10%; temp coef ltr A.	9/24/36 RE48A148 JAN-C-5	CM20A100K	16-C-26025-8271	N16-C-9791-21			CSL CAW CD CMR CSL	MO-1403-10 1468 5W 0 MOW.5-41-10	CBM CRR CNA CFT CG	744-570 A1727-1a1t0 A26112-1 RF-4582-1-21aaA K-27J362-504rev9	LD-4 LM LM-1 LM-2 LM-4 SEE NOTE:
-48710-B5	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 5%; temp coef ltr B.	9/24/36 RE48A148 JAN-C-5	CM20B100J	16-C-26020-7796	N16-C-9790	R16-C-9806-250		CD CAW CSL CMR	5WLS 1468LS MOW-1403-5 OXM			
-48710-B10	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 10%; temp coef ltr B.	9/24/36 RE48A148 JAN-C-5	CM20B100K	16-C-26025-8276	N16-C-9790-1 N16-C-9791-21	R16-C-9807-3	3K2010021	CAW CD CSL CMR CAN CER CSL	1468LS 5WLS MOW-1403-10 OXM KS MIX10 MOW	COL CBM CHZ CRR CRR CRB CRV CG CRP	909 4107 52 rev3 744-602 CO-612 C-60023-100 issaZ B-6992a1t0 CD-1033-31aaC P-720473-28rev19 P-7761328-9rev1 35-5131	BL-1 BL-2 BL-3 BL-4 BL-5 BL-6 RAP(6) SB SO-7M(2) SEE NOTE:
-48710-B20	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 20%; temp coef ltr B.	9/24/36 RE48A148 JAN-C-5	CM20B100M	16-C-26031-1756	N16-C-9790-3 N16-C-9791-13	R16-C-9807-18		CD CAW CSL CMR CAN	5WLS 1468LS MOW-1403 OXM KS	COL CBM	909 4107 54rev3 744-570	TCZ-1(2) MK-16 MK-29 Mod2(3) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-241

RESTRICTED

RESTRICTED

SHEET 48 - 242

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48710-05	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 5%; temp coef ltr C.	9/24/36 RE48A148 JAN-C-5	CM20C100J	16-C-26020-7801		R16-C-9806-255		CAW CAW CSL CD CMR	K 1469 MOSCW SR PO			DAE (4) DAE-1 (4)
-48710-C10	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 10%; temp coef ltr C. NOTE: RBC (3); RBC-1 (3); TBC-2 (3); SA-3 (5); SM (5); SN; SO (2); SO-a (2); SO-1 (2); SO-2 (2); SO-3; SO-8 (2); SO-9 (2); SO-13 (2); WEA-1.	9/24/36 RE48A148 JAN-C-5	CM20C100K	16-C-26025-8281	N16-C-9790-1	R16-C-9807-5		CAW CD CER CMR CSL CSL CSL CSL	1469 SRS MLK10 PO MOSCW MOSW MOSCW-5-41-10 MTCW	CMT CRV CRV CRP CG	P-720473-3rev19 W-30314-411 P-720473-2 35-5131 E-27J362-504	QRH QCU QCC-2 QCJ-8 QCL-7 RBB(3) RBB-1(3) RBB-2(3) SEE NOTE:
-48710-D5	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 5%; temp coef ltr D.	9/24/36 RE48A148 JAN-C-5	CM20D100J	16-C-26020-7806	N16-C-9791			CD CAW CMF CSL CMR	SR521 1469 603M MOSDW PO	CRM CS CG CPN	744-601a1t0 011-7revD M-7463969-19rev3 c-1218	DBB(2) RCD(2) SU SU-1
-48710-D10	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 10%; temp coef ltr D. NOTE: RBS-1 (4); RBS-2 (4); RCD; TCC; WEA.	9/24/36 RE48A148 JAN-C-5	CM20D100K	16-C-26025-8286	N16-C-9791-19	R16-C-9807-10		CSL CD CAW CMR	MOSTW SRS 1469 PO	CPT CPN CG CRV CALG CADV CRB CCT CAY CPK	M-7463969-3rev3 C-1068 F-720592-31rev30 W-303314-411 A-1303rev0 CD-1034-31sec 7608011-102 7608010-6	ARB DAK DAE-1 OBV(2) QWD(2) RAX-1(6) RBD RSM-1 thru RSM-5(9) RBS(4) SEE NOTE:
-48710-D20	CAPACITOR, fixed: NT-48710 w/10 mmf p/m 20%; temp coef ltr D.	9/24/36 RE48A148 JAN-C-5	CM20D100M	16-C-26031-1766	N16-C-9791-24			CAW CD CMR CSL	1469 SRS PO MOSDW			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-242

RESTRICTED

RESTRICTED

SHEET 48 - 243

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48711	CAPACITOR, fixed: 9/24/36 mica; 25 mmf; 500 vdcw, 1000v DC test; case 51/64" 18 max x 15/32" wd x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148 JAN-C-5										
-48711-A10	CAPACITOR, fixed: 9/24/36 NP-48711 w/25 mmf p/m 10%; temp coef ltr A. NOTE: LM-1 thru LM-4; LM-4a; IM-5 thru IM-7; LM-15; LM-16; LM-17; SG-1; SG-28	RE48A148 JAN-C-5	CM20A250K	16-C-26949-1271	N16-C-9799-3			CAW CD CSL CMR CAN	1468 5WS-SQ25 MO O K-1425	CFI CRR CKB CNA CRV CRP	A1727-2alt0 A26112-2 15-A3009-1 P-720473-42rev19 35-5018	DAH DAH-2(10) DAK-2(10) DAK-3(10) DAK-4(10) IM SEE NOTE
-48711-B5	CAPACITOR, fixed: 9/24/36 NP-48711 w/25 mmf p/m 5%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B250J	16-C-26943-9796	N16-C-9799-10			CAW CD CSL CMR	1468L 5WL MOBW OXM	CRR	B6992 alt0	
-48711-B10	CAPACITOR, fixed: 9/24/36 NP-48711 w/25 mmf p/m 10%; temp coef ltr B. NOTE: YH-1; AN/CPN-6(5); MK-16; MK-18; MK-27; MK-28(2); MK-29 Mod 2; MK-34 Mod3; MK-34 Mod4; MK-34 Mod2.	RE48A148 JAN-C-5	CM20B250K	16-C-26949-1276	N16-C-9799-3	R16-C-9817-15		CD CMP CSL CAW CMR CW CAN	5WLS 503M MOBW-1406-10 1468LS OXM CM20B25 K	CRM CRB CKR CG CRV CGG CHZ CW	744-605 CD-1033-41aEC C56306-250 M-7463930-5 P-720473-3 CO-673 21R6600	RAP(4) SC-2(2) SJ-1 SU(2) SU-1(2) TDF(12) WEA-1(4) YH SEE NOTE
-48711-B20	CAPACITOR, fixed: 9/24/36 NP-48711 w/25 mmf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B250M	16-C-26954-3756	N16-C-9799-5			CSL CD CAW CMR	MOBW-1406 5WLS 1468LS OXM	CDU CW	3-420	OCA MK-16
-48711-C2	CAPACITOR, fixed: 9/24/36 NP-48711 w/25 mmf p/m 2%; temp coef ltr C. NOTE: SG-1; SG-28.	RE48A148 JAN-C-5	CM20C250C	16-C-26938-8311				CSL	MOSCW-25	CRP		SG(2) SG-a SEE NOTE
-48711-C5	CAPACITOR, fixed: 9/24/36 NP-48711 w/25 mmf p/m 5%; temp coef ltr C.	RE48A148 JAN-C-5	CM20C250J	16-C-26943-9806				CAW CD CSL CMR	1469 5R MOSCW FO	CRB COL	CD-1054-61aEH 912 4253 10rev4	LU-3(4) Cont

SHEET 48-243

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 244

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48711-C20	CAPACITOR, fixed: NT-48711 w/25 mmf p/m 20%; temp coef ltr C.	9/24/36 RE48A148 JAN-C-5	CM20C250M	16-C-26954-3761			3D9025-88	CMF CD CSL CMR CAW	603-M SR MOSCW PO 1469	CRZ COL	912 4253 40rev4	LO-1 thru LO-4
-48711-D2	CAPACITOR, fixed: NT-48711 w/25 mmf p/m 2%; temp coef ltr D.	9/24/36 RE48A148 JAN-C-5	CM20D250G	16-C-26938-8321	N16-C-9799		3D9025-4	CD CSL CAW CMR	SRS MOSDW 1469 PO	CRP	35-5016	SG-1 SG-28
-48711-D5	CAPACITOR, fixed: NT-48711 w/25 mmf p/m 5%; temp coef ltr D.	9/24/36 RE48A148 JAN-C-5	CM20D250J	16-C-26943-9811	N16-C-9799-1			CAW CD CSL CMR CEC	1469S SRS MOSDW PO	CRV CRV CRZ CG CWI	P-720538-49rev30 W-303314-344 CO-1016ies0 M-7463969-21rev3	ARB LS(3) QCJ-8(2) QCL-7(2) TS-186/UP (3)
-48711-D10	CAPACITOR, fixed: NT-48711 w/25 mmf p/m 10%; temp coef ltr D. NOTE: QCX (5); QCY (5); QCZ (5); RAX-1 (6); RCD; SJ-1 (3); MK-16 (3); MK-18 (3); MK-19 (3); MK-27 (3); MK-28 (3); MK-29 MOD 2 (3); MK-34 Mod 2 (3); MK-34 Mod 3; MK-34 Mod 4.	9/24/36 RE48A148 JAN-C-5	CM20D250K	16-C-26949-1206	N16-C-9799-2	R16-C-9817-25		CSL CAW CD CER CMR CW	MOSCW-1406 1469 SRS MLE25 PO CM20D250K	CPT CRV CDL CWT CG GRB CW CPH CW	P-720473-3rev19 B-8F-828revD M-7463969-5rev3 CD-1034-4isaC C-1098 ESA-682069-155	DAX(8) LAE-1 thru LAE-3 LAF-2 RMB-1(4) QBR(4) QCQ-2(4) QCU (3) QCW (5) SEE NOTE
-48711-D15	CAPACITOR, fixed: NT-48711 w/25 mmf p/m 15%; temp coef ltr D.	9/24/36 RE48A148 16C40		16-C-26953-5350	N16-C-9799-4			CD CSL CAW CMR	SRS MOSDW 1469 PO			
-48711-D2C	CAPACITOR, fixed: NT-48711 w/25 mmf p/m 20%; temp coef ltr D.	9/24/36 RE48A148 JAN-C-5	CM20D250M	16-C-26954-3761	N16-C-9799-6			CD CSL CAW CMR	SRS MOSDW 1469 PO			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-244

RESTRICTED

RESTRICTED

SHEET 48 - 245

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48712	CAPACITOR, fixed: 9/24/36 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 400 vdcw ea sect; ES metal can; case 1 13/16" lg x 3/4" wd x 15/16" h; oil impr and filled; three solder lug term 5/16" h on side, spaced 1/2" c to c; ctr term gnd to case; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c; superseded by NR-48712-B.			16-C-53104-9255				CD	DB-4010	CRR CKB	A204-3 alt 0 15-A3013-1	IM IM-1 IM-15 thru IM-17
-48712-A	CAPACITOR, fixed: 11/23/36 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 400 vdcw ea sect; ES metal can; case 1 13/16" lg x 1" wd x 7/8" h; oil impr end filled; two solder lug term 5/16" h on side, spaced 1" c to c; int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c; superseded by NT-48712-B.	RE13A488 RE48A129		16-C-53104-9320								
-48712-B	CAPACITOR, fixed: 12/9/40 paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 600 vdcw ea sect; ES metal can; case 1 13/16" lg x 1" wd x 3/4" h; oil impr and filled; two solder lug term 3/8" h on side, spaced 1" c to c; both sect int gnd; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A129		16-C-53115-6112		R16-C- 11333-97	3DA100-186	CTD	RLO-6210			
-48712-B10	CAPACITOR, fixed: 12/9/40 NR-48712 w/100,000 mmf p/m 10% ea sect. NOTE: SX; VD(3); VD-1(3); SO-12M; SO-12N.	RE13A488 RE48A129		16-C-53159-5370	N16-C-11332-46		3DA100-133.10 3DA100-133.12 3DA100-393	CTD CSL CBV CD	RLO-6210 XDMRT6-.1-10 A7175 DVR6011-8	CFE	10.136	RBO-1 RBO-2 RCH RCK(2) RDO(2) SEE NOTE
-48712-B20	CAPACITOR, fixed: 12/9/40 NR-48712 w/100,000 mmf p/m 20% ea sect.	RE13A488 RE48A129		16-C-53214-7487	N16-C-11333-1-1		3DA100-347	CSL CBV CTD	XDMRT6-.1-20 A7175 RLO-6210	CGG CFE	8A42241 1es0 10.136	TCZ AN/APA-6(4) AN/APA-6A (4)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-245

RESTRICTED

RESTRICTED

SHEET 48 - 246

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48713	CAPACITOR, fixed: 9/24/36 paper dielectric; three sect; 100,000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; HS metal can; 1 13/16" lg x 1" wd x 3/4" h; wax impr and filled; three solder lug term 3/8" h on side, spaced 1/2" c to c; all sect int gnd; two mtg ft 3/8" wd flush w/ bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c; superseded by NT-48713-B.	RE13A488 RE48A129		16-C-54429-6079				CD	DC-4010	CFE	10.71rev0	
-48713-10	CAPACITOR, fixed: 9/24/36 NT-48713 w/100,000 mmf p/m 10% ea sect; superseded by NT-48713-B10. NOTE: IM-4a(2); IM-5(2) thru IM-7(2).	RE13A488 RE48A129		16-C-54443-2293			3DA100-92	CD	DC-4010	CFR	A205-2	IM(2) IM-2(2) IM-4(2) SEE NOTE
-48713-A	CAPACITOR, fixed: 11/23/36 paper dielectric; three sect; 100,000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; HS metal can; case 1 3/4" lg x 1" wd x 7/8" h; wax impr and filled; 3 solder lug term 3/8" h on side spaced 1/2" c to c; all sect int gnd; 2 mtg ft 3/8" wd flush w/bottom w/ 3/16" diam mtg holes spaced 2 1/8" c to c; superseded by NT-48713-B.	RE13A488		16-C-54429-6005		R16-C-11336-25		CD CAW	DE-4111 430	CIB CRV CFR CKB	D5409.1C-150 K-865492-3 A205-2 15-A3002-1	ARB(2) DAG(3) LD-4 IM-15 IM-16 IM-17 LP thru LP-4
-48713-B	CAPACITOR, fixed: 12/9/40 paper dielectric; three sect; 100,000 mmf plus 10 minus 3% ea sect; 600 vdcv ea sect; HS metal can; 1 13/16" lg x 1" wd x 3/4" h o/a; oil impr and filled; three solder lug term 5/16" h on side spaced 1/2" c to c; all sect int gnd; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A129		16-C-54432-8720	N16-C-11335-1 N16-C-11334-4			CSF CD CIE	2528-14 DVR-6111 6BA111	CFE CIA CZC	10.71rev0 D5507-35 CO-840	ARB(2) DAG(3) JM-4(3) LP(2) LP-1(2) thru LP-4(2) YJ YJ-1
-48713-B10	CAPACITOR, fixed: 12/9/40 NT-48713-B w/100,000 mmf p/m 10% ea sect. NOTE: RBO-1(3); RBO-2(3); RCH(5); RDO(2); SU; SU-1; YJ-2.	RE13A488 RE48A129		16-C-54446-5177	N16-C-11335-1	R16-C-11707-12	3DA100-108.6	CSF CD CIE CIE	2528-14 DYR-6111 7569 AH122	CEM COL CZC CZC	744-624 956 3018 20 5065 CO-840	DAB DAB-1 DAB-3 IM SEE NOTE Cont

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-246

RESTRICTED

RESTRICTED

SHEET 48 - 247

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48713-B20	CAPACITOR, fixed: 12/9/40 NT-48713-B w/100,000 mmf p/m 20% ea sect. NOTE: MK-BMod2; MK-16; MK-18; MK-27; MK-29Mod2; MK-34 Mod3; MK-34 Mod4.	RE13A488 RE48A129		16-C-54463-6405	N16-C-11335	R16-C-11336-65	3DA100-381	CD	DYE-6111	COL	956 0001 00	DAU-1
								CSF	2528-14	CFT	RF-2619-1-3	SJ-1
								CSL	3XMRW6-.1	CW	ES-682063-62	SLa
								CSF	PPTS-401E			SL-1
								CGF	7511			SJ
								CTD	RLO-6310			TCS-6
								CBV	12M-12-40			TCZ,1,2
CSF	P-9454			AN/TFS-1B SEE NOTE								
-48714	CAPACITOR, FIXED: 10/10/36 mica; 700 mmf; 6000 peak vdw, 8 amp at 1000 kc, 5.25 amp at 500 kc, 4.50 amp at 300 kc, 1.70 amp at 100 kc; 3" h x 3 1/2" diam; ceramic case; 2 fl elliptical end term w/two 17/64" diam holes in ea on 4 1/4" mtg/c.	RE48A122 16C40										
-48714-B5	C PACITOR, fixed: 10/10/36 NT-48714 w/700 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-30584-4151				CD	PL-455-50	CG	ML-7660174-25	TAJ-6
-48714-B10	C PACITOR, fixed: 10/10/36 NT-48714 w/700 mmf p/m 10%; temp coef ltr B.	RE48A122 16C40		16-C-30589-4631	N16-C-1006?			CD	PL-455-50			
-48715	CAPACITOR, fixed: 10/10/36 mica; 40,000 mmf; 1,000 vdw; 20 amp at 3,000 kc, 25 amp at 1,000 kc, 22 amp at 300 kc, 15 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast aluminum end-cap term 1/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48715-B5	CAPACITOR, fixed: 10/10/36 NT-48715 w/40,000 mmf p/m 5%; temp coef ltr B. NOTE: TAJ-11; TAJ-13 thru TAJ-19.	RE48A132 16C40		16-C-34989-7086	N16-C-10585-18			CD	PL-633-59	CG	ML-7660174-27 7660607-127 M-7 63523-2 P-7762813-20	TAJ-6(2) TAJ-7(2) TAJ-9(2) TAJ-10 SEE NOTE
-48715-B10	CAPACITOR, fixed: 10/10/36 NT-48715 w/40,000 mmf p/m 10%; temp coef ltr B.	RE48A132 16C40		16-C-34994-7566	N16-C-10585			CD	PL-633-59			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-247

RESTRICTED

RESTRICTED

SHEET 48 - 248

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48716	CAPAC TOR, fixed: mica; 80,000 mmf; 1,500 vdcw, 20 amp at 3000 kc, 35 amp at 1,000 kc, 27 am at 300 kc, 20 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low-loss ceramic case; one elliptical cast aluminum end-cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	10/10/36 RE48A132 16C40										
-48716-B5	CAPACITOR, fixed: NT-48716 w/80,000 mmf p/m 5%; temp coef ltr B. NOTE: TAJ-11; TAJ-13 thru TAJ-19.	10/10/36 RE48A132 16C40		16-C-35755-1897				CD	PL-848-59	CG	ML-7660174-28 766007-128 P-7762013-22 M-7463523-3	TAJ-6 TAJ-7 TAJ-9 TAJ-10 SEE NOTE
-48716-B10	CAPACITOR, fixed: NT-48716 w/80,000 mmf p/m 10%; temp coef ltr B.	10/10/36 RE48A132 16C40		16-C-35760-2377				CD	PL-848-59			
-48717	CAPAC T , fixed: mica; 90,000 mmf; 1,500 vdcw, 25 amp at 3000 kc, 40 amp at 1000 kc, 30 amp at 300 kc, 20 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low-loss ceramic case; one elliptical cast aluminum end-cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	10/10/36 RE48A132 16C40										
-48717-B5	CAPACITOR, fixed: NT-48717 w/90,000 mmf p/m 5%; tem coef ltr B. NOTE: TAJ-11 (3); TAJ-13 (3) thru TAJ-19 (3).	10/10/36 RE48A132 16C40		16-C-35966-2098	N16-C-10624			CD	PL-849-59	CG	ML-7660174-C29 7660607-0129 M-7463523-4 P-7762813-23	TAJ-6 (3) TAJ-7 (3) TAJ-9 (3) TAJ-10(3) SEE NOTE
-48717-B10	CAPACITOR, fixed: NT-48717 w/90,000 mmf p/m 10%; temp coef ltr B.	10/10/36 RE48A132 16C40		16-C-35971-2578	N16-C-10625			CD	PL-849-59			
-48718	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 2,000 vdcw; HS metal can; case 2 5/8" lg x 1 3/16" wd x 3 3/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 3/16" h located on to 1 1/8" c to c; no int gnd connection; two mtg fl on bottom of case ea w/ two 0.213" diam mtg holes 13/32" apart, 3 1/8" c to c	10/10/36 RE48A159 RE13A488		16-C-48803-4141				CG	9CE5A88	CG	X-5222640 rev1	TAJ-6
-48718-10	CAPACITOR, fixed: NT-48718 w/ 1 mf p/m 10%.	10/10/36 RE48A159 RE13A488		16-C-48824-4141	N16-C-11435		3DBL.2009 3DBL.2009-1	CG	9CE5A88	CRP	35-5058	SG-1 SG-2S

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-248

RESTRICTED

RESTRICTED

SHEET 48-249

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWE OR PART NO	EQUIPMENT USED IN
-48719	CAPACITOR, fixed: 10/10/36 paper dielectric; 1 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 7/8" lg x 1" wd x 2 1/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 3/16" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 0.213" diam mtg holes 13/32" apart 2 3/8" c to c.	RE48A159 RE13A488		16-C-48796-3366	N16-C-11417		3DB1-609-1	CG CG	9CE5A90 23F1	CG CG CRV	K-5222640rev1 K-7873047-4 K-860217-1rev5	TAQ-5 TAQ-6 TCN TCN-1 TCU TCU-1 VEA
-48720	CAPACITOR, fixed: 10/10/36 paper dielectric; 10 mf plus 10 minus 3%; 2,000 vdcw; HS metal can; case 3 7/8" lg x 4 5/8" wd x 4 3/4" h o/a; pyranol impr and filled; two ceramic ins screw type term 1 3/32" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 9/32" diam mtg holes 3 3/8" apart 4 1/2" c to c.	RE48A159 RE13A488		16-C-51843-7309	N16-C-11682-4			CG	9CR5A89	CG CBM CRV	K-5222640rev1 744-46 M-418141-37 sub0	TAJ-6 JK-3
-48721	CAPACITOR, fixed: 10/10/36 paper dielectric; 10 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 3 7/8" lg x 1 5/16" wd x 4 3/4" h o/a; oil impr and filled; two ceramic ins screw type term 1 3/16" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 0.213" diam mtg holes 13/32" apart 4 3/8" c to c. NOTE: TCM-1(5); TCM-2(3); TCN(5); TCR-1(5); TCU(2); TCU-1(2); WAF(3); YE; YE-2	RE48A159 RE13A488		16-C-51837-2615	N16-C-11669		3DB10-75	CG CG	9CR5A87 23F8	CG CBM CRV CG CG CRV CG	K-5222640rev1 744-263alt0 WW-8009141 K-7873047-1 M-7464792-4 K-860217-2 W-7350697-248	TAJ-6 TAQ-5 TAQ TBC-5(12) TBR(3) TBR-1(3) TCM(5) SEE NOTE
-48722	CAPACITOR, fixed: 10/10/36 paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 2 1/2" lg x 1 3/16" wd x 3 7/16" h o/a; oil impr and filled; two ceramic ins screw type term 7/8" h located on top 1 1/8" c to c; no int gnd connections; two mtg fl 1" wd on side of case, ea with a 3/16" diam mtg hole 3/4" c to c. NOTE: TCP-3 (4); TDF (4).	RE48A146 RE13A488		16-C-49936-5961	N16-C-11554-2			CG CD	9CR5A24 TJ-6040	CBM CAY CRM	744-37 7809148-3 CA-236	TBL-2 CQ-7 JK-3 CQG TCP(4) TCP-1(4) TCP-2(4) SEE NOTE
-48722-20	CAPACITOR, fixed: 10/10/36 RT-48722 w/4 mf p/m 20%.	RE48A146 RE13A488		16-C-49987-9197			3DB4-39-1	CD	TJ-6040	COL	930 3014 00	TDR-3(2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-249

RESTRICTED

RESTRICTED

SHEET 48 - 251

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFCR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48726	CAPACITOR, fixed: 10/10/36 mica; 30,000 mmf; 2,000 max vdcw, 12 amp at 3,000 kc, 12 amp at 1,000 kc, 10 amp at 300 kc, 5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48512.	RE48A131 16C40										
-48726-A5	CAPACITOR, fixed: 10/10/36 NT-48726 w/30,000 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-34726-5481				CD	PL-479-6			
-48726-B5	CAPACITOR, fixed: 10/10/36 NT-48726 w/30,000 mmf p/m 5%; temp coef ltr B. NOTE: TBL-6; TBL-7; TBL-10; TBL-11; TBL-12; TBL-13.	RE48A131 16C40		16-C-34726-5486	N16-C-10580			CD	PL-479-6L	CAY	7607471-75	TBL-2 TBL-3 TBL-5 SEE NOTE
-48727	CAPACITOR, fixed: 10/10/36 mica; 30,000 mmf; 1200 vdcw, 2500v DC test; case 1 25/32" lg max x 1 11/32" wd max x 3/4" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48727-A10	CAPACITOR, fixed: 10/10/36 NT-48727 w/30,000 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM60A303K	16-C-34731-2594				CD CSL	9-21030 XMW1.2-13-10			
-48727-B5	CAPACITOR, fixed: 10/10/36 NT-48727 w/30,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B303J	16-C-34726-2119		R16-C-10557-500		CD CSL CAW	9-21030 XMW1.2-13-5 1651-L	CRR	A26201-3	TAJ-8
-48727-B10	CAPACITOR, fixed: 10/10/36 NT-48727 w/30,000 mmf p/m 10%; temp coef ltr B. NOTE: TAJ-13(2) thru TAJ-19(2); TBC-5(2); TBL-2(2); TBL-3(2); TBL-5(2) thru TBL-7(2); TBL-10(2) thru TBL-13(2); TBU(5); TBU-1(5) thru TBU-4(5).	RE48A112 JAN-C-5	CM60B303K	16-C-34731-2599	N16-C-10576			CD CSL	9L-21030 XMBW-1.2-13-10	CAY CG CG CG CAY CAY	T-7606683-14 7660571-156 P-7762664-58 P-7764888-58 7607471-82 T-7609144-11 T-7607321-11	TAB-5(6) thru TAB-7(6) TAJ-7 TAJ-9 TAJ-10(2) TAJ-11(2) SEE NOTE
-48727-B20	CAPACITOR, fixed: 10/10/36 NT-48727 w/ 30,000 mmf p/m 20%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B303M	16-C-34736-5079	N16-C-10576-55			CD CSL	9L-21030 XMW1.2-13-20			
-48727-C5	CAPACITOR, fixed: 10/10/36 NT-48727 w/30,000 mmf p/m 5%; temp coef ltr C.	RE48A112 JAN-C-5	CM60C303J	16-C-34726-2124		R16-C-10558-500		CD CSL	9L-21030 XMBW1.2-13-10			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-251

RESTRICTED

RESTRICTED

SHEET 48 - 253

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48730	CAPACITOR, fixed: paper dielectric; 6 mf plus 10 minus 3%; 2,000 vdcw; HS metal can; case 3" lg x 3" wd x 4 5/8" h, o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 7/32" diam mtg holes 2" apart 3 1/2" c to c.	10/10/36 RE48A159 RE13A488		16-C-50703-4735	W16-C-11622	R16-C- 11660-500		CAY CAY	SO-35F810 FL	CAY	45-D-644-1 rev 5	
-48730-10	CAPACITOR, fixed: NT-48730 w/6 mf p/m 10%. NOTE: SR-5(2); TBL-3; TBL-5; TBL-6; TBL-7; TBL-12; TB	10/10/36 RE48A159 RE13A488 L-13.		16-C-50724-4735						CAY CAY	T-7605846-17 7607478-1	TBL-2 SR(2) SEE NOTE
-48731	CAPACITOR, fixed: paper dielectric; 6 mf plus 10 minus 3%; 1,500 vdcw; HS metal can; case 3" lg x 2 1/2" wd x 4 5/8" h, o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea with two 7/32" diam mtg holes 1 1/2" apart 3 1/2" c to c; add suffix indicating capacity tolerance in per cent.	10/10/36 RE48A159 RE13A488		16-C-50701-7943	W16-C-11621-7			CAY CAY	SO-35F813 FL	CAY	45-D-644-6 rev 5	
-48731-10	CAPACITOR, FIXED: Navy Type 48731 w/6 mfd p/m 10%. NOTE: QCJ-6; QCL-4; QCL-5; QCN-2; QCN-3; QCO-1; QCO-2; QCCQ;	10/10/36 RE48A159 RE13A488 QCQ-1; QCR;		16-C-50722-7943	MC-1(2); TBL-3; TB	L-5; TBL-6; TBL-7;	TBL-12; TBL-13.			CAY	7607478-2	TBL-2 QCJ-5 SEE NOTE
-48732	CAPACITOR, fixed: paper dielectric; 30 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 3" lg x 4 1/4" wd x 4 5/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 1 1/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/two 7/32" diam mtg holes 3" apart 3 1/2" c to c.	10/10/36 RE48A159 RE13A488		16-C-52597-4132	W16-C-11696			CAY CAY	SO-35787 FL	CAY	45-D-644-2 rev 5	
-48732-10	CAPACITOR, fixed: NT-48732 w/30 mf p/m 10%. NOTE: TBL-3; TBL-5; TBL-6; TBL-7; TBL-12; TBL-13.	10/10/36 RE 8A159 RE13A488		16-C-52618-4132				CAY CAY	FL S#1247903	CAY CAY	7610384-7 7607478-4	TBL-2 TBL-16(2) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-253

RESTRICTED

RESTRICTED

SHEET 48 - 254

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFG	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48733	CAPACITOR, fixed: 10/10/36 paper dielectric; 5 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 3" lg x 1" wd x 4 5/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 1 1/4" c to c; no int gnd connections; two mtg feet on bottom with two 0.19" diam holes 3 1/2" c to c.	RE48A146 RE13A488		16-C-50316-7992	N16-C-11605-1	R16-C-11657		CAY	SO-35F812 type FL	CAY	45-D-643-1	
-48733-10	CAPACITOR, fixed: 10/10/36 NT-48733 w/5 mf p/m 10%. NOTE: TBL-5; TBL-6; TBL-7; TBL-12; TBL-13.	RE48A146 RE13A488		16-C-50337-7992						CAY	7607478-3	TBL-2 TBL-3 SEE NOTE
-48734	CAPACITOR, fixed: 10/10/36 paper capacitor; 3 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 3" lg x 1" wd x 3 1/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 1 1/4" c to c; no internal connections; two mtg flanges 1" wd on side of case, ea w/a 7/32" diam mtg hole 3 1/2" c to c.	RE48A146 RE13A488		16-C-49556-7992	N16-C-11516	R16-C-1152*		CAY	SO-35F787 type FL	CAY	45-D-643-4	
-48734-10	CAPACITOR, fixed: 10/10/36 NT-48734 w/3 mf p/m 10%. NOTE: TBL-5; TBL-6; TBL-7; TBL-12; TBL-13.	RE48A146 E13A488		16-C-49577-7992						CAY	7607478-5	TBL-2 TBL-3 SEE NOTE:
-48735	CAPACITOR, fixed: 10/10/36 mica; 150,000 mmf; 2500 vdcw, operated at 1325v, 1 amp at 800 cyc, 25 amp at 3000 kc, 50 amp at 1000 kc, 40 amp at 300 kc, 25 amp at 100 kc; case 5" diam x 4" h; ceramic case; one fl elliptical end term ea end two 3/8" diam holes in ea term 5 3/4" c to c.	RE48A116 16C40										
-48735-B5	CAPACITOR, fixed: 10/10/36 NT-48735 w/150,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-36573-2753				CD	PL-512-51	CG	405A1-C45	TAJ-6
-48735-B10	CAPACITOR, fixed: 10/10/36 NT-48735 w/150,000 mmf p/m 10%; temp coef ltr B.	RE48A116 16C40		16-C-36578-3233	N16-C-10709			CD	PL-512-51			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-254

RESTRICTED

RESTRICTED

SHEET 48 - 255

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48736	CAPACITOR, fixed: 11/2/36 mica; 10,000 mmf; 2000 vdcw max, 10 amp at 3000 kc, 8 amp at 1000 kc, 5 amp at 300 kc, 2 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h, molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48352.	RE48A131 16C40										
-48736-B2	CAPACITOR, fixed: 11/2/36 NT-48736 w/10,000 mmf p/m 2%; temp coef ltr B. NOTE: QCL (2); QCL-7 (2); QGB (2).	RE48A131 16C40		16-C-33613-5206	W16-C-10507			CD CRV	PL-151-6 UC-3368	CRV	W-303083-151	KMB-1 (2) QCJ-2 (2) QCJ-8 (2) SEE NOTE:
-48736-D2	CAPACITOR, fixed: 11/2/36 NT-48736 w/10,000 mmf p/m 2%; temp coef ltr D. NOTE: TBL-6; TBL-7; TBL-10; TBL-11; TBL-12; TBL-13.	RE48A131 16C40		16-C-33613-5216		R16-C-10504-500		CD CAW CAW	PL-151-6L PL-1551-6H 1550-H-320	CAY	7607471-76	TBL-2 TBL-3 TBL-5 SEE NOTE:
-48736-F5	CAPACITOR, fixed: 11/2/36 NT-48736 w/10,000 mmf p/m 5%; temp coef ltr F.	RE48A131 16C40		16-C-33618-6706				CD	PL-151-6RB			
-48737	CAPACITOR, fixed: 11/2/36 mica; 1000 mmf; 6000 vdcw max, 10.0 amp at 3000 kc, 7.0 amp at 1000 kc, 4.0 amp at 300 kc, 2.0 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg and 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48737-A5	CAPACITOR, fixed: 11/2/36 NT-48737 w/1,000 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-31087-5060		R16-C-10128		CD	PL-463-6			TBL-2
-48737-B2	CAPACITOR, fixed: 11/2/36 NT-48737 w/1000 mmf p/m 2%; temp coef ltr B. NOTE: TBL-5 (3); TBL-6 (3); TBL-7 (3); TBL-10 (3); TBL-11 (3); TBL-12 (3); TBL-13 (3).	RE48A131 16C40		16-C-31082-4245				CD	PL-463-6L	CAY	7607471-95	TBL-2 (3) TBL-3 (3) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-255

RESTRICTED

RESTRICTED

SHEET 48 - 256

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E B O STOCK NO	A B O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48738	CAPACITOR, fixed: 11/2/36 mica; 300 mmf; 5000 max vdcw, 3 amp at 3000 kc; 1.2 amp at 1000 kc, 0.8 amp at 300 kc, 0.4 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48426.	RE48A131 16C40										
-48738-A5	CAPACITOR, fixed: 11/2/36 NF-48738 w/300 mmf p/m 5%; temp coef 1tr A.	RE48A131 16C40		16-C-29662-9118				CD	PL-294A-6			
-48738-B2	CAPACITOR, fixed: 11/2/36 NT-48738 w/300 mmf p/m 2%; temp coef 1tr B. NOTE: TBL-6; TBL-7; TBL-10; TBL-11; TBL-12; TBL-13.	RE48A131 16C40		16-C-29657-7643	N16-C-9995-5			CD	PL-294A-6L	CAY	7607471-89	TBL-2 TBL-3 TBL-5 SEE NOTE
-48738-B5	CAPACITOR, fixed: 11/2/36 NT-48738 w/300mmf p/m 5%; temp coef 1tr B.	RE48A131 16C40		16-C-29662-9123	N16-C-9995-7 N16-C-9995-6			CD	PL-294A-6L			
-48739	CAPACITOR, fixed: 11/2/36 mica; 450 mmf; 5000 vdcw max, 4 amp at 3000 kc, 2.5 amp at 1000 kc, 1.3 amp at 300 kc, 0.6 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48739-A5	CAPACITOR, fixed: 11/2/36 NT-48739 w/450 mmf p/m 5%; temp coef 1tr A.	RE48A131 16C40		16-C-30084-9518				CD	PL-646-6			
-48739-B2	CAPACITOR, fixed: 11/2/36 NT-48739 w/450 mmf p/m 2%; temp coef 1tr B. NOTE: TBL-10; TBL-11; TBL-12; TBL-13.	RE48A131 16C40		16-C-30079-8043	N16-C-10015			CD	PL-646-6L	CAY	7607471-90	TBL-2 TBL-3 TBL-5 thru TBL-7 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-256

RESTRICTED

RESTRICTED

SHEET 48 - 257

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48740	CAPACITOR, fixed: 11/2/36 mica; 6,000 mmf; 3,500 vdcw, 13 amp at 3,000 kc, 10 amp at 1,000 kc, 7 amp at 300 kc, 3 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 22/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48740-A5	CAPACITOR, fixed: 11/2/36 NT-48740 w/6000 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-32854-2373				CD	PL-439-6H	CBM	744-87	QC-7 QCG
-48740-B2	CAPACITOR, fixed: 11/2/36 NT-48740 w/6,000 mmf p/m 2%; temp coef ltr B. NOTE: TBL-5(3); TBL-6(3); TBL-7(3); TBL-10(3); TBL-11(3); TBL-12(3); TBL-13(3)	RE48A131 16C40		16-C-32848-9895				CD CAW	PL-439-6H 1550-M-321	CAY	7607471-77	TBL-2(3) TBL-3(3) SEE NOTE:
-48740-B5	CAPACITOR, fixed: 11/2/36 NT-48740 w/6,000 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-32854-2376	N16-C-10449-51			CD	PL-439-6L			
-48740-B2	CAPACITOR, fixed: 11/2/36 NT-48740 w/6,000 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-32848-9899	N16-C-10449-50	R16-C-10452-50		CD	PL-439-6L			
-48740-D5	CAPACITOR, fixed: 11/2/36 NT-48740 w/6,000 mmf p/m 5%; temp coef ltr D.	RE48A131 16C40		16-C-32854-2382				CD	PL-439-6H	CBM	744-87	JR-3
-48741	CAPACITOR, FIXED: 11/13/36 sulphur; 31 mmf; 7000 vdcw, 5 amp at 6000 kc; 3 7/8" lg x 1 7/16" diam; metal case; 1 screw term 5/8" lg incl ins on top, #6-32 thd stud.	RE48A269 16C40										
-48741-B5	CAPACITOR, fixed: 11/13/36 NT-48741 w/31 mmf p/m 5%; temp coef ltr B.	RE48A269 16C40		16-C-56454-5341	N16-C-11800-27			CRV	UC-3232	CRV	X-36229eub0	GP GP-2
-48742	CAPACITOR, fixed: 12/3/36 paper dielectric; 1 mf plus 10, minus 3%; 1500 vdcw, 4500v DC test; HS metal can; case 1 15/32" lg x 2 13/32" wd x 3 11/16" h c/a; oil impr and sealed; two por ins screw type term 15/16" h located on top, spaced 13/16" c to c; no int gnd connection; strap mtg not supplied.	RE48A139		16-C-48801-7155								GO-1 (2) GO-2 (2)
-48742-15	CAPACITOR, fixed: 12/3/36 NT-48742 w/1 mf p/m 15%.	RE48A139		16-C-48838-1060	N16-C-11433	R16-C-11437		CW	D-96966	CW	E80-609850-6	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-257

RESTRICTED

RESTRICTED

SHEET 48 - 258

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48743	CAPACITOR, fixed: 12/3/36 paper dielectric; 4 sect; 3.5 mf/2 mf/1 mf/500,000 mf plus 10 minus 3% ea sect; 250 vdcw ea sect, 800v DC test; HS metal can; case 4 15/16" lg x 1 1/2" wd x 3 5/8" h o/a; oil filled; five solder lug term located on bottom; no int gnd connections; two thd mtg studs 7/16" h on bottom, 4" c to c.	RE48A196 RE13A488		16-C-54851-9979	N16-C-12711			CW	D-97337	CW	ES-609851-2	GO-1 GO-2
-48744	CAPACITOR, fixed: 12/3/36 mica; 50 mf; 1,200 vdcw, 2,500v DC test; case 1 1/4" lg x 1 1/8" wd x 1 1/32" thk; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes 1/8" case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48744-A10	CAPACITOR, fixed: 12/3/36 NT-48744 w/50 mf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-27635-5208				CD	4-24050			GO-2
-48744-B2	CAPACITOR, fixed: 12/3/36 NT-48744 w/50 mf p/m 2%; temp coef ltr B. NOTE: RCX; TBX.	RE48A221 16C40		16-C-27625-3253	N16-C-9843-125			CD	4L	CG CW	F7762925-8 ES0-611146-1	GO-1 GO-2 SEE NOTE
-48744-B10	CAPACITOR, fixed: 12/3/36 NT-48744 w/50 mf p/m 10%; temp coef ltr B. NOTE: TDE-2; TDE-3.	RE48A221 16C40		16-C-27635-5213	N16-C-9843-126			CD CAN CAW	4L-24050	CR CAY CAY	A1728-23 T-7606408-14 7608227-74	TDE-2(2) TDE TDE-1 SEE NOTE:
-48745	CAPACITOR, fixed: 12/3/36 paper dielectric; 400,000 mf plus 10 minus 3%; 250 vdcw, 800 vdcw; HS metal can; case 3 9/16" h x 1 1/2" wd x 1 9/32" thk; wax impr and filled; two hooked wire term 1 1/8" c to c on top ctr line; no int gnd connections; one #8-32 thd mtg stud in ctr of top. NOTE: QCN-3 (12); QCN-4 (12); QCO-1 (12); QCO-2 (12); QCO-3 (12); QCS (13); QCS-1 (13); QCT (13); QCT-1 (13); WEB (11); QCN-2 (1,2)	RE48A212 RE13A488		16-C-46890-9642				CW CW CW	Type #230A Part #D-99846 LA-7001851ee19	CW	ES0-610772-3	QCJ-5(5) QCJ-6(8) QCJ-9(8) QCL-4(5) QCL-5 (8) QCL-8 (8) SEE NOTE
-48745-10	CAPACITOR, fixed: 12/3/36 NT-48745 w/400,000 p/m 10%. NOTE: QCJ-6 (12); QCJ-9 (12); QCL-4 (12); QCL-5 (12); QCL-8 (1,2); QCN-2 (12); QCN-3 (12); QCN-4 (12); QCO-1 (1,2); QCO-2 (12); QCO-3 (12); QCQ (13); QCR (13); WAB (13).	RE48A212 RE13A488		16-C-46911-9642				CW CW CW	D-99846 D-160801 230A	CW CBM	IA-7001851ee1 744-16A alt 0	GO-1 GO-2 QCJ-5(12) SEE NOTE:
-48746	CAPACITOR, fixed: 12/3/36 CANCELLED: replaced by NT-48790, this number to be reassigned.											

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-258

RESTRICTED

RESTRICTED

SHEET 48 - 259

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48747	CAPACITOR, fixed: 12/3/36 mica; 550 mmf; 5,000 vdcw, 5,000v, 60 cyc AC test, 7 amp at 3,000 kc, 4 amp at 1,000 kc, 2 amp at 300 kc, 0.8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48747-A5	CAPACITOR, fixed: 12/3/36 NT-48747 w/550 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-30269-6318				CW	D-99627	CW	ES-610773-1	GO-2 GO-1
-48747-B5	CAPACITOR, fixed: 12/3/36 NT-48747 w/550 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-30269-6323		R16-C-10029		CD	6LS			
-48748	CAPACITOR, fixed: 12/3/36 mica; 350 mmf; 5,000 vdcw, 5,000v 60 cyc AC test, 6 amp at 3,000 kc, 3.3 amp at 1,000 kc, 1.3 amp at 300 kc, 0.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48748-A5	CAPACITOR, fixed: 12/3/36 NT-48748 w/350 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-29794-8118				CW	D-99628	CW	ES-610773-1	GO-1 GO-2
-48748-B5	CAPACITOR, fixed: 12/3/36 NT-48748 w/350 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-29794-8123								
-48749	CAPACITOR, fixed: 12/3/36 mica; 250 mmf; 5,000 vdcw, 5,000 v 60 cyc AC test, 5 amp at 3,000 kc, 2.8 amp at 1,000 kc, 1 amp at 300 kc, 0.3 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48749-A5	CAPACITOR, fixed: 12/3/36 NT-48749 w/250 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-29478-3313				CW	D-99629	CW	ES-610773-1	GO-1 GO-2
-48749-B2	CAPACITOR, fixed: 12/3/36 NT-48749 w/250 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-29473-1843	N16-C-9979-3							
-48749-B5	CAPACITOR, fixed: 12/3/36 NT-48749 w/250 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-29478-3323	N16-C-9979-7			CRV	UC-3367	CRV	K-856829-3	TBL-4 TBL-8 TBL-9

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-259

RESTRICTED

RESTRICTED

SHEET 48 - 260

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48750	CAPACITOR, fixed: 12/3/36 mica; 200 mmf; 5000 vdcw, 5000v 60 cyc AC test, 4.5 amp at 3000 kc, 2.5 amp at 1000 kc, 0.8 amp at 300 kc; 0.3 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48750-A5	CAPACITOR, fixed: 12/3/36 NT-48750 w/200 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-29267-3118				CW	D-99630	CW	BS-610773-1	GO-2 (6) GO-1 (6)
-48750-B5	CAPACITOR, fixed: 12/3/36 NT-48750 w/200 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-29267-3123	N16-C-9972-3			CW	D-99631			
-48751	CAPACITOR, fixed: 12/3/36 mica; 150 mmf; 5000 vdcw, 5000v 60 cyc AC test; 3.3 amp at 3000 kc, 1.8 amp at 1000 kc, 0.68 amp at 300 kc, 0.24 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48751.	RE48A131 JAN-C-5										
-48751-A5	CAPACITOR, fixed: 12/3/36 NT-48751 w/150 mmf p/m 5%; temp coef ltr A.	RE48A131 JAN-C-5	CM76A151J	16-C-28977-1718				CW	D-99632			GO-2
-48751-C5	CAPACITOR, FIXED: 9/9/47 Navy Type 48751 w/5 mmf p/m 5%; temp coef ltr C.			16-C-25097-5801				CAN	K-1550	CDC	7568	RDO
-48752	CAPACITOR, fixed: 12/3/36 mica; 100 mmf; 5000 vdcw, 2.0 amp at 3000 kc; 1.0 amp at 1000 kc, 0.3 amp at 300 kc; 0.1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48752-A2	CAPACITOR, fixed: 12/3/36 NT-48752 w/100 mmf p/m 2%; temp coef ltr A.	RE48A131 16C40		16-C-28549-8838				CD CAW	PL-321-6 1550-300	CAY CAY CAY	7406467-1 T-7605247-5 T-7609856-41	GP-3 GP-4 TCE-2
-48752-A5	CAPACITOR, fixed: 12/3/36 NT-48752 w/100 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-28555-1318				CW CAW	D-99633 1550-301	CW CDE	BS-610773-1 2375-4	GO-2 (2) GO-1 (2) YB-2
-48752-B2	CAPACITOR, fixed: 12/3/36 NT-48752 w/100 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-28549-8843	N16-C-9941							
-48752-B5	CAPACITOR, fixed: 12/3/36 NT-48752 w/100 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-28555-1323	N16-C-9940-200			CD CAW	PL-321-6L 1550	COL CDE	906 3101 00rev0 S-2378-3	YR

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-260

RESTRICTED

RESTRICTED

SHEET 48 - 261

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S #WG OR PART NO	EQUIPMENT USED IN
-48753	CAPACITOR, fixed: 12/3/36 mica; 50 mmf; 5000 vdcw, 5000v 60 cyc AC test, 1.5 amp at 3000 kc; 0.5 amp at 1000 kc, 0.3 amp at 300 kc, 0.1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48753-A5	CAPACITOR, fixed: 12/3/36 NT-48753 w/50 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-27631-8318				CW	D-99634	CW	ES-610773-1	GO-1 (2) GO-2 (2)
-48753-B5	CAPACITOR, fixed: 12/3/36 NT-48753 w/50 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-27631-8323	N16-C-9847-44			CD	6L			
-48754	CAPACITOR, fixed: 12/3/36 mica; 500 mmf; 5000 vdcw, 7 amp at 3000 kc, 4 amp at 1000 kc, 2 amp at 300 kc, 0.7 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48754-A5	CAPACITOR, fixed: 12/3/36 NT-48754 w/500 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-30164-1718	N16-C-10022-100			CW	D-97637	CW	ES-610773-1	GO-1 GO-2
-48754-B5	CAPACITOR, fixed: 12/3/36 NT-48754 w/500 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-30164-1723	N16-C-10024-18			CD	6L			
-48755	CAPACITOR, fixed: 12/3/36 mica; 1500 mmf; 5,000 vdcw, 5,000v 60 cyc AC test, 8 amp at 3,000 kc, 7 amp at 1,000 kc, 3 amp at 300 kc, 1.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48755-A5	CAPACITOR, fixed: 12/3/36 NT-48755 w/1,500 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-31509-4117				CW	D-96952	CW	ES-610773-1	GO-1 (3) GO-2 (3)
-48755-B5	CAPACITOR, fixed: 12/3/36 NT-48755 w/1,500 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-31509-4122				CD	6L			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-261

RESTRICTED

RESTRICTED

SHEET 48 - 262

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48756	CAPACITOR, fixed: 12/11/36 paper dielectric; 2.5 mf plus 10 minus 3%; 250 vdcw, 800v AC test; HS metal can; case 3 1/2" h x 2 1/32" wd x 1 1/2" thk; wax impr and filled; two hooked wire term 1 1/16" c to c along top ctr line; no int grd connections; two 8-32 thd mtg studs 1" c to c on top ctr line.	RE48A213 RE13A488		16-C-49360-9147				CW	D-99700			
-48756-16	CAPACITOR, fixed: 12/11/36 NT-48756 w/2.5 mf p/m 16%.	RE48A213 RE13A488		16-C-49411-9910	N16-C-11498	R16-C-11520		CW	D-99700	CW	ES0-610772-6	GO-1 (2) GO-2 (2)
-48757	CAPACITOR, variable: 12/22/36 air; plate meshing type, single sect; 2 to 10 mmf; SLC; 3/4" lg x 15/16" wd x 1 7/32" h, shaft 9/32" diam x 5/16" lg; scdr adj w/hex nuts; three dull nickel plated brass plates; 360 deg rotation; iso-lantite insulation; post term for stator, lug term for rotor; single hole 9/32" diam for shaft, two mtg studs tapped for #4-36 screws in base on 21/32" mtg/c 31/64" from top. NOTE: DP-15; DP-16; DP-17; DP-18; DP-19.			16-C-58243-2647	N16-C-12217			CBC	APC-10	CRV	M-413394-1rev6	DP-4 DP-5 DP-6 DP-8 DP-10 DP-11 DP-12 DP-13 DP-14 SEE NOTE
-48758	CAPACITOR, variable: 12/22/36 air; plate meshing type single sect; 5.5 to 100 mmf; SLC; air gap 0.015", 500v RMS test; 1 7/16" lg x 15/16" wd x 1 7/32" h, shaft 9/32" diam x 5/16" lg o/a w/nut; scdr adj; twenty seven silver pl brass plates; 360 deg rotation; ceramic insulation; post term for stator, lug term for rotor on RE side; two mtg holes tapped for #4-36 screws on 21/32" mtg/c 31/64" from top. NOTE: JKA-2 thru JKA-5; JKA-5a; JKA-5b; JKA-5c; JKA-5d; JKA-5e; JKA-5f; JKA-5g; JKA-5h; JKA-5i; JKA-5j; JKA-5k; JKA-5l; JKA-5m; JKA-5n; JKA-5o; JKA-5p; JKA-5q; JKA-5r; JKA-5s; JKA-5t; JKA-5u; JKA-5v; JKA-5w; JKA-5x; JKA-5y; JKA-5z; JKA-5aa; JKA-5ab; JKA-5ac; JKA-5ad; JKA-5ae; JKA-5af; JKA-5ag; JKA-5ah; JKA-5ai; JKA-5aj; JKA-5ak; JKA-5al; JKA-5am; JKA-5an; JKA-5ao; JKA-5ap; JKA-5aq; JKA-5ar; JKA-5as; JKA-5at; JKA-5au; JKA-5av; JKA-5aw; JKA-5ax; JKA-5ay; JKA-5az; JKA-5ba; JKA-5bb; JKA-5bc; JKA-5bd; JKA-5be; JKA-5bf; JKA-5bg; JKA-5bh; JKA-5bi; JKA-5bj; JKA-5bk; JKA-5bl; JKA-5bm; JKA-5bn; JKA-5bo; JKA-5bp; JKA-5bq; JKA-5br; JKA-5bs; JKA-5bt; JKA-5bu; JKA-5bv; JKA-5bw; JKA-5bx; JKA-5by; JKA-5bz; JKA-5ca; JKA-5cb; JKA-5cc; JKA-5cd; JKA-5ce; JKA-5cf; JKA-5cg; JKA-5ch; JKA-5ci; JKA-5cj; JKA-5ck; JKA-5cl; JKA-5cm; JKA-5cn; JKA-5co; JKA-5cp; JKA-5cq; JKA-5cr; JKA-5cs; JKA-5ct; JKA-5cu; JKA-5cv; JKA-5cw; JKA-5cx; JKA-5cy; JKA-5cz; JKA-5da; JKA-5db; JKA-5dc; JKA-5dd; JKA-5de; JKA-5df; JKA-5dg; JKA-5dh; JKA-5di; JKA-5dj; JKA-5dk; JKA-5dl; JKA-5dm; JKA-5dn; JKA-5do; JKA-5dp; JKA-5dq; JKA-5dr; JKA-5ds; JKA-5dt; JKA-5du; JKA-5dv; JKA-5dw; JKA-5dx; JKA-5dy; JKA-5dz; JKA-5ea; JKA-5eb; JKA-5ec; JKA-5ed; JKA-5ee; JKA-5ef; JKA-5eg; JKA-5eh; JKA-5ei; JKA-5ej; JKA-5ek; JKA-5el; JKA-5em; JKA-5en; JKA-5eo; JKA-5ep; JKA-5eq; JKA-5er; JKA-5es; JKA-5et; JKA-5eu; JKA-5ev; JKA-5ew; JKA-5ex; JKA-5ey; JKA-5ez; JKA-5fa; JKA-5fb; JKA-5fc; JKA-5fd; JKA-5fe; JKA-5ff; JKA-5fg; JKA-5fh; JKA-5fi; JKA-5fj; JKA-5fk; JKA-5fl; JKA-5fm; JKA-5fn; JKA-5fo; JKA-5fp; JKA-5fq; JKA-5fr; JKA-5fs; JKA-5ft; JKA-5fu; JKA-5fv; JKA-5fw; JKA-5fx; JKA-5fy; JKA-5fz; JKA-5ga; JKA-5gb; JKA-5gc; JKA-5gd; JKA-5ge; JKA-5gf; JKA-5gg; JKA-5gh; JKA-5gi; JKA-5gj; JKA-5gk; JKA-5gl; JKA-5gm; JKA-5gn; JKA-5go; JKA-5gp; JKA-5gq; JKA-5gr; JKA-5gs; JKA-5gt; JKA-5gu; JKA-5gv; JKA-5gw; JKA-5gx; JKA-5gy; JKA-5gz; JKA-5ha; JKA-5hb; JKA-5hc; JKA-5hd; JKA-5he; JKA-5hf; JKA-5hg; JKA-5hh; JKA-5hi; JKA-5hj; JKA-5hk; JKA-5hl; JKA-5hm; JKA-5hn; JKA-5ho; JKA-5hp; JKA-5hq; JKA-5hr; JKA-5hs; JKA-5ht; JKA-5hu; JKA-5hv; JKA-5hw; JKA-5hx; JKA-5hy; JKA-5hz; JKA-5ia; JKA-5ib; JKA-5ic; JKA-5id; JKA-5ie; JKA-5if; JKA-5ig; JKA-5ih; JKA-5ii; JKA-5ij; JKA-5ik; JKA-5il; JKA-5im; JKA-5in; JKA-5io; JKA-5ip; JKA-5iq; JKA-5ir; JKA-5is; JKA-5it; JKA-5iu; JKA-5iv; JKA-5iw; JKA-5ix; JKA-5iy; JKA-5iz; JKA-5ja; JKA-5jb; JKA-5jc; JKA-5jd; JKA-5je; JKA-5jf; JKA-5jg; JKA-5jh; JKA-5ji; JKA-5jj; JKA-5jk; JKA-5jl; JKA-5jm; JKA-5jn; JKA-5jo; JKA-5jp; JKA-5jq; JKA-5jr; JKA-5js; JKA-5jt; JKA-5ju; JKA-5jv; JKA-5jw; JKA-5jx; JKA-5jy; JKA-5jz; JKA-5ka; JKA-5kb; JKA-5kc; JKA-5kd; JKA-5ke; JKA-5kf; JKA-5kg; JKA-5kh; JKA-5ki; JKA-5kj; JKA-5kl; JKA-5km; JKA-5kn; JKA-5ko; JKA-5kp; JKA-5kq; JKA-5kr; JKA-5ks; JKA-5kt; JKA-5ku; JKA-5kv; JKA-5kw; JKA-5kx; JKA-5ky; JKA-5kz; JKA-5la; JKA-5lb; JKA-5lc; JKA-5ld; JKA-5le; JKA-5lf; JKA-5lg; JKA-5lh; JKA-5li; JKA-5lj; JKA-5lk; JKA-5ll; JKA-5lm; JKA-5ln; JKA-5lo; JKA-5lp; JKA-5lq; JKA-5lr; JKA-5ls; JKA-5lt; JKA-5lu; JKA-5lv; JKA-5lw; JKA-5lx; JKA-5ly; JKA-5lz; JKA-5ma; JKA-5mb; JKA-5mc; JKA-5md; JKA-5me; JKA-5mf; JKA-5mg; JKA-5mh; JKA-5mi; JKA-5mj; JKA-5mk; JKA-5ml; JKA-5mm; JKA-5mn; JKA-5mo; JKA-5mp; JKA-5mq; JKA-5mr; JKA-5ms; JKA-5mt; JKA-5mu; JKA-5mv; JKA-5mw; JKA-5mx; JKA-5my; JKA-5mz; JKA-5na; JKA-5nb; JKA-5nc; JKA-5nd; JKA-5ne; JKA-5nf; JKA-5ng; JKA-5nh; JKA-5ni; JKA-5nj; JKA-5nk; JKA-5nl; JKA-5nm; JKA-5nn; JKA-5no; JKA-5np; JKA-5nq; JKA-5nr; JKA-5ns; JKA-5nt; JKA-5nu; JKA-5nv; JKA-5nw; JKA-5nx; JKA-5ny; JKA-5nz; JKA-5oa; JKA-5ob; JKA-5oc; JKA-5od; JKA-5oe; JKA-5of; JKA-5og; JKA-5oh; JKA-5oi; JKA-5oj; JKA-5ok; JKA-5ol; JKA-5om; JKA-5on; JKA-5oo; JKA-5op; JKA-5oq; JKA-5or; JKA-5os; JKA-5ot; JKA-5ou; JKA-5ov; JKA-5ow; JKA-5ox; JKA-5oy; JKA-5oz; JKA-5pa; JKA-5pb; JKA-5pc; JKA-5pd; JKA-5pe; JKA-5pf; JKA-5pg; JKA-5ph; JKA-5pi; JKA-5pj; JKA-5pk; JKA-5pl; JKA-5pm; JKA-5pn; JKA-5po; JKA-5pp; JKA-5pq; JKA-5pr; JKA-5ps; JKA-5pt; JKA-5pu; JKA-5pv; JKA-5pw; JKA-5px; JKA-5py; JKA-5pz; JKA-5qa; JKA-5qb; JKA-5qc; JKA-5qd; JKA-5qe; JKA-5qf; JKA-5qg; JKA-5qh; JKA-5qi; JKA-5qj; JKA-5qk; JKA-5ql; JKA-5qm; JKA-5qn; JKA-5qo; JKA-5qp; JKA-5qq; JKA-5qr; JKA-5qs; JKA-5qt; JKA-5qu; JKA-5qv; JKA-5qw; JKA-5qx; JKA-5qy; JKA-5qz; JKA-5ra; JKA-5rb; JKA-5rc; JKA-5rd; JKA-5re; JKA-5rf; JKA-5rg; JKA-5rh; JKA-5ri; JKA-5rj; JKA-5rk; JKA-5rl; JKA-5rm; JKA-5rn; JKA-5ro; JKA-5rp; JKA-5rq; JKA-5rr; JKA-5rs; JKA-5rt; JKA-5ru; JKA-5rv; JKA-5rw; JKA-5rx; JKA-5ry; JKA-5rz; JKA-5sa; JKA-5sb; JKA-5sc; JKA-5sd; JKA-5se; JKA-5sf; JKA-5sg; JKA-5sh; JKA-5si; JKA-5sj; JKA-5sk; JKA-5sl; JKA-5sm; JKA-5sn; JKA-5so; JKA-5sp; JKA-5sq; JKA-5sr; JKA-5ss; JKA-5st; JKA-5su; JKA-5sv; JKA-5sw; JKA-5sx; JKA-5sy; JKA-5sz; JKA-5ta; JKA-5tb; JKA-5tc; JKA-5td; JKA-5te; JKA-5tf; JKA-5tg; JKA-5th; JKA-5ti; JKA-5tj; JKA-5tk; JKA-5tl; JKA-5tm; JKA-5tn; JKA-5to; JKA-5tp; JKA-5tq; JKA-5tr; JKA-5ts; JKA-5tt; JKA-5tu; JKA-5tv; JKA-5tw; JKA-5tx; JKA-5ty; JKA-5tz; JKA-5ua; JKA-5ub; JKA-5uc; JKA-5ud; JKA-5ue; JKA-5uf; JKA-5ug; JKA-5uh; JKA-5ui; JKA-5uj; JKA-5uk; JKA-5ul; JKA-5um; JKA-5un; JKA-5uo; JKA-5up; JKA-5uq; JKA-5ur; JKA-5us; JKA-5ut; JKA-5uu; JKA-5uv; JKA-5uw; JKA-5ux; JKA-5uy; JKA-5uz; JKA-5va; JKA-5vb; JKA-5vc; JKA-5vd; JKA-5ve; JKA-5vf; JKA-5vg; JKA-5vh; JKA-5vi; JKA-5vj; JKA-5vk; JKA-5vl; JKA-5vm; JKA-5vn; JKA-5vo; JKA-5vp; JKA-5vq; JKA-5vr; JKA-5vs; JKA-5vt; JKA-5vu; JKA-5vv; JKA-5vw; JKA-5vx; JKA-5vy; JKA-5vz; JKA-5wa; JKA-5wb; JKA-5wc; JKA-5wd; JKA-5we; JKA-5wf; JKA-5wg; JKA-5wh; JKA-5wi; JKA-5wj; JKA-5wk; JKA-5wl; JKA-5wm; JKA-5wn; JKA-5wo; JKA-5wp; JKA-5wq; JKA-5wr; JKA-5ws; JKA-5wt; JKA-5wu; JKA-5wv; JKA-5ww; JKA-5wx; JKA-5wy; JKA-5wz; JKA-5xa; JKA-5xb; JKA-5xc; JKA-5xd; JKA-5xe; JKA-5xf; JKA-5xg; JKA-5xh; JKA-5xi; JKA-5xj; JKA-5xk; JKA-5xl; JKA-5xm; JKA-5xn; JKA-5xo; JKA-5xp; JKA-5xq; JKA-5xr; JKA-5xs; JKA-5xt; JKA-5xu; JKA-5xv; JKA-5xw; JKA-5xx; JKA-5xy; JKA-5xz; JKA-5ya; JKA-5yb; JKA-5yc; JKA-5yd; JKA-5ye; JKA-5yf; JKA-5yg; JKA-5yh; JKA-5yi; JKA-5yj; JKA-5yk; JKA-5yl; JKA-5ym; JKA-5yn; JKA-5yo; JKA-5yp; JKA-5yq; JKA-5yr; JKA-5ys; JKA-5yt; JKA-5yu; JKA-5yv; JKA-5yw; JKA-5yx; JKA-5yy; JKA-5yz; JKA-5za; JKA-5zb; JKA-5zc; JKA-5zd; JKA-5ze; JKA-5zf; JKA-5zg; JKA-5zh; JKA-5zi; JKA-5zj; JKA-5zk; JKA-5zl; JKA-5zm; JKA-5zn; JKA-5zo; JKA-5zp; JKA-5zq; JKA-5zr; JKA-5zs; JKA-5zt; JKA-5zu; JKA-5zv; JKA-5zw; JKA-5zx; JKA-5zy; JKA-5zz;	JKA-2 thru JKA-5; JKA-5a; JKA-5b; JKA-5c; JKA-5d; JKA-5e; JKA-5f; JKA-5g; JKA-5h; JKA-5i; JKA-5j; JKA-5k; JKA-5l; JKA-5m; JKA-5n; JKA-5o; JKA-5p; JKA-5q; JKA-5r; JKA-5s; JKA-5t; JKA-5u; JKA-5v; JKA-5w; JKA-5x; JKA-5y; JKA-5z; JKA-5aa; JKA-5ab; JKA-5ac; JKA-5ad; JKA-5ae; JKA-5af; JKA-5ag; JKA-5ah; JKA-5ai; JKA-5aj; JKA-5ak; JKA-5al; JKA-5am; JKA-5an; JKA-5ao; JKA-5ap; JKA-5aq; JKA-5ar; JKA-5as; JKA-5at; JKA-5au; JKA-5av; JKA-5aw; JKA-5ax; JKA-5ay; JKA-5az; JKA-5ba; JKA-5bb; JKA-5bc; JKA-5bd; JKA-5be; JKA-5bf; JKA-5bg; JKA-5bh; JKA-5bi; JKA-5bj; JKA-5bk; JKA-5bl; JKA-5bm; JKA-5bn; JKA-5bo; JKA-5bp; JKA-5bq; JKA-5br; JKA-5bs; JKA-5bt; JKA-5bu; JKA-5bv; JKA-5bw; JKA-5bx; JKA-5by; JKA-5bz; JKA-5ca; JKA-5cb; JKA-5cc; JKA-5cd; JKA-5ce; JKA-5cf; JKA-5cg; JKA-5ch; JKA-5ci; JKA-5cj; JKA-5ck; JKA-5cl; JKA-5cm; JKA-5cn; JKA-5co; JKA-5cp; JKA-5cq; JKA-5cr; JKA-5cs; JKA-5ct; JKA-5cu; JKA-5cv; JKA-5cw; JKA-5cx; JKA-5cy; JKA-5cz; JKA-5da; JKA-5db; JKA-5dc; JKA-5dd; JKA-5de; JKA-5df; JKA-5dg; JKA-5dh; JKA-5di; JKA-5dj; JKA-5dk; JKA-5dl; JKA-5dm; JKA-5dn; JKA-5do; JKA-5dp; JKA-5dq; JKA-5dr; JKA-5ds; JKA-5dt; JKA-5du; JKA-5dv; JKA-5dw; JKA-5dx; JKA-5dy; JKA-5dz; JKA-5ea; JKA-5eb; JKA-5ec; JKA-5ed; JKA-5ee; JKA-5ef; JKA-5eg; JKA-5eh; JKA-5ei; JKA-5ej; JKA-5ek; JKA-5el; JKA-5em; JKA-5en; JKA-5eo; JKA-5ep; JKA-5eq; JKA-5er; JKA-5es; JKA-5et; JKA-5eu; JKA-5ev; JKA-5ew; JKA-5ex; JKA-5ey; JKA-5ez; JKA-5fa; JKA-5fb; JKA-5fc; JKA-5fd; JKA-5fe; JKA-5ff; JKA-5fg; JKA-5fh; JKA-5fi; JKA-5fj; JKA-5fk; JKA-5fl; JKA-5fm; JKA-5fn; JKA-5fo; JKA-5fp; JKA-5fq; JKA-5fr; JKA-5fs; JKA-5ft; JKA-5fu; JKA-5fv; JKA-5fw; JKA-5fx; JKA-5fy; JKA-5fz; JKA-5ga; JKA-5gb; JKA-5gc; JKA-5gd; JKA-5ge; JKA-5gf; JKA-5gg; JKA-5gh; JKA-5gi; JKA-5gj; JKA-5gk; JKA-5gl; JKA-5gm; JKA-5gn; JKA-5go; JKA-5gp; JKA-5gq; JKA-5gr; JKA-5gs; JKA-5gt; JKA-5gu; JKA-5gv; JKA-5gw; JKA-5gx; JKA-5gy; JKA-5gz; JKA-5ha; JKA-5hb; JKA-5hc; JKA-5hd; JKA-5he; JKA-5hf; JKA-5hg; JKA-5hh; JKA-5hi; JKA-5hj; JKA-5hk; JKA-5hl; JKA-5hm; JKA-5hn; JKA-5ho; JKA-5hp; JKA-5hq; JKA-5hr; JKA-5hs; JKA-5ht; JKA-5hu; JKA-5hv; JKA-5hw; JKA-5hx; JKA-5hy; JKA-5hz; JKA-5ia; JKA-5ib; JKA-5ic; JKA-5id; JKA-5ie; JKA-5if; JKA-5ig; JKA-5ih; JKA-5ii; JKA-5ij; JKA-5ik; JKA-5il; JKA-5im; JKA-5in; JKA-5io; JKA-5ip; JKA-5iq; JKA-5ir; JKA-5is; JKA-5it; JKA-5iu; JKA-5iv; JKA-5iw; JKA-5ix; JKA-5iy; JKA-5iz; JKA-5ja; JKA-5jb; JKA-5jc; JKA-5jd; JKA-5je; JKA-5jf; JKA-5jg; JKA-5jh; JKA-5ji; JKA-5jj; JKA-5jk; JKA-5jl; JKA-5jm; JKA-5jn; JKA-5jo; JKA-5jp; JKA-5jq; JKA-5jr; JKA-5js; JKA-5jt; JKA-5ju; JKA-5jv; JKA-5jw; JKA-5jx; JKA-5jy; JKA-5jz; JKA-5ka; JKA-5kb; JKA-5kc; JKA-5kd; JKA-5ke; JKA-5kf; JKA-5kg; JKA-5kh; JKA-5ki; JKA-5kj; JKA-5kl; JKA-5km; JKA-5kn; JKA-5ko; JKA-5kp; JKA-5kq; JKA-5kr; JKA-5ks; JKA-5kt; JKA-5ku; JKA-5kv; JKA-5kw; JKA-5kx; JKA-5ky; JKA-5kz; JKA-5la; JKA-5lb; JKA-5lc; JKA-5ld; JKA-5le; JKA-5lf; JKA-5lg; JKA-5lh; JKA-5li; JKA-5lj; JKA-5lk; JKA-5ll; JKA-5lm; JKA-5ln; JKA-5lo; JKA-5lp; JKA-5lq; JKA-5lr; JKA-5ls; JKA-5lt; JKA-5lu; JKA-5lv; JKA-5lw; JKA-5lx; JKA-5ly; JKA-5lz; JKA-5ma; JKA-5mb; JKA-5mc; JKA-5md; JKA-5me; JKA-5mf; JKA-5mg; JKA-5mh; JKA-5mi; JKA-5mj; JKA-5mk; JKA-5ml; JKA-5mm; JKA-5mn; JKA-5mo; JKA-5mp; JKA-5mq; JKA-5mr; JKA-5ms; JKA-5mt; JKA-5mu; JKA-5mv; JKA-5mw; JKA-5mx; JKA-5my; JKA-5mz; JKA-5na; JKA-5nb; JKA-5nc; JKA-5nd; JKA-5ne; JKA-5nf; JKA-5ng; JKA-5nh; JKA-5ni; JKA-5nj; JKA-5nk; JKA-5nl; JKA-5nm; JKA-5nn; JKA-5no; JKA-5np; JKA-5nq; JKA-5nr; JKA-5ns; JKA-5nt; JKA-5nu; JKA-5nv; JKA-5nw; JKA-5nx; JKA-5ny; JKA-5nz; JKA-5oa; JKA-5ob; JKA-5oc; JKA-5od; JKA-5oe; JKA-5of; JKA-5og; JKA-5oh; JKA-5oi; JKA-5oj; JKA-5ok; JKA-5ol; JKA-5om; JKA-5on; JKA-5oo; JKA-5op; JKA-5oq; JKA-5or; JKA-5os; JKA-5ot; JKA-5ou; JKA-5ov; JKA-5ow; JKA-5ox; JKA-5oy; JKA-5oz; JKA-5pa; JKA-5pb; JKA-5pc; JKA-5pd; JKA-5pe; JKA-5pf; JKA-5pg; JKA-5ph; JKA-5pi; JKA-5pj; JKA-5pk; JKA-5pl; JKA-5pm; JKA-5pn; JKA-5po; JKA-5pp; JKA-5pq; JKA-5pr; JKA-5ps; JKA-5pt; JKA-5pu; JKA-5pv; JKA-5pw; JKA-5px; JKA-5py; JKA-5pz; JKA-5qa; JKA-5qb; JKA-5qc; JKA-5qd; JKA-5qe; JKA-5qf; JKA-5qg; JKA-5qh; JKA-5qi; JKA-5qj; JKA-5qk; JKA-5ql; JKA-5qm; JKA-5qn; JKA-5qo; JKA-5qp; JKA-5qq; JKA-5qr; JKA-5qs; JKA-5qt; JKA-5qu; JKA-5qv; JKA-5qw; JKA-5qx; JKA-5qy; JKA-5qz; JKA-5ra; JKA-5rb; JKA-5rc; JKA-5rd; JKA-5re; JKA-5rf; JKA-5rg; JKA-5rh; JKA-5ri; JKA-5rj; JKA-5rk; JKA-5rl; JKA-5rm; JKA-5rn; JKA-5ro; JKA-5rp; JKA-5rq; JKA-5rr; JKA-5rs; JKA-5rt; JKA-5ru; JKA-5rv; JKA-5rw; JKA-5rx; JKA-5ry; JKA-5rz; JKA-5sa; JKA-5sb; JKA-5sc; JKA-5sd; JKA-5se; JKA-5sf; JKA-5sg; JKA-5sh; JKA-5si; JKA-5sj; JKA-5sk; JKA-5sl; JKA-5sm; JKA-5sn; JKA-5so; JKA-5sp; JKA-5sq; JKA-5sr; JKA-5ss; JKA-5st; JKA-5su; JKA-5sv; JKA-5sw; JKA-5sx; JKA-5sy; JKA-5sz; JKA-5ta; JKA-5tb; JKA-5tc; JKA-5td; JKA-5te; JKA-5tf; JKA-5tg; JKA-5th; JKA-5ti; JKA-5tj; JKA-5tk; JKA-5tl; JKA-5tm; JKA-5tn; JKA-5to; JKA-5tp; JKA-5tq; JKA-5tr; JKA-5ts; JKA-5tt; JKA-5tu; JKA-5tv; JKA-5tw; JKA-5tx; JKA-5ty; JKA-5tz; JKA-5ua; JKA-5ub; JKA-5uc; JKA-5ud; JKA-5ue; JKA-5uf; JKA-5ug; JKA-5uh; JKA-5ui; JKA-5uj; JKA-5uk; JKA-5ul; JKA-5um; JKA-5un; JKA-5uo; JKA-5up; JKA-5uq; JKA-5ur; JKA-5us; JKA-5ut; JKA-5uu; JKA-5uv; JKA-5uw; JKA-5ux; JKA-5uy; JKA-5uz; JKA-5va; JKA-5vb; JKA-5vc; JKA-5vd; JKA-5ve; JKA-5vf; JKA-5vg; JKA-5vh; JKA-5vi; JKA-5vj; JKA-5vk; JKA-5vl; JKA-5vm; JKA-5vn; JKA-5vo; JKA-5vp; JKA-5vq; JKA-5vr; JKA-5vs; JKA-5vt; JKA-5vu; JKA-5vv; JKA-5vw; JKA-5vx; JKA-5vy; JKA-5vz; JKA-5wa; JKA-5wb; JKA-5wc; JKA-5wd; JKA-5we; JKA-5wf; JKA-5wg; JKA-5wh; JKA-5wi; JKA-5wj; JKA-5wk; JKA-5wl; JKA-5wm; JKA-5wn; JKA-5wo; JKA-5wp; JKA-5wq; JKA-5wr; JKA-5ws; JKA-5wt; JKA-5wu; JKA-5wv; JKA-5ww; JKA-5wx; JKA-5wy; JKA-5wz; JKA-5xa; JKA-5xb; JKA-5xc; JKA-5xd; JKA-5xe; JKA-5xf; JKA-5xg; JKA-5xh; JKA-5xi; JKA-5xj; JKA-5xk; JKA-5xl; JKA-5xm; JKA-5xn; JKA-5xo; JKA-5xp; JKA-5xq; JKA-5xr; JKA-5xs; JKA-5xt; JKA-5xu; JKA-5xv; JKA-5xw; JKA-5xx; JKA-5xy; JKA-5xz; JKA-5ya; JKA-5yb; JKA-5yc; JKA-5yd; JKA-5ye; JKA-5yf; JKA-5yg; JKA-5yh; JKA-5yi; JKA-5yj; JKA-5yk; JKA-5yl; JKA-5ym; JKA-5yn; JKA-5yo; JKA-5yp; JKA-5yq; JKA-5yr; JKA-5ys; JKA-5yt; JKA-5yu; JKA-5yv; JKA-5yw; JKA-5yx; JKA-5yy; JKA-5yz; JKA-5za; JKA-5zb; JKA-5zc; JKA-5zd; JKA-5ze; JKA-5zf; JKA-5zg; JKA-5zh; JKA-5zi; JKA-5zj; JKA-5zk; JKA-5zl; JKA-5zm; JKA-5zn; JKA-5zo; JKA-5zp; JKA-5zq; JKA-5zr; JKA-5zs; JKA-5zt; JKA-5zu; JKA-5zv; JKA-5zw; JKA-5zx; JKA-5zy; JKA-5zz;	DP-4 thru DP-6 DP-8 DP-10 thru DP-19 JK-2B JK-5 JK-8 JK-9 JK-1 SEE NOTE									
-48759	CAPACITOR, fixed: 12/22/36 mica; 33 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	RE48A238 16C40										
-48759-B10	CAPACITOR, fixed: 12/22/36 NT-48759 w/33 mmf p/m 10%; temp coef 1tr B. NOTE: DP-8; DP-10; DP-11; DP-12; DP-13; DP-14; DP-15; DP-16; DP-17.	RE48A238 16C40		16-C-27186-5052	N16-C-9840			CRV	M-17	CRV	K-850253-12 M-60342-517rev3	DP-4 thru DP-6 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-262

RESTRICTED

RESTRICTED

SHEET 48 - 263

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFOR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48760	CAPACITOR, fixed: 12/22/36 mica; 39 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	RE48A238 16C40										
-48760-B10	CAPACITOR, fixed: 12/22/36 NT-48760 w/39 mmf p/m 10%; temp coef ltr B. NOTE: DP-8; DP-10; DP-11; DP-12; DP-13; DP-14; DP-15; DP-16; DP-17.	RE48A238 16C40		16-C-27371-1852	N16-C-9843-25			CRV	Model H Code M-18	CRV CRV	K-850253-13 M-80342-518	DP-4 thru DP-6 SEE NOTE
-48761	CAPACITOR, fixed: 12/22/36 mica; 100 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	RE48A238 16C40										
-48761-B10	CAPACITOR, fixed: 12/22/36 NT-48761 w/100 mmf p/m 10%; temp coef ltr B. NOTE: DP-17; TBS; TBS-1 thru TBS-8.	RE48A238 16C40		16-C-28558-1852	N16-C-9923-20			CRV	Model H Code M-26	CRV CRV CRV	K-850253-14 M-80342-526 M-86012-547	DP-4 thru DP-6 DP-8 DP-10 thru SEE NOTE
-48761-D5	CAPACITOR, fixed: 12/22/36 NT-48761 w/100 mmf p/m 5%; temp coef ltr D.	RE48A238 16C40		16-C-28553-1382	N16-C-9923-21			CRV	Model H			
-48762	CAPACITOR, fixed: 12/24/36 electrolytic; two sect; 20/5 mf; 25/25 vdcw, max surge minus 40v; working temp range minus 40°C to plus 65°C; case 1.78" lg x 0.905" wd x 1.5" h; ES metal case; two solder lug term 0.266" h on bottom spaced 0.5" c to c; neg term gnd internally; two mtg ft on bottom, 0.149" diam hole in ea, on 2.125" mtg/c	RE48A351 RE13A549		16-C-21457-1832		R16-C-9674				CBY	3563-2-E	
-48763	CAPACITOR, fixed: 12/24/36 paper dielectric; 3 sect; 500,000 mmf plus 10 minus 3%; 100 vdcw ea sect, 500v DC flash test; ES metal can; case 1 3/4" lg x 7/8" wd x 1 1/2" h; oil impr and filled; three solder lug term 5/16" h on bottom of case 1/2" from c to c; all sect int gnd; two mtg ears 3/8" wd integral w/bottom of case w/two 3/16" diam mtg holes on 2 1/8" c to c.	RE48A138 RE13A488		16-C-54570-4105	N16-C-11378-121			CD				GF-11 RU-16
-48763-10	CAPACITOR, fixed: 12/24/36 NT-48763; 500,000 mmf p/m 10% ea sect.	RE48A138 RE13A488		16-C-54587-8109	N16-C-11378-120			CD CBY		CW	3562	GF-11 RU-16

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-263

RESTRICTED

RESTRICTED

SHEET 48 - 264

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48764	CAPACITOR, FIXED: 12/29/36 mica; 1000 mmf; 2500 vdcw, 5000 vdc; case 1 1/4" lg x 1 1/8" wd x 23/64" h; molded low loss bakelite case; 2 term solder lug w/1 hole ea 0.173" diam located on ends spaced 1 3/4" c to c; 2 tab mtg holes 0.144" diam located on ends spaced 1 5/16" c to c; add suffix indicating capacity tolerance in per cent.	RE48A221 JAN-C-5										
-48764-A10	CAPACITOR, fixed: 12/29/36 NT-48764 w/1,000 mmf p/m 10%; temp coef ltr A. NOTE: SO-1; SO-2; SO-8; SO-13.	RE48A221 JAN-C-5	CM45A102K	16-C-31091-6112	N16-C-10093-1-2		3K4510211	CD CSL	4 XQW2.5-21-10	CRR CRP	A-1728-3 35-5087	SO SO-a SEE NOTE
-48764-B2	CAPACITOR, FIXED: 3/10/48 Navy Type 48764 w/1000 mmf p/m 2%; temp coef letter B.	JAN-C-5	CM45B102G	16-C-31081-4157								TS-587/U TS-587A/U
-48764-B5	CAPACITOR, fixed: 12/29/36 NT-48764 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B102J	16-C-31086-5632	N16-C-10091-100		3K4510222	CD	4L			
-48764-B10	CAPACITOR, fixed: 12/29/36 NT-48764 w/1000 mmf p/m 10%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B102K	16-C-31091-6114	N16-C-10091-200			CD CD CAW CD	4L 4-25D1-LL 1447L-001 4LS52012	CG CCI	P-7761328-3rev1	TBO TBO-1 TDD-2
-48764-B20	CAPACITOR, FIXED: 2/24/50 Navy Type 48764 w/1000 mmf p/m 20%; temp coef ltr B.	RE48A221 JAN-C-5		16-C-31096-8595	N16-C-10093-2							
-48765	CAPACITOR, fixed: 12/29/36 mica; 5,000 mmf; 600 vdcw, 1000 vdc; 1 1/4" lg x 1 1/8" wd x 23/64" thk max; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c; for replacement use NT-482938.	RE48A221 JAN-C-5										
-48765-A2	CAPACITOR, fixed: 12/29/36 NT-48765 w/5,000 mmf p/m 2%; temp coef ltr A.	RE48A221 JAN-C-5	CM45A502G	16-C-32689-3791				CD	4LS-12050	CRR	A13753-14	TBO LD-4
-48765-A10	CAPACITOR, fixed: 12/29/36 NT-48765 w/5,000 mmf p/m 10%; temp coef ltr A. NOTE: LP-2; LP-3; LP-4; SG(11); SG-1(3); SG-2a(3).	RE48A221 JAN-C-5	CM45A502K	16-C-32699-5751				CD CAW CSL CSL	4-12050 1445 XQW.6-25-10 M4C-1239	CGZ CRP	0315 35-5011	LAG LAG-1 LP LP-1 SEE NOTE
-48765-B5	CAPACITOR, fixed: 12/29/36 NT-48765 w/5,000 mmf p/m 5%; temp coef ltr B. NOTE: SC-4; SK-2; SK-3; SF-1M; SX; VC; VG; VG-3.	RE48A221 JAN-C-5	CM45B502J	16-C-32694-5276	N16-C-10404		3DA5-74.2	CD CAW	4L C	CG	K-8680806-1rev0	SC-2 SC-3 SEE NOTE
-48765-B10	CAPACITOR, fixed: 12/29/36 NT-48765 w/5,000 mmf p/m 10%; temp coef ltr B. NOTE: SC-4; SK-3 (2); SF-1M; SX; TBO; TBO-1; TCX (4); VG; VC-1; VG-3.	RE48A221 JAN-C-5	CM45B502K	16-C-32699-5756	N16-C-10406		3DA5-23	CD CSF CAN	4LS-12050 4-6D5-LL Type C	CG CG CG	P-7762925-46rev0 K-35J292-2rev3 P-7761328-18rev1	RBD (4) SC-2 (2) SC-3 SEE NOTE

SHEET 48-264

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 265

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48766	CAPACITOR, fixed: 12/29/36 mica; 3,000 mmf; 500 vdcw, 1,000v DC test; 1 1/32" max lg x 4 1/64" max wd x 1 1/32" thk; molded bakelite case; one wire lead 1 1/2" lg at ea end.	RE48A151 16C40										
-48766-A2	CAPACITOR, fixed: 12/29/36 NT-48766 w/3,000 mmf p/m 2%; temp coef ltr A.	RE48A151 16C40		16-C-29655-7775				CD CSL CAN	3W MK-5-33 J	CG	P-7761328-11 rev4	TBO TBO-1
-48766-B5	CAPACITOR, fixed: 12/29/36 NT-48766 w/3,000 mmf p/m 5%; temp coef ltr B.	RE48A151 16C40		16-C-29660-9260	N16-C-9990-6			CD CSL CAN	3WL MKB JL			
-48767	CAPACITOR, fixed: 12/29/36 mica; 400 mmf; 500 vdcw, 1,000v DC test; 1 1/32" max lg x 4 1/64" max wd x 1 1/32" thk; molded bakelite case; one wire lead 1 1/2" lg at ea end.	RE48A151 16C40										
-48767-A2	CAPACITOR, fixed: 12/29/36 NT-48767 w/400 mmf p/m 2%; temp coef ltr A.	RE48A151 16C40		16-C-29919-5775				CD CSL CAN	3W MK J	CG	P-7761328-12 rev4	TBO TBO-1
-48768	CAPACITOR, fixed: 12/29/36 mica; 500 mmf; 500 vdcw, 1,000v DC test; 1 1/32" max lg x 4 1/64" max wd x 1 1/32" thk max; molded bakelite case; one wire lead 1 1/2" lg at ea end.	RE48A151 16C40										
-48768-A20	CAPACITOR, fixed: 12/29/36 NT-48768 w/500 mmf p/m 20%; temp coef ltr A.	RE48A151 16C40		16-C-30172-4815				CD CSL CAN	3W MK J			
-48768-B10	CAPACITOR, fixed: 12/29/36 NT-48768 w/500 mmf p/m 10%; temp coef ltr B. NOTE: TBX-4; TBX-4a.	RE48A151 16C40		16-C-30167-2340	N16-C-10016-8			CD	3W-13050-LL	CG CBZ	P-7761328-15 CO-733	TBO (2) TBO-1 (2) SEE NOTE
-48769	CAPACITOR, fixed: 12/29/36 mica; 700 mmf; 500 vdcw, 1,000v DC test; 1 1/32" max lg x 4 1/64" max wd x 1 1/32" thk max; molded bakelite case; one wire lead 1 1/2" lg at ea end.	RE48A151 16C40										
-48769-A2	CAPACITOR, fixed: 12/29/36 NT-48769 w/700 mmf p/m 2%; temp coef ltr A.	RE48A151 16C40		16-C-30578-9731				CD CSL CAN	3W MK J	CG	P-7761328-13rev4	TBO TBO-1
-48769-B2	CAPACITOR, fixed: 12/29/36 NT-48769 w/700 mmf p/m 2%; temp coef ltr B.	RE48A151 16C40		16-C-30578-9780	N16-C-10066			CD CSL CAN	3WL MKB JL			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-265

RESTRICTED

RESTRICTED

SHEET 48 - 266

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48770	CAPACITOR, fixed: 12/29/36 mica; 6,000 mmf; 500 vdcw, 100V DC test; 1 1/32" max lg x 41/64" max wd x 3/16" thk max; molded bakelite case; one wire lead 1 1/2" lg at ea end.	RE48A151 JAN-C-5										
-48770-A10	CAPACITOR, fixed: 1/29/36 NF-48770 w/6,000 mmf p/m 10%; temp coef ltr A.	RE48A151 JAN-C-5	CM40A602K	16-C-32857-7091				CSL	MOB-1403-10	CRP	35-5131	SO-4 SO-1 M SO-12N
-48770-A 0	CAPACITOR, fixed: 12/29/36 NF-48770 w/6,000 mmf p/m 20%; temp coef ltr A.	RE48A151 JAN-C-5	CM40A602M	16-C-32862-9571				CD CSL CAN	3W MK J			
-48770-B10	CAPACITOR, fixed: 12/29/36 NF-48770 w/6,000 mmf p/m 10%; temp coef ltr B. NOTE: TBX-5 (14); TBX-8 (6).	RE48A151 JAN-C-5	CM40B602K	16-C-32857-7096	N16-C-10443			CD CD CSL	1W5D5-LL 3W12060-LL MWBW-1241	CG CEZ CGQ CBF	P-7761328-5 rev4 CO-723 B-00-723 31554 rev2	TBO (12) TBO-1 (12) TBX-4 (18) TBX-4a(18) SEE NOTE
-48770-05	CAPACITOR, FIXED: 11/4/47 Navy Type 48770 w/6000 mmf p/m 5%; temp coef letter C.	RE48A151C		16-C-32852-6647				CSL		CFT		DAK-2 DAK-3
-48771	CAPACITOR, fixed: 12/29/36 mica; 5 mmf; 500 vdcw; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148 JAN-C-5										
-48771-A10	CAPACITOR, fixed: 12/29/36 NF-48771 w/5 mmf p/m 10%; temp coef ltr A.	RE48A148 JAN-C-5	CM20A050K	16-C-25102-6271				CD CAW CSL CMR	5W-5Q5 1468 MO 0	CGZ	0311	DAH LAG LAG-1
-48771-B10	CAPACITOR, fixed: 12/29/36 NF-48771 w/5 mmf p/m 10%; temp coef ltr B. NOTE: TBX-5; TBX-8; TCK thru TCK-7; TCJ(2); TCJ-1(2)	RE48A148 JAN-C-5	CM20B050K	16-C-25102-6276	N16-C-9765			CAW CD CSL CMR CSL CD	1468LS 5WLS MOBW-1401-10 OXM MGSW 5W-5Q5-LL	CAY CRB CG CRR CEZ CGQ CG	T-7608011-83sub5 CD-1033-2100C P-77613284rev15 C56306-050 7608011-P83 CO-732 M-7463930-P13	RAP (3) RBM-1thru RBM-5 TBO TBO-1 TBX-4 TBX-4a SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-266

RESTRICTED

RESTRICTED

SHEET 48 - 267

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48771-B20	CAPACITOR, fixed: 12/29/36 NT-48771 w/5 mmf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B050M	16-C-25107-8756	N16-C-9766	R16-C-9802	3X2005024	CD CAW CMR CSL CSL	SWLS 1468LS OXM MOBW MOBW	CFE CCT CG CW CHE	15.115 7608010-3 P-7761328-21 rev15 CO-674	MK-16 (2) RBM-1 (4) thru RBM-5 (4) RBS (4) RBS-1 (4) SEE NOTE
-48771-C2	CAPACITOR, FIXED: 3/1/48 Navy Type 48771 w/5 mmf p/m 0.1 mmf; temp coef ltr C.	RE48A148		16-C-25092-4322				CD	SRS	CANQ	A-113	OF-2
-48771-C10	CAPACITOR, fixed: 12/29/36 NT-48771 w/5 mmf p/m 10%; temp coef ltr C.	RE48A148 JAN-C-5	CM20C050K	16-C-25102-6281				CAW CD CSL CMR CER CSL	1469 SRS MOBOW PO MLK5 MOBW	CRV CRV	W-303314-283 P-720473-1rev19	QCJ-8 QCL-7 RBB (3) RBB-1 (3) RBB-2 (3) RBC (3) SEE NOTE
-48771-C20	CAPACITOR, fixed: 12/29/36 NT-48771 w/5 mmf p/m 20%; temp coef ltr C.	RE48A148 JAN-C-5	CM20C050M	16-C-25107-8761			3D9005-40	CER CAW CD CSL CMR	K 1469 SRS MOBOW PO	CRM		DAE DAE-1
-48771-D5	CAPACITOR, fixed: 12/29/36 NT-48771 w/5 mmf p/m 5%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D050J	16-C-25097-5806	N16-C-9763			CD CAW CSL CMR	SRS 1469 MOBOW PO	CG CRV CRV CML	M-7463969-18rev3 P-720538-14rev30 W-303314-344 24160	LS-1 (3) WRA (2)
-48771-D10	CAPACITOR, fixed: 12/29/36 NT-48771 w/5 mmf p/m 10%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D050K	16-C-25102-6286	N16-C-9765-1			CD CAW CSL CMR CMF	SRS 1469 MOBOW PO 603J	CG CRB CFW	M-7463969-2rev3 CD-1034-2188C C-1084	RBD RCD TCX
-48771-D20	CAPACITOR, fixed: 12/29/36 NT-48771 w/5 mmf p/m 20%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D050M	16-C-25107-8766	N16-C-9765-3 N16-C-9763			CD CAW CSL CMR	SRS 1469 MOBOW PO	CEM CFT CAY CML	744-349 alto 7608011-104 17102	DAO (2) DAO-1 (2) LS-1 RBM-1 (4) SEE NOTE
-48772	CAPACITOR, fixed: 12/29/36 CANCELLED: use NT-48674.	16C48						CD	SM	CG	P-7761328-7	TBO

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-267

RESTRICTED

RESTRICTED

SHEET 48 - 268

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48773	CAPACITOR, fixed: 12/29/36 paper dielectric; two sect; 4 mf plus 10 minus 3% ea sect; 200 vdcv sect #1, 25 vdcv sect #2; ES metal can; case 2 3/8" h x 1 3/4" wd x 3 5/16" lg o/a; oil impr and filled; two stud type term 3/8" h located on end spaced 3/4" c to c; both sect int gnd; three mtg ears ea w/a 0.180" diam hole, two at one end 1" c to c, 3 11/16" from one at other end.	RE48A200 RE13A488		16-C-54091-5810				CD	VC641			
-48773-10	CAPACITOR, fixed: 12/29/36 NT-48773 w/4 mf p/m 10% ea sect. NOTE: TBX-4a; TEX-5 (2).	RE48A200 RE13A488		16-C-54094-1010				CD	VC-641	CG CHZ CGQ	M-7461876rev0 CO-750 C-CO-750	TBO TBO-1 TEX-4 SEE NOTE
-48774	CAPACITOR, fixed: 12/29/36 paper dielectric; 20,000 mmf plus 10 minus 3%; 400 vdcv; ES metal can; 1 9/32" lg x 7/16" diam; oil filled and impr; one axial wire lead; one term int gnd.	RE48A163 RE13A488										
-48774-10	CAPACITOR, fixed: 12/29/36 NT-48774 w/20,000 mmf p/m 10%. NOTE: TBX-4; THX-4a.	RE48A163 RE13A488		16-C-43113-7345	R16-C-11010			CD	BC-1250	CG CHZ	7870431-1rev3 CO-747	TBO TBO-1 SEE NOTE
-48775	CAPACITOR, fixed: 12/29/36 paper dielectric; two sect; 500,000/500,000 mmf plus 10 minus 3%; 300/300 vdcv; ES metal can; 1 15/16" h x 1 5/16" wd x 1 1/16" thk; pyronal impr and filled; two solder lug term on bottom ea w/one 0.078" diam hole, 5/8" c to c; one side of ea sect common and gnd to case; two integral mtg ft ea w/a 5/32" wd slot 1 15/16" c to c on bottom; superseded by NT-48775-A.	RE48A175 RE13A488		16-C-53625-3710				CG	K-5204555	CG CG	K-3977195 rev8 K-7870208-1 rev1	
-48775-A	CAPACITOR, fixed: 1/17/41 paper dielectric; two sect; 500,000/500,000 mmf plus 10, minus 3%; 400/400 vdcv; ES metal can; 1 15/16" h x 1 5/16" wd x 1 1/16" thk; pyronal impr and filled; two ins solder lug term 5/8" c to c on bottom; one side of ea sect common and gnd to case; two integral mtg ft each with a 5/32" wd slot 1 15/16" c to c on bottom; same as NT-48775 except 400 vdcv.	RE48A175 RE13A488		16-C-53570-4210		R16-C-11371		CG	25P188	CEM	744-539	GA (2) SG (2)
-48775-A10	CAPACITOR, fixed: 1/17/41 NT-48775-A w/500,000/500,000 mmf p/m 10%. NOTE: TBX-4 (2); TBX-4a (2).			16-C-53626-7656				CG	K-5204555	CG CHZ	K-7870208-1 CO-748	TBO (2) TBO-1 (2) SEE NOTE

SHEET 48-268

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 269

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48776	CAPACITOR, fixed: 12/29/36 paper dielectric; 1 mf plus 10, minus 3%; 400 vdcw; HS metal can; case 2 5/8" lg x 1.031" diam; oil filled and impr; one axial wire lead; one term gnd int.	E48A163 RE13A488										
-48776-10	CAPACITOR, fixed: 12/29/36 NT-48776 w/1 mf p/m 10%.	RE48A163 RE13A488		16-C-48814-3656	N16-C-11396			CD	VC-564A	CG	7870490-1rev2	TBO
	NOTE: TBX-4; TBX-4a.							CD	5F64	CHE	CO-749	TBO-1 SEE NOTE
-48777	CAPACITOR, FIXED: 12/29/36 paper dielectric; 2 mfd plus 10, minus 3%; 600 vdcw, 330 vacw at 60 cys; HS metal can; case dimen 1 13/16" lg x 1 1/16" wd x 2 3/4" h; 2 solder lug type term 5/8" h located on top spaced 13/16" c to c on par pillars; Dykanol "A" impr and filled; no int gnd connections.	E48A110 E13A488D		16-C-49176-2852			3DB2-18	CG	26F406	CG	E-7371523 rev 0	TBO
	NOTE: TCJ-2; TCJ (5); TCK-7 (5); TCK-1 (5) thru TCK-6 (5).							CG	26F52232	CG	X-3912264 rev 5	LAF (2)
								CG	9CE1A154	CRV	M-422477-1 sub C	LAF-3 (2)
								CG	23F102	CABL	95658-1	SR-2 (11)
								CIE		CG	P7763476-P2	TBO-1 TCJ TCJ-1 NOTE
-48777-10	CAPACITOR, fixed: 12/29/36 NT-48777 w/2 mf p/m 10%.	RE48A110 RE13A488		16-C-49197-2852	N16-C-11488			CBV	A7649	COL	930 7822 00	TCZ (2)
	NOTE: UE-1 (2).							CD	EG-3020		rev D8595	SA
								CG	26F406	CRV	M-422477-1aub0	SA-2
								CMR	CSL-48	CG	K-35J756-1 rev0	SW (2)
								CG	9CE1A154	CHE	CO-758	TBX-4
										CG	K-52J566-2rev0	TBX-4a SEE NOTE
-48777-20	CAPACITOR, FIXED: 12/29/36 Navy Type 48777 w/2 mfd p/m 20%.	RE48A110 RE13A488D		16-C-49227-7299	N16-C-11488-5			CD	EG-3020	COL	930 7824 00	TCZ
											rev D8595	TCZ-1 (2) TCZ-2 (2)
-48778	CAPACITOR, fixed: 1/7/37 paper dielectric; 4 mf plus 10 minus 3%; 500 vdcw; HS metal can; case 4 3/4" h x 1 3/4" wd x 1" d o/a; PYRANOL filled; two stud term 1/2" h located on top, spaced 3/4" c to c; no int gnd connections.	E48A110 E13A488		16-C-49935-1178				CG	9CE A145	CG	7870656	TBO (2)
								CSF	2526-5	CHE	CO-1003-3	BL-1 (2) thru EL-5 (2) BL-6 TBO-1 (2)
-48778-10	CAPACITOR, fixed: 1/7/37 NT-48778 w/4 mf p/m 10%.	RE13A488 RE48A110		16-C-49956-1178	N16-C-11546			CSF	2526-5	CHE	CO-700 see C-6	BM-1
	NOTE: OAP-1 (2); TBX-4 (2); TBX-4a (2); TBX-5.							CG	9CE1A145	CG	CO-757	OAP (2) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-269

RESTRICTED

RESTRICTED

SHEET 48 - 270

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48779	CAPACITOR, fixed: mica; 75 mmf; 1250 vdcv, 2500v AC test; case 1 7/32" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug term 5/8" lg, 7/16" c to c on top; two mtg ft at bottom, ea w/slot 5/32" wd, one located 13/64" in front of case ctr, one located 13/64" in front, slot ctr lines 1 19/32" apart.	1/14/37 RE48A214 16C40										
-48779-A5	CAPACITOR, fixed: NT-48779 w/75 mmf p/m 5%; temp coef ltr A.	1/14/37 RE48A214 16C40		16-C-28131-7930		R16-C-9885		CW	D-99837	CW	E80-609851-3rev3	
-48779-A10	CAPACITOR, fixed: NT-48779 w/75 mmf p/m 10%; temp coef ltr A.	1/14/37 RE48A214 16C40		16-C-28136-B 10								GO-1 GO-2
-48780	CAPACITOR, fixed: mica; 175 mmf; 1250 vdcv, 2500v AC test; case 1 7/32" lg x 1 3/32" wd x 1 3/8" h; sheet metal case; two lug term 5/8" lg 7/16" c to c on top; two mtg ft at bottom, ea w/slot 5/32" wd, one located 13/64" in back of case ctr, one 13/64" in front slot ctr lines 1 19/32" apart.	1/14/37 RE48A214 16C40										
-48780-A5	CAPACITOR, fixed: NT-48780 w/175 mmf p/m 5%; temp coef ltr A.	1/14/37 RE48A214 16C40		16-C-29107-7730				CW	D-99838	CW	E80-609851-3rev3	GP-1 GP-2
-48781	CAPACITOR, fixed: mica; 20,000 mmf; 3,000 vdcv, 20 amp at 3000 kc, 22 amp at 1000 kc, 21 amp at 600 kc, 18 amp at 300 kc, 12 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; low loss ceramic case; one elliptical cast-aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c.	1/25/37 RE48A132 16C40										
-48781-B5	CAPACITOR, fixed: NT-48781 w/20,000 mmf p/m 5%; temp coef ltr B. NOTE: TAJ-13; TAJ-14; TAJ-15; TAJ-16; TAJ-17; TAJ-18; TAJ-19.	1/25/37 RE48A132 16C40		16-C-34331-2442				CD	PL-889-59L	CG	P-7763250-24rev1 ML-7660174-C32 7660607-C132 M-7463523-5 P-7762813-18	TAJ-6 TAJ-7 TAJ-9 TAJ-10 TAJ-11 SEE NOTE:
48781-B10	CAPACITOR, fixed: NT-48781 w/20,000 mmf p/m 10%; temp coef ltr B.	1/25/37 RE48A132 16C40		16-C-34336-2922	R16-C-10565			CD	PL-889-59L			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-270

RESTRICTED

RESTRICTED

SHEET 48 - 271

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48782	CAPACITOR, fixed: 2/2/37 mica; 250 mmf; 500 vdcv, 1000v DC test; case 1 1/32" lg x 4 1/64" max wd x 1 1/32" thk; molded bakelite case one wire lead 1 1/2" lg at ea end.	RE48A151 16C40										
-48782-A20	CAPACITOR, fixed: 2/2/37 NT-48782 w/250 mmf p/m 20%; temp coef ltr A.	RE48A151 16C40		16-C-29486-6459				CD CSL CAN	3W ME J			
-48782-B10	CAPACITOR, fixed: 2/2/37 NT-48782 w/250 mmf p/m 10%; temp coef ltr B. NOTE: TBX-4a; TBX-5(2).	RE48A151 16C40		16-C-29481-3940	N16-C-9974-5			CD CSL	3W13025-LL CGZ CGQ	CG CGQ	P-7761328-10rev4 CO-728 B-CO-728	TBO TBO-1 TBX-4 SEE NOTE
-48783	CAPACITOR, FIXED: 2/2/37 mica; 20 mmf; 500 vacv; body 5 1/64" lg x 1 5/32" wd x 7/32" d; molded low loss phenolic body; 2 axial wire leads; add suffix indicating capacity tolerance in per cent.	RE48A148 JAN-C-5										
-48783-A10	CAPACITOR, fixed: 2/2/37 NT-48783 w/20 mmf p/m 10%; temp coef ltr A.	RE48A148 JAN-C-5	CM20A200K	16-C-26738-1071				CSL CD CAW CMR	M0-1405-10 5W 1463 0	CBM CRP	744-574 35-5132	50-3 50-4 SY (2)
-48783-B5	CAPACITOR, fixed: 2/2/37 NT-48783 w/20 mmf p/m 5%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B200J	16-C-26732-9596	N16-C-9794		3E2020022	CD CAW CSL CMR CMR	5WLS 1468LS MOEM-1405-5 OXM MOCW	CG CG	P-7761328-19 K-273362-107-1	SK SK-1M SK-2
-48783-B10	CAPACITOR, fixed: 2/2/37 NT-48783 w/20 mmf p/m 10%; temp coef ltr B. NOTE: TEX-5; ME-2Mod2 (2); ME-33 (3); SU-1 (2).	RE48A148 JAN-C-5	CM20B200K	16-C-26738-1076	N16-C-9795			CD CAW CSL CMR CD	5WLS 1468LS MOEM-1405-10 OXM 5W-5Q2-1L	CBM CG CRV CEZ CGQ CBM	744-604 P-7761328-19rev4 P-720473-29rev19 CO-737 B-CO-971 744-574	SU (2) OBV TBO TBO-1 TBX-4 TBX-4a SEE NOTE:
-48783-B20	CAPACITOR, fixed: 2/2/37 NT-48783 w/20 mmf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B200M	16-C-26743-3556	N16-C-9795-11			CD CAW CSL CMR	5WLS 1468LS MOEM-1405-20 OXM			MK-16 Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-271

RESTRICTED

RESTRICTED

SHEET 48 - 272

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48783-C5	CAPACITOR, fixed: 2/2/37 NT-48783 w/20mmf p/m 5%; temp coef ltr C.	RE48A148 JAN-C-5	CM20C200J	16-C-26732-9601	N16-C-9794-200	R16-C-9813-14-500	3K2020032	CER CMR CAW CD CSL	X FO 1469 5R MOSCW-20	CCT COL	7608011-111 912 4203 10rev3	DAE DAE-1 RBS RBS-1 RBS-2 SEE NOTE:
-48783-D2	CAPACITOR, FIXED: 4/12/48 Navy Type 48783 w/20 mmf p/m 2%; temp coef ltr D.	RE13A389 RFA8A148		16-C-26727-8127				CD	5R			
-48783-D5	CAPACITOR, fixed: 2/2/37 NT-48783 w/20 mmf p/m 5%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D200J	16-C-26732-9606	N16-C-9795-1	R16-C-9813-15		CD CAW CSL CMR CER CMF CW	5RS 1469 MOSDW FO MIX-20 603M	CG CRV CAY	M-7463969-20rev3 P-720539-1rev30 7608011-111	RBA(4) RBA-1 (4) RBB RBS-1 RBB-2 RBC RBC-1 SEE NOTE:
-48783-D10	CAPACITOR, fixed: 2/2/37 NT-48783 w/20 mmf p/m 10%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D200K	16-C-26738-1091	N16-C-9795-16	R16-C-9813-25		CD CAW CSL CMR CSL	5RS 1469 MOSDW-20 FO MOSW14-05	CG CALC CW CFN	M-7463969-4rev3 744-574 SS-682032-4 C-1070	OBV RAX-1 (2) RBD RCD (3) SU-1 (2) SEE NOTE:
-48783-D20	CAPACITOR, fixed: 2/2/37 NT-48783 w/20 mmf p/m 20%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D200M	16-C-26743-3566	N16-C-9795-17			CD CAW CSL CMR	5RS 1469 MOSDW FO			
-48784	CAPACITOR, variable: 2/8/37 air; plate meshing type single sect; 1.9 to 2.1 min, 2.9 to 3.1 max mmf; SLC; air gap adj to meet cap requirements; 25/32" lg x 15/16" wd x 1 7/32" h shaft 1/4" diam x 1" lg; two cnd pl brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor; single hole 9/32" diam for shaft, two mtg holes tapped for #4-40 screws in base 21/32" mtg/c, 31/64" from top.			16-C-57974-5001				CHC CRK	APC type B Modified	CG CHEZ CGQ	P-7761345-9rev19 CO-816 C-CO-816	TBO TBO-1 TBX-4 TBX-4a TBX-5

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-272

RESTRICTED

RESTRICTED

SHEET 48 - 273

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48785	CAPACITOR, variable: 2/8/37 air; plate meshing type single sect; 3 to 13.8 mmf; SLC; 0.015" air gap; 1" lg x 15/16" wd x 1 7/32" h shaft 9/32" diam x 2 1/32" lg; extension shaft adj; four cad plated brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RH side; single 9/32" hole for shaft, two mtg holes tapped for #4-40 screws in base on 2 1/32" mtg/c, 3 1/64" from top.			16-C-58420-9495				CHC	APC type B Modified	CG CGQ	F-7761345-11 rev25 CO-808	TBO TBO-1 TBX-4 TBX-4a
-48785-A	CAPACITOR, variable: 8/21/44 air; plate meshing type single sect; 3 to 13.8 mmf; SLC; 0.015" air gap; 29/32" lg x 15/16" wd x 1 7/32" h shaft 9/32" diam x 1" lg; extension shaft adj; four cad plated brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RH side; single 9/32" hole for shaft, two mtg holes tapped for #4-40 thd screws in base on 2 1/32" mtg/c, 3 1/64" from top; same as NI-48785 except for 1" shaft length.			16-C-58420-9475				CHC	APC type B	CG	F-7767343-1rev0	TBK-7 TD-2
-48786	CAPACITOR, variable: 2/8/37 air; plate meshing type single sect; 3 to 25 mmf; SLC; 0.030" air gap; 19/32" lg x 15/16" wd x 1 7/32" lg shaft 5/32" diam x 3/16" lg w/1/8" bushing and 1/4" diam x 9/32" lg collar; scdr adj; thirteen silver pl brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RH side; two mtg holes tapped for #4-40 thd screws on 2 1/32" mtg/c, 3 1/64" from top.			16-C-58974-4001				CHC	APC type C Modified	CG CGZ CGQ	F-7761345-6rev19 CO-814 C-CO-814	TBO TBO-1 TBX-4 TBX-4a TBX-5 TBZ
-48787	CAPACITOR, variable: 2/8/37 air; plate meshing type single sect; 3.9 to 50 mmf; SLC; 0.015" air gap; 3/32" lg x 15/16" wd x 1 7/32" h, shaft completely housed in housing shaft 1/8" lg x 5/32" OD, split bushing 13/32" lg x 5/16" OD incl 5/16" hex nut for locking on 1/4"-32 thd bushing, shoulder 9/32" diam x 3/32" lg; scdr adj; fourteen dull nickel pl brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on LH side; two mtg holes tapped for #4-40 screws on 2 1/32" mtg/c, 3 1/64" from top. NOTE: RBP (3); TBO (6); TBO-1 (6); TBX-4 (6); TBX-4a (6); TBX-5 (6); TCX; TCX-1 thru TCX-7.			16-C-59718-4826	N16-C-12231		3D9050-11	CHC	APC-50-C Modified	CRV CG CGZ CGQ	W-303275-163 rev16 F-7761345-2 rev16 CO-509 CO-809	LP (6) LP-1 (6) LP-2 (6) LP-3 (6) LP-4 (6) LR (3) LR-1 (3) LR-2 (3) LR-3 (3) QBR QCU (2) SEE NOTE

SHEET 48-273

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 274

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48787-A	CAPACITOR, variable: CANCELLED same as NT-48787. NOTE: LP-2 (6); LP-3 (6); LP-4 (6); LR (3); LR-1 (3);	5/9/39	LR-2 (3);	16-C-59718-4846				CEC	APC-50-C	CAG CRV	10A2 #303275-163	LP (6) LP-1 (6) SEE NOTE:
-48787-B	CAPACITOR, variable: air; plate meshing type single sect; 3.9 to 50 muf; SLC; 0.015" air gap; 1 3/32" lg x 15/16" wd x 1 7/32" h, shaft completely encl in housing, shaft 1/8" lg x 5/32" OD, split bushing 13/32" lg x 5/16" OD, incl 5/16" hex lock nut on 1/4"-32 thd bushing, shoulder 9/32" diam x 3/32" lg; scdr adj; fourteen dull nickel pl brass plates; 360 deg rotation; isolantite ins; post term for stator, lug term for rotor on top; two mtg holes tapped for #4-40 screws on 21/32" mtg/c, 31/64" from top; same as NT-48787 except terminal is on opposite side of mtg.	4/1/46		16-C-59718-4846				CEC	APC-50-C Modified	CG	P-7761345-18 rev25	
-48788	CAPACITOR, variable: air; plate meshing type single sect; 4.5 to 75 muf; SLC; 0.015" air gap; 1 1/8" lg x 15/16" wd x 1 7/32" h, shaft completely housed in housing, shaft 1/8" lg x 5/32" OD, split bushing 13/32" lg x 15/16" OD, incl 5/16" hex lock nut on 1/4"-32 thd bushing, shoulder 9/32" diam x 3/32" lg; scdr adj; twenty brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RH side; two mtg holes tapped for #4-40 screws on 21/32" mtg/c, 31/64" from top.	2/8/37		16-C-60233-6626				CEC CRK	APC type C Modified	CG C Q	P-7761345-7rev19 CO-810 C-C-810	TBO TBO-1 TRX-4
-48789	CAPACITOR, fixed: misc; 2,000 muf; 2500 wdcw, 5000 wdc; case 1 1/4" lg x 1 1/8" wd x 29/64" thk max; molded low-loss bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	2/15/37	RE48A221 JAN-C-5									
-48789-B5	CAPACITOR, fixed: NT-48789 w/2,000 muf p/m %; temp coef ltr B. NOTE: DAB-1 (2); DAB-3 (2).	2/15/37	RE48A221 JAN-C-5	CM50B202J	16-C-31798-7498	N16-C-10241-71		CD	4IS-13020	COL	910 2203 10	GP-3 DAB (2) SEE NOTE: Con't

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-274

RESTRICTED

RESTRICTED

SHEET 48 - 275

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48789-B10	CAPACITOR, fixed: NT-48789 w/2,000 mmf p/m 10%; temp coef ltr B.	2/15/37 RE48A221 JAN-C-5	CM50B202K	16-C-31803-7978	N16-C-10255			CD CSL	4L XQBW2.5-22	CG	K-35J292-5	SM-1
-48789-B20	CAPACITOR, fixed: NT-48789 w/2,000 mmf p/m 20%; temp coef ltr B.	2/15/37 RE48A221 JAN-C-5	CM50B202M	16-C-31809-1458	N16-C-10255-1		3DA2-120.2	CD CAN	4IS HLS-50	COL	950 2203 40 rev D4743	TCZ (2) TCZ-1 (2)
-48790	CAPACITOR, fixed: quartz; 2100 mmf p/m 2%; 3,000v AC peak; 5 1/16" h x 2 7/8" wd x 2 1/4" lg metal can; two ins post term on top, 3/4" h, 1 1/4" c to c; four mtg studs on top #8-32 thd on 1 3/8" x 2 1/8" mtg/c.	2/23/37			N16-C-10294			CW	D-97340	CW	ES0-610772-4	GO-1 GO-2
-48791	CAPACITOR, variable: air; plate meshing type single sect; 5.5 to 100 mmf; SIC; 0.015" air gap; 1 13/32" lg x 15/16" wd x 1 7/32" h, shaft completely housed in housing 17/32" lg x 13/64" diam w/ 1/4"-32 thd x 3/16" lg split bushing, shoulder 9/32" diam x 3/32" lg, lock nut; scdr adj; twenty seven brass plates; 360 deg	3/3/37			N16-C-12237	R16-C-12060		CBC CRK	APC type C Modified	CG CBZ COQ	F-7761345-3rev19 C0-811 C-C0-811	TBO (3) TBO-1 (3) TBX-4 (2) TBX-4a (2) TBX-5 (2)
-48792	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 300 vdcw; BS metal can; case 2 1/8" lg x 2 23/64" wd x 3 1/8" h; castor oil impr and filled; two screw type term rotation; isolantite insulation; post term for stator; lug term for rotor on RH side; two mtg holes tapped for #4-40 screws on 21/32" mtg/c, 31/64" from top. 5/8" h on bottom of case 1" c to c; no int gnd connections; two mtg fl 2 1/8" lg integral w/bottom of case w/four 0.199" diam mtg holes on 2 5/8" x 1 1/4" mtg/c; superseded by NT-48792-A. NOTE: DP-14 (3); DP-16 (3).	3/3/37 RE48A137 RE13A488		16-C-49931-8460	N16-C-11543			CRV	73039-508	CRV CRV	M-420071-1 M-421827-1 sub0	DP-4 (3) DP-5 (3) DP-6 (3) DP-8 (3) DP-9 (3) DP-10 (3) DP-12 (3) DP-13 (3) SEE NOTE:

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-275

RESTRICTED

RESTRICTED

SHEET 48 - 276

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48792-A	CAPACITOR, fixed: 10/10/38 paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 2 1/8" lg x 2 23/64" wd x 3 1/8" h o/a; castor oil impr and filled; two screw type term 5/8" h on bottom of case 1" c to c; no int gnd connections; two mtg fl 2 1/8" lg integral w/bottom of case w/four 0.199" diam mtg holes on 2 5/8" x 1 1/4" mtg/c.	RE48A137 RE13A488		16-C-49936-5294				CRV				
-48792-A10	CAPACITOR, fixed: 10/10/38 NT-48792-A w/4 mf p/m 10%.	RE48A137 RE13A488		16-C-49957-5299	N16-C-11586							
-48793	CAPACITOR, fixed: 3/3/37 paper dielectric; 900,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 15/16" h x 1 3/8" wd x 3/4" thk; oil impr and filled; two stud and nut term 5/8" c to c on top; no int gnd connections; integral mtg bkt w/two ft w/ 5/32" wd mtg slots 1 7/8" c to c.	RE48A160 RE13A488		16-C-47276-1340				CRV	72039-502	CRV	P-721074-9 M-420071-2 M-421827-2 rev 0	DP-4 DP-5 DP-6 DP-8 DP-9 thru DP-19
-48793-15	CAPACITOR, fixed: 3/3/37 NT-48793 w/500,000 mmf p/m 15%.	RE48A160 RE13A488		16-C-47276-1340	N16-C-11357							
-48794	CAPACITOR, fixed: 3/3/37 paper dielectric; 250,000 mmf plus 10 minus 3%; 800 vdcw; HS metal can; case 1 3/8" lg x 3/4" wd x 1 7/8" h; oil filled; two solder lug type term on top spaced 5/8" c to c; no int gnd connections; two mtg fl ea w/one 5/32" mtg slot, 1 7/8" c to c; for replacement use NT-48802.	RE48A160 RE13A488		16-C-46328-4644	N16-C-11341-62			CRV	72039-504	CRV	M-421827-3rev0	
-48794-15	CAPACITOR, fixed: 3/3/37 NT-48794 w/250,000 mmf p/m 15%; for replacement use NT-48802. NOTE: DP-8; DP-10 thru DP-19.	RE48A160 RE13A488		16-C-46366-1562				CRV	72024-506	CRV	M-420071-3	DP-4 DP-5 DP-6 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-276

RESTRICTED

RESTRICTED

SHEET 46 - 277

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48795	CAPACITOR, fixed: 3/3/37 paper dielectric; 2 sect; 125,000 mmf plus 10 minus 3% ea sect; 500 vdcw, 500 vacw between case and term #1, 500 vdcw, 500 vacw between case and term #2; BS metal can; case 1 7/8" h x 1 3/8" wd x 3/4" d o/a; castor oil filled; two stud term 3/4" h located on top, spaced 5/8" c to c; both sections int gnd; bkt mtg not supplied. NOTE: DQ-1 (2); TBS (5); TBS-1 (5) thru TBS-8 (5).	RE48A110 RE13A488		16-C-53227-3330	N16-C-11336-11			CRV	72039-505	CRV	M-420071-4alt8	DP-4 (2) DP-5 (2) DP-6 (2) DP-8 (2) DP-10 (2) thru DP-17 (2) DP-19 (2) SEE NOTE:
-48795-10	CAPACITOR, fixed: 3/3/37 MT-48795 w/125,000 mmf p/m 10% ea sect.	RE48A110 RE13A488		16-C-53227-3530				CRV	72039-522			
-48796	CAPACITOR, fixed: 3/3/37 paper dielectric; 7500 mmf plus 10 minus 3%; 500 vdcw, 350 vacw; BS metal can; case 1 1/16" h x 1 3/8" wd x 3/4" d o/a; castor oil filled; two stud term 1/2" h located on top, spaced 5/8" c to c; no int gnd connections; bkt mtg not supplied. NOTE: DP-12 (2) thru DP-19 (2); DQ-1; ME-26 Mod 3; M	RE48A110 RE13A488		16-C-42144-9734	N16-C-10859			CRV	72039-506	CRV CRV	F-720555-15alt10 M-420071-5 M-421827-5 sub C	DP-4 (2) DP-5 (2) DP-6 (2) DP-8 (2) DP-10 DP-11 (2) SEE NOTE
-48796-10	CAPACITOR, fixed: 3/3/37 MT-48796 w/7500 mmf p/m 10%.	RE48A110 RE13A488		16-C-42165-9734				CRV	72039-523	CRV	720555-65alt10	
-48797	CAPACITOR, fixed: 3/3/37 mica; 560 mmf; 500 vdcw; case 1 13/32" lg x 1/2" wd x 3/8" thk; thermoplastic case; two axial wire leads.	RE48A248 16C40										
-48797-B10	CAPACITOR, fixed: 3/3/37 MT-48797 w/560 mmf p/m 10%; temp coef ltr B. NOTE: DP-6; DP-8; DP-10 (3); DP-11 (3) thru DP-17 (3).	RE48A248 16C40		16-C-30299-1593	N16-C-10034			CRV	M-512	CRV	K-850253-1	DP-4 DP-5 SEE NOTE:
-48798	CAPACITOR, fixed: 3/3/37 mica; 1,000 mmf; 500 vdcw; case 1 13/32" lg x 1/2" wd x 3/8" thk; thermoplastic case; two axial wire leads.	RE48A248 16C40										
-48798-B5	CAPACITOR, fixed: 3/3/37 MT-48798 w/1,000 mmf p/m 5%; temp coef ltr B. NOTE: DP-5 (3); DP-6 (3); DP-8 (3); DP-10 (3) thru D	RE48A248 16C40		16-C-31085-4106	N16-C-10084-4			RV	1000	CRV	K-850253-2	DC-1 DP-4 (3) SEE NOTE:
-48799	CAPACITOR, fixed: 3/3/37 mica; 1800 mmf; 500 vdcw; case 1 13/32" lg x 1/2" wd x 3/8" thk; thermoplastic case; two axial wire leads.	RE48A248 16C40										
-48799-B5	CAPACITOR, fixed: 3/3/37 MT-48799 w/1800 mmf p/m 5%; temp coef ltr B. NOTE: DP-6 (6); DP-8 (6); DP-10 (6); DP-11 (6); DP-12 (6); DP-13 (6); DP-14 (3); DP-15 (3); D	RE48A248 16C40		16-C-31665-6906	N16-C-10225			CRV	1800	CRV	K-850253-3	DP-4 (6) DP-5 (6) SEE NOTE:

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 46-277

RESTRICTED

RESTRICTED

SHEET 48 - 278

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48800	CAPACITOR, fixed: mica; 2,700 mmf; 500 vdcw; case 1 13/32" lg x 1/2" wd x 3/8" thk; thermoelastic case; two axial wire leads. 3/3/37	RE48A248 16040										
-48800-B10	CAPACITOR, fixed: NT-48800 w/2,700 mmf p/m 10%; temp coef ltr B. 3/3/37	RE48A248 16040		16-C-32145-5586	N16-C-10325-24			CRV CRV	M-524 86034-534 M00352-524	CRV CRV	K-890253-4 M-86034 sub 18	DP-4 (5) thru DP-6 (5) SEE NOTE
-48801	CAPACITOR, fixed: mica; 47 mmf; 500 vdcw; case 27/32" lg x 15/32" wd x 5/16" thk; thermo-plastic case; two axial wire leads; term mtg; add suffix indicating capacity tolerance in per cent. 3/3/37	RE48A238 16040										
-48801-B10	CAPACITOR, fixed: NT-48801 w/47 mmf p/m 10%; temp coef ltr B. NOTE: DP-8; DP-10 thru DP-17. 3/3/37	RE48A238 16040		16-C-27582-2051	N16-C-9843-83			CRV	Model H Code M-20	CRV	K-890253-11 M-80342-520	DP-4 thru DP-6 SEE NOTE
-48801-B20	CAPACITOR, FIXED: Navy Type 48801 w/47 mmf p/m 20%; temp coef ltr B. 5/8/48	RE48A238 RE48A154		16-C-27587-4532				CRV	H			
-48802	CAPACITOR, fixed: paper dielectric; 250,000 mmf plus 10 minus 3%; 1,000 vdcw; HS metal can; case 1 5/16" lg x 11/16" wd x 1 9/16" h o/a; oil impr and filled; two solder post term 13/32" h located on top 5/8" c to c; no int gnd connections; two mtg fl on bottom of case w/ a 5/32" mtg slot 1 15/16" c to c. 3/16/37	RE48A160 RE13A488		16-C-46329-5972				CG	9CE6A15	CRV CG CG CG	P-721478-11 P-7763475-11 K-5222637rev3 K-8396301rev11	SA (9) SA-2 (10) SA-3 (10) SP (2) TAJ-6 TAJ-9 thru TAJ-11 SEE NOTE
-48802-10	CAPACITOR, fixed: NT-48802 w/250,000 mmf p/m 10%. 3/16/37	RE48A160 RE13A488		16-C-46350-5972	N16-C-11342-5			CG CG	23F242 9CE6A15	CEM CEM	744-657 744-504	QGA SU (2) SU-1
-48803	CAPACITOR, fixed: paper dielectric; 500,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 3/4" wd x 3/4" h x 2 11/32" lg o/a; oil impr and filled; two ins #20 flex wire term 5" lg, located on end 1/2" c to c; no int gnd connections; two mtg feet 1" wd, integral w/bottom of case ea w/one 0.205" mtg hole 2 27/32" c to c. 3/18/37	RE48A142 RE13A488		16-C-47276-5293	N16-C-11356-1			CRV	4648			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-278

RESTRICTED

RESTRICTED

SHEET 48-279

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48804	CAPACITOR, fixed: 3/20/37 paper dielectric; 500,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 3/4" lg x 1" wd x 2 1/8" h o/a; oil impr and filled; two screw type term 3/8" h located on top 3/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/ a 3/16" diam mtg hole 2 1/4" c to c.	RE48A147 RE13A488		16-C-47276-2851				CD	TDF-6005-1	CAY	K-7808812 sub 0	00-3
-48805	CAPACITOR, fixed: 3/25/37 mica; 2,750 mmf; 2,000 vdcw, 6.5 amp at 3000 kc, 5.0 amp at 1000 kc, 3.0 amp at 300 kc, 1.7 amp at 100 kc; case 2" lg x 1 5/16" wd x 1 1/2" h; molded bakelite case; two screw type term 7/16" lg 1 1/2" c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-48805-A5	CAPACITOR, fixed: 3/25/37 NT-48805 w/ 2,750 mmf p/m 5%; temp coef 1tr A.	RE48A222 16C40		16-C-32158-2980				CD	PL-888-15			
-48805-B10	CAPACITOR, fixed: 3/25/37 NT-48805 w/2,750 mmf p/m 10%; temp coef 1tr B.	RE48A222 16C40		16-C-32158-3508				CD	PL-888-15L			
-48805-D2	CAPACITOR, fixed: 3/25/37 NT-48805 w/2,750 mmf p/m 2%; temp coef 1tr D.	RE48A222 16C40		16-C-32158-1925	N16-C-10325-100			CD	PL-888-15H			
-48806	CAPACITOR, fixed: 4/20/37 paper dielectric; 25,000 mmf plus 10 minus 3%; 500 vdcw; HS metal can; case 1 5/16" lg x 3/4" wd x 1 1/8" h o/a; oil impr and filled; two solder post term 13/32" h located on top 5/8" c to c; no int gnd connections; two mtg fl on bottom of case w/ 5/32" wd mtg slot 1 7/8" c to c.	RE48A160 RE13A488		16-C-43284-9660				CRV	72039-510	CRV	P-721074-4 alt 3	RAL-6 RAL-7
-48806-10	CAPACITOR, fixed: 4/20/37 NT-48806 w/25,000 mmf p/m 10%. NOTE: RAK-3; RAK-4; RAK-8; RAL-3 thru RAL-5; RAL-8.	RE48A160 RE13A488		16-C-43305-9660	N16-C-11050			CRV	72024-518	CRV CMX	P-721024-518 B-250101-1	RAK-2 RAL-2 SEE NOTE
-48807	CAPACITOR, fixed: 4/20/37 paper dielectric; 75,000 mmf plus 10 minus 3%; 500 vdcw; HS metal can; case 1 5/16" lg x 3/4" wd x 1 1/8" h o/a; oil impr and filled; two solder post term 13/32" h located on top 5/8" c to c; no int gnd connections; two mtg fl on bottom of case w/ a 5/32" wd mtg slot 1 7/8" c to c.	RE48A160 RE13A488		16-C-45184-9660	N16-C-11220-1					CRV	P-721074-5 rev 3	RAL-6 RAL-7
-48807-10	CAPACITOR, fixed: 4/20/37 NT-48807 w/75,000 mmf p/m 10%. NOTE: RAK-3; RAK-4; RAK-8; RAL-3 thru RAL-5; RAL-8.	RE48A160 RE13A488		16-C-45205-9660	N16-C-11220			CRV	72039-511	CRV CMX	P-72024-519 B-250101-2	RAK-2 RAL-2 SEE NOTE

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-279

RESTRICTED

RESTRICTED

SHEET 48 - 280

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48808	CAPACITOR, fixed: 4/21/37 mica; 2250 mmf; 500 vdcw, 1000 vdc; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end ea w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48808-A2	CAPACITOR, fixed: 4/21/37 NT-48808 w/2,250 mmf p/m 2%; temp coef ltr A.	RE48A149 16C40		16-C-31924-3131				CD	3L			
-48808-A10	CAPACITOR, fixed: 4/21/37 NT-48808 w/2,250 mmf p/m 10%; temp coef ltr A.	RE48A149 16C40		16-C-31934-5091				CD	3L			
-48808-D2	CAPACITOR, fixed: 4/21/37 CANCELLED: use Navy Type 48808-A2.	RE48A149 16C40		16-C-31924-3131				CD	3L			
-48808-D5	CAPACITOR, fixed: 4/21/37 NT-48808 w/2,250 mmf p/m 5%; temp coef ltr D.	RE48A149 16C40		16-C-31929-4526				CD	3BLS	CW	EB0-613080-21ea1	
-48809	CAPACITOR, fixed: 4/21/37 mica; case style 23; 3000 mmf; 500 vdcw; molded low-loss bakelite case; case 1" lg x 5/8" wd x 3/16" thk; 2 lug term, 1 at ea end; 5/32" hole in ea lug for mtg, 1 5/8" mtg/c; add suffix indicating capacity tolerance in per cent.	RE48A149 16C40										
-48809-A10	CAPACITOR, fixed: 4/21/37 NT-48809 w/2,000 mmf p/m 10%; temp coef ltr A.	RE48A149 16C40		16-C-31862-6091			3DA2-114.3	CD	3L			DR
-48809-B20	CAPACITOR, fixed: 7/28/49 Navy Type 48809 w/2000 mmf, p/m 20%; temp coef ltr B.	RE48A149 16C40		16-C-31807-8575				CD	3IS			
-48810	CAPACITOR, fixed: 4/21/37 mica; 7,000 mmf; 300 vdcw, 600 vdc; case 1" lg x 5/8" wd x 5/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48810-A2	CAPACITOR, fixed: 4/21/37 Navy Type 48810 w/7,000 mmf p/m 2%; temp coef letter A.	RE48A149		16-C-33111-1780				CD	3L-3D7			DR
-48810-A10	CAPACITOR, fixed: 4/21/37 NT-48810 w/7,000 mmf p/m 10%; temp coef ltr A.	RE48A149 16C40		16-C-33121-3739				CD	3L			
-48811	CAPACITOR, fixed: 4/21/37 mica; 95 mmf; 1200 vdcw, 2500 vdc; case 1 1/4" lg x 1 1/8" wd x 11/32" d; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48811-A10	CAPACITOR, fixed: 4/21/37 NT-48811 w/95 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-28492-2270				CD	4-24095			DR
-48812	CAPACITOR, fixed: 4/21/37 mica; 120 mmf; 1200 vdcw, 2500 vdc; case 1 1/4" lg x 1 1/8" wd x 11/32" d; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										

SHEET 48-280

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 281

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48812-A10	CAPACITOR, fixed: 4/21/37 NT-48812 w/120 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-28743-4008				CD	4-23012			DR
-48813	CAPACITOR, fixed: 4/21/37 mica; 3,000 mmf; 1200 vdcv, 2500 vdcv; case 1 1/4" lg x 1 1/8" wd x 23/64" thk max; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 JAN-C-5										
-48813-A2	CAPACITOR, fixed: 4/21/37 NT-48813 w/3,000 mmf p/m 2%; temp coef ltr A.	RE48A221 JAN-C-5	CM45A302G	16-C-32188-6448				CSL	IQW1.2-23-2			SG
-48813-A10	CAPACITOR, fixed: 4/21/37 NT-48813 w/3,000 mmf p/m 10%; temp coef ltr A.	RE48A221 JAN-C-5	CM45A302K	16-C-32198-8408				CD	4-22030			
-48813-B2	CAPACITOR, FIXED: 1/26/48 Navy Type 48813 w/3000 mmf p/m 2%; temp coef letter B.	JAN-C-5	CM45B302G	16-C-32188-6453								SG-B SG-1B
-48813-B10	CAPACITOR, FIXED: 4/20/49 Navy Type 48813 w/3000 mmf p/m 10%; temp coef letter B.			16-C-32198-8 1h				CD	4LS	CEM	744-825	MX-39 Mod 3
-48814	CAPACITOR, fixed: 4/21/37 mica; 5,000 mmf; 1,200 vdcv, 2,500v DC test; case 1 1/4" lg x 1 1/8" wd x 7/16" d; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48814-A2	CAPACITOR, FIXED: 4/21/37 Navy Type 48814 w/5,000 mmf p/m 2%; temp coef letter A.	RE48A221		16-C-32689-8206				CD				DR
-48814-A10	CAPACITOR, fixed: 4/21/37 T-48814 w/5,000 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-32700-1165			3DA574.1	CD CAN	4-22050 HST			SG
-48814-B5	CAPACITOR, fixed: 4/21/37 T-48814 w/5000 mmf p/m 5%; temp coef ltr B.	RE48A221 16C40		16-C-32694-9688	N16-C-10408-10			CD CAN	4LST HLST	COL	925 2502 10rev0	TC2-1 TC2
-48814-B10	CAPACITOR, fixed: 4/21/37 T-48814 w/5,000 mmf p/m 10%; temp coef ltr B.	RE48A221 16C40		16-C-32700-1169			3DA5-74	CD	4LST	CG COL	F-7768925-47 925 2502 10rev 0	FBD TCX
-48815	CAPACITOR, variable: 4/21/37 air; plate meshing type single sect; 2 to 20 mmf; SLC 1" lg x 15/16" wd x 1 7/32" h; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RH side; single hole for shaft, two mtg studs tapped for #4-36 screws on 21/32" mtg/c 31/64" from top.							CEC	APC-20			DR

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-281

RESTRICTED

RESTRICTED

SHEET 48 - 282

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48816	CAPACITOR, variable: 4/21/37 air; plate meshing type single sect; 3.9 to 50 mmf; SLC; 0.015" air gap; 1 3/32" lg x 15/16" wd x 1 7/32" h shaft completely encl in housing of collar and nut 9/32" diam x 5/16" lg; acdr adj; fourteen silver or nickel plated brass plates; 360 deg rotation; isolanite insulation; post term for stator, lug term for rotor; two mtg studs 3/32" lg w/#4-36 tap on 21/32" mtg/c; same as NT-481747 except for mtg holes. NOTE: JKA-5e; QCC (3); QCD (3); QCJ-5 (3); QCJ-6 (3); QCJ-9 (3); QCL-4 (3); QCL-5 (3); QCL-8 (3); QCM-1; QCM-2; QCM-3 (3); QCM-4 (3); QCN-2 (4); QCN-3 (3); QCN-4 (7); QCO-1 (4); QCO-2 (3); QCO-3 (7); QOQ-3 (3); QOR-2 (3); QOS (3); QOS-1 (3); QOT-1 (3); QQA; WAA (3); WAD-1 (3); WBA (3); WCA-1 (6); WDA (3); WEB; WFA (3).			16-C-59718-4866			3290507-97	CHC	APC-50		1002E-26alt0 744-24 922 3000 00rev0 DD-3304-2	DR JK-2b(3) JK-5(3) JK-8(3) JKA(3) JKA-1(3) JKA-2(3) JKA-3(6) JKA-4(6) JEA-5 SEE NOTE:
-48816-A	CAPACITOR, variable: 4/28/38 air; plate meshing type single sect; 5 to 50 mmf; SLC; 1 1/16" lg x 15/16" wd x 1 7/32" h shaft completely encl in brg 9/32" diam x 5/16" lg; acdr adj; fourteen gold plated invar plates; 360 deg rota- tion; ceramic insulation; post term for stator lug term for rotor on RE side; two mtg studs 3/32" lg w/ #4-40 tapped hole on 21/32" mtg/c.			16-C-59823-8221	W16-C-12230			CHC	APC-50Modified	CRV	A-110015alt0	LD-4
-48817	CAPACITOR, variable: 4/21/37 air; plate meshing type single sect; 10 to 110 mmf p/m 2%; SLC; 15/16" wd x 1 7/32" h shaft completely encl in collar and nut 9/32" diam x 5/16" lg; acdr adj; cad pl brass plates; 360 deg rotation; isolanite insulation; post term for stator, lug term for rotor on RE side; two mtg studs 3/32" lg w/#4-36 tapped hole on 21/32" mtg/c.			16-C-60952-2601				CHC	APC-110			DR
-48818	CAPACITOR, fixed: 5/17/37 mica; 4375 mmf; 500 vdcw; case 1 13/32" lg x 1/2" wd x 3/8" thk; thermo-plastic case; two axial wire leads.	RE48A248 16C40										
-48818-B1 1/2	CAPACITOR, fixed: 5/17/37 NT-48818 w/4375 mmf p/m 1 1/2%; temp coef ltr B. NOTE: DP-8; DP-10 thru DP-19; DP-1.	RE48A248 16C40		16-C-32583-1072	N16-C-10393			CRV	M-80352-529	CRV	K-850253-5rev1	DP-4thru DP-6 SEE NOTE:
-48819	CAPACITOR, fixed: 5/17/37 mica; 2030 mmf; 500 vdcw; case 1 13/32" lg x 1/2" wd x 3/8" thk; thermo-plastic case; two axial wire leads.	RE48A248 16C40										
-48819-B1 1/2	CAPACITOR, fixed: 5/17/37 NT-48819 w/2030 mmf p/m 1 1/2%; temp coef ltr B. NOTE: DP-5; DP-6; DP-8; DP-10 thru DP-19.	RE48A248 16C40		16-C-31818-1462				CRV	M-80352-523	CRV	K-850253-6rev1	DQ-1 DP-4 SEE NOTE

SHEET 48-282

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 283

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A B O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48820	CAPACITOR, fixed: mica; 854 mmf; 500 vdcw; case 1 13/32" lg x 1/2" wd x 3/8" thk; thermo-plastic case; two axial wire leads.	5/17/37 RE48A248 16C40										
-48820-B3	CAPACITOR, fixed: NT-48820 w/854 mmf p/m 3%; temp coef ltr B. NOTE: DP-8; DP-10 thru DP-17.	5/17/37 RE48A248 16C40		16-C-3820-6715				CRV	M-80352-515	CRV	K-850253-7rev1	DP-4 thru DP-6 SEE NOTE:
-48821	CAPACITOR, fixed: mica; 70,000 mmf; 1,000 vacv effective, 12 amp at 3,000 kc, 13 amp at 1,000 kc, 12 amp at 300 kc, 7 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/ two diam mtg holes 2 5/8" c to c.	5/21/37 RE48A131 16C40										
-48821-A5	CAPACITOR, fixed: NT-48821 w/70,000 mmf p/m 5%; temp coef ltr A.	5/21/37 RE48A131 16C40		16-C-35649-1909				CD	PL-482-6S			QC-6
-48821-B5	CAPACITOR, fixed: NT-48821 w/70,000 mmf p/m 5%; temp coef ltr B. NOTE: QCJ-6; QCT (2); QCL-4; QCL-5; QCN-2; QCN-3; QCO-2; QCQ; QCC-1 (2); QCR; QCR-1 (2); QCS (2); QCT (2); WCA-1 (2); WCA-2 (2); WCA-3; WEB (2).	5/21/37 RE48A131 16C40		16-C-35649-1914	N16-C-10598			CD	PL-482-6LS	CRM CRM	744-15 744-101	QCJ (2) QCI-5 SEE NOTE:
-48822	CAPACITOR, fixed: paper dielectric; 150,000 mmf plus 10 minus 3%; 1,500 vdcw; HS metal can; case 2 1/2" lg x 1 5/8" h x 2" wd o/a; oil impr and filled; two solder lug term 3/8" h on end of case 1 3/4" c to c; no int gnd connections; three 3/8" wd mtg ft w/ 3/16" diam hole, one at top on ctr line and two on bottom 1 3/8" c to c and 2 1/2" from top hole; for replacement use NT-48822-A.	8/27/37		16-45951-7271	N16-C-11337-10			CD		CAY	M-7406537 sub 0	
-48822-A	CAPACITOR, FIXED: paper dielectric; single sect; 150000 mmf plus 10 minus 3%; 2000 vdcw; HS metal can; 2 1/2" lg x 2" wd x 1 5/8" h, o/a; oil filled; has 2 solder lug term on top, spaced 1 3/4" c to c; no int gnd connection; three 3/8" wd mtg ft w/ 3/16" diam holes, 1 at top on ctr line and 2 on bottom 1 3/8" c to c and 2 1/2" from top hole.	5/6/38 RE48A145 RE13A488		16-C-45953-3943	N16-C-11337			CD				
-48822-A10	CAPACITOR, FIXED: Navy Type 48822-A w/150000 mmf p/m 10%.	5/6/38 RE48A145 RE13A488		16-C-45973-8232	N16-C-11338-45			CAW				
-48823	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 5 1/16" lg x 2" wd x 2 5/16" d, o/a; two stud term 1/2" h located on top, spaced 1" c to c; no int gnd connections.	9/2/37 RE48A110 RE13A488		16-C-49176-5165								

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-283

RESTRICTED

RESTRICTED

SHEET 48 - 284

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CO. TRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48824	CAPACITOR, fixed: 10/8/37 mica; 8,000 mmf; 600 vdcw; 1 1/4" lg x 1 1/4" wd x 3/8" h; molded bakelite case; two lug term ea w/one 3/16" diam hole on 1 3/4" ctr; two mtg holes on back of case 5/32" diam on 1 1/2" std/c.	RE48A215 16C40										
-48824-A10	CAPACITOR, fixed: 10/8/37 NT-48824 w/8,000 mmf p/m 10%; temp coef ltr A.	RE48A215 16C40		16-C-33227-2151				CAW	1455	CRV	K-30090-12 rev15	UA-2 (2)
-48824-B10	CAPACITOR, fixed: 10/8/37 NT-48824 w/8,000 mmf p/m 10%; temp coef ltr B.	RE48A215 16C40		16-C-33227-2156				CAW	1455L			
-48825	CAPACITOR, fixed: 10/14/37 CANCELLED; for replacement use NT-48825.	RE48A131 16C40						CD	PL-266-6			
-48826	CAPACITOR, fixed: 10/14/37 mica; 600 mmf; 6,000 vdcw, 8 amp at 3,000 kc, 6 amp at 1,000 kc, 3 amp at 300 kc, 1 amp at 100 kc; 2 1/2" h x 2 13/16" diam; ceramic case; one elliptical cast aluminum end cap term 3 13/16" lg at end ea with two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48826-B2	CAPACITOR, fixed: 10/14/37 NT-48826 w/600 mmf p/m 2%; temp coef ltr B.	RE48A132 16C40		16-C-30317-4071				CD	PL-664-59	CBM	744-82	JK-3 QC-7 QCG
-48826-B5	CAPACITOR, fixed: 10/14/37 NT-48826 w/600 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-30322-5552	N16-C-10050-3			CD	PL-664-59			
-48827	CAPACITOR, fixed: 10/14/37 mica; 40,000 mmf; 1,500 vdcw, 12 amp at 3,000 kc, 13 amp at 1,000 kc, 11 amp at 300 kc, 6 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48827-A5	CAPACITOR, fixed: 10/14/37 NT-48827 w/40,000 mmf p/m 7%; temp coef ltr A.	RE48A131 16C40		16-C-34990-2109				CD	PL-480-6			
-48827-B10	CAPACITOR, fixed: 10/14/37 NT-48827 w/40,000 mmf p/m 10%; temp coef ltr B.	RE48A131 16C40		16-C-34995-2594	N16-C-10586			CD	PL-480-6L			
-48827-D2	CAPACITOR, fixed: 10/14/37 NT-48827 w/40,000 mmf p/m 2%; temp coef ltr D.	RE48A131 16C40		16-C-34984-9644				CD	PL-480-6H	CBM	744-86	JK-3

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-284

RESTRICTED

RESTRICTED

SHEET 48 - 285

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48828	CAPACITOR, fixed: 10/14/37 mica; 90,000 mmf; 1,000 vdcw; 11 amp at 3,000 kc, 12 amp at 1,000 kc, 12 amp at 300 kc, 8 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48828-A5	CAPACITOR, fixed: 10/14/37 NT-48828 w/90,000 mmf p/m 2%; temp coef ltr A.	RE48A131 16C40		16-C-35965-6709						CD	PL-484-6	
-48828-D2	CAPACITOR, fixed: 10/14/37 NT-48828 w/90,000 mmf p/m 2%; temp coef ltr D.	RE48A131 16C40		16-C-35966-5244						CD	PL-484-6H	CBM 744-85 JK-3
-48829	CAPACITOR, fixed: 10/14/37 paper dielectric; 1 mf plus 10 minus 3%; 500 vdcw; HS metal can; case 1 5/16" lg x 1 1/16" wd x 1 15/16" h o/a; oil impr and filled; two solder post term 13/32" h located on top 5/8" c to c; no int gnd connections; two mtg fl on bottom of case w/ a 5/32" wd mtg elot 1 15/16" c to c.	RE48A160 RE13A488		16-C-48795-1410	116-C-11406-51		3DB1.4017-1	CG CG CBM	9CE6A8 23F154 744-7	CBM CG CG	744-88 K-3977197rev7 P-7763475-15 rev3	QC-7 JK-3 OBH CQG TBA-12 TBA-13
-48829-5	CAPACITOR, FIXED: 3/4/48 Navy Type 48829 w/ 1.0 mf p/m 5%.			16-C-48773-9660				CG	9CE6A4	CAY	T-7611797-P6	SR SR-a SR-5
-48830	CAPACITOR, fixed: 10/14/37 paper dielectric; 10 mf plus 10 minus 3%; 1,000 vdcw; HS metal can; case 3 3/4" lg x 1 3/4" wd x 4 3/4" h o/a; oil impr and filled; two ceramic ins screw type term 1 5/32" h located on top 2" c to c; no int gnd connections; two mtg fl 1 1/4" wd on side of case, ea w/a 3/16" diam mtg hole 4 3/8" c to c.	RE48A146 RE13A488		16-C-51840-2452				CG	9CE5A37	CBM CG	744-45 H-3984542 rev7/27/34	QC-7 JK-3 CQ-7 CQG
-48831	CAPACITOR, fixed: 10/14/37 electrolytic; 450 mf; 65 vdcw; working temp range minus 20°C to plus 65°C; case 6" lg x 3" wd x 6 1/4" h; metal case; two screw type term on top on stand-off insulators, term 1 1/4" h spaced 3" c to c; both term insulated from can; two mtg fl on bottom, two 0.156" diam holes in ea, on 2" x 6 1/2" mtg/c.	RE48A339 RE13A549		16-C-20634-7401				CD	MA13285-E	CBM	744-38a1to	CQ-7 CQG

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-285

RESTRICTED

RESTRICTED

SHEET 48 - 286

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48832	CAPACITOR, fixed: 10/21/37 mica; 1,000 mmf; 5,000 vdcw, 11 amp at 3,000 kc, 7 amp at 1,000 kc, 4 amp at 300 kc, 1.5 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	RE48A108 16C40										
-48832-B5	CAPACITOR, fixed: 10/21/37 NT-48832 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A108 16C40		16-C-31087-3796				CRV	UC-3072			
-48833	CAPACITOR, fixed: 10/21/37 mica; 500 mmf; 5,000 vdcw, 7.5 amp at 3,000 kc, 5 amp at 1,000 kc, 2.5 amp at 300 kc, 0.9 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term shielded on top 2" h ctr, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" mtg/c.	RE48A108 16C40										
-48833-B5	CAPACITOR, fixed: 10/21/37 NT-48833 w/500 mmf p/m 5%; temp coef ltr B.	RE48A108 16C40		16-C-30164-1796				CRV	UC-3096			
-48834	CAPACITOR, fixed: 10/21/37 mica; 1,500 mmf; 5,000 vdcw, 12 amp at 3,000 kc, 9 amp at 1,000 kc, 5 amp at 300 kc, 2 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term on top 2" h ctr shielded, one side gnd to case; two 1/4" diam mtg holes in base on 3 1/4" mtg/c.	RE48A108 16C40										
-48834-B5	CAPACITOR, fixed: 10/21/37 NT-48834 w/1,500 mmf p/m 5%; temp coef ltr B.	RE48A108 16C40		16-C-31509-4196				CRV	UC-3063			
-48835	CAPACITOR, fixed: 10/28/37 paper dielectric; 1 mf plus 10 minus 3%; 1,000 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 2 1/8" h; oil impr and filled; two screw type term 1/2" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/ 3/16" diam mtg hole 2 1/4" c to c.	RE48A147 RE13A488		16-C-48799-7097	R16-C-11426-2	R16-C-11423		CD	TDF-10010	CBM	744-59	NM-9(3) NM-9a(3) QCF

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-286

RESTRICTED

RESTRICTED

SHEET 48 - 287

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48836	CAPACITOR, fixed: 10/28/37 paper dielectric; 1 mf plus 10 minus 3%; 2,000 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 4 3/4" h o/a; oil impr and filled; two screw type term 1/2" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/ 3/16" diam mtg hole 2 1/4" c to c.	RE48A147 RE13A488		16-C-48803-2854	N16-C-11434-2			CD	TFP-20010	CBM CBM	744-58 744-52	NM-9 NM-9a QCF(2)
-48836-10	CAPACITOR, fixed: 10/23/37 WT-48836 w/1 mf p/m 10%.	RE48A147 RE13A488		16-C-48824-2854				CD	TDF-20010	CBM	744-172	NJ-4 (2)
-48837	CAPACITOR, fixed: 10/28/37 mica; 35,000 mmf; 1,500 vdcw, 11 amp at 3,000 kc, 10 amp at 1,000 kc, 8 amp at 300 kc, 5 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48837-A5	CAPACIT R, fixed: 10/28/37 NT-48837 w/35,000 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-34858-3108				CD	FL-781-6	CBM	744-14	NM-9(2) NM-9a(2)
-48837-B5	CAPACITOR, fixed: 10/28/37 NT-48837 w/35,000 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-34858-3113	N16-C-10581-12			CD	FL-781-6L			
-48838	CAPACITOR, fixed: 10/28/37 paper dielectric; 1 mf plus 10 minus 3%; 1,000 vdcw, 350 vacw at 60 cyc; HS metal can; case 4 3/8" h x 1 3/4" wd x 1 5/8" d o/a; two stud term 1/2" h located on top, spaced 7/8" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-48799-6962	N16-C-11428			CPC	8260A			NM-9
-48839	CAPACITOR, fixed: 10/30/37 mica; 70 mmf; 500 vdcw, 1000v DC test; case 5 1/64" lg max x 1 5/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148 JAN-C-5										
-48839-A10	CAPACITOR, fixed: 10/30/37 NT-48839 w/70 mmf p/m 10%; temp coef ltr A. NOTE: YG-2; YL.	RE48A148 JAN-C-5	CM20A700E	16-C-28056-9071			3D9070-2	CSL UD CFT	MDW 5W5Q7	CRV CFT	K-863187-17	GQ FR YG-1 SEE NOTE
-48839-B2	CAPACITOR, fixed: 10/30/37 NT-48839 w/70 mmf p/m 2%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B700G	16-C-28046-7116	N16-C-9870-6	R16-C-9877		CD CAW CSL CMR	SWLS 1468LS MDBW-1413-2 OXM	CRR	R6992alt0	Can't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-287

RESTRICTED

RESTRICTED

SHEET 48 - 288

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48839-B10	CAPACITOR, fixed: NT-48839 w/70 mmf p/m 10%; temp coef ltr B.	10/30/37 RE48A148 JAN-C-5	CM20B70CK	16-C-28056-9076	N16-C-9871			CD CAW CSL CMR	5WLS 1468LS MOBW-1413-10 OXM	CRR	CD-1033-81essc	
-48839-D5	CAPACITOR, fixed: NT-48839 w/70 mmf p/m 5%; temp coef ltr D.	10/30/37 RE48A148 JAN-C-5	CM20D700J	16-C-28051-8606	N16-C-9870-7	R16-C-9878		CER CD CAW CSL CMR	MIK70 5RS 1469 MOBWDW PO	CRV CG	P-720538-6rev30 M-7463969-25rev1	QCW QCX QCY QCZ
-48839-D10	CAPACITOR, fixed: NT-48839 w/70 mmf p/m 10%; temp coef ltr D.	10/30/37 RE48A148 JAN-C-5	CM20D700K	16-C-28056-9086	N16-C-9870-9	R16-C-9879		CAW CD CSL CMR CER	1469 5RS MOBWDW PO MIK70	CRV CG CRR CRV	W-303314-342 M-7463969-9rev3 CD-1034-81essc P-720473-21rev19	QCJ-8(3) QCL-7(3) RAX-1(2) WEA(3)
-48840	CAPACITOR, FIXED: mtoa; 15 mmf; 500 vdcw; body 51/64" lg x 15/32" wd x 7/32" d; molded low loss phenolic body; 2 axial wire leads; add suffix indicating capacity tolerance in per cent.	10/30/37 RE48A148 REL3A389										
-48840-B2	CAPACITOR, fixed: NT-48840 w/15 mmf p/m 2%; temp coef ltr B.	10/30/37 RE48A148 JAN-C-5	CM20B150B	16-C-26437-6716		R16-C-9809		CAW CD CSL CMR	1468LS 5WLS MOBW OXM	CRR	C56734-150	CG EW-
-48840-B5	CAPACITOR, fixed: NT-48840 w/15 mmf p/m 5%; temp coef ltr B.	10/30/37 RE48A148 JAN-C-5	CM20B150J	16-C-26442-8196	N16-C-9792			CD CAW CSL CMR	5WLS 1468LS MOBW OXM	CRR	B6992alt0	
-48840-B7	CAPACITOR, FIXED: Navy Type 48840 w/15 mmf p/m 7%; temp coef ltr B.	4/16/48 RE48A148 REL3A389		16-C-26447-1973				CAW CAW	7-1415 1463L			
-48840-B10	CAPACITOR, fixed: NT-48840 w/15 mmf p/m 10%; temp coef ltr B.	10/30/37 RE48A148 JAN-C-5	CM20B150K	16-C-26447-8676	N16-C-9792-3	R16-C-9809-60	3K2015021	CD CAW CSL CMR	5WLS 1468LS MOBW OXM	CRR CBZ	C56306-150 CO-971	RAP (3) TBX-4 TBX-4a
-48840-B20	CAPACITOR, fixed: NT-48840 w/15 mmf p/m 20%; temp coef ltr B.	10/30/37 RE48A148 JAN-C-5	CM20B150M	16-C-26453-2156	N16-C-9792-4	R16-C-9811	3K2015024	CD	5WLS	CRV		MX-16
-48840-D5	CAPACITOR, fixed: NT-48840 w/15 mmf p/m 5%; temp coef ltr D.	10/30/37 RE48A148 JAN-C-5	CM20D150J	16-C-26442-8206	N16-C-9792-6	R16-C-9809-25		CD CAW CSL CMR	5RS 1469 MOBWDW PO	CRV CPW	P-720538-22rev30 C-1469	RCD

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-288

RESTRICTED

Con't

RESTRICTED

SHEET 48 - 289

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48840-D7	CAPACITOR, FIXED: 4/10/48 Navy Type 48840 w/15 mmf p/m 7%; temp coef ltr D.	RE48A148C RE48A154F		16-C-26447-1983				CAW	1469	CAY	7608011-97	RBS-1
-48840-D10	CAPACITOR, fixed: 10/30/37 NT-48840 w/15 mmf p/m 10%; temp coef ltr D. NOTE: RBC-1 (2); RBC-2 (2); RBM-1 (3); RBM-2 (3); RBM-3 (3); RBM-4 (3); RBM-5 (3); TBX-8 (2).	RE48A148 JAN-C-5	CM20D15CE	16-C-26447-8636	N16-C-9792-10			CD CAW CSL CMR	5RS 1469 MOSDW PO	COQ CRV CAY	B-CO-971-D alt D P-720592-20 rev30 7608011-97	RBB (2) RBB-1(2) RBB-2(2) RBB(2) SEE NOTE
-48840-D20	CAPACITOR, FIXED: 4/9/48 Navy Type 48840 w/15 mmf p/m 20%; temp coef ltr D.	RE48A148 RE13A389		16-C-26453-2167				CAN	K-1415			
-48841	CAPACITOR, variable: 4/8/38 air; plate meshing type single sect; 11 to 157 mmf; SLO; 0.0245" air gap; 1 13/16" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 19/32" lg bushing 1/4" lg x 3/8"-32 thd; scdr adj; twenty-one silver or nickel pl brass plates; counter clock-wise rotation; insulantite ins; lug term; single hole mtg by 3/8" diam mtg bushing or base mtg by one mtg foot w/ #6-32 tapped hole.			16-C-61332-9464		R16-C-11943-75		CHC	MC-157-8 Modified	CRR	QB8179altB	
-48842	CAPACITOR, FIXED: 10/30/37 mica; 2 mmf; 500 vdcw; body 51/64" lg x 15/32" wd x 7/32" d; molded low loss phenolic body; 2 axial wire leads; ageing treatment and sealed for immersion; add suffix indicating capacity tolerance in per cent.	RE48A154 RE48A148										
-48842-B10	CAPACITOR, fixed: 10/30/37 NT-48842 w/ 2 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B020K	16-C-24205-7676				CD CAW CSL	5WLS 1468LS MOBW-1400A	CRB CRB	B-6992alt0 CD-1034-1180C	Q2
-48842-D10	CAPACITOR, fixed: 10/30/37 NT-48842 w/ 2 mmf p/m 10%; temp coef ltr D.	RE48A148 JAN-C-5	CM2020K	16-C-24205-7686				CD CAW CSL	5RS 1469 MOSDW	CRB	CD-1034-1180C	
-48842-D25	CAPACITOR, FIXED: 4/9/48 Navy Type 48842 w/2 mmf p/m 25%; temp coef ltr D.	RE48A154 RE48A148		16-C-24215-4566				CSL	MOSDW			DAK-4
-48843	CAPACITOR, fixed: 10/30/37 mica; 100 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143										
-48843-A3	CAPACITOR, fixed: 10/30/37 NT-48843 w/100 mmf p/m 3%; temp coef ltr A. NOTE: RBJ-1 thru RBJ-4.	RE48A143 16C40		16-C-28552-2673				CAW	1467	CNA		RAW RBJ SEE NOTE:
-48843-B5	CAPACITOR, fixed: 10/30/37 NT-48843 w/100 mmf p/m 5%; temp coef ltr B. NOTE: WCA; WCA-1; WDA; WDA-1; WFA.	RE48A143 JAN-C-5	CM30B101J	16-C-28553-1284	N16-C-9923-49		3D9100-6	CD	1WLS	CBM	744-297	NGA NMC-1 SEE NOTE: Con't

SHEET 48-289

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 44 - 290

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTORS DWG OR PART NO	EQUIPMENT USED IN
-48843-R10	CAPACITOR, fixed: NT-48843 w/100 mmf p/m 10%; temp coef ltr B.	10/30/37 RE48A143 JAN-C-5	CM30B101K	16-C-28558-1764	N16-C-9923-50	R16-C-9924-75	3D9100-50	CD CSL CAN	1WLS MWB-1216-10 C	CDM CWQ CG CRM CBM	744-297 47X359 P7762455-10 CA-98 744-364	SC-2(3) SC-3(3) SC-4(3) SK-2(2) SK-3(3) SEE NOTE:
-48843-C02	CAPACITOR, fixed: NT-48843 w/100 mmf p/m 2%; temp coef ltr C.	10/30/37 RE48A143 JAN-C-5	CM30C101G	16-C-28547-8809			3D9100-39	CAW	1467L	CRR CRR	A292altB B6985altC	
-48843-C10	CAPACITOR, fixed: NT-48843 w/100 mmf p/m 10%; temp coef ltr C.	10/30/37 RE48A143 JAN-C-5	CM30C101K	16-C-28558-1769				CAN	C1-60670	CAN	817743alt1	
-48843-D5	CAPACITOR, fixed: NT-48843 w/100 mmf p/m 5%; temp coef ltr D.	10/30/37 RE48A143 JAN-C-5	CM30D101J	16-C-28553-1294	N16-C-9923-51	R16-C-9924-57-1G		CD	1RS	CG CFT	M-7464527-36rev0	DAH (4)
-48843-D10	CAPACITOR, fixed: NT-48843 w/100 mmf p/m 10%; temp coef ltr D.	10/30/37 RE48A143 JAN-C-5	CM30D101K	16-C-28558-1774	N16-C-9923-54			CD CAN	1R C	CW CAN	817743	QFA-5(5) QFA-6(5) SEE NOTE:
-48843-D20	CAPACITOR, fixed: NT-48843 w/100 mmf p/m 20%; temp coef ltr D.	10/30/37 RE48A143 JAN-C-5	CM30D101M	16-C-28563-4254	N16-C-9923-56			CD	1R	CBZ	CO-769-B 1aeB2	
-48843-E5	CAPACITOR, fixed: NT-48843 w/100 mmf p/m 5%; temp coef ltr E.	10/30/37 RE48A143 JAN-C-5	CM30E101J	16-C-33617-4635				CD	1R	COL	912 3101 10 rev2	
-48844	CAPACITOR, fixed: mica; 330 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	10/30/37 RE48A143										
-48844-A20	CAPACITOR, fixed: NT-48844 w/330 mmf p/m 20%; temp coef ltr A.	10/30/37 RE48A143 JAN-C-5	CM30A331M	16-C-29723-9839				CAW	1467			
-48844-B5	CAPACITOR, fixed: NT-48844 w/330 mmf p/m 5%; temp coef ltr B.	10/30/37 RE48A143 JAN-C-5	CM30B331J	16-C-29713-6884	N16-C-9997-34			CSL	MOBW	CG	K-27J362-136-1	SK-1M SK-2 SK-3
-48844-C2 1/2	CAPACITOR, fixed: NT-48844 w/330 mmf p/m 2 1/2%; temp coef ltr C.	10/30/37 RE48A143 16C40		16-C-29712-7556				CAW	1467L	CRR	B6985 alt 0	
-48845	CAPACITOR, fixed: mica; 650 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	10/30/37 RE48A143 16C40										
-48845-A20	CAPACITOR, fixed: NT-48845 w/650 mmf p/m 20%; temp coef ltr A.	10/30/37 RE48A143 16C40		16-C-30438-9439				CAW	1467			
-48845-C2 1/2	CAPACITOR, fixed: NT-48845 w/650 mmf p/m 2 1/2%; temp coef ltr C.	10/30/37 RE48A143 16C40		16-C-30477-7156				CAW	1467L	CRR	B6985alt0	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-290

RESTRICTED

RESTRICTED

SHEET 48 - 291

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-4 46	CAPACITOR, fixed: 10/30/37 mica; 1,210 mmf; 500 vdcw, 1,000v DC test; case 53/64" lg x 53/64" wd x 9/32" d; molded bakelite case; two axial wire leads.	RE48A143 16C40										
-48846-A20	CAPACITOR, fixed: 10/30/37 NT-48846 w/1,210 mmf p/m 20%; temp coef ltr A.	RE48A143 16C40		16-C-31306-6839				CAW	1467			
-48846-B10	CAPACITOR, FIXED: 11/28/47 Navy Type 48 46 w/1210 mmf p/m 10%; temp coef letter B.	RE13A389		16-C-31301-4364				CSL	MMW	CBJL	ES-13107	NK-5
-48846-C2 1/2	CAPACITOR, fixed: 10/30/37 NT-48846 w/1,210 mmf p/m 2 1/2%; temp coef ltr C.	RE48A143 16C40		16-C-31295-4556				CAW	1467L	CRB	B6985alt0	
-48847	CAPACITOR, fixed: 10/30/37 mica; 6,000 mmf; 300 vdcw, 600v DC test; case 53/64" lg x 53/64" wd x 9/32" d; molded bakelite case; two axial wire leads.	RE48A143 16C40										
-48847-A10	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 10%; temp coef ltr A. NOTE: QCQ-2 (3); QCU (4); QCV (3); QCX (3); QCY (3); QCZ (3); RBL-1 (2); RBL-2 (2); RBL-5 (2); BL-6 (2).	RE48A143 16C40		16-C-32857-5495			3DA6-34 3DA6-10	CAW CD CMR CSL	1467 1WS W MW	CRV CRV CNA	P-720473-14 W-303314-349 D-775	NMB-1 QBE(3) QJ-8 QCL-7 SEE NOTE:
-48847-A20	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 20%; temp coef ltr A.	RE48A143 16C40		16-C-32862-7975	N16-C-10436-3	R16-C-10436-45	3DA6-31	CAW C CAN CSL	1467 1W C1 MW-1241	CRP	35-5076	SG SG-1 SG-2S
-48847-B2	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 2%; temp coef ltr B. NOTE: SO-2; SO-3; SO-4; SO-8; SO-9; SO-13; SO-7M; SO-7N; SO-12 M; SO-12N.	RE48A143 16C40		16-C-32847-3540	N16-C-10437			CSL	MW-5-26-3	CRP	35-5124	SO SO-1 SEE NOTE:
-48847-B3	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 3%; temp coef ltr B.	RE48A143 16C40		16-C-32851-7928				CD CAW CSL	1W 1467 MW-1241			
-48847-B5	CAPACITOR, FIXED: 12/10/47 Navy Type 48847 w/6000 mmf p/m 5%; temp coef letter B.	RE48A143 RE48A154		16-C-32852-5020				CSL	MW-1241			MK-2B Mod2
-48847-B10	CAPACITOR, fixed: 10/30/37 NT-48 47 w/6,000 mmf p/m 10%; temp coef ltr B. NOTE: TCM-2; TCN; TCU-2; ZB-3 (4); AN/UPM-1 (2); AN/UPM-1B (2); MK-11 Mod 1 (7)	RE48A143 16C40		16-C-32857-5500	N16-C-10436	R16-C-10434-5	3DA6-15.1	CD CAN CAW CAN CD CSL	1W C 1467 C-1260 1WLS MWBW-1241-10	CEL CEL CWQ CG CHZ CW CHZ	909 2603 20rev3 B-8F-3886rev14 47X345 P-7762455-27 CO-861 ESO-677316-1 CO-1057	AX-1(5) RBD(10) RBL-4(2) TBX-4 TBX-4A TCC TCM SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-291

RESTRICTED

RESTRICTED

SHEET 48 - 292

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48847-B20	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 20%; temp coef ltr B.	RE48A143 16C40		16-C-32862-7980	N16-C-10436-3	R16-C-10436-50	3DA6-15	CD CAN	1W CLS	COL	909 2603 40rev3	TCZ-1(3)
-48847-B25	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 25%; temp coef ltr B.	RE48A143 16C40		16-C-32867-3748								
-48847-C2 1/2	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 2 1/2%; temp coef ltr C.	RE48A143 16C40		16-C-32851-7156				CAW	1467L	CRP CRR	B6785 alt0 A2722-B altB	
-48847-C10	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 10%; temp coef ltr C.	RE48A143 16C40		16-C-32857-5505				CD CMR CSL CMF	1WLS WXM MOSW 502L	CW CZR	ES0-613080-1 186C 226149	ZB-2(4) AN/ARR-1(4) AS-1/ ARR-1(4)
-48847-D3	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 3%; temp coef ltr D.	RE48A143 16C40		16-C-32851-7938				CD CAW	1RS 1464			
-48847-D10	CAPACITOR, fixed: 10/30/37 NT-48847 w/6,000 mmf p/m 10%; temp coef ltr D.	RE48A143 16C40		16-C-32857-5510				CD	1WLS	CADV	A-1301rev0	WEA WEA-1(2)
-48848	CAPACITOR, FIXED: 10/30/37 mins; 10000 mmf; 300 vdcw, 600v IC test; case 53/64" lg x 53/64" wd x 11/32" d, max; molded low loss bake- lite case; 2 axial wire leads; salt water immersion test.	RE48A143 JAN-C-5										
-48848-A5	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM35A103J	16-C-33617-4739				CD	1W			SJ-1 (2)
-48848-A10	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 10%; temp coef ltr A.	RE48A143 JAN-C-5	CM35A103K	16-C-33622-5218			3DA10-27 3DA10-53 3DA10-109	CSL	MW-1249-10	CBM CRU CPT CC CDE CNA CRM CBM	744-571 P-720473-46 24161 K-273362-540 2807-3 D-775 744-231 744-448	ARB DAH LS IS-1 (2) QCQ-2 (7) QCU-5 QCW QCX
	NOTE: QCY; QCZ; RAS thru RAS-5; RAW; RBR-1 thru RBR-3; RBL-1; RB L-2; RBL-5; RBL-6; SB (2); SJ-1 (6); SM (3); SM-1 (3); SU-1; YB-2 (3); MK-8 Mod 2 (5); MK-29 Mod 2.											SEE NOTE
-48848-A20	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 20%; temp coef ltr A.	RE48A143 JAN-C-5	CM35A103M	16-C-33627-7698			3DA10-73	CD CD	1WS 2DS	CFP COL CJF CW	RF-4575-1A 186A 935 5009 00 revC ST-1186chg0	MK-8 Mod2 MK-16 (2)
-48848-B2	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 2%; temp coef ltr B.	RE48A143 JAN-C-5	CM35B1030	16-C-33612-3263								Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-292

RESTRICTED

RESTRICTED

SHEET 48 - 293

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48848-B5	CAPACITOR, fixed: NT-48848 w/10,000 mmf p/m 5%; temp coef ltr B.	10/30/37 RE48A143 JAN-C-5	CM35B103J	16-C-33617-4743	N16-C-10491	R16-C-10492-50		CSL	MWW		CFT RF-4575-1A CWT P-721133-11 CRV P-7762455-62 CG T-7610394-11 CAY	DAH-2 DAK-2 DAK-3 DAK-4 QCU (9) SEE NOTE
	NOTE: RAR (2); SR-5 (10); TCK-1 (10) thru TCK-7(10);	YE-1 (10);	ME-16									
-48848-B10	CAPACITOR, fixed: NT-48848 w/10,000 mmf p/m 10%; temp coef ltr B.	10/30/37 RE48A143 JAN-C-5	CM35B103K	16-C-33622-5222	N16-C-10490-500	R16-C-10493-20	3DKA10-220	CD CMF CAW CSL CAY	IWLS 502J 1467LS MWBW C-06110	CBM CMV CRR CFT CG CAY CBM CW	744-268 P-720592-7rev22 C-56303-103 P-7762455-31 7608010-7 744-231 744-158	ATB DW DAH-2 DAK-1 DAK-3 NJ-4 (3) NGA (2) RAP SEE NOTE
	NOTE: MAX-1 (3); RBB-1 (6); RBB-2 (6); RBD; RBM-1 (26); RBM-2(26); RBM-3(26); RBM-4 (26); RBM-5 (26); RBM-6 (26); RBS-1 (13); RBS-2 (13); SD	thru	SD-4									
-48848-B20	CAPACITOR, fixed: NT-48848 w/10,000 mmf p/m 20%; temp coef ltr B;	10/30/37 RE48A143 JAN-C-5	CM35B103M	16-C-33627-7703	N16-C-10491-10	R16-C-10495-7-800		CD CMF CSL CAW	IWLS 503M MWBW-1249 1467LS	CBM CHZ CW	744-439 CO-11161ea0 ES-696993	DAU-1 (4) RBA-1 (4) SJ-1 (15) SU-1 (6) SEE NOTE
	NOTE: SY; AN/UPM-1 B (3); MX-28 (5); MX-29 Mod 2 (9).											
-48848-B30	CAPACITOR, FIXED: Navy Type 48848 w/10000 mmf p/m 30%; temp coef ltr B.	10/30/37 RE48A143 JAN-C-5		16-C-33632-5195				CMF CMR	502L W	CPR	D-5000	AN/AFS-2
-48848-C1	CAPACITOR, FIXED: Navy Type 48848 w/10000 mmf p/m 1%; temp coef ltr C.	9/28/48 RE48A143		16-C-33611-6570				CAW	602L	CRM	744-1194	MK-39
-48848-C2	CAPACITOR, fixed: NT-48848 w/10,000 mmf p/m 2%; temp coef ltr C.	10/30/37 RE48A143 JAN-C-5	CM35C103G	16-C-33612-3268		R16-C-10491-5		CD CAW	IWL 1467L			
-48848-C5	CAPACITOR, fixed: NT-48848 w/10,000 mmf p/m 5%; temp coef ltr C.	10/30/37 RE48A143 JAN-C-5	CM35C103J	16-C-33617-4748			3DA10-154	CD CAW CSL	IRS 1467LST MWCW			
-48848-C10	CAPACITOR, fixed: NT-48848 w/10,000 mmf p/m 10%; temp coef ltr C.	10/30/37 RE48A143 JAN-C-5	CM35C103K	16-C-33622-5228	N16-C-10491-5-5	R16-C-10493-22		CSL	MWCW-1247-10	CG CRP	K-27J362-540 rev6 35-5096	SO-1 (9) SO-2 (9) SO-3 SEE NOTE
	NOTE: SO-4; SO-7M (9); SO-7N (9); SO-8 (9); SO-9 (9); SO-12M; SO-12N; SO-13 (9); 4F (8); MK-33 (11)											
-48848-C20	CAPACITOR, fixed: NT-48848 w/10,000 mmf p/m 20%; temp coef ltr C.	10/30/37 RE48A143 JAN-C-5	CM35C103M	16-C-33627-7706				CSL	MFCW	CG	K-27J362-540rev6	SN (3)
-48848-D2	CAPACITOR, fixed: NT-48848 w/10,000 mmf p/m 2%; temp coef ltr D.	10/30/37 RE48A143 JAN-C-5	CM35D103G	16-C-33612-3273		R16-C-10491-170		CD CAW	IRS 1464			Con't

SHEET 48-293

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 294

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48848-D5	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 5%; temp coef ltr D. NOTE: QCY (4); QCY (4); QCZ (4); WEA-1 (4).	RE48A143 JAN-C-5	CM35D103J	16-C-33617-4753	N16-C-10491-9	R16-C-10492-60	3DA10-154	CD CAW CAW	1RS 1464 14675	CRV CW	P-721133-11 98-686118-1	OBR (4) QCQ-2 (4) QCW (4) SEE NOTE
-48848-D10	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 10%; temp coef ltr D.	RE48A143 JAN-C-5	CM35D103K	16-C-33622-5233	N16-C-10491-8	R16-C-10493-24		CD CAW CAN CSL	1RS 1464 CRW MWSGW			
-48848-D20	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 20%; temp coef ltr D.	RE48A143 JAN-C-5	CM35D103M	16-C-33627-7713		R16-C-10495-7-932		CD CAW CSL	1RS 1464 MWSGW			
-48848-E2	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 2%; temp coef ltr E.	RE48A143 JAN-C-5	CM35E103C	16-C-33612-3278				CD CAW	1RS 1464			
-48848-E5	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 5%; temp coef ltr E.	RE48A143 JAN-C-5	CM35E103J	16-C-33617-4759		R16-C-10492-62	3DA10-154	CD CAW	1RS 1464			
-48848-E10	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 10%; temp coef ltr E.	RE48A143 JAN-C-5	CM35E103K	16-C-33622-5238		R16-C-10493-26		CD	1RS			
-48848-E20	CAPACITOR, fixed: 10/30/37 NT-48848 w/10,000 mmf p/m 20%; temp coef ltr E.	RE48A143 JAN-C-5	CM35E103M	16-C-33627-7718		R16-C-10495-7-990		CD CAW	1RS 1464			
-48849	CAPACITOR, fixed: 10/30/37 paper dielectric: three sect; 100,000 mmf/100,000 mmf/100,000 mmf plus 10 minus 3%; 400/400/400 vdcw; BS metal can; case 1 13/16" lg x 1" wd x 3/4" h; oil impr and filled; three solder lug term ea 1/2" c to c on top; one side of all sect common and gnd to case; two integral mtg ears at bottom ends w/two 3/16" diam holes 2 1/8" c to c; for replacement use NT-48849-A.	RE48A128 R 13A488		16-C-54429-6084			3DA100-29	CD CSL	BYRT-4111 3XDMRTW4-.1	CRP CW COL	A-206-2 ESA-682063-205 1es15 954 3016 20	C2 DAB (9) DAB-1(9) DAB-3(9) ID-4
-48849-10	CAPACITOR, fixed: 10/30/37 NT-48849 w/100,000 mmf/100,000 mmf/100,000 mmf p/m 10%; for replacement use NT-48849-A10.	RE48A128 RE13A488		16-C-54443-2305	N16-C-11334-3			CAW	3XDMRTW4-.1-10	CRP	C-55839 alt 0	RAP
-48849-20	CAPACITOR, fixed: 10/30/37 NT-48849 w/100,000 mmf/100,000 mmf/100,000 mmf p/m 20%; for replacement use NT-48849-A20.	RE48A128 RE13A488		16-C-54461-9349			3DA100-350	CD CSL CSF	BYRT-4111 C-950 2527-8	COL	956WTO1W-M	TDR-3 (3)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-294

RESTRICTED

RESTRICTED

SHEET 48 - 295

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48849-A	CAPACITOR, fixed: 12/3/40 paper dielectric; three sect; 100,000 mmf plus 10 minus 3% ea sect; 600 vdcw ea sect; ES metal can; 1 13/16" lg x 1", wd x 3/4" h; oil impr and filled; three solder lug term 3/8" lg on top, spaced 1/2" c to c; all sect int gnd; two mtg ft 3/8" wd flush w/bottom, w/3/16" mtg holes spaced 2 1/8" c to c.	RE48A128 RE13A488		16-C-54432-8740	N16-RC-13966			CD CME CSF	DYRT-6111 8832B18	CFN CHZ CFN	300447-6 rev 9 00-665 300447-6	BN (2) BN-1 BN-2 (3) DAH-2 (11) YH YH-1
-48849-A6	CAPACITOR, fixed: 12/3/40 NT-48849-A w/100,000 mmf/100,000 mmf p/m 6%.	RE48A128 RE13A488		16-C-54426-5171				CEV		CG	M-29J407-15	SK-3
-48849-A10	CAPACITOR, fixed: 12/3/40 NT-48849-A w/100,000 mmf p/m 10% ea sect. NOTE: YJ; YJ-1; YJ-2; AN/CPN-6.	RE48A128 RE13A488		16-C-54446-5197	N16-C-11335-5	R16-C-11336-48		CD CIE CSF CIE CEV	DYRT-6111 8832B18 2527-8 6BAT111	CFM COL CGG CG CFN CHZ	744-634 956 3016 20 revD8521 8A1061391ss0 M-29J407-15 C-1010 00-665	REF SC-2 (3) SC-3 (4) SK-2 (4) SN (5) SU SU-1 SEE NOTE
-48849-A20	CAPACITOR, fixed: 12/3/40 NT-48849-A w/100,000 mmf p/m 20% ea sect. NOTE: SQ (3); TCS-13; TCS-14; TCZ (3); TCZ-1 (3); TDH-4 (3); AN/TPS-1R (5).	RE48A128 RE13A488		16-C-54463-6425	N16-C-11334-100 N16-C-11334-125		3DA100-116.10 3DA100-126.1 3DA100-380	CD CIE CO CSL CSF CIE	DYRT 8832-18 25F469 3XDMRT6-1 2527-8 6BAT111	CFE CFN CW COL CHZ COL CG	F-36416-1 issF C-1010 ES-682063-12 956 0001 00 rev9 00-779revB 956 3016 40 revD8521 K-35J639-2rev1	DAK(11)chru DAK-4 (11) DAU (3) DAU-1 (3) RDP SM (9) SM-1 (9) SP(8) SP-1M(24) SEE NOTE
-48850	CAPACITOR, fixed: 10/30/37 paper dielectric; three sect; 800,000 mmf/800,000 mmf /3 mf plus 10 minus 3% ea sect; 400 vdcw ea sect; ES metal can; case 1 7/8" lg x 1 7/8" wd x 2 11/16" h o/a; dykanol impr and filled; three solder lug term 1/4" h located on top, spaced 19/32" c to c; int gnd; two mtg ft w/5/32" diam mtg holes, one on bottom on side, one on top opposite side.	RE48A169 RE13A488		16-C-54626-9037				CD	FC-674-1	CRF CD	B-4899 25929rev0	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-295

RESTRICTED

RESTRICTED

SHEET 48 - 296

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48851	CAPACITOR, VARIABLE: 10/30/37 c/• 2 var air capacitors on same baseplate, plate washing, air dielectric, ea capacitor rated 110 mmf min to 150 mmf max, SLC; 1 15/32" lg x 1 7/8" wd x 1 7/16" h, o/a; panel mtd by 2 posts w/#4-40 tapped holes csk 82 deg x 9/64" diam on 1 11/16" x 1 11/16" mtg/c; 24 plates per sect; lug term; sodr adj.			16-C-62806-1001	M16-C-12400			CBC	APC-2556	CRR	R7066 1ea F	QX
-48852	CAPACITOR, fixed: 10/30/37 paper dielectric; 1 mf plus 10 minus 3%; 100 vdcw; HS metal can; case 1 13/16" lg x 1" wd x 3/4" h o/a; oil impr and filled; two solder lug term 3/4" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-48852-A.	RE13A488 RE48A129		16-C-48787-9137				CD	HC-1923	CRR CRR	B-4991 alt 0 A-104092-2revK	QX
-48852-5	CAPACITOR, fixed: 10/30/37 NT-48852 w/ 1 mf p/m 5%; for replacement use NT-48852-A.	RE13A488 RE48A129		16-C-48766-9137				CD	HC-1923	CRR	C-220050-1 chg 0	DAZ DBF-1
-48852-10	CAPACITOR, fixed: 10/30/37 NT-48852 w/1 mf p/m 10%.	RE13A488 RE48A129		16-C-48808-9137			3DKB1-10	CAW		CRR	A-15449	RAP
-48852-A	CAPACITOR, fixed: 9/10/40 paper dielectric; 1 mf plus 10 minus 3%; 200 vdcw; HS metal can; case 1 13/16" lg x 1" wd x 3/4" h o/a; wax impr and filled; two solder lug term 5/16" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A129		16-C-48789-3641		R16-C-11380-25		CD	HC-3430			
-48852-A5	CAPACITOR, fixed: 9/10/40 NT-48852-A w/1 mf p/a 5%.	RE13A488 RE48A129		16-C-48769-36 1			3DB1.30 3DB1.284	CD	HC-3430			
-48852-A10	CAPACITOR, fixed: 9/10/40 NT-48852-A w/1 mf p/m 10%. NOTE: TEM-6 (4); TEM-7 (2); TEM-8 (4); TEF-13 (2).	RE13A488 RE48A129		16-C-48810-3641	M16-C-11381			CD	HC-3430	CAY CAY	T-7605948-22subB T-7606286-3	TEM-4 TEM-5 (2) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-296

RESTRICTED

RESTRICTED

SHEET 48 - 297

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-48853	CAPACITOR, fixed: mica; 250 mmf; 500 vdcw 1000v DC test; case 25/32" lg x 25/32" wd x 9/32" d max; molded bakelite case; two axial wire leads.	11/6/37 RE48A143 JAN-C-5										
-48853-A10	CAPACITOR, fixed: NT-48853 w/250 mmf p/m 10%; temp coef ltr A.	11/6/37 RE48A143 JAN-C-5	CM30A251K	16-C-29481-3759			3D9250-31.1	CD CSL	1W MW-1219-10	CPT F-9234-2-5	TDN TDN-2 thru TDN-4	
-48853-A20	CAPACITOR, fixed: NT-48853 w/250 mmf p/m 20%; temp coef ltr A.	11/6/37 RE48A143 JAN-C-5	CM30A251M	16-C-29486-6239				CD CAW CSL	1W 1467 MW-1219			
-48853-B5	CAPACITOR, fixed: NT-48853 w/250 mmf p/m 5%; temp coef ltr B. NOTE: M-13 (2); QCA.	11/6/37 RE48A143 JAN-C-5	CM30B251J	16-C-29476-3284	N16-9973-125			CD CAW CSL	1WLS 1467 S MWBW	CG CBM CBM	P-7762455-44rev7 744-95 744-682	NM-9 (2) NM-9a (2) NM-12 SEE NOTE
-48853-B10	CAPACITOR, fixed: NT-48853 w/250 mmf p/m 10%; temp coef ltr B. NOTE: WCA-1 (2); WCA-2.	11/6/37 RE48A143 JAN-C-5	CM30B251K	16-C-29481-3764	N16-C-9974-16	R16-C-9976-25	3D9250-31.1	CD CAW CSL	1WLS 1467LS MWBW	CG CBM	P-7762455-13rev0 744-95	TEX-4 TEX-4a WCA (2) SEE NOTE
-48853-B20	CAPACITOR, fixed: NT-48853 w/250 mmf p/m 20%; temp coef ltr B.	11/6/37 RE48A143 JAN-C-5	CM30B251M	16-C-29486-6244	N16-C-9974-4			CD CAW CAN	1W 1467 C	CKV L-61009-12	TDF (5)	
-48853-C10	CAPACITOR, fixed: N-48853 w/250 mmf p/m 10%; temp coef ltr C.	11/6/37 RE48A143 JAN-C-5	CM30C251K	16-C-29481-3769				CA CL	CL	CAN 817745alt2		
-48853-D5	CAPACITOR, fixed: N-48853 w/250 mmf p/m 5%; temp coef ltr D.	11/6/37 RE48A143 JA -C-5	CM30D251J	16-C-29476-3289				CD	LR			
-48854	CAPACITOR, fixed: mica; 300 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 54/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	11/6/37 RE48A143										
-48854-A2	CAPACITOR, fixed: Navy Type 48854 w/300 mmf p/m 2%; temp coef letter A.	7/5/38 RE48A143		16-C-29655-7639				CAW	1467		GQ	
-48854-A3	CAPACITOR, fixed: NT-48854 w/300 mmf p/m 3%; temp coef ltr A.	11/6/37 RE48A143 16C40		16-C-29660-1323				CAW CSL CD	1467 MW-1220-10 1W	CNA	RAS-1 thru RAS-4 RAS-5 (2)	
-48854-A10	CAPACITOR, fixed: NT-48854 w/300 mmf p/m 10%; temp coef ltr A.	11/6/37 RE48A143 JAN-C-5	CM30A301K	16-C-29665-9559				CSL CAW CD	MW-1220-10	CNA	SG	
-48854-A20	CAPACITOR, fixed: NT-48854 w/300 mmf p/m 20%; temp coef ltr A.	11/6/37 RE48A143 JA -C-5	CM30A301M	16-C-29671-3039			3D9300-20	CD CAW	1W 1467			

SHEET 48-297

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 298

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48854-B5	CAPACITOR, fixed: NT-48854 w/300 mmf p/m 5%; temp coef ltr B.	11/6/47 RE48A143 JAN-C-5	CM30B301J	16-C-29660-9084	N16-C-9992-4	R16-C-9994-13		CAN	C	CGA	9390rev0	NM-9
								CD	1WL	CG	F-7762455-45rev7	NM-9a
										CBM	744-98	NM-11
										CBM	744-672	NM-12
	NOTE: NM-15; NMA; RMB-2; NMT-1; WEB.											SEE NOTE
-48854-B10	CAPACITOR, fixed: NT-48854 w/300 mmf p/m 10%; temp coef ltr B.	11/6/47 RE48A143 JAN-C-5	CM30B301K	16-C-29665-9564	N16-C-9992-9			CD	1W	CG	F-7762455-14rev7	DAH
								CAW	1467	CG	RF-1663-1	DAH-2
								CSL	MWSW	CBWQ	47X334	RBL-3
								CAN	X-1330	CBM	744-98	RBL-4
	NOTE: WCA (10); WCA-1 (10); WCA-2 (4); WCA-3 (2); WDA; WDA-1; MK-10.											SEE NOTE
-48854-C2 1/2	CAPACITOR, fixed: NT-48854 w/300 mmf p/m 2.5%; temp coef ltr C.	11/6/47 RE48A143 16C40		16-C-29659-9756				CAW	1467L	CRR	A-292-7altB	
								CD	1WL			
-48854-D5	CAPACITOR, fixed: NT-48854 w/300 mmf p/m 5%; temp coef ltr D.	11/6/47 RE48A143 JAN-C-5	CM30D301J	16-C-29660-9094				CD	1R			
-48854-D10	CAPACITOR, fixed: NT-48854 w/300 mmf p/m 10%; temp coef ltr D.	11/6/47 RE48A143 JAN-C-5	CM30D301J	16-C-29665-9574	N16-C-9992-6			CD	1R			
-48855	CAPACITOR, fixed: mica; 370 mmf; 500 vdcw; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	11/6/37 RE48A143										
-48855-A20	CAPACITOR, fixed: NT-48855 w/370 mmf p/m 20%; temp coef ltr A.	11/6/37 RE48A143 JAN-C-5	CM30A371M	16-C-29855-8839				CD	1W			
								CAW	1467			
								CSL	MW			
								CAN	C			
-48855-B1	CAPACITOR, fixed: NT-48855 w/370 mmf p/m 1%; temp coef ltr B.	11/6/37 RE48A143 16C40		16-C-29839-6415				CD	1W1S	CBM	744-94	NM-9 (6)
								CAW	14671S			NM-9a (6)
								CSL	MWBW			NM-11
	NOTE: NM-13 (8); NM-13a (8); NMA (8); NMR-2 (8); NMC-1 (8).											NM-12 (8)
												SEE NOTE
-48855-B2	CAPACITOR, FIXED: Navy Type 48855 w/370 mmf p/m 2%; temp coef letter B.	11/6/37 RE48A143		16-C-29840-4405				CD	1W			CBM-46059
												CBM-46060
-48855-B3	CAPACITOR, fixed: NT-48855 w/370 mmf p/m 5%; temp coef ltr B.	11/6/37 RE48A143 16C40		16-C-29844-7263	N16-C-10003-3			CD	1W			
								CAW	1467			
								CSL	MW			
								CAN	C			
-48855-B5	CAPACITOR, fixed: NT-48855 w/370 mmf p/m 5%; temp coef ltr B.	11/6/37 RE48A143 JAN-C-5	CM30B371J	16-C-29845-5884	N16-C-10003-6			CD	1W1S or 1W	CBM	744-93	NM-9 (10)
								CAW	1467	CBM	744-695	NM-9a (10)
								CSL	MW			NM-13 (9)
								CAN	C			NM-15 (10)
	NOTE: NMA (10); NMB-2 (10); WAA (8); WAB (8); WBA (8); WDA (8); WDA-1 (8).											SEE NOTE
												Cont

SHEET 48-298

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 299

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48855-B10	CAPACITOR, fixed: 11/6/37 NT-48855 w/370 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B371K	16-C-29850-6364	N16-C-10003-16			CD	LWLS	CBM	744-93	WDA (9) WDA-1 (9)
-48855-D1	CAPACITOR, fixed: 11/6/37 NT-48855 w/370 mmf p/m 1%; temp coef ltr D.	RE48A143 16C40		16-C-29839-6420	N16-C-10003-5			CD CAW CSL	LRS 1464 MWSDW	CBM	744-228	NJ-4 (2) WFA (6)
-48855-D5	CAPACITOR, fixed: 11/6/37 NT-48855 w/370 mmf p/m 5%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D371J	16-C-29845-5894				CD CAW CSL CMP CMR CAN CD	LRS 1464 MWSDW 602J PW CRW LRLS	CBM	744-881	WFA (7)
-48856	CAPACITOR, FIXED: 11/6/37 mica; 2000 mmf; 500 vdcw, 1000v, DC test; case 53/64" lg x 53/64" wd x 9/32" h max; molded low loss case; 2 axial wire leads.	RE48A143										
-48856-A5	CAPACITOR fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A202J	16-C-31797-5435		R16-C-10240-60	3K3020212	CAW CSL CAN CMR CMP CD	1467 MW C-1220-5 W 502J 1W	CBZ CRV CRP	CO-9351ess4 K-837955-2rev5 35-5039	NM-9 NM-9a RO-2 SG SG-1 SG-28 SEE NOTE
-48856-A10	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 10%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A202K	16-C-31802-5959			3DA2-70	CSL CD CAW CMR	MW-1233-10 1W-12020 1467 W	CBZ CRV CW CZC	CO-9351ess4 K-837955-2rev P-720473-11 ES-682069-22 525-391	EM (3) thru EM-2 (3) BO (2) BO-1 (2) LP (2) SEE NOTE
-48856-A20	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 20%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A202M	16-C-31807-8439			3DA2-73.1	CD CAW CSL	1W5D2 1467 MW	CFP CW CBM	ES-682069-22 574-68	DAV-1 NM-14 NM-14a SEE NOTE
-48856-B2	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 2%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B202G	16-C-31792-3960	N16-C-10240			CD CSL CAW CAN	1W MW 1467 C			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-299

RESTRICTED

RESTRICTED

SHEET 48 - 300

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48856-B5	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B202J	16-C-31797-5484	N16-C-10240-200	R16-C-10240-70	3K3020222	CD MP CSL CAW CMR	1WLS 502J MWBW 1467LS XXM	CFT CG CG CBM CG CBM CRV CAY CG	P-7762455-53rev7 K-27J362-155rev7 744-98 M7463931-19 744-297 F-720538-45 T-7610894-15 K-12J902-181	BG (2) NM-9 NM-9a NM-12 NM-15 PAK PAK-1 RAR (2) RBB RBB-1 SEE NOTE
	NOTE: RBB-2; RBC; RBC-1; RBC-2; SF-1 (4); SR-5; WAC-3										rev13	
-48856-B10	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B202K	16-C-31802-5964	N16-C-10240-24	R16-C-10241	3K3020221	CD CAW CMR CSL CAN	1WLS 1467LS XXM MWBW CLW	CBM CEZ CRV COL COL CRV CG CGG CEZ	744-97 60-651 F-720473-39 909N220CN alt0 909 2203 20 rev1 K-837955-2 rev5 P-7762455-22rev7 21X101443 C-1035	AYA-1 thru AYA-3 BL-5 (11) BL-6 (11) DAK-2 thru DAR-4 NM-11 RBA-1 SU-1 (2) SU-1 (2) SEE NOTE
	NOTE: SX(4); TBS(5) thru TBS-8 (5); TDH thru TDH-4; WDA A (2); WDA -1 (2); AN/APA-6 (3); AN/APA-6A (3); AN/SPA-1 (3); MK-8 Mod 2; MK-16 (2); MK-18; MK-34 Mod 2; MK-34 Mod 3; MK-34 Mod 4.											
-48856-B20	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B202M	16-C-31807-844	N16-C-10240-26	R16-C-10241-3		CD CAW CAN CSL CBN	1WLS 1467LS CW MWBW	CW CW CGG	890-613080-1 iss 1 88-682069-22 P-30068	PF MK-18 N (18) MN-1 (18) MN-2 (18) SEE NOTE
-48856-C2	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 5%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C202G	16-C-31792-3965	N16-C-10240-12	R16-C-10240-45	3K3020233	CD CAW CAN CSL	LRS 1467LST CRW MWSCW			
-48856-C5	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 5%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C202J	16-C-31797-5445	N16-C-10239-10	R16-C-10240-75	3K3020232	CD CAW CSL CMF	1WLS 1467LST MWCW 602J	CBM CG CBM	744-595 K-27J362-155 744-98	NM-15 SK-2 SK-3 SU-1 Con't

SHEET 48-300

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 301

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48856-D1	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 1%; temp coef ltr D. NOTE: TCH-1; TDB; TDB-1; TDH-2; TDH-3; TDH-4.	RE48A143 16C40		16-C-31791-6066	N16-C-10239-9			CD CAW CSL	1RS 1464 MMSDW	CHV	P-72081-2 rev23	RBP-1 RCP TCK SEE NOTE
-48856-D2	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 2%; temp coef ltr D.	RE48A 43 JAN-C-5	CM30D202G	16-C-31792-4014		R16-C-10240-48	3K3020243	CD CAW CSL	1RS 1464 MMSDW			
-48856-D3	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 3%; temp coef ltr D.	RE48A143 16C40		16-C-31797-1548				CD CAW CSL CMF	1R-5RZ 1464 MMSDW 602J	CFE	15.106	OF-1
-48856-D5	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 5%; temp coef ltr D. NOTE: MK-34 Mod 2 (2); MK-34 Mod 3; MK-34 Mod 4.	RE48A143 JAN-C-5	CM30D202J	16-C-31797-5450	N16-C-10239-12	R16-C-10240-80	3K3020242	CD CEC	1R5D2 1R	CEM CW	744-595 alt0	SU MK-18 MK-28 MK-29 Mod2 SEE NOTE
-48856-D10	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 10%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D202K	16-C-31802-5974	N16-C-10240-7			CD CSL CAW CAW	1RS MMSDW 1464 1467S			
-48856-D20	CAPACITOR, FIXED: 4/27/49 Navy Type 48856 w/2000 mmf p/m 20%; temp coef letter D.			16-C-31807-8454				CMR	PW	MWQ	47X307	RBF-3
-48856-E1	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 1%; temp coef ltr E.	RE48A143 16C40		16-C-31791-6071				CD CD	1R 1RS	COL COL	912 2204 60rev3 912 2201 60rev2	
-48856-E2	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 2%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E202G	16-C-31792-3975	N16-C-10240-14	R16-C-10240-49	3K3020253	CD CAW CSL	1RS 1464 MMSDW			
-48856-E5	CAPACITOR, fixed: 11/6/37 NT-48856 w/2,000 mmf p/m 5%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E202J	16-C-31797-5455				CD	1RS	COL	912 2201 10 rev2	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-301

RESTRICTED

RESTRICTED

SHEET 48 - 302

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48857	CAPACITOR, fixed: 11/6/37 mica; 40,000 mmf; 600 vdcw, 1000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 3/4" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48857-A2	CAPACITOR, FIXED: 10/29/48 Navy Type 48857 w/40000 mmf p/m 2%; temp coef letter A.			16-C-34984-3293				CD		CJF	ST-1213	RAU-2
-48857-A10	CAPACITOR, fixed: 11/6/37 NT-48857 w/40,000 mmf p/m 10%; temp coef ltr A. NOTE: NMA; NMB-2; WCA-2; WCA-3.	RE48A112 JAN-C-5	CM60A403E	16-C-34994-5331				CD CSL	9-11040 XW.6-14-10	CBM	744-96	NM-9 NM-9a SEE NOTE
-48857-B5	CAPACITOR, fixed: 11/6/37 NT-48857 w/40,000 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM60B403J	16-C-34989-4776				CAW	1650L	CRR	A106555-403	ATD (2) SEE NOTE
-48857-B10	CAPACITOR, fixed: 11/6/37 NT-48857 w/40,000 mmf p/m 10%; temp coef ltr B. NOTE: WCA; WCA-1; WDA; WDA-1.	RE48A112 JAN-C-5	CM60B403K	16-C-34994-5336	N16-C-10582			CD	9L-11040	CBM	744-96	NM-13 NM-13a SEE NOTE
-48858	CAPACITOR, fixed: 11/12/37 paper dielectric; 8 mf plus 10 minus 3%; 600 vdcw; ES metal can; case 3 3/4" lg x 1 3/4" wd x 4 13/16" h o/a; two screw type term 1/2" h on top of case 2" from c to c; no int gnd connections; two mtg fl 1 1/2" lg, w/four 3/16" diam mtg holes on 4 1/4" x 1" mtg/c. NOTE: NMA (2); NMB-2 (2).	RE48A137 RE13A488		16-C-51457-2200	N16-C-11641-3			CAT CD	S29454 PC539B	CBM	744-48	NM-8 NM-9 NM-9a NM-11 (2) NM-15 (2) NM-13 (2) NM-13a (2) SEE NOTE
-48858-10	CAPACITOR, fixed: 11/12/37 NT-48858 w/8 mf p/m 10%. NOTE: NM-14b; NM-14c; NMA (2); NMC-1 (2); WCA (2); WCA-1 (2); WCA-2 (2); WCA-3 (2); WDA (2); WDA-1 (2); WDA-2 (2); WDA-3 (2); WFA.	RE48A137 RE13A488		16-C-51478-2171	N16-C-11641			CD CAT	PC539B S29454	CBM CBM	744-48 574-327	NM-14 NM-14a SEE NOTE
-48859	CAPACITOR, fixed: 11/12/37 paper dielectric; two sect; 1 and 8 mfd plus 10, minus 3%; 600 vdcw ea sect; ES metal can; 3 3/4" lg x 2 1/4" wd x 4 7/8" h; all impr and filled; three screw type term 1/2" h on bottom of case 1" from c to c; no int gnd connections; two mtg fl on side of case ea w/two 3/16" diam holes 1 1/2" x 4 1/4" c to c. NOTE: NMB-2; NMC-2.	RE13A488		16-C-53824-5335				CD	PC540B	CBM	744-49	NM-8 NM-9 NM-9a NM-11 NM-13 NM-13a NM-15 NMA-2 SEE NOTE
-48859-10	CAPACITOR, fixed: 11/12/37 NT-48859 w/ 1 and 8 mf p/m 10%. NOTE: NM-14a; NM-14b; NM-14c; WAC-1 thru WAC-3; WCA; WDA; WDA-1; WKB; WFA.	RE13A488		16-C-53869-5395	N16-C-12727			CD CAT	PC540B S29455	CBM CBM	744-49 574-328	NMA NM-13 SEE NOTE
-48859-15	CAPACITOR, fixed: 11/12/37 NT-48859 w/ 1 mfd/8 mfd p/m 1%.	RE13A488		16-C-53893-9165	N16-C-12712-7							

SHEET 48-302

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 303

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48860	CAPACITOR, fixed: 11/13/37 electrolytic; 300 mf; 120 vdcw; working temp range minus 20°C to plus 65°C; case 6" lg x 3" wd x 6 1/4" h; metal case; two screw type term on top stand-off ins, term 1" h spaced 3" c to c; both term ins from can; two mtg fl on bottom, two 0.144" diam holes in ea, on 2" x 6 1/2" mtg/c.	RE48A339 RE13A549		16-C-20563-2201	N16-C-9697-125			CD	R-EVMA12258FS	CBM CBM	744-38alt0 744-104	NM-9 (2) NM-9a (2)
-48861	CAPACITOR, fixed: 11/23/37 electrolytic; 3 mfd; 450 vdcw; working temp range minus 20°C to plus 65°C; case 2 1/4" lg x 1" wd x 1" h; two screw type term on top; term ins from can.	RE48A144 RE13A549		16-C-19418-8057	N16-C-9650	R16-C-9650						
-48862	CAPACITOR, fixed: 11/23/37 electrolytic; 8 mfd; 200 vdcw; working temp range minus 20°C to plus 65°C; case 2 1/4" lg x 1" wd x 1" h; two screw type term on top; term ins from can.	RE48A144 RE13A549		16-C-19539-7851	N16-C-9663	R16-C-9660						
-48863	CAPACITOR, fixed: 11/23/37 electrolytic; 8 mf; 450 vdcw; working temp range minus 20°C to plus 65°C; case 1 3/8" lg x 7/8" wd x 4 1/4" h; two screw type term on top; term ins from can.	RE48A144 RE13A549		16-C-19543-6461	N16-C-9664-9	R16-C-9665						
-48864	CAPACITOR, fixed: 11/23/37 electrolytic; 25 mf; 50 vdcw; working temp range minus 20°C to plus 65°C; case 2 1/4" lg x 1" wd x 1" h; two screw type term on top; term ins from can. NOTE: QCL-1 (9) thru QCL-3 (9); QCN-1 (9); QCO (9); WAB (9).	RE48A144 RE13A549		16-C-19784-1426	N16-C-9680	R16-C-9680		CSF	1967-4	CRV CAY CAY	981025-1 T-7610944-19 T-7610894-38	SR SR-2 (4) SR-5 VE VE-1 SEE NOTE
-48865	CAPACITOR, fixed: 12/3/37 paper dielectric; 4 mf plus 10, minus 3%; 600 vdcw; BS metal can; case 1 13/16" lg x 1 1/16" wd x 4" h; oil impr and filled; two screw type term 1/2" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/ 3/16" diam mtg hole 2 1/4" c to c.	RE48A147 RE13A488		16-C-49936-3114	N16-C-11552-1			CD	TDF-6040	CBM CBM CAG	744-54 744-79 P-432-74	LR (9) LR-1 (9) thru LR-3 (9) QCF (9) QCJ (9) QCK-(9)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-303

RESTRICTED

RESTRICTED

SHEET 48 - 304

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48866	CAPACITOR, fixed: 12/14/37 paper dielectric; 4 mfd plus 10, minus 3%; 250 vdcw; BS metal can; case 1 3/4" h x 1 3/4" wd x 2" lg; oil lmpr and filled; two solder lug term 3/8" h, on end of case 1" c to c; no int gnd connections; two 3/8" wd mtg ft w/0.154" diam hole at end opposite term on 1 3/8" c to c; for replacement use NT-48866-A.	RE48A145 RE13A488										TCR (2) TCR-1 (2) TDR (2) TDR-1 (2) TDR-2 (2) TDR-4 (2)
-48866-A	CAPACITOR, fixed: 5/6/38 paper dielectric; 4 mf plus 10, minus 3%; 250 vdcw; BS metal can; case 1 3/4" lg x 1 3/4" wd x 2" h; oil lmpr and filled; two solder lug term 3/8" h, on top of case 1" c to c; no int gnd connections; three 3/8" wd mtg ft w/0.154" diam hole, one at top on ctr line and two on bottom 1 3/8" c to c and 2 1/2" from top hole; same as NT-48866 except has extra mtg.	RE48A145 RE13A488		16-C-49931-1234	N16-C-11344-70 N16-C-11542-300 N16-C-11542							
-48867	CAPACITOR, fixed: 12/21/37 paper dielectric; 10 mmf plus 10, minus 3%; 600 vdcw, 330 vacw at 60 cyc; BS metal can; case 4 5/8" h x 3 3/4" wd x 1 1/4" d o/s; pyranol filled; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections; bkt mtg not supplied. NOTE: TAJ-15 thru TAJ-19; TBA-11 (2); TBA-12; TBA-13; TAQ-10 (2); TIE (3); RRP	RE48A110 RE13A488		16-C-1837-2036	N16-C-11659			CSF CG CG CG CG CG	2526-10 25F685 67X12 9CE1A312 KG-3100 23F104	CG CEM CG CRV CEM	P-7763476-4 744-343 P-7763476-4rev1 M-418301-12 rev1 744-50	JL-3 SU SU-1 TAJ-11 TAJ-13 TAJ-14 (2) SEE NOTE
-48867-10	CAPACIT R, fixed: 12/21/37 NT-48867 w/10 mf p/m 10%.	RE13A488 RE48A110		16-C-51858-2076	N16-C-11665		3DB10-103	CSF CAAI CD	2526-10 A-1000 KPU-3100	CHZ CRV CZC COL CG	00-947 iss B 896205-10 8107 930 1120 00 K52J565-1 rev0	RM (3) RM-1 (3) RM-2 (3) BO (3) BO-1 (3) SEE NOTE
-48868	CAPACIT R, fixed: 12/21/37 paper dielectric; 20 mf plus 10, minus 3%; 600 vdcw, 330 vacw; BS metal can; case 4 5/8" h x 3 3/4" wd x 2 1/2" d o/s; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-52217-2076	N16-C-11694			CD CG	KG-3200 25F254	CEM CG	744-51 K-5260290rev7	JL-3
-48868-10	CAPACITOR, fixed: 12/21/37 NT-48868 w/20 mf p/m 10%.	RE48A110 RE13A488		16-C-52238-2091	N16-C-11694-3			CG CG	25F844 22F928	CG CG	K-9230096rev0 P-7720312F8 rev3	SX (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-304

RESTRICTED

RESTRICTED

SHEET 48 - 305

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-4886g	CAPACITOR, fixed: 12/23/37 paper dielectric; 100,000 mmf plus 10, minus 3%; 1,000 vdcw; HS metal can; case 1 5/16" lg x 1 1/16" wd 1 5/16" h; oil impr and filled; two solder lug term on top 5/8" c to c; no int gnd connections; two mtg bkt at bottom of both sides ea w/one 5/32" slot, 1 5/16" c to c.	RE48A160 RE13A488		16-C-45759-5972	N16-C-11310-13			CG CG	9CE6A6 9CE6A14	CG CRM CBM	K-3977197rev7 CA-202 744-52	CBM-50048 TCP (4) TCP-1 (4) TCP-2 (4) TCP-3 (4) TDF (2)
-48870	CAPACITOR, fixed: 12/23/37 paper dielectric; 5 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 2 1/2" lg x 1 3/16" wd x 4" h o/a; pyranol impr and filled; two ceramic ins screw type term 1 5/32" h located on top 1 1/8" c to c; no int gnd connections; two mtg fl 1" wd on side of case, ea w/ 3/16" diam mtg hole 3" c to c.	RE48A146 RE13A488		16-C-50316-5936				CG	9CE5A25	CBM	744-6	CBM-50048
-48871	CAPACITOR, fixed: 12/28/37 paper dielectric; 2 mf plus 10 minus 3%; 400 vdcw; HS metal can; 2 3/16" lg x 1 5/16" wd x 2" h; oil impr and filled; two screw type term 5/16" h located on top 1 1/2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/ 3/16" diam mtg hole 2 5/8" c to c.	RE48A147 RE13A488		16-C-49173-1927								
-48872	CAPACITOR, fixed: 12/29/37 paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 3/4" wd x 1 2/16" h x 4" lg o/a; oil impr and filled; two solder lug term located on end, spaced 13/16" c to c; no int gnd connections; mtg bkt welded to back w/two 3/16" diam mtg holes 5" c to c.	RE48A168 RE13A488		16-C-49937-3104	N16-C-11551-2							NM-8 NM-9
-48872-10	CAPACITOR, fixed: 12/29/37 NT-48872 w/4 mf p/m 10%. NOTE: NM-11 (3); NM-13 (3); NM-13a (3); NM-15 (3); N	RE48A168 RE13A488	MA (3); NM	16-C-49958-3104	N16-C-11551-1			CD	TC593A	CBM	744-75	NM-9(2) NM-9a(2) SEE NOTE:

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-305

RESTRICTED

RESTRICTED

SHEET 48 - 306

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48873	CAPACITOR, fixed: 12/30/37 paper dielectric; 1 mf plus 10 minus 3%; 400 vdcw; ES metal can; case 1 11/16" lg x 11/16" h x 1 15/16" wd o/a; oil impr and filled; two solder lug term 3/8" h, on end of case 3/4" c to c; no int gnd connections; three 3/8" wd mtg ft w/ 5/32" diam hole, one at top and two on bottom 1 5/16" c to c and 2 5/16" from top hole. NOTE: QCA (4); QCF (4); QCJ (4); QCJ-3 (4); QCJ-4 (4); QCK; QCL-1 (4); QCL-2 (4); QCL-3 (4); QCN-3 (4); QCO (4).	RE48A145 RE13A488		16-C-48792-8951	N16-C-11390			CD	VC-553-C	CRM	744-43	NM-9 NM-9a NM-11(12) NM-13(12) NM-13a(12) NM-15(12) NMA(12) NMA-2(12) SEE NOTE:
-48873-10	CAPACITOR, fixed: 12/30/37 WT-48873 w/1 mf p/m 10%. NOTE: WCA (12); WCA-1 (12); WCA-2 (12); WCA-3 (11); WDA (12); WDA-1 (12); WEA (12).	RE48A145 RE13A488		16-C-48813-8951	N16-C-11390			CD	VC-553-C	CRM	744-43	NMC-1 (12) WAB (4) SEE NOTE
-48874	CAPACITOR, variable: 1/10/38 air; plate meshing type single sect; 3 to 25 mmf; SLC; 0.0195" air gap; 7/8" lg x 15/16" wd x 1 7/32" h shaft and unthreaded bushing 11/32" diam x 5/16" lg o/a; sldr adj; seven nickel plated invar plates; 360 deg rotation; isolantite insulation; post term for stator; lug term for rotor on RH side; two mtg studs 11/32" lg w/ #4-40 thd, csk 82 deg x 9/64" d on 21/32" mtg/c 31/64" from top.			16-C-58940-6750				CRG	APC-25	CRR	B-7175-25100E	OQ
-48875	CAPACITOR, variable: 1/10/38 air; plate meshing type single sect; 3.9 to 50 mmf; SLC; 0.015" air gap; 1 3/32" lg x 15/16" wd x 1 7/32" h shaft and unthreaded bushing 11/32" diam x 5/16" lg o/a; sldr adj; fourteen nickel pl invar plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RH side; two mtg studs 11/32" lg w/ #4-40 thd, csk 82 deg x 9/64" d on 21/32" mtg/c 31/64" from top.			16-C-59718-4886				CRG	APC-50	CRR	B-7175-27100E	GQ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-306

RESTRICTED

RESTRICTED

SHEET 48 - 307

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48876	CAPACITOR, variable: 1/10/38 air; plate meshing type single sect; 4.5 to 75 mmf; SLC; 0.015" air gap; 1 9/32" lg x 1 5/16" wd x 1 7/32" h shaft and unthreaded bushing 1 1/32" diam x 5/16" lg o/a; scdr adj; twenty nickel pl invar plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RE side; two mtg studs 1 1/32" lg w/ #4-40 thd, csk 82 deg x 9/64" d on 2 1/32" mtg/c 3 1/64" from top.			16-C-60233-6776				CEC	APC-75	CRR	B7175-281aeE	
-48877	CAPACITOR, variable: 1/10/38 air; plate meshing type single sect; 5.5 to 100 mmf; SLC; 0.015" air gap; 1 15/32" lg x 1 5/16" wd x 1 7/32" h shaft and unthreaded bushing 1 1/32" diam x 5/16" lg o/a; scdr adj; twenty-seven nickel plated invar plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RE side; two mtg studs 1 1/32" lg w/ #4-40 thd, csk 82 deg x 9/64" d on 2 1/32" mtg/c 3 1/64" from top.			16-C-60609-7521				CEC	APC-100	CRR	B7175-291aeE	QQ
-48878	CAPACITOR, fixed: 2/9/38 mica; 150,000 mmf; 2,500 vdcw, operated 1 amp, 1325v at 800 cyc, 25 amp at 3,000 kc, 50 amp at 1,000 kc, 40 amp at 300 kc, 25 amp at 100 kc; case 4" lg x 5 3/8" max diam; ceramic case; two 5" sq cast aluminum end-cap term ea w/ four 0.377" diam holes spaced 90 deg on 2 7/8" rad circle.	RE48A270 16C40										
-48878-B5	CAPACITOR, fixed: 2/9/38 NT-48878 w/150,000 mmf p/m 5%; temp coef ltr B.	RE48A270 16C40		16-C-36573-2789				CD CD	PL-953-51B 4678	CG CG	405B1-C145 K-7876526-1	TAJ-7 TAJ-9
-48879	CAPACITOR fixed: 2/28/38 mica; 570 mmf; 10,000 vdcw, 9.0 amp at 3,000 kc, 8.0 amp at 1,000 kc, 4.0 amp at 300 kc, 1.3 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 1 7/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48879-B2	CAPACITOR, fixed: 2/28/38 NT-48879 w/570 mmf p/m 5%; temp coef ltr B. NOTE: TAJ-10; TAJ-11; TAJ-13; TAJ-14; TAJ-15; TAJ-16 ; TAJ-17; TAJ-18; TAJ-19.	RE48A122 16C40		16-C-30310-3284				CD	PL-956-50	CG CG	7660607-C125 P7762163-2	TAJ-7 TAJ-9 SEE NOTE:
-48879-B5	CAPACITOR, fixed: 2/28/38 NT-48879 w/570 mmf p/m 5%; temp coef ltr B.	RE48A122 16C40		16-C-30310-3568				CD	PL-956-50			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-307

RESTRICTED

RESTRICTED

SHEET 48 - 308

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-48880	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw, 150v RMS at 800 cyc; HS metal can; case 2 1/2" lg x 1 3/16" wd x 4 7/8" h o/a; oil impr and filled; two screw type term 3/8" h located on top 1" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/ a 3/16" diam mtg hole 3" c to c.	3/10/38 RE48A147 RE13A488		16-C-49936-5996				CD	MC-334	CD K-7809705rev0		
-48880-5	CAPACITOR, fixed: NT-48880 w/4 mf p/m 5%. NOTE: TEL-5; TEL-6; TEL-7; TEL-10; TEL-11; TEL-12; TEL-13.	3/10/38 RE48A147 RE13A488 L-13.		16-C-49915-5936	N16-C-11553-1		3DB4-5			CAY 7607470-35	TEL-2 TEL-3 SEE NOTE:	
-48881	CAPACITOR, fixed: mica; 25,000 mmf; 2,500 vdcw, 12 amp at 3,000 kc, 12 amp at 1,000 kc, 10 amp at 300 kc, 7 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; two stud term on top 7/16" lg, 1 1/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	4/1/38 RE48A131 16C40										
-48881-A5	CAPACITOR, fixed: NT-48881 w/25,000 mmf p/m 5%; temp coef ltr A. NOTE: JKA-1; JKA-4; QCJ-3; QCJ-4; QCL-1; QCL-2; QCL-3; QCM-3; QCM-4; QCN-1; QCO; QCR.	4/1/38 RE48A131 16C40		16-C-34542-1753				CD	678-6S	CBM 744-106	QC-8 QC-9 SEE NOTE:	
-48881-B5	CAPACITOR, fixed: NT-48881 w/25,000 mmf p/m 5%; temp coef ltr B. NOTE: QCA-1; QCB; QCB-1; QCB-2; QCB-3; QCC; QCD; QCE-2; QCE-3; QCJ-5; QCJ-6; QCL-4; QCL-5; QCN-3; QCO-2; QCO-1; WCA; WCA-1; WDA; WDA-1.	4/1/38 RE48A131 16C40		16-C-34542-1755	N16-C-10569-95			CD	PL-678-6LS	CBM 744-106	JK-4 JK-5 SEE NOTE:	
-48881-B10	CAPACITOR, fixed: NT-48881 w/25,000 mmf p/m 10%; temp coef ltr B.	4/1/38 RE48A131 16C40		16-C-34547-2235	N16-C-10570			CD	PL-678-6ts			
-48882	CAPACITOR, fixed: electrolytic; 200 mmf; 25 vdcw, working temp range minus 20°C to plus 65°C; case 4 1/2" lg x 1 3/8" diam; tubr metal case; two solder lug term on top, 13/32" h spaced 3/4" c to c, both term ins from can.	4/5/38 RE48A341 RE13A549		16-C-20456-8036				CRV	80310-3	CRV K-843325rev0		
-48883	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 600 vdcw; HS metal can; 1 7/8" lg x 1" wd x 2 7/8" h; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/ two 0.213" diam mtg holes 13/32" apart 2 3/8" c to c.	4/5/38 RE48A159 RE13A488		16-C-49176-3376	N16-C-11487		3DB2.634	CG CG CG CG	9CE5A93 9CE23F2 23F34 23F2	CRV CG CG CRR	K-860217-8rev6 W-7350697-243 M-7464792-7 A114299 rev0	3i(3) TBR(2) TBR-1(2) TCM(2) TCM-2(2) TCN(2) TCU-2(2) Coq't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-308

RESTRICTED

RESTRICTED

SHEET 48 - 309

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48883-10	CAPACITOR, fixed: NT-48883 w/2 mf p/m 10%.	4/5/38 RE48A159 RE13A488		16-C-49197-3366	N16-C-11487			CG	9CE5A93	CRP	35-5061	Sg-1(3) Sg-28(3) SO-3(2)
-48884	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; BS can; case 2 5/8" lg x 1 3/16" wd x 3 3/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 1 1/8" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 0.213" diam mtg holes 13/32" apart 3 1/8" c to c. NOTE: QCL-7 (2); QGB (2); WFA (2).	4/5/38 RE48A159 RE13A488		16-C-49936-6465	N16-C-11553 N16-C-11552-700			CG CG	26F4 26F111	CRV CRV CBM	K-860217-9rev6 W-303083-153 744-262a1t0	TBL-2 TBL-3 NGA NMB-1(2) QCJ-2(2) QCJ-8(2) QCL(2) SEE NOTE:
-48885	CAPACITOR, FIXED: mica; 25 mmf; 1200 vdcw; body 1 25/32" lg x 1 11/32" wd x 15/32" h; molded low loss bakelite body; one #6-32 NC thd tapped hole ea end 1 1/4" mtg/c; add suffix indicating capacity tolerance in per cent.	4/6/38 RE48A154 RE48A112										
-48885-A10	CAPACITOR, fixed: NT-48885 w/25 mmf p/m 10%; temp coef 1tr A.	4/6/38 RE48A112 16C40		16-C-26949-7437				CD	9-24025			GG
-48885-B2	CAPACITOR, fixed: NT-48885 w/25 mmf p/m 2%; temp coef 1tr B. NOTE: TCK-2; TCK-3; TCK-4; TCK-5; TCK-6; TCK-7.	4/6/38 RE48A112 16C40		16-C-26938-8877	N16-C-9799-45			CD	9LS-24025	CG	P7762664-2	TCK TCK-1 SEE NOTE:
-48885-B10	CAPACITOR, fixed: NT-48885 w/25 mmf v/m 10%; temp coef 1tr B.	4/6/38 RE48A112 16C40		16-C-26949-7442	N16-C-9799-48	R16-C-9818		CD	9L-24025	CRR	C-55564-31 1eaG	
-48885-B20	CAPACITOR, FIXED: Navy Type 48885 w/25 mmf p/m 20%; temp coef 1tr B.	4/19/48 RE48A154 RE48A112		16-C-26954-9922				CDU	9LS			
-48886	CAPACITOR, fixed: mica; 6,000 mmf; 300 vdcw, 600 vdcw; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end ea w/whole 5/32" diam, holes 1 5/8" c to c.	4/6/38 RE48A149 16C40										
-48886-A10	CAPACITOR, fixed: NT-48886 w/6,000 mmf p/m 10%; temp coef 1tr A.	4/6/38 RE48A149 16C40		16-C-32857-5739				CD	3L-12060			GG
-48886-B10	CAPACITOR, fixed: NT-48886 w/6,000 mmf v/m 10%; temp coef 1tr B.	4/6/38 RE48A149 16C40		16-C-32857-5744		R16-C-10436-10		CD	3LL-12060	CRR	QB15276-18F alt 0	
-48887	CAPACITOR, fixed: mica; 300 mmf; 3,000 vdcw, 3.5 amp at 3,000 kc, 2.0 amp at 1,000 kc, 0.8 amp at 300 kc, 0.4 amp at 100 kc; case 2" lg x 15/16" wd x 1 1/2" h; molded bakelite case; two screw term 7/16" lg, 1 1/2" c to c on top; two mtg ft on bottom, ea w/whole 0.15" diam, holes 2 3/8" c to c.	4/6/38 RE48A222										Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-309

RESTRICTED

RESTRICTED

SHEET 48 - 310

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48887-A5	CAPACITOR, fixed: NT-48887 w/300 mmf p/m 5%; temp coef ltr A.	4/6/38 RE4 A222 16C40		16-C-29662-3420				CD	PL-640-15	CRR	QB15273	QQ
-48887-B5	CAPACITOR, fixed: T-48887 w/300 mmf p/m 5%; temp coef ltr B.	4/6/38 RE48A222 JAN-C-5	CM65B301J	16-C-29662-3422	N16-C-9994-50		3K6530122	CD	PL-640-15L	COL CRR	907N330C QB7716-3-8	TCC-1(3)
-48888	CAPACITOR, fixed: paper dielectric; 5 mf plus 10 minus 3%; 1,000 vdcw; HS metal can; case 5 1/2" lg x 1 3/4" wd x 1 3/4" h o/a; oil impr and filled; two stud term 3/16" h located on top, spaced 1 1/4" c to c; no int gnd connections.	4/12/38 RE48A201 RE13A488		16-C-50320-5502				CD	PC-893			QQ
-48888-20	C PACITOR, fixed: NT-48888 w/5 mf p/m 2%.	4/12/38 RE48A201 RE13A488		16-C-50370-4250		R16-C-11660		CD	PC-893	CRR	QB6917 alt 0	
-48889	C PACITOR, fixed: electrolytic; 8 mf; 450 vdcw; working temp range minus 20°C to plus 65°C; case 3 1/2" lg x 1 3/8" diam max; tubr metal case; two ins wire leads 6" lg; both term ins from can; thd mtg neck 1/2" lg x 5/8" diam, 5/8"-18 thd w/palnut.	4/19/38 RE48A337 RE13A549		16-C-19543-9776	N16-C-9664-18 N16-C-9664-10			OMA	RS-213			
-48890	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 4" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/16" h located on top 1" c to c; no int gnd connections; two mtg fl 13/16" wd on side of case, ea w/a 3/16" diam mtg hole 2 1/4" c to c.	4/28/38 RE48A146 RE13A488		16-C-49936-3119				CD	TD-6040	CRR	A11600-4 iss 0	LD-4(3)
-48891	C PACITOR, fixed: paper dielectric; two sect; 100,000 mmf plus 10 minus 3% ea sect; 400 vdcw; HS metal can; case 1 13/16" lg x 1" wd x 3/4" h; oil filled; two solder lug term 3/8" h on top, spaced 1" c to c; both sect int gnd; two mtg ft 3/8" wd flush w/bottom w/ two 3/16" diam mtg holes spaced 2 1/8" c to c; superseded by NT-4 891-A.	4/28/38 RE13A488 RE48A128		16-C-53104-9285				CD	HC-1258	CRR	A201-3 alt 0	LD-4(3)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-310

RESTRICTED

RESTRICTED

SHEET 48 - 311

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFCR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48891-A	CAPACITOR, fixed: 12/3/40 paper dielectric; 2 sect; 100,000 mmf plus 10 minus 3% ea sect; 600 vdcv ea sect; HS metal can; case 1 13/16" lg x 1" wd x 3/4" h; oil filled; two solder lug term 3/8" h on top, spaced 1" c to c; both sect int grd; two mtg ft 3/8" wd flush w/ bottom, w/ two 3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A128		16-C-53115-6132								
-48892	CAPACITOR, FIXED: 4/28/38 mica; 25 mmf; 600 vdcv; molded low loss bakelite case; 1 1/4" lg x 1 1/8" wd x 23/64" h; 2 solder lug term w/1 hole ea 0.173" diam located on end spaced 1 3/4" c to c; tab mtg; 2 mtg holes 0.144" diam located on ends spaced 1 5/16" c to c.	RE48A221 16C40										
-48892-A10	CAPACITOR, fixed: 4/28/38 NT-48892 w/25 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-26949-2551				CD	4-14025	CRR CRR	A13753-1 4-6Q25	LD-4(3)
-48892-B20	CAPACITOR, FIXED: 2/24/50 Navy Type 48892 w/25 mmf p/m 20%; temp coef ltr B.	RE48A221 16C40		16-C-26954-5355	N16-C-9799-30			CD	4LS			
-48893	CAPACITOR, FIXED: 4/28/38 mica dielectric; 50 mmf; 600 vdcv; 1 1/4" lg x 1 1/8" wd x 11/32" h; molded low loss phenolic body; 2 axial tab terms; 2 mtg holes on 1 side 0.144" diam x 1 5/16" mtg/c; add suffix indicating capacity tolerance in per cent.	RE48A221										
-48893-A10	CAPACITOR, fixed: 4/28/38 NT-48893 w/50 mmf p/m 10%; temp coef ltr A. NOTE: LR-1; LR-2; LR-3; NGA.	RE48A221		16-C-27634-9951				CD	4-14050	CRR	A13753-2	LD-4 LR SEE NOTE
-48893-B5	CAPACITOR, FIXED: 5/14/48 Navy Type 48893 w/50 mmf p/m 5%; temp coef ltr B.	RE48A221		16-C-27629-9477				CD	4-14050			
-48893-B10	CAPACITOR, fixed: 4/28/38 NT-48893 w/50 mmf p/m 10%; temp coef ltr B.	RE48A221		16-C-27634-9955	N16-C-9843-106			CD CD	4L-14050 1WLS	CRR CBM	A1728-20 744-364	WFA(8)
-48893-B20	CAPACITOR, FIXED: 5/14/48 Navy Type 48893 w/50 mmf p/m 20%; temp coef ltr B.	RE48A221		16-C-27640-3437				CD	4L-14050	CRR	A-1728-20	
-48894	CAPACITOR, fixed: 4/28/38 mica; 2820 mmf; 600 vdcv, 1,000v DC test; case 1 1/4" lg x 1 1/8" wd x 11/32" thk; molded low-loss bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48894-B2	CAPACITOR, fixed: 4/28/38 NT-48894 w/2,820 mmf p/m 2%; temp coef ltr B.	RE48A221 16C40		16-C-32182-3796				CD	4-120282	CRR	A-1728-43	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-311

RESTRICTED

RESTRICTED

SHEET 48 - 312

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48895	CAPACITOR, fixed: 4/28/38 mica; 50 mmf; 500 vdcw; case 51/64" lg max x 15/32" w/ max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A18 JAN-C-5										
-48895-A10	CAPACITOR, fixed: 4/28/38 NT-48895 w/50 mmf p/m 10%; temp coef ltr A.	RE48A18 JAN-C-5	CM20A500K	16-C-27634-8671				CAW CSL CD CMR CSL	1468 MO-1410 5W O MOW-1410	CRA CBM CRR CRV CRP CGG	D-774-37 744-573 A1727-6 alt0 P-720473-5 rev9 35-5133 21R6512	LD-4 RAO-2 RAO-6 RAO-7 RAO-9 RBE-1 SEE NOTE
-48895-A20	CAPACITOR, fixed: 4/28/38 NT-48895 w/50 mmf p/m 20%; temp coef ltr A.	RE48A148 JAN-C-5	CM20A500M	16-C-27640-2151				CMR CD CSL CAW	O 5W MO-1410 1468	CER	CO-635 revR	ABK (16) ABK-1 (16) AWK-2 (15) ABK-3 (15) SEE NOTE
-48895-B2	CAPACITOR, fixed: 4/28/38 NT- 8895 w/50 mmf p/m 2%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B500G	16-C-27624-6716	N16-C-9843-97	R16-C-9843-50		CAW CD CSL CMR	1468LS 5WLS MOBW-1410 OXM	CRR	C56734-500	DW-2
-48895-B5	CAPACITOR, fixed: 4/28/38 NT- 8895 w/50 mmf p/m 5%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B500J	16-C-27629-8196	N16-C-9843-108	R16-C-9843-51		CAW CMR CD CSL CMF	1468LS OXM 5WS MOBW 503M	CRV CW	P-720538-18rev30	MK-8 Mod2(2)
-48895-B10	CAPACITOR, fixed: 4/28/38 NT-48895 w/50 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B500K	16-C-27634-8676	N16-C-98 3-100			CD CMF CSL CAN CAW CMR CW	5WLS 503M MOBW-1410 K 1468LS OXM 5WL	CBM CER CRV CZC CCT CRB CDE CW CZR CGG CW CZC	744-404 CO-645 P-720 73-31rev10 5076 7608010-2 CD-1033-7 1sec 2806-4 ES0-677316-2 22G184 21R6578 ES-682069-158 5076	BL-1 thru BL-5 DAJ (2) RBA RBA-1 RBM RBM-1 thru RBM-5 RBO-2 RBS RBS-1 RBS-2 SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-312

RESTRICTED

RESTRICTED

SHEET 48 - 313

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48895-B20	CAPACITOR, fixed: 4/28/38 NT-48895 w/50 mmf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B500M	16-C-27640-2156	N16-C-9843-101	R16-C-9843-53-35		CAW CD CSL CMR CMP	1468LS 54LS MOBW-1410 OXM 503M	CHZ	CO-672	YE (3) YE-1 (3)
-48895-C5	CAPACITOR, fixed: 4/28/38 NT-48895 w/50 mmf p/m 5%; temp coef ltr C. NOTE: TCH (4); TCH-1 (4); TDH (4); TDH-1 (4); TDH-2 (4); TDH-3 (4); TDH-4 (4).	RE48A148 JAN-C-5	CM20C500J	16-C-27629-8201				CD CAN CSL CAW	5R K-1450C MOSCW 1469	CCL CZC CRR	912 4503 10 rev12 7132 CC-20046-1 alt0	DAB (4) DAB-1 (4) DAB-3 (4) RBO-2 (2) SEE NOTE
-48895-C20	CAPACITOR, fixed: 4/28/38 NT-48895 w/50 mmf p/m 20%; temp coef ltr C.	RE48A148 JAN-C-5	CM20C500M	16-C-27640-2161				CMF CAW CD CMF CSL	603-M 1469 5RS PO MOSCW	CHZ COL	912 4503 40rev2	LO-1 thru LO-4
-48895-D2	CAPACITOR, fixed: 4/28/38 NT-48895 w/50 mmf p/m 2%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D500G	16-C-27624-6726	N16-C-9843-98			CD CAW CSL CMR	5RS 1469 MOSIW PO			
-48895-D5	CAPACITOR, fixed: 4/28/38 NT-48895 w/50 mmf p/m 5%; temp coef ltr D. NOTE: OAN; OAX; PF; QCI-8; QCL-7; HGO-1; SF; SF-1; S U; SU-1; W FA; MK-11 Mod1; TS-186/UP.	RE48A148 JAN-C-5	CM20D500J	16-C-27629-8206	N16-C-9843-102	R16-C-9843-52-25	3D9050-36	CD CMR CAW CMR CSL CAN	5R5Q5 MLK50 1469 PO MOSIW K-1450	CBM CRV CRV CZC CBM CG	744-603 alt0 P-720538-5rev30 W-303314-299 7132 744-322 M-7463969-24 rev3	ARB DAK DAJ DAK DAK-1thru DAK-4 LS-1 SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-313

RESTRICTED

RESTRICTED

SHEET 48 - 314

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48895-D10	CAPACITOR, fixed: NT-48895 w/50 mmf p/m 10%; temp coef ltr D.	4/28/38	RE48A148 JAN-C-5	CM20D500K	16-C-27634-8686	N16-C-9843-105	3D9050-33,1	CD CAW CSL CMR CER CD CW	SRS 1469 MOSDW PO MIE50 SR CM20D510K	CG CRB CRV CHZ	M-7463969-Brev3 CD-1034-71aaC P-720473-4rev19 CO-790	RAX-1(11) RBB(7) RBB-1(7) RBB-2(7) RBC(7) RBC-1(7) RBC-2(7) SEE NOTE
	NOTE: SA-1; SA-2; SA-3; SB; SD-a; SD-1; SD-3; SD-4; SJ; TRD; TCS-6; TCX; MX-8 Mod 2.											
48895-D20	CAPACITOR, fixed: NT-48895 w/50 mmf p/m 20%; temp coef ltr D.	4/28/38	RE48A148 JAN-C-5	CM20D500M	16-C-27640-2166	N16-C-9843-107		CD CSL CAW CMR	SRS MOSDW 1469 PO			
-48895-E5	CAPACITOR, fixed: NT-48895 w/50 mmf p/a 5%; temp coef ltr E.	4/28/38	RE48A148 JAN-C-5	CM20E500J	16-C-27629-8211			CAW	1469	CRV	P-721133-10rev5	
-48896	CAPACITOR, fixed: CANCELLED: 500 mmf; 300 vdcv.	4/28/38	RE48A148 16C40					CD	5W	CRR	A1727B-7	ID-4
-48897	CAPACITOR, fixed: paper dielectric; two sect; 500,000 mmf plus 10 minus 3% ea sect; 400 vdcv ea sect; ES metal can; case 1 13/16" lg x 3/4" wd x 1 3/4" h; oil impr and filled; two screw type term 9/16" h located on top 7/8" c to c; both sect int gnd; two mtg fl on bottom of case, ea w/ 3/16" diam mtg hole 2 1/8" c to c.	4/28/38	RE48A147 RE13A488		16-C-53570-4350			CD		CRR	A208A-2 ait A	ID-1
-48898	CAPACITOR, variable: air; plate meshing type single sect; 2 to 3 mmf; SIL; 0.060" air gap; 13/16" lg x 15/16" wd x 1 7/32" h shaft 5/32" diam x 15/32" lg shaft brg 9/32" diam x 7/16" lg; round shaft; two gold plated invar steel plates; 360 deg rotation; isolantite insulation; stator post term, lug term for rotor on top; single 9/32" hole for brg two mtg studs tapped for #4-40 screws in base on 21/32" mtg/c 1/2" from top.	4/28/38			16-C-57976-7721			CRC	APC	CRR	A-A10205aitA	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-314

RESTRICTED

RESTRICTED

SHEET 48 - 315

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48899	CAPACITOR, fixed: 4/29/38 paper dielectric; 4 mf plus 10 minus 3%; 330 vacw 60 cyc, 600 vdcw; HS metal can; case 2 1/2" lg x 1 13/16" wd x 3 1/4" h; pyranol impr and filled; two screw type term 7/8" h located on top 1 1/8" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/0.228" diam mtg hole 3 1/16" c to c.	RE48A147 RE13A488		16-C-49932-3920				CG	9CE1A305	CRR	A11746 iss 0	LD-1
-48900	CAPACITOR, fixed: 5/2/38 mica; 2,500 mmf; 500 vdcw, 1,000v DC test; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48900-A10	CAPACITOR, fixed: 5/2/38 NT-48900 w/2,500 mmf p/m 10%; temp coef ltr A.	RE48A149 16C40		16-C-32013-6291				CD	3L-12025			TBL-2 TBL-3
-48900-B10	CAPACITOR, fixed: 5/2/38 NT-48900 w/2,500 mmf p/m 10%; temp coef ltr B.	RE48A149 16C40		16-C-32013-6296	N16-C-10300			CD	FL-3	CRV	K-823039-4rev3	
-48901	CAPACITOR, FIXED: 5/2/38 mica dielectric; 30 mmf; 500 vdcw; 27/32" lg x 1/2" wd x 3/8" h; thermo-plastic body; 2 axial wire leads; term mtg; ad4 suffix indicating capacity tolerance in per cent.	RE48A238 RE48A154										
-48901-B10	CAPACITOR, fixed: 5/2/38 NT-48901 w/30 mmf p/m 10%; temp coef ltr B.	RE48A238 16C40		16-C-27133-7252	N16-C-9829			CRV	Model H	CRV	M-86016-527rev0	TBL-2 TBL-3
-48901-R20	CAPACITOR, FIXED: 5/4/48 Navy Type 48901 w/30 mmf p/m 20%; temp coef ltr B.	RE48A238 RE48A154		16-C-27138-9732				CRV	H			
-48902	CAPACITOR, fixed: 5/2/38 mica; 70 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo plastic case; two wire leads.	RE48A238 16C40										
-48902-B10	CAPACITOR, fixed: 5/2/38 NT-48902 w/70 mmf p/m 10%; temp coef ltr B.	RE48A238 16C40		16-C-28056-9251	N16-C-9870			CRV	Model H	CRV	M-86016-528 rev0	TBL-2 TBL-3
-48903	CAPACITOR, fixed: 5/2/38 mica; 150 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	RE48A238 16C40										
-48903-B10	CAPACITOR, fixed: 5/2/38 NT-48903 w/150 mmf p/m 10%; temp coef ltr B.	RE48A238 16C40		16-C-28980-2252	N16-C-9954-7			CRV	Model H	CRV	M-86016-529rev0	TBL-2 TBL-3
-48904	CAPACITOR, fixed: 5/2/38 mica; 300 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	RE48A238 16C40										
-48904-B10	CAPACITOR, fixed: 5/2/38 NT-48904 w/300 mmf p/m 10%; temp coef ltr B.	RE48A238 16C40		16-C-29665-9652				CRV	Model H	CRV	M-86016-530rev0	TBL-2 TBL-3
-48905	CAPACITOR, fixed: 5/2/38 mica; 700 mmf; 500 vdcw; case 27/32" lg x 1/2" wd x 5/16" thk; thermo-plastic case; two wire leads.	RE48A238 16C40										
-48905-B10	CAPACITOR, fixed: 5/2/38 NT-48905 w/700 mmf p/m 10%; temp coef ltr B.	RE48A238 16C40		16-C-30589-2652	N16-C-10067-1			CRV	Model H	CRV	M-86016-531rev0	TBL-2 TBL-3

SHEET 48-315

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 316

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S BWC OR PART NO	EQUIPMENT USED IN
-48906	CAPACITOR, fixed: 5/4/38 paper dielectric; 3 mf plus 10 minus 3%; 2,000 vdcw; HS metal can; case 3 3/4" lg x 1 1/4" wd x 4 3/4" h; oil impr and filled; two ins screw type pillar term 1" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/0.190" diam mtg hole 1/4" c to c.	RE48A146 RE13A488		16-C-49563-5913	N16-C-11525			CAY CAY	S 1087313 FL	CAY CAY CAY	T7605600-58 92-D-820rev0 T7606408-38 R-7810057-96	GP-4 TCB-2 TCE
-48906-10	CAPACITOR, fixed: 5/4/38 NT-48906 w/3 mf p/m 10%.	RE48A146 RE13A488		16-C-49584-5913				CAY		CAY CAY	T-7609856-6 T-7606591-6 7609848-14	TCE-1 TCE-2 TDE SEE NOTE
-48907	CAPACITOR, variable: 5/14/38 air; plate meshing type single sect; 4 to 35 mmf (const freq chg); MLF; 0.0245" air gap; 1 21/32" lg x 2 3/32" wd x 1 15/16" h shaft 1/4" diam x 3/32" lg bushing 13/32" lg x 3/8-32 thd; screw adj; five gold pl brass plates; clockwise rotation; isolantite ins; lug term; single hole mtg by 3/8" diam mtg bushing or base mtg by 2 mtg feet ea w/one #6-32 tapped hole on 1 7/32" mtg/c.			16-C-59411-1631				CHC	MC-35-M	CRR CRR	A124151esB C215047 chgC	LD-4
-48908	CAPACITOR, variable: 5/14/38 air; plate meshing type single sect; 13 to 320 mmf; MLF; 0.0245" air gap; 3 7/16" lg x 2 3/32" wd x 1 15/16" h w/ plates out of mesh, shaft 1/4" diam 3/32" lg, bushing 3/8"-32 thd 13/32" lg FMS; rounded shaft adj; forty-three cad pl brass plates; clockwise rotation; isolantite ins; lug term; single hole 3/8" diam bushing mtg, or base mtd by two mtg ft ea w/one #6-32 tapped hole 2 23/32" c to c; superseded by NT-48908-A.			16-C-61711-7721				CHC	MC-325-M	CRR CRR	A-11000-71esB A-124151esB	LD-4
-48908-A	CAPACITOR, variable: 6/8/45 air; plate meshing type single sect; 13.5 to 320 mmf; MLF; 0.0245" air gap; 3 7/32" lg x 2 3/32" wd x 1 15/16" h, w/ plates out of mesh, shaft 1/4" diam x 1/2" lg, bushing 13/32" lg x 3/8"-32 thd; rounded shaft adj; forty-three cad pl brass plates; clockwise rotation; isolantite ins; lug term; single hole 3/8" diam mtg bushing or base mtg by two mtg feet ea w/ one #6-32 tapped hole 2 23/32" c to c.			16-C-61711-7881	N16-C-12472			CHC	MC-325-M	COL COL	922 1400 00 922N14rev1	TCA (8)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-316

RESTRICTED

RESTRICTED

SHEET 48 - 317

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFOR	MANUFACTURER'S PART NUMBER	Con. Fractor	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48909	CAPACITOR, fixed: paper dielectric; 20,000 mmf plus 10 minus 3%; 2000 vdcw; 2200v peak; ES metal can; case 1 13/16" lg x 1 1/16" wd x 2 1/8" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/16" h located on top 13/16" c to c; no int grd connections; two mtg fl 13/16" wd on side of case, ea w/a 3/16" diam mtg hole 2 1/4" c to c.	6/6/38 RE48A146 RE13A488		16-C-43103-2854	N16-C-11030			CD	PC-961	CAY CAY	T-7605600-123 K-7809148-1 sub1	GP-4
-48909-10	CAPACITOR, fixed: T-48909 w/20,000 mmf p/m 10%.	6/6/38 RE48A146 RE13A488		16-C-43124-2854	N16-C-11030-20			CAW CD	AX-1002 PC-961	CAY CAY	T-7609856-20 T-7606591-20	TCE-1 TCE-2
-48910	CAPACITOR, FIXED: mica dielectric; 50 mmf; 1200 vdcw; 1 25/32" lg x 1 11/32" wd x 5/32" h; molded phenolic body, low loss; one #6-32 NC tapped hole ea end 1 1/4" c to c; term mtg; add suffix indicating capacity tolerance in per cent.	6/13/38 RE48A112 RE48A154										
-48910-A10	CAPACITOR, fixed: NF-48910 w/ 50 mmf p/m 10%; temp coef ltr A.	6/13/38 RE48A112 16C40		16-C-27635-5837				CD CAW CAN	9L-24050 1651 A2L2450	CKV	I-61014-1 rev 1	
-48910-B2	CAPACITOR, fixed: NF-48910 w/50 mmf p/m 2%; temp coef ltr B. NOTE: TBA-6 (4); TBA-10 (4); TBC-5 (2); TCE; TCE-1 thru TCE-7	6/13/38 RE48A112 16C40		16-C-27629-3877	N16-C-9843-118			CD	9L-24050	CG CG	P-7762664-8 W-7350697-209	TBR TBR-1 SEE NOTE
-48910-B5	CAPACITOR, fixed: NF-48910 w/50 mmf p/m 5%; temp coef ltr B. NOTE: TBA-12 (4); TBA-13 (4); TCM; TCM-2; TCN; TCU-2	6/13/38 RE48A112 16C40		16-C-27630-5327	N16-C-9843-117			CD CAN	9L-24050	CG CG	P-7761560-4rev4 P-7764687-8	TBA-8 (4) TBA-11 (4) SEE NOTE
-48910-B10	CAPACITOR, fixed: NF-48910 w/50 mmf p/m 10%; temp coef ltr B.	6/13/38 RE48A112 16C40		16-C-27635-5842	N16-C-9843-116			CD CAW CAW	9L-24050 1651L 8242450	CKV	I-61014-1 rev 1	TDT
-48910-B20	CAPACITOR, FIXED: Navy Type 48910 w/50 mmf p/m 20%; temp coef ltr B.	5/12/48 RE48A112 RE48A154		16-C-27640-8323				CD	9-24050			
-48911	CAPACITOR, fixed: mica; 60 mmf; 1200 vdcw, 2500v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	6/13/38 RE48A112 16C40										
-48911-A10	CAPACITOR, fixed: NF-48911 w/60 mmf p/m 10%; temp coef ltr A.	6/13/38 RE48A112 16C40		16-C-27793-8237				CD	9-24060			Con't

SHEET 48-317

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 318

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48911-B2	CAPACITOR, fixed: 6/13/38 NT-48911 w/60 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-27783-6277				CD	9-24060			
-48911-B5	CAPACITOR, fixed: 6/13/38 NT-48911 w/60 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40		16-C-27788-7757	N16-C-9850			CD	9-24060			
-48911-B10	CAPACITOR, fixed: 6/13/38 NT-48911 w/60 mmf p/m 10%; temp coef ltr B. NOTE: TAQ-5 (2); TAQ-6 (2); TAQ-10 (2); TCM; TCM-2; TCN; TCU-2	RE48A112 16C40		16-C-27793-8242	N16-C-9851			CD CAN	9L-24060	CG CG	P-7761560-12rev9 W-7350697-222	TBR (2) TBR-1 (2) SEE NOTE
-48912	CAPACITOR, fixed: 6/13/38 mica; 500 mmf; 1200 vdcw; 2500v DC test; case 1 3/4" lg x 15/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48912-A10	CAPACITOR, fixed: 6/13/38 NT-48912 w/500 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-30167-8237				CD CAW CAN	9-23050 1651 AZL 2350	CKV	I-61014-11 rev1	TBR TBR-1
-48912-B2	CAPACITOR, fixed: 6/13/38 NT-48912 w/500 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-30157-6282				CD	9-23050	CG	P-7762664-29	TCJ (2) TCJ-1 (2)
-48912-B10	CAPACITOR, fixed: 6/13/38 NT-48912 w/500 mmf p/m 10%; temp coef ltr B. NOTE: TCU-1 (2); TDI (2).	RE48A112 16C40		16-C-30167-8242	N16-C-10020		3DE9500-98	CD CAW CAN	9L-23050 1651L AZL2350	CG CKV	P-7761560-5rev8 I-61014-11rev1	TCN (2) TCN-1 (2) TCU (2) SEE NOTE
-48913	CAPACITOR, fixed: 6/13/38 mica; 2000 mmf; 1200 vdcw; 2500v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite test; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48913-A10	CAPACITOR, fixed: 6/13/38 NT-48913 w/2,000 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-31803-3037				CD CAN	9-22020 A-25			
-48913-B2	CAPACITOR, fixed: 6/13/38 NT-48913 w/2,000 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-31793-1082	N16-C-10241-54			CD	9-22020	CG	P-7762664-38	TBC-5
-48913-B5	CAPACITOR, fixed: 6/13/38 NT-48913 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A112 16C40		16-C-31798-2562				CD	9L-22020	COL	925N220H 1880	TCA-1
-48913-B10	CAPACITOR, fixed: 6/13/38 NT-48913 w/2,000 mmf p/m 10%; temp coef ltr B. NOTE: TCB; TCB-1; TCM; TCM-2; TCN; TCU-2; TDR-1 thru TDR-4	RE48A112 16C40		16-C-31803-3042	N16-C-10241-51 N16-C-10241-52		3DA2-10.1	CD CAN	9L-22020 825	CG CG COL	P-7761560-11rev8 W7350697-221 925 2201 20	TBR TBR-1 TCC SEE NOTE

SHEET 48-318

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 319

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A B O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48914	CAPACITOR, fixed: mica; 1100/2700 mmf; 1000 vdcw 0.4/0.55 amp at 3000 kc, 0.25/0.35 amp, at 1000 kc, 0.15/0.23 amp at 300 kc, 0.08/0.12 amp at 100 kc; 2 5/16" lg x 1 17/64" wd x 1 27/32" h; three #10-32 screw term 13/16" c to c; two 0.180" diam mtg holes 2.625" c to c; 2 sect; add suffix indicating capacity tolerance in per cent.	6/13/38 RE48A236 16040										
-48914-B10	CAPACITOR, FIXED: Navy Type 48914 w/1100/2700 mmf p/m 10%; temp coef 1 tr B.	5/23/49		16-C-39428-4910				CDU	61S			
-48914-D2	CAPACITOR, fixed: NT-48914 w/1100/2700 mmf p/m 3%; temp coef 1 tr D. NOTE: TCM (2); TCM-1 (2); TCU (2); TCU-1 (2).	6/13/38 RE48A236 16040			N16-C-10150			CD	PL-829-6HL	CG CG	M-7462693-2rev1 W-7350699-451	TBR TBR-1 SEE NOTE
-48915	CAPACITOR, fixed: mica; 5,000 mmf; 5000 vdcw, 20 amp at 3000 kc, 18 amp at 1000 kc, 12 amp at 300 kc, 7 amp at 100 kc; case 3"h x 3 1/2"diam; ceramic case; one fl elliptical end term w/two 17/64" diam holes in ea, 4 1/4" c to c.	6/13/38 RE48A122 16040										
-48915-B5	CAPACITOR, fixed: NT-48915 w/5,000 mmf p/m 5%; temp coef 1 tr B. NOTE: TCM; TCM-2; TCM; TCU-2.	6/13/38 RE48A122 16040		16-C-32696-4295				CD CAN	PL-178-50	CG CG	W-7350697-235 W-7462694-1	TBR TBR-1 SEE NOTE:
-48915-B10	CAPACITOR, fixed: NT-48915 w/5,000 mmf p/m 10%; temp coef 1 tr B.	6/13/38 RE48A122 16040		16-C-32701-5500	N16-C-10421			CD	PL-178-50			
-48916	CAPACITOR, fixed: paper dielectric; 150,000 mmf plus 10 minus 3%; 2000 vdcw, 405v AC at 1000 cyc; BS metal can; case 1 7/8" lg x 1" wd x 2 7/16" h o/a; oil impr and filled; two screw type term 3/8" h located on top 13/16" c to c; no int gnd connections; two mtg fl 7/8" wd on side of case, ea w/two 7/32" diam mtg holes 13/32" apart 2 3/8" c to c; for replacement use only. NOTE: TCU-1; TCU-2.	6/14/38 RE48A158 RE13A488		16-C-45953-2953				CG	5213288-1	CG	W-7350697-246	TBR (2) TBR-1 (2) TCM TCM-1 TCM-2 TCN (2) TCN-1 (2) TCU SEE NOTE:
-48916-3	CAPACITOR, fixed: NT-48916 w/150,000 mmf p/m 3%; for replacement use only.	6/14/38 RE48A158 RE13A488		16-C-45916-1210				CG	5213288-1	CG	K-522234rev3	

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-319

RESTRICTED

RESTRICTED

SHEET 48 - 320

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	F S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	NFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48917	CAPACITOR, fixed: 6/14/38 paper dielectric; 10 mf plus 10 minus 3%; 1500 vdcw; HS metal can; case 3 3/16" wd x 3 7/8" lg x 4 25/32" h, o/a; oil impr and filled; 2 ceramic ins screw type term 1 3/16" h located on top 2" c to c; no int gnd connections; 2 mtg fl on bottom of case ea w/two 9/32" diam mtg holes 1 15/16" apart 4 1/2" c to c. NOTE: TCU (2); TCU-1 (2).	RE48A159 RE13A488		16-C-51841-9130				CG	9CB5A92	CG	K-5222610 rev 2 P-7762164-3	TBR TBR-1 SG (2) TCM (2) TCM-1 (2) TCN (2) TCN-1 (2) SEE NOTE:
-48917-10	CAPACITOR, fixed: 6/14/38 NT-48917 w/10 mf p/m 10%.	RE48A159 RE13A488		16-C-51862-9119	N16-C-11680			CG	9CB5A92	CRP	35-5003	SG-1 (2) SG-2S (2)
-48918	CAPACITOR, fixed: 6/24/38 paper dielectric; 1 mf plus 10 minus 3%; 250 vdcw, 800v DC test; HS metal can; case 3 7/16" h x 1 1/2" lg x 1" wd; white wax impr and filled; two hooked wire term 1" h in diagonal corner on bottom; no int gnd connections; two #8-32 thd mtg studs in diagonal corners of top on 1" x 3/8" mtg/c. NOTE: QCM-1 (9); QCM-2 (9); QCM-3 (9); QCN-3 (9); QC 0-2 (9); QCQ (7); QCQ-1 (8); QCR (7); QCR -1 (8); QCS (9); QCS-1 (9); QCT (9); QCT-1 (9); QGA (5).	RE48A224 RE13A488		16-C-48790-9642	N16-C-11383-92			CW CW	229C D-155003			JKA-1 (9) JKA-5 (9) JKA-5a (9) QCJ-5 (9) QCJ-6 (9) QCL-4 (9) QCL-5 (9) SEE NOTE:
-48918-10	CAPACITOR, fixed: 6/24/38 NT-48918 w/1 mf p/m 10%.	RE48A224 RE13A488		16-C-48811-9642	N16-C-11384			CW	D-160800	CEM	744-13A	QCJ-9 (9) QCL-4 (9) SEE NOTE:
-48918-15	CAPACITOR, fixed: 6/24/38 NT-48918 w/1 mf p/m 15%	RE48A224 RE13A488		16-C-48831-5081	R16-C-11384			CW CW CW	229C D-155003 ESA-3409751s12	CEM CW CW	744-13 ES-614126-2188A ES-609967-2188B	JKA-1 (9) QCM-3 (9) OH RAM
-48919	CAPACITOR, fixed: 6/24/38 paper dielectric; 3 mf plus 10 minus 3%; 1500 vdcw, 800v DC test; HS metal can; case 4 15/16" lg x 1 1/2" wd x 4 3/4" h o/a; oil impr and filled; two stand-off type term 7/8" h located on top, spaced 1" c to c; no int gnd connections; four mtg studs 1/2" h x #8-32 thd located on top on 4" x 3/4" mtg/c.	RE48A202 RE13A488		16-C-49562-1547								
-48919-15	CAPACITOR, fixed: 6/24/38 NT-48919 w/3 mf p/m 15%.	RE48A202 RE13A488		16-C-49598-3946				CW	D-155002	CW	ES0-613062-2 188B	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-320

RESTRICTED

RESTRICTED

SHEET 48 - 321

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48920	CAPACITOR, fixed: paper dielectric; five sect; 250,000 mmf/1.75 mf/ 500,000 mmf/ 1 mf/2 mf plus 10 minus 3%; 250 vdcw ea sect, 800v DC test; ES metal can; case 4 15/16" lg x 1 1/2" wd x 3 5/8" h o/a; oil filled; six solder lug term located on bottom 9/16" c to c 5/8" h; no int gnd connection; two thd mtg studs 7/16" h x #8-32 thd on bottom 4" c to c.	6/24/38 RE48A196 RE13A488		16-C-54935-9924	N16-C-12680							GN RAM
-48920-15	CAPACITOR, fixed: NT-48920 w/250,000 mmf/ 1.75 mf/500,000 mmf/1 mf/2 mf p/m 15% ea sect.	6/24/38 RE48A196 RE13A488		16-C-54942-8984		R16-C-11339		CW	D-155001	CW CW	ES0-613062 ES0-6263751e8	
-48921	CAPACITOR, fixed: paper dielectric; two sect; 200,000 mmf plus 10 minus 3% ea sect; 400 vdcw ea sect; ES metal can; case 1 13/16" lg x 7/8" wd x 3/4" h o/a; oil filled; two solder lug term 3/8" h on top, spaced 1" c to c; both sect int gnd; two mtg ft 3/8" wd flush w/bottom w/two 3/16" diam mtg holes spaced 2 1/8" c to c.	6/24/38 RE13A488 RE48A128		16-C-53235-6630		R16-C-11338		CD	VC-566			CW RAM
-48921-10	CAPACITOR, fixed: NT-48921 w/200,000 mmf p/m 10% ea sect.	6/24/38 RE13A488 RE48A128		16-C-53239-4445				CD	VC-566	CW	ES0-6130793 1e8A	
-48922	CAPACITOR, fixed: paper dielectric; 600,000 mmf plus 10 minus 3%; 400 vdcw; ES metal can; case 1 13/16" lg x 1 9/32" wd x 3/4" h o/a; oil filled; two screw type term 7/16" h on top, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/two 3/16" diam mtg holes spaced 2 1/8" c to c.	6/24/38 RE13A488 RE48A128		16-C-47652-9445				CD	VC-1389			GN RAM
-48922-10	CAPACITOR, fixed: NT-48922 w/600,000 mmf p/m 10%.	6/24/38 RE13A488 RE48A128		16-C-47673-9445				CD	VC-1389	CW	ES0-613060-61e8A	
-48923	CAPACITOR, fixed: paper dielectric; four sect; 100,000 mmf plus 10 minus 3% ea sect; 300 vdcw ea sect; ES metal can; case 3 1/4" lg x 5/8" wd x 2 1/2" h o/a; oil impr and filled; four stud type term 7/16" h located on bottom, spaced 1/2" c to c; all sect int gnd; four mtg ft w/5/32" diam mtg holes spaced 3 9/16" c to c.	6/24/38 RE48A203 RE13A488		16-C-54822-6183		R16-11336-100		CD	HC-1269			GN RAM
-48923-10	CAPACITOR, fixed: NT-48923 w/100,000 mmf p/m 10% ea sect.	6/24/38 RE48A203 RE13A488		16-C-54825-4144				CD	HC-1269	CW	ES0-613079-1 1e8A	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-321

RESTRICTED

RESTRICTED

SHEET 48 - 322

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48924	CAPACITOR, fixed: 6/24/38 paper dielectric; 500,000 mmf plus 10 minus 3%; 300 vdcw; BS metal can; case 1 3/8" lg x 5/8" wd x 2 5/16" h o/a; oil impr and filled; one solder lug term 9/16" h located on top; int gnd; two mtg studs 3/8" h x 0.138"-32 thd located on top spaced 7/8" c to c.	RE48A204 RE13A488		16-C-47271-7294		R16-C-11344		CD	HC-1257			GN RAM
-48924-10	CAPACITOR, fixed: 6/24/38 NT-48924 w/500,000 mmf p/m 10%.	RE48A204 RE13A488		16-C-47292-7294				CD	HC-1257	CW	ESO-613079-2 iss A1	
-48925	CAPACITOR, fixed: 6/24/38 paper dielectric; 1 mf plus 10 minus 3%; 300 vdcw; BS metal can; case 1 3/8" lg x 5/8" wd x 3 5/16" h o/a; oil impr and filled; one solder lug term 9/16" h located on top; int gnd; two mtg studs 3/8" h x 0.138"-32 thd located on top, spaced 7/8" c to c.	RE48A204 RE13A488		16-C-48791-7294				CD	HC-1256			GN RAM
-48925-10	CAPACITOR, fixed: 6/24/38 NT-48925 w/1 mf p/m 10%.	RE48A204 RE13A488		16-C-48812-7294				CD	HC-1256	CW	ESO-613079-2 iss A1	
-48926	CAPACITOR, fixed: 6/24/38 paper dielectric; three sect; 1.4 mf plus 20 minus 10%; 400 vdcw ea sect; BS metal can; case 1 7/8" lg x 1 7/8" wd x 2 11/16" h o/a; oil impr and filled; three solder lug term 5/16" h located on top; int gnd; two mtg ft w/ 5/32" diam mtg holes, one on bottom one side, one on top opposite side.	RE48A169 RE13A488		16-C-54685-6951								GN RAM
-48926-10	CAPACITOR, fixed: 6/24/38 NT-48926 w/1.4 mf p/m 10% ea sect.	RE48A169 RE13A488		16-C-54685-7051				CD	VC-509			
-48927	CAPACITOR, fixed: 6/25/38 mica; 125 mmf; 3,000 vdcw, 2.2 amp at 3000 kc, 0.8 amp at 1000 kc, 0.3 amp at 300 kc, 0.1 amp at 100 kc; 2 1/16" lg x 61/64" wd x 1 17/32" h; molded bakelite case; two screw term 7/16" lg, 1 1/2" c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-48927-B5	CAPACITOR, fixed: 6/25/38 NT-48927 w/125 mmf p/m 5%; temp coef ltr B.	RE48A222 16C40		16-C-28791-8227		R16-C-9808-10		CD	PL-768-151S	CW	ESO-613060-2 iss A1	GN RAM

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-322

RESTRICTED

RESTRICTED

SHEET 48 - 323

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48928	CAPACITOR, fixed: 6/25/38 mica; 175 mmf; 3000 vdcw, 2.5 amp at 3000 kc, 1.0 amp at 1000 kc, 0.5 amp at 300 kc, 0.2 amp at 100 kc; 2" lg x 15/16" wd x 1 1/2" h; molded bakelite case; two screw term 7/16" lg, 1 1/2" c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-48928-A5	CAPACITOR, fixed: 6/25/38 NT-48928 w/175 mmf p/m 5%; temp coef ltr A.	RE48A222 16C40		16-C-29108-4020				CD	PL-668-15			GN RAM
-48928-B5	CAPACITOR, fixed: 6/25/38 NT-48928 w/175 mmf p/m 5%; temp coef ltr B.	RE48A222 16C40		16-C-29108-4021				CD	PL-668-15IS	CW	ES0-613060-2 see A1	
-48929	CAPACITOR, FIXED: 6/25/38 mica; 4000 mmf; 500 vdcw, 1000 vac; case 53/64" lg x 53/64" wd x 1 1/32" d max; molded low loss bakelite case; 2 axial wire leads.	RE48A143										
-48929-A10	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 10%; temp coef ltr A. NOTE: RBL-6; MK-8; MK-8 Mod1; MK-8 Mod2; MK-8 Mod3; MK-27; RAM.	RE48A143 JAN-C-5	CM35A402K	16-C-32461-9959				CAW CD CSL CAN	1467 1W MW C	CHA CW	D-775 ES-682029-26	GN RBL-2 (2) RBL-4 (2) RBL-5 (2) SEE NOTE
-48929-A20	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 20%; temp coef ltr A.	RE48A143 JAN-C-5	CM35A402M	16-C-32467-3439				CD CSL CAW CAN	1W MW 1467 C			
-48929-B2	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 2%; temp coef ltr B.	RE48A143 JAN-C-5	CM35B402G	16-C-32451-8004				CSL	MWB	CMK	B-250131-2	RCU RCU RCU-1
-48929-B5	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 5%; temp coef ltr B. NOTE: MK-11 Mod1; MK-26 Mod 3; MK-26 Mod 4.	RE48A143 JAN-C-5	CM35B402J	16-C-32456-9484				CD CAW CSL CSL	1WLS 1467LS MWBW-1237-5 MWBW	CG CHZ CIH CRV	P-7762455-56rev7 CO-11131000 CO-780 K-885477-11	TCS-13 TCS-14 AN/UPM-1 AN/UPM-1B SEE NOTE
-48929-B10	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 10%; temp coef ltr B. NOTE: MK-18 (2); MK-19; MK-29 Mod 2; MK-16; MK-10 Mod 5.	RE48A143 JAN-C-5	CM35B402K	16-C-32461-9964				CAN CAW CSL CAN	C-1240 1467LS MWBW CLW	CWQ COL	47X342 see B 909 2403 52rev1	RBL-3 RBL-4 MK-9(2) MK-10 SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-323

RESTRICTED

RESTRICTED

SHEET 48 - 324

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48929-B20	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM35B402M	16-C-32467-3444	N16-C-10372-1			CSL CD CAW	MWB-1237 1WL-12040 1467LS	CW	ES0-613080-1 1881	MM thru MY-3 MY-4 (5)
-48929-C2	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 2%; temp coef ltr C.	RE48A143 JAN-C-5	CM35C402G	16-C-32456-1546				CAW CD CSL CSL	1467L 1WL MWB MECW	CKR CG	A-292-8 alt2 K-27J362-304-2	SC-4 SK SK-2 SK-1M
-48929-C5	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 5%; temp coef ltr C.	RE48A143 JAN-C-5	CM35C402J	16-C-32456-9489			JDA4-102	CAW CD CAN CAN CSL CSL	1467LST 1RS CRW MWCW C-1240C MWSW	CBC CZC CZC	23015rev0 7138 CO-780	RBO-2 TCS-6
-48929-D1	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 1%; temp coef ltr D.	RE48A143 16C40		16-C-32451-1066	N16-C-10370-9			CD CAW CSL	LIR 1464 MWSW			
-48929-D2	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 2%; temp coef ltr D.	RE48A143 JAN-C-5	CM35D402G	16-C-32451-8014				CD CAW CSL	1RS 1464 MWSW			
-48929-D5	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 5%; temp coef ltr D.	RE48A143 JAN-C-5	CM35D402J	16-C-32456-9494				CD CAW CSL CAN	1RS 1464 MWSW C-1240	CZC	7138	RBO-1
-48929-D10	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 10%; temp coef ltr D.	RE48A143 JAN-C-5	CM35D402K	16-C-32461-9974				CD CAW CSL	1RS 1464 MWSW	CRY	W-303314-350	QC7-8 QC7-7 WEA
-48929-E2	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 2%; temp coef ltr E.	RE48A143 JAN-C-5	CM35E402G	16-C-32451-8019				CD CAW CSL	1R 1464 MWSW	COL	912 2401 70 rev2	
-48929-E5	CAPACITOR, fixed: 6/25/38 NT-48929 w/4,000 mmf p/m 5%; temp coef ltr E.	RE48A143 JAN-C-5	CM35E402J	16-C-32456-9499				CD CAW CSL	1R 1464 MWSW	COL	912 2401 10 rev2	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-324

RESTRICTED

RESTRICTED

SHEET 48 - 325

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48930	CAPACITOR, fixed; 6/27/38 mica; 15 mmf; 500 vdcv, 1000 vdcv; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48930-A20	CAPACITOR, fixed; 6/27/38 NT-48930 w/15 mmf p/m 20%; temp coef ltr A.	RE48A149 16C40		16-C-26453-2371			204197/10	CD	3L			GN RAM
-48930-D10	CAPACITOR, fixed; 6/27/38 NT-48930 w/15 mmf p/m 10%; temp coef ltr D.	RE48A149 16C40		16-C-26447-8906				CD	3HLS	CW	ESO-613080-2 1eaA1	
-48931	CAPACITOR, fixed; 6/21/39 mica; 465 mmf; 500 vdcv, 1000 vdcv; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48931-A20	CAPACITOR, fixed; 6/21/39 NT-48931 w/465 mmf p/m 20%; temp coef ltr A.	RE48A149 16C40		16-C-30101-9611				CD	3L			
-48931-D2	CAPACITOR, fixed; 6/21/39 NT-48931 w/465 mmf p/m 2%; temp coef ltr D.	RE48A149 16C40		16-C-30101-8846		R16-C-10017-10		CD	3HLS	CW	ESO-613080-2 1eaC3	
-48932	CAPACITOR, fixed; 6/21/39 mica; 500 mmf; 500 vdcv, 1000 vdcv; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end ea w/hole 5/32" diam holes 1 5/8" c to c.	RE48A149 16C40										
-48932-A10	CAPACITOR, fixed; 6/21/39 NT-48932 w/500 mmf p/m 10%; temp coef ltr A.	RE48A149 16C40		16-C-30167-2291				CD	3L-13050			LP thru LP-4
-48932-A20	CAPACITOR, fixed; 6/21/39 NT-48932 w/500 mmf p/m 20%; temp coef ltr A.	RE48A149 16C40		16-C-30172-4771				CD	3L			
-48932-D2	CAPACITOR, fixed; 6/21/39 NT-48932 w/500 mmf p/m 2%; temp coef ltr D.	RE48A149 16C40		16-C-30156-9346		R16-C-10018-3		CD	3HLS	CW	ESO-613080-2 1eaC3	
-48933	CAPACITOR, fixed; 6/21/39 mica; 720 mmf; 500 vdcv, 1000 vdcv; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end ea w/hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48933-A20	CAPACITOR, fixed; 6/21/39 NT-48933 w/720 mmf p/m 20%; temp coef ltr A.	RE48A149 16C40		16-C-30620-8571				CD	3L			
-48933-D2	CAPACITOR, fixed; 6/21/39 NT-48933 w/720 mmf p/m 2%; temp coef ltr D.	RE48A149 16C40		16-C-30605-4146		R16-C-10034		CD	3HLS			
-48933-D3	CAPACITOR, fixed; 6/21/39 NT-48933 w/720 mmf p/m 3%; temp coef ltr D.	RE48A149 16C40		16-C-30609-6823				CD	3HLS	CW	ESO-613080-2 1eaA1	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-325

RESTRICTED

RESTRICTED

SHEET 48 - 326

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48934	CAPACITOR, fixed: 6/21/39 mica; 830 mmf; 500 vdcw, 1000 vdc; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end ea w/ hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48934-A20	CAPACITOR, fixed: 6/21/39 NT-48934 w/830 mmf p/m 20%; temp coef ltr A.	RE48A149 16C40		16-C-30805-5371				CD	3L			
-48934-D2	CAPACITOR, fixed: 6/21/39 NT-48934 w/830 mmf p/m 2%; temp coef ltr D.	RE48A149 16C40		16-C-30789-9946		R16-C-10075-10		CD	3HLS	CW	ESO-613080-2 1ssC3	
-48934-D2 1/2	CAPACITOR, fixed: 6/21/39 NT-48934 w/830 mmf p/m 2 1/2%; temp coef ltr D.	RE48A149 16C40		16-C-30794-2957				CD	3HLS	CW	ESO-613080-2 1ssA1	
-48935	CAPACITOR, fixed: 6/21/39 mica; 1,330 mmf; 500 vdcw, 1000 DC test; 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end ea w/ hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48935-A20	CAPACITOR, fixed: 6/21/39 NT-48935 w/1,330 mmf p/m 20%; temp coef ltr A.	RE48A149 16C40		16-C-31385-8171				CD	3L			
-48935-D2	CAPACITOR, fixed: 6/21/39 NT-48935 w/1,330 mmf p/m 2%; temp coef ltr D.	RE48A149 16C40		16-C-31370-3746				CD	3HLS	CW	ESO-613080-2 1ssC3	
-48935-D4	CAPACITOR, fixed: 6/21/39 NT-48935 w/1,330 mmf p/m 4%; temp coef ltr D.	RE48A149 16C40		16-C-31374-7757				CD	3HLS	CW	ESO-613080-2 1ssC3	
-48936	CAPACITOR, fixed: 6/21/39 mica; 1500 mmf; 500 vdcw, 1000 vdc; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end ea w/ hole 5/32" diam, holes 1 5/8" c to c.	RE4 A149 16C40										
-48936-A20	CAPACITOR, fixed: 6/21/39 NT-48936 w/1,500 mmf p/m 20%; temp coef ltr A.	RE4 A149 16C40		16-C-31517-7171				CD	3L			
-48936-D2	CAPACITOR, fixed: 6/21/39 NT-48936 w/1,500 mmf p/m 2%; temp coef ltr D.	RE48A149 16C40		16-C-31502-2746		R16-C-10209		CD	3HLS	CW	ESO-613080-2 1ssC3	
-48936-D6	CAPACITOR, fixed: 6/21/39 NT-48936 w/1,500 mmf p/m 6%; temp coef ltr D.	RE48A149 16C40		16-C-31511-6170				CD	3HLS	CW	ESO-613080-2 1ssA1	
-48937	CAPACITOR, fixed: 6/21/39 mica; 4000 mmf; 300 vdcw, 600 vdc; case 1" lg x 5/8" wd x 3/16" thk; molded bakelite case; one lug term 15/32" lg at ea end w/ hole 5/32" diam, holes 1 5/8" c to c.	RE48A149 16C40										
-48937-A10	CAPACITOR, fixed: 6/21/39 NT-48937 w/4,000 mmf p/m 10%; temp coef ltr A.	RE48A149 16C40		16-C-32461-8862				CD	3L-12040			CN RAM
-48937-R10	CAPACITOR, fixed: 6/21/39 NT-48937 w/4000 mmf p/m 10%; temp coef ltr D.	RE48A149 16C40		16-C-32461-8867				CD	3HLS-12040	CW	ESO-613080-2 1ssC3	

SHEET 48-326

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 327

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48938	CAPACITOR, fixed: 6/27/38 mica; 10,000 mmf; 300 vdcw, 600v DC test; case 1 1/32" max lg x 41/64" max wd x 5/16" thk max; molded bakelite case; one wire lead 1 1/2" lg at ea end.	RE48A151 JAN-C-5										
-48938-A5	CAPACITOR, fixed: 6/27/38 NT-48938 w/10,000 mmf p/m 5%; temp coef ltr A.	RE48A151 JAN-C-5	CM40A103J	16-C-33617-5103				CMF	504L	CDU	DD-5286-A-1	GN RAM
-48938-A10	CAPACITOR, fixed: 6/27/38 NT-48938 w/10,000 mmf p/m 10%; temp coef ltr A.	RE48A151 JAN-C-5	CM40A103K	16-C-33622-5583			3DA10-44	CAW CD CMR CSL	1441W 3WS R MEW.3-11-10	CRV	P-720473-15	RAI-6 (4) RAI-7 (4) RAE-7 (4)
-48938-B5	CAPACITOR, FIXED: 11/18/47 Navy Type 48938 w/10000 mmf p/m 5%; temp coef letter B.	JAN-C-5	CM40B103J	16-C-33617-5109								SV
-48938-B10	CAPACITOR, fixed: 6/27/38 NT-48938 w/10,000 mmf p/m 10%; temp coef ltr B. NOTE: RBB (51); RBB-1 (51); RBB-2 (51); RBC (51); RB C-1 (51); RBC-2 (51); RBU (5); RBV (5).	RE48A151 JAN-C-5	CM40B103K	16-C-33622-5588	N16-C-10492	R16-C-10493-30		CAW	1441W	CRV	P-720592-6rev25	ATB RAK-6 (4) SEE NOTE
-48938-B20	CAPACITOR, fixed: 6/27/38 NT-48938 w/10,000 mmf p/m 20%; temp coef ltr B.	RE48A151 JAN-C-5	CM40B103M	16-C-33627-8069	N16-C-10492-11	R16-C- 10495-8-500		CD	3WLS	CW	ES0-613081-2 188A1	ME-16 (6) SS
-48938-C10	CAPACITOR, FIXED: 10/29/47 Navy Type 48938 w/10000 mmf p/m 10%; temp coef letter C.	JAN-C-5	CM40C103K	16-C-33622-5594								SS
-48938-D2	CAPACITOR, FIXED: 11/23/48 Navy Type 48938 w/10000 mmf p/m 2%; temp coef letter D.	JAN-C-5	CM40D103G	16-C-33612-3639								QUB
-48938-E2	CAPACITOR, FIXED: 4/22/48 Navy Type 48938 w/10000 mmf p/m 2%; temp coef letter E.	JAN-C-5	CM40E103G	16-C-33612-3644			3K4010353					AN/YFS-1B
-48938-E10	CAPACITOR, FIXED: 2/20/48 Navy Type 48938 w/10000 mmf p/m 10%; temp coef letter E.	JAN-C-5	CM40E103K	16-C-33622-5604								FO
-48939	CAPACITOR, fixed: 7/11/39 mica; 110 mmf; 500 vdcw; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143 JAN-C-5										
-48939-A20	CAPACITOR, fixed: 7/11/39 NT-48939 w/110 mmf p/m 20%; temp coef ltr A.	RE48A143 JAN-C-5	CM35A111M	16-C-28668-8839	N16-C-9946-60			CAW CD CSL CAN	1467 1W MW C			
-48939-C2 1/2	CAPACITOR, fixed: 7/11/39 NT-48939 w/110 mmf p/m 2.5%; temp coef ltr C.	RE48A143 16C40		16-C-28657-6557				CAW CD CSL	1467L 1WL MWB	CRV	B-6985mltc	
-48939-A2	CAPACITOR, FIXED: 7/5/38 Navy Type 48939 w/110 mmf p/m 2%; temp coef letter A.	RE48A143		16-C-28653-4439				CAW	1467			QQ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-327

RESTRICTED

RESTRICTED

SHEET 48 - 328

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48940	CAPACITOR, fixed: mica; 500 mmf; 500 vdcw, 1000 vdc; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	7/11/39 RE48A143										
-48940-A2	CAPACITOR, fixed: Navy Type 48940 w/580 mmf p/m 2%; temp coef letter A.	7/5/38 RE48A143		16-C-30311-6015				CAW	1467			QQ
-48940-A20	CAPACITOR, fixed: NT-48940 w/580 mmf p/m 20%; temp coef ltr A.	7/11/39 RE48A143 JAN-C-5	CM30A581M	16-C-30311-6794				CAW CD CSL CAN	1467 1W MW C			
-48940-C2 1/2	CAPACITOR, fixed: NT-48940 w/580 mmf p/m 2.5%; temp coef ltr C.	7/11/39 RE48A143 16C40		16-C-30311-6142				CAW CD CSL	1467L 1WL MWB	CRM	B-6989altc	
-48941	CAPACITOR, fixed: mica; 1110 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d; molded bakelite case; two axial wire leads.	7/11/39 RE48A143 16C40										
-48941-A20	CAPACITOR, fixed: NT-48941 w/1110 mmf p/m 20%; temp coef ltr A.	7/11/39 RE48A143 16C40		16-C-31207-1101				CAW CD CSL CAN	1467 1W MW C			
-48941-B2	CAPACITOR, fixed: NT-48941 w/1110 mmf p/m 2%; temp coef ltr B.	7/11/39 RE48A143 16C40		16-C-31206-9604		RL6-C-10155		CD CAW CSL CAN	1WL 1467L MWB C			
-48941-C2 1/2	CAPACITOR, fixed: NT-48941 w/1110 mmf p/m 2.5%; temp coef ltr C.	7/11/39 RE48A143 16C40		16-C-31206-9704				CAW CD CSL	1467LST 1WLST MWC	CRM	B6985 altc	
-48942	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 4" h x 1 3/4" wd x 1" d o/a; castor oil filled; two screw type term #8-32 thd x 7/16" lg on top 13/16" c to c; no int gnd connections; mtg bkt 5 1/4" lg x 3/4" wd welded to side w/two 0.157" holes 4 3/4" c to c. NOTE: QCM-2 thru QCM-4; QCN (2).	7/12/38 RE48A117 RE13A488		16-C-49937-3124				CD	VC-601	CBM	744-118 alt 0	JX-4 QCN JXA-1 JXA-4 JXA-5 JXA-5a QCM-1 SPE NOTE
-48942-10	CAPACITOR, fixed: NT-48942 w/4 mf p/m 10%.	7/12/38 RE48A117 RE13A488		16-C-49938-3124	N16-C-11557			CD	VC-601	CBM	744-118 alt 0	WDA WDA-1
-48943	CAPACITOR, fixed: mica; 2000 mmf; 20,000 vdcw, 22 amp at 3,000 kc, 22 amp at 1,000 kc, 15 amp at 300 kc, 9 amp at 100 kc; case 5 3/4" h x 5" diam; low-loss ceramic case; two elliptical cast aluminum end cap term, ea w/two 0.377" diam holes 5 3/4" c to c.	7/12/38 RE48A117 16C40										

SHEET 48-328

RESTRICTED

NAVSHIPS 900,109 (A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 329

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48943-B5	CAPACITOR, fixed: 7/12/38 NT-48943 w/2000 mmf p/m 5%; temp coef 1tr B.	RE48A237 16C40		16-C-31800-9342	N16-0-10290			CD	P6-227-52	CG	P-7762812-1rev3	TBC-2 TBC-5(4)
-48944	CAPACITOR, fixed: 7/12/38 mica; 5000/5000 mmf; 2000 vdcw, 12 amp at 3000 kc, 7 amp at 1,000 kc, 4.5 amp at 300 kc, 1.5 amp at 100 kc; case 2 3/4" lg x 2 13/16" wd x 1 1/2" h; cast metal case; two tab term 7/8" lg x 5/8" wd on one end ea w/one 5/8" x 11/32" slot spaced 1" c to c; one mtg fl on bottom w/three 1/4" diam holes spaced 1" c to c; two #6-32 tapped holes on ea side of case on 1 1/16" mtg/c.	RE48A237 16C40										
-48944-B5	CAPACITOR, fixed: 7/12/38 NT-48944 w/5000/5000 mmf p/m 5%; temp coef 1tr B.	RE48A267 16C40		16-C-39429-1751				CD CD	PL-367-34 4471	CG	M-7464499-1	TBC-2 TBC-5
-48945	CAPACITOR, fixed: 7/12/38 mica; 10000/10000/10000 mmf; 2,000 vdcw, 30 amp per tap 4 to 26 mc, 30 amp at 3,000 kc, 27 amp at 1,000 kc, 24 amp at 300 kc, 20 amp at 100 kc; case 7" lg x 4 1/2" wd x 4 3/4" h; metal case; three tab term 1 3/4" lg ea w/one 13/32" diam hole 2" c to c; eight 1/4"-20 tapped holes 1/4" d, four in front, four in back on 6 3/8" x 3 1/4" mtg/c.	RE48A258 16C40										
-48945-B5	CAPACITOR, fixed: 7/12/38 NT-48945 w/10000/10000/10000 mmf p/m 5%; temp coef 1tr B.	RE48A258 16C40		16-C-39439-4116				CD	PL-977-132	CG	4691	TBC-2
-48946	CAPACITOR, fixed: 7/15/38 paper dielectric; 500,000 mmf plus 10 minus 3%, 500 vdcw; BS metal can; case 1 5/16" lg x 1 1/16" wd x 1 9/16" h; pyranol oil impr and filled; two solder lug term on top 5/8" c to c; no int gnd connections; one mtg bkt at bottom on each side ea w/one 5/32" slot, 1 15/16" c to c. NOTE: SP-1M (2); SX (2); TBC-5; ME-26 Mod 3; MX-26 Mod 4.	RE48A160 RE13A488		16-C-47274-9660	N16-11349-1			CG	9CE6A3	CGV CG CG	TK-7875547-3 P-7763475-3rev0 K-3977197rev7	TBC-2 QCJ-2 QCL SK-2 (2) SK-3 (2) SM-1 (15) SP (2) SEE NOTE
-48947	CAPACITOR, fixed: 7/18/38 paper dielectric; 4 mf plus 10 minus 3%; 2500 vdcw; BS metal can; case 3 7/8" lg x 4 5/8" wd x 4" h o/a; oil impr and filled; two ceramic ins screw type term 1 3/16" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 9/32" diam mtg holes 3 3/8" apart 4 1/2" c to c.	RE48A159 RE13A488		16-C-049944-3216	N16-C-11578			CD CD	25F56 23F41	CG CG	K-5222640rev3 K-7873047-5	TBC-2 TBC-5 (5) TAQ-5 (3) TAQ-6 (3)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-329

RESTRICTED

RESTRICTED

SHEET 48 - 330

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48948	CAPACITOR, variable: 7/27/38 air; plate meshing type single sect; 2.8 to 17.5 mmf, 15 mmf nom; SLC; 0.015" air gap; 11/16" lg x 1 5/16" wd x 1 9/32" h shaft 1/4" diam x 1/2" lg bushing 9/32" lg x 5/16"-32 thd; round shaft; five cad pl brass plates; 360 deg rotation; isolentite insulation; post term for stator, lug term for rotor on LE side; single hole mtg by 5/16" diam bushing or base mtg by means of bkt 1/2" wd w/one #6-32 tapped hole ctr.			16-C-58626-8211	N16-C-12219-100				CBC	HF-15		
-48949	CAPACITOR, fixed: 7/27/38 electrolytic; 20 mf; 150 vdcw; working temp range minus 20°C to plus 65°C; case 1 13/16" lg x 11/16" diam; ES metal case w/cardboard sleeve, two axial wire leads 3 1/4" lg; case is neg term.	RE48A340 RE13A549		16-C-19713-8736	N16-C-9675-20	R16-C-9678	3UR2-42	CD CAW	HR-2015 PHS	CWI CDE	24169 20006-7	IS YB-2 (4)
-48950	CAPACITOR, fixed: 7/28/38 electrolytic; 500 mf; 2 vdcw; working temp range minus 20°C to plus 65°C; case 3 1/2" lg x 1 3/8" diam; tubr metal case; two ins wire leads 6" lg; both term ins from can; thd mtg neck 1/2" lg x 3/4" diam w/palnut, 3/4"-16 thd screw base; for replacement use NT-48950-A.	RE48A337 RE13A549		16-C-20651-9601		R16-C-9725		CD	MA-12218PE			
-48950-A	CAPACITOR, fixed: 4/2/41 electrolytic; 500 mf; 10 vdcw; working temp range minus 20°C to plus 65°C; case 3 1/2" lg x 1 3/8" diam; tubr metal case; two ins wire leads 6" lg; both term ins from can; thd mtg neck 1/2" lg x 3/4" diam 3/4"-16 thd w/palnut.	RE13A549 RE48A337		16-C-20653-7611				CD	MA-12218-1			
-48951	CAPACITOR, fixed: 8/5/38 mica; 185 mmf; 5000 vdcw, 3 amp at 3,000 kc, 1.5 amp at 1,000 kc, 0.5 amp at 300 kc, 0.15 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48951-C5	CAPACITOR, fixed: 8/5/38 NT-48951 w/185 mmf p/m 5%; temp coef 1tr C. NOTE: TCN; TCN-1; TCU; TCU-1.	RE48A131 16C40		16-C-29188-1928				CD	PL-556-6LS	CG	P-7761566-15 rev13	TBR TBR-1 SEE NOTE

SHEET 48-330

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 331

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48952	CAPACITOR, fixed: electrolytic; 650 mf; 80 vdcw; working temp range minus 20°C to plus 65°C; case 6" lg x 3" wd x 6 1/4" h; metal case; two screw type term on top on stand off ins, term 1" h spaced 3" c to c; both term ins from can; two mtg fl on bottom, two 0.144" diam holes in ea, on 2" x 6 1/2" mtg/c. NOTE: QCN-4 (2); QCN-2; QCN-3 (2); QCO-1; QCO-2 (2);	8/10/38 RE48A139 REL3A488		16-0-20736-2601	N16-C-9714			CD CD	22850-2 SCP-2	CEM CEM	744-38a160 744-109	NM-11 (2) NM-12 (2) QCJ-5 (2) QCJ-6 (2) QCL-4 (2) QCL-5 (2) QCM-1 thru SEE NOTE
-48953	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 1000 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 2 1/8" h; oil impr and filled; two pillar ins screw type term 7/8" h located on top 13/16" c to c; no int gnd connections; two mtg fl on side of case, ea w/3/16" diam mtg hole 2 1/4" c to c. NOTE: thru QCL-5 (3); QCN-1 (3) thru QCN-3 (3); QCO (3); QCO-1 (3); QCO-2 (3); QCO-3 (3); QCO-1 (3); QCO-2 (3); QCO-3 (3); QCO-1 (3); QCO-2 (3); QCO-3 (3); QCR-1 (3); QCR-2 (3); QCR-3 (3); QCS (3); QCS-1 (3); QCS-2 (3); QCR (3);	8/10/38 RE48A146 REL3A488		16-0-48799-7102				CD CD	TJ-100-10 TJ-15060	CEM CEM	744-114 744-178	QCJ (3) QCJ-3 (3) QCJ-4 (3) QCJ-5 (3) QCJ-6 (3) QCK (3) QCL-1 (3) SEE NOTE
-48953-10	CAPACITOR, fixed: NE-48953 w/ 1 mfd p/m 10%.	8/10/38 RE48A146 REL3A488		16-0-48820-7102	N16-C-11425		3DB1.1009.1	CD	TS-10010	CEM	744-114	WDA WDA-1
-48954	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 2000 vdcw; HS metal can; case 2 1/2" lg x 1 3/16" wd x 3 7/16" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/4" h located on top 1 1/8" c to c; no int gnd connections; two mtg fl 1" wd on sides of case, ea w/a 3/16" diam mtg hole 3" c to c. NOTE: QCL-4; QCL-5; QCL-8; QCN-3; QCN-4; QCO-2; QCO-3; QCO-1; QCO-2; QCO-3; QCO-1; QCO-2; QCO-3; QCR-1; QCR-2; QCR-3; QCS; QCS-1; QCS-2; QCS-3; QCS-1; QCS-2; QCS-3; QCS-1; QCS-2; QCS-3; QCT; QCT-1; WAB; WCA; WCA-1.	8/10/38 RE48A146 REL3A488		16-0-48803-3968	N16-C-11434			CD	TJ-20010	CEM	744-113rev0	QCJ QCJ-5 QCJ-6 QCJ-9 QCK QCL-1 QCL-2 SEE NOTE
-48955	CAPACITOR, variable: air; plate meshing type dual sect; 9 to 180 mmf ea sect; SLC ea sect; 0.0245" air gap; 3 13/16" lg x 1 5/8" wd x 2 11/64" h; round shaft; twenty five plates; clockwise rotation; steatite ins; single hole panel mtg by 3/8"-32 thd bushing; superseded by NT-48955-A.	6/13/41		16-0-62863-7526				CBC	MCD-180-S			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-331

RESTRICTED

RESTRICTED

SHEET 48-332

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48955-A	CAPACITOR, variable: 8/29/38 air; plate meshing type dual sect; 9 to 180 mmf ea sect; SLC ea sect; 0.0245" air gap; 3 11/32" lg x 1 1/2" wd x 1 7/8" h shaft 1/4" diam x 7/16" lg bushing 3/8" lg x 3/8"-32 thd set screw in brg for locking; round shaft adj; cad pl brass plates; clockwise rotation; isolantite ins; solder lug term; single hole panel mtg by 3/8" diam mtg bushing.			16-C-62862-8340				CBC	MCD-180-S	CRR	A-12963188A	
-48956	CAPACITOR, fixed: 9/19/38 mica; 400 mmf; 600 vdcw, 1000 vdc; case 1 1/4" lg x 1 1/8" wd x 23/64" d; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-48956-A2	CAPACITOR, fixed: 9/19/38 NT-48956 w/400 mmf p/m 2%; temp coef ltr A.	RE48A221 16C40		16-C-29919-6791				CD CD	4-13040 4-6T4	CRR CRR	A-13753-6 A-1728-45	LD-4
-48957	CAPACITOR, fixed: 6/13/41 mica; 600 mmf; 2500 max vdcw, 3.4 amp at 3,000 kc, 1.5 amp at 1,000 kc, 0.46 amp at 300 kc, 0.15 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low-loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48957-001N2	CAPACITOR, fixed: 6/13/41 NT-48957 w/600 mmf p/m 2%; temp coef ltr 001N. NOTE: TBA-8; TBA-10 thru TBA-13; TBO-5; TBA-2.	RE48A131 16C40		16-C-30316-5013				CD	PL-997-6K	CG	P-7762161-3rev3	TBC-2 TBA-6 SEE NOTE
-48958	CAPACITOR, fixed: 6/13/41 mica; 700 mmf; 2500 vdcw max, 4.0 amp at 3,000 kc, 1.7 amp at 1,000 kc, 0.55 amp at 300 kc, 0.18 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low-loss bakelite case; two stud term on top 9/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48958-001N2	CAPACITOR, fixed: 6/13/41 NT-48958 w/700 mmf p/m 2%; temp coef ltr 001N. NOTE: TBA-10 thru TBA-13.	RE48A131 16C40		16-C-30580-3010				CD	PL-996-6K	CG	P-7762161-2rev3	TBC-2 TBA-8 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-332

RESTRICTED

RESTRICTED

SHEET 48 - 333

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48959	CAPACITOR, fixed: 6/13/41 mica; 1,000 mmf; 2500 vdcw effective, 5.5 amp at 3,000 kc, 2.6 amp at 1,000 kc, 0.8 amp at 300 kc, 0.26 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low-loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48959-001N2	CAPACITOR, fixed: 6/13/41 NT-48959 w/1,000 mmf p/m 2%; temp coef ltr 001N. NOTE: TBA-8; TBA-10; TBA-11; TBA-12; TBA-13; TBC-5.	RE48A131 16C40		16-C-31091-4900				CD	PL-995-6K	CC	P-7762161-1rev3	TBC-2 TBA-6 SEE NOTE
-48960	CAPACITOR, fixed: 9/27/38 mica; 3,000 mmf; 7,000 vdcw, 20 amp at 3,000 kc, 15 amp at 1,000 kc, 11 amp at 300 kc, 6 amp at 100 kc; 3" h x 4" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48960-B5	CAPACITOR, fixed: 9/27/38 NT-48960 w/3,000 mmf p/m 5%; temp coef ltr B. NOTE: TBA-10 (2); TBA-11 (2); TBA-12 (2); TBA-13 (2); TBC-5 (2); YB-2 (6); YR (7).	RE48A122 16C40		16-C-32195-5354	N16-C-10335			CD CAW	PL-201-508 1960-417	CG UDE CDE	P-7762163-1 2383-1 8-23611	TBC-2 TBA-6 (2) TBA-8 (2) SEE NOTE
-48961	CAPACITOR, fixed: 9/27/38 mica; 2500 mmf; 6000 vdcw, 13 amp at 3000 kc, 11 amp at 1000 kc, 8 amp at 300 kc, 2.5 amp at 100 kc; 2 1/2" h x 2 13/16" diam; ceramic case; one elliptical cast-aluminum end cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c in ea term.	RE48A132 16C40										
-48961-B5	CAPACITOR, fixed: 9/27/38 NT-48961 w/2,500 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-32010-7121				CD	PL-546-59	CG	P-7763250-15rev1	TBC-2
-48962	CAPACITOR, fixed: 9/28/38 paper dielectric; 2 sect; 100,000 mmf plus 10 minus 3% ea sect; 600 vdcw ea sect; HS metal can; case 2 1/16" lg x 1 13/16" wd x 13/16" h; dykenol impr and filled; three solder lug term 3/8" h on side, spaced 1/2" c to c; no int gnd connections; three mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 3/8" c to c.	RE13A488 RE48A129		16-C-53115-6362	N16-C-11332-51			CD	DY-6011			TBC-5 GO-3

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-333

RESTRICTED

RESTRICTED

SHEET 48 - 334

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFOR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48963	CAPACITOR, fixed: 11/15/39 mica; 30 mmf; 2,000 vdcw, 1.0 amp at 3,000 kc, 0.4 amp at 1000 kc, 0.1 amp at 300 kc, 0.04 amp at 100 kc; 2 1/16" lg x 61/64" wd x 1 17/32" h; molded bakelite case; two screw term 7/16" lg 1 1/2" c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-48963-B10	CAPACITOR, fixed: 11/15/38 NT-48963 w/30 mmf p/m 10%; temp coef ltr B. NOTE: TBK-12; TBK-14; TBK-17; TBK-19; TBL-4; TBL-8; TBL-9.	RE48A222 16C40		16-C-27134-7707	N16-C-9835-1			CRV	UC-2944, case #352	CRV	K-860215-1rev0	TBK-8 TBK-10 SEE NOTE
-48964	CAPACITOR, fixed: 11/15/38 mica; 60 mmf; 3,000 vdcw, 1.0 amp at 3,000 kc, 0.5 amp at 1,000 kc, 0.15 amp at 300 kc, 0.1 amp at 100 kc; 2 1/16" lg x 61/64" wd x 1 17/32" h; molded bakelite case; two screw term 7/16" lg 1 1/2" c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-48964-B5	CAPACITOR, fixed: 11/15/38 NT 48964 w/60 mmf p/m 5%; temp coef ltr B. NOTE: TBK-12; TBK-14; TBK-17; TBK-19; TBL-4; TBL-8; TBL-9.	RE48A222 16C40		16-C-27789-5027	N16-C-9852			CRV	UC-3150, case #352	CRV	K-860215-2rev0	TBK-8 TBK-10 SEE NOTE
-48965	CAPACITOR, fixed: 11/15/38 mica; 30 mmf; 5,000 vdcw, 2.0 amp at 3,000 kc, 0.75 amp at 1,000 kc, 0.25 amp at 300 kc, 0.1 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48965-B5	CAPACITOR, fixed: 11/15/38 NT-48965 w/30 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-27130-6723	N16-C-9837			CRV	UC-3180, case #351	CRV	K-860215-25rev6	TBK-8

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-334

RESTRICTED

RESTRICTED

SHEET 48 - 335

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48966	CAPACITOR, fixed: 6/13/41 mica; 320 mmf; 5,000 vdcv, 3.5 amp at 3,000 kc, 2.5 amp at 1,000 kc, 1.5 amp at 300 kc, 0.75 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48966-B2	CAPACITOR, fixed: 6/13/41 NT-48966 w/320 mmf p/m 2%; temp coef ltr B. NOTE: TBK-12; TBK-14; TBK-17; TBK-19; TBL-4 (2); TBL-8 (2); TBL-9 (2).	RE48A131 16C40		16-C-29704-9461	N16-C-9997-1			CRV	UC-3298case#351	CRV	K-860215-3rev6	TBK-8 TBK-10 SEE NOTE:
-48967	CAPACITOR, fixed: 11/15/38 mica; 800 mmf; 5,000 vdcv, 6 amp at 3,000 kc, 4 amp at 1,000 kc, 2.5 amp at 300 kc, 1 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam holes 2 5/8" c to c.	RE48A131 16C40										
-48967-B5	CAPACITOR, fixed: 11/15/38 NT-48967 w/800 mmf p/m 2%; temp coef ltr B. NOTE: TBK-12 (2); TBK-14 (2); TBK-17 (2); TBK-19 (2); TBL-4 (3); TBL-8 (3); TBL-9 (3).	RE48A131 16C40		16-C-30691-6723	N16-C-10074-11			CRV	UC-3079,case#351	CRV	K-860215-9rev6	TBK-8(2) TBK-10(2) SEE NOTE:
-48968	CAPACITOR, fixed: 11/15/38 mica; 900 mmf; 5,000 vdcv, 6 amp at 3,000 kc, 4 amp at 1,000 kc, 2.5 amp at 300 kc, 1.0 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48968-B5	CAPACITOR, fixed: 11/15/38 NT-48968 w/900 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-30902-6923				CRV	UC-3312case#351	CRV	K-860215-10rev6	TBK-8
-48968-C2	CAPACITOR, fixed: 11/15/38 NT-48968 w/900 mmf p/m 2%; temp coef ltr C.	RE48A131 16C40		16-C-30897-5448	N16-C-10080-100							
-48969	CAPACITOR, fixed: 11/16/38 paper dielectric; 4 mf plus 10 minus 3%; 1,500 vdcv; HS metal can; case 3 7/8" lg x 1 5/16" wd x 4 3/4" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 2" c to c; no int and connections; two mtg fl on bottom of case ea with two 0.213" diam mtg holes on 13/32" x 4 3/8" mtg/c.	RE48A159 RE13A488		16-C-49941-9119				CG	23F23	CRV	K-860217-brev0	TBK-8

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-335

RESTRICTED

RESTRICTED

SHEET 48 - 336

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48970	CAPACITOR, fixed: 11/16/38 paper dielectric; 4 mf plus 10 minus 3%; 3,000 vdcw; HS can; case 3 7/8" lg x 4 5/8" wd x 5" h o/a; oil impr and filled; two ceramic ins screw type term 1 15/16" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/ two 9/32" mtg holes on 3 3/8" x 4 1/2" mtg/c; for replacement only.	RE48A159 RE13A488		16-C-49944-6616	N16-C-11582-1			CG CG	23F44 25F7102	CG CYV	K-660217-7 rev5 14-13A	TBK-8 TEC(2)
-48971	CAPACITOR, fixed: 11/23/38 paper dielectric; 1 mf plus 10 minus 3%; 600 vdcw and 120 vacw; HS metal can; case 1 7/8" lg x 1" wd x 2 3/16" h o/a; oil impr and filled; two screw type term 13/32" h located on top 13/16" c to c; no int gnd connections; two mtg fl 7/8" wd on side of case, ea w/two 0.213" diam mtg holes on 13/32" x 2 3/8" mtg/c.	RE48A158 RE13A488		16-C-48796-3371		R16-C-11419		CG	25F83	CG	K-6808050rev1	GO-4
-48972	CAPACITOR, fixed: 11/23/38 paper dielectric; 2 mf plus 10 minus 3%; 600 vdcw and 120 vacw; HS metal can; case 1 7/8" lg x 1" wd x 2 5/16" h, o/a; oil impr and filled; two screw type term 13/32" h located on top 13/16" c to c; no int gnd connections; two mtg fl on side of case, ea with two 0.213" diam mtg holes 13/32", 2 3/8" c to c.	RE48A158 RE13A488		16-C-49176-3366				CG CG	25F82 25F89	CG	K-6808050rev1	GO-4
-48973	CAPACITOR, fixed: 11/23/38 paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw and 120 vacw; HS metal can; case 2 5/8" lg x 1 3/16" wd x 3 7/16" h o/a; oil impr and filled; two screw type term 13/32" h located on top 1 1/8" c to c; no int gnd connections; two mtg fl 7/8" wd on side of case, ea w/two 0.213" diam mtg holes on 13/32" x 3 1/8" mtg/c.	RE48A158 RE13A488		16-C-49236-6450				CG	25F81	CG	K-6808050rev1	GO-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-336

RESTRICTED

RESTRICTED

SHEET 48 - 337

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGH	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48974	CAPACITOR, fixed: 11/23/38 paper dielectric; 5 mf plus 10 minus 3%; 600 vdcw and 120 vacw; HS metal can; case 2 5/8" lg x 1 3/16" wd x 4 1/16" h, o/a; oil impr and filled; two screw type term 13/32" h located on top 1 1/8" c to c; no int gnd connections; two mtg fl on side of case, ea w/two 0.213" diam mtg holes on 13/32" x 3 1/8" mtg/c.	RE48A158 RE13A488		16-C-50316-6450				CG	25F80	CG	K-6808050rev1	GO-4
-48975	CAPACITOR, fixed: 11/23/38 paper dielectric; 8 mf plus 10 minus 3%; 600 vdcw and 120 vacw; HS metal can; case 3 7/8" lg x 1 1/4" wd x 4 1/16" h o/a; oil impr and filled; two fork type solder term 13/32" h located on top 2" c to c; no int gnd connections; two mtg fl 7/8" wd on side of case, ea w/two 0.213" diam mtg holes on 13/32" apart centered 4 3/8" c to c.	RE48A158 RE13A488		16-C-51457-2590	N16-C-11625-100			CG CG	25F79 26F221	CG CG	K-6808050rev1 M-7463126-9	GO-4 MK-33 (2)
-48976	CAPACITOR, fixed: 11/23/38 paper dielectric; 500,000 mf plus 10 minus 3%; 1500 vdcw; HS metal can; case 1 7/8" lg x 1" wd x 2 3/16" h o/a; oil impr and filled; two screw type term 13/32" h located on top 13/16" c to c; no int gnd connections; two mtg fl 7/8" wd on side of case, ea w/two 0.213" diam mtg holes on 13/32" x 2 1/8" mtg/c.	RE48A158 RE13A488		16-C-47281-6431		R16-C-11364		CG	25F78	CG	K-6808050rev1	GO-4
-48977	CAPACITOR, fixed: 11/23/38 paper dielectric; 2 mf plus 10 minus 3%; 1500 vdcw; HS metal can; case 2 5/8" lg x 1 3/16" wd x 4 5/16" h o/a; oil impr and filled; two screw type term 13/32" h located on top 1 1/8" c to c; no int gnd connections; two mtg fl on bottom case, ea w/two 0.213" diam mtg holes on 13/32" x 3 1/8" mtg/c.	RE48A158 RE13A488		16-C-49181-7439				CG	25F77	CG CRV	K-6808050rev1 K-860217-12	GO-4 WEA
-48978	CAPACITOR, fixed: 12/1/38 paper dielectric; 1 mf plus 10 minus 3%; 1500 vdcw; HS metal can; case 1 7/8" lg x 1" wd x 4" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 0.213" diam mtg holes on 13/32" x 3 1/8" mtg/c.	RE48A159 RE13A488		16-C-48801-6436	N16-C-11431-12			CG	25F68	CRV CG	K-860217-3rev0 P-5271179rev0	TBL-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-337

RESTRICTED

RESTRICTED

SHEET 48 - 338

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48979	CAPACITOR, fixed: 12/1/38 paper dielectric; 4 mf plus 10 minus 3%; 2000 vdcw; BS metal can; case 3 7/8" lg x 2 5/16" wd x 4" h #/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 9/32" diam mtg holes 1 1/4" apart 4 1/2" c to c.	RE48A159 RE13A488		16-C-49943-6121	N16-C-11574			CG CG	25F70 25F33	CRV CRV CG	W-303083-152 K-860217-5rev0 M-7464792-1	TBL-4 NMB-1 QBE QJ-2 QJ-8 QCL QCL-7
-48980	CAPACITOR, fixed: 12/1/38 mica; 600 mmf; 1200 vdcw, 2500v DC test; case 1 25/32" lg max x 1 11/32" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg. NOTE: QJ-2; QJ; QX; QY; QZ; Q8; TCJ; TCJ-1; TCK; TCK-1 thru TCK-7; WEA-1.	RE48A112 JAN-C-5										SEE NOTE
-48980-B1	CAPACITOR, fixed: 12/1/38 NT-48980 w/6,000 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B602K	16-C-32858-4042	N16-C-10449-28					CRV F		K-35482-47rev6 TBL-4 TBL-5 TBL-9
-48981	CAPACITOR, fixed: 12/5/38 mica; 600 mmf; 1,200 vdcw, 2,500v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; moulded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-48981-A10	CAPACITOR, fixed: 12/5/38 NT-48981 w/600 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-30326-1637						CD	9-22060	GO-4
-48981-B2	CAPACITOR, fixed: 12/5/38 NT-48981 w/600 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-30315-8682						CD	9L-22050	CG P-7761560-21 rev0
-48982	CAPACITOR, fixed: 12/5/38 mica; 200 mmf; 2500 vdcw, 5000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-48982-A5	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 5%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A201J	16-C-29266-5582		R16-C-9968-585				CD	9-53020	
-48982-A10	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 10%; temp coef ltr A.	RE48A112 JAN-C-5	CM55A201K	16-C-29271-6062						CD	9-53020	GO-4
-48982-B2	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 2%; temp coef ltr B. NOTE: TCK thru TCK-7; YE(2); YE-1; YE-2.	RE48A112 JAN-C-5	CM55B201G	16-C-29261-4107	N16-C-9969-1 N16-C-9970-1					CD CRV	9-53020 Model F	CG CRV P-7762664-18 K-35484-36 TCJ TCJ-1 SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-338

RESTRICTED

RESTRICTED

SHEET 48 - 339

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48982-B5	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 5%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B201J	16-C-29266-5587		R16-C-9968-630		CD	9-53020			
-48982-B10	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 10%; temp coef ltr B.	RE48A112 JAN-C-5	CM55B201K	16-C-29271-6067	N16-C-9970			CD	9L-53020	CG	P-7761560-23rev9	TAQ-5 TAQ-6 TAQ-10
-48982-C2	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 2%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C201G	16-C-29261-4112		R16-C-9968-230		CD	9L-53020			
-48982-C5	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 5%; temp coef ltr C.	RE48A112 JAN-C-5	CM55C201J	16-C-29266-5592		R16-C-9968-680		CD	9L-53020			
-48982-D2	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 2%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D201G	16-C-29261-4117		R16-C-9968-330		CD	9H-53020			
-48982-D5	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 5%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D201J	16-C-29266-5597		R16-C-9968-780		CD	9H-53020			
-48982-D10	CAPACITOR, fixed: 12/5/38 NT-48982 w/200 mmf p/m 10%; temp coef ltr D.	RE48A112 JAN-C-5	CM55D201K	16-C-29271-6077		R16-C-9969-10		CD	9H-53020			
-48983	CAPACITOR, FIXED: 12/5/38 mica; 1000 mmf; 500 vdcv, 1000v, DC test; case 53/64" lg x 53/64" wd x .9/32" d max dimen; molded low loss bakelite case; 2 axial wire leads.	RE48A143										
-48983-A2	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 2%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A102G	16-C-31080-2199				CAN CMR CSL CD CMF CAW	C-1210-2 W MM-1227-2 1W 502J 1467	CRP	35-5034	GO-4 SG(3) SG-1(3) SG-28(3)
-48983-A3	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 3%; temp coef ltr A.	RE48A143 16C40		16-C-31084-5023				CAW CD CSL CMR CMF	1467 1W MM W 502J	CNA		RAS thru RAS-4 RAS-5(2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-339

RESTRICTED

RESTRICTED

SHEET 48 - 340

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48983-A5	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A102J	16-C-31085-3679	N16-C-10083-100		3DA1-22	CSL CAW CD CMR CMP CAN	MW 1467 1W W 502J C-1210-5	CNA	D775-55	RTG
-48983-A10	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 10%; temp coef ltr A. NOTE: RBL-2(4); RBJ-1 (3); RBJ-4(3); SG-1(4); SG-2(4); SJ-1(2); SL; SM-1(4); SO -1(3); WFA(4); MK-8; MK-8 Mod1.	RE48A143 JAN-C-5	CM30A102K	16-C-31090-4159			3K3010211	CMR CSL CD CMP CAW CAN	W MW-1227-10 1W5D1 502J 1467 C-1210-10	CHEZ CBM CHEZ CGZ CN CRP CBM CNA CG	CO-634 744-569 00-936198A4 035 ES-682029-20 35-5036 744-721 D-775 K-27J362-528	ABK-1 (3) ABK-7(3) BM-1(8) BM-2(8) BO(8) LAG RAS-1(3) RAS-5(3) RAW(3) SEE NOTE
-48983-A20	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 20%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A102M	16-C-31095-6639	N16-C-10083-150			CD CAW CSL CAN CMR CMP	1W 1467 MW C-1210-20 W 502J	CGI	813-2414	OAA-2
-48983-B2	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 2%; temp coef ltr B.	RE48A143 16C40		16-C-31080-2204	N16 C-10084-2		3K3010223	CD CAW CSL CSL CSL	1WL 1467L MWB MNSCW LS	CPT CAY	T-7610894-22	DAH-2(3) VE VE-1 Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-340

RESTRICTED

RESTRICTED

SHEET 48 - 341

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
48983-B5	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B102J	16-C-31085-3684	N16-C-10084-7 N16-C-10083-235	R16-C-10083-55		CD CAW CSL CMR	1WLS-12010 1467L MWB WXM	CHZ CFT CG	A102947-2188M CO-10761880 744-31 P-7762455-51rev0	DAH(3) QCJ-9(6) QCL-8(6) QCN-4(6) SEE NOTE
48983-B10	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B102K	16-C-31090-4164	N16-C-10084-8	R16-C-10084	3K3010221	CD CSL CAW CAN CMF	1WLS-12010 MWB-1227 1467LS C-1210 CM-30-102	COL CHZ CFW COL CG CFT CFY CRV CBM CWR CAY CBM	909 2103 52 CO-616 C-1207 909N210CNrev0 P-7761328-20rev9 P-720473-37rev19 270-165 P7762455-20 744-31 47X340 T-7610894-22 744-276	BL-1 thru BL-6 DAH-2(2) DAK-1(2) DAK-2(2) NGA NMB-1 QBG(3) QCJ-5(6) QCL-4(6) QCN-2 QCO-2(6) SEE NOTE
48983-B20	CAPACITOR, fixed: 12/5/38 NT-48983 w/1000 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B102M	16-C-31095-6644	N16-C-10084-16	R16-C-10084-75		CD CAW	1WL-5D1 1467	CHZ CBM CRV CHZ CRV	3095-9 744-608 P-722017-939 CO-668 L-61009-16	DAJ(2) DSX OBL TBS thru TBS-8 SEE NOTE
48983-C2	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 2%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C102G	16-C-31080-2209	N16-C-10083-200	R16-C-10079-800		CD CD CAW CAW CSL	1WL 1R 1467L 1464 MNSCW	CBM	744-224	DAH-2(3) QFB QFB-1 Cont.

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-341

RESTRICTED

RESTRICTED

SHEET 48 - 342

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
48983-C5	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 5%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C102J	16-C-31085-3689		R16-C-10083-35	3K3010232	CD CD CAW CAW CSL	1WL 1R 1467L 1464 MTCB	CG	K-27J362-148rev0	SK-1M SK-2 SK-3
48983-C10	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 10%; temp coef ltr C. NOTE: SU-1(3); VD: VD-1.	RE48A143 JAN-C-5	CM30C102K	16-C-31090-4169	N16-C-10054-75	R16-C-10084-1	3K3010231	CD CD CAW CAW CSL CAN	1WLST 1R 1467LST 1464 MWCW-1227-10 C-1210-10	CRP CBM	35-5036 744-569	SO SO-2(3) SO-8(3) SO-9 SO-12M (4) SO-12N(4) SEE NOTE
48983-C20	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 20%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C102M	16-C-31095-6649		R16-C-10084-80		CD CAW CAW CSL CAN	1RS 1467LST 1464 MWCW-1227 CRW	CRP	35-5105	SO SO-a SO-7M SO-7R SO-8 SO-13
48983-D1	CAPACITOR, FIXED: 4/20/49 Navy Type 48983 w/1000 mmf p/m 1%; temp coef letter D.			16-C-31079-4286				CD	1R	CBM	744-821	MR-39 Mod3
48983-D2	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 2%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D102G	16-C-31080-2214	N16-C-10084-6	R16-C-10080-25		CD CAW CSL CAN	1RS 1464 MWSIW CRW			
48983-D5	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 5%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D102J	16-C-31085-3694	N16-C-10084-9	R16-C-10083-45	3K3010242	CD CMF CAW CSL	1RS 602J 1464 MWSIW	CBM	744-330	SU(2) MR-8 Mod2 MR-8 Mod3 MR-8 MR-8 Mod1 Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-342

RESTRICTED

RESTRICTED

SHEET 48 - 343

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48983-D10	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 10%; temp coef ltr D. NOTE: MK-8(3); MK-8 Mod1(3); MK-8 Mod2(3); MK-9; MK-10; MK-10 Mod1(3).	RE48A143 JAN-C-5	CM30D102K	16-C-31090-4174	R16-C-10084-31	R16-C-10084-2		CD CAW CSL	1RS 1464 MUSEW	CRV CW	W-303314-348	QCJ-8 QCL-7 WLA(3) SEE NOTE
-48983-D20	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 20%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D102M	16-C-31095-6654	R16-C-10084-33	R16-C-10084-44-200	3K3010244	CD CAW CSL	1RS 1464 MUSEW			
-48983-E1	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 1%; temp coef ltr E.	RE48A143 16C40		16-C-31079-4285				CD CAW CSL	1R 1464 MUSEW	COL CBM	912 2101 60rev1 744-821alt0	TCH TCH-1 TDR thru TDE-4
-48983-E2	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 2%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E102G	16-C-31080-2219		R16-C-10080-30		CD CAW CSL	1RS 1464 MUSEW			
-48983-E5	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 5%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E102J	16-C-31085-3699		R16-C-10083-70	3K3010252	CD CAW CSL CAN	1R 1464 MUSEW CRW	COL	912 2101 10rev1	
-48983-E10	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 10%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E102K	16-C-31090-4179		R16-C-10084-3		CD CAW CSL	1RS 1464 MUSEW			
-48983-E20	CAPACITOR, fixed: 12/5/38 NT-48983 w/1,000 mmf p/m 20%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E102M	16-C-31095-6659		R16-C-10084-44-500		CD	1RS	COL	912 2101 54rev1	TCZ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-343

RESTRICTED

RESTRICTED

SHEET 48 - 344

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48984	CAPACITOR, fixed: 12/5/38 mica; 8,000/1,600 mmf; 1,000 vdcw max, 0.2/1.5 amp at 3,000 kc, 0.8/1.1 amp at 1,000 kc, 0.3/0.5 amp at 300 kc, 0.13/0.2 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; three screw term 13/32" h on top spaced 13/16" c to c; two mtg fl on sides of bottom, ea w/ one 0.180" diam hole, on 2.625" mtg/c.	RE48A236 16C40										
-48984-D2	CAPACITOR, fixed: 12/5/38 NT-48984 w/8,000/1,600 mmf p/m 2%; temp coef ltr D.	RE48A236 16C40		16-C-39430-4666				CD	PL-1006-GEL	CG	M-746293-3rev3	GO-4 TCJ TCJ-1
-48985	CAPACITOR, fixed: 12/13/38 mica; 330 mmf; 400 vdcw; case 1 13/32" lg x 1/2" wd x 3/8" thk; thermo plastic case; two axial wire leads.	RE48A248 16C40										
-48985-B20	CAPACITOR, fixed: 12/13/38 NT-48985 w/330 mmf p/m 20%; temp coef ltr B.	RE48A248 16C40		16-C-29723-9392				CRV	Model R	CRV	Z-86013-503rev0	
-48986	CAPACITOR, fixed: 12/5/38 paper dielectric; 100,000 mmf plus 10 mlcus 3%; 300 vdcw; HS metal can; case 1 1/8" lg x 15/32" wd x 1 5/32" h o/m; pyranol filled; two wire lead term 4 5/16" h located on top spaced 9/16" c to c; no int gnd connections.	RE48A205 RE13A488		16-C-45751-6998								GO-4
-48986-10	CAPACITOR, fixed: 12/5/38 NT-48986 w/100,000 mmf p/m 10%.	RE48A205 RE13A488		16-C-45772-6998				CG	25F96	CG	Z-526024rev2	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-344

RESTRICTED

RESTRICTED

SHEET 48 - 345

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48987	CAPACITOR, fixed: 12/5/38 mica; 400 mmf; 3,000 vdcw, 4.0 amps at 3,000 kc, 2.0 amps at 1,000 kc, 0.9 amps at 300 kc, 0.45 amps at 100 kc; case 2" lg x 1 5/16" wd x 1 1/2" h; molded bakelite case; two screw term 7/16" lg c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE45A222 16C40										
-48987-A5	CAPACITOR, fixed: 12/5/38 NT-48987 w/400 mmf p/m 5%; temp coef ltr A.	RE48A222 16C40		16-C-29926-1420				CD	PL-641-15			GP-4
-48987-B5	CAPACITOR, fixed: 12/5/38 NT-48987 w/400 mmf p/m 5%; temp coef ltr B.	RE48A222 16C40		16-C-29926-1421				CD	PL-641-15L			
-48988	CAPACITOR, fixed: 12/6/38 mica; 1,800 mmf; 5,000 vdcw, 7.0 amp at 3000 kc, 5.0 amp at 1000 kc, 3.0 amp at 300 kc, 1.5 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48988-B5	CAPACITOR, fixed: 12/6/38 NT-48988 w/1,800 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-31667-6523				CRV	UC-3224 case #351	CRV	X-860215-16rev6	
-48989	CAPACITOR, fixed: 12/6/38 mica; 3,500 mmf; 3,000 vdcw, 15 amp at 3000 kc, 10 amp at 1000 kc, 5.5 amp at 300 kc, 2.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-48989-B5	CAPACITOR, fixed: 12/6/38 NT-48989 w/3,500 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-32326-4885	N16-C-10344			CRV	UC-3187 case #371	CRV	X-860215-19rev6	TBL-4 (2) TBL-5 (2) TBL-9 (2)
-48990	CAPACITOR, fixed: 12/14/38 electrolytic; 10 mf; 25 vdcw; working temp range minus 20°C to plus 65°C; case 1 9/16" lg x 5/8" diam; HS metal case w/ cardboard sleeve; two axial wire leads 3" lg; case is neg term.	RE48A340 RE13A549		16-C-19556-4921	N16-C-9667-46	R16-C-9668		CD	BR	CAY		GP-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-345

RESTRICTED

RESTRICTED

SHEET 48 - 346

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48991	CAPACITOR, fixed: paper dielectric; 3.75 mf plus 10 minus 3%; 600 vdcw, 330 vacw at 60 cyc; HS metal can; case 3 1/4" h x 2 1/2" wd x 1 3/16" d o/a; pyranol filled; two solder lug term 1/2" h located on top; no int gnd connections.	1/16/39 RE48A110 RE13A488		16-C-49841-5936				CG CD	61X4 KG-3037	CG	H-3984562rev2	TBC-2
-48991-10	CAPACITOR, fixed: NT-48991 w/3.75 mf p/m 10%.	1/16/39 RE48A110 RE13A488		16-C-49862-5936				CD	KG-3037	CW	ES-682061-21ss1	MK-28 MK-28 Mod 2
-48991-15	CAPACITOR, FIXED: Navy Type 48991 w/3.75 mfd p/m 15%.	12/10/47 RE48A110 RE13A488		16-C-49377-3660				CG CD	67X4 KI-3037	CG CW	H-3984562 rev 2 ES-6820612	MK-28 Mod 2
-48992	CAPACITOR, fixed: paper dielectric; 12 mf plus 10 minus 3%; 600 vdcw, 330 vacw at 60 cyc; HS metal can; case 3 7/8" h x 3 3/4" wd x 1 3/4" d o/a; pyranol filled; two stud term 1/2" h located on top, spaced 2" c to c; no int gnd connections.	1/16/39 RE48A110 RE13A488		16-C-51899-8230	N16-C-1169P-3			CG CG	67X13 25F166	CG	H-3984562rev2	SC-2 SK TBC-2 TBC-5
-48993	CAPACITOR, FIXED: mica; 950 mmf; 2000 vdcw, 5 amp at 3 mc, 3.5 amp at 1 mc, 2 amp at 0.3 mc, 0.7 amp at 0.1 mc; potted molded bakelite case; case 2 5/16" lg x 1 17/32" wd x 1 27/32" h; 2 stud term #10-32 thd located on top spaced 1 5/8" c to c; 2 tab mtg holes 3/16" diam located on bottom 2 5/8" c to c; add suffix indicating capacity tolerance in per cent.	3/13/39 RE48A131 16C40										
-48993-D2	CAPACITOR, fixed: NT-48993 w/950 mmf p/m 2%; temp coef ltr D.	3/13/39 RE48A131 16C40		16-C-31023-8196	N16-C-10081-20			CD	PL-1018-6LBS	CG	P-7761566-25 rev13	TAQ-5 TAQ-6 TAQ-10(2)
-48993-D5	CAPACITOR, FIXED: Navy Type 48993 w/950 mmf p/m 5%; temp coef letter D.	2/24/50 RE48A131 16C40		16-C-31023-8969				CD	LS			
-48994	CAPACITOR, fixed: mica; 1,250 mmf; 2,000 vdcw, 6 amp at 3,000 kc, 4 amp at 1,000 kc, 2.8 amp at 300 kc, 1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	3/13/39 RE48A131 16C40										
-48994-D2	CAPACITOR, fixed: NT-48994 w/1250 mmf p/m 2%; temp coef ltr D.	3/13/39 RE48A131 16C40		16-C-31318-6416	N16-C-10175-80			CD	PL-1017-6LBS	CG	P-7761566-21 rev13	TAQ-5 TAQ-6 TAQ-10

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-346

RESTRICTED

RESTRICTED

SHEET 48 - 347

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A B O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48995	CAPACITOR, fixed: 3/15/39 mica; 22,500 mmf; 2,500 vdcw, 20 amp at 3,000 kc, 30 amp at 1,000 kc, 28 amp at 300 kc, 16 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term each end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48995-B5	CAPACITOR, fixed: 3/15/39 NT-48995 w/22,500 mmf p/m 3%; temp coef 1tr B.	RE48A122 16C40		16-C-34462-9588				CD	PL-985-508	CG	M-74626;4-4	TAQ-5
-48996	CAPACITOR, fixed: 3/15/39 mica; 45,000 mmf; 2,000 vdcw, 20 amp at 3,000 kc, 35 amp at 1,000 kc, 34 amp at 300 kc, 20 amp at 100 kc; case 3" h x 3 1/2" diam; ceramic case; one fl elliptical end term ea end w/two 17/64" diam holes in ea 4 1/4" c to c.	RE48A122 16C40										
-48996-B5	CAPACITOR, fixed: 3/15/39 NT-48996 w/45,000 mmf p/m 3%; temp coef 1tr B.	RE48A122 16C40		16-C-35148-6251	N16-C-10588			CD CAN	PL-984-508	CG	M-74626;4-6	TAQ-5(4) TAQ-6(4) TAQ-10(6)
-48997	CAPACITOR, fixed: 3/15/39 paper dielectric; 50,000 mmf plus 10 minus 3%; 2,500 vdcw; HS metal can; case 2 5/8" lg x 1 3/16" wd x 3 3/16" h, o/a; oil impr and filled; two ceramic ins screw type term 15/16" h, located on top 2" c to c; no int grd connections; two mtg fl on bottom of case ea w/two 0.213" diam mtg holes 13/32" apart 3 1/8" c to c.	RE48A159 RE13A488		16-C-44244-2032	N16-C-11174-13			CG	26F160	CG	K-5276597rev0	TAQ-5 TAQ-6
-48998	CAPACITOR, fixed: 3/15/39 paper dielectric; 100,000 mmf plus 10 minus 3%; 2,500 vdcw, 1,240 vacw at 800 cyc; HS metal can; case 3 7/8" lg x 1 1/4" wd x 4 5/16" h, o/a; oil impr and filled; two ceramic ins screw type term 15/16" h located on top 2" c to c; no int grd connections; two mtg fl on bottom of case ea w/two 0.213" diam mtg holes 13/32" apart 4 3/8" c to c.	RE48A159 RE13A488		16-C-45764-2772	N16-C-11326			CG	26F159	CG	K-5276597rev0	TAQ-5

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-347

RESTRICTED

RESTRICTED

SHEET 48 - 348

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48999	CAPACITOR, fixed: 3/15/39 paper dielectric; 2 mf plus 10 minus 3%; 2,500 vdcw; ES metal can; case 3 7/8" lg x 1 3/4" wd x 4 3/4" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/16" h, located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea with two 0.213" diam mtg holes 5/8" apart 4 3/8" c to c.	RE48A159 RE13A488		16-C-49184-2772	N16-C-11494-1			CG	25R85	CG	K-7873955-1rev0	TAR-5 (2) TAR-6 (2)
-481000	CAPACITOR, fixed: 4/7/39 paper dielectric; 5 mf plus 10 minus 3%; 25 vdcw, 50v DC test; ES metal can; case 1 3/4" lg x 1" wd x 2 3/4" h; oil impr and filled; two screw type term 1/2" h located on top 3/4" c to c; no int gnd connections; two mtg fl on bottom of case, ea with 3/16" diam mtg hole 2 1/4" c to c.	RE48A147 RE13A488		16-C-50307-1667	N16-C-11597			CD	DC-1208	CAY	P-7706891-Leub0	
-481000-10	CAPACITOR, fixed: 4/7/39 NT-481000 w/5 mf p/m 10%.	RE48A147 RE13A488		16-C-50328-1666		R16-C-11640		OAW CD	AX-1003 DC-1208	CAY CAY	T-7609856-21 T-7606591-21	TCE-1 TCE-2
-481001	CAPACITOR, fixed: 4/10/39 paper dielectric; 100,000 muf plus 10 minus 3%; 600 vdcw; ES metal can; case 1 13/16" lg x 1" wd x 3/4" h o/a; oil impr and filled; two solder lug term 5/16" h on top, spaced 1" c to c; no int gnd connections; two mtg fl 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c. NOTE: BL-5 (4); RN; BN-1 BN-2; LAF-3 (3); LP-1 thru LP-4; OAP; OAP-1; YH (3) YH-1 (3).	RE48A128		16-C-45756-3129			3DA100-121	CIE CD CSF	6TA10 DYT-6010 2527-12	CMD CAG CFN	4C10 1C12 300 447-11rev9	LP ARD-1 (4) ARD-2 BL-1 (7) BL-2 (7) BL-3 (4) BL-4 (3) SEE NOTE
-481001-5	CAPACITOR, fixed: 4/10/39 NT-481001 w/100,000 muf p/m 5%.	RE48A128 RE13A488		16-C-45735-3109	N16-C-11309-3			CD CIE CMD CSF CG	DYT-6010 6TA10 4C10 2527-12 26R465	CG	K-353613-1 rev 0	SQ Con't

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-348

RESTRICTED

RESTRICTED

SHEET 48 - 349

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481001-10	CAPACITOR, fixed: paper dielectric w/100,000 mmf p/m 10%. 4/10/39	RE48A128 JAN-C-25	CP54BLDF104MK	16-C-45777-3134	N16-C-11308-800	R16-C-11706-135	3DA100-108.2 3DA100-116.8 3DA100-291	CMD CD CSF CG CSL CTD	4C10 DYRT-6010 P-6830 25F468 XDMRTW6-.1-10 RLON-610	CFT CAY CGZ CAG CHE CRB CG CW CRR	F-37824-1 P-7706376-24 034 1012 CO-606 CD-1029-1 iss D K-35J639-1 ESA-682063-2 C59592-1 iss 0	BL-6 DAU (2) DAU-1 (2) LAE (3) LAE-1 (4) thru LAE-3 (4) LAF-1 (4) LAF-2 (4) SEE NOTE
-481001-20	CAPACITOR, fixed: NT-481001 w/100,000 mmf p/m 20%. 4/10/39	RE48A128 RE13A488		16-C-45807-7478	N16-C-11309-5		3DA100-116.9	CD		COL	956 2016 40	TDH-4 (2)
-481002	CAPACITOR, fixed: paper dielectric; 500,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1" wd x 7/8" h o/a; oil impr and filled; two solder lug term 5/16" h on top, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c. 4/10/39	RE48A128		16-C-47276-3119	N16-C-11351-2-1		3DA500-97.20 3DA500-263	CD CFS CIE	DYT-6050 P-6830 6BAT-50	CFN CAY	300 447-1 11-D-4701rev2	LP ARD-2 BN BN-2 LAF JP-1 thru LP-4 SEE NOTE
-481002-5	CAPACITOR, FIXED: Navy Type 481002 w/500,000 mmf p/m 5%. 4/27/48	RE13A488		16-C-47255-3134				CMX	25007705 rev F			RCU RCU-1
-481002-6	CAPACITOR, fixed: NT-481002 w/500,000 mmf p/m 5%. 4/10/39	RE48A128 RE13A488		16-C-47266-9910				CB		CG	M-29J407-6	SK-3
-481002-10	CAPACITOR, fixed: NT-481002 w/500,000 mmf p/m 10%. 4/10/39	RE48A128 JAN-C-25	CP51B1GF504K	16-C-47297-3109	N16-C-11351-23	R16-C-11709-280	3DA500-97.27	CD CG CSL CTD	DYT-6050 25F-470 XDMRTW6-.5-10 RLON-650	CFN CHEZ CFT CG CW COL CG	300 447-1 CO-610 F-36430-1 K-35J639-3 ES-682063-4 956 2086 20rev0 K-56J876-3rev0	BL 1 thru BL-3 BL-4 (4) BL-5 (3) BL-6 (3) BN-1 DAE (3) SEE NOTE
-481002-20	CAPACITOR, fixed: NT-481002 w/ 500,000 mmf p/m 20%. 4/10/39	RE48A128 RE13A488		16-C-47327-7458	N16-C-11351-22		3DA500-97.4	CIE CD CSL CSF CSF	4BAT-50 DYT-6050 XDMRT-6-5-20 P-6830 2527-13	CHEZ CGQ COL CG	CO-701-B B-CO-10010 956 2086 40rev0 M-7472814-1rev0	EM OAP TBX-8 TDH-4 AN/OPM-1 AN/OPM-1B

SHEET 48-349

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 350

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORP STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481003	CAPACITOR, fixed: 4/10/39 paper dielectric; two sect; 250,000 mmf plus 10 minus 3/8 ea sect; 600 vdcv ea sect; HS metal can; case 1 13/16" lg x 1 1/4" wd x 3/4" h o/a; dykanol impr and filled; three solder lug term 3/8" on top spaced 1/2" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/ bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c.	RE13A488 RE48A128		16-C-53334-1524				CD	DTT-6022	CAG	1CLB9	LP DAJ LP-2 thru LP-4
-481003-15	CAPACITOR, fixed: 4/10/39 NT-481003 w/250,000 mmf p/m 15% ea sect. NOTE: DAK-1 (2) thru DAK-4 (2); OAN (2).	RE13A488 RE48A128		16-C-53433-4174	N16-C-11343-53			3DA250-20.2	DTT-6022	CAG CPT	1CLB9	DAH-2 (2) DAK (2) SEE NOTE
-481004	CAPACITOR, fixed: 4/18/39 paper dielectric; 1 mf plus 10 minus 3/8; 600 vdcv; HS metal can; case 1 13/16" lg x 15/16" wd x 1 1/2" h o/a; oil impr and filled; two screw type term 1/4" h located on top 7/8" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/a 0.161" diam mtg hole 2 1/8" c to c.	RE48A147 RE13A488		16-C-48796-3079	N16-C-11411			CD	VC-1430	CAG	P-432-75rev0	LP thru L-4 LR (5) thru LR-3 (5)
-481004-10	CAPACITOR, FIXED: 3/1/49 Navy Type 481004 w/1.0 mfd p/m 10%.			16-C-48817-3087				CAG	COL-5 chg 3	CAG	COL-5	NObar- 43099
-481005	CAPACITOR, fixed: 4/18/39 paper dielectric; 2 mf plus 10 minus 3/8; 600 vdcv; HS metal can; case 1 13/16" lg x 1 1/16" wd x 2 7/8" h o/a; dykanol impr and filled; two screw type term 1/2" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case, ea w/a 3/16" diam mtg hole 2 1/4" c to c; same as NT-48687 except less elevated bushing.	RE48A147 RE13A488		16-C-49176-3176				CD	TDF-6020	CAG	P-432-74rev0	LP thru LP-4
-481006	CAPACITOR, fixed: 4/18/39 CANCELLED: 4 mfd plus 10 minus 3/8; 600 vdcv; for replacement use NT-48865.	RE48A147						CD	TDF-6040	CAG	P-432-74rev0	LP LP-1 LP-2 LP-3 LP-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-350

RESTRICTED

RESTRICTED

SHEET 48 - 351

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481007	CAPACITOR, fixed: mica; 20 mmf; 500 vdcw, 1,000v DC test; case 21/32" lg x 21/32" wd x 3/16" thk; molded bakelite case; two solder lug term ea w/one 5/32" diam hole 1 15/16" c to c.	4/19/39 RE48A218 16C40										
-481007-A5	CAPACITOR, fixed: NT-481007 w/20 mmf p/m 5%; temp coef ltr A. NOTE: LP-2; LP-3; LP-4.	4/19/39 RE48A218 16C40		16-C-27632-9459				CAW	1465			LP LP-1 SER NOTE:
-481007-A10	CAPACITOR, fixed: NT-481007 w/20 mmf p/m 10%; temp coef ltr A.	4/19/39 RE48A218 16C40		16-C-27637-9939				CAW	1465			
-481008	CAPACITOR, fixed: mica; 200 mmf; 500 vdcw, 1,000v DC test; case 21/32" lg x 21/32" wd x 3/16" thk; molded bakelite case; two solder lug term ea w/ one 5/32" diam hole 1 15/16" c to c.	4/19/39 RE48A218 16C40										
-481008-A10	CAPACITOR, fixed: NT-481008 w/200 mmf p/m 10%; temp coef ltr A.	4/19/39 RE48A218 16C40		16-C-29270-3339				CAW	1465			LP
-481009	CAPACITOR, fixed: mica; 400 mmf; 500 vdcw; case 21/32" lg x 21/32" wd x 3/16" thk; molded bakelite case; two solder lug term ea w/one 5/32" diam hole 1 15/16 c to c.	4/19/39 RE48A218 16C40										
-481009-A10	CAPACITOR, fixed: NT-481009 w/400 mmf p/m 10%; temp coef ltr A.	4/19/39 RE48A218 16C40		16-C-29929-7339			3D9400-37	CAW	1465	CFD	180-125-B	LP
-481009-B10	CAPACITOR, fixed: NT-481009 w/400 mmf p/m 10%; temp coef ltr B.	4/19/39 RE48A218 16C40		16-C-29929-7344				CAW	1465L			LX
-481010	CAPACITOR, fixed: mica; 100 mmf; 1,200 vdcw; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	4/25/39 RE48A112 16C40										
-481010-A10	CAPACITOR, fixed: NT-481010 w/100 mmf p/m 10%; temp coef ltr A.	4/25/39 RE48A112 16C40		16-C-28558-7837			3D9100-2	CD	9-23010			TBA-3 Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-351

RESTRICTED

RESTRICTED

SHEET 48 - 352

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481010-B2	CAPACITOR, fixed: NT-481010 w/100 mmf p/m 2%; temp coef ltr B.	4/25/39 RE48A112 16040		16-C-28548-5877	N16-C-9926			CD	9L-23010	CG CG CG	P-7761560-6rev1.7 P-7762162-8rev2 P-7762664-14	TBA-6 TBA-10
-481010-B5	CAPACITOR, fixed: NT-481010 w/100 mmf p/m 5%; temp coef ltr B.	4/25/39 RE48A112 16040		16-C-28553-7397	N16-C-9926-4		3D9100-60	CD CAN	9L-23010 A2LS-2310	CG CPT	P-7764887-14	TBA-8 TBA-11 SEE NOTE
-481010-B10	CAPACITOR, fixed: NT-481010 w/100 mmf p/m 10%; temp coef ltr B.	4/25/39 RE48A112 16040		16-C-28558-7842	N16-C-9926-12		3D9100-14	CD	9L-23010			
-481011	CAPACITOR, fixed: CANCELLED: reassigned 150 mmf; 3,000 vdcw max; 1.8 amp at 3000 kc, 1.0 amp at 1000 kc, 0.45 amp at 300 kc, 0.15 amp at 100 kc.	6/9/39 RE48A222 16040						CRV	UC-3120	CRV	W-303207-14rev0	CRV-78091
-481012	CAPACITOR, fixed: mica; 30 mmf; 1200 vdcw, 2500 vdc; case 1 1/4" lg x 1 1/8" wd x 23/64" thk; molded bakelite case; two lug term ea w/one 0.173" diam holes; two mtg holes in case 0.144" diam 1/5/16" c to c.	5/17/39 RE48A221 16040										
-481012-A10	CAPACITOR, fixed: NT-481012 w/30 mmf p/m 10%; temp coef ltr A.	5/17/39 RE48A221 16040		16-C-27134-3529				CD	4-24030			
-481012-B10	CAPACITOR, fixed: NT-481012 w/30 mmf p/m 10%; temp coef ltr B.	5/17/39 RE48A221 16040		16-C-27134-3613	N16-C-9835			CD CSL	4L	CG CHZ COQ	P-7761328-26rev0 CO-744 B-CO-744	TAX-4 TAX-4a TAX-5
-481013	CAPACITOR, fixed: mica; 80 mmf; 1200 vdcw, 2500 vdc; case 1 1/4" lg x 1 1/8" wd x 11/32" d; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1/5/16" c to c.	5/17/39 RE48A221 16040										
-481013-A10	CAPACITOR, fixed: NT-481013 w/80 mmf p/m 10%; temp coef ltr A.	5/17/39 RE48A221 16040		16-C-28163-1208				CD	4-24080			
-481013-B10	CAPACITOR, fixed: NT-481013 w/80 mmf p/m 10%; temp coef ltr B.	5/17/39 RE48A221 16040		16-C-28163-1213	N16-C-9922-5 N16-C-9921-11			CD CSL	4L	CG CHZ COQ	P-7761328-27 rev10 CO-745 B-CO-745	TAX-4 TAX-4a TAX-5

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-352

RESTRICTED

RESTRICTED

SHEET 48 - 353

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481014	CAPACITOR, fixed: mica; 300 mmf; 500 vdcv; case 5 1/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	5/17/39 RE48A148										
-481014-A5	CAPACITOR, fixed: NT-481014 w/300 mmf p/m 5%; temp coef ltr A.	5/17/39 RE48A148 JAN-C-5	CM20A301J	16-C-29660-8991				CAW CD CSL CMR	1468 5W MO-14200 0	CNA	D-774-19	TBX RAO-7 BAO-9
-481014-A10	CAPACITOR, fixed: NT-481014 w/300 mmf p/m 10%; temp coef ltr A. NOTE: LAG-1; RBL; RBL-1; RBL-2; RBL-5; RBL-6.	5/17/39 RE48A148 JAN-C-5	CM20A301K	16-C-29665-9471				CMR CAW CD CSL	0 1468 5W-5T3 MO-1420	CHZ CNA OGZ	CO-632revF D-774 0310	ARK ARK-1 thru ARK-7 LAG SEE NOTE:
-481014-B2	CAPACITOR, fixed: NT-481014 w/300 mmf p/m 2%; temp coef ltr B.	5/17/39 RE48A148 JAN-C-5	CM20B301G	16-C-29655-7516	N16-C-9987-5			CMR CD CAW CSL	0XM 5WLS 1468LS MOBW-1420-2	CRR	C56304-301 1seeB	
-481014-B5	CAPACITOR, fixed: NT-481014 w/300 mmf p/m 5%; temp coef ltr B.	5/17/39 RE48A148 JAN-C-5	CM20B301J	16-C-29660-8996	N16-C-9988	R16-C-9994-15	3K2030122	CMR CAW CD CSL	0XM 1468LS 5WLS MOBW-1420	CHZ CRR CG	CO-642revH C-563051seeJ M-7466441-30rev1	ARK ARK-1 thru ARK-7
-481014-B10	CAPACITOR, fixed: NT-481014 w/300 mmf p/m 10%; temp coef ltr B. NOTE: SK-1M; SK-2; SK-3; SO; SR; SR-5.	5/17/39 RE48A148 JAN-C-5	CM20B301K	16-C-29665-9476	N16-C-9989	R16-C-9994-85		CD CSL CAW CER CMR CMF	5WLS MOBW-1420 1468LS M4K300 0XM 0XM	CIA CRB CIP CRV CEM CG CAY	D-5498.1B-190 CD-1033-131seeC SN-516 P-720473-35rev19 744-606 M-7466441-14rev1 T-7610947-32	ARQ DAG LAE-2 LAE-3 LAF-1 LAF-2 SC-4 SEE NOTE:
-481014-B20	CAPACITOR, fixed: NT-481014 w/300 mmf p/m 20%; temp coef ltr B.	5/17/39 RE48A148 JAN-C-5	CM20B301M	16-C-29671-2956	N16-C-9992-12			CD CAW CSL CMR	5WLS 1468LS MOBW-1420 0XM			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-353

RESTRICTED

RESTRICTED

SHEET 48 - 354

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTORS DWG OR PART NO	EQUIPMENT USED IN
-481014-D1	CAPACITOR, fixed: 5/17/39 NT-481014 w/300 mmf p/m 1%; temp coef ltr D.	RE48A148 16C40		16-C-29654-9610	N16-C-9987			CD CAW CSL CMR CSL	5RS 1469 MO5DW PO MO5DW-1420	CBM CG rev15 CBZ CGQ	744-272 P-7761328-25 rev15 CO-743 B-CO-743	TBX-4 TBX-4a TBX-5 TBX-8 NT-3 (3) SEE NOTE:
-481014-D2	CAPACITOR, fixed: 5/17/39 NT-481014 w/300 mmf p/m 2%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D301G	16-C-29655-7526	N16-C-9990-4	R16-C-9994-11		CD CAW CSL CMR	5R 1469 MO5DW PO			DAJ (2)
-481014-D5	CAPACITOR, fixed: 5/17/39 NT-481014 w/300 mmf p/m 5%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D301J	16-C-29660-9006	N16-C-9991-1	R16-C-9994-20	3K2030142	CD CAW CSL CMR	5R5T3 1469 MO5DW PO	CG	M-7463969-30rev3	DAU (2) DAU-1 (2)
-481014-D10	CAPACITOR, fixed: 5/17/39 NT-481014 w/300 mmf p/m 10%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D301K	16-C-29665-9486	N16-C-9992-7	R16-C-9994-75		CAW CD CSL CMR CER CD	1469 5RS MO5DW PO M4K300 5R	CRV CG CRB CRV	M-303114-347 M-7463969-14rev3 ED-1034-131anC P-720473-24rev13	QCJ-8 QCL-7 RAX-1 SA SA-1 SA-2 SA-3 (2) SEE NOTE:
-481015	CAPACITOR, fixed: 5/17/39 mica; 400 mmf; 500 vdcw; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148										
-481015-A5	CAPACITOR, FIXED: 5/17/49 Navy Type 481015 w/400 mmf p/m 5%; temp coef letter A.			16-C-29925-2075				CNB		CFL		AN/ARW-2
-481015-A10	CAPACITOR, fixed: 5/17/39 NT-481015 w/400 mmf p/m 10%; temp coef ltr A.	RE48A148 JAN-C-5	CM20A401K	16-C-29929-7471				CAW CD CSL CMR	K 1468 5W MO 0	CMK CRV	B250073-145rev4 P-720592-36rev32	TBX RAK-8 RAL-7 RAL-8
-481015-B2	CAPACITOR, fixed: 5/17/39 NT-481015 w/400 mmf p/m 2%; temp coef ltr B.	RE48A148 JAN-C-5	CM20A401G	16-C-29919-5516		R16-C-10007		CD CAW CSL CMR	5WLS 1468LS MO5W-1421-2 OXM	CRR	C56304-401 1anB	Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-354

RESTRICTED

RESTRICTED

SHEET 48 - 355

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-481015-B5	CAPACITOR, fixed: NT-481015 w/400 mmf p/m 5%; temp coef ltr B.	5/17/39	RE48A148 JAN-C-5	CM20B401	16-C-29924-6996	N16-C-10007-11		3E2039122	CD CAW CSL CMR	5WLS 14681S MOBW-1421-5 OXM	CHZ CO-11181aa0	SJ-1 (2) AN/ UPM-1(2) AN/ UPM-1B(2) SEE NOTE:	
	NOTE: MK-8 Mod2 (2); MK-8 Mod3 (2); MK-9 (2); MK-10 (2); MK-10 Mod5 (2); MK-34 Mod2.												
-481015-B10	CAPACITOR, fixed: NT-481015 w/400 mmf p/m 10%; temp coef ltr B.	5/17/39	RE48A148 JAN-C-5	CM20B401K	16-C-29929-7476	N16-C-10007-1	R16-C-10009-25	3D89400-23	CD CMF CAW CSL CMR	5WLS 503M 14681S MOBW-1421 OXM	CFM CFT CDL CRB	744-99 B-8F-6911revE CD-1033-141aaC	JEA-1 JEA-4 JEA-5 JEA-5a QCC SEE NOTE:
	NOTE: QCD; QCU-5; QCU-6; QCU-9; QCU-9; QCL-4; QCL-5; QCL-8; QCM-1; QCM-2; QCM-3; QCM-4; QCN-2; QCN-3; QCN-4; QCO-1; QCO-2; QCO-3; QCO-4; QCO-1; QCR; QCR-1; QCS; QCS-1; QCT; QCT-1; QGA; RBA; RBA-1; WDA; WDA-1; WFA; JK-2B; JK-5; SU.												
-481015-C5	CAPACITOR, fixed: NT-481015 w/400 mmf p/m 5%; temp coef ltr C.	5/17/39	RE48A148 JAN-C-5	CM20C401J	16-C-29924-7001		R16-C-10008-60		CSL CAW CD CMR	MOSCV 14681ST 5RS PO	CRP	35-5211	SM SM-1 SO SO-a SEE NOTE:
-481015-D1	CAPACITOR, fixed: NT-481015 w/400 mmf p/m 1%; temp coef ltr D.	5/17/39	RE48A148 16C40		16-C-29918-7610	N16-C-10005-30			CD CAW CSL	R 1469 MOSDW	CG CHZ CC2	P-7761328-24 rev15 CO-742 B-CO-742	TBX-4 TBX-4a TBX-5 TBX-8
-481015-D2	CAPACITOR, fixed: NT-481015 w/400 mmf p/m 2%; temp coef ltr D.	5/17/39	RE48A148 JAN-C-5	CM20D401G	16-C-29919-5526	N16-C-10005-3		3D9400-15	CD CAW CSL CMR	5RS 1469 MOSDW PO	CRB	CD-10 4-51aaC	TS-120/ UF (2) TS-191/ UF (2)
-481015-D5	CAPACITOR, fixed: NT-481015 w/400 mmf p/m 5%; temp coef ltr D.	5/17/39	RE48A148 JAN-C-5	CM20D401J	16-C-29924-7006	N16-C-10007-3	R16-C-10009		CAW CD CSL CMR	1469S 5RS MOSDW PO	CFM CG CRV	744-467 M-7463969-31rev3 P-720538-8rev30	SU SU-1
-481015-D10	CAPACITOR, fixed: NT-481015 w/400 mmf p/m 10%; temp coef ltr D.	5/17/39	RE48A148 JAN-C-5	CM20D401K	16-C-29929-7486	N16-C-10005-25	R16-C-10009-15	3D9400-15	CD CAW CSL CMR	5RS 1469 MOSDW PO	CG CWB	M-7463969-15rev3 CD-1034-141aaC	BAX-1 (4)
-481015-D20	CAPACITOR, fixed: NT-481015 w/400 mmf p/m 20%; temp coef ltr D.	5/17/39	RE48A148 JAN-C-5	CM20D401M	16-C-29934-9966	N16-C-10007-4		3D9400-15	CD CAW CSL CMR	5RS 1469 MOSDW PO			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-355

RESTRICTED

RESTRICTED

SHEET 48 - 356

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK, NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481016	CAPACITOR, fixed: 5/17/39 mica; 700 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64"wd x 9/32"d; molded bakelite case; two axial wire leads.	RE48A143										
-481016-A3	CAPACITOR, fixed: 5/17/39 NT-481016 w/700 mmf p/m 3%; temp coef 1tr A.	RE48A143 16C40		16-C-30583-3423				CAW CD CSL CMR	1467 1W MW W	CHA		RAS RAS-1 RAS-2 RAS-3 RAS-4 RAS-5
-481016-A10	CAPACITOR, fixed: 5/17/39 NT-481016 w/700 mmf p/m 10%; temp coef 1tr A.	RE48A143 JAN-C-5	CM30A701K	16-C-30589-2559				CAW CD CSL	1467 1W MW	CHA	D-775-75	RAO-2 RAO-6 RAO-7 RAO-9
-481016-B2 1/2	CAPACITOR, fixed: 5/17/39 NT-481016 w/700 mmf p/m 2 1/2%; temp coef 1tr B.	RE48A143 16C40		16-C-30583-2756				CD CAW CSL CAN	1WL 1467L MWB CL	CRR	A-292-4a1 TB	
-481016-B5	CAPACITOR, fixed: 5/17/39 NT-481016 w/700 mmf p/m 5%; temp coef 1tr B; RSW immersion.	RE48A143 JAN-C-5	CM30A701J	16-C-30584-2084	N16-C-10066-4			CD CAW CSL CAN	1WLS 1467LS MWBW CLW	CG	P-7762455-59rev7	
-481016-B10	CAPACITOR, fixed: 5/17/39 NT-481016 w/700 mmf p/m 10%; temp coef 1tr B; RSW immersion.	RE48A143 JAN-C-5	CM30B701K	16-C-30589-2564	N16-C-10068-3			CD CAW CSL CAN	1WLS 1467LS MWBW CLW	CG CHA	P-7762455-17rev7 D-775	RBH-1 RBH-2 RBH-3
-481016-B20	CAPACITOR, fixed: 5/17/39 NT-481016 w/700 mmf p/m 20%; temp coef 1tr B.	RE48A143 JAN-C-5	CM30B701M	16-C-30594-5044	N16-C-10068-4			CD CAW CSL CAN	1WL 1467L MWB CL			
-481016-C5	CAPACITOR, FIXED: 1/26/48 Navy Type 481016 w/700 mmf p/m 5%; temp coef letter C.			16-C-30584-2090				CSL	MNCW-1224-5	CHZ	CO-910	RM BO SM
-481016-D1	CAPACITOR, fixed: 5/17/39 NT-481016 w/700 mmf p/m 1%; temp coef 1tr B; RSW immersion.	RE48A143 16C40		16-C-30578-2510	N16-C-10064-9 N16-C-10066-2		3D9700-14	CD CAW CSL CSL	1RS 1464 MWSBW MWSBW-1224	CG CHZ COQ	P-7761328-23 CO-741 B-00-741 rev16	TBX TBX-4 TBX-4a TBX-5 Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-356

RESTRICTED

RESTRICTED

SHEET 48 - 357

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481016-D5	CAPACITOR, fixed: 5/17/39 NT-481016 w/700 mmf p/m 5%; temp coef ltr D; RSW immersion.	RE48A143 JAN-C-5	CM30D701J	16-C-30584-2094				CD CAW CSL	IRS 1464 M65DW	CG	M-7464-527-43rev0	
-481016-D10	CAPACITOR, fixed: 5/17/39 NT-481016 w/700 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM30D701K	16-C-30589-2574				CAN	CRM-1370	CWQ	47X349	RAO-3 RAO-4 RAO-5
-481017	CAPACITOR, fixed: 5/19/39 paper dielectric; 100,000 mmf plus 10 minus 3%; 400 vdcw; HS metal can; case 1 1/2" lg x 5/8" diam; oil impr and filled; two axial wire leads; no int gnd connections; radial mtg strap w/one 0.154" diam hole 15/16" from ctr of capacitor.	RE48A162 RE13A488		16-C-45752-8210				CD	TVC-4F1	CD	SK-3696	CXX
-481018	CAPACITOR, variable: 5/25/39 air; plate meshing type single sect; 3 to 25 mmf; SiC; 0.0195" air gap; 7/8" lg x 15/16" wd x 1 1/32" h shaft w/bushing and lock nut 5/16" diam x 5/16" lg o/a; scdr adj; seven nickel pl brass plates; 360 deg rotation; ceramic insulation; post term for stator, lug term for rotor on RH side; two mtg studs 5/16" lg w/#4-40 tapped in ea csk 82 deg x 9/64" diam on 21/32" mtg/c 31/64" from top.			16-C-58940-6500				CEC	APC-25	CHR	A15441-1 1see0	RAP
-481019	CAPACITOR, fixed: 5/25/39 paper dielectric; 9 mf plus 10 minus 3%; 400 vdcw; HS metal can; case 2 13/16" lg x 1 3/4" wd x 4 5/16" h o/a; oil filled; one solder lug type term 5/8" h located on bottom 3/4" off-ctr; int gnd; four 1/4" d x #6-32 thd mtg holes on 2 1/8" x 1 1/8" mtg/c on bottom.	RE48A206 RE13A488		16-C-51643-4397								
-481019-10	CAPACITOR, fixed: 5/25/39 NT-481019 w/9 mf p/m 10%.	RE48A206 RE13A488		16-C-51664-4397						CHR	A17469	RAP

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-357

RESTRICTED

RESTRICTED

SHEET 48 - 358

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481020	CAPACITOR, fixed: 5/25/39 paper dielectric; two sect; 4 mf plus 10 minus 3% ea sect; 450 vdcv ea sect; metal case; case 3 1/2" lg x 3" wd x 2" h; oil impr and filled; two solder lug term on top of case 3/4" c to c 1/2" h; common connection gnd to case; one mtg skt on ea side at bottom of case ea w/two 7/32" diam holes on 3 13/16" x 2 1/4" mtg/c.	RE46A172 REL3A488		16-C-54092-5180				CRR CAW	A15463A	CRR	A15463A dated 2/9/39	RAP
-481021	CAPACITOR, FIXED: 5/25/39 ceramic dielectric; 10 mmf; neg temp coef 750 (tol p/m 120) mmf/mfd/°C; 500 vdcv; case 0.812" lg x 0.25" diam; axial wire leads; ceramic ins; add suffix indicating capacity tolerance in per cent.											
-481021-5	CAPACITOR, fixed: 5/25/39 NT-481021 w/10 mmf p/m 5%.			16-C-15917-2590				CEN	Class F	CG	P-7763769-10rev0	
-481021-10	CAPACITOR, fixed: 5/25/39 NT-481021 w/10 mmf p/m 10%.			16-C-15925-1269		RC-C-7790		CER	W750L10 p/m 1.0	CRR CW	A17464-100rev0	RAP MK-3 MK-4
-481022	CAPACITOR, FIXED: 5/25/39 ceramic dielectric; 20 mmf; neg temp coef 680 (tol p/m 40.8) mmf/mfd/°C; 500 vdcv; case 7/16" lg x 7/32" diam; axial wire leads; ceramic ins; add suffix indicating cap tolerance in per cent.											
-481022-5	CAPACITOR, FIXED: 5/25/39 Navy Type 481022 w/20 mmf p/m 5%.			16-C-16085-1223		R16-C-7820		CER	RG60K20 p/m 1	CRV CRR CW CZR	M-428801-19 A-17462-200 rev0 250-677726-3 22G-146	ARB ZB-2 AN/ARR-1 TS-1/ARR-1
-481022-10	CAPACITOR, fixed: 5/25/39 NT-481022 w/20 mmf p/m 10%.			16-C-16094-5749				CER		CER CRR	CO-623 A25328-200	RAP BL-1 thru BL-6
-481023	CAPACITOR, FIXED: 5/25/39 ceramic dielectric; 35 mmf; neg temp coef 680 (tol p/m 40.8) mmf/mfd/°C; 500 vdcv; case 7/16" lg x 7/32" diam; axial wire leads; ceramic ins; add suffix indicating capacity tolerance in per cent.											
481023-5	CAPACITOR, fixed: 5/25/39 NT-481023 w/35 mmf p/m 5%.			16-C-16341-1223		R16-C-8257		CER		CRR	A17462-350 rev0	RAP (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-358

RESTRICTED

RESTRICTED

SHEET 48 - 359

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481024	CAPACITOR, fixed: 5/25/39 ceramic dielectric; 50 mmf; neg temp coef 680 (tol p/m 40.8) mmf/mfd/°C; 500 vdcw; case 7/16" lg x 7/32" diam; axial wire leads; ceramic ins; add suffix indicating capacity tolerance in per cent.											
-481024-5	CAPACITOR, fixed: 5/25/39 NT-481024 w/50 mmf p/m 5%.			16-C-16565-1223	N16-C-8142-3	R16-C-8273		CER		CRR	A17462-500	RAP
-481024-6	CAPACITOR, fixed: 5/25/39 NT-481024 w/50 mmf p/m 6%.			16-C-16567-6723	N16-C-8141-10			CER		CTA	D5507-42	JM-4 (c)
-481024-7	CAPACITOR, fixed: 5/25/39 NT-481024 w/50 mmf p/m 7%.			16-C-16567-7623	N16-C-8142			CER		CW		ME-3 (4) ME-4 (4)
-481024-10	CAPACITOR, fixed: 5/25/39 NT-481024 w/50 mmf p/m 10%.			16-C-16574-5723				CER		CRR CCI	A17462-500rev0 130-50	DAG DAV-2
-481025	CAPACITOR, fixed: 5/25/39 paper dielectric; 30,000 mmf plus 10 minus 3%; 400 vdcw; BS black phenolic case; case 1 7/16" lg x 3/4" wd x 3/8" thk; wax impr; pigtail term 2" lg at ea end; no int gnd connections; no mtg hkt required.	E48A164 RE13A488		16-C-43472-7963	N16-C-11097-75			CMR	345			
-481025-10	CAPACITOR, fixed: 5/25/39 NT-481025 w/30,000 mmf p/m 10%.	RE48A164 RE13A488		16-C-43493-7963			3DA30-47	CMR	345	CRR	A17457-303	BAP
-481025-20	CAPACITOR, fixed: 5/25/39 NT-481025 w/30,000 mmf p/m 20%.	RE48A164 RE13A488		16-C-43525-6184	N16-C-11099-500			CMR	342-120	CMX	B-250129-4 rev1	RCT RCU RCU-1
-481025-A	CAPACITOR, fixed: 3/29/45 paper dielectric; 30,000 mmf plus 10 minus 3%; 600 vdcw; BS molded phenolic case; case 1 1/2" lg x 13/16" wd x 7/16" thk; wax impr; pigtail term 2" lg at ea end; no int gnd connections; no mtg hkt required; same as NT-481025 except 600v instead of 400v.	RE13A488 RE48A164		16-C-43476-1824				CMR	345			
-481025-A20	CAPACITOR, fixed: 3/29/45 NT-481025-A w/30,000 mmf p/m 20%.	RE48A164 RE13A488		16-C-43527-6663	N16-C-11101			CMR	345	CFN	300446-2rev1	BN BN-1 (2) BN-2

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-359

RESTRICTED

RESTRICTED

SHEET 48 - 360

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	COM. TRADES	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481026	CAPACITOR, fixed: paper dielectric; 50,000 mmf plus 10 minus 3%; 400 vdcw; BS phenolic case; case 1 7/16" lg x 3/4" wd x 3/8" thk; oil impr; wire lead term 1 1/8" lg at ea end; no int gnd connections; no mtg bkt required; for replacement use NT-481026-A.	5/25/39 RE48A164 RE13A488		16-C-44232-7968	N16-C-11155-60			CMR CSL	345 MPW-5145-310	CRR	A17457-503rev0	
-481026-10	CAPACITOR, fixed: NT-481026 w/50,000 mmf p/m 10%; for replacement use NT-481026-A10. NOTE: AN/MFN-1A (3).	5/25/39 RE48A164 RE13A488		16-C-44233-7973			3DA50-15	CMR CSL	345-22 MPW-5145-10	CRR CRR CSV	A-17457-903 rev 0 A18015-503 rev J A-61066 rev 0	RAP (6) SM SEE NOTE
-481026-A	CAPACITOR, fixed: paper dielectric; 50,000 mmf plus 10 minus 3%; 600 vdcw; BS black phenolic case; case 1 7/16" lg x 3/4" wd x 3/8" thk; wax impr; pig tail term 1 1/2" lg at ea end; no int gnd connections; no mtg bkt required; same as NT-484773 except tol.	10/7/42 RE48A164 RE13A488						CMR	345			SM
-481026-A10	CAPACITOR, fixed: NT-481026-A w/50,000 mmf p/m 10%.	10/7/42 RE48A164 RE13A488		16-C-44257-1567	N16-C-11164		3DA50-115	CMR	345-22	CG CHL CW	K-357604-2rev1 46A1503H BA-49356	SM-1 SQ (4)
-481026-A20	CAPACITOR, fixed: NT 481026-A w/50,000 mmf p/m 20%.	10/7/42 RE48A164 RE13A488		16-C-44287-6529			3DA50-57.1	CMR	345	CIA	A-6.2.1-6chg0	
-481027	CAPACITOR, fixed: paper dielectric; 100,000 mmf plus 10 minus 3%; 400 vdcw; BS black phenolic case; case 1 7/16" lg x 3/4" wd x 3/8" thk; wax impr; pig tail term 1 1/2" lg at ea end; no int gnd connections; no mtg bkt required.	5/25/39 RE48A164 RE13A488		16-C-45752-7963				CMR	345			
-481027-5	CAPACITOR, fixed: NT-481027 w/100,000 mmf p/m 5%.	5/25/39 RE48A164 RE13A488		16-C-45731-7963			3DKA100-157.1	CMR	345-21	CRR	A18014-104	RAP (30)
-481027-10	CAPACITOR, fixed: NT-481027 w/100,000 mmf p/m 10%.	5/25/39 RE48A164 RE13A488		16-C-45773-7973	N16-C-11296			CD CMR	345-21	CG CG CRR CRP CRF DADV	K-357604-1 M-140832rev13 A18015-104 iss J A17457-104 iss J 0220030-45 chg 0 E252	SC-3 (3) SK-2 (3) SK-3 (3) SM (15) SM-1 (15) SEE NOTE
-481027-20	CAPACITOR, fixed: NT-481027 w/100,000 mmf p/m 20%.	5/25/39		16-C-45805-6184	N16-C-11296-4		3DA100-612	CMR	345-21	CAOR CRV CIA	H1090-4 97670-10 sub 10 A-6.2.3-2chg0	MAR (2) OCF RDR (2)
-481027-A10	CAPACITOR, FIXED: CANCELLED; use Navy Type 481783-10.	3/5/46 RE48A164 RE13A488		16-C-42737-1567				CMR	342-17			

SHEET 48-360

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 361

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-481028	CAPACITOR, fixed: 5/25/39 paper dielectric; 30,000 mmf plus 10 minus 3%; 200 vdcw; US black phenolic case; case 1 7/16" lg x 3/4" wd x 5/16" thk; wax impr; pig tail term 2" lg at ea end; no int gnd connections; no mtg bkt required.	RE48A164 RE13A488										
-481028-10	CAPACITOR, fixed: 5/25/39 NT-481028 w/30,000 mmf p/m 10%.	RE48A164 RE13A488		16-C-4490-2459				CMR	342	CRR	A17461-303rev0	HAP (2)
-481029	CAPACITOR, fixed: 5/25/39 electrolytic; 5 mf; 50 vdcw; working temp range minus 40°C to plus 65°C; case 1 13/16" lg x 1" wd x 7/8" h; brass case; two solder lug term w/ins, term 1/2" h spaced 1" c to c, term located on side; term ins from can; two mtg ft on bottom, 3/16" diam hole in ea, on 2 1/8" mtg/c.	RE48A311		16-C-19458-9791		R16-C-9652-20	3DF5-16	CAW	C55838	CRR	C55838	HAP
-481030	CAPACITOR, fixed: 6/9/39 paper dielectric; 1.1 mf plus 10 minus 3%; 330v AC (50 cyc; MS metal can; case 1 7/8" lg x 1" wd x 2 3/16" h o/a; oil impr and filled; two screw type term 13/32" h located on top 13/16" c to c; no int gnd connections; two mtg fl 7/8" wd on side of case, ea w/two 0.213" diam mtg holes 13/32" apart 2 3/8" c to c; for replacement use only.	RE48A158 RE13A488		16-C-48397-4610				CG	26F270			CRV-78091
-481031	CAPACITOR, fixed: 6/30/39 mica; 5 mmf; 1200 vdcw, 2500v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-481031-A10	CAPACITOR, fixed: 6/30/39 NT-481031 w/5 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-25103-3437				CD	9-25050			60-5
-481031-B10	CAPACITOR, fixed: 6/30/39 NT-481031 w/5 mmf p/m 10%; temp coef ltr B.	RE48A112 16C40		16-C-25103-3447				CD	9L-25050	CG	P-7761560-25 rev 12	
-481032	CAPACITOR, fixed: 6/30/39 mica; 550 mmf; 1200 vdcw, 2500v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 16C40										
-481032-A10	CAPACITOR, fixed: 6/30/39 NT-481032 w/550 mmf p/m 10%; temp coef ltr A.	RE48A112 16C40		16-C-30273-3837				CD	9-23055			60-5
-481032-B2	CAPACITOR, fixed: 6/30/39 NT-481032 w/550 mmf p/m 2%; temp coef ltr B.	RE48A112 16C40		16-C-30263-1882		R16-C-10027		CD	9L-23055	CG	P-7761560-26rev9	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-361

RESTRICTED

RESTRICTED

SHEET 48 - 362

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGN	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481033	CAPACITOR, fixed: mica; 700 mmf; 5000 vdcw, 5 amp at 3000 kc, 4 amp at 1000 kc, 2.5 amp at 300 kc, 1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low-loss bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	6/30/39 RE48A131 16C40										
-481033-B2	CAPACITOR, fixed: NT-481033 w/700 mmf p/m 2%; temp coef ltr B.	6/30/39 RE48A131 16C40		16-C-30580-9643				CD	PL-762-618	CG	P-7761566-19 revi3	
-481033-B5	CAPACITOR, fixed: NT-481033 w/700 m f p/m 5%; temp coef ltr B.	6/30/39 RE48A131 16C40		16-C-30586-2123	N16-C-10069-5			CD CAW CSF	PL-762-618 F2LS MX-17	COL	906 3701.10	GO-5 TC2
-481034	CAPACITOR, fixed: mica; 15 mmf; 1200 vdcw, 2500v DC test; case 1 3/4" lg x 1 5/16" wd x 15/32" h; molded low loss bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	8/5/39 RE48A112 16C40										
-481034-A10	CAPACITOR, fixed: NT-481034 w/15 mmf p/m 10%; temp coef ltr A.	8/5/39 RE48A112 16C40		16-C-26448-5837				CD	9-24015			GO-5
-481034-B10	CAPACITOR, fixed: NT-481034 w/15 mmf p/m 10%; temp coef ltr B.	8/5/39 RE48A112 16C40		16-C-26448-5842				CD	9LS-24015	CG	P-7761560-17 revi4	
-481035	CAPACITOR, fixed: mica; 550 mmf; 3000 vdcw, 4 amp at 300 kc, 2 a p at 1000 kc, 1.2 amp at 300 kc, 0.6 amp at 100 kc; case 2" lg x 15/16" wd x 1 1/2" h; molded bakelite case; two screw term 7/16" lg 1 1/2" c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	8/10/39 RE48A222 16C40										
-481035-A5	CAPACITOR, fixed: NT-481035 w/550 mmf p/m 5%; temp coef ltr A.	8/10/39 RE48A222 16C40		16-C-30268-9620				CD	PL-1072-15			GO-5
-481035-B2	CAPACITOR, fixed: NT-481035 w/550 mmf p/m 2%; temp coef ltr B.	8/10/39 RE48A222 16C40		16-C-30263-8141		R16-C-10028		CD	PL-1072-1518	CG	E-7875296rev0	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-362

RESTRICTED

RESTRICTED

SHEET 48 - 363

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	Com. TRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481036	CAPACITOR, fixed: 8/11/39 mica; 3,000 mmf; 500 vdcw; case 53/64" lg x 53/64" wd x 9/32" d; molded bakelite case; two axial wire leads.	RE48A143										
-481036-A5	CAPACITOR, fixed: 8/11/39 NT-481036 w/3,000 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A302J	16-C-32193-2479	N16-C-10326			CSL	MMW	CRP	35-5143	RAR TCD VF
-481036-A10	CAPACITOR, fixed: 8/11/39 NT-481036 w/3,000 mmf p/m 10%; temp coef ltr A. NOTE: RBE-1 thru RBE-3; REL-1; REL-2; REL-5; REL-6; MK-8; MK-8 Mod 1; MK-8 Mod 2; MK-8 Mod 3.	RE48A143 JAN-C-5	CM30A302K	16-C-32198-2959	N16-C-10326-5		3DA3-5.1	CMR CSL CAW CD CAN	W MMW-1235-10 1467 1W C	CEZ CCI CBM CNA CW	CO-6531seeF CO-9381seeA4 2-1467rev1 744-515 D-775 ES-682029-24	ABK-1 thru ABK-7 EM-1 EM-2 BO-1 QGA SEE NOTE
-481036-A20	CAPACITOR, fixed: 8/11/39 NT-481036 w/3,000 mmf p/m 20%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A302M	16-C-32203-5439			3DA3-35	CD CAW CSL CAN CMF CMR	1W 1467 MM C 502J W	CCI	H-1W5D3.003	MAB (4)
-481036-B2	CAPACITOR, fixed: 8/11/39 NT-481036 w/3,000 mmf p/m 2%; temp coef ltr B.	RE48A143 16C40		16-C-32188-1004	N16-C-10325-150	R16-C-10326-20		CAW CD CSL CAN	1467LS 1WLS MMW CLW	CER CER	C-56306-251 C-56736-3021seeD	EM-2
-481036-B3	CAPACITOR, fixed: 8/11/39 NT-481036 w/3,000 mmf p/m 3%; temp coef ltr B.	RE48A143 16C40		16-C-32192-3823		R16-C-10326-23		CD CAW CSL CAN	1WLS 1467LS MMW CLW			
-481036-B5	CAPACITOR, fixed: 8/11/39 NT-481036 w/3,000 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B302J	16-C-32193-2484	N16-C-10326-10	R16-C-10326-26	3K3030222	CD CAW CSL CAN	1WLS 1467LS MMW CLW	CG CG CG	M-7463931-21rev0 P-7762455-55rev7 K-27J362-159	RAR (2) VC-1
-481036-B10	CAPACITOR, fixed: 8/11/39 NT-481036 w/3,000 mmf p/m 10%; temp coef ltr B. NOTE: SD-a; SD-1 thru SD-4; TCD; TCJ-1; TCK-1 thru TCK-7; MK-9; MK-10; MK-10 Mod 5.	RE48A143 JAN-C-5	CM30B302K	16-C-32198-2964	N16-C-10326-4	R16-C-10326-40	3DXA3-61.1 3DA3-65	CAW CSL CMR CD	1467LS MMW WDM 1WLS	CRV CG CG	P-720473-41rev19 P-7762455-24rev7 M-7463931-9	ARJ ATJ AVD-2 AVD-3 SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-363

RESTRICTED

RESTRICTED

SHEET 48 - 364

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
481036-B20	CAPACITOR, fixed: NT-481036 w/3,000 mmf p/m 20%; temp coef 1tr B.	8/11/39	RE48A143 JAN-C-5	CM308302M	16-C-32203-5444	N16-C-10326-16		CD CAW CSL CAN CMF CMR	1WL 1467L MWR CL 502J WXM			BU-1 TDN (2) TDN-4 ME-8 Mod 2 ME-8 Mod 3 (?) SEE NOTE	
481036-C5	CAPACITOR, fixed: NT-481036 w/3,000 mmf p/m 5%; temp coef 1tr C.	8/11/39	RE48A143 JAN-C-5	CM30302J	16-C-32193-2489	N16-C-10326-2	R16-C-10326-27	3K3030232	CSL CD CAW CAW CAN	MWV IRS 1467LST 1464 C-1230C	CG CZC	K-27J352-659rev6 7137	RBO-2 SM (7) SM-1 (5)
481036-D2	CAPACITOR, fixed: NT-481036 w/3,000 mmf p/m 2%; temp coef 1tr D.	8/11/39	RE48A143 JAN-C-5	CM30D302G	16-C-32188-1014	N16-C-10326-1	R16-C-10326-22	3K3030243	CD CAW CSL CMF CMR CAN	IRS 1464 MMSDW 602J PW CRW			
481036-D5	CAPACITOR, fixed: NT-481036 w/3,000 mmf p/m 5%; temp coef 1tr D.	8/11/39	RE48A143 JAN-C-5	CM30D302J	16-C-32193-2494	N16-C-10326-11		3K3030242	CAW CD CSL CAN	1464 IRS MMSDW C-1230	CRV CZC	P-721133-12 7137	ARB (2) RBO-1
481036-D10	CAPACITOR, fixed: NT-481036 w/3,000 mmf p/m 10%; temp coef 1tr D.	8/11/39	RE48A143 JAN-C-5	CM30D302K	16-C-32198-2974	N16-C-10326-7			CAW CD CMR CSL	1464 IRS PW MMSDW	CG CRV	P-720473-26rev19 W-303314-304	40J-8 QCL-7 SA-2 (2) SA-3 (2) WEA
481036-E2	CAPACITOR, fixed: NT-481036 w/3,000 mmf p/m 2%; temp coef 1tr E.	8/11/39	RE48A143 JAN-C-5	CM30E302G	16-C-32188-1019		R16-C-10326-22-900		CD CAW CSL CMF CMR	IRS 1464 MMSDW 502J PW			
481036-E5	CAPACITOR, fixed: NT-481036 w/3,000 mmf p/m 5%; temp coef 1tr E.	8/11/39	RE48A143 JAN-C-5	CM30E302J	16-C-32193-2499			3K3030252	CAW CD CSL CMF CMR	1464 IRS MMSDW 602J PW	CRV	P-721133-9rev5	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-364

RESTRICTED

RESTRICTED

SHEET 48 - 365

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481037	CAPACITOR, fixed: 8/11/39 mice; 5000 mmf; 500 v _{ac} , 1000V DC test; case 53/64" lg x 53/64" wd x 11/32" d; molded bakelite case; two axial wire leads.	RE48A143										
-481037-A10	CAPACITOR, fixed: 8/11/39 NT-481037 w/5,000 mmf p/m 10%; temp coef 1tr A. NOTE: RAS; RAS-1 thru RAS-5; RAW; RBE; RBJ-1 thru RB	RE48A143 JAN-C-5	CM35A502K	16-C-32699-4603			3DA5-38	CD CAW CSL CAN CMR CMP	1DS 1467S MMW C W 502L	CNA CW CZE	D-775 ES-682029-27 525-159	RAN TCD DAH DAB-1 OBJ RAO-1 SEE NOTE
-481037-A20	CAPACITOR, FIXED: 5/17/49 Navy Type 481037 w/5000 mmf p/m 20%; temp coef letter A.			16-C-32704-7084				CNB		CTL		AN/ARW-2
-481037-B2	CAPACITOR, fixed: 8/11/39 NT-481037 w/5,000 mmf p/m 2%; temp coef 1tr B.	RE48A143 16C40		16-C-32689-2650	N16-C-10402			CD CAW CSL CAN CMR CMP	1DES 1467LS MMBW CLW 502L WXM	CBM CAY	744-740 alto T-7610894-14	SR (4) SR-5 (4) VE (4) VE-1 (4)
-481037-B5	CAPACITOR, fixed: 8/11/39 NT-481037 w/5,000 mmf p/m 5%; temp coef 1tr B.	RE48A143 JAN-C-5	CM35A502J	16-C-32694-4128	N16-C-10402-3 N16-C-10406-11		3DA5-9.1	CSL CD CAW CAN CMR CMP	MMW-1239-5 1DL 1467L CL W 502L	CZE CIA CG	CO-10121as0 D-5498.1B-153 P-7762455-57	RM-1 DAG (2) RAR (2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-365

RESTRICTED

RESTRICTED

SHEET 48 - 366

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481037-B10	CAPACITOR, fixed: 8/11/39 NT-481037 w/5,000 mmf p/m 10%; temp coef 1tr B.	RF48A143 JAN-C-5	CM35B502K	16-C-32699-4608	N16-C-10403		3DA5-38	CAW CMR CSL CD CMF CAN	1467LS WIM MWBW-1239 IDL 502L C-1250	CRV CBE CFT CWR CZC CZR CG CC CRV CBM CGG CPN	P-720473-40rev19 CO-617 CD-1073-15 47X343 5079 C-56303-502 P-7762455-26 M-7463931-11 K-837955-5 744-400 21R6567 C-1063	ARJ ATB BL-1 thru BL-4 BL-6 DAH-2 DAK thru DAK-4 NGA QBC QBC-1 RAP
	NOTE: RAR; RBA; RBA-1; RBB thru RBB-2; RBC thru RBC-2; RBD; RBL-3; RBL-4; RBM thru RBM-5; RBO-1; RBS thru RBS-2; TBC-5; WFA; MK-9; MK-10; MK-10 Mod 5; AN/CPN-6; OBU.											SEE NOTE
-481037-B20	CAPACITOR, fixed: 8/11/39 NT-481037 w/5,000 mmf p/m 20%; temp coef 1tr B.	RF48A143 JAN-C-5	CM35B502M	16-C-32704-7088	N16-C-10403-4		3DA5-125	CD CMF CSL CAW CMR CAN CAN	IDL-3D5 502-L MWBW-1239 1467LS WIM CLW C-1250	CHK CZC	3095-11 7272	ARD-2 LO-1 thru LO-4 BL RBO-1
-481037-C5	CAPACITOR, fixed: 8/11/39 NT-481037 w/5,000 mmf p/m 5%; temp coef 1tr C.	RF48A143 JAN-C-5	CM35C502J	16-C-32694-4133	N16-C-10402-3			CAW CD CSL	1467LST IRS MWCW	CRP	35-5260	PF (2) VF
-481037-C10	CAPACITOR, fixed: 8/11/39 NT-481037 w/5,000 mmf p/m 10%; temp coef 1tr C.	RF48A143 JAN-C-5	CM35C502K	16-C-32699-4613	N16-C-10403		3DAJ-38	CSL	MWC-1239	CRP	35-5071	SG-1 (11) SG-2S (11)
-481037-D5	CAPACITOR, fixed: 8/11/39 NT-481037 w/5,000 mmf p/m 5%; temp coef 1tr D.	RF48A143 JAN-C-5	CM35D502J	16-C-32694-4138	N16-C-10403-1			CD CAW CSL CAN CMF	1DR 1464 MWSDW CRW 602L	CM		MK-9 Cont

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-366

RESTRICTED

RESTRICTED

SHEET 48 - 367

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481037-D10	CAPACITOR, fixed: NT-481037 w/5,000 mmf p/m 10%; temp coef ltr D.	8/11/39 RE48A143 JAN-C-5	CM35D502K	16-C-32699-4618	N16-C-10403-3		3DA5-38	CAW CD CMR CSL CMF	1464 1DR PW MWSDW 602L	CG CPK	P-720473-15rev19 20,017	QBD MK-8 Mod 2 MK-8 Mod 3
-481037-D20	CAPACITOR, fixed: NT-481037 w/5000 mmf p/m 20%; temp coef ltr D.	8/11/39 RE48A143 JAN-C-5	CM35D502M	16-C-32704-7098	N16-C-10403-7			CD CAW CMF CSL CAN	1DR 1464 602L MWSDW CRW			
-481038	CAPACITOR, fixed: mica; 1,300 mmf; 500 vdcw; case 53/64" lg x 53/64" wd x 11/32" d max; molded low-loose bakelite case; two axial wire leads.	8/12/39 RE48A143 16C40										
-481038-B2	CAPACITOR, fixed: NT-481038 w/1,300 mmf p/m 2%; temp coef ltr B.	8/12/39 RE48A143 16C40		16-C-31343-9248				CSL CAW CD	MWBW 1467LS 1WLS	OMI CRR	B-250131-1revA A-18766-132rev0	RAF RCT RCU RCU-1
-481038-B5	CAPACITOR, fixed: NT-481038 w/1,300 mmf p/m 5%; temp coef ltr B.	8/12/39 RE48A143 16C40		16-C-31349-1728	N16-C-10177-1	R16-C-10205-130		CD CSL CAW	1WLS MWBW 1467LS	CTU CG	P-8462 K-27J362-151rev0	QBL-3 SC-3 SC-3 RCH
-481038-C5	CAPACITOR, FIXED: Navy Type 481038 w/1300 mmf p/m 5%; temp coef letter C.	9/4/47 JAN-C-5	CM30C132J	16-C-31349-1689								
-481038-D2	CAPACITOR, FIXED: Navy Type 481038 w/1300 mmf p/m 2%; temp coef letter D.	2/13/48 JAN-C-5	CM35D1320	16-C-31343-9258								SG-6
-481039	CAPACITOR, fixed: mica; 500 mmf, 2,500 vdcw, 4.5 amp at 3000 kc, 3 amp at 1000 kc, 1 amp at 300 kc, 0.3 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	8/16/39 RE48A131 16C40										
-481039-001N2	CAPACITOR, fixed: NT-481039 w/1,500 mmf p/m 2%; temp coef ltr 001N.	8/16/39 RE48A131 16C40		16-C-31503-5261				CD	PL-1083-6K	CAY CAY	T-7609144-1 T-7607321-1	TBU TBU-1 thru TBU-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-367

RESTRICTED

RESTRICTED

SHEET 45 - 368

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MPGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481040	CAPACITOR, fixed: 8/24/39 mica; 2,000 mmf; 3,000 vdcw, 6 amp at 3000 kc, 4 amp at 1000 kc, 1.4 amp at 300 kc, 0.4 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded low loss bakelite case; 2 stud term on top 7/16" lg, 1 5/8" c to c; 2 mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481040-00LN2	CAPACITOR, fixed: 8/24/39 NT-481040 w/2,000 mmf p/m 2%; temp coef ltr 00LN.	48A131 16C40		16-C-31798-8898	N16-C-10256-11			CD	PL-1075-6K	CAY CAY	T-7609144-3 T-7607321-3	TBU (2) thru TBU-4 (2)
-481040-25	CAPACITOR, fixed: 8/24/39 NT-481040 w/2,000 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-31798-8885	N16-C-10256-20			CD	613			
-481041	CAPACITOR, fixed: 10/5/39 mica; 625 mmf; 3,000 vdcw max, 4 amp at 3000 kc, 2.5 amp at 1000 kc, 0.8 amp at 300 kc, 0.3 amp at 100 kc; case 2" lg x 1 5/16" wd x 1 1/2" h; molded bakelite case; two screw term 7/16" lg 1 1/2" c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-481041-A5	CAPACITOR, fixed: 10/5/39 NT-481041 w/625 mmf p/m 5%; temp coef ltr A.	RE48A222 16C40		16-C-30400-8620				CD	PL-1076-15			GR-1a TCE
-481041-D2	CAPACITOR, fixed: 10/5/39 NT-481041 w/625 mmf p/m 2%; temp coef ltr D.	RE48A222 16C40		16-C-30395-7143	N16-C-10054	R16-C-10029-25		CD CAW	PL-1076-15H 1570H-123	CAY CAY CAY	T-7609356-60 T-760623-25 T-7606591-42	TCE TCE-1 TCE-2
-481042	CAPACITOR, fixed: 10/10/39 mica; 100 mmf; 500 vdcw; case 2 1/32" lg x 2 1/32" wd x 3/16" thk; molded bakelite case; two solder lug term ea w/one 5/32" diam hole on 1 5/16" ctr.	RE48A218 16C40										
-481042-A10	CAPACITOR, fixed: 10/10/39 NT-481042 w/100 mmf p/m 10%; temp coef ltr A. NOTE: RAS-1 thru RAS-5; RBJ; RBJ-1 thru RBJ-4; LR-1 thru LR-3	RE48A218 16C40		16-C-28558-1539				CAW	1465			RAS RAW SEE NOTE
-481042-B10	CAPACITOR, fixed: 10/10/39 NT-481042 w/100 mmf p/m 10%; temp coef ltr B.	RE48A218 16C40		16-C-28558-1544	N16-C-9923-34			CAW	1465L			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 45-368

RESTRICTED

RESTRICTED

SHEET 48 - 369

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481043	CAPACITOR, fixed: 10/10/39 mica; 500 mmf; 500 vdc, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143										
-481043-A5	CAPACITOR, fixed: 10/10/39 NF-481043 w/500 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A50LJ	16-C-30162-1679				CAN CD CSL CMR	1467 1W MW W	CMA		RBE (2)
-481043-A10	CAPACITOR, fixed: 10/10/39 NF-481043 w/500 mmf p/m 10%; temp coef ltr A. NOTE: RAS-2 thru RAS-5; REJ: RBJ-1 thru RBJ-4.	RE48A143 JAN-C-5	CM30A50LK	16-C-30167-2159				CSL CD CAW CMF CMR CAN	MW-1222-10 1W 1467 502J W C	CBZ	CO-9161eeA4	RAS RAW EM-1 EM-2 BO-1 RAS-1 SEE NOTE
-481043-B5	CAPACITOR, fixed: 10/10/39 NF-481043 w/500 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B50LJ	16-C-30162-1684	N16-C-10016-5			CAW CMR CD CSL	1467L W 1WLS MWBW	CRV	P-720538-20rev30	MK-10 (2) MK-10 Mod 5(2)
-481043-B10	CAPACITOR, fixed: 10/10/39 NF-481043 w/500 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B50LK	16-C-30167-2164	N16-C-10016-6			CAW CD CAW CSL CMF CAN CMR	M4 1WLS 1467LS MWBW-1222 50 J CLW WXM	CDU CRV CGA	3-342 P-720592-12rev30 B-CO-733	TBX-5 TBX-8
-481043-B20	CAPACITOR, fixed: 10/10/39 NF-481043 w/500 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B50LM	16-C-30172-4644	N16-C-10017			CD CAW CSL CAN CMF CMR	1WLS 1467L MWB CL 502J WXM			MK-9 (4) MK-10 (2) MK-10 Mod 5(2)
-481 43-D1	CAPACITOR, FIXED: 11/7/47 Navy Type 481043 w/500 mmf p/m 1%; temp coef letter D.			16-C-30156-2210				CD	1R-LS	CBM	744-227	WFA-1 Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-369

RESTRICTED

RESTRICTED

SHEET 48 - 370

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481043-D5	CAPACITOR, fixed: 10/10/39 NT-481043 w/500 mmf p/m 5%; temp coef 1tr D.	RE48A143 JAN-C-5	CM30D501J	16-C-30162-1694	N16-C-10017-1			CD CAW CSL CMR CAN CMF	1RS 1464 MWSW FW CRW 602J			
-481043-D10	CAPACITOR, fixed: 10/10/39 NT-481043 w/500 mmf p/m 10%; temp coef 1tr D.	RE48A143 JAN-C-5	CM30D501K	16-C-30167-2174	N16-C-10017-2			CD CAW CSL CAN	1RS 1464 MWSW CRW	CON	744-227	NJ-4
-481043-D20	CAPACITOR, fixed: 10/10/39 NT-481043 w/500 mmf p/m 20%; temp coef 1tr D.	RE48A143 JAN-C-5	CM30D501M	16-C-30172-4654	N16-C-10017-3			CD CAW CSL CAN	1RS 1464 MWSW CRW			
-481043-E5	CAPACITOR, fixed: 10/10/39 NT-481043 w/500 mmf p/m 5%; temp coef 1tr E.	RE48A143 JAN-C-5	CM30E501J	16-C-30162-1699				CD CAW CSL CMF CMR	1R 1464 MWSW 602J FW	COL	912 3501 40rev1	
-481043-E20	CAPACITOR, fixed: 10/10/39 NT-481043 w/500 mmf p/m 20%; temp coef 1tr E.	RE48A143 JAN-C-5	CM30E501M	16-C-30172-4659				CD CAW CSL	1R 1464 MWSW	COL	912 3501 40rev1	
-481044	CAPACITOR, fixed: 10/10/39 electrolytic; 10 mf; 50 vdcw; working temp range minus 20°C to plus 65°C; case 1 11/16" lg x 1" diam; metal case; two solder lug term 1/2" h at one end; term ins from can; mts by flat axial strap riveted to can w/two 3/16" diam holes on 2 1/4" mtg/c.	RE48A342 RE13A549		16-C-19558-9221	N16-C-9668	R16-C-9668-25	3DB10-97	CD	FA10025	CD CNA	SK-3852	RAW RAS RAS-1thru RAS-5 RBJ TBJ-3 RBJ-4
-481045	CAPACITOR, fixed: 10/10/39 electrolytic; 25 mf; 50 vdcw; working temp range minus 20°C to plus 65°C; case 1 11/16" lg x 1" diam; metal case; two solder lug term 1/2" h at one end; term ins from can; mts by flat axial strap riveted to can w/two 3/16" diam holes on 2 1/4" mtg/c.	RE48A342 RE13A549		16-C-19783-9221	N16-C-9681	R16-C-9679-60	3DB25-3	CD	FA10062	CD CNA	SK-3852	RAW RAS RAS-1thru RAS-5

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-370

RESTRICTED

RESTRICTED

SHEET 48 - 371

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481046	CAPACITOR, fixed: 10/10/39 mica; 10,000 mmf; 600 vdcw, 1,000v DC test; case 1 1/4" lg x 1 1/4" wd x 5/16" thk; molded bakelite case; two solder lug term ea w/one 3/16" hole on 1 3/4" mtg/c.	RE48A216 16C40										
-481046-A10	CAPACITOR, fixed: 10/10/39 NT-481046 w/10,000 mmf p/m 10%; temp coef 1tr A. NOTE: RAS-1 thru RAS-5 (2); RBE (2); RBJ (2); RBJ-1	RE48A216 16C40 thru RBJ-4 (2).		16-C-33622-7851	N16-C-10499			CAW	1450			RAW(2) RAS(2) SEE NOTE:
-481047	CAPACITOR, fixed: 10/23/39 paper dielectric; 2 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 2 7/8" h; oil impr and filled; two stud and nut term 7/8" h on por pillars 13/16" c to c on top; no int gnd connections; no mtg holes; no mtg bkt supplied.	RE48A139 RE13A488		16-C-49176-3205	N16-RC-14360		3DB2-18	CD CAAI CAW	T-6020 A-1006 609MB	CEM CGG CM CDE	744-138 8A5274100 CB-20103-1 alt0 2376-3	YB YC YD SU(2) XB-2
-481047-10	CAPACITOR, fixed: 10/23/39 NT-481047 w/ 2 mf p/m 10%. NOTE: AN/UPM-1; AN/UPM-1B.	RE48A139 RE13A488		16-C-49197-3145	N16-C-11489-8			CD CAW	T-6020 609	CEM CEM CRR CRR	00-1123100 744-138 0A106653 100 J L-74955-TrevJ	SU-1(2) SX(6) AN/ MPN-1A(2) SEE NOTE:
-481047-20	CAPACITOR, fixed: 10/23/39 NT-481047 w/2 mf p/m 20%.	RE48A139 RE13A488		16-C-49227-7468	N16-C-11489-2							
-481048	CAPACITOR, fixed: 10/23/39 paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 2 1/2" lg x 1 3/16" wd x 3 3/8" h; dykanol impr and filled; two por ins screw type term 7/8" h located on top, spaced 1 1/8" c to c; no int gnd connections; no mtg holes; no mtg bkt supplied.	RE48A139 RE13A488		16-C-49936-5953	N16-C-11554-5			CD CAW	T-6040 609MB	CGG CM CW CEM CDE	8A52278100 CB-20103-2alt0 BA-10001-51006 744-416 2376-2	YB-2 (2) YC YD NK-7 (2)
-481048-10	CAPACITOR, fixed: 10/23/39 NT-481048 w/4 mf p/m 10%. NOTE: AN/MPN-1A (7).	RE48A139 RE13A488		16-C-49957-5931	N16-C-11554-5 N16-C-11559-3		3DB4-3 3DB4-39	CD	T-6040	CEM CEM CRR	744-181 744-542 L74955-1 revJ	WCA (2) WCA-1 (2) WFA (4) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-371

RESTRICTED

RESTRICTED

SHEET 48 - 372

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	COM. TRACER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481049	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 1000 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 4" h; dykanol "A" impr and filled; two por ins screw type term 7/8" h located on top, spaced 13/16" c to c; no int gnd connection, no mtg holes; no mtg wkt supplied.	10/23/39 RE48A139 RE13A488		16-C-49179-7112	N16-C-11490-29			CD CAW	T-10020 1009MB	CDE	2376-5	YB-2 (4) YC YD
-481049-10	CAPACITOR, fixed: NT-481049 w/2 mf p/m 10%.	10/23/39 RE48A139 RE13A488		16-C-49200-7112			3DB2.10020	CD CD	T-10020 TJU-120	CRP CGG CRP	L-74955-2revJ 8A1010881ae0 35-5000	SO-3 (2) SO-7M (2) SO-7N (2)
-481050	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 1,000 vdcw; HS metal can; case 2 1/2" lg x 1 3/16" wd x 4 5/8" h; dykanol "A" impr and filled; two por ins screw type term 7/8" h located on top, spaced 1 1/8" c to c; no int gnd connections; strap mtd.	10/23/39 RE48A139 RE13A488		16-C-49939-8610	N16-C-11561		3DB4-113	CD CAW CIE	T-10040 1009-MB 105A400	CDE	2376-4	YC YB-2 (4) YD YF (2) TS-120/ UP (3) SEE NOTE:
-481050-5	CAPACITOR, fixed: NT-481050 w/4 mf p/m 5%.	10/23/39 RE48A139 RE13A488		16-C-49918-8632				CD CAW	T-10040 1009	CRP	CD-1074-71aaA	
-481050-10	CAPACITOR, fixed: NT-481050 w/4 mf p/m 10%.	10/23/39 RE48A139 RE13A488		16-C-49960-8647	N16-C-11561		3DB4-54.1	CD	T-10040	CRP CW CHR CGG CCT	35-5063 744-513 L-74955-11aeJ 8A527311aeB 45913rev0	FA QCA SG-1 (5) SG-1 (5) SG-2S (5) SEE NOTE:
-481051	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 2000 vdcw; HS metal can; case 3 3/4" lg x 1 1/4" wd x 4" h; dykanol "A" impr and filled; two stud and nut term 1 1/4" h on por pillars 2" c to c on top; no int gnd connections.	10/23/39 RE48A139 RE13A488		16-C-49183-5924	N16-C-11490-200			CD	T-20020			YB YC YD
-481051-10	CAPACITOR, fixed: NT-481051 w/2 mf p/m 10%.	10/23/39 RE48A139 RE13A488		16-C-49204-5948	N16-C-11401		3DB2.20020-3	CD	TJB-20020	CW	ES-602050-49	MK-9 MK-9Mod 1 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-372

RESTRICTED

RESTRICTED

SHEET 48 - 373

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481052	CAPACITOR, fixed: 10/23/39 paper dielectric; 2 mf plus 10 minus 3%; 4000 vdcw; HS metal can; case 3 3/4" lg x 4 9/16" wd x 5 1/16" h o/a; oil impr and filled; two ceramic ins screw type term 2" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 3/16" diam mtg holes 3 3/8" apart 4 3/8" c to c.	RE48A159 RE13A488		16-C-49184-9027				CD CAW	TJ-40020 4009MF	CDE	4155-14	YB YC YD YB-2
-481053	CAPACITOR, fixed: 10/23/39 paper dielectric; 4 mf plus 10 minus 3%; 4000 vdcw; HS metal can; case 5 1/8" lg x 3 1/2" wd x 9 1/16" h, o/a; oil impr and filled; two ceramic ins screw type term 2" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 3/16" diam mtg holes 2 1/4" apart 5 7/8" c to c; add suffix indicating capacity tolerance in per cent.	RE48A159 RE13A488		16-C-49944-9659				CD CAW	TJ-40040 4009MF	CDE	4155-13	YB YC YD YB-2
-481053-20	CAPACITOR, fixed: 10/23/39 NT-481053 w/4 mfd p/m 2%.	RE13A488 RE48A159		16-C-49993-2903				CD	TJ-40040A	COL	930 4514 00 rev 0	
-481054	CAPACITOR, fixed: 10/23/39 paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; cylindrical metal case; case 1 1/2" diam x 4 1/2" lg; oil impr and filled; one #10-32 thd term stud and 1 solder lug term on bottom; int gnd; one 3/4"-16 thd mtg stud 1/2" long on bottom. NOTE: DAK-1 (3); DAK-2 (3); DAK-4 (3); IM-15 (3); IM-16 (3); L M-17 (3); MBM (2); QFO (3).	RE48A207 RE13A488		16-C-49937-5160	N16-C-11554-10			CD CAW	TJA-6040 610	CMD CPT CAPI CJ CIP CPR	408 15-A-3014-1 116-159 SN-508 ST-1176 iss 4	YB YC YD ARD-1 ARD-2 (4) DAK (3) SEE NOTE:
-481054-5	CAPACITOR, fixed: 10/23/39 NT-481054 w/4 mf p/m 5%.	RE48A207 RE13A488		16-C-49918-5160				CD	TJA-6040	CRN	A26161	Con't

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-373

RESTRICTED

RESTRICTED

SHEET 48 - 374

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN	
-481054-10	CAPACITOR, fixed: NT-481054 w/4 mf p/m 10%.	10/23/39 RE48A207 RE13A488		16-C-49998-5160	N16-C-11554-10		3DB4-43	CD CAW	TIA-6040 610	CHL COG CFT OSZ CEM COL CFT CTH RQ CW CPE CRV CADV CAJR	46A018-A 8K42196 188 0 CU-1143 744-347 930 3200 00 NCP-9-2 10.65-B K-866924-1 A-1265 A-43-11 1880	DAB (5) DAB-1 (5) DAB-3 (5) DAJ (7) CAW (2) OAY (9) OBC QBD (2) SD-1 SD-2 SM (2) SM-1 (2) SP (4) SP-1M (4) SEE NOTE:
	NOTE: SU (8); SU-1 (8); SZ (8); TCC (8); TCS-12 (8); TDG (9); TDN-2 (2); TDN-3 (2); TDN-4 (2); YL (4); AN/APA-6 (3); AN/APA-6a (3); TS-202/U (2); MK-3 (2); MK-4 (2).											
-481054-20	CAPACITOR, fixed: NT-481054 w/4 mf p/m 20%.	10/23/39 RE48A207 RE13A488		16-C-49988-5285	N16-C-11554-11			CD	TIA-6040	CFT COL CEP	930 3400 00 CO-11420	DAB (4) DAU DAU-1 TCS-15(8)
-481055	CAPACITOR, variable: air; plate meshing type single sect; 3 to 100 mmf; SLC; 0.020" air gap; 1 1/2" lg x 1 13/32" wd x 1 5/16" h shaft 1/4" diam x 33/64" lg bushing 37/64" lg x 3/8"-32 thd; locking nut sdr adj; nineteen aluminum plates; 360 deg rotation; isolantite ins; lug term; single hole mtg by 3/8" diam mtg bushing or panel mtg by two holes for #6 screws on 1 3/32" mtg/c.	10/24/39		16-C-60541-1236				CBK	ZU-100-AS	CRM CDE	CA-58 4062-45	YB YC YD TCP TCP-1 TCP-2 TCP-3 TF YB-2 (3)
-481056	CAPACITOR, variable: air; plate meshing type dual sect; 1.5 to 4/1.5 to 4 mmf; SLC/SIC; 0.140" air gap; 3 5/8" lg x 1 13/32" wd x 1 45/64" h shaft 1/4" diam x 1/2" lg bushing 11/32" x 3/8"-32 thd; round shaft; five aluminum plates per sect; 360 deg rotation; isolantite ins; lug term; base mtg by means of 4 mtg holes w/#4-36 tapped on 1 15/16" x 1 5/64" mtg/c.	10/24/39		16-C-62059-1676				CBK	ES-4-SD			YB YC YD

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-374

RESTRICTED

RESTRICTED

SHEET 48 - 375

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481057	CAPACITOR, variable: 10/24/39 air; plate meshing type dual sect; 3 to 15 mmf/ 3 to 15 mmf; SIC/SIC; 0.070" air gap; 3 5/8" lg x 1 13/32" wd x 1 45/64" h shaft 1/4" diam x 1/2" lg bushing 11/32" lg x 3/8"-32 thd; round shaft; nine aluminum plates per sect; 360 deg rotation; isolantite ins; lug term; base mtg by means of 4 mtg holes w/#4-36 thd on 1 15/16" x 1 5/64" mtg/c.			16-C-62093-5155				CEK	ET-15-AD	CDE	4074-59.	YB YC YD YB-2 (4)
-481058	CAPACITOR, variable: 10/24/39 air; plate meshing type dual sect; 4 to 30 mmf/4 to 30 mmf; SIC/SIC; 0.070" air gap; 5 3/32" lg x 1 13/32" wd x 1 45/64" h shaft 1/4" diam x 1/2" lg bushing 11/32" lg x 3/8"-32 thd; round shaft; seven-teen aluminum plates per sect; 360 deg rotation; isolantite ins; lug term; base mtg by means of 4 mtg holes w/ #4-36 thd on 3 3/8" x 1 5/64" mtg/c			16-C-62257-9308				CEK	ET-30-AD			YB YC YD
-481059	CAPACITOR, variable: 10/24/39 air; plate meshing type dual sect; 14 to 250 mmf/ 14 to 250 mmf; SIF/SIF; 0.018" air gap; 4 3/4" lg x 2 1/2" wd x 2 1/2" h shaft 1/4" diam x 7/8" lg bushing 3/8" lg x 7/16" diam; scdr adj; thirty-two aluminum plates per sect; 270 deg rotation; isolantite ins; lug term; base mtg by means of 4 mtg holes.			16-C-62957-6581				CNA	2-SE-250			YB YC YD
-481060	CAPACITOR, variable: 11/6/39 air; plate meshing type single sect; 3.6 to 15 mmf; SIC; 0.045" air gap; 1 1/2" lg x 1 5/16" wd x 1 9/32" h shaft 1/4" diam x 1/2" lg bushing 9/32" lg x 5/16"-32 thd; round shaft; ten cad plated brass plates; 360 deg rotation; isolantite ins; post term for stator, lug term for rotor on LH side; single hole mtg by 5/16" diam bushing or base mtg by means of bkt 1/2" wd w/one #6-32 tapped hole ctr.			16-C-58501-6768	N16-C-12218-100			CEC	EP-15X	CWI CDE	4062-46	YB YC YD IS (2) YB-2 (5)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-375

RESTRICTED

RESTRICTED

SHEET 48 - 376

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481061	CAPACITOR, variable: 11/6/39 air; plate meshing type single sect; 3.7 to 50 mmf; SLC; 0.015" air gap; 29/32" lg x 1 5/16" wd x 1 9/32" h shaft 1/4" diam x 1/2" lg bushing 9/32" lg x 5/16"-32 thd; round shaft; fourteen cad plated brass plates; 360 deg rotation; isolantite ins; post term for stator, lug term for rotor on LH side; single hole mtg by 5/16" diam bushing or base mtg by means of bkt 1/2" wd w/one #6-32 tapped hole ctr.			16-C-59690-6626				CHC	HF-50			YB YC YD
-481062	CAPACITOR, variable: 11/6/39 air; plate meshing type single sect; 7.8 to 50 mmf; SLC; 0.045" air gap; 2 3/4" lg x 1 5/16" wd x 1 9/32" h shaft 1/4" diam x 1/2" lg bushing 9/32" lg x 5/16"-32 thd; round shaft; thirty six cad plated brass plates; 360 deg rotation; isolantite ins; post term for stator, lug term for rotor on LH side; single hole mtg by 5/16" diam bushing or base mtg by means of bkt 1/2" wd w/one #6-32 tapped hole ctr.			16-C-59911-8111				CHC	HF-50X			YB YC YD
-481063	CAPACITOR, FIXED: 11/7/39 mica; 1 mmf; 500 vacv, 1000V, DC test; case 51/64" lg x 15/32" wd x 7/32" d, max; molded low loss bakelite case; 2 axial wire lead; term mtg.	RE48A148 JAN-C-5										
-481063-B2	CAPACITOR, fixed: 11/7/39 NT-481063 w/1 mmf p/m 2%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B0100	16-C-23483-3916				CD CAW CSL	5WLS 1468LS MOHW-1400-2	CRB	C56304-010 1a#B	
-481063-B5	CAPACITOR, FIXED: 1/16/50 Navy Type 481063 w/1 mmf p/m 5%; temp coef letter B.	RE48A148 JAN-C-5		16-C-23483-5397	N16-C-9750-4			CD	5WLS			
-481063-B10	CAPACITOR, fixed: 11/7/39 NT-481063 w/1 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B010K	16-C-23493-5876	N16-C-9750-5			CD CAW CSL	5WLS-5V1 1468LS MOHW-1400	CALG CRB	C56306-010 CD-10331a#C	RAF OBV
-481063-D5	CAPACITOR, FIXED: 6/24/48 Navy Type 481063 w/1 mmf p/m 5%; temp coef letter D.	RE48A148		16-C-23480-5407	N16-C-9750-9			CD	5WLS			
-481063-D10	CAPACITOR, fixed: 11/7/39 NT-481063 w/1 mmf p/m 10%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D010K	16-C-23493-5886				CD CAW CSL	5RS 1469 MO6DW	CRB	CD-10341a#C	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-376

RESTRICTED

RESTRICTED

SHEET 48 - 377

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481064	CAPACITOR, fixed: 11/7/39 mica; 46 mmf; 500 vdcw, 1000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; moulded bakelite case; two axial wire leads.	RE48A148 JAN-C-5										
-481064-B2	CAPACITOR, fixed: 11/7/39 NT-481064 w/46 mmf p/m 2%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B600	16-C-27568-3796		R16-C-9843-31		CAW CD CSL CMR	1468LS 5WLS MOBW OXM	CRR	C56304-4601seB	RAP
-481065	CAPACITOR, fixed: 11/7/39 mica; 60 mmf; 500 vdcw, 1000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; moulded bakelite case; two axial wire leads.	RE48A148										
-481065-A5	CAPACITOR, fixed: 11/7/39 NT-481065 w/60 mmf p/m 5%; temp coef ltr A.	RE48A148 JAN-C-5	CM20A600J	16-C-27788-1591				CAW CSL CD CMR	1468 MO 5W O	CNA	D-774	RBL RBL-1 RBL-2 RBL-5 RBL-6
-481065-B2	CAPACITOR, fixed: 11/7/39 NT-481065 w/60 mmf p/m 2%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B600J	16-C-27782-9116				CAW CD CSL CMR	1468LS 5WLS MOBW OXM	CRR	C56304-6001seB	
-481065-B5	CAPACITOR, fixed: 11/7/39 PP-481065 w/60 mmf p/m 5%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B600J	16-C-27788-1596	N16-C-9849-90			CAW CAW CD CSL CMR	1460 1468LS 5WLS MOBW OXM	CWQ CRR CRP	47-x3371seB C56305-6001seC 35-5086	RAP RBL-3 RBL-4 VD(2) VD-1(2)
-481065-B10	CAPACITOR, fixed: 11/7/39 NT-481065 w/60 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B600K	16-C-27793-2076	N16-C-9849-110			CAW CD CSL CMR	1468L 5WL MOBW OXM			
-481065-B20	CAPACITOR, fixed: 11/7/39 NT-481065 w/60 mmf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B600M	16-C-27798-4556	N16-C-9849-150			CAW CD CSL CMR	1468L 5WL MOBW OXM			
-481065-D2	CAPACITOR, fixed: 11/7/39 NT-481065 w/60 mmf p/m 2%; temp coef ltr D.	RE48A148 JAN-C-5	CM20B600G	16-C-27782-9126	N16-C-9849-93	R16-C-9873-175		CAW CMR CD CSL	1469 PO 5RS MOSEW			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-377

RESTRICTED

RESTRICTED

SHEET 48 - 378

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481065-D3	CAPACITOR, fixed: 11/7/39 NT-481065 w/60 mmf p/m 3%; temp coef ltr D.	RE48A148 16C40		16-C-27787-3023		R16-C-9873-200		CAW CMR CER CD CSL	1469 PO M1E-60 5RS MO5DW	CHV	P-721081-11rev2	
-481065-D5	CAPACITOR, fixed: 11/7/39 NT-481065 w/60 mmf p/m 5%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D600J	16-C-27788-1606	N16-C-9849-91		3D9060	CD CSL CAW CMR	5RS MO5DW 1469 PO	CDL	B-8F-4461rev14	SJ-1
-481065-D10	CAPACITOR, fixed: 11/7/39 NT-481065 w/60 mmf p/m 10%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D600K	16-C-27793-2086			3D9060-12	CD CAW CSL CMR	5R-5Q6 1469 MO5DW PO	CADY	A-1302rev0	
-481066	CAPACITOR, fixed: 11/7/39 mica; 110 mmf; 500 vdcw; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148 JAN-C-5										
-481066-B5	CAPACITOR, fixed: 11/7/39 NT-481066 w/110 mmf p/m 5%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B111J	16-C-28658-5796		R16-C-9947-35		CD CAW CSL CMR	5WLS 1468LS MOBW OXM	CTU CRR	P8461 C56305-111 1cc	RAP (2) BL-3
-481066-C5	CAPACITOR, FIXED: 2/20/48 Navy Type 481066 w/110 mmf p/m 10%; temp coef letter C.	JAN-C-5	CM20C111J	16-C-28658-5801								PO
-481067	CAPACITOR, fixed: 11/7/39 mica; 115 mmf; 500 vdcw; case 51/64" lg max x 15/32" wd max x 7/32" d max; moulded bakelite case; two axial wire leads.	RE48A148 16C40										
-481067-B2	CAPACITOR, fixed: 11/7/39 NT-481067 w/115 mmf p/m 2%; temp coef ltr B.	RE48A148 16C40		16-C-28700-5239		R16-C-9947-39		CD CAW CSL CMR	5WLS 1468LS MOBW OXM	CRR	C56304-11501secB	RAP
-481067-B5	CAPACITOR, fixed: 11/7/39 NT-481067 w/115 mmf p/m 5%; temp coef ltr B.	RE48A148 16C40		16-C-28700-5473		R16-C-9947-39+20		CD CAW CSL CMR	5WLS 1468LS MOBW OXM	CRR	C56305-11501secC	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-378

RESTRICTED

RESTRICTED

SHEET 48 - 379

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481068	CAPACITOR, fixed: mics; 450 mmf; 500 vdcw; case 51/64" lg max x 15/32" wd max x 7/32" d max; moulded bakelite case; two axial wire leads.	11/7/39 RE48A148 JAN-C-5										
-481068-B2	CAPACITOR, fixed: NT-481068 w/450 mmf p/m 2%; temp coef ltr B.	11/7/39 RE48A148 JAN-C-5	CM20B451G	16-C-30077-7916				CAW CD CSL CMR	1468LS 5WLS MOBW OXM	CRR	C56304-4511eaB	RAP
-481069	CAPACITOR, fixed: mics; 775 mmf; 300 vdcw; case 51/64" lg max x 15/32" wd max x 7/32" d max; moulded bakelite case; two axial wire leads.	11/7/39 RE48A148 16C40										
-481069-B2	CAPACITOR, fixed: NT-481069 w/775 mmf p/m 2%; temp coef ltr B.	11/7/39 RE48A148 16C40		16-C-30580-8680				CAW CD CSL CMR	1468LS 5WLS MOBW OXM	CRR	C56304-77501eaB	RAP
-481070	CAPACITOR, fixed: mics; 1000 mmf; 300 vdcw; case 51/64" lg max x 15/32" wd max x 7/32" d max; moulded bakelite case; two axial wire leads; for replacement use NT-481657-D10.	11/7/39 RE48A148 16C40										
-481070-A10	CAPACITOR, fixed: NT-481070 w/1000 mmf p/m 10%; temp coef ltr A; for replacement use NT-481657-A10.	11/7/39 RE48A148 16C40		16-C-31090-2512				CAW CMR CD CSL	1468S 0 5WS MOW	CRV	P-770473-9rev19	
-481070-B2	CAPACITOR, fixed: NT-481070 w/1000 mmf p/m 2%; temp coef ltr B; for replacement use NT-481657-B2.	11/7/39 RE48A148 16C40		16-C-31079-9554		R16-C-10079		CAW CD CSL CMR	1468LS 5WLS MOBW-1427-2 OXM	CRR CRR	C56734-102 C56304-1021eaB	DW-2
-481070-B10	CAPACITOR, fixed: NT-481070 w/1000 mmf p/m 10%; temp coef ltr B; for replacement use NT-481657-B10. NOTE: REM-5 (2); RBS (2) thru RBS-2 (2); MK-11 Mod-1	11/7/39 RE48A148 16C40 (6).		16-C-31090-2514				CAW CMR CSL CD	1468LS OXM MOBW-1427 5WLS	CRV CCT CRR CS CRB CG	P-720592-19rev30 7608013-259 C56306-1021eaB 212222revD CD-1033-201eaC K-27362-53rev9	RAP ARJ (23) DBE RBA (2) RBA-1 (2) RBM(2) thru SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-379

RESTRICTED

RESTRICTED

SHEET 48 - 380

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481070-C10	CAPACITOR, fixed: 11/7/39 NT-481070 w/1000 mmf p/m 10%; temp coef 1tr C; for replacement use NT-481657-C10.	RE48A148 16C40		16-C-31090-2516	N16-C-10083-25			CSL CAW CD CMR	MOCW-1427 1468LST >R PO	CEM CRP	744-567 35-5086	80(20) 80-a(20) 80-13(20) 80-1(19) SEE NOTE
-481070-D10	CAPACITOR, fixed: 11/7/39 NT-481070 w/1000 mmf p/m 10%; temp coef 1tr D; for replacement use NT-481657-D10.	RE48A148 16C40		16-C-31090-2518	N16-C-10083-80	R16-C-10079-15		CD CSL CMR CAW	5RS MOSEW-1427 PO 1468XM	CRB CRV	CD-1034-201aaC P-720473-10rev19	GA(16) SA-1(13) SA-2(14) SA-3(17) SEE NOTE
-481071	CAPACITOR, fixed: 11/7/39 ceramic dielectric; 128 mmf; zero temp coef (tol p/m 30) mmf/mf/°C; 500 vdcw; case 1" lg x 17/64" diam; radial wire leads; uninsulated; add suffix indicating capacity tolerance in per cent.											
-481071-2	CAPACITOR, fixed: 11/7/39 NT-481071 w/128 mmf p/m 2%.			16-C-17254-3374		R16-C-9947-100			814	CRR	A25324-1280rev0	RAP
-481072	CAPACITOR, fixed: 11/8/39 paper dielectric; 10,000 mmf plus 10 minus 3%; 400 vdcw; HS metal can; case 1 1/16" lg x 11/16" diam; hyvol impr and filled; two axial wire leads; no int gnd connections; radial mtg strap w/two 5/32" diam holes 7/32" c to c; for replacement use NT-481079-10.	RE48A162 RE13A488						CAW	489			
-481072-10	CAPACITOR, fixed: 11/8/39 NT-481072 w/10,000 mmf p/m 10%; for replacement use NT-481079-10.	RE48A162 RE13A488		16-C-42733-6481	N16-C-11732-16			CAW	489	CNA CAW	E-369-13eub6 13413	RAS(5) RAW(5) RAS-i (5) SEE NOTE
-481073	CAPACITOR, fixed: 11/8/39 paper dielectric; 100,000 mmf plus 10 minus 3%; 400 vdcw; HS metal can; case 2 3/16" lg x 1 1/16" diam; hyvol impr and filled; two axial wire leads; no int gnd connections; radial mtg strap w/two 5/32" diam holes 7/32" c to c; for replacement use NT-481075-10.	RE48A162 RE13A488										
-481073-10	CAPACITOR, fixed: 11/8/39 NT-481073 w/100,000 mmf p/m 10%; for replacement use NT-481075-10.	RE48A162 RE13A488		16-C-45774-1927	N16-C-11299		3DA100-96	CAW CAW	489 13413	CNA	E-369-15 sub 6	RAS(9) RAW(9) RDC (7) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-380

RESTRICTED

RESTRICTED

SHEET 48 - 381

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481074	CAPACITOR, fixed: 11/8/39 paper dielectric; 250,000 mmf plus 10 minus 3%; 400 vdcw; MS metal can; case 2 3/16" lg x 1 5/16" diam; hyvol impr and filled; two axial wire leads; no int gnd connection; radial mtg strap w/two 5/32" diam holes 7/32" c to c; for replacement use NT-481076-10.	RE48A162 RE13A488										
-481074-10	CAPACITOR, fixed: 11/8/39 NT-481074 w/250,000 mmf p/m 10%; for replacement use NT-481076-10. NOTE: RAS-4; RAS-5 (2); RBJ thru RBJ-4.	RE48A162 E13A488		16-C-46344-1942				CAW	489	CNA CAW	E-369-19sub6 13413	RAS RAW AS-1 thru SEE NOTE
-481075	CAPACITOR, fixed: 11/8/39 paper dielectric; 100,000 mmf plus 10 minus 3%; 500 vdcw; MS metal can; case 2 3/16" lg x 1 3/16" diam; hyvol impr and filled; two axial wire leads; no int gnd connections; circumferential mtg strap w/two 5/32" diam holes 7/32" c to c.	RE48A162 RE13A488		16-C-45756-4651				CAW	589	CAW CAW	13413 15398	
-481075-10	CAPACITOR, fixed: 11/8/39 NT-481075 w/100,000 mmf p/m 10%. NOTE: RBJ (6) thru RBJ-4 (6); RDG (7).	RE48A162 13A488		16-C-45777-4651	N16-C-11309-34			CAW	689	CNA CGG CTE CAW CAW	E-369-17sub6 8A1039921seeA 13413 15398	RAW (6) OAY RAS(6) thru RAS-4 (6) RAS-5 (12) SEE NOTE
-481076	CAPACITOR, fixed: 11/8/39 paper dielectric; 250,000 mmf plus 10 minus 3%; 600 vdcw; MS metal can; case 2 3/16" lg x 1 5/16" diam; hyvol impr and filled; two axial wire leads; no int gnd connections; radial mtg strap w/two 5/32" diam holes 7/32" c to c, first one 15/16" from ctr of capacitor.	RE48A162 RE13A488						CAW	689	CHS CAW CAW	V12-220-4653 revo 13413 15398	
-481076-5	CAPACITOR, FIXED: 3/4/48 Navy Type 481076 w/250,000 mmf p/m 5%.			16-C-46305-4651				CAW	689	CBCM		FOA
-481076-10	CAPACITOR, fixed: 4/27/37 NT-481076 w/250,000 mmf p/m 10%. NOTE: RAD-5 (6); RBJ (3) thru RBJ-4 (3); ROB.	R 48A162 E13A488		16-C-46347-4651				CAW	689	CNA CHS CAW CAW	E-307-21sub6 V12-220-4653revo 13413 15398	RAW (3) OAY (4) RAS(3) thru RAS-4 (3) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-381

RESTRICTED

RESTRICTED

SHEET 48 - 382

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	K S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481077	CAPACITOR, fixed: 11/17/39 mica; 40 mmf; 500 vdcw, 1000v, DC test; case 1 1/16" lg x 7/16" wd x 3/16" h; molded low loss phenolic; 2 axial wire leads; term mtg; sealed for immersion.	RE48A148										
-481077-A10	CAPACITOR, fixed: 11/17/39 NT-481077 w/40 mmf p/m 10%; temp coef ltr A.	RE48A148 JAN-C-5	CM20A400K	16-C-27397-5071				CAW CD CSL CMR	1468 5M MO O	CQA	10167rev1	TBX OAB RAS-5 RAW SEE NOTE
-481077-B5	CAPACITOR, fixed: 5/7/48 Navy Type 481077 w/40 mmf p/m 5%; temp coef letter B.	RE48A148 JAN-C-5		16-C-27397-4597	N16-C-9843-49			CD CSL	5M155Q4 MOBW-1408			
-481077-B10	CAPACITOR, fixed: 11/17/39 NT-481077 w/40 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B400K	16-C-27397-5076	N16-C-9843-50			CD CAW CSL CMR	5M15 1468LS MOBW-1408-10 OXM	CRB CRV	CD-1033-6 1ssc P-720473-30rev19	
-481077-B12	CAPACITOR, fixed: 11/17/39 NT-481077 w/40 mmf p/m 12%; temp coef ltr B.	RE48A148 16C40		16-C-27401-7650								
-481077-B16	CAPACITOR, fixed: 11/17/39 NT-481077 w/40 mmf p/m 16%; temp coef ltr B.	RE48A148 16C40		16-C-27401-9650								
-481077-B20	CAPACITOR, fixed: 5/7/48 Navy Type 481077 w/40 mmf p/m 20%; temp coef letter B.	RE48A148 JAN-C-5		16-C-27401-7461	N16-C-9843-51			CD	5M			
-481077-C5	CAPACITOR, fixed: 11/17/39 NT-481077 w/40 mmf p/m 5%; temp coef ltr C.	RE48A148 JAN-C-5	CM20C400J	16-C-27392-4601				CER CAW CD CSL CMR	K 1469 5R MO5CW PO			DAE DAE-1
-481077-D3	CAPACITOR, fixed: 11/17/39 NT-481077 w/40 mmf p/m 3%; temp coef ltr D.	RE48A148 16C40		16-C-27391-5963		R16-C-9842-300		CAW CMR CER CD CSL	1469 PO M1K40 5RS MO5DW	CRV	P-720537-1 rev19	
-481077-D5	CAPACITOR, fixed: 11/17/39 NT-481077 w/40 mmf p/m 5%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D400J	16-C-27392-4606	N16-C-9843-30	R16-C-9842-305		CD CAW CSL CMR CER CMF	5RS 1469 MO5DW PO M1K40 603M	CG CG CRV CHZ CCQ	P-7761320-28 rev15 M-7463969-23 rev 3 P-720538-4rev30 CO-746 8-CO-746	TBX-4 TBX-4a TBX-5
-481077-D10	CAPACITOR, fixed: 11/17/39 NT-481077 w/40 mmf p/m 10%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D400K	16-C-27397-5086	N16-C-9843-45			CD CAW CSL CMR	5RS 1469 MO5DW PO	CG CRB	M-7463969-7rev3 CD-1034-61ssc	RBD TCX

SHEET 48-382

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 46 - 383

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481078	CAPACITOR, fixed: mica; 70 mmf; 3,000 vdcw, 6,000v DC test; case 1 3/4" lg x 15/16" wd x 15/32" h; molded bakelite case; two through holes for screw #6-32 thd 1 1/4" mtg/c.	11/17/39 RE48A112 16C40										
-481078-A10	CAPACITOR, fixed: NT-481078 w/70 mmf p/m 10%; temp coef 1tr A.	11/17/39 RE48A112 16C40		16-C-28058-3498				CD	9-64070			
-481078-B10	CAPACITOR, fixed: NT-481078 w/70 mmf p/m 10%; temp coef 1tr B. NOTE: TBL-6; TBL-7; TBL-10; TBL-11; TBL-12; TBL-13.	11/17/39 RE48A112 16C40		16-C-28058-3501	N16-C-9880			CD	9L-84070	CAT	7607470-44	TBL-5 TBL-3 SEE NOTE
-481079	CAPACITOR, fixed: paper dielectric; 10,000 mmf plus 20 minus 10%; 600 vdcw; HS metal can; case 1 11/16" lg x 11/16" diam; hyvol impr end filled; two axial wire leads; no int gnd connections; radial mtg strap w/two 5/32" diam hole 7/32" c to c.	11/20/39 RE48A162 RE13A488						CAW	689	CAW CAW COG	13413 15398 8A103987 188 B	RAW RAW
-481079-10	CAPACITOR, fixed: NT-481079 w/10,000 mmf p/m 10%.	11/20/39 RE48A162 RE13A488		16-C-42737-2595				CAW	689	CAW CAW	13413 15398	
-481079-20	CAPACITOR, fixed: NT-481079 w/10,000 mmf p/m 20%.	11/20/39 RE48A162 RE13A488		16-C-42767-7145				CAW	689			DAH (2)
-481080	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; HS metal can; 1 1/2" diam x 4 1/2" h; oil filled; two rivet lug terms, located on bottom; no int gnd connections; bushing mtg, 3/4"-16 thd 1/2" lg w/hex nut; same as NT-481054 except has two term. NOTE: RAS-2 (4); RAS-3 (4); RAS-4 (4); RAS-5 (4); RBG (5); RBG-1 (5); RBG-2 (5).	1/1/39 RE13A488 RE48A330		16-C-49937-5145				CD CAAI	TLAD-6040 68C400	CRC CRB CWA CNA	6294 CD-10991eeB 48X249	RAS (4) RAW RAO-3 (3) RAO-4 (3) RAO-5 (3) RAS-1 (4) SEE NOTE
-481080-10	CAPACITOR, fixed: NT-481080 w/4 mf p/m 10%. NOTE: RBH-1 thru RBH-3; RBJ-1 thru RBJ-4 (4); RBJ-6 (3); RBL (6); RBL-1 (6); RBL-2 (3); RBL-3 (3); RBL-5 (3); RBL-6 (3); RBL-4; RBO-1 (4); RBO-2 (4); RDG (4); RDP (6); SU (8); TDD-2 (3); TS-120/UP (2); TS-191/UP (2).	12/1/39 RE13A488 RE48A330		16-C-49958-5140	N16-C-11551		3DB4-135	CAW CIE CAAI CBV CD CSF CTD	610N2-4 7577A 68C400 7670 TLAD-6040 P8213 MAC-104	CBM CBM CRV CFF CWQ CNA CZC CPN CCI	CD-10991eeB 744-347 896205-7 T270-150 48X249 E-333-8 5070 C1180	RAW (4) MAR (10) QBG (5) QBG-1 (3) RAO-2 (3) RAO-6 (3) JAO-7 (3) RAO-9 (3) RBF (5) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-383

RESTRICTED

RESTRICTED

SHEET 48 - 384

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481081	CAPACITOR, fixed: 12/1/39 mica; 1,000 mmf; 20,000 vdcv max, 15 amp at 3,000 kc, 16 amp at 1,000 kc, 9 amp at 300 kc, 3 amp at 100 kc; case 5" diam x 4" h; ceramic case; one fl elliptical and term ea end two 3/8" diam holes in ea term 5 3/4" c to c.	RE48A116 16C40										
-481081-B5	CAPACITOR, fixed: 12/1/39 NT-481081 w/1,000 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-31088-7286	N16-C-10099-15			CD	PL-252-51	CG	P-7762810-1	TBC-2 TBC-5 (4)
-481082	CAPACITOR, variable: 12/4/39 air; plate meshing type single sect; 3 to 25 mmf; SLC; 0.0195" air gap; 7/8" lg x 15/16" wd x 1 7/32" h shaft w/bushing assembled 9/32" diam x 5/16" lg o/s; sdr adj extension type; seven rad pl brass plates; 360 deg rotation; isolantite ins; post term for stator, lug term for rotor on RH side; two mtg holes tapped for #4-36 thd screws on 21/32" mtg/c 31/64" from top.			16-C-98940-6000			3D9025V-37	CHC	APC-25			YB YC YD ARB (4) YF
-481083	CAPACITOR, fixed: 12/6/39 mica; 980 mmf; 500 vdcv, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143										
-481083-A3	CAPACITOR, fixed: 12/6/39 NT-481083 w/980 mmf p/m 3%; temp coef ltr A.	RE48A143 16C40		16-C-31058-1623				CAW CD CSL CAN	1467 1W MW C			RA3 RAW RAQ-1 (2)
-481083-A5	CAPACITOR, fixed: 12/6/39 NT-481083 w/980 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A9813	16-C-31058-9279				CAW CD CSL CMR	1467 1W MW W	CNA	D-779-51	RAQ-7 (2) RAQ-3 (2)
-481083-B5	CAPACITOR, fixed: 12/6/39 NT-481083 w/980 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B9813	16-C-31058-9284	N16-C-10092			CAW CD CSL CAN	1467L 1WL MWB CL			Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-384

RESTRICTED

RESTRICTED

SHEET 48 - 385

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E E O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481083-B20	CAPACITOR, fixed: 12/6/39 NT-481083 w/980 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B981M	16-C-31069-3244	N16-C-10083-11			CAW CD CSL CAN CMR CMF	1467L 1WL MWB CL WXM 502J			
-481083-D5	CAPACITOR, fixed: 12/6/39 T-481083 w/980 mmf p/m 5%; temp coef ltr D.	RE48A143 JA -C-5	CM30D981J	16-C-31058-9294				CAN CD CAW CSL	CRW-1398 1RS 1464 MWSBW	CMQ	47X352188B	RAO-3 (2) RAO-4 (2) RAO-5 (2)
-481083-F1	CAPACITOR, fixed: 18/2/49 Navy Type 481083 w/1200 mmf p/m 1%; temp coef ltr E.	RE48 143 JAN-C-5		16-C-31052-9377				CADV	10114	CD	IR	AN/URM-6
-481084	CAPACITOR, fixed: 12/6/39 mica; 1,200 mmf; 500 vdcw, 1,000v DC test; case 53/64" lg x 53/64" wd x 9/32" h max; molded bakelite case; two axial wire leads.	RE48A143										
-481084-A3	CAPACITOR, fixed: 12/6/39 T-481084 w/1,200 mmf p/m 3%; temp coef ltr A.	RE48A143 16C40		16-C-31269-1823				CAW CMR CD CSL CAN CMF	1467 W 1W MW C 502J			RAS RAW RAS-5 (2) RBJ RBJ-1thru RBJ-4
-481084-A10	CAPACITOR, fixed: 12/6/39 NT-481084 w/1,200 mmf p/m 10%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A122K	16-C-31274-9939	N16-C-10163-6		3K3012211	CAW CMR CD CSL CAN CMF	1467S W 1WS MW C 502J	CRW	P-720473-48rev19	
-481084-B3	CAPACITOR, fixed: 12/6/39 NT-481084 w/1200 mmf p/m 3%; temp coef ltr B.	RE48A143 16C40		16-C-31269-1828	N16-C-10159			CD CAW CSL CAN CMR CMF	1WL 1467L MWB CL WXM 502J			
-481084-B5	CAPACITOR, fixed: 12/6/39 NT-481084 w/1,200 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B122J	16-C-31269-9484	N16-C-10163-1	R16-C-10185-15		CD CAW CSL CAN CMR CMF	1WL 1467L MWB CL WXM 502J			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-385

RESTRICTED

RESTRICTED

SHEET 48-386

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	DATE	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481084-C2	CAPACITOR, fixed: NT-481084 w/1,200 mmf p/m 2%; temp coef ltr C.	12/6/39	RE48A143 JAN-C-5	CM30C122G	16-C-31264-8009	N16-C-10163-3	R 16-C-10180		CD CAW CSL CAN CMR	LRS 1464 MWCW CRW PW			
-481084-C5	CAPACITOR, fixed: NT-481084 w/1,200 mmf p/m 5%; temp coef ltr C.	12/6/39	RE48A143 JAN-C-5	CM30C122J	16-C-31269-9489		R16-C-10185-20	3K3012232	CD CAW CSL CAN CMR	LRS 1464 MWCW CRW PW	CBZ	CC-782	ECS-6
-481084-C10	CAPACITOR, fixed: NT-481084 w/1,200 mmf p/m 10%; temp coef ltr C.	12/6/39	RE48A143 JAN-C-5	CM30C122K	16-C-31274-9969		R16-C-10185-45		CD CAW CSL CAN	LRS 1464 MWCW CRW			
-481084-D1	CAPACITOR, fixed: NT-481084 w/1,200 mmf p/m 1%; temp coef ltr D.	12/6/39	RE48A143 16C40		16-C-31264-1010	N16-C-10161			CD CAW CSL CMR CAN	LRS 1464 MNSDW PW CRW	CNA	D-775	RBE-1 RBE-2 RBE-3
-481084-D2	CAPACITOR, fixed: NT-481084 w/1,200 mmf p/m 2%; temp coef ltr D.	12/6/39	RE48A143 JAN-C-5	CM30D122G	16-C-31264-8014	N16-C-10162-11	R16-C-10183		CD CAW CSL CAN CMR	LRS 1464 MNSDW CRW PW			
-481084-D5	CAPACITOR, fixed: NT-481084 w/1,200 mmf p/m 5%; temp coef ltr D.	12/6/39	RE48A143 JAN-C-5	CM30D122J	16-C-31269-9494	N16-C-10163	R16-C-10185		CAW CSL CMR CD	1464 MNSDW PW LRS	CRV	P-720533-10 rev30	ARJ SB
-481084-D10	CAPACITOR, fixed: NT-481084 w/1,200 mmf p/m 5%; temp coef ltr D.	12/6/39	RE48A143 JAN-C-5	CM30D122K	16-C-31274-9974		R16-C-10185-50		CD CAW CMR CSL	LRS 1464 PW MNSDW			
													Cont

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-386

RESTRICTED

RESTRICTED

SHEET 48 - 387

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481084-B2	CAPACITOR, fixed: NT-481084 w/1,200 mmf p/m 2%; temp coef ltr E.	12/6/39 RE48A143 JAN-C-5	CM30E122G	16-C-31264-8019	N16-C-10163-3-2	R16-C-10185-30	3K3012252	CD CAW CSL CMR CMF	LRS 1464 MASEW PW 602J			
-481084-B10	CAPACITOR, fixed: NT-481084 w/1,200 mmf p/m 10%; temp coef ltr E.	12/6/39 RE48A143 JAN-C-5	CM30E122X	16-C-31274-9979		R16-C-10185-55		CD CAW CMR CSL	LRS 1464 PW MASEW			
-481085	CAPACITOR, fixed: mica; 2600 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	12/6/39 RE48A143										
-481085-A3	CAPACITOR, fixed: NT-481085 w/2600 mmf p/m 3%; temp coef ltr A.	12/6/39 RE48A143 16C40		16-C-32060-4823				CAW CD CSL CAN	1467 1W MW C	CNA		RAS RAW RAS-5
-481085-A5	CAPACITOR, fixed: NT-481085 w/2600 mmf p/m 5%; temp coef ltr A.	12/6/39 RE48A143 JAN-C-5	CM30E262J	16-C-32061-3479			3DA2.600	CAW CD CSL CAN	1467 1W MW C	CNA	D775-27	RDG
-481085-B2	CAPACITOR, fixed: NT-481085 w/2600 mmf p/m 2%; temp coef ltr B.	12/6/39 RE48A143 JAN-C-5	CM30E262G	16-C-32056-2004	N16-C-10324-55			CD CAW CSL CAN	1WL 1467L MWB CL			
-481085-B3	CAPACITOR, fixed: NT-481085 w/2600 mmf p/m 3%; temp coef ltr B.	12/6/39 RE48A143 16C40		16-C-32060-4828				CD CAW CSL CAN	1WL 1467L MWB CL			
-481085-D1	CAPACITOR, fixed: NT-481085 w/2600 mmf/m 1%; temp coef ltr D.	12/6/39 RE48A143 16C40		16-C-32055-4010	N16-C-10324-53			CAW CD CAN CSL	1464 LRS CRW MWSW			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-387

RESTRICTED

RESTRICTED

SHEET 48 - 388

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481086	CAPACITOR, fixed: 12/6/39 mica; 5100 mmf; 300 vdcv, 600v DC test; case 53/64" lg x 53/64" wd x 11/32" d max; molded bakelite case; two axial wire leads.	RE48A143 16C40										
-481086-A3	CAPACITOR, fixed: 12/6/39 NT-481086 w/5100 mmf p/m 3%; temp coef ltr A.	RE48A143 16C40		16-C-32719-8823				CAW CMR CD	1467 W 1W or 1D			RAS RAW RAS-5
-481086-B2	CAPACITOR, fixed: 12/6/39 NT-481086 w/5100 mmf p/m 2%; temp coef ltr B.	RE48A143 16C40		16-C-32715-4563	N16-C-10431							SC-1
-481086-B5	CAPACITOR, fixed: 12/6/39 NT-481086 w/5,100 mmf p/m 5%; temp coef ltr B.	RE48A143 16C40		16-C-32720-6143	N16-C-10432			CD CMR CAW	1W1 or 1DL WXM 1467L			
-481086-B10	CAPACITOR, fixed: 12/6/39 NT-481086 w/5100; mmf p/m 10%; temp coef ltr B.	RE48A143 16C40		16-C-32725-6623				CD CAW CMR	1W1 or 1DL 1467L WXM			
-481086-B20	CAPACITOR, fixed: 12/6/39 NT-481086 w/5100 mmf p/m 20%; temp coef ltr B.	RE48A143 16C40		16-C-32730-9103				CAW CD CMR	1467L 1W1 or 1DL WXM			
-481086-C2	CAPACITOR, FIXED: 11/17/47 Navy Type 481086 w/5100 mmf p/m 2%; temp coef letter C.	JAN-C-5 CM35C512G		16-C-32715-6033								3V
-481086-C5	CAPACITOR, fixed: 12/6/39 NT-481086 w/5100 mmf p/m 5%; temp coef ltr C.	RE48A143 16C40		16-C-32720-6143		R16-C- 10430-15-500		CD CMR CAW CAW	1RS or 1DR PW 1467LST 1464			
-481087	CAPACITOR, fixed: 12/6/39 mica; 8800 mmf; 300 vdcv, 600v DC test; case 53/64" lg x 53/64" wd x 11/32" d max; molded bakelite case; two axial wire leads.	RE48A143										
-481087A3	CAPACITOR, fixed: 12/6/39 NT-481087 w/8800 mmf p/m 3%; temp coef ltr A. NOTE: RAS-1; RAS-2; RAS-3; RAS-4; RAS-5.	RE48A143 16C40		16-C-33405-7223				CAW	1467			RAS RAW SEE NOTE
-481087-B3	CAPACITOR, fixed: 12/6/39 NT-481087 w/8800 mmf p/m 3%; temp coef ltr B.	RE48A143 16C40		16-C-33405-7228	N16-C-10482			CAW CD CMR	1467L 1W1 or 1DL WXM			
-481087-B5	CAPACITOR, fixed: 12/6/39 NT-481087 w/8800 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5		16-C-33404-6542	N16-C-10482-7			CAW CD CMR	1467L 1W1 or 1DL WXM			
-481087-B10	CAPACITOR, fixed: 12/6/39 NT-481087 w/8800 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5		16-C-33411-5022	N16-C-10482-9			CAW CD CMR	1467L 1W1 or 1DL WXM	CFT	K-895560-4rev0	YL

SHEET 48-388

RESTRICTED.

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 389

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481088	CAPACITOR, fixed: 12/12/39 mica: 1500 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" max; molded bakelite case; two axial wire leads.	RE48A143 JAN-C-5										
-481088-A5	CAPACITOR, fixed: 12/12/39 N-481088 w/1500 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A152J	16-C-31507-4079			3K3015212	CD CMR CAW CSL	1W5 W 1467S MWW			TCD
-481088-A10	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 10%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A152K	16-C-31512-4559	R16-C-10179-35	R16-C-10212-2	3K3015211	CD CMR CAW CSL	1W5 W 1467S MWW	CRV	P-720473-44 rev19	
-481088-A20	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 20%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A152M	16-C-31517-7039		R16-C-10212-3	3K30 15214	CD CAW CSL CMR	1W 1467 MWW W			
-481088-B2	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 2%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B152B	16-C-31502-2604				CAW CSL	1467LS MWW	CAY	T-7610984-23	VR VB-1
-481088-B5	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 5%; temp coef ltr B. NOTE: RBC-2; SU; SU-1; AN/UPM-1 (2); AN/UPM-1B (2).	RE48A143 JAN-C-5	CM30B152J	16-C-31507-4084	N16-C-10179-1	R16-C-10211-10	3K30 15222	CD CMF CSL CAW CMR CD	1W5D15 502J MWW-1229-5 1467 or 1467L WXM 14LS	CRM CHZ CG CRV	744-562 CO-1117 iss0 P-7762455-52 rev7 P-720538-44rev30	RAR (2) RBB RBB-1 RBB-2 RBC RBC-1 SEE NOTE
-481088-B10	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 10%; temp coef ltr B. NOTE: YG-1; YG-2.	RE48A143 JAN-C-5	CM30B152K	16-C-31512-4564	N16-C-10179-3 N16-C-10179-36	R16-C-10212-2-200	3K30 15221	CD CAW CSL CMF CAM CMR	1WLS 1467LS MWW 502J C WXM	CRM CRV COL CG CAY CAY CWS	744-598 P-720473-36 rev19 909 2153 20rev1 P-7762455-21 rev7 T-7610894-23 T-7610947-33 560507	AYD (4) AYD-2 (4) AYD-3 (4) RAR SR (2) SR-5 (2) SU SU-1 TDC (2) SEE NOTE Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-389

RESTRICTED

RESTRICTED

SHEET 48 - 390

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481088-B20	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B152M	16-C-31517-7044	N16-C-10179-4	R16-C-10212-4	3K3015224	CD CAW CSL CMR CMF	1464 1467LS MWBW WXM 502J			
-481088-C2	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 2%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C152G	16-C-31502-2609		R16-C-10208-800	3K3015233	CSL CD CAW CMF CMR	MWBCW LRS 1464 602J PW			
-481088-C5	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 5%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C152J	16-C-31507-4089	N16-C-10179-1	R16-C-10211-100	3K3015232	CSL CD CAW CMR CAN	MWBCW LRS 1464 PW CRW			
-481088-C10	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 10%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C152K	16-C-31512-4569		R16-C-10212	3K3015231	CSL CD CAW CMR CAN	MWBCW LRS 1464 PW CRW			
-481088-C20	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 20%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C152M	16-C-31517-7049		R16-C-10212-50	3K3015234	CD CAW CSL	LRS 1464 MWBCW			
-481088-D2	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 2%; temp coef ltr B.	RE48A143 JAN-C-5	CM30D152G	16-C-31502-2614		R16-C-10210	3K3015243	CD CAW CSL CMF CMR CAN	LRS 1464 MWBCW 602J PW CRW			
-481088-D5	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 5%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D152J	16-C-31507-4094	N16-C-10179	R16-C-10211-200	3K3015242	CD CAW CSL CMF CMR CAN	LRS 1464 MWBCW 602J PW CRW			MX-16 (1; Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-390

RESTRICTED

RESTRICTED

SHEET 48 - 391

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481088-D10	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 10%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D152K	16-C-31512-4574		R16-C-10212-2-350	3K3015241	CAW CSL CD	1464 MWSDW 1RS	CRV	P-720592-8 rev30	SD SD-A SD-1 SD-2
-481088-D20	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 20%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D152M	16-C-31517-7054	N16-C-10179-12	R16-C-10212-100		CD CSL CAW	1RS MWSDW 1464			
-481088-E2	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 2%; temp coef ltr E	RE48A143 JAN-C-5	CM30E152G	16-C-31502-2619		R16-C-10210-50	3K3015253	CD CAW CSL CMF CMR	1RS 1464 MWSEW 602J FW			
-481088-E5	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 5%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E152J	16-C-31507-4099		R16-C-10211-300	3K3015252	CD CAW CSL CMF CMR	1RS 1464 MWSEW 602J FW			
-481088-E10	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 10%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E152K	16-C-31512-4579		R16-C-10212-2-450		CD CAW CSL	1RS 1464 MWSEW			
-481088-E20	CAPACITOR, fixed: 12/12/39 NT-481088 w/1500 mmf p/m 20%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E152M	16-C-31517-7059		R16-C-10212-150		CAW CD CSL	1464 1RS MWSEW			
-481089	CAPACITOR, fixed: 12/12/39 mica; 2500 mmf; 500 vdcw, 1000vDC test; case 53/64" lg x 53/64" wd x 9/32" h; molded bakelite case; two axial wire leads.	RE48A143										
-481089-A2	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 2%; temp coef ltr A.	RE48A143 16C40		16-C-32003-4199				CAW	C-1225-2	CRP	35-5040	TCD SG-1 SG-28
-481089-A5	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A252J	16-C-32008-5679				CAW CD CSL CMR	1467 1W MW W	CRP CZE	35-5143 525-177	OBJ RBE (2) SO-2 SO-7M SO-7N Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-391

RESTRICTED

RESTRICTED

SHEET 48 - 392

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFG	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481089-A10	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 10%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A252K	16-C-32013-6159				CAN CD CSL CMR CAN	1467 1W MW W C-1225-10	CNA	D-775	RBL RBL-1 RBL-2 RBL-5 RBL-6 SEE NOTE
	NOTE: SO; SO-A; SO-3; SO-13; ME-8; ME-8 Mod 1.											
-481089-B2	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 2%; temp coef ltr B.	RE48A143 16C40		16-C-32003-4204	N16-C-10301			CD CAW CSL CAN CMR	1WLS 1467L MWBW CLS WXM	CBM	744-739	WEA (2)
-481089-B3	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 3%; temp coef ltr B.	RE48A143 16C40		16-C-32007-7023		R16-C-10313-65		CD CAW CSL CMF CMR	1WL 1467L MWBW 502J WXM			
-481089-B5	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B252J	16-C-32008-5684	N16-C-13003-16	R16-C-10313-63		CD CAW CSL CMR CMF CAN	1WLS 1467L MW WXM 502J CLW	CBM CG CG CAY	744-739 P-7762455-54rev7 M-7463931-20 T-761047-5	RAR (4) SR SR-5
-481089-B10	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B252K	16-C-32013-6164	N16-C-10304	R16-C-10313-70	3DA2.500-4.1	CD CAN CSL CAW CMR	1WLS CLS MWB 1467L WXM	COL CRV CG CWQ CFE	909 2253 52rev2 P-720473-49rev19 P-7762455-23rev7 47X347 270-164	DAB (6) DAB-1 (6) DAB-3 (6) QBC (2) QBC-1 (2) SEE NOTE
-481089-B20	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B252M	16-C-32018-8644	N16-C-10305-1	R16-C-10313-100		CD CAW CSL CMR CMF	1WL 1467L MWBW WXM 502J			
-481089-C2	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 2%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C252C	16-C-32003-4209								Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-392

RESTRICTED

RESTRICTED

SHEET 48 - 393

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481089-C10	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 10%; temp coef 1tr C.	RE48A143 JAN-C-5	CM30C252K	16-C-32013-6169				CD CAW CSL CMF CAN	1RS 1464 MNSCW 602J CRW			
-481089-C20	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 20%; temp coef 1tr C.	RE48A143 JAN-C-5	CM30C252M	16-C-32018-8649	N16-C-10300-14	R16-C-10313-100		CD CAW CSL	1RS 1464 MNSCW			
-481089-D1	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 1%; temp coef 1tr D.	RE48A143 16040		16-C-32002-6210				CD CAW CSL CMF CMR	1RLS 1464 MNSDW 602J PW	CBM	744-812alt0	
-481089-D2	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 2%; temp coef 1tr D.	RE48A143 JAN-C-5	CM30D252G	16-C-32003-4214	N16-C-10302			CD CAW CSL CMR CMF	1RS 1464 MNSDW PW 602J			
-481089-D10	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 10%; temp coef 1tr D.	RE48A143 JAN-C-5	CM30D252K	16-C-32013-6174	N16-C-10305	R16-C-10313-85		CD CAW CSL CMF CMR CAN	1RS 1464 MNSDW 602J PW CRW	CDL CPK	B-8F-6691revE 20019	QBD
-481089-D20	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 20%; temp coef 1tr D.	RE48A143 JAN-C-5	CM30D252M	16-C-32018-8654				CD CAW CSL	1RS 1464 MNSDW			
-481089-E20	CAPACITOR, fixed: 12/12/39 NT-481089 w/2500 mmf p/m 20%; temp coef 1tr E.	RE48A143 JAN-C-5	CM30E252M	16-C-32018-8659				CD CAW CSL CMF CMR	1RS 1464 MNSDW 602J PW	COL	912 2251 54rev1	TCZ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-393

RESTRICTED

RESTRICTED

SHEET 48 - 394

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTORS DWG OR PART NO	EQUIPMENT USED IN
-481090	CAPACITOR, fixed: 12/12/39 mica; 60,000 mmf; 600 vdcw, 1000v DC test; case 1 25/32" lg max x 1 11/32" wd max x 3/4" h; molded bakelite case; two #6-32 tapped holes 1 1/4" c to c for term and mtg.	RE48A112 JAN-C-5										
-481090-A10	CAPACITOR, fixed: 12/12/39 NT-481090 w/60,000 mmf p/m 10%; temp coef 1tr A.	RE48A112 JAN-C-5	CM60A603K	16-C-35390-2251				CD	9-11060			
-481090-B2	CAPACITOR, fixed: 12/12/39 NT-481090 w/60,000 mmf p/m 2%; temp coef 1tr B; RSW immersion.	RE48A112 JAN-C-5	CM60B603G	16-C-35379-9296				CD	9LS-11060	CG	P-7761560-28 rev20	TCD
-481091	CAPACITOR, fixed: 12/12/39 paper dielectric; 50,000 mmf plus 10 minus 3%; 1,000 vdcw; HS metal can; 1 5/16" lg x 11/16" wd x 1 5/16" h; pyranol oil impr and filled; two solder lug term on top 5/8" c to c; no int gnd connections; two mtg bkt on bottom both sides ea w/one 5/32" slot. 1 15/16" c to c. NOTE: QCC-3; QCQ (2); QCQ-1 (3); QCR (2); QCR-1 (3); QCS (3); QCS-1; QCT (3); QCT-1; SA-2; SA-3; SU; SU-1; TCD (4).	RE48A160 RE13A488		16-C-44239-5972	N16-C-11174-3			CG	9CE6A1	CG CRV CBM CBM CG	P-7763475-9rev3 P-721478-9 X-7875547-1rev1 744-656 X-8396301	QCJ-8 (2) QCJ-9 QCL-8 (2) QCN-2 (2) QCN-4 (2) QCO-1 (2) SEE NOTE
-481092	CAPACITOR, fixed: 12/12/39 paper dielectric; 200,000 mmf plus 10 minus 3%; 600 vdcw, 1200v DC test; HS metal can; case 1 5/16" lg x 11/16" wd x 1 5/16" h; pyranol oil impr and filled; two solder lug term on top 5/8" c to c; no int gnd connections; two mtg bkt on bottom ea side, ea with 5/8" slot 1 15/16" c to c.	RE48A160 RE13A488		16-C-46136-1053	N16-C-11340-14			CG	26E290	CG	X-7875547-10rev1	TCD RAR
-481093	CAPACITOR, fixed: 12/12/39 paper dielectric; 2 mf plus 10 minus 3%; 400 vdcw, 800v DC test; oval HS metal can; case 2 1/16" lg x 1" wd x 2 9/16" h o/s; oil impr and filled; two solder lug term 1/2" h located on top; spaced 5/8" c to c; no int gnd connections.	RE48A208 RE13A488		16-C-49173-1433				CG	25F152	CG	X-6822846-1rev0	TCD RAR
-481094	CAPACITOR, fixed: 12/12/39 paper dielectric; 4 mf plus 10 minus 3%; 400 vdcw, 800v DC test; oval HS metal can; case 2 1/16" lg x 1" wd x 4 9/16" h o/s; oil impr and filled; two solder lug term 1/2" h located on top, spaced 5/8" c to c; no int gnd connections.	RE48A208 RE13A488		16-C-49933-1433								TCD RAR
-481094-10	CAPACITOR, fixed: 12/12/39 NT-481094 w/4 mf p/m 10%.	RE48A208 RE13A488		16-C-49953-8877	N16-C-11545-7			CG	25F153	CRP CG	35-5062 X-6822846-2rev2	SG-1(2) SG-2S(2)

SHEET 48-394

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 395

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFCR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481095	CAPACITOR, fixed: 12/12/39 electrolytic; 25 mfd; 25 vdcw; working temp range minus 20°C to plus 65°C; case 1 3/4" lg x 1 7/16" diam; HS metal case; one solder lug term 1" h on top; neg term gnd int; mtg clamp one 5/32" diam hole and one 5/32" x 7/32" slot at bottom on 1 13/16" mtg/c. NOTE: TCK-1 (3) thru TCK-7 (3).	RE13A549 RE48A343		16-C-19781-5506	N16-C-9679-7			CD	MA-12C58-PE	CG	K-7875699-1 Rev 0	TCD TCB-2 TCJ (2) TCJ-1 (2) TCJ-2 (3) TCK (3) SEE NOTE
-481096	CAPACITOR, fixed: 12/13/39 mica; 350 mfd; 500 vdcw, 1000v DC test; case 3/4" lg x 3/4" wd x 9/32" d max; moulded bakelite case; two axial wire leads.	RE48A143										
-481096-A3	CAPACITOR, fixed: 12/13/39 WT-481096 w/350 mfd p/m 3%; temp coef ltr A.	RE48A143 16C40		16-C-29791-9423				CAW CD CSL CAN CMR CMF	1467 1W MW C W 502J			RAW RBJ thru RBJ-4
-481096-B5	CAPACITOR, fixed: 12/13/39 NT-481096 w/350 mfd p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B351J	16-C-29792-8084				CD	1W1S	CEM	744-557	WEB(8)
-481096-D 2 1/2	CAPACITOR, FIXED: 11/4/47 Navy Type 481096 w/350 mfd p/m 2 1/2%; temp coef letter D.	RE48A143 RE48A154		16-C-29791-9090				CZC	5085			HBO
-481097	CAPACITOR, fixed: 12/13/39 mica; 550 mfd; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; moulded bakelite case; two axial wire leads.	RE48A143 16C40										
-481097-B3	CAPACITOR, fixed: 12/13/39 NT-481097 w/550 mfd p/m 3%; temp coef ltr B.	RE48A143 16C40		16-C-30266-7623				CAW CD CSL CAN	1467 1W MW C			RAW RBJ thru RBJ-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-395

RESTRICTED

RESTRICTED

SHEET 48 - 396

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A R O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481098	CAPACITOR, fixed: 12/13/39 mica; 900 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; moulded bakelite case; two axial wire leads.	RE48A143										
-481098-A3	CAPACITOR, fixed: 12/13/39 NT-481098 w/900 mmf p/m 3%; temp coef ltr A.	RE48A143 16C40		16-C-30899-8323				CAW CD CSL CAN CMR	1467 1W MW C W			RAW RBJ thru RBJ-4
-481098-A10	CAPACITOR, fixed: 12/13/39 NT-481098 w/900 mmf p/m 10%; temp coef ltr A. NOTE: RBL-3 (3); RBL-5 (3); RBL-6 (3).	RE48A143 JAN-C-5	CM30A901K	16-C-30905-7359				CAW	1467	CNA	D-775	RBL(3) RBL-2(3) SEE NOTE
-481098-B10	CAPACITOR, fixed: 12/13/39 NT-481098 w/900 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B901K	16-C-30905-7364	N16-C-10079		3D9900-9	CD CAW CSL CAN CMF CMR	1WL 1467L MWB CL 502J WXM			RBL-3(3)
-481098-B20	CAPACITOR, fixed: 12/13/39 NT-481098 w/900 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B901M	16-C-30910-9844	N16-C-10078-12			CD CAW CSL CMF CAN CMR	1WL 1467L MWB 502J CL WXM			
-481098-C10	CAPACITOR, fixed: 12/13/39 NT-481098 w/900 mmf p/m 10%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C901K	16-C-30905-7369				CAW CD CSL CMR	1464 1RS MWCW PW			
-481098-D3	CAPACITOR, fixed: 12/13/39 NT-481098 w/900 mmf p/m 3%; temp coef ltr D.	RE48A143 16C40		16-C-30899-8338		R16-C-10077-55		CAW	1464T	CRV	P-721-1-27rev27	ARB
-481098-D10	CAPACITOR, fixed: 12/13/39 NT-481098 w/900 mmf p/m 10%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D901K	16-C-30905-7374	N16-C-10078			CD CAW CSL CMR	1R 1464 MWSW PW			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-396

RESTRICTED

RESTRICTED

SHEET 48 - 397

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CMR TRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481099	CAPACITOR, fixed: 12/13/39 mica; 950 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; moulded bakelite case; two axial wire leads.	RE48A143 16C40										
-481099-A3	CAPACITOR, fixed: 12/13/39 NT-481099 w/950 mmf p/m 3%; temp coef ltr A.	RE48A143 16C40		16-C-31023-8469				CAW	1467			RAW RBJ RBJ-3 RBJ-4
-481099-B3	CAPACITOR, fixed: 12/13/39 NT-481099 w/950 mmf p/m 3%; temp coef ltr B.	RE48A143 16C40		16-C-31023-8474				CAW CD CSL CMR	1467 1W MW W			
-481099-D3	CAPACITOR, fixed: 5/4/49 Navy Type 481099 w/950 mmf 1/m 3%; temp coef letter D.	RE48A143 16C40		16-C-31023-8484				CAW	1467			RAW
-481099-D5	CAPACITOR, fixed: 2/24/50 Navy Type 481099 w/950 mmf p/m 5%; temp coef letter D.	RE48A143 16C40		16-C-31023-8900	R16-C-10001-14			CAW	1464			
-481100	CAPACITOR, fixed: 12/13/39 mica; 1700 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; moulded bakelite case; two axial wire leads.	RE48A143 16C40										
-481100-B2	CAPACITOR, fixed: 12/13/39 NT-481100 w/1700 mmf p/m 2%; temp coef ltr B.	RE48A143 16C40		16-C-31631-3853		R16-C-10229		CAW CD CSL CMR	1467 1W MW W			
-481100-B3	CAPACITOR, fixed: 12/13/39 NT-481100 w/1700 mmf p/m 3%; temp coef ltr B.	RE48A143 16C40		16-C-31631-3888				CAW CD CSL CMR	1467 1W MW W	CRA		RAW RBJ RBJ-3 RBJ-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-397

RESTRICTED

RESTRICTED

SHEET 48 - 398

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481101	CAPACITOR, fixed: 12/13/39 mica; 3100 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; moulded bakelite case; two axial wire leads.	RE48A143										
-481101-A3	CAPACITOR, fixed: 12/13/39 NT-481101 w/3100 mmf p/m 3%; temp coef ltr A.	RE48A143 16040		16-C-32218-7223				CAW CD CSL CMR	1467 1W MW W			RAW RAO-1 RBJ RBJ-3 RBJ-4
-481101-A5	CAPACITOR, fixed: 12/13/39 NT-481101 w/3100 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM3CA312J	16-C-32219-5879			3DA3.100-1	CAW CD CSL CMR	1467 1W MW W	CNA	D-775-23	RAO-7 RAO-9
-481101-B5	CAPACITOR, fixed: 12/13/39 NT-481101 w/3100 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM3CB312J	16-C-32219-5884	N16-C-10342			CD CAW CSL CAN CMF CMR	1W 1467 MW C 502J W			
-481101-B10	CAPACITOR, fixed: 12/13/39 NT-481101 w/3100 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM3OB312K	16-C-32224-5364	N16-C-10341-100			CD CAW CSL CMR CMF	1WL 1467L MWB WXM 502J			
-481101-B20	CAPACITOR, fixed: 12/13/39 NT-481101 w/3100 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM3OB312M	16-C-32229-8844	N16-C-10341-105			CD CAW CSL CAN CMR CMF	1WL 1467L MWB CL WXM 502J			
-481101-C5	CAPACITOR, fixed: 12/13/39 NT-481101 w/3100 mmf p/m 5%; temp coef ltr C.	RE48A143 JAN-C-5	CM3CC312J	16-C-32219-5889				CD CAW CSL CAN CMR CMF	1RS 1464 MWSW CRW PW 502J			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-398

RESTRICTED

RESTRICTED

SHEET 48 - 399

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481102	CAPACITOR, fixed: 12/18/39 mica; 65,000 mmf; 1800 vdcw max, 13 amp at 3,000 kc, 15 amp at 1,000 kc, 12 amp at 300 kc, 7 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; moulded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c; same as NT-48725 except for voltage rating.	RE48A131 16C40										
-481102-A5	CAPACITOR, fixed: 12/18/39 NT-481102 w/65,000 mmf p/m 5%; temp coef ltr A.	RE48A131 16C40		16-C-35544-2650				CD	PL-865A-6			
-481102-B5	CAPACITOR, fixed: 12/18/39 NT-481102 w/65,000 mmf p/m 5%; temp coef ltr B. NOTE: TBL-3; TBL-6; TBL-7; TBL-10 thru TBL-13.	RE48A131 16C40		16-C-35544-2655	N16-C-10597-100			CD	PL-865A-6L	CAY	7607470-41	TBL-5 TBL-2 SEE NOTE
-481103	CAPACITOR, fixed: 12/18/39 paper dielectric; 4 mf plus 10 minus 3%; 100 vdcw; HS metal can; case 1 7/8" lg x 1" wd x 2 11/16" h o/a; pyranol imp and filled; two screw type term 3/8" h located on top 13/16" c to c; no int gnd connections; two mtg fl 7/8" wd on side of case, ea w/two 0.213" diam mtg holes 13/32" apart 2 3/8" c to c.	RE48A158 RE13A488		16-C-49927-9205				CG	25F41	CG	K-7875545-1rev2	TCD(4) RAR
-481104	CAPACITOR, fixed: 12/22/39 CANCELLED: for replacement use NT-481635.							CBN	813	CG	P-7762396-3rev2	RAR
-481105	CAPACITOR, fixed: 12/27/39 mica; 200 mmf; 5,000 vdcw max, 3.5 amp at 3,000 kc, 2 amp at 1,000 kc, 0.7 amp at 300 kc, 0.25 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; moulded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c; for replacement use NT-48750.	RE48A131 16C40										
-481105-A2	CAPACITOR, fixed: 12/27/39 NT-481105 w/200 mmf p/m 2%; temp coef ltr A.	RE48A131 16C40		16-C-29262-1638	N16-C-9971			CD	PL-307-6	COL	T-7606408-22	TCB-2
-481105-B2	CAPACITOR, FIXED: 3/23/49 Navy Type 481105 w/200 mmf p/m 2%; temp coef letter B.	RE48A131C		16-C-29262-1643				CAY	T-7606408P22			TBW-1
-481105-B5	CAPACITOR, fixed: 12/27/39 NT-481105 w/200 mmf p/m 5%; temp coef ltr B. NOTE: TBK-10; TBK-12; TBK-14; TBK-17; TBK-19; TBL-8; TBL-9.	RE48A131 16C40		16-C-29267-3121	N16-C-9971-7			CRV CAW	UC-3115case351 1550-L-165	CRV CRR	K-860215-30rev6 A26200-3	TBK-8 TAJ-8 SEE NOTE
-481105-C5	CAPACITOR, FIXED: 3/12/48 Navy Type 481105 w/200 mmf p/m 5%; temp coef letter C. NOTE: TCM, TCM-1, TCU, TCU-1, TCU-2.	RE13A389 RE48A131		16-C-29267-3128				CD	PL-307-61ST	CG	P-7761566-P17	TCM TCM-1 TCM-2 SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-399

RESTRICTED

RESTRICTED

SHEET 48-400

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481106	CAPACITOR, fixed: 12/27/39 mica; 7000 mmf; 300 vdcw, 600v DC test; case 53/64" lg x 53/64" wd x 11/32" d max dmmen; molded bakelite case; two axial wire leads.	RE48A143										
-481106-A10	CAPACITOR, fixed: 12/27/39 NF-481106 w/7,000 mmf p/m 10%; temp coef ltr A.	RE48A143 JAN-C-5	CM35A702K	16-C-33121-3617				CSL CMR	MW W	CNA	D-775-95	RAO-2 RAO-6 RAO-7 RAO-9
-481106-B5	CAPACITOR, fixed: 12/27/39 NF-481106 w/7,000 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM35B702J	16-C-33116-3142	N16-C-10454-100			CD CAW CSL CAN CMP CMR	1WLS 1467L MWBW CL 502J WXM	CG	P-7762455-59rev7	TCD
-481106-B10	CAPACITOR, fixed: 12/27/39 NF-481106 w/7,000 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM35B702K	16-C-33121-3622	N16-C-10455 N16-C-10455-8			CAN CD CAW CSL CMR	CL 1D 1467L MWB WXM	CWQ CNA	47X3481aeB P-7762455-28rev7 D-775	RAO-3 RAO-4 RAO-5 RBB-1 RBB-2 RBB-3
-481106-B20	CAPACITOR, fixed: 12/27/39 N-481106 w/7,000 mmf p/m 20%; temp coef ltr B.	RE48A143 JAN-C-5	CM35B702M	16-C-33126-6102	N16-C-10454-85			CD CSL CAN	1D MWBW CLW			
-481107	CAPACITOR, fixed: 12/28/39 ceramic dielectric; 5 mmf; zero temp coef (tol p/m 30) mmf/mfd/°C; 500 vdcw; case 13/32" lg x 9/64" diam; radial wire leads; uninsulated; retrace to within 0.2% of original cap; add suffix indicating capacity tolerance in per cent.											
-481107-5	CAPACITOR, fixed: 12/28/39 NF-481107 w/5 mmf p/m 5%.			16-C-15624-3570				CEN	813	CG	P-7762396-2rev2	TCD RAR
-481108	CAPACITOR, fixed: 2/28/39 ceramic dielectric; 50 mmf; neg temp coef 100 (tol p/m 15) mmf/mfd/°C; 500 vdcw; case 13/32" lg x 9/64" diam; radial wire leads; uninsulated; retrace to within 0.2% of original cap; add suffix indicating capacity tolerance in per cent.											
-481108-5	CAPACITOR, fixed: 2/28/39 NF-481108 w/50 mmf p/m 5%.			16-C-16562-8548				CEN	813	CG	E-7875518-1rev0	TCD (4)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-400

RESTRICTED

RESTRICTED

SHEET 48 - 401

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTORS DWG OR PART NO	EQUIPMENT USED IN
-481109	CAPACITOR, fixed: 12/28/39 ceramic dielectric; 50 mmf; neg temp coef 200 (tol p/m 30)mmf/mfd/°C; 500 vdcw; case 13/32" lg x 9/64" diam; radial wire leads; uninsulated; retrace to within 0.2% of original cap; add suffix indicating capacity tolerance in per cent.											
-481109-5	CAPACITOR, fixed: 12/28/39 NT-481109 w/50 mmf p/m 5%.			16-C-16563-4283				CBN	813	CG	K-7875518-2rev0	TCD
-481110	CAPACITOR, fixed: 12/28/39 ceramic dielectric; 50 mmf; neg temp coef 250 (tol p/m 37.5)mmf/mfd/°C; 500 vdcw; case 0.46" lg x 0.24" diam; radial wire leads; uninsulated; retrace to within 0.2% of original cap; add suffix indicating capacity tolerance in per cent.											
-481110-2	CAPACITOR, fixed: 12/28/39 NT-481110 w/50 mmf v/m 2%.			16-C-16556-7820	N16-C-8143-4	R16-C-7857		CBN	813	COL	913 0011 00	
-481110-5	CAPACITOR, fixed: 12/28/39 NT-481110 w/50 mmf p/m 5%.			16-C-16563-7962				CBN	813	CG	K-7875518-3rev0	TCD
-481111	CAPACITOR, fixed: 12/28/39 ceramic dielectric; 100 mmf; neg temp coef 700 (tol p/m 105) mmf/mfd/°C; 500 vdcw; case 0.406" lg x 0.141" OD; radial wire leads; uninsulated; retrace to within 0.2% of original cap; add suffix indicating capacity tolerance in per cent.											
-481111-5	CAPACITOR, fixed: 12/28/39 NT-481111 w/100 mmf p/m 5%.			16-C-17076-8008				CBN	813	CG	P-7762396-1rev1	TCD BAR (4)
-481112	CAPACITOR, fixed: 12/28/39 ceramic dielectric; 270 mmf; neg temp coef 750 (tol p/m 112.5)mmf/mf/°C; 500 vdcw; case 15/16" lg x 0.285" diam; two axial ribbon term ea 1 1/2" lg x 3/16" wd x 0.01" thk; uninsulated; retrace to within 1% of original cap; add suffix indicating capacity tolerance in per cent.											
-481112-10	CAPACITOR, fixed: 12/28/39 NT-481112 w/270 mmf p/m 10%.			16-C-17822-5460				CBN	2424B	CG	K-7875519-1rev1	TCD (3)
-481113	CAPACITOR, fixed: 12/28/39 ceramic dielectric; 500 mmf; negative temp coef 750 (tol p/m 112.5) mmf/mf/°C; 500 vdcw; case 1 3/8" lg x 0.4 " diam; two axial ribbon leads ea 1 1/2" lg x 3/16" wd x 0.01" thk; ceramic ins; add suffix indicating capacity tolerance in per cent.											
-481113-10	CAPACITOR, fixed: 12/28/39 NT-481113 w/500 mmf p/m 10%.			16-C-18206-5526				CBN	2424A	CG	K-7875520-1rev1	TCD (6)
-481113-20	CAPACITOR, FIXED: 2/19/48 Navy Type 481113 w/500 mmf p/m 20%.			16-C-18211-7009				CBN	2424-A			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-401

RESTRICTED

RESTRICTED

SHEET 48 - 402

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481114	CAPACITOR, fixed: 12/28/39 ceramic dielectric; 50.1 mmf; negative temp coef 25 (tol p/m 8.75) mmf/mf/°C; 500 vdcw; case 1 1/4" lg x 1/2" wd x 5/16" max thk; axial wire leads; ceramic ins; retrace to within 0.01% of original cap; add suffix indicating capacity tolerance in per cent.											
-481114-1	CAPACITOR, fixed: 12/28/39 NT-481114 w/50.1 mmf p/m 1%.			16-C-16581-2898				CER	CA	CG	K-7875927rev0	TCD
-481115	CAPACITOR, fixed: 12/28/39 ceramic capacitor; 50.6 mmf; negative temp coef 47 (tol p/m 16.45) mmf/mf/°C; 500 vdcw; case 1 1/4" lg x 1/2" wd x 5/16" max thk; axial wire leads; ceramic ins; retrace to within 0.01% of original cap; add suffix indicating capacity tolerance in per cent.											
-481115-1	CAPACITOR, fixed: 12/28/38 NT-481115 w/50.6 mmf p/m 1%.			16-C-62435-4683				CER	CA	CG	K-7875926rev0	TCD
-481116	CAPACITOR, fixed: 1/6/40 electrolytic; 2 sect; 160/160 mf; 150/150 vdcw; working temp range minus 20°C to plus 65°C; case 5 3/4" lg x 3 3/8" wd x 5 1/8" h; BS metal case; four solder lug term 7/16" h on top; term ins from can; two mtg fl on top, two 0.204" diam holes in ea on 6 1/4" x 2 7/8" mtg/c.	RE13A549 RE48A344		16-C-22251-9242	N16-C-9697			CRP CRP	S-30174-1 DU35-62	OSM	571-306a1to	WAA RMA RMA-2
-481117	CAPACITOR, fixed: 1/8/40 paper dielectric; 6 mf plus 10 minus 3%; 1000 vdcw, 2000v DC test; BS metal can; case 3 3/4" lg x 1 1/4" wd x 4 3/4" h; oil impr and filled; two por ins screw type term 7/8" h located on top, spaced 2" c to c; no int gnd connections; strap mtg not supplied.	RE48A139 RE13A488		16-C-50700-2442				CD CAW	T-10060 1009MB	CDE		YB YC YD YF
-481118	CAPACITOR, fixed: 1/8/40 paper dielectric; 4 mf plus 10 minus 3%; 2000 vdcw; BS metal can; case 3 3/4" lg x 2 1/4" wd x 3 13/16" h; pyranol impr and filled; two por ins screw type term 1 1/4" h located on top, spaced 2" c to c; no int gnd connections; strap mtg not supplied. NOTE: TAJ-15 (3); TAJ-16; TAJ-17 (3) thru TAJ-19 (3); TAJ-2; YB-2.	RE48A139 RE13A488		16-C-49943-5913	N16-C-11575			CD CG CAW	T-20040 23F119 2009MB	CG CDE	P-7763477-3 rev 1 2376-1	YB YC YD TAJ-11 (3) TAJ-13 (3) TAJ-14 (3) SEE NOTE
-481118-10	CAPACITOR, fixed: 1/8/40 NT-481118 w/4 mf p/m 10%.	RE48A139		16-C-49964-5933				CD CAW CG	T-20040 2009MB 23F119	CRR	L-74955-6revJ	

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-402

RESTRICTED

RESTRICTED

SHEET 48 - 403

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481119	CAPACITOR, fixed: 1/22/40 ceramic dielectric; 20 mmf; neg temp coef 2500 (tol p/m 375) mmf/mfd/°C; 500 vdcw; case 0.46" lg x 0.24" OD; radial wire leads; uninsulated; retrace to within 0.2% of original cap; add suffix indicating capacity tolerance in per cent.											
-481119-5	CAPACITOR, fixed: 1/22/40 NT-481119 w/20 mmf p/m 5%.			16-C-16085-3351				CBN	813	CG	F-7762396-4rev3	TCD
-481120	CAPACITOR, fixed: 1/29/40 ceramic dielectric; 150 mmf; zero temp coef (tol p/m 30) mmf/mf/°C; 500 vdcw; case 1" lg x 17/64" diam; radial wire leads; unins; retrace to within 0.2% of original cap; add suffix indicating capacity tolerance in per cent.											
-481120-2	CAPACITOR, fixed: 1/29/40 NT-481120 w/150 mmf p/m 2%.			16-C-17387-8294				CBN	814	CCR	A-25324-151revB	RAP
-481121	CAPACITOR, FIXED: 2/5/40 mica dielectric; 10 mmf; 600 vdcw, 1000v, DC test; case 1 1/4" lg x 1 1/8" wd x 23/64" d; molded low loss bakelite body; 2 axial tab term; 2 mtg holes, 1 ea side 3/16" diam x 1 5/16" mtg/c.	RE48A221 16C40										
-481121-A10	CAPACITOR, fixed: 2/5/40 NT-481121 w/10 mmf p/m 10%; temp coef ltr A. NOTE: IR-2; IR-3.	RE48A221 16C40		16-C-26025-9551				CD	4-14010			IR LR-1 SEE NOTE:
-481121-B10	CAPACITOR, FIXED: 4/12/48 Navy Type 481121 w/10 mmf p/m 10%; temp coef letter B.	RE48A154 16C40		16-C-26025-9556	N16-C-9791-100			CAW	14451S			LR-2
-481122	CAPACITOR, fixed: 2/5/40 mica; 20 mmf; 600 vdcw, 1000 vdcw; case 1 1/4" lg x 1 1/8" wd x 23/64" thk; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	RE48A221 16C40										
-481122-A10	CAPACITOR, fixed: 2/5/40 NT-481122 w/20 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-26738-2351				CD	4-14020			IR

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-403

RESTRICTED

RESTRICTED

SHEET 48 - 404

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481123	CAPACITOR, fixed: 2/5/40 mica; 152 mmf; 600 vdcw, 1000 vdc; case 1 1/4" lg x 1 1/8" wd x 23/64" thk; molded bakelite case; two lug terminals w/one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	E48A221 16C40										
-481123-A10	CAPACITOR, fixed: 2/5/40 NT-481123 w/152 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-28992-7525				CD	4-130152			
-481123-C2	CAPACITOR, fixed: 2/5/40 NT-481123 w/152 mmf p/m 2%; temp coef ltr C. NOTE: L-2 (2); LR-3 (2).	E48A221 16C40		16-C-28992-7132	N16-C-9962-50			CD	4LTS-130152			LR (2) LR-1 (2) SEE NOTE:
-481123-C5	CAPACITOR, fixed: 2/5/40 NT-481123 w/152 mmf p/m 5%; temp coef ltr C.	E48A221 16C40		16-C-28992-7394	N16-C-9962-48			CD	4LTS-130152			
-481124	CAPACITOR, fixed: 2/5/40 mica; 450 mmf; 600 vdcw, 1000 vdc; case 1 1/4" lg x 1 1/8" wd x 23/64" d; molded bakelite case; two lug terminals w/one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	RE48A221 16C40										
-481124-A10	CAPACITOR, fixed: 2/5/40 NT-481124 w/450 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-30085-2151				CD	4-13045			LR
-481125	CAPACITOR, fixed: 2/5/40 mica; 750 mmf; 600 vdcw, 1000 vdc; case 1 1/4" lg x 1 1/8" wd x 23/64" thk; molded bakelite case; two lug terminals w/one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	RE48A221 16C40										
-481125-A10	CAPACITOR, fixed: 2/5/40 NT-481125 w/750 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-30668-4951				CD	4-13075			
-481125-C2	CAPACITOR, fixed: 2/5/40 NT-481125 w/750 mmf p/m 2%; temp coef ltr C. NOTE: LR-2 (2); LR-3 (2).	RE48A221 16C40		16-C-30658-2995	N16-C-10070-45			CD	4LTS-13075			LR (2) LR-1 (2) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-404

RESTRICTED

RESTRICTED

SHEET 48 - 405

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481126	CAPACITOR, fixed: 2/5/40 mica; 800 mmf; 600 vdcw, 1000 vdct; case 1 1/4" lg x 1 1/8" wd x 23/64" thk; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg hole in 0.144" diam, 1 5/16" c to c.	RE48A221 16C40										
-481126-A10	CAPACITOR, fixed: 2/5/40 NT-481126 w/800 mmf p/m 10%; temp coef ltr A. NOTE: IR-2; IR-3.	RE48A221 16C40		16-C-30694-8351				CD	4-13080			LR IR-1 SEE NOTE
-481126-B20	CAPACITOR, fixed: 2/5/40 NT-481126 w/800 mmf p/m 20%; temp coef ltr B.	RE48A221 16C40		16-C-30700-1836	N16-C-10073-2			CD	4L			
-481127	CAPACITOR, fixed: 2/5/40 mica; 1,500 mmf; 600 vdcw, 1000 vdct; case 1 1/4" lg x 1 1/8" wd x 23/64" d; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	RE48A221 16C40										
-481127-A10	CAPACITOR, fixed: 2/5/40 NT-481127 w/1,500 mmf p/m 10%; temp coef ltr A. NOTE: IR-2; IR-3.	RE48A221 16C40		16-C-31512-5750			3DA1.50-6	CD	4-12015			LR IR-1 SEE NOTE
-481127-B1	CAPACITOR, fixed: 2/5/40 NT-481127 w/1,500 mmf p/m 1%; temp coef ltr B.	RE48A221 16C40		16-C-31501-4715				CD	4L			
-481127-B10	CAPACITOR, fixed: 2/5/40 NT-481127 w/1,500 mmf p/m 10%; temp coef ltr B.	RE48A221 16C40		16-C-31512-5755	N16-C-10181			CD	4L			
-481127-C2	CAPACITOR, fixed: 2/5/40 NT-481127 w/1,500 mmf p/m 2%; temp coef ltr C. NOTE: IR-2; IR-3.	RE48A221 16C40		16-C-31502-3701	N16-C-10180-1			CD	4LTS-12015			LR IR-1 SEE NOTE
-481128	CAPACITOR, fixed: 2/5/40 mica; 1,620 mmf; 600 vdcw, 1000 vdct; case 1 1/4" lg x 1 1/8" wd x 23/64" d; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg hole in case 0.144" diam, 1 5/16" c to c.	RE48A221 16C40										
-481128-A10	CAPACITOR, fixed: 2/5/40 NT-481128 w/1,620 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-31628-5635				CD	4-120162			
-481128-C2	CAPACITOR, fixed: 2/5/40 NT-481128 w/1,620 mmf p/m 2%; temp coef ltr C. NOTE: IR-2 (2); IR-3 (2).	RE48A221 16C40		16-C-31628-5531	N16-C-10212			CD	4LTS-120162			LR (2) IR-1 (2) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48.405

RESTRICTED

RESTRICTED

SHEET 48 - 406

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481129	CAPACITOR, fixed: paper dielectric; 250,000 mmf plus 10 minus 3%; 1400 vdcw, 1000 vacw at 800 c/s; HS metal can; case 2 1/2" lg x 1 3/16" wd x 4 11/16" h o/a; oil impr and filled; two ceramic ins screw type term 7/8" h located on top 1 1/8" c to c; no int grd connections; two mtg fl 1" wd on side of case, ea w/3/16" diam mtg hole 3" c to c.	RE48A146 RE13A488		16-C-46331-4420				CD	PC-1335			
-481129-3	CAPACITOR, fixed: NT-481129 w/250,000 mmf p/m 3%.	RE48A146 RE13A488		16-C-46676-1216				CD	PC-1335	CRR	A26204-4revB	TAJ-8
-481130	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 1,500 vdcw; HS metal case; case 3 3/4" lg x 1 1/4" wd x 4 11/16" h o/a; oil impr and filled; two ceramic ins screw type term 7/8" h located on top 2" c to c; no int grd connections; two mtg fl 1 1/8" wd on side of case, ea w/3/16" diam mtg hole 4 3/8" c to c.	RE48A146 RE13A488		16-C-49941-8956				CD	TJ-15040	CRR	A26204-2 revB	TAJ-8
-481130-15	CAPACITOR, FIXED: Navy Type 481130 w/4 mfd p/m 15%.			16-C-49978-2925				CD	TJ-15040 (p/a 15%)	CS	5812382	TS-147/UP
-481131	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 3,000 vdcw; HS metal can; 3 3/4" lg x 4 9/16" wd x 4 13/16" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/4" h located on top 2" c to c; no int grd connections; two mtg fl on bottom of case ea w/two 3/16" diam mtg holes 3 3/8" apart 4 3/8" c to c.	RE48A159 RE13A488		16-C-49944-6579	N16-C-11584			CD	TJ-30040	CRR	A26204-3revB	TAJ-8
-481131-10	CAPACITOR, FIXED: Navy Type 481131 w/4 mf p/m 10%.			16-C-49965-6585	N16-C-11583-800			CAW	905-D			
-481132	CAPACITOR, FIXED: ceramic dielectric; 90 mmf; neg temp coef 750 (tol plus 120 minus 335) mmf/mfd/°C; 500 vdcw; case dimen 0.812" lg x 0.250" diam; 2 axial wire leads; ins body; add suffix indicating capacity tolerance in per cent.											
-481132-2	CAPACITOR, FIXED: Navy Type 481132 w/90 mmf p/m 2%.			16-C-16973-1810	N16-C-8207			CER	N750190P/M1.8 mmf			
-481132-5	CAPACITOR, fixed: NT-481132 w/90 mmf p/m 5%.			16-C-16981-1280				CER		CRR	A26205-A	TAJ-8 (3)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-406

RESTRICTED

RESTRICTED

SHEET 48 - 407

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481133	CAPACITOR, fixed: 3/12/40 mica; 6,000 mmf; 2,000 vdcw max, 9.0 amps at 3,000 kc, 7.5 amps at 1,000 kc, 4.5 amps at 300 kc; 2.2 amps at 100 kc; case 2 1/16" lg x 61/64" wd x 1 17/32" h; molded bakelite case; two screw term 7/16" lg, 1 1/2" c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-481133-A5	CAPACITOR, fixed: 3/12/40 NT-481133 w/6,000 mmf v/m 5%; temp coef ltr A.	RE48A222 16C40		16-C-32853-7025				CD	PL-580-15			
-481133-A10	CAPACITOR, fixed: 3/12/40 NT-481133 w/6,000 mmf p/m 10%; temp coef ltr A.	RE48A222 16C40		16-C-32858-7505	N16-C-10449-41			CD	PL-580-15			
-481133-B5	CAPACITOR, fixed: 3/12/40 NT-481133 w/6,000 mmf p/m 5%; temp coef ltr B. NOTE: TCB-2 (2); TDE (2); TDE-1 (2); TUE-2 (2); TDE-	RE48A222 16C40		16-C-32853-7027	N16-C-10449-40	R16-C-10448		CD	PL-580-15L	CAY CAY	T-7606409-78 7608226-68	GO-7 TBW SEE NOTE
-481134	CAPACITOR, fixed: 3/12/40 mica; 250 mmf; 2,500 vdcw max, 1.4 amp at 3,000 kc, 0.6 amp at 1,000 kc, 0.2 amp at 300 kc, 0.06 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 23/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam holes 2 5/8" c to c.	RE48A131 16C40										
-481134-002N2	CAPACITOR, fixed: 3/12/40 NT-481134 w/250 mmf p/m 2%; temp coef 002N.	RE48A131 16C40		16-C-29472-4477				CD	PL-1053-6K	CAY CAY	7608226-46 7606233-16	TDE thru TDE-3
-481134-003N2	CAPACITOR, fixed: 3/12/40 NT-481134 w/250 mmf p/m 2%; temp coef 003N	RE48A131 16C40		16-C-29472-4482	N16-C-9978-10			CD	PL-1053-6K	COL	T-7606408-53	TCB-2
-481134-A2	CAPACITOR, fixed: 3/12/40 NT-481134 w/250 mmf p/m 2%; temp coef ltr A.	RE48A131 16C40		16-C-29472-4474				CD	PL-1053-6			GO-7 TBW
-481134-D2	CAPACITOR, FIXED: 3/23/49 Navy Type 481134 w/250 mmf p/m 2%; temp coef letter D.			16-C-29472-4477				CD	1053-6K	CAY	T-7606408P53	TBW-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-407

RESTRICTED

RESTRICTED

SHEET 48 - 408

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481135	CAPACITOR, fixed: 3/12/40 mica; 600 mmf; 2,500 vacw max, 3.4 amp at 3,000 kc, 1.5 amp at 1,000 kc, 0.46 amp at 300 kc, 0.15 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam holes 2 5/8" c to c; for replacement use NT-48957.	RE48A131 16C40								CAY	7606233	
-481135-002N2	CAPACITOR, fixed: 3/12/40 NT-481135 w/600 mmf p/m 2%; temp coef 002N.	RE48A131 16C40		16-C-30316-4998					PL-1066-6K	CAY CAY	7608226-47 7606223-17	TDE thru TDE-3
-481135-003N2	CAPACITOR, fixed: 3/12/40 NT-481135 w/600 mmf p/m 2%; temp coef 003N.	RE48A131 16C40		16-C-30316-5015	N16-C-10045-2				PL-1066-6K			TCB-2
-481135-A2	CAPACITOR, fixed: 3/12/40 NT-481135 w/600 mmf p/m 2%; temp coef ltr A.	RE48A131 16C40		16-C-30316-4983					PL-1066-6			GC-7 PBW
-481135-B20	CAPACITOR, fixed: 3/12/40 NT-481135 w/600 mmf p/m 20%; temp coef ltr B.	RE48A131 16C40		16-C-30330-8902					PL-1066-6L			
-481136	CAPACITOR, fixed: 3/12/40 mica; 750 mmf; 2,500 vdcw, 4 amp at 3,000 kc, 1.7 amp at 1,000 kc, 0.55 amp at 300 kc, 0.18 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481136-001N2	CAPACITOR, fixed: 3/12/40 NT-481136 w/750 mmf p/m 2%; temp coef 001N.	RE48A131 16C40		16-C-30659-4495					PL-1023-6K	CAY	T-7606408-55	TCB-2
-481136-A2	CAPACITOR, fixed: 3/12/40 NT-481136 w/750 mmf p/m 2%; temp coef ltr A.	RE48A131 16C40		16-C-30659-4460					PL-1023-6			
-481136-D2	CAPACITOR, fixed: 3/12/40 NT-481136 w/750 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-30659-4475					PL-1023-6K	CAY CAY	7608226-48 7606233-16	GC-7 TBW TDE SEE NOTE
	NOTE: TDE-1; TDE-2; TDE-3.											

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-408

RESTRICTED

RESTRICTED

SHEET 48 - 409

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	Contractor	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481137	CAPACITOR, fixed: 3/12/40 mica; 3,000 mmf; 2,000 vdcw, max 7 amp at 3,000 kc, 6 amp at 1,000 kc, 2 amp at 300 kc, 0.6 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481137-001N2	CAPACITOR, fixed: 3/12/40 NT-481137 w/3,000 mmf p/m 2%; temp coef 001N2.	RE48A131 16C40		16-C-32189-1627				CD	PL-1031-6K	CAY	T-7606408-56	TCB-2
-481137-A2	CAPACITOR, fixed: 3/12/40 NT-481137 w/3,000 mmf p/m 2%; temp coef ltr A.	RE48A131 16C40		16-C-32189-1600				CD	PL-1031-6			
-481137-B2	CAPACITOR, fixed: 3/12/40 NT-481137 w/3,000 mmf p/m 2%; temp coef ltr B.	RE48A131 16C40		16-C-32189-1605	N16-C-10327-45			CD	PL-1031-6L			
-481137-D2	CAPACITOR, fixed: 3/12/40 NT-481137 w/3,000 mmf p/m 2%; temp coef ltr D. NOTE: TDE; TDE-1; TDE-2; TDE-3.	RE48A131 16C40		16-C-32189-1615						CAY	7608226-49	GO-7 TBW SEE NOTE
-481138	CAPACITOR, variable: 3/22/40 air; plate meshing type single sect; 13 to 320 mmf; SLC; 0.0245" air gap; 3 9/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 1/2" lg bushing 7/16" lg x 3/8"-32 thd; acdr adj; forty-three cad pl brass plates; clockwise rotation; isolantite ins; lug term; single hole mtg by 3/8" diam mtg bushing or base mtg by two mtg feet ea w/one #6-32 tapped hole on 2 23/32" mtg/c.			16-C-61711-7771				CBC	MC-325-S	CAG CDU	1CA6 DD-5059-A	LR(2) thru LR-3 (2)
-481139	CAPACITOR, fixed: 3/22/40 paper dielectric; 500,000 mmf plus 10 minus 3%; 1,000 vdcw; HS metal can; case 1 15/16" lg x 15/16" wd x 1 1/2" h; oil impr; two screw type term 1/4" h located on top 7/8" c to c; no int. gnd connections; two mtg fl on bottom of case, ea w/ 0.161" diam mtg holes 2 1/8" c to c.	RE48A147 RE13A488		16-C-47279-7372	N16-C-11360-11			CD	VC-1819	CAG CAG	1C124 P-43275	LR LR-1 LR-2 LR-3
-481140	CAPACITOR, fixed: 3/26/40 paper dielectric; 6 mf plus 5 minus 3%; 330 vacw, 465 vdcw; HS metal can; case 4 1/2" lg x 1 3/4" diam; dykanol A impr and filled; two ins solder lug term 3/4" c to c on top 3/8" lg; no int gnd connections; no mtg holes, no mtg bkt supplied.	RE48A185 RE13A488		16-C-50666-2340	N16-C-11615-28			CD	CRA-3060	CRR	C56602alt0	LD-4

SHEET 48-409

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 410

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR'S DWG NO PART NO	EQUIPMENT USED IN
-481141	CAPACITOR, fixed: 4/2/40 mica; 1,030 mmf; 500 vdcw, 1,000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143 16C40									
-481141-D3	CAPACITOR, fixed: 4/2/40 NT-481141 w/1,030 mmf p/m 3%; temp coef ltr D.	RE48A143 16C40		16-C-31127-9793				CAW CMR CD CSL	1464 PW 1RS MWSDW	CRV P-720537-9rev19	DZ
-481142	CAPACITOR, fixed: 4/2/40 mica; 1,900 mmf; 500 vdcw, 1,000v DC test; case 53/64" lg x 53/64" wd x 9/32" diam; molded bakelite case; two axial wire leads.	RE48A143 16C40									
-481142-D3	CAPACITOR, fixed: 4/2/40 NT-481142 w/1,900 mmf p/m 3%; temp coef ltr D.	RE48A143 16C40		16-C-31743-9023		R16-C-10235		CAW CMR CD CSL	1464 PW 1RS MWSDW	CRV P-720537-10 rev19	DZ
-481143	CAPACITOR, fixed: 4/2/40 mica; 2,100 mmf; 500 vdcw, 1,000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143									
-481143-D5	CAPACITOR, fixed: 4/2/40 NT-481143 w/2,100 mmf p/m 5%; temp coef ltr D.	RE48A143 JAF-C-5	CM30D212J	16-C-31850-3294		R16-C-10305		CAW CD CMR CSL	1464 1RS PW MWSDW	CRV P-720533-11 rev30	DZ
-481143-E1	CAPACITOR, fixed: 4/2/40 NT-481143 w/2,100 mmf p/m 1%; temp coef ltr E.	RE48A143 16C40		16-C-31844-3810				CD CAW CSL CMR	1RS 1464 MWSDW PW	COL 914 2214 60rev2	
-481144	CAPACITOR, fixed: 4/2/40 mica; 3,500 mmf; 300 vdcw, 600v DC test; case 53/64" lg x 53/64" wd x 11/32" d max; molded bakelite case; two axial wire leads.	RE48A143 16C40									
-481144-D5	CAPACITOR, fixed: 4/2/40 NT-481144 w/3,500 mmf p/m 5%; temp coef ltr D.	RE48A143 16C40		16-C-32324-9153		R16-C-10342		CAW CMR CD CSL	1464 PW 1RS MWSDW	CRV P-720538-12 rev30	DZ
-481144-D6	CAPACITOR, fixed: 4/2/40 NT-481144 w/3,500 mmf p/m 6%; temp coef ltr D.	RE48A143 16C40		16-C-32329-3570		R16-C-10342-25		CAW	1464		

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-410

RESTRICTED

RESTRICTED

SHEET 48-411

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481145	CAPACITOR, fixed: 4/2/40 mica; 5,700 mmf; 300 vdcw, 600v DC test; case 3/4" lg x 3/4" wd x 11/32" d max; molded bakelite case; two axial wire leads.	RE48A143 16C40										
-481145-D5	CAPACITOR, fixed: 4/2/40 NT-481145 w/5,700 mmf p/m 5%; temp coef ltr D.	RE48A143 16C40		16-C-32842-5927		R16-C- 10430-150		CAW CMR CSL	1464 PW MOSDW	CRV	P-720538-13rev30	DZ
-481146	CAPACITOR, fixed: 4/2/40 mica; 27 mmf; 500 vdcw, 1,000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148 JAN-C-5										
-481146-B5	CAPACITOR, fixed: 4/2/40 NT-481146 w/27 mmf p/m 5%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B270J	16-C-27075-8796	N16-C-9812-100			CMF CAW CD CSL CMR	503M 1468LS 5WLS MOEW OXM	CG	K27J362-9rev9	BG SC-2
-481146-B10	CAPACITOR, fixed: 4/2/40 NT-481146 w/27 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B270K	16-C-27080-9276	N16-C-9812	R16-C-9835	3K202/021	CD CAW CSL CMR	5WLS 1468LS MOEW OXM			
-481146-D5	CAPACITOR, fixed: 4/2/40 NT-481146 w/27 mmf p/m 5%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D270J	16-C-27075-8806		R16-C-9833		CAW CMR CER CD CMF CSL	1469 FO MOK27 5RS 603H MOSDW	CRV	P-720538-2rev30	DZ AYA AYA-1 AYA-2 AYA-3
-481146-D10	CAPACITOR, fixed: 4/2/40 NT-481146 w/27 mmf p/m 10%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D270K	16-C-27080-9286	N16-C-9813			CD CAW CSL CMR	5RS 1469 MOSDW FO			
-481147	CAPACITOR, FIXED: 4/2/40 mica dielectric; 33 mmf; 500 vdcw, 1000v, DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded low loss phenolic body; 2 axial wire leads; term mtg.	RE48A148 JAN-C-5										

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-411

RESTRICTED

RESTRICTED

SHEET 48 - 412

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481147-A20	CAPACITOR, FIXED: 3/14/49 Navy Type 481147 w/330 mmf p/m 20%; temp coef letter A.	JAN-C-5	CM20A331M	16-C-29723-9751								FRE
-481147-B5	CAPACITOR, FIXED: 6/25/48 Navy Type 481147 w/33 mmf p/m 5%; temp coef ltr B.	JAN-C-5	CM20B330J	16-C-27181-4396								SK
-481147-B10	CAPACITOR, fixed: 4/2/40 NT-481147 w/33 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B330K	16-C-27186-4876	N16-C-9840-50		3K2033021	CMR CAW CSL CD	OXM 1468L MOISW 5HL			
-481147-B20	CAPACITOR, FIXED: 5/9/48 Navy Type 481147 w/33 mmf p/m 20%; temp coef letter B.	RE48A148 JAN-C-5	CM20B330M	16-C-27191-7356	R16-C-9941			CSL	5S			SC-1
-481147-D5	CAPACITOR, fixed: 4/2/40 NT-481147 w/33 mmf p/m 5%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D330J	16-C-27181-4406	N16-C-9840-55-5 N16-C-9840-55	R16-C-9839-150		CER CAW CMR CSL CD	MLK33 1469 PO MOISW 5RS	CRV CS	P-720533-3rev30 011-19revD	DZ AMB (3) DBE
-481148	CAPACITOR, fixed: 4/2/40 mica; 147 mmf; 500 vdcw, 1,000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148 16C40										
-481148-D3	CAPACITOR, fixed: 4/2/40 NT-481148 w/147 mmf p/m 3%; temp coef ltr D.	RE48A148 16C40		16-C-28965-8143		R16-C-9951-150		CAW CMR CER CD CSL	1469 PO M2R147 5RS MOISW	CRV	P-720537-3rev19	DZ
-481149	CAPACITOR, fixed: 4/2/40 mica; 170 mmf; 500 vdcw, 1,000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148 16C40										
-481149-D1	CAPACITOR, fixed: 4/2/40 NT-481149 w/170 mmf p/m 1%; temp coef ltr D.	RE48A148 16C40		16-C-29099-2086	N16-C-9964-4			CSL CAW CD CMR	MOISW 1469 5RS PO	CMX	B250085029chg?	RCT (2) RCU (2) RCU-1 (2)
-481149-D3	CAPACITOR, fixed: 4/2/40 NT-481149 w/170 mmf p/m 3%; temp coef ltr D.	RE48A148 16C40		16-C-29099-2783				CAW CMR CER CD CSL	1469 PO M3K170 5RS MOISW	CRV CAY	P-720537-4rev19 7609011-89	DZ RBM RBM-1 RBM-2 RBM-3 SEE NOTE
-481150	CAPACITOR, fixed: 4/2/40 CANCELLED: use NT-48675.											

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-412

RESTRICTED

RESTRICTED

SHEET 48-413

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481151	CAPACITOR, fixed: 4/2/40 mica; 370 mmf; 500 vdcw, 1,000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148		16-C-29839-6410	N16-C-10003-2							
-481151-A10	CAPACITOR, fixed: 4/2/40 NT-481151 w/370 mmf p/m 10%; temp coef ltr A.	RE48A148 JAN-C-5	CM20A371K	16-C-29850-6271				CD CAW CSL CMR	SMS 1468S MOW 0	CBM CRV	744-165 P-720473-18rev19	NK-1 (12) NK-3 (12) NK-7 (12)
-481151-B5	CAPACITOR, fixed: 4/2/40 NT-481151 w/370 mmf p/m 5%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B371J	16-C-29845-5796	N16-C-10003-1			CD CAW CSL CMR	SMS 1468WLS MOEW OXM			
-481151-B10	CAPACITOR, fixed: 4/2/40 NT-481151 w/370 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B371K	16-C-29850-6276	N16-C-10003-9			CD CAW CSL CMR	SMS 1468WLS MOEW OXM			
-481151-D1	CAPACITOR, fixed: 4/2/40 NT-481151 w/370 mmf p/m 1%; temp coef ltr D.	RE48A148 16C40		16-C-29839-6410	N16-C-10003-2			CD CSL CAW CMR	SRS MOSDW 1469 PO	CBM CIP CEM	744-243 EC-744-2561ea2 744-28	NJ-3 (2) NJ-6 (3) NJ-7 (2) NJ-9 (2)
-481151-D2	CAPACITOR, fixed: 4/2/40 NT-481151 w/370 mmf p/m 2%; temp coef ltr D. NOTE: QCY; QCZ.	RE48A148 JAN-C-5	CM20D371G	16-C-29840-4326	N16-C-10003	R16-C- 10003-150		CER CAW CMR CD CSL	M5K-370 1469 PO SRS MOSDW	CRV CRV	P-721081-28 rev27 P-720537-7rev19	QBH (3) QCQ-2 (3) QCU (3) QCW QCX SEE NOTE
-481151-D3	CAPACITOR, fixed: 4/2/40 NT-481151 w/370 mmf p/m 3%; temp coef ltr D.	RE48A148 16C40		16-C-29844-7223				CAW CMR CER CD CSL	1469 PO M5K370 SRS MOSDW	CRV	P-720537-6rev19	DZ
-481152	CAPACITOR, fixed: 4/2/40 mica; 470 mmf; 500 vdcw, 1000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148										
-481152-A10	CAPACITOR, FIXED: 12/6/48 Navy Type 481152 w/470 mmf p/m 10%; temp coef letter A.	JAN-C-5	CM20A471X	16-C-30114-4271								MK-25 Mod 2

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-413

RESTRICTED

RESTRICTED

SHEET 48 - 414

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481152-A20	CAPACITOR, FIXED: 11/23/48 Navy Type 481152 w/470 mmf p/m 20%; temp coef letter A.	JAN-C-5	CM20A471M	16-C-30119-6751								QJB
-481152-B10	CAPACITOR, fixed: 4/2/40 NT-481152 w/470 mmf p/m 10%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B471K	16-C-30114-4276	N16-C-10015-39	R16-C-10017-21	3K2047121	CD CAW CSL CMR	5WLS 1468LS MOBW OXM	CRP	C56306-471 188K	
-481152-B20	CAPACITOR, fixed: 4/2/40 NT-481152 w/470 mmf p/m 20%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B471M	16-C-30119-6756	N16-C-10015-60	R16-C-10017-24-500	3K2047124	CD CAW CSL CMR	5WLS 1468LS MOBW OXM			
-481152-C5	CAPACITOR, FIXED: 1/21/49 Navy Type 481152 w/470 mmf p/m 5%; temp coef letter C.	JAN-C-5	CM20C471J	16-C-30109-3301			3K2047120	CRP	35-5355	CRP	S-35-5350 10s 2	MC-561A/ TPS-1B AI/TPS-1B
-481152-C10	CAPACITOR, FIXED: 12/6/48 Navy Type 481152 w/470 mmf p/m 10%; temp coef letter C.	JAN-C-5	CM20C471K	16-C-30114-4281								ME-25 Mod 2
-481152-C20	CAPACITOR, FIXED: 2/10/49 Navy Type 481152 w/470 mmf p/m 20%; temp coef letter C.	JAN-C-5	CM20C471M	16-C-30119-6761								QDA
-481152-D2	CAPACITOR, FIXED: 12/16/47 Navy Type 481152 w/470 mmf p/m 2%; temp coef letter D.	JAN-C-5	CM20D471G	16-C-30104-2326								Q3B
-481152-D5	CAPACITOR, fixed: 4/2/40 NT-481152 w/470 mmf p/m 5%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D471J	16-C-30109-3806		R16-C-10017-20		CER CAW CMR CSL CD	M6K470 1469 PO MOSDW 5RS	CRV	P-720538-9 rev30	DZ ARB (10)
-481153	CAPACITOR, fixed: 4/2/40 mica; 485 mmf; 500 vdcv, 1000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148 16C40										
-481153-D2	CAPACITOR, fixed: 4/2/40 NT-481153 w/485 mmf p/m 2%; temp coef ltr D.	RE48A148 16C40		16-C-30128-3467		R16-C-10017-25		CAW CD CMR CER CSL	1469 5RS PO M6K485 MOSDW	CRV	P-720537-8rev19	DZ
-481154	CAPACITOR, fixed: 4/26/40 paper dielectric; two sect; 250,000 mmf plus 10 minus 3% ea sect; 750 vdcv ea sect, 550v 60 cyc ea sect; HS metal can; 2" lg x 2" wd x 2" h; oil impr and filled; four solder lug term 11/16" h on side of case; no int gnd connections; two integral mtg fl 7/16" wd on bottom of case, ea w/a 3/16" diam mtg hole 2 1/2" o to c.	RE48A156 RE13A488		16-C-53356-2210				CAW CAW	CS-549 5980	CAW CRP	13582 dated 3/15/40 3403 rev 2	CRP-21029 WBA

SHEET 48-414

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 415

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481155	CAPACITOR, fixed: 5/29/40 mica; 750 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143										
-481155-A5	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 5%; temp coef ltr A.	RE48A143 JAN-C-5	CM30A751J	16-C-30663-3279	N16-C-10070-39	R16-C-10039-8	3K3075112	CD CAW CSL CMR CAN CMF	1W 1467 MW W C 502J			QCJ-2 QCL
-481155-B2	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 2%; temp coef ltr B.	RE48A143 16-C-40		16-C-30658-1804	N16-C-9891			CD CSL CAW CMR	1W MW 1467 W	CNA	D-775	RBB-1 RBB-2 RBB-3
-481155-B5	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 5%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B751J	16-C-30663-3284	N16-C-10070-39		3K3075122	CD CAW CSL CMR CMF CAN	1WL 1467L MWBW WXM 502J CLW	CTA	D5498.1B-184	DAG
-481155-B10	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 10%; temp coef ltr B.	RE48A143 JAN-C-5	CM30B751K	16-C-30668-3764	N16-C-10070-40			CD CAW CSL CMR	1WL 1467 MW W			
-481155-C2	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 2%; temp coef ltr C.	RE48A143 JAN-C-	CM30C751G	16-C-30658-1809		R16-C-10039-5-500	3K3075133	CAW CD CSL CMF CMR	1467LST 1RS MWSCH 602J FW	CBM	744-336	QFB
-481155-C5	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 5%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C751J	16-C-30663-3289		R16-C-10039-9	3K3075132	CAW CSL CD CMR CMF	1464 MWSCH 1RS FW 602J	CBM	744-597	QGA SU-1 (2)
-481155-D2	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 2%; temp coef ltr D. NOTE: TS-120/UP(2); TS-191/UP(2).	RE48A143 JAN-C-5	CM30D751G	16-C-30658-1814	N16-C-9891	R16-C-10039-6	3K3075143	CAW CMR CSL CD	1464 FW MWSIW 1RS	CRB	CD-1072-1	S&E NOTE Con't

SHEET 48-415

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 416

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481155-D5	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 5%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D751J	16-C-30663-3294	N16-C-10070-36	R16-C-10039-10		CAW CMR CSL CD	1464 FW MWSW LMS	CRV CBM CRV	P-720538-16 rev 30 744-597 alt 0 W-303314-282	ARB QCJ-8 (8) QCL-7 (8) SB (2) WEA (6)
-481155-E2	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 2%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E751G	16-C-30658-1819		R16-C-10039-6-500		CAW CD CSL CMP CMR	1464 LRS MWSW 602J FW			
-481155-E5	CAPACITOR, fixed: 5/29/40 NT-481155 w/750 mmf p/m 5%; temp coef ltr E.	RE48A143 JAN-C-5	CM30E751J	16-C-30663-3299		R16-C-10039-15-300		CAW CD CSL CMP CMR	1464 LRS MWSW 602J FW			
-481156	CAPACITOR, fixed: 5/29/40 mica; 60,000 mmf; 1000 vdcw max, 14 amp at 3000 kc, 17 amp at 1000 kc, 13 amp at 300 kc, 7 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481156-B5	CAPACITOR, fixed: 5/29/40 NT-481156 w/60,000 mmf p/m 5%; temp coef ltr B. NOTE: QCJ-8 (2); QCL-7; WEB (2).	RE48A131 16C40		16-C-35385-3914	N16-C-10597			CRV CD	UC-3363, case 351 6L	CRV CBM	W-303056-11 744-666	QCJ-2 (2) QCL (2) SEE NOTE
-481157	CAPACITOR, FIXED: 6/5/40 mica dielectric; 85 mmf; 500 vdcw, 1000v, DC test; case 51/64" lg x 15/32" wd x 7/32" d max; molded phenolic case, low loss; 2 axial wire leads; term mtg.	RE48A148 JAN-C-40										
-481157-B2	CAPACITOR, fixed: 6/5/40 NT 481157 w/85 mmf p/m 2%; temp coef ltr B.	RE48A148 JAN-C-5	CM20B850G	16-C-28284-1716		R 16-C-9924		CAW CD CSL CMR	1468LS SWLS MOBW OXM	CRR	C56734-850 rev D	DU-1 DW-1 DW-2
-481157-B5	CAPACITOR, FIXED: 6/24/48 Navy Type 481157 w/85 mmf p/m 5%; temp coef letter B.	RE48A148D JAN-C-5		16-C-28289-3197	N16-C-9923-5			CAW	K			
-481157-B20	CAPACITOR, FIXED: 6/28/44 Navy Type 481157 w/85 mmf p/m 20%; temp coef letter B.	RE48A148 JAN-C-5		16-C-28299-6157	R16-C-9923-7			CAW	1468			
-481157-D2	CAPACITOR, fixed: 6/5/40 NT-481157 w/85 mmf p/m 2%; temp coef ltr D.	RE48A148 JAN-C-5	CM20D850G	16-C-28284-1726	N16-C-9923-2			CD CAW CSL CMR	SRS 1469 MOSDW PO	CHC	6180	DAJ RBC RBC-1 RBC-2

SHEET 48-416

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 417

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481157-D5	CAPACITOR, FIXED: Navy Type 481157 w/85 mmf p/m 5%; temp coef letter D.	6/24/48 RE48A148 JAN-C-5		16-C-28289-3207	N16-C-9923-3			CAN	KR			
-481158	CAPACITOR, fixed: mica; 750 mmf; 300 vdcw; case 51/64" lg x 15/32" wd x 7/32" d max; molded bakelite case; two axial wire leads.	6/5/40 RE48A148 16C40										
-481158-B2	CAPACITOR, fixed: NT-481158 w/750 mmf p/m 2%; temp coef ltr B.	6/5/40 RE48A148 16C40		16-C-30657-9153		R16-C-10039		CAW	1468LS	CRR	C56734-751 1esD	DU-1 DW-1 DW-2
-481158-B10	CAPACITOR, fixed: NT-481158 w/750 mmf p/m 10%; temp coef ltr B.	6/5/40 RE48A148 16C40		16-C-30668-2113	N16-C-10070-34			CAW CSL CMR	1468LS MOBW OXM	CDL	B-8F-7041 revE	
-481158-C2	CAPACITOR, FIXED. Navy Type 481158 w/750 mmf p/m 2%; temp coef letter C.	10/28/47 RE48A148 RE48A154		16-C-30657-9162				CSL	MOSCW	CRP	35-5265	VF
-481159	CAPACITOR, fixed: electrolytic; 1,000 mf; 25 vdcw, 50v max surg voltage; working temp range minus 20°C to plus 85°C; case 3 3/4" lg x 1 3/8" diam; ES metal case; two solder lug term on top; both term ins from can; mtg neck 7/8"-20 thd x 7/16" lg.	6/6/40 RE13A549		16-C-20881-7641	N16-C-9730			CSL	S-8560-PE	CRV	K-856047-1rev0	TDQ (4)
-481160	CAPACITOR, fixed: paper dielectric; 500,000 mmf plus 10, minus 3%; 600 vdcw, 200 vacw at 60 cyc, 1800v DC test; ES metal case; 1 7/8" h x 1 3/8" wd x 3/4" d o/a; two stud term 1/2" h located on top, spaced 5/8" c to c; no int gnd connections. NOTE: MK-26 Mod 3 (2); MK-26 Mod 4 (2).	7/10/40 RE48A110 RE13A488		16-C-47276-1320	N16-C-11351-10			CRV	72053-507	CRV CRV	F-720555-8rev2 F-72049-507sub5	QCJ-2 QCL SB (3) TBL-4 TBL-8 TBL-9 SEE NOTE
-481160-10	CAPACITOR, fixed: NT-481160 w/500,000 mmf p/m 10%.	7/10/40 RE48A110 RE13A488		16-C-47297-1295	N16-C-11351-3			CRV	72053-557	CRV	F-720555-58rev2	TDQ (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-417

RESTRICTED

RESTRICTED

SHEET 48 - 418

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481161	CAPACITOR, fixed: paper dielectric; two sect; 500,000 mmf plus 10 minus 3/8 ea sect; 400 vdcw, 100 vacw at 60 cyc between case and term 1, 400 vdcw, 100 vacw at 60 cyc between case and term #2, 1,200VDC test; ES metal can; case 1 7/8" h x 1 3/8" wd x 3/4" d o/a; two stud term 1/2" h located on top, spaced 5/8" c to c; both sect int gnd; bkt mtg not supplied. NOTE: QBH (11); QCJ-8 (4); QCL-7 (4); QCR-2 (4); QCW (5); QCX (7); QCY (7); QDZ (7); QGB (12); SR (12); MK-26 Mod 3; MK-26 Mod 4.	RE48A110 RE13A488		16-C-53570-4290	N16-C-11377-1 N16-C-11377-15			CRV	72053-509	CRV CRV CRV CWT	P-720555-3rev2 W-303335-26 W-303276-192	QCJ-2 QCL ATB(2) ATA(8) AYA-1(8) AYA-2(8) AYA-3(8) NMB-1 (5) SEE NOTE:
-481161-10	CAPACITOR, fixed: NT-481161 w/500,000 mmf p/m 10% ea sect.	RE48A110 RE13A488		16-C-53626-7686	N16-C-11377			CRV	72053-559	C V	P-720555-53 rev2	
-481161-15	CAPACITOR, fixed: NT-481161 w/500,000 mmf p/m 15% ea sect.	RE48A110 RE13A488		16-C-53676-4867				C V		C V	P-72024-509	TBS(2) TBS-1(2) SEE NOTE:
-481162	CAPACITOR, fixed: paper dielectric; 3.5 mf plus 10 minus 3/8; 175 vdcw; 125 vacw 60 cyc, 500V DC test; ES metal can; case 1 7/8" lg x 3/4" wd x 4 7/16" h; oil impr and filled; two solder lug term on top 1" c to c; no int gnd connections; one mtg bkt on ea side ea w/one .154" diam hole 2 7/8" c to c.	RE48A174 RE13A488		16-C-49738-8210	N16-C-11537					C V CRV CRV	W-303065-7 K-90543-1rev1 P-72029-505 sub 11	QCJ-2 QCL QCJ QCJ-7 QCJ-8 QCL-7
-481163	CAPACITOR, fixed: paper dielectric; 7.5 mf plus 10 minus 3/8; 330 vacw at 60 cyc, 600 vdcw; ES metal case; case 3 3/4" h x 3 3/16" wd x 1 5/8" d o/a; two stud term 1/2" h located on top, spaced 1 1/2" c to c; no int gnd connections. NOTE: QCJ-8; QCL-7; QCW(3); QCX(3); QCY(3); QDZ(3)	RE48A110 RE13A488		16-C-51266-8763				CG CAJ CSF	67X45 100057	CAJ CRV CEZ C V	18178 K-866157-1 CO-1003-1 W-303263-118	QCJ-2 QCL BL-1(2) thru BL-6(2) NMB-1 SEE NOTE
-481164	CAPACITOR, fixed: paper dielectric; 50 mf plus 10 minus 3/8; 100 vdcw; ES metal can; case 5 1/16" h x 3 3/8" wd x 7/8" d o/a; two stud term 1" h located on top, spaced 2" c to c; no int gnd connections.	RE48A110 RE13A488		16-C-52663-1560	N16-C-11697			CRV	P-72004-507	CRV CRV	P-72004-507 rev4 W-303245-71	QCJ-2 QCL QCJ-8 (2) QCL-7 (2)

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

SHEET 48-418

RESTRICTED

RESTRICTED

SHEET 48 - 419

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFG	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481165	CAPACITOR, fixed: 7/22/40 mica; 15,000 mmf; 600 vdcw, 1000v DC test, case 1 1/4" lg x 1 1/8" wd x 29/64" d max; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 JAN-C-5										
-481165-A10	CAPACITOR fixed: 7/22/40 NT-481165 w/15,000 mmf p/m 10%; temp coef ltr A. NOTE: QCC-7 (2); QCJ-8 (2); WEA (2).	RE48A221 JAN-C-5	CM50A153K	16-C-34044-8251				CAW CD	1445 4	CRV CRV	W-303284-212 W-720567-1 rev2	QCJ-2 QCL SEE NOTE:
-481165-B2	CAPACITOR, fixed: 7/22/40 NT-481165 w/15,000 mmf p/m 2%; temp coef ltr B.	RE48A221 JAN-C-5	CM50B153G	16-C-34034-6296	N16-C-10525-3	R16-C-10529-1-800		CD CAW CD	4L 1445LS 4LS-110115	CW		MX-9 MX-10 MX-18
-481165-B5	CAPACITOR, fixed: 7/22/40 NT-481165 w/15,000 mmf p/m 5%; temp coef ltr B.	RE48A221 JAN-C-5	CM50B153J	16-C-34039-7776	N16-C-10525-4	R16-C-10529-5-800		CAW CD	1445LS 4L			RBA RBA-1
-481165-B10	CAPACITOR, fixed: 7/22/40 NT-481165 w/15,000 mmf p/m 10%; temp coef ltr B.	RE48A221 JAN-C-5	CM50B153K	16-C-34044-8255	N16-C-10525	R16-C-10529-15		CD CAW	4L-11015 1445LS	CW		MX-16
-481166	CAPACITOR, fixed: 7/22/40 paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw; metal case; case 2 5/8" lg x 1 3/16" wd x 3 27/64" h; pyramol impr and filled; two screw-type term 1 5/32" h on top, spaced 1 1/8" c to c on por pillars; no int gnd connections; one mtg bkt on ea side ea w/two 0.213" diam holes 13/32" x 3 1/8" c to c. NOTE: QGB (2); WEA (4); WEA (5).	RE48A173 RE13A488		16-C-49936-6470	N16-C-11556			CG CG	26F317 26F106	CRV CWT CRV CRV	W-303335-24 GV-1637 W-418476-106 W-305284-149 W-303089-6	TDQ NMB-1(4) QBH(2) QCU(5) QCC-2(4) QCJ-8(3) QCL-7(3) SEE NOTE:
-481167	CAPACITOR, fixed: 8/5/40 paper dielectric; two sect; 125,000 mmf plus 10 minus 3% ea sect; 400 vdcw, 120 vacw between case and term #1, 400 vdcw, 120 vacw between case and term #2, 1,200v DC test; HS metal can; case 1 1/16" h x 1 3/8" wd x 3/4" d o/a; two stud term 1/2" h located on top, spaced 5/8" c to c; both sect int gnd; bkt mtg not supplied. NOTE: WEA; WEA-1.	RE48A110 RE13A488		16-C-53227-3260	N16-C-11336			CRV	72053-512	CRV CWT	P-720555-5sub2 W-303276-193	QCJ-2 QCL QBH (2) QCW QCX QCY QOZ SB SEE NOTE
-481167-10	CAPACITOR, fixed: 8/5/40 NT-481167 w/125,000 mmf p/m 10% ea sect. NOTE: QCJ-8; QCL-7; QCC-2; QCU; QGB(4); QEB-1 (4); RBB-2 (4); RBC (4); RBC-1 (4); RBC-2 (4).	RE48A110 RE13A488		16-C-53227-3460	N16-C-11437-30			CRV	72053-562	CRV	P-720555-55sub2	ARJ(7) ATJ(2) SEE NOTE:

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-419

RESTRICTED

RESTRICTED

SHEET 48 - 420

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTORS DWG OR PART NO	EQUIPMENT USED IN
-481168	CAPACITOR, fixed: 8/14/40 paper dielectric; 250,000 mmf plus 10 minus 3%; 1,000 vdcw; BS metal can; case 1 3/4" lg x 1" wd x 2 1/8" h; oil impr and filled; 2 screw type term 3/8" b located on top 3/4" c to c; no int gnd connections; no mtg fl on bottom of case ea with 3/16" diam mtg holes 2 1/4" c to c.	RE13A488 RE48A147		16-C-46329-6952		R16-C-11338-30		CD	TDF-100025			GO-7 GO-8 GO-9
-481168-10	CAPACITOR, fixed: 8/14/40 NT-481168 w/250,000 mmf p/m 10%.	RE13A488 RE48A147		16-C-46350-6942	N16-C-11341-77			CD	TDF-100025			
-481169	CAPACITOR, FIXED: 8/14/40 ceramic dielectric; 40 mmf; neg temp coef 680 (tol p/m 40.9) mmf/mf ^{1/2} /°C; 500 vdcw; case 7/16" lg x 7/32" diam; axial wire leads; ceramic ins; add suffix indl- cating capacity tolerance in per cent.											
-481169-5	CAPACITOR, fixed: 8/14/40 NT-481169 w/40 mmf p/m 5%.			16-C-16437-1223				CER		CER	A-17462-400revB	RAF
-481169-10	CAPACITOR, fixed: 8/14/40 NT-481169 w/40 mmf p/m 10%. NOTE: BL-3 (14); BL-5 (14).			16-C-16446-5723				CER				BL-1 (16) BL-2 (16) SEE NOTE
-481170	CAPACITOR, fixed: 9/10/40 mica; 500 mmf; 2500 vdcw, 5000 vdot; case 1 1/4" lg x 1 1/8" wd x 23/64" thk max; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	RE48A221										
-481170-A2	CAPACITOR, FIXED: 1/14/40 Navy Type 481170 w/500 mmf p/m 5%; temp coef letter A.	RE48A221 RE48A184		16-C-32689-8049				CSL	XGW 1.2-35-2	CBZ	CO-619	BL-1 BL-2
-481170-A5	CAPACITOR, fixed: 9/10/40 NT-481170 w/500 mmf p/m 5%; temp coef ltr A.	RE48 221 JAN-C-5	CM45A501J	16-C-30163-2631				CSL CSF CD	XQW MX-12B 4			
-481170-A10	CAPACITOR, fixed: 9/10/40 NT-481170 w/500 mmf p/m 10%; temp coef ltr A. NOTE: TBM-8 (2); TBM-10; TBM-12 (2); TBK-13 (2).	RE48A221 JAN-C-5	CM45A501K	16-C-30168-4111				CD CSL CAW CAW	4-53050 XQ 48-53050 1447E-0005	CAY CAY CAY	T-7606233-30sub6 T-7606286-25 T-7606286-27	TBM-4 TBM-5 (2) TBM-6 (2) TBM-7 (2) SEE NOTE
-481170-B5	CAPACITOR, fixed: 9/10/40 NT-481170 w/500 mmf p/m 5%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B501J	16-C-30163-3633	N16-C-10021			CD CSL	4LS XQBW			
-481170-B10	CAPACITOR, fixed: 9/10/40 NT-481170 w/500 mmf p/m 10%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B501K	16-C-30168-4113	N16-C-10021-1			CD	4LS	CRM	744-694	NMC-1 (2)
-481170-B20	CAPACITOR, fixed: 9/10/40 NT-481170 w/500 mmf p/m 20%; temp coef ltr B.	RE48A221 JAN-C-5	CM45B501M	16-C-30173-6593				CSL CD	XQ2.5-35 4L	COL	925.3507.20	ORH

SHEET 48-420

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 421

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481171	CAPACITOR, fixed: 9/10/40 paper dielectric; 8 mf plus 10 minus 3%; 600 vdcw, 1,200v MC test; HS metal can; case 3 3/4" lg x 1 1/4" wd x 3 13/16" h o/a; oil impr and filled; two ceramic ins screw type term 7/8" h located on top 2" c to c; no int grd connections; two mtg fl 1 1/8" wd on side of case, ea w/ 3/16" diam mtg hole 4 3/8" c to c.	RE13A488 RE48A146		16-C-51457-2091		R16-C-11675-500		CD	TJ-6080			TBM-4 thru TBM-6
-481171-10	CAPACITOR, fixed: 9/10/40 NT-481171 w/8 mf p/m 10%.	RE13A488 RE48A146		16-C-51478-2081	N16-C-11640		3083-69.1	CD	TJ-6080	CAY CAY	7606286-19 7605848-24eub8	TBM-12 TDE thru TDE-3
-481172	CAPACITOR, fixed: 10/16/40 mica; 360 mmf; 5,000 vdcw, 4 amp at 3000 kc, 3 amp at 1000 kc, 2 amp at 300 kc, 0.8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481172-B5	CAPACITOR, fixed: 10/16/40 NT-481172 w/360 mmf p/m 5%; temp coef 1tr B.	RE48A131 16C40		16-C-29821-2523	N16-C-10002-80			CRV	UC-3301 case351	CRV	K-860215-4rev6	TBL-4 TBL-8 TBL-9
481173	CAPACITOR, fixed: 10/17/40 ceramic dielectric; 2 mmf; neg temp coef 750 (tol p/m 120) mmf/mfd/°C; 500 vdcw; case 0.812" lg x 0.25" OD; axial wire leads; ceramic ins; add suffix indicating capacity tolerance in per cent.											
-481173-12	CAPACITOR, fixed: 11/17/40 NT-481173 w/2 mmf p/m 0.25 mmf. NOTE: AR/ARR-1 (2); TS-1/ARR-1 (2).			16-C-15433-7090		R16-C-7850		CER	N750Lp/m120	CW	ES0-677726-1 1eaB(2)	ZB ZB-3 (2) SEE NOTE
-481174	CAPACITOR, fixed: 10/17/40 ceramic dielectric; 5mmf; pos temp coef 120 (tol p/m 12) mmf/mfd/°C; 500 vdcw; case 0.562" lg x 0.25" OD; ceramic ins; add suffix indicating capacity tolerance in per cent.											
-481174-1	CAPACITOR, fixed: 10/17/40 NT-481174 w/5 mmf p/m .05 mmf.			16-C-15623-2017	N16-C-8069-13			CER	F120K5p/m.05			
-481174-5	CAPACITOR, fixed: 10/17/40 NT-481174 w/5 mmf p/m 0.25 mmf. NOTE: AR/ARR-1 (7); TS-1/ARR-1 (7).			16-C-15623-9039	N16-C-8069-13	R16-C-7855		CER	F120K5p/m.25	CW	ES0-677726-2 1eaB(2)	ZB ZB-3 (8) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-421

RESTRICTED

RESTRICTED

SHEET 48 - 422

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481175	CAPACITOR, fixed: 10/17/40 ceramic dielectric; 30 mmf; negative temp coef 750 (tol p/m 120) mmf/mm ² /°C; 500 vdcw; case 7/16" lg x 7/32" diam; axial wire leads; ceramic line; add suffix indicating capacity tolerance in per cent.											
-481175-3	CAPACITOR, fixed: 12/17/40 NT-481175 w/30 mf p/m 3%. NOTE: AN/ARR-1 (23); TS-1/ARR-1 (23).			16-C-16270-3038		16-C-7875		CER	N750Kp/m120	CW	ES0-677726-4 1eaB (2)	ZB ZB-3 (23) SEE NOTE
-481176	CAPACITOR, fixed: 10/18/40 paper dielectric; 250,000 mmf plus 10 minus 3%; 400 vdcw, 120 vacw, 1,200v DC test; HS metal can; case 1 1/16" h x 1 3/8" wd x 3/4" d o/a; two stud term 1/2" h located on top, spaced 5/8" c to c; no int gnd connections; bkt mtg not supplied. NOTE: QOZ (2); TBL-8; TBL-9; WEA-1 (3).	RE48A110 RE13A488		16-C-46322-7716				CRV	72053-511	CRV CWT	P-720555-1aub2	TBL-4 MAR QBH QOZ (2) QCY (2) SEE NOTE
-481176-10	CAPACITOR, fixed: 10/18/40 NT-481176 w/250,000 mmf p/m 10%.	RE48A110 RE13A488		16-C-46343-7716	N16-C-11341			CRV	72053-561	CRV	P-720555-51	QOZ-2 QCY
-481177	CAPACITOR, fixed: 10/18/40 paper dielectric; 500,000 mmf plus 10 minus 3%; 1000 vdcw; HS metal can; case 1 7/8" lg x 1" wd x 2 1/8" h o/a; oil impr and filled; two ceramic line screw type term 1 1/8" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case ea two 0.213" diam mtg holes 13/16" apart 2 3/8" c to c.	RE48A159 RE13A488		16-C-47279-7242	N16-C-11360-16			CG	26F296	CRV	K-860217-11sub5	TBL-4
-481178	CAPACITOR, fixed: 10/20/40 mica; 30,000 mmf; 600 vdcw, 1,200v DC test; case 1 1/4" lg x 1 1/8" wd x 29/64" dia; molded bakelite case; two lug term ea w/ one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	RE48A221 JAN-C-5										
-481178-B2	CAPACITOR, fixed: 10/20/40 NT-481178 w/30,000 mmf p/m 2%; temp coef 1tr B. NOTE: MK-28; MK-10 Mod 5; MK-29 Mod 2; MK-34 Mod 3; MK-34 Mod 4.	RE48A221 JAN-C-5	CM50B303G	16-C-34720-4696	N16-C-10575-6			CSL CAN CD	XQBW.6-13-2 HL-1130 4L	CW		MK-9 MK-10 MK-18 MK-19 SEE NOTE
-481178-B5	CAPACITOR, fixed: 10/20/40 NT-481178 w/30,000 mmf p/m 5%; temp coef 1tr B.	RE48A221 JAN-C-5	CM50B303W	16-C-34725-6176	N16-C-10575-3		3DKA30-23	CSL CAN CD	XQBW.6-13-5 HL-1130 4L			Con't

SHEET 48-422

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 423

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481178-B10	CAPACITOR, fixed: 10/20/40 NT-481178 w/30,000 mmf p/m 10%; temp coef ltr B. NOTE: QCT-1; QFA-5 (2); QFA-6 (2); TAB-6 (13); TAB-7 (12); TCK; TUK-1 thru TUK-7; QFA-5 (2); QFA-6 (2).	RE48A221 JAN-C-5	CM50B303K	16-C-34730-6655	N16-C-10575-7			CSL CAN CD	DXQEW.6-13-10 HL-1130 4L	CDU CG CAY CAN	DD-3345-2 P-7762925-54 T-7606683-42 840599alt2	TAB-5 (13) QCS QCS-1 QCT SEE NOTE
-481178-B20	CAPACITOR, fixed: 10/20/40 NT-481178 w/30,000 mmf p/m 20%; coef ltr B.	RE48A221 JAN-C-5	CM50B303K	16-C-34735-9135	N16-C-10575-4			CSL CAN CD	DXQEW.6-13-20 HL-1130 4L			
-481179	CAPACITOR, fixed: 10/20/40 mica; 3,000 mmf; 2,500 vdcw, 7.1 amp at 3000 kc, 5.0 amp at 1000 kc, 3.0 amp at 300 kc, 1.5 amp at 100 kc; case 2 1/16" lg x 61/64" wd x 1 17/32" h; molded bakelite case; two screw term 7/16" lg, 1 1/2" c to c on top; two mtg pt on bottom, ea w/ hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-481179-003N2	CAPACITOR, fixed: 10/20/40 NT-481179 w/3,000 mmf p/m 2%; temp coef ltr 003N.	RE48A222 16C40		16-C-32189-3661				CAW	1570K-240	CAY	T-7606683-2	TAB-5 TAB-7 (2)
-481179-B10	CAPACITOR, fixed: 10/20/40 NT-481179 w/3,000 mmf p/m 10%; temp coef ltr B.	RE48A222 16C40		16-C-32199-4814				CD	645-151S	CBM CGG	744-479	TAB-1 (2)
-481179-D2	CAPACITOR, fixed: 10/20/40 NT-481179 w/3,000 mmf p/m 2%; temp coef ltr D.	RE48A222 16C40		16-C-32189-3656				CAW	1570K-240			TAB-5 TAB-6 (2)
-481179-D5	CAPACITOR, fixed: 10/20/40 NT-481179 w/3,000 mmf p/m 5%; temp coef ltr D.	RE48A222 16C40		16-C-32194-5136				CAW	1570K-240			
-481180	CAPACITOR, fixed: 10/20/40 mica; 8,500 mmf; 2,500 vdcw max, 8 amp at 3000 kc, 7 amp at 1000 kc, 5 amp at 300 kc, 2.6 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg pt w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A121 16C40										
-481180-003N2	CAPACITOR, fixed: 10/20/40 NT-481180 w/8,500 mmf p/m 2%; temp coef ltr 003N.	RE48A131 16C40		16-C-33349-9280				CAW	1550-K-177	CAY	T-7606683-64	TAB-5 TAB-6 TAB-7
-481180-D2	CAPACITOR, fixed: 10/20/40 NT-481180 w/8,500 mmf p/m 2%; temp coef ltr D.	RE48A131 16C40		16-C-33349-9277				CAW	1550-K-177			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-423

RESTRICTED

RESTRICTED

SHEET 48 - 424

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481181	CAPACITOR, fixed: 10/20/40 mica; 1,750 mmf; 8,000 vdcw max, 9 amp at 3000 kc, 9 amp at 1000 kc, 6 amp at 300 kc, 2 amp at 100 kc; case 3" lg x 2 3/8" wd x 2 7/8" h; molded bakelite case; two screw term 1" h on top #14-24 thd spaced 1 7/16" c to c; two mtg fl on bottom ea w/ three 17/64" diam holes on 13/16" x 3 9/16" mtg/c.	RE48A292 16C40										
-481181-B2	CAPACITOR, fixed: 10/20/40 NT-481181 w/1,750 mmf p/m 2%; temp coef 1tr B.	RE48A292 16C40		16-C-31636-7205	R16-C-10223-550			CSL	XEBW-8-2175-2	CAY	T-7606683-27	TAB-5 thru TAB-7
-481182	CAPACITOR, variable: 3/21/42 air; plate meshing type, single sect; 12 to 200 mmf; SLW; 0.018" air gap; 2 1/4" lg x 1 5/8" wd x 2" h, shaft 3/8" lg x 1/4" diam bushing; round shaft adj twenty seven plates; 180 deg rotation; isolantite ins; solder lug term; single hole mtg by mtg bushing; two 0.138"-32 thd holes 3/4" c to c, first hole 3/8" from front end.			16-C-61488-8347			3D9260V-15	CNA	STR-200	OW	ESA-682054-1	SJ
-481183	CAPACITOR, fixed: 10/20/40 mica; 40,000 mmf, 4,000 vdcw max, 5,700v DC test, 18 amp at 3000 kc, 22 amp at 1000 kc, 22 amp at 300 kc, 12 amp at 100 kc; case 3" lg x 2 3/8" wd x 2 7/8" h; molded bakelite case; two screw term 1" h on top #14-24 thd spaced 1 7/16" c to c; two mtg ft on bottom ea w/ three 17/64" diam holes on 13/16" x 13/16" x 3 9/16" mtg/c.	RE48A292 16C40										
-481183-B5	CAPACITOR, fixed: 10/20/40 NT-481183 w/40,000 mmf p/m 5%; temp coef 1tr B.	RE48A292 16C40		16-C-34991-1533	N16-C-10587			CSL CD	XEBW-4-14-5 30B	CAY	T-7606683-32	TAB-5 (4) TAB-6 (4) TAB-7 (4)
-481184	CAPACITOR, fixed: 10/20/40 mica; 50,000 mmf; 4,000 vdcw, 5,700v DC test, 18 amp at 3000 kc, 25 amp at 1000 kc, 22 amp at 300 kc, 12 amp at 100 kc; case 3" lg x 2 3/8" wd x 2 7/8" h; molded bakelite case; two screw term 1" h on top #14-24 thd spaced 1 7/16" c to c; two mtg ft on bottom ea w/ three 17/64" diam holes on 13/16" x 13/16" x 3 9/16" mtg/c.	RE48A292 16C40										
-481184-B5	CAPACITOR, fixed: 10/20/40 NT-481184 w/50,000 mmf p/m 5%; temp coef 1tr B.	RE48A292 16C40		16-C-35228-5133	N16-C-10596-10			CSL	XEBW-4-15-5	CAY	T-7606683-29	TAB-5 thru TAB-7

SHEET 48-424

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 425

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481185	CAPACITOR, fixed: 3/23/42 electrolytic; 40 mf; 25 vdcw; working temp range minus 20°C to plus 65°C; case 2 3/8" lg x 1" diam; metal case; top solder lug term 1/2" h on top; both term ins from can.	RE48A341 RE13A549		16-C-19906-6721	N16-C-9684-130 N16-RC-12096			CMA	MA-94632	CRV	M-253011-38ub1	SD-3 thru SD-5
-481186	CAPACITOR, fixed: 11/27/40 mica; 200 mf; 600 vdcw, 1,000v DC test; case 1 1/4" lg x 1 1/8" wd x 23/64" thk; molded bakelite case; two lug term ea w/ one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	RE48A221 16C40										
-481186-A2	CAPACITOR, fixed: 11/27/40 NT-481186 w/200 mf p/m 2%; temp coef ltr A.	RE48A221 16C40		16-C-29260-2791				CD	4-13020	CRR	A13753-4	ID-4
-481186-A10	CAPACITOR, fixed: 11/27/40 NT-481186 w/200 mf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-29270-4751				CD	4-13020			LR thru LR-3
-481186-B5	CAPACITOR, fixed: 11/27/40 NT-481186 w/200 mf p/m 5%; temp coef ltr B.	RE48A221 16C40		16-C-29265-4276	N16-C-9968-3			CD	4LS			
-481186-B10	CAPACITOR, fixed: 11/27/40 NT-481186 w/200 mf p/m 10%; temp coef ltr B.	RE48A221 16C40		16-C-29270-4756	N16-C-9968-1			CD	4LS			
-481187	CAPACITOR, fixed: 11/27/40 mica; 2,500 mf; 600 vdcw, 1000 vdcw; case 1 1/4" lg x 1 1/8" wd x 23/64" d; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam, 1 5/16" c to c.	RE48A221 16C40										
-481187-A10	CAPACITOR, fixed: 11/27/40 NT-481187 w/2,500 mf p/m 10%; temp coef ltr A. NOTE: LR-2; LR-3.	RE48A221 16C40		16-C-32013-7351				CD	4-12025			LR LR-1 SEE NOTE
-481187-B5	CAPACITOR, fixed: 11/27/40 NT-481187 w/2,500 mf p/m 5%; temp coef ltr B.	RE48A221 16C40		16-C-32008-6875	N16-C-10314-1			CD	4LS			
-481187-B10	CAPACITOR, fixed: 11/27/40 NT-481187 w/2,500 mf p/m 10%; temp coef ltr B.	RE48A221 16C40		16-C-32013-7355	N16-C-10315-1			CD	4LS			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48 - 425

RESTRICTED

RESTRICTED

SHEET 48 - 426

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MEGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481188	CAPACITOR, fixed: 11/27/40 mica; 3,000 mmf; 600 vdcw, 1,000v DC test; case 1 1/4" lg x 1 1/8" wd x 23/64" d; molded bakelite case; two lug term ea w/one 0.173" diam hole; two mtg holes in case 0.144" diam 1 5/16" c to c.	RE48A221 16C40										
-481188-A2	CAPACITOR, fixed: 11/27/40 NT-481188 w/3,000 mmf p/m 2%; temp coef ltr A.	RE48A221 16C40		16-C-32188-2191				CD	4-12030	CRR	A13753-12	LD-4
-481188-A10	CAPACITOR, fixed: 11/27/40 NT-481188 w/3,000 mmf p/m 10%; temp coef ltr A.	RE48A221 16C40		16-C-32193-4150			3DA3-4.1	CD	4-12030			LR thru LR-3
-481188-B10	CAPACITOR, fixed: 11/27/40 NT-481188 w/3,000 mmf p/m 10%; temp coef ltr B.	RE48A221 16C40		16-C-32198-4155	N16-C-10327-1	R16-C-10327-2		CD	WLS			
-481189	CAPACITOR, fixed: 12/17/40 paper dielectric; 25 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 3 7/8" lg x 4 5/8" wd x 4 3/8" h o/a; oil impr and filled; two ceramic ins screw type term 9/32" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 9/32" diam mtg holes 3 3/8" apart 4 1/2" c to c.	RE48A159 RE13A488		16-C-52407-5674				CG	25P257	CG	K-6683025-6rev2	TBC-3
-481190	CAPACITOR, fixed: 12/18/40 paper dielectric; 1 mf plus 10 minus 3%; 500 vdcw; HS metal can; case 1 15/16" h x 1 5/16" wd x 11/16" thk; pyranol impr and filled; two ins solder lug term 5/8" c to c on top; no int gnd connections; two integral mtg ft with a 5/32" wd slot in ea 1 15/16" c to c on top. NOTE: SP-1M (5); SX (13); TAJ-13; TAQ-10; TBA-11; TB X-4; TBI-4 a; TUX; MK-26 Mod 3 (2); MK-26 Mod 4 (2).	RE48A175 RE13A488		16-C-48795-1420	N16-C-11399		3DB1.4017-1	CG	23F115	CG	P-7763475-6rev2 K-3977153rev8 CO-842 K-885477-21	TBA-4 ORR RBD SC-2 (3) SK-2 (3) SK-3 (4) SP (4) SEE NOTE
-481190-2 1/2	CAPACITOR, fixed: 12/18/40 NT-481190 w/1 mf p/m 2 1/2%.			16-C-48766-1102				CG	23F115	CG	P-7763475-6	SC-2 (3) SC-3 (3)
-481190-10	CAPACITOR, fixed: 12/18/40 NT-481190 w/1 mf p/m 10%. NOTE: SO-12N (3); SO-4 (3); MK-22; MK-33 (3).			16-C-48815-9660	N16-C-11399-5			CG	23F115	CRM CRP CW CG	744-540 35-5152	RGA (4) SG-1 (2) SG-2S (2) SO-12M(3) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-426

RESTRICTED

RESTRICTED

SHEET 48 - 427

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481190-A	CAPACITOR, fixed: 9/3/43 CANCELLED: reassigned to NT-481190 on 10/18/44; 1 mf, 500 vdcw.							CG	23F115	CG	P-7763475-6rev8	TCX
-481190-A10	CAPACITOR, fixed: 9/3/43 CANCELLED: reassigned to NT-481190-10.											
-481190-B	CAPACITOR, fixed: 12/8/44 CANCELLED: reassigned to NT-481852; 1 mf, 500 vdcw; same as NT-481190 except for stronger bkt of different construction but with the same mtg/c.	RE48A325 RE13A488		16-C-48795-1420				CG	23F211	CG	K-44J334-1	
-481191	CAPACITOR, fixed: 12/18/40 paper dielectric; 10 mf plus 10 minus 3%; 600 vdcw, 1,200v DC test; HS metal can; case 3 7/8" lg x 1 1/4" wd x 4 3/4" h o/s; pyranol impr and filled; two solder lug term 21/64" h on bottom of case 2" c to c; no int gnd connections; two mtg fl 13/16" lg integral w/bottom of case w/four 0.213" diam mtg holes on 4 3/8" x 13/32" mtg/c.	RE48A137 RE13A488		16-C-51837-2598				CD CG CG	T-6100 25F241 25F223	CG CRV	K-6808231rev3 K-877681aub0	TBA-4 MK-1
-481191-10	CAPACITOR, fixed: 12/18/40 NT-481191 w/10 mf p/m 10%.	RE48A137 RE13A488		16-C-51858-2600	N16-C-11666			CD CG CG	T-6100 25F241GZ 25F223	CW CG CRV CG	K-8396342rev1 K-6808231rev3 K-877681aub0 K-34J722-2rev3	SC-3 (8) SK-3 (9)
-481192	CAPACITOR, fixed: 12/19/40 mica; 2,000 mmf; 2,500 vdcw max, 5.5 amp at 3,000 kc, 4.0 amp at 1,000 kc, 2.5 amp at 300 kc, 1.3 amp at 100 kc; case 2 1/16" lg x 61/64" wd x 1 17/32" h; molded bakelite case; two screw term 7/16" lg, 1 1/2" c to c on top; two mtg ft on bottom ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-481192-003N2	CAPACITOR, fixed: 12/19/40 NT-481192 w/2,000 mmf p/m 2%; temp coef 003N.	RE48A222 16C40		16-C-31793-6661				CAW	1570E-237	CAY	T-7606683-4	TAB-5 TAB-7 (2)
-481192-D2	CAPACITOR, fixed: 12/19/40 NT-481192 w/2,000 mmf p/m 2%; temp coef 1tr D.	RE48A222 16C40		16-C-31793-6698				CAW	1570E-237			
-481192-D5	CAPACITOR, fixed: 12/19/40 NT-481192 w/2,000 mmf p/m 5%; temp coef 1tr D.	RE48A222 16C40		16-C-31798-8136				CAW	1570E-237			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-427

RESTRICTED

RESTRICTED

SHEET 48 - 428

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG DR PART NO	EQUIPMENT USED IN
-481193	CAPACITOR, fixed: 12/19/40 mica; 3,500 mmf; 2,500 vdcw max, 10 amp at 3,000 kc, 8 amp at 1,000 kc, 5 amp at 300 kc, 2.3 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RB48A131 16C40										
-481193-003N2	CAPACITOR, fixed: 12/19/40 NT-481193 w/3,500 mmf p/m 2%; temp coef 1tr 003N.	RB48A131 16C40		16-C-32321-2602				CAW	1550-K-226	CAY	T-7606683-63	TAB-5 TAB-6 TAB-7
-481194	CAPACITOR, fixed: 12/19/40 mica; 5,000 mmf; 2,500 vdcw, 10 amp at 3,000 kc, 6.8 amp at 1,000 kc, 5.0 amp at 300 kc, 2.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg, 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RB48A131 16C40										
-481194-003N2	CAPACITOR, fixed: 12/19/40 NT-481194 w/5,000 mmf p/m 2%; temp coef 003N.	RB48A131 16C40		16-C-32690-5282				CAW	1550K-230	CAY	T-7606683-1	TAB-5 thru TAB-7
-481195	CAPACITOR, variable: 12/20/40 air; plate meshing type single sect; 3.5 to 26.8 mmf; SLC; 0.025" air gap; 7/8" lg x 15/16" wd x 1 7/32" h shaft 5/32" diam x 5/32" lg bushing 5/32" lg x 1/4"-32 thd, lock nut collar 9/32" diam x 7/32" lg; scdr adj; eleven cad pl brass plates; 360 deg rotation; inoalntite insulation; post term for stator, lug term for rotor on RH side; single hole mtg by 1/4" diam mtg bushing.			16-C-59254-6088				CHC	APC-250	CAG	1CA-13	IR thru IR-3

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-428

RESTRICTED

RESTRICTED

SHEET 48 - 429

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481196	CAPACITOR, variable: 12/20/40 air; plate meshing type single sect; 4 to 36.6 mmf; SIC; 0.025" air gap; 1 3/32" lg x 15/16" wd x 1 7/32" h shaft 5/32" diam x 5/32" lg bushing 5/32" lg x 1/4"-32 thd, lock nut collar 9/32" diam x 7/32" lg; scdr adj; fifteen cad pl brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on RE side; single hole mtg by 1/4" diam mtg bushing.			16-C-59507-2496	N16-C-12228-24			CHC	APC-35-C	CAG	1CA-14	LR LR-1 LR-2 LR-3
-481197	CAPACITOR, fixed: 12/30/40 ceramic dielectric; 25 mmf; neg temp coef 750 (tol p/m 120) mmf/mf/C; 500 vdcw; case 0.437" lg x 0.218" diam; axial wire leads; ceramic ins; add suffix indicating capacity tolerance in per cent.											
-481197-10	CAPACITOR, fixed: 12/30/40 NT-481197 w/25 mmf p/m 10%. NOTE: BL-1; BL-2; BL-3; BL-5; LR-1; LR-2; LR-3.			16-C-16222-5723	N16-C-8137-12	R16-C-7868-1		CER	N750K25p/m 2.5	CCI CAG	47K 462	LR ARD-2 (3) SEE NOTE
-481198	CAPACITOR, fixed: 1/11/41 mica; 6 mmf; 500 vdcw; case 51/64" lg x 15/32" wd x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148										
-481198-B5	CAPACITOR, fixed: 1/11/41 NT-481198 w/6 mmf p/m 5%; temp coef ltr B.	RE48A148 JAN-C-5	CM2CB060J	16-C-25255-8196				CD CAW CMR CSL	5WLS 1468LS OXM MOBW	CRV	P-720538-19rev30	TBT
-481196-D3	CAPACITOR, fixed: 1/11/41 NT-481198 w/6 mmf p/m 3%; temp coef ltr D.	RE48A148 16C40		16-C-25254-9623				CD CAW CMR CSL	SRS 1469 FO MOBIM	CHC	6151	RBG RBG-1 RBG-2
-481199	CAPACITOR, fixed: 2/4/41 mica; 90 mmf; 500 vdcw; case 51/64" lg x 15/32" wd x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148										Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-429

RESTRICTED

RESTRICTED

SHEET 48 - 430

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481199-D3	CAPACITOR, fixed: 2/4/41 NT-481199 w/90 mmf p/m 3%; temp coef 1tr D.	RE48A148 16C40		16-C-28367-5763		R16-C-9924-2-50		CAW CMR CER CD CSL CMF	1469 PO MLK90 SRS MOSEW 603M	CRV	P-721081-12rev27	
-481199-D5	CAPACITOR, fixed: 2/4/41 NT-481199 w/90 mmf p/m 5%; temp coef 1tr D.	RE48A148 JAN-C-5	CM20D900J	16-C-28368-4406	N16-C-9923-14	R16-C-9924-3		CAW CMR CER CD CSL CMF	1469 PO MLK90 SRS MOSEW 603M	CRV	P-720533-2rev30	DZ-1
-481200	CAPACITOR, fixed: 2/14/41 paper dielectric; 150,000 mmf plus 10 minus 3%; 4,000 vdcw, 1,3 v RMS working at 800 cyc; metal can; 3 7/8" lg x 2 5/16" wd x 3 1/2" h o/a; oil impr and filled; two ceramic ins screw type term 1 5/8" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 9/32" diam mtg holes 1 1/4" apart 4 1/2" c to c.	RE48A159 RE13A488		16-C-45934-9083								TAJ-10
481200-5	CAPACITOR, fixed: 2/14/41 NT-481200 w/150,000 mmf p/m 5%.	RE48A159 RE13A488		16-C-45933-9083				CC	25F279	CC	M-7464792-2sub6	
481201	CAPACITOR, fixed: 2/27/41 ceramic dielectric; 135 mmf; var temp coef 0 to minus 60 mmf/mf/C; 500 vdcw, 1000v DC test, 1100v RMS 60 cyc test; case 1.3" lg x 0.35" max diam; radial wire leads; uninsulated; add suffix indicating capacity tolerance in per cent.											
-481201-1	CAPACITOR, fixed: 2/27/41 NT-481201 w/135 mmf p/m 1%.			16-C-17289-8433				CBN	Type B	CRP	A100272-1350rev1	LD-4
-481202	CAPACITOR, fixed: 2/27/41 ceramic dielectric; 160 mmf; var temp coef 0 to minus 60 mmf/mf/C; 500 vdcw, 1000v DC test, 1100v RMS 60 cyc test; case 1.3" lg x 0.35" max diam; radial wire leads; uninsulated; add suffix indicating capacity tolerance in per cent.											
-481202-1	CAPACITOR, fixed: 2/27/41 NT-481202 w/160mmf p/m 1%			16-C-17449-8431				CBN	Type B	CRP	A100272-161rev1	LD-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-430

RESTRICTED

RESTRICTED

SHEET 48 - 431

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USES IN
-481203	CAPACITOR, fixed: paper dielectric; 50,000 mmf plus 10 minus 3%; 1,000 vdcw; HS metal case; case 1 13/16" lg x 1" wd x 3/4" h o/a; oil impr and filled; two solder lug term 3/4" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c.	2/27/41 RE13A488 RE48A129		16-C-44239-7092				CD	DYR-10005			TCQ
-481203-1	CAPACITOR, FIXED: Navy Type 481203 w/50000 mmf p/m 1%.	8/29/47		16-C-44206-1090				CD	DYR-10005			48A-1
-481203-10	CAPACITOR, fixed: NT-481203 w/50,000 mmf p/m 10%.	2/27/41 RE13A488 RE48A129		16-C-44260-7092	N16-C-11165			CD CGF CIE	DYR-10005 7500 6BA05	CRP CTE	S-35-5126 1#e1 10.73	DAS-1 DAS-3
-481204	CAPACITOR, FIXED: electrolytic; 1 sect; 50 mfd; 25 vdcw; working temp range approx minus 20°C to plus 65°C; approx 1 7/16" lg x 5/8" diam, excluding term; tubr aluminum case w/cardboard sleeve; 2 axial wire leads approx 3" lg; neg term int gnd.	2/27/41 RE48A340 RE13A549		16-C-19956-4721			3DBB50-18	CD	BR-502	CDU	3-2	OBL-1
-481205	CAPACITOR, fixed: electrolytic; 10 mf; 50 vdcw; worki g temp range minus 20°C to plus 65°C; case 1 7/16" lg x 5/8" diam; HS metal case w/cardboard sleeve; two axial wire leads 3" lg; neg term gnd internally.	2/27/41 RE48A340 RE13A549			N16-C-9668-5			CD	BR-105			TCQ
-481206	CAPACITOR, fixed: electrolytic; 8 mf; 250 vdcw; working temp range minus 20°C to plus 65°C; case 1 7/16" lg x 5/8" diam; HS metal case w/ cardboard sleeve; two axial wire leads 3" lg; neg term gnd internally.	2/27/41 RE48A340 RE13A549		16-C-19540-7161	N16-C-9664		3DBB-18	CD	BR-825			TCQ
-481207	CAPACITOR, variable: ceramic; rotary type, single sect; 6 to 30 mmf; 500 vdcw; temp coef minus 600 mmf/mfd/°C p/a 15%; 0.835" lg x 0.61" wd x 0.276" h; solder lug term at right angle bend; two holes 0.117" diam on 0.375" mtg/c; scdr slot adj; ceramic base.	2/27/41		16-C-64090-2153				CBN	820C size 6-30			TCQ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-431

RESTRICTED

RESTRICTED

SHEET 48 - 432

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481208	CAPACITOR, variable: 2/27/41 ceramic dielectric; rotary type, 1 sect; 3 to 12 mmf; 1,500 vac peak; neg temp coef 600 (tol p/m 90) mmf/mf/°C; 0.835" lg x 0.61" wd x 0.276" h; two solder lug term; two 0.117" diam holes 0.375" c to c; sodr slot adj; ceramic base.			16-C-63939-9623	N16-C-12558-10			CBN	820-B			TCQ
-481209	CAPACITOR, variable: 2/27/41 air; plate meshing type single sect; 5.6 to 100 mmf; SLC; 0.015" air gap; 1 11/32" lg x 1 5/16" wd x 1 9/32" h shaft 1/4" diam x 1/2" lg bushing 9/32" lg x 5/16"-32 thd; round shaft; twenty-seven cad pl brass plates; 360 deg rotation; isolantite insulation; post term for stator, lug term for rotor on LH side; single hole mtg by 5/16" diam bushing or base mtg by means of bkt 1/2" wd w/one #6-32 tapped hole ctr.			16-C-60642-4331	N16-C-12241			CRC	HF-100			TCQ
-481209-A	CAPACITOR, variable: 2/8/44 air; plate meshing type single sect; 5.6 to 100 mmf; SLC; 0.015" air gap; 1 3/8" lg x 1 5/16" wd x 1 3/16" h shaft 1/4" diam x 2 19/32" lg w/end 1/32" x 45° chamfer bushing 13/32" lg x 5/16"-32 thd; round shaft; twenty-seven dull nickel pl brass plates; 360 deg rotation; ceramic base; post term for stator, lug term for rotor on RH side; single hole mtg by 5/16" diam bushing, two 1/8" diam holes in base on 1" mtg/c.			16-C-60642-4361				CBC	HF-100	CRV	W-306509-253rev4	QGB
-481210	CAPACITOR, variable: 2/27/41 air; plate meshing type, dual sect; 8 to 140 mmf ea sect; SLC ea sect; 0.0245" air gap; 3 3/8" lg x 1 1/2" wd x 1 7/8" h shaft 1/4" diam x 1/2" lg bushing 7/16" lg x 3/8"-32 thd; round shaft adj; nineteen cad pl brass plates ea sect; clockwise rotation; isolantite ins; solder lug term; single hole mtg by 3/8" diam mtg bushing.			16-C-62762-1526				CRC	MOD-140-S			TCQ

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-432

RESTRICTED

RESTRICTED

SHEET 48 - 433

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481211	CAPACITOR, variable: 2/27/41 air; plate meshing type, three sect; 6.8 to 140 mmf ea sect; SLC ea sect; 1" wd x 1 1/2" h shaft 1/4" diam x 1/2" lg bushing 5/16" lg x 5/16"-32 thd; round shaft adj; thirty-seven cad pl brass plates ea sect; isolantite ins; solder lug term.			16-C-63229-1001				CRG	HFD epcl			TCQ
-481212	CAPACITOR, fixed: 3/10/41 paper dielectric; 500,000 mmf plus 10 minus 3%; 400 vdcw, 1,000v DC test; HS metal can; case 2 3/16" lg x 1 1/16" diam; byvol impr and filled; two axial wire leads; no int gnd connections; radial mtg strap w/ two 5/32" diam holes 7/32" c to c.	RE48A162 REL3A488										
-481212-10	CAPACITOR, fixed: 3/10/41 NT-481212 w/500,000 mmf p/m 10%.	RE48A162 REL3A488		16-C-47294-1927			3DA500-56.1	CAW	489	CES CTH CAW	V12-220-3353revo 15398	RBE OAY(4)
-481213	CAPACITOR, fixed: 3/20/41 mica; 1,200 mmf; 2,000 vdcw max, 5.0 amp at 3,000 kc, 3.0 amp at 1,000 kc, 1.6 amp at 300 kc, 0.8 amp at 100 kc; case 2 1/16" lg x 61/64" wd x 1 17/32" h; molded bakelite case; two screw term 7/16" lg 1 1/2" c to c on top; two mtg ft on bottom, ea w/hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-481213-A5	CAPACITOR, fixed: 3/20/41 NT-481213 w/1,200 mmf p/m 5%; temp coef ltr A.	RE48A222 16C40		16-C-31271-1025				CD	FL-929-15			
-481213-F2	CAPACITOR, fixed: 3/20/41 NT-481213 w/1,200 mmf p/m 2%; temp coef ltr F.	RE48A222 16C40		16-C-31265-8571	N16-C-10165			CD	FL-929-15H	COL	T-7606408-3	TBW TEW-1 TCB-2
-481214	CAPACITOR, fixed: 4/16/41 mica; 100 mmf; 7,500 vdcw max, 1.3 amp at 3,000 kc, 0.5 amp at 1,000 kc, 0.3 amp at 300 kc, 0.1 amp at 100 kc; case 2 5/16" lg x 1 17/64" x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" mtg holes 2 5/8" c to c.	RE48A131 16C40										Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-433

RESTRICTED

RESTRICTED

SHEET 46 - 434

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481214-A5	CAPACITOR, fixed: NT-481214 w/100 mmf p/m 5%; temp coef ltr A. NOTE: TBK-16; TEM-5; TEM-8; TEM-12.	4/16/41 RE48A131 16040		16-C-28955-5485	N16-C-9942-9			CD CAW	FL-321-6P 1550-318	CAY CAY CAY	7607281-80 T-7605005-16 T-7606970-80 T-7606233-34	TEM-6 TBK-11 TBK-5 TBK-15 SEE NOTE:
-481215	CAPACITOR, fixed: mica; 500 mmf; 7,500 vdcw max, 4 amp at 3,000 kc, 3 amp at 1,000 kc, 1.5 amp at 300 kc, 0.5 amp at 100 kc; case 2 5/16" lg x 1 17/64" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg c to c; two mtg ft w/two 3/16" diam mtg hole 2 5/8" c to c.	4/16/41 RE48A131 16040										
-481215-A5	CAPACITOR, fixed: NT-481215 w/500 mmf p/m 5%; temp coef ltr A. NOTE: TBK-15; TEM-5; TEM-7; TEM-10; TEM-12.	4/16/41 RE48A131 16040		16-C-30164-5885	N16-C-10024-35			CD CAW	PL-592-6P 1550-335	CAY CAY CAY	7607280-54 T-7606117-478 T-7607093-54 T-7606233-35	TBK-11 TEM-6 TBK-1 TBK-13 SEE NOTE:
-481216	CAPACITOR, fixed: mica; 1,000 mmf; 5,300 vdcw effective, 7 amp at 3,000 kc, 4 amp at 1,000 kc, 2 amp at 300 kc, 1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two mtg holes 2 5/8" c to c.	4/16/41 RE48A131 16040										
-481216-A5	CAPACITOR, fixed: NT-481216 w/1,000 mmf p/m 5%; temp coef ltr A. NOTE: TBK-16; TEM-8; TEM-12; TEM-15.	4/16/41 RE48A131 16040		16-C-31087-7862				CD	PL-246-6P	CAY CAY CAY	7607280-63 T-7605026-347 T-7607093-63	TBK-11 TBK-6 TBK-15 SEE NOTE:
-481216-B5	CAPACITOR, fixed: NT-481216 w/1,000 mmf p/m 5%; temp coef ltr B.	4/16/41 RE48A131 16040		16-C-31087-7865	N16-C-10099			CD	PL-246-6P			
-481217	CAPACITOR, fixed: mica; 100 mmf; 500 vdcw, 1000 vdcw; case 1 1/16" lg x 15/32" wd max x 7/32" thk max; molded bakelite case; two axial wire leads.	4/22/41 RE48A233 JAN-C-5										

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900109(A)
SUPPLEMENT # 1

SHEET 48-434

RESTRICTED

RESTRICTED

SHEET 48 - 435

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481217-B20	CAPACITOR, fixed: 4/22/41 NF-481217 w/100 mmf p/m 20%; temp coef ltr B.	RE48A233 JAN-C-5	CM25B101M	16-C-28563-4552	N16-C-9923-45			CD CAW CFW	2R 1478L BSC			
-481217-D2	CAPACITOR, fixed: 4/22/41 NF-481217 w/100 mmf p/m 2%; temp coef ltr D.	RE48A233 JAN-C-5	CM25D101G	16-C-28547-9122	N16-C-9923-41			CD CAW CFW	2R 1479 BSC	CRP	35-5023	SG-1 (2) SG-2S (2)
-481217-D5	CAPACITOR, fixed: 4/22/41 NF-481217 w/100 mmf p/m 5%; temp coef ltr D.	RE48A233 JAN-C-5	CM25D101J	16-C-28553-1602	N16-C-9923-43		3K2510142	CD CAW CFW	2R 1479 BSC	CG CW	M-7465676-14rev0	ME-1 ME-2 ME-3 ME-4
-481217-D10	CAPACITOR, fixed: 4/22/41 NF-481217 w/100 mmf p/m 10%; temp coef ltr D.	RE48A233 JAN-C-5	CM25D101K	16-C-28558-2082	N16-C-9923-44			CD CAW CFW	2R 1479 BSC			
-481217-E2	CAPACITOR, FIXED: 3/26/48 Navy Type 481217 w/100 mmf p/m 2%; temp coef letter E.	JAN-C-5	CM25E101G	16-C-28547-9127								TEM TEM-1
-481218	CAPACITOR, fixed: 4/21/41 mica; 700 mmf; 500 vdcw, 1000 vdc; case 1 1/16" lg x 15/32" wd max x 7/32" thk max; molded bakelite case; two axial wire leads.	RE48A233										
-481218-B10	CAPACITOR, FIXED: 3/3/49 Navy Type 481218 w/700 mmf p/m 10%; temp coef letter B.	RE48A233		16-C-30589-2872								AN/UFA-16 (XN-21)
-481218-D1	CAPACITOR, fixed: 4/21/41 NF-481218 w/700 mmf p/m 1%; temp coef ltr D.	RE48A233 16C40		16-C-30578-2610	N16-C-10067-7			CD CAW CFW	2R 1479 BSC	CG CW	M-7465676-15rev0	ME-1 thru ME-4
-481218-D5	CAPACITOR, fixed: 4/21/41 NF-481218 w/700 mmf p/m 5%; temp coef ltr D.	RE48A233 JAN-C-5	CM25D701J	16-C-30584-2402	N16-C-10067-9			CD CFW CAW	2R BSC 1479	CTR		OAY (2)
-481219	CAPACITOR, fixed: 4/22/41 mica; 800 mmf; 500 vdcw, 1000 vdc; case 1 1/16" lg x 15/32" wd max x 7/32" thk max; molded bakelite case; two axial wire leads.	RE48A233										
-481219-D1	CAPACITOR, fixed: 4/22/41 NF-481219 w/800 mmf p/m 1%; temp coef ltr D.	RE48A233 16C40		16-C-30683-7210	N16-C-10072-35			CD CAW CFW	2R 1479 BSC	CG CW	M-7465675-16rev0	ME-1 ME-2 ME-3 ME-4
-481219-D2	CAPACITOR, fixed: 4/22/41 NF-481219 w/800 mmf p/m 2%; temp coef ltr D.	RE48A233 JAN-C-5	CM25D801G	16-C-30684-5522	N16-C-10072-36			CD CAW CFW	2R 1479 BSC			Con't

SHEET 48-435

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 436

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481219-D5	CAPACITOR, fixed: 4/22/41 NT-481219 w/800 mmf p/m 5%; temp coef ltr D.	RE48A233 JAN-C-5	CM25D81J	16-C-30689-7002				CD CAW CFW	2R 1479 BSC	CBM CPN	744-229a1.10 C-1224	RCD
-481219-D10	CAPACITOR, fixed: 4/22/41 NT-481219 w/800 mmf p/m 10%; temp coef ltr D.	RE48A233 JAN-C-5	CM25D801K	16-C-30694-7482	N16-C-10072-55			CD CAW CFW	2R 1479 BSC			
-481220	CAPACITOR, FIXED: 4/22/41 mica dielectric; 100 mmf; 300 vdcw; 1 1/4" lg x 9/16" wd x 3/8" h case incl term; metal case; 2 tab term 1 ea end, bent at 90 deg angle w/hole at end, also 1 tab type term 1 side w/5/32" hole at end; 2 end term are common.	RE48A249 16C40										
-481220-B2	CAPACITOR, FIXED: 6/25/45 Navy Type 481220 w/100 mmf p/m 2%; temp coef ltr B.	RE48A249 16C40		16-C-28547-8104				CD	742			
-481220-B10	CAPACITOR, fixed: 4/22/41 NT-481220 w/100 mmf p/m 10%; temp coef ltr B. NOTE: ME-3; ME-4.	RE48A249 16C40		16-C-28558-1078	N16-C-9923-18		3D9100-91	CD	742	CAT CW	160-TX	MK-1 MK-2 SEE NOTE
-481221	CAPACITOR, fixed: 4/22/41 mica; 115,000 mmf; 2,000 vdcw max, 15 amp at 3,000 kc, 20 amp at 1000 kc, 20 amp at 300 kc, 20 amp at 100 kc; case 3" lg x 2 7/16" wd x 2 7/8" h; cast metal case; two screw term 1" h on top spaced 1 7/16" connected to one side of cap, other side gnd to case; three mtg ft on bottom ea w/17/64" diam hole, two on one side spaced 1 5/8" c to c and 3" from ctr of mtg hole on other side.	RE48A124 16C40										
-481221-A5	CAPACITOR, fixed: 4/22/41 NT-481221 w/115,000 mmf p/m 5%; temp coef ltr A.	RE48A124 16C40		16-C-36297-3673				CD	PL-1150-30B			
-481221-E2	CAPACITOR, fixed: 4/22/41 NT-481221 w/115,000 mmf p/m 2%; temp coef ltr E. NOTE: ME-3; ME-4.	RE48A124 16C40		16-C-36297-3439	N16-C-10703			CD	PL-1150-30B	CW		MK-1 MK-2 SEE NOTE
-481222	CAPACITOR, fixed: 4/22/41 mica; 400,000 mmf; 600 vdcw, 1200v DC test, 18 amp at 3,000 kc, 25 amp at 1,000 kc, 22 amp at 300 kc, 12 amp at 100 kc; case 3" lg x 2 7/16" wd x 2 7/8" h; cast metal case; two screw term 1" h on top spaced 1 7/16" connected to one side of capacitor, other side gnd to case; three mtg ft on bottom ea w/ 17/64" diam hole, two on one side spaced 1 5/8" c to c and 3" from ctr of mtg hole on other side.	RE48A124 16C40										Cont

SHEET 48-436

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 437

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481222-A5	CAPACITOR, fixed: NT-481222 w/400,000 mmf p/m 5%; temp coef 1tr A.	4/22/41 RE48A124 16C40		16-C-37521-7271				CD	PL-1110-30B	CD	4622 rev0	
-481222-E5	CAPACITOR, fixed: NT-481222 w/400,000 mmf p/m 5%; temp coef 1tr E. NOTE: MK-3; MK-4.	4/22/41 RE48A124 16C40		16-C-37521-7276	N16-C-10720			CD	PL-1110-30BH	CW CD	4622rev0	MK-1 MK-2 SEE NOTE
-481223	CAPACITOR, fixed: paper dielectric; 500,000 mmf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1" wd x 7/8" h o/a; oil impr and filled; two solder lug term 3/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/ 3/16" diam mtg holes spaced 2 1/8" c to c. NOTE: QFN (4); RAX-1; SD-3; TCC (3); MK-11 Mod 1; MK	4/22/41 RE13A488 RE48A129 -26 Mod 3; MK-26 Mod 4.		16-C-47276-3114	N16-C-11351-2		3DA500-263	CD CIE CBV CIE CSF CAW CSL	DVR-6050 8611 A-7147 6BA50 2528 630 XIMRW6-.5	CG CG CAY CIA CRV CG COL	M-7465899-4rev2 K-7890505-1 8-D-2577-3sub2 D-5507-38 M-422765-1 M-7464514-4rev2	MK-1 MK-2 JM-4 (3) OAA OAF OAO OAO-1 SEE NOTE
-481223-5	CAPACITOR, fixed: NT-481223 w/500,000 mmf p/m 5%.	4/22/41 RE48A129 RE13A488		16-C-47245-3125	N16-C-11351-1			CD	DYR-6050	CRP	35-5054	VD (3) VD-1 (3)
-481223-6	CAPACITOR, fixed: NT-481223 w/500,000 mmf p/m 6%.	4/22/41 RE48A129 RE13A488		16-C-47266-9810				CD	DYR-6050			TCX RBD
-481223-10	CAPACITOR, fixed: NT-481223 w/500,000 mmf p/m 10%.	4/22/41 RE13A488 RE48A129		16-C-47297-3124	N16-C-11351		3DA500-394	CBW CD CSF CIE CBV CCF CIE CSL CAW CIB	DYR-6050 PPTS-364A 8611 12M-4-20 A-7147 7503 6BA50 XIMRW6-5-10 630-5 RLO-650	CRP CG CG COL CRV CRR CML CAY CM CFE CW CBM COL	35-5054 K-347920-1rev0 K-432251-3 956 0005 00 revD8597 0A30879-1revC 26120 8D2577-3sub2 CC-20187revA 10.64 ESA-682063-65 744-294 744-190 956 2088 20 rev9/4/40	DAS-1 (9) DAS-3 QAA SG-1 (3) SG-2S (3) SJ-1 (4) SL (3) SL-a (6) SL-1 (6) SM (5) SM-1 (5) SO SO-a SO-3 SO-7M SEE NOTE
	NOTE: SO-7N; SO-9; SO-13; SP-1M (2); SS (2); ST (2); YL; AN/TPS-1B (2); RDZ; TS-34A/AP (2); MK-8 Mod 2 (2); MK-10 Mod 5 (2); MK-8 (3); MK-8 Mod 1 (3); MK-16 (5);	SU (5); SV 1 (2); TDE (4); TDE-1 (4); TDE-3 (4); TDE-4 (4); MK-13 Mod 0 (3); MK-8 Mod 3 (3); MK-9 (4); MK-10 (2); MK-18 (4); MK-19 (5); MK-22; MK-27 (5).										Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-437

RESTRICTED

RESTRICTED

SHEET 48 - 438

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S OR PART NO	BWG	EQUIPMENT USED IN
-481223-20	CAPACITOR, fixed: NT-481223 w/500,000 mmf p/m 20%.	4/22/41 RE13A488 RE13A129		16-C-47327-7468	N16-C-11354-100			CD CIE CBV CSF	DYR-6050 0611 A-7147 P8296	COL CAM CG CO:	956 0006 00 rev 8/5/57 744-644 956 2038 40 rev 9/4/40		SU-1 (7) SX TCZ (2) TCZ-1 (2) TCZ-2 (2)
-481224	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 1000 vdcw; cylindrical metal can; case 1 1/2" diam x 4 1/2" lg; dykanol impr end filled; one #10-32 thd term stud and one solder lug term on bottom; int gnd; one 3/4"-16 thd mtg stud 1/2" lg on bottom.	4/22/41 RE48A207 RE13A488		16-C-49180-4112				CD	TLA-10020				
-481224-10	CAPACITOR, fixed: NT-481224 w/2 mf p/m 10%.	4/22/41 RE48A207 RE13A488		16-C-49201-4112	N16-C-11490-30			CD	TLA-10020	CW			MK-1 MK-2 SEE NOTE
-481224-20	CAPACITOR, fixed: NT-481224 w/2 mf p/m 20%.	4/22/41 RE48A207 RE13A488		16-C-49230-3350				CD	TLA-10020				
-481225	CAPACITOR, fixed: paper dielectric; 3 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" wd x 3 7/8" h; dykanol impr and filled; two por ins screw type term 7/8" h located on top, spaced 13/16" c to c; no int gnd connections; strap mtg not supplied.	4/22/41 RE48A139 RE13A488		16-C-49556-3119				CD	T-6030				MK-1 MK-2
-481226	CAPACITOR, fixed: paper dielectric; 5 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 1 13/16" lg x 1 1/16" w x 4 3/4" h; oil impr and filled; two por ins screw type term 7/8" h located on top, spaced 13/16" c to c; no int gnd connections; strap mtg not supplied.	4/22/41 RE48A139 RE13A488		16-C-50316-3124				CD	T-6050				MK-1 MK-2
-481226-10	CAPACITOR, fixed: NT-481226 w/5 mf p/m 10%.	4/22/41 RE48A139 RE13A488		16-C-50337-3094	N16-C-11606		3DM5-14.1	CD	T-6050	CRP	S-35-52731a01		VF (17)
-481227	CAPACITOR, fixed: paper dielectric; 15 mf plus 10 minus 3%; 1000 vdcw; HS metal can; case 3 3/4" lg x 2 1/2" wd x 4 3/4" h; dykanol impr and filled; two por ins screw type term 7/8" h located on top, spaced 2" c to c; no int gnd connections; strap mtg not supplied.	4/22/41 RE48A139 RE13A488		16-C-52030-2442				CD	T-10150				MK-1 MK-2
-481227-10	CAPACITOR, FIXED: Navy Type 481227 w/15 mfd p/m 10%.	1/26/48		16-C-52051-2342				CD	T-10150	CBZ	CO-918		BM BO SM

SHEET 48-438

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 439

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A B O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481228	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 2000 vdcw, 4000v DC test; HS metal can; case 2 1/2" lg x 1 3/16" wd x 3 3/8" h; pyranol impr and filled; two por ins screw type term 1 1/4" h located on top, spaced 1 1/8" c to c; no int grd connection; strap mtg not supplied. NOTE: DAK-2; DAK-4; QCC; QCD; JK-2B; JK-5; TAJ-11; TAJ-13 thru TAJ-19; MK-11 Mod 1; ME-26 Mod 3.	4/22/41 RE48A139 RE13A488		16-C-48803-3963	N16-C-11437			CD CG	T-20010 23P117	CG CFT CBM CRV	P-7763477-1rev1 NCP-9-4 744-120	MK-1 MK-2 DAH DAH-2 DAK DAK-1 MK-26 Mod 4 SEE NOTE
-481228-10	CAPACITOR, fixed: NT-481228 w/1 mf p/m 10%. NOTE: DAU-1; FA; MK-8; MK-8 Mod 1; ME-9; MK-10; MK-10 Mod 5; MK-16 (3); ME-16	4/22/41 R 48A139 RE13A488		16-C-48824-3968	N16-C-11437		3DB1.2009	CD	T-20010	CFT CW	RF-2209-1	DAJ DAU SEE NOTE
-481229	CAPACITOR, fixed: paper dielectric; 3 mf plus 10 minus 3%; 2000 vdcw; HS metal can; case 3 3/4" lg x 1 1/4" wd x 4 3/4" h; dykanol impr and filled; two por ins screw type term 1 1/4" h located on top, spaced 2" c to c; no int grd connections; strap mtg not supplied.	4/22/41 RE48A139 RE13A488		16-C-49563-5938				CD	T-20030			MK-1 ME-2
-481230	CAPACITOR, fixed: paper dielectric; 1 mf plus 10 minus 3%; 10,000 vdcw; HS metal can; case 8" lg x 4" wd x 11" h; dykanol "A" impr and filled; two por ins screw type term 3 7/16" h located on top, spaced 4 1/2" c to c; no int grd connections; strap mtg not supplied; spl low inductance construction.	4/22/41 RE48A139 RE13A488		16-C-48805-9688	N16-C-11437-13-5							MK-1 MK-2
-481230-5	CAPACITOR, fixed: NT-481230 w/1 mf p/m 5%.	4/22/41 RE48A139 RE13A488		16-C-48784-9687				CD	TK-10010-1			
-481231	CAPACITOR, variable: air; plate meshing type single sect; 6.3 to 34 mmf; SLC; 0.0245" air gap; 1 23/32" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 1/2" lg bushing 13/32" lg x 3/8"-32 thd; rounded shaft adj; five cad pl brass plates; clockwise rotation; isolantite ins; lug term; single hole mtg by 3/8" diam mtg bushing or base mtg by two mtg feet ea w/one #6-32 tapped holes on 1 7/32" mtg/c.	4/23/41		16-C-59370-9932	N16-C-12226-1-2	R16-C-11922-572		CHC	MC-35-S	CHC	9907 rev 0	FA FB ME-3 MK-4

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-439

RESTRICTED

RESTRICTED

SHEET 48 - 440

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481232	CAPACITOR, variable: 4/23/41 air; plate meshing type, single sect; 4.5 to 75 mmf; SLC; 0.015" air gap; 1 1/4" lg x 15/16" wd x 1 3/16" h shaft assembled w/nut and bushing 1/4" diam x 5/16" lg o/a; scdr adj; twenty cad pl brass plates; 360 deg rotation; isolantite ins; post term for stator; lug term for rotor; two mtg studs 3/32" lg w/#4-40 tapped 21/32" c to c. NOTE: MK-4; MK-12; MK-12 Mod 1.			16-C-60282-1541	R16-RC-14595	R16-C-11914-5		CHC	APC-75	CPT COL CAJTR CW CRV CRC	922 3900 00rev0 A-44-1 1aaA ESA-682070-9 1aa24 MX-242109-4 9906rev0	DAH (2) TCB-1 TCB-2 SA-2 TS-202 MK-1 MK-2 MK-3 SEE NOTE
-481233	CAPACITOR, variable: 4/29/41 air; plate meshing type single sect; 10 to 140 mmf; SLC; 0.0245" air gap; 2 1/16" lg x 1 11/16" wd x 1 11/16" h; shaft 1/4" diam x 1/2" lg bushing 7/16" lg x 3/8"-32 thd; rounded shaft adj; nineteen dull nickle pl brass plates; clockwise rotation; isolan- tite ins; lug term, stator term in front; single hole mtg by 3/8" diam mtg bushing or base mtg by 2 mtg ft ea w/one #6-32 tapped hole on 1 19/32" mtg/c.			16-C-61102-7076				CHC CMI	MC-140-S 50-216-2	CRV CRV CRM	W-303335-26sub1 K-634539-2rev6 744-306	NMB-1 QFB QFB-1
-481233-A	CAPACITOR, variable: 4/29/41 air; plate meshing type single sect; 10 to 140 mmf; SLC; 0.0245" air gap; 2 1/16" lg x 1 11/16" wd x 1 11/16" h shaft 1/4" diam x 1/2" lg bushing 7/16" lg x 3/8"-32 thd; scdr adj; 19 dull nickle pl brass plates; clockwise rotation; isolantite ins; lug term, stator term in front; single hole mtg by 3/8" diam mtg bushing or base mtg by 2 mtg ft ea w/one #6-32 tapped hole on 1 19/32" mtg/c.			16-C-61102-7096				CHC	MC-140-S Modified	CRV	W-303335-27sub1	NMB-1
-481234	CAPACITOR, fixed: 4/29/41 mica; 190 mmf; 500 vdcw, 1000v DC test; case 51/64" lg max x 15/32" wd max x 7/32" d max; molded bakelite case; two axial wire leads.	RE48A148 JAN-C-5										
-481234-D2	CAPACITOR, fixed: 4/29/41 NT-481234 w/190 mmf p/m 2%; temp coef 1tr D.	RE48A148 JAN-C-5	CH20P1910	16-C-29207-3726	N16-C-9966-14			CAW CMR CER CE CSL	1469 P M3K-19 SRS MOSIW	CRV	P-720537-11 rev19	NMB-1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-440

RESTRICTED

RESTRICTED

SHEET 48 - 441

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN		
-481235	CAPACITOR, fixed: 5/1/41 ceramic dielectric; 195 mmf; zero temp coef (tol plus 0 minus 2) mmf/mf/°C; 500 vdcw; case 1.3" lg x 0.35" max diam; radial wire leads; uninsulated; add suffix indicating capacity tolerance in per cent.													
-481235-1	CAPACITOR, fixed: 5/1/41 NT-481235 w/195 mmf p/m 1%.			16-C-17670-1087						CEN	B	CG	K-7879219-1rev0	TCM TCN
-481236	CAPACITOR, fixed: 5/1/41 mica; 1,250 mmf; 2,500 max vdcw, 5.5 amp at 3,000 kc, 3.0 amp at 1,000 kc, 0.9 amp at 300 kc, 0.3 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40												
-481236-001N2	CAPACITOR, fixed: 5/1/41 NT-481236 w/1,250 mmf p/m 2%; temp coef 001N.	RE48A131 16C40		16-C-31318-8443						CD	PL-1200-6K	CG	F-7762161-4rev3	TCG
-481237	CAPACITOR, fixed: 5/1/41 mica; 1,850 mmf; 2,500 max vdcw, 6 amp at 3,000 kc, 3.5 amp at 1,000 kc, 1.1 amp at 300 kc, 0.4 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40												
-481237-001N2	CAPACITOR, fixed: 5/1/41 NT-481237 w/1,850 mmf p/m 2%; temp coef 001N.	RE48A131 16C40		16-C-31712-9411						CD	PL-1201-6K	CG	F-7762161-5rev3	TCG
-481238	CAPACITOR, fixed: 5/1/41 mica; 2,750 mmf; 2,500 vdcw max, 6 amp at 3,000 kc, 4 amp at 1,000 kc, 1.6 amp at 300 kc, 0.6 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40												
-481238-001N2	CAPACITOR, fixed: 5/1/41 NT-481238 w/2,750 mmf p/m 2%; temp coef 001N.	RE48A131 16C40		16-C-32158-2255						CD	PL-1202-6K	CG	F-7762161-6rev3	TCG

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-441

RESTRICTED

RESTRICTED

SHEET 48 - 442

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481239	CAPACITOR, fixed: 5/1/41 mica; 4,150 mmf; 1,050 vdcw RMS, 1,500v RMS test, 6 amp at 3,000 kc, 5 amp at 1,000 kc, 2.3 amp at 300 kc, 0.8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481239-001N2	CAPACITOR, fixed: 5/1/41 NT-481239 w/4,150 mmf p/m 2%; temp coef 001N.	RE48A131 16C40		16-C-32479-1656				CD	PL-1203-6K	CG	P-7762161-7rev3	TCG
-481240	CAPACITOR, fixed: 5/1/41 mica; 6,000 mmf; 1,050 vdcw RMS, 1,500v RMS test, 7 amp at 3,000 kc, 6 amp at 1,000 kc, 3.5 amp at 300 kc, 1.2 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481240-001N2	CAPACITOR, fixed: 5/1/41 NE-481240 w/6,000 mmf p/m 2%; temp coef 001N.	RE48A131 16C40		16-C-32848-4229				CD	PL-1204-6K	CG	P-7762161-8rev3	TCG
-481241	CAPACITOR, fixed: 5/1/41 mica; 2,000 mmf; 1,500 max vdcw, 7.8 amp at 3,000 kc, 7 amp at 1,000 kc, 5 amp at 300 kc, 1.8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481241-001N2	CAPACITOR, fixed: 5/1/41 NT-481241 w/2,000 mmf p/m 2%; temp coef 001N.	RE48A131 16C40		16-C-33488-7056				CD	PL-1205-6K	CG	P-7762161-9rev6	TCG
-481242	CAPACITOR, fixed: 5/1/41 mica; 13,500 mmf; 1,500 max vdcw, 9 amp at 3,000 kc, 8 amp at 1,000 kc, 6.5 amp at 300 kc, 2.8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481242-001N2	CAPACITOR, fixed: 5/1/41 NT-481242 w/13,500 mmf p/m 2%; temp coef 001N.	RE48A131 16C40		16-C-33925-8656				CD	PL-1206-6K	CG	P-7762161-10rev3	TCG

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-442

RESTRICTED

RESTRICTED

SHEET 48 - 443

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481243	CAPACITOR, fixed: 5/1/41 mica; 6,300 mmf; 5,000 vdcw max, 15 amp at 3,000 kc, 17 amp at 1,000 kc, 14 amp at 300 kc, 7.5 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; molded bakelite case; one elliptical cast-aluminum end-cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c.	RE48A132 16C40										
-481243-B5	CAPACITOR, fixed: 5/1/41 NT-481243 w/6,300 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-32960-2242				CD	PL-1194-59	CG	P-7763250-19rev1	TCG
-481244	CAPACITOR, fixed: 5/2/41 mica; 8,000 mmf; 5,000 vdcw max, 15 amp at 3,000 kc, 18 amp at 1,000 kc, 14 amp at 300 kc, 7 amp at 100 kc; case 2 1/2" h x 2 13/16" diam; molded bakelite case; one fl elliptical cast-aluminum end-cap term 3 13/16" lg at ea end w/two 17/64" diam holes 3 1/4" c to c.	RE48A132 16C40										
-481244-B5	CAPACITOR, fixed: 5/2/41 NT-481244 w/8,000 mmf p/m 5%; temp coef ltr B.	RE48A132 16C40		16-C-33223-9242				CD	PL-914-59	CG	P-7763250-20rev1	
-481245	CAPACITOR, fixed: 5/2/41 mica; 7500 mmf; 10,000 vdcw max, 25 amp at 3000 kc, 30 amp at 1000 kc, 20 amp at 300 kc, 10 amp at 100 kc; case 5" diam x 4" h; ceramic case; one fl elliptical end term ea end w/two 3/8" diam holes in ea term 5 3/4" c to c.	RE48A116 16C40										
-481245-B5	CAPACITOR, fixed: 5/2/41 NT-481245 w/7,500 mmf p/m 5%; temp coef ltr B.	RE48A116 16C40		16-C-33198-4193				CD CD	PL-1146-51 PL-243-51	CG	P-7762810-2 rev3	TCG
-481246	CAPACITOR, fixed: 5/2/41 mica; 22,400 mmf; 7,500 vdcw max, 30 amp at 3,000 kc, 40 amp at 1,000 kc, 40 amp at 300 kc, 25 amp at 100 kc; case 5 3/4" h x 5" diam; ceramic case; two elliptical cast aluminum end cap term, ea w/two 0.377" diam holes 5 3/4" c to c.	RE48A237 16C40										
-481246-B5	CAPACITOR, fixed: 5/2/41 NT-481246 w/22,400 mmf p/m 5%; temp coef ltr B.	RE48A237 16C40		16-C-34454-5274				CD	PL-1145-52	CG	P-7762812-2rev4	TCG
-481247	CAPACITOR, fixed: 5/2/41 mica; 3,000 mmf; 25,000 vdcw max, 35 amp at 3,000 kc, 45 amp at 1,000 kc, 35 amp at 300 kc, 19 amp at 100 kc; case 15" lg x 6 1/8" diam; ceramic case; two elliptical end term ea w/two 7/16" diam holes 8 1/2" c to c.	RE48A245 16C40										Com't

SHEET 48-443

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 444

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-48 247-B2	CAPACITOR, fixed: NT-481247 w/3,000 mmf p/m 2%; temp coef ltr B.	5/2/41 RE48A245 16C40		16-C-32191-9691	N16-C-10341-74			CD	PL-1147-156	CG	P-7763299-1rev0	TCG
-481248	CAPACITOR, fixed: mica; 15,000 mmf; 16,000 vdcw max, 35 amp at 3,000 kc 45 amp at 1,000 kc, 35 amp at 300 kc, 20 amp at 100 kc; case 15" lg x 6 1/2" diam; ceramic case; two elliptical end term ea w/two 7/16" diam holes 8 1/2" c to c.	5/2/41										
-481248-B5	CAPACITOR, fixed: NT-481248 w/15,000 mmf p/m 5%; temp coef ltr B.	5/2/41 RE48A245 16C40		16-C-34042-9730				CD	PL-1148-156	CG	P-7763299-2rev0	TCG
-481249	CAPACITOR, fixed: paper dielectric; 4 mf plus 10 minus 3%; 600 vdcw at 330 vacv 60 cyc, 120v DC test; BS metal can; case 3 1/4" h x 2 1/2" wd x 1 3/16" d o/a; pyranol filled; two stud term 1/2" h located on top, spaced 1 1/8" c to c; no int gnd connections; bkt mtg not supplied. NOTE: TBA-13; TBX-2; TEX-4 (3); TEX-4a (3); TCJ-2 (3); TCJ (2); TCJ-1 (2); TCK (5); TCK-1 (5); TCK-2 (5); TCK-3 (5); TCK-4 (5); TCK-5 (5); TCK-6 (5); TCK-7 (5); TDP-1 (2); MK-26 Mod 3 (2); MK-26 Mod 4 (2); MK-11 Mod 1 (2).	5/2/41 RE48A110 RE13A488		16-C-49936-5885	N16-C-11555			CG CG CD	23F103 26F396 KG-3040	CG CFT CEM	P-7763476-3rev1 K-885477-19 MRA-244-1 rev A CO-843 744-342	QFB QFB-1 SF (4) SX (6) TBA-11 TBA-12 SEE NOTE
-481249-10	CAPACITOR, fixed: NT-481249 w/4 mf p/m 10% NOTE: RBS-2 (3); TEX (2); VL.	5/2/41 RE48A110 RE13A488		16-C-49957-5925	N16-C-11555 N16-C-11544-90	R16-C-11607	3DB4-34 3DB4-34.1	CG CG CD	23F103 26F396 KG-3040	CG CFT COL	P-7763476-3rev1 MRA-244-1revA 930 8220 00rev3	RBS-2 (2) RBS-3 (3) RBS-1 (3) SEE NOTE
-481249-20	CAPACITOR, fixed: NT-481249 w/4 mf p/m 20% NOTE: TCS-12 (6); TCS-13 (4); TCS-14 (4); TCS-15 (6).	5/2/41 RE48A110 RE13A488		16-C-49987-9187		R16-C-11612-800		CG CG CD CSF	23F103 26F396 KG-3040 S-7784	CG CFT COL CHE CIR CKP	P-7763476-3rev1 MRA-244-1revA 930 8240 00rev3 CO-772-B	TCS-6 (4) TCS-7 (4) TCS-8 (4) TCS-9 (4) TCS-10 (5) TCS-11 (5) SEE NOTE
-481250	CAPACITOR, fixed: electrolytic; 2,000 mf; 6 vdcw; working temp range minus 20°C to plus 65°C; case 4 3/16" lg x 1 3/8" diam; tubr metal case; four bayonet term 0.355" min lg x 0.093" diam; can connected to term 1 and 3 connection diagram; plug in mtg using octal tube soc- ket.	5/2/42 RE48A294 RE13A549		16-C-21053-4201	N16-C-9735			CAW	AP	CG CHE	K-7879149rev4 CO-852	TBX-2 TBX-4 (2) TBX-4a (2)
-481251	CAPACITOR, FIXED: mica dielectric; 10 mmf; 500 vdcw; 53/64" lg x 53/64" wd x 9/32" d body; molded low loss bakelite body; 2 axial wire leads.	5/13/41 RE48A143 JAN-C-5										

SHEET 48-444

RESTRICTED

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

SHEET 48 - 445

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481251-B10	CAPACITOR, FIXED: 4/6/48 Navy Type 481251 w/10 mmf p/m 10%; temp coef ltr B.	RE48A143	JAN-C-5	16-C-26025-0364				CD	1WLS			
-481251-D5	CAPACITOR, fixed: 5/13/41 NT-481251 w/10 mmf p/m 5%; temp coef ltr D.	RE48A143	JAN-C-5	CM30D100J	16-C-26020-7894			CD	1RS			MX-2
-481252	CAPACITOR, fixed: 5/13/41 mica; 20 mmf; 500 vdcw, 1,000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143	JAN-C-5									
-481252-B10	CAPACITOR, FIXED: 4/13/48 Navy Type 481252 w/20 mmf p/m 10%; temp coef ltr B.	RE48A143	JAN-C-5	16-C-26738-1164				CD	1WLS			
-481252-D5	CAPACITOR, fixed: 5/13/41 NT-481252 w/20 mmf p/m 5%; temp coef ltr D.	RE48A143	JAN-C-5	CM30D200J	16-C-26732-9694	N16-C-9795-14		CD	1RS			MX-2
-481253	CAPACITOR, fixed: 5/13/41 mica; 40 mmf; 500 vdcw, 1,000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143	JAN-C-5									
-481253-D5	CAPACITOR, fixed: 5/13/41 NT-481253 w/40 mmf p/m 5%; temp coef ltr D.	RE48A143	JAN-C-5	CM30D400J	16-C-27392-4694			CD	1RS			MX-2
-481254	CAPACITOR, fixed: mica; 70 mmf; 500 vdcw, 1,000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143	JAN-C-5									
-481254-D2	CAPACITOR, fixed: 5/13/41 NT-481254 w/70 mmf p/m 2%; temp coef ltr D.	RE48A143	JAN-C-5	CM30D700G	16-C-28046-7214	N16-C-9870-4		CD	1RS			MX-2
-481254-D5	CAPACITOR, fixed: 5/13/41 NT-481254 w/70 mmf p/m 5%; temp coef ltr D.	RE48A143	JAN-C-5	CM30D700J	16-C-28051-8694	N16-C-9870-5		CD	1RS	CW		MX-3 MX-4
-481254-B1	CAPACITOR, fixed: 7/4/45 NT-481254 w/70 mmf p/m 1%; temp coef ltr E.	RE48A143	16C40	16-C-28045-7610				CD	1R	COL	912 4704 60rev1	DAB thru DAB-3
-481255	CAPACITOR, fixed: 5/13/41 mica; 200 mmf; 500 vdcw, 1000v DC test; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143	JAN-C-5									
-481255-B5	CAPACITOR, fixed: 5/13/41 NT-481255 w/200 mmf p/m 5%; temp coef ltr B. NOTE: WCA-1; WFA (4).	RE48A143	JAN-C-5	CM30B201J	16-C-29265-3084			CD CSL	1WLS MWBW-1218-5	CBM	744-413	NGA (4) WCA SEE NOTE
-481255-B10	CAPACITOR, fixed: 5/13/41 NT-481255 w/200 mmf p/m 10%; temp coef ltr B.	RE48A143	JAN-C-5	CM30B201K	16-C-29270-3564	N16-C-9967-5		CD CSL	1WLS MWBW-1218-10	CBM	744-545	NGA (2) QGA WFA (2) Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-445

RESTRICTED

RESTRICTED

SHEET 48 - 446

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481255-C2	CAPACITOR, FIXED: 8/28/47 Navy Type 481255 w/200 mmf p/m 2%; temp coef letter C.			16-C-29260-1609				CSL	MNSW 200			QLA-1
-481255-C10	CAPACITOR, fixed: 5/13/41 NF-481255 w/200 mmf p/m 10%; temp coef ltr C.	RE48A143 JAN-C-5	CM30C201K	16-C-29270-3569				CSL CAN CD	MWCW-1218-10 CRW IRS	CAN	817741 aitt1	
-481255-D2	CAPACITOR, fixed: 5/13/41 NF-481255 w/200 mmf p/m 2%; temp coef ltr D.	RE48A143 JAN-C-5	CM30D201G	16-C-29260-1614				CD CSL	IRS MNSDW-200-2			MK-2
-481256	CAPACITOR, fixed: 5/13/41 ceramic dielectric; 10 mmf; neg temp coef 100 (tol p/m 30)mmf/mfd/°C; 500 vdcw; case 0.562" lg x 0.25" diam; axial wire leads; ceramic ins; add suffix indicating capacity tolerance in per cent.											
-481256-10	CAPACITOR, fixed: 5/13/41 NF-481256 w/10 mmf p/m 10%.			16-C-15922-8574	N16-C-8091	R16-C-8352-575		CER	N100K10p/ml	CER	CW	MK-2 MK-3 MK-4
-481257	CAPACITOR, FIXED: 5/13/41 ceramic dielectric; 150 mmf; neg temp coef 680 (tol p/m 102) mmf/mfd/°C; 500 vdcw; case 1 9/64" lg x 5/16" diam; axial wire leads; ceramic ins; add suffix indicating capacity tolerance in per cent.											
-481257-5	CAPACITOR, fixed: 5/13/41 NF-481257 w/150 mmf p/m 5%.			16-C-17397-1330				CER				MK-2
-481258	CAPACITOR, FIXED: 5/13/41 ceramic dielectric; 170 mmf; neg temp coef 680 (tol p/m 102) mmf/mfd/°C; 500 vdcw; case 1 9/16" lg x 5/16" diam; axial wire leads; ceramic ins; add suffix indicating capacity tolerance in per cent.											
-481258-3	CAPACITOR, fixed: 5/13/41 NF-481258 w/170 mmf p/m 3%.			16-C-17518-3038				CER				
-481258-5	CAPACITOR, fixed: 5/13/41 NF-481258 w/170 mmf p/m 5%. NOTE: MK-3 (2); MK-4 (2).			16-C-17525-1330	N16-C-8267	R16-C-8352-570		CER		CW		MK-1 MK-2 SEE NOTE
-481259	CAPACITOR, fixed: 5/13/41 paper dielectric; 500,000 mmf plus 10 minus 3%; 3000 vdcw; ES metal can; case 2 1/2" lg x 1 3/16" wd x 3 7/8" h; dykanol "A" impr and filled; two por ins screw type term 1 1/4" h located on top, spaced 1 1/8" c to c; no int gnd connections; strap mtg not supplied.	RE48A139 RE13A488		16-C-47284-5316				CAW	3009			MK-2

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-446

RESTRICTED

RESTRICTED

SHEET 48 - 447

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481259-10	CAPACITOR, fixed: 5/13/41 NT-481259 w/500,000 mm ² p/m 10%.	RE48A139 RE13A488		16-C-47305-5348	N16-C-11370			CAW	3009	CRV CBM CW	M-95652-5rev4 744-625	SR-2 (3) SU-1 (2) MK-3 (4) MK-4 (4)
-481260	CAPACITOR, fixed: 5/19/41 electrolytic; 40 mf; 25 vdcw; working temp range minus 20°C to plus 65°C; case 2" lg x 3/4" diam; tubr aluminum can; one lug term on top; mtg ring is neg term; two mtg ears spaced 180 deg on 0.24" rad.	RE13A549 RE48A310		16-C-19906-6041	N16-C-9685			CMA CMA	FPS-102 MA-101094	CW		MK-3 MK-4
-481261	CAPACITOR, fixed: 5/14/41 paper dielectric; 4 mf plus 10 minus 3%; 1500 vdcw; BS metal can; case 3 3/4" lg x 1 1/4" wd x 4 5/8" h; oil impr and filled; two por ins ecrew type term 7/8" h located on top, spaced 2" c to c; no int gnd connections; strap mtg not supplied.	RE48A139 RE13A488		16-C-49941-8925			3DB4-55.1 3DB4-125					MK-2
-481261-10	CAPACITOR, fixed: 5/14/41 NT-481261 w/4 mf p/m 10%. NOTE: MK-3 (3); MK-4 (3).	RE48A139 RE13A488		16-C-49962-8936	N16-C-11567			CD CD CAW	T-15040 T-15040G 1509	CW CHEZ	BA-10001-271aa6 00-7100-A	YJ (3) YJ-1 (3) YJ-2 (3) SEE NOTE
-481261-20	CAPACITOR, FIXED: 8/29/49 Navy Type 481261 w/4 mfd p/m 20%.	RE48A139 RE13A488		16-C-49991-8960				CD	T-15040			
-481262	CAPACITOR, fixed: 5/14/41 electrolytic; 125 mf; 350 vdcw; working temp range minus 20°C to plus 65°C; case 3" lg x 1 3/8" diam; tubr aluminum can; one lug term on bottom; mtg ring is neg term; four mtg ears spaced 90 deg on 0.5" rad.	RE13A549 RE48A310		16-C-20292-5171	N16-C-9695		3DB125-1	CMA CMA CMA	FPS-140 MA-101451 FP-140	CW CJF	ES-637016 1aa 3 A-512922 1aa B	MK-3 MK-4 MK-12 MK-12 Mod1
-481263	CAPACITOR, fixed: 5/14/41 electrolytic; three sect; 15/15/40 mf; 450/450/25 vdcw; working temp range minus 20°C to plus 65°C; case 3" lg x 1" diam; tubr aluminum can; three lug term on bottom; can and mtg ring is neg term; three mtg ears spaced 120 deg on 0.368" diam.	RE13A549 RE48A310		16-C-22574-6937	N16-C-12719		3DB40-22	CMA	FP-101355	CW CMA	MA-101355rev0	MK-3 (6) MK-4 (6) MK-12 (2)
-481264	CAPACITOR, fixed: 5/14/41 electrolytic; four sect; 30/30/10/40 mf; 450/450/450/150 vdcw; working temp range minus 20°C to plus 65°C; case 3" lg x 1 3/8" diam; tubr aluminum can; two lug term on bottom spaced 90° on 0.4375" rad; can and mtg ring is neg term; four mtg ears spaced 90 deg on 0.5" rad.	RE13A549 RE48A310		16-C-22997-6646	N16-C-12720			CMA	FP-101456	CW CMA	MA-101456	MK-2 MK-3 (8) MK-4 (8)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-447

RESTRICTED

RESTRICTED

SHEET 48 - 448

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481265	CAPACITOR, fixed: mica; 20,000 mmf; 2000v max vdcw, 12 amp at 3000 kc, 11 amp at 1000 kc, 8 amp at 300 kc, 4 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481265-E2	CAPACITOR, fixed: NT-481265 w/20,000 mmf p/m 2%; temp coef 1tr E.	RE48A131 16C40		16-C-34325-7011	N16-C-10556-3			CD	PL-476-6L	CW		MK-2 MK-3 MK-4 YA-1 YA-2
-481265-F2	CAPACITOR, FIXED: Navy Type 481265 w/20000 mmf p/m 2%; temp coef letter F.		JAN-C-5	GM70P203C	16-C-34325-7026							
-481266	CAPACITOR, fixed: paper dielectric; 650,000 mmf plus 10 minus 3%; 12500 vdcw; HS metal can; case 8" lg x 4" wd x 11" h o/a; #11 impr and sealed; two por ins screw type term 3 5/16" h located on top, spaced 4 1/2" c to c; no int gnd connections; strap mtd not supplied; epcl low impedance construction.	RE48A139 RE13A488		16-C-47855-9990	N16-C-11379-13-5			CD	TK-120065-1	CW CD	SK-4419	MK-2 MK-1 MK-3 MK-4
-481267	CAPACITOR, fixed: paper dielectric; 2000 mmf plus 10 to minus 3%; 600 vdcw; HS metal case w/ins cover; paper case; 1 1/4" lg x 5/8" diam; halowax impr; two axial wire leads; no int gnd connections; for replacement use NT-481267-A.	RE48A163 RE13A488		16-C-40055-9796								
-481267-A	CAPACITOR, fixed: paper dielectric; 2000 mmf p/m 10%; 800 vdcw; molded bakelite case; case 1 3/16" lg x 0.35" dia; mineral oil impr; two axial wire leads; no int gnd connection.	RE48A163 RE48A163										
-481267-10	CAPACITOR, fixed: NT-481267 w/ 2000 mmf p/m 10%; for replacement use NT-481267-10.	RE48A163 RE13A488		16-C-40076-9806				CD	DT-622			YE-1 WE2 (14)
-481267-A10	CAPACITOR, fixed: NT-481267-A w/ 2000 mmf p/m 10%.	RE13A488 RE48A163		16-C-40079-4317				CD	BT-P26	CEM	744-076 411	WE2
-481268	CAPACITOR, variable: air dielectric; neutralizing type; dist type; 2 to 10 mmf, 10 mmf nominal; two plates; one solder lug term; base mtg w/three mtg holes; micrometer thimble adj.						3D70107-32	CNA	NC-800			YC-1

SHEET 48-448

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 449

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481269	CAPACITOR, fixed: 5/20/41 electrolytic; 16 mf; 350 vdcw; working temp range minus 20°C to plus 65°C; case 2" lg x 7/8" diam; BS metal case w/cardboard sleeve; two axial wire leads 3 1/4" lg; neg term gnd to case.	RE13A549 RE48A340		16-C-19667-3506	N16-C-8675-4			CD	BR-1635			YC-1
-481270	CAPACITOR, fixed: 5/28/41 mica; 688 mmf; 5000 max vdcw, 5 amp at 3000 kc, 3.5 amp at 1000 kc, 2 amp at 300 kc, 1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481270-B2	CAPACITOR, fixed: 5/28/41 NT-481270 w/688 mmf p/m 2 1/2; temp coef ltr B. NOTE: TBU-2 (2); TBU-3 (2); TBU-4 (2).	RE48A131 16C40		16-C-30550-5820	N16-C-10064-100			CD	PL-1208-6LS	CAY CAY	T-7609144-14 T-7607321-14	TBU (2) TBU-1 (2) SEE NOTE
-481270-B5	CAPACITOR, fixed: 5/28/41 NT-481270 w/688 mmf p/m 5 1/2; temp coef ltr B.	RE48A131 16C40		16-C-30550-5925	N16-C-10064-100			CD	PL-1208-6LS			
-481271	CAPACITOR, fixed: 5/28/41 mica; 850 mmf; 4240 vacw RMS, 6000v RMS test, 8 amp at 3000 kc, 5 amp at 1000 kc, 3 amp at 300 kc, 1 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481271-B5	CAPACITOR, fixed: 5/28/41 NT-481271 w/850 mmf p/m 5 1/2; temp coef ltr B. NOTE: TBU-2; TBU-3; TBU-4.	RE48A131 16C40		16-C-30823-7475	N16-C-10077-100			CD	PL-735B-6LS	CAY CAY	T-7609144-57 T-7607321-57	TBU TBU-1 SEE NOTE
-481272	CAPACITOR, fixed: 5/28/41 mica; 1700 mmf; 5000 vdcw max, 9 amp at 3000 kc, 5 amp at 1000 kc, 3 amp at 300 kc, 1.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481272-B5	CAPACITOR, fixed: 5/28/41 NT-481272 w/1700 mmf p/m 5 1/2; temp coef ltr B. NOTE: TBU-2 (2); TBU-3 (2); TBU-4 (2).	RE48A131 16C40		16-C-31631-3913	N16-C-10219			CD	PL-736-6LS	CAY CAY	T-7609144-58 T-7607321-58	TBU (2) TBU-1 (2) SEE NOTE

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-449

RESTRICTED

RESTRICTED

SHEET 48 - 450

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481273	CAPACITOR, fixed: mica; 1830 mmf; 3525 vacw RMS, 5000v RMS test, 9 amp at 3000 kc, 5 amp at 1000 kc, 3 amp at 300 kc, 1.8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	5/28/41 RE48A131 16C40										
-481273-B2	CAPACITOR, fixed: NT-481273 w/1830 mmf p/m 2%; temp coef ltr B. NOTE: TBU-2 (2); TBU-3 (2); TBU-4 (2).	5/28/41 RE48A131 16C40		16-C-31681-2982	N16-C-10229-7			CD	PL-1209-61S	CAY CAY	T-7609144-20 T-7607321-20	TBU (2) TBU-1 (2) SEE NOTE
-481273-B5	CAPACITOR, fixed: NT-481273 w/1830 mmf p/m 5%; temp coef ltr B.	5/28/41 RE48A131 16C40		16-C-31681-8892	N16-C-10229-50			CD	PL-1209-61S			
-481274	VACUUM CAPACITOR TYPE: vacuum dielectric; 50 mmf p/m 2%; 32000 vacw, 42000 vact; 6 1/2" lg x 2 1/4" max diam, o/a, glass case w/metal ends; two 11/16" lg x 13/16" diam axial term; mts by term; our rating 30 amp at 3000 kc, 10 amp at 1000 kc, 1 amp at 100 kc.	5/28/41 RE13A488E		16-C-56773-1719	N16-C-7500			CDM	VC-50-32	CAY CG CG CAY	7407897 sub 4 P-7766389-4 K-9241224-21 rev 0 T-7607321-67	TBU (13) TBU-1 (13) TBU-2 (13) TBU-3 (13) TDP-1 (2) SX (4)
-481275	CAPACITOR, fixed: paper dielectric; 100,000 mmf plus 10 minus 3%; 3000 vdcw; ES metal can; case 2 3/4" lg x 1 3/8" diam; castor oil impr and filled; one stud and nut term on por pillar 1 1/4" h in ctr of one end; one side int gnd; removable universal clamp mtg bkt w/ two holes 1 13/16" c to c.	6/2/41 RE48A230 RE13A488		16-C-45764-5506	N16-C-11327-4			CAW	3014			SD SD-1 SD-2 SD-3 SD-4 SD-5 SDa
-481275-10	CAPACITOR, fixed: NT-481275 w/100,000 mmf p/m 10%. NOTE: SD-3 (2); SD-4 (2); SD-5 (3); SR (5); SR-5 (5)	6/2/41 RE48A230 RE13A488		16-C-45785-5506	N16-C-11327-200			CAW	3014	CAY CAY CRV	T-7610944-21 T-7610947-24 K-866432-1 sub 1	SD-1 SD-a SD-2 SEE NOTE
-481276	CAPACITOR, fixed: paper dielectric; 2 sect; 30000 mmf plus 10 minus 3% ea sect; 6000 vdcw ea sect; ES metal can; case 2 3/8" h x 2 3/32" wd x 5 1/64" h; oil impr; three stud term 1 9/16" h located on end on ceramic pillars; no int gnd connections; mtg bkt, four 0.228" diam holes on 4" x 2 21/32" mtg/c.	6/2/41 RE13A488 RE48A322		16-C-52890-9440				CRV	86070-501	CRV	M-86070-501rev10	SD SD-a SD-1 SD-2
-481276-15	CAPACITOR, fixed: NT-481276 w/30,000 mmf p/m 15% ea sect.	6/2/41 RE13A488 RE48A322		16-C-52893-2970	N16-C-11110							

SHEET 48-450

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 451

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481277	CAPACITOR, fixed: 6/2/41 paper dielectric; 100,000 mmf plus 10 minus 3%; 25000 vdcw; HS metal can; case 13 1/2" lg x 4 1/8" wd x 7" h o/a; pyranol impr and filled; two per ins screw type term 4 5/8" h located on top, spaced 6 3/4" c to c; no int gnd connections; strap mtg not supplied; screw term in ctr of top case to gnd case.	RE48A139 RE13A488		16-C-45766-8024	N16-C-11329-250			CG	14-F-52	CRV	K-866959rev1	SD SA SA-1 SA-2 SA-3 SD-a SD-1 thru SD-5
-481278	CAPACITOR, fixed: 6/5/41 paper dielectric; 1 mf plus 10 minus 3%; 600 vdcw; HS metal can; case 2" h x 1 3/4" wd x 1" d o/a; pyranol filled; two stud term 1/2" h located on top, spaced 13/16" c to c; no int gnd connections; BMT mtg not supplied.	RE48A110 RE13A488		16-C-48796-2852	N16-C-11417-1		3DB1.609-1	CG	23F101	CG	P-7763476-1	TCK TAJ-11 TAJ-13 thru TAJ-19 TAQ-10 TCK-1 thru TCK-7
-481278-10	CAPACITOR, fixed: 6/5/41 NT-481278 w/1 mf p/m 10%.	RE48A110 RE13A488		16-C-48817-2827				CD	TJU-6010	CBM	744-215	SX (2)
-481279	CAPACITOR, fixed: 6/6/41 mica; 50 mmf; 500 vdcw; case 53/64" lg x 53/64" wd x 9/32" d max; molded bakelite case; two axial wire leads.	RE48A143 JAN-C-5										
-481279-B10	CAPACITOR, fixed: 6/6/41 NT-481279 w/50 mmf p/m 10%; temp coef 1tr B. NOTE: SK-2 (23); SK-3 (21).	RE48A143 JAN-C-5	CM30B500X	16-C-27634-8764	N16-C-9843-111			CD CAW CAN CAN	1WLS 1467LS CLW K-1450	CG CHL CWQ	P-7762455-8rev7 47B500E1e8D 47X331	TCK RBL-3 RBL-4 SC-3 (22) SEE NOTE
-481279-B20	CAPACITOR, fixed: 6/6/41 NT-481279 w/50 mmf p/m 20%; temp coef 1tr B.	RE48A143 JAN-C-5	CM30B500M	16-C-27640-2244	N16-C-9843-110	R16-C-9843-53-42	3D9050-99	CAN CD CAW	CL 14L 1467L	COL	909 4503 40rev2	TCZ TCZ-1 TCZ-2
-481279-C10	CAPACITOR, fixed: 6/6/41 NT-481279 w/50 mmf p/m 10%; temp coef 1tr C.	RE48A143 JAN-C-5	CM30C500X	16-C-27634-8769				CAN CAW CD	CRW 1467LST 1RS	CAN	817742a1t1	QFA-5 (3) QFA-6 (3)
-481279-D5	CAPACITOR, fixed: 6/6/41 NT-481279 w/50 mmf p/m 5%; temp coef 1tr D.	RE48A143 JAN-C-5	CM30D500J	16-C-27629-8294	N16-C-9843-109			CD CAW	1RS 1464			
-481279-D10	CAPACITOR, fixed: 6/6/41 NT-481279 w/50 mmf p/m 10%; temp coef 1tr D.	RE48A143 JAN-C-5	CM30D500K	16-C-27634-8774	N16-C-9843-104			CD CAW CD CAN	1RS 1464 1WLS "c"			

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

SHEET 48-451

RESTRICTED

RESTRICTED

SHEET 48 - 452

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481280	CAPACITOR ASSEMBLY: 6/11/41 c/o 2 mica capacitors ea 2000 mmf p/m 1/5%, molded bakelite case connected in parallel to be 4000 mmf p/m 1/5%, 600 vdcw, 1000v DC test; 3/4" lg x 3/4" wd x 1/2" d o/a; two axial wire leads.	16C40		16-C-66203-5614				CD	(2) type 1R	CW	ES0-67484-2	MX-2 MX-3 MX-4
-481281	CAPACITOR ASSEMBLY: 6/11/41 c/o 3 mica capacitors ea 3333 mmf p/m 1/5%, molded low loss bakelite case connected in parallel to be 10000 mmf p/m 1/5%, 300 vdcw, 6000v DC test; 3/4" lg x 3/4" wd x 3/4" d o/a; two axial wire leads.	16C40		16-C-66217-3881				CD	(3) type 1R	CW	ES0-679484-1	MX-3 MX-4
-481282	CAPACITOR, fixed: 6/12/41 mica; 300 mmf; 5000 vdcw max, 5.5 amp at 3000 kc, 3.5 amp at 1000 kc, 1.8 amp at 300 kc, 0.6 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term on top 2" h ctr shielded, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" c to c.	RE48A108 16C40										
-481282-B5	CAPACITOR, fixed: 6/12/41 NT-481282 w/300 mmf p/m 5%; temp coef ltr B.	RE48A108 16C40		16-C-29662-9198	N16-C-9995-8 N16-C-9995-9			CRV	UC-3110			
-481283	CAPACITOR, fixed: 6/12/41 mica; 2000 mmf; 6000 vdcw max, 13 amp at 3000 kc, 10 amp at 1000 kc, 6 amp at 300 kc, 3 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term on top 2" h ctr shielded, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" c to c.	RE48A108 16C40										
-481283-A5	CAPACITOR, fixed: 6/12/41 NT-481283 w/2000 mmf p/m 5%; temp coef ltr A.	RE48A108 16C40		16-C-31799-6871	N16-C-10283			CRV	UC-3055A			
-481283-B5	CAPACITOR, fixed: 6/12/41 NT-481283 w/2000 mmf p/m 5%; temp coef ltr B.	RE48A108 16C40		16-C-31799-6878				CRV	UC-3055A			
-481284	CAPACITOR, fixed: 6/12/41 mica; 2500 mmf; 5000 vdcw max, 10 amp at 3000 kc, 8 amp at 1000 kc, 5 amp at 300 kc, 2.5 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 3 1/16" h; cast metal case; one pillar term on top 1 1/2" h ctr shielded, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" c to c.	RE48A108 16C40										
-481284-B5	CAPACITOR, fixed: 6/12/41 NT-481284 w/2500 mmf p/m 5%; temp coef, ltr B.	RE48A108 16C40		16-C-32010-5796	N16-C-10319-14			CD	PL-210-40			
-481284-B10	CAPACITOR, fixed: 6/12/41 NT-481284 w/2500 mmf p/m 10%; temp coef ltr B.	RE48A108 16C40		16-C-32015-6276	N16-C-10319-16							

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-452

RESTRICTED

RESTRICTED

SHEET 48 - 453

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481285	CAPACITOR, fixed: mica; 4000 mmf; 5000 vdcw max, 16 amp at 3000 kc, 15 amp at 1000 kc, 9 amp at 300 kc, 4 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term on top 2" h, ctr shielded, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" c to c.	6/12/41 RE48A108 16C40										
-481285-B5	CAPACITOR, fixed: NT-481285 w/4000 mmf p/m 5%; temp coef ltr B.	6/12/41 RE48A108 16C40		16-C-32458-9598				CRV	UC-3039			
-481285-B10	CAPACITOR, fixed: NT-481285 w/4000 mmf p/m 10%; temp coef ltr B.	6/12/41 RE48A108 16C40		16-C-32464-1076	N16-C-10385-1			CRV	UC-3039			
-481286	CAPACITOR, fixed: mica; 5000 mmf; 5000 vdcw max, 18 amp at 3000 kc, 17 amp at 1000 kc, 13 amp at 300 kc, 6 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term on top 2" h, ctr shielded, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" c to c.	6/12/41 RE48A108 16C40										
-481286-B5	CAPACITOR, fixed: NT-481286 w/5000 mmf p/m 5%; temp coef ltr B.	6/12/41 RE48A108 16C40		16-C-32696-4194				CRV	UC-3031A			
-481287	CAPACITOR, fixed: mica; 10,000 mmf; 3000 vdcw max, 18 amp at 3000 kc, 22 amp at 1000 kc, 15 amp at 300 kc, 7 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term on top 2" h ctr shielded, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" c to c.	6/12/41 RE48A108 16C40										
-481287-A5	CAPACITOR, fixed: NT-481287 w/10,000 mmf p/m 5%; temp coef ltr A.	6/12/41 RE48A108 16C40		16-C-33618-9593	N16-C-10523			CRV	UC-3005			
-481287-B5	CAPACITOR, fixed: NT-481287 w/10,000 mmf p/m 5%; temp coef ltr B.	6/12/41 RE48A108 16C40		16-C-33618-9598	N16-C-10523-200			CRV	UC-3005			
-481288	CAPACITOR, fixed: mica; 20,000 mmf; 3000 vdcw max, 18 amp at 3000 kc, 21 amp at 1000 kc, 16 amp at 300 kc, 8 amp at 100 kc; case 2 1/2" wd x 2 1/4" d x 2 9/16" h; cast metal case; one pillar term on top 2" h, ctr shielded, one side gnd to case; two 1/4" mtg holes in base on 3 1/4" c to c.	6/12/41 RE48A108 16C40										
-481288-B5	CAPACITOR, fixed: NT-481288 w/20,000 mmf p/m 5%; temp coef ltr B.	6/12/41 RE48A108 16C40		16-C-34331-2397	N16-C-10566-1			CRV	UC-2997			

SHEET 48 - 453

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 454

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481289	CAPACITOR, fixed: mica; 4000 mmf; 5000 vdcw max, 11 amp at 3000 kc, 8.5 amp at 1000 kc, 5.5 amp at 300 kc, 2.5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg ft w/ two 3/16" diam mtg holes 2 5/8" c to c.	6/12/41 RE48A131 16C40										
-481289-A5	CAPACITOR, fixed: NT-481289 w/4,000 mmf p/m 5%; temp coef ltr A.	6/12/41 RE48A131 16C40		16-C-32458-9518				CD	PL-184A-6			
-481289-B2	CAPACITOR, FIXED: Navy Type 481289 w/4000 mmf p/m 2%; temp coef letter B.	4/27/48		16-C-32451-8034				CSL	XSBW-3-24-2	CAY	T-7606683-225	TAB-6
-481289-B5	CAPACITOR, fixed: NT-481289 w/4000 mmf p/m 5%; temp coef ltr B. NOTE: TAB-7 (2); TAJ-3 (2); TAJ-4 (2); TAJ-7 (2); TAJ-9 (2) thru TBL (2); TBL-1 (2); TBL-2 thru TBL-13; TBM-4.	6/12/41 RE48A131 16C40		16-C-32458-9523	N16-C-10386			CD	PL-184A-6L	CG CG	P-7762166-6 P-7762166-7	TAB-5 (2) TAB-6 (2) SEE NOTE
-481289-B10	CAPACITOR, fixed: NT-481289 w/4,000 mmf p/m 10%; temp coef ltr B.	6/12/41 RE48A131 16C40		16-C-32464-1003	N16-C-10386-10			CD	PL-184A-6L			
-481290	CAPACITOR, FIXED: mica; 60000/50000 mmf; 2000 vdcw, 20 amp at 25000 kc; case 4" lg x 3 1/2" wd x 4" h; potted in cast metal case; 2 solder lug term near bottom 3 1/2" c to c; 4 holes #10-32 thd 5/16" dia in bottom on 3 1/2" lg x 1 13/16" wd mtg/c; use suffix indicating capacity tolerance in per cent.	6/12/41 RE48A239 16C40										
-481290-B5	CAPACITOR, fixed: NT-481290 w/60,000/50,000 mmf p/m 5%; temp coef ltr B. same as NT-48047 except has #10-32 tapped mtg holes.	6/12/41 RE48A239 16C40		16-C-32433-1826				CRV	UC-2563 Modified	CRV	K-35398aunb0	
-481291	CAPACITOR, fixed: mica; 25 mmf; 6000 vdcw max, 0.9 amp at 3000 kc, 0.3 amp at 1000 kc, 0.1 amp at 300 kc, 0.03 amp at 100 kc; case 2 5/16" lg x 1 17/32" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	6/16/41 RE48A131 16C40										
-481291-A10	CAPACITOR, fixed: NT-481291 w/25 mmf p/m 10%; temp coef ltr A.	6/16/41 RE48A131 16C40		16-C-26951-3701	N16-C-9800			CD	PL-1116A-6			
-481291-B5	CAPACITOR, fixed: NT-481291 w/25 mmf p/m 5%; temp coef ltr B.	6/16/41 RE48A131 16C40		16-C-26946-2231	N16-C-9800-5			CD	PL-1116A-6L	CW		MK-2 MK-3 MK-4

SHEET 48-454

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 455

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E B O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481291-B10	CAPACITOR, FIXED: 7/12/48 Navy Type 481291 w/25 mmf p/m 10%; temp coef letter B.	RE48A131 16C40		16-C-26951-2701	N16-C-9800			CD	6L			
-481292	CAPACITOR, fixed: 6/16/41 mica; 200 mmf; 5000 vdcw max, 3.5 amp at 3000 kc, 1.7 amp at 1000 kc, 0.7 amp at 300 kc, 0.18 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481292-E5	CAPACITOR, fixed: 6/16/41 NT-481292 w/200 mmf p/m 5%; temp coef ltr E.	RE48A131 16C40		16-C-29267-3138	N16-C-9972-2			CD	PL-307-6H	CW		MK-2 MK-3 MK-4
-481292-E20	CAPACITOR, fixed: 6/16/41 NT-481292 w/200 mmf p/m 20%; temp coef ltr E.	RE48A131 16C40		16-C-29277-6098	N16-C-9972			CD	PL-307-6E			
-481293	CAPACITOR, fixed: 6/16/41 paper dielectric, 20,000 mmf plus 10, minus 3%; 15,000 vdcw; BS phenolic tube; case 1 3/4" diam x 8 1/2" lg; dykanol impr and filled; one 1/4"-20 thd stud term in ctr of ea end; no int gnd connections.	RE48A231 RE13A488		16-C-43106-3300				CD CD	PC-1951 BT-3	CW CD	SE-4327 chg F	MK-3 MK-1 MK-4
-481293-10	CAPACITOR, fixed: 6/16/41 NT-481293 w/20,000 mmf p/m 10%.	RE48A231 RE13A488		16-C-43127-4098				CD CD	PC-1951 BT-3	CW	BA10048-1 1ea2	
-481294	CAPACITOR, fixed: 6/16/41 paper dielectric; 500,000 mmf plus 10 minus 3%; 1500 vdcw; BS metal can; 1 13/16" lg x 1 1/16" wd x 2 7/8" h; oil impr and filled; two por ins screw type term 7/8" h located on top, spaced 13/16" c to c; no int gnd connections; strap mtg not supplied; for replacement use NT-481294-A.	RE48A139 RE13A488		16-C-47281-6273								
-481294-10	CAPACITOR, fixed: 6/16/41 NT-481294 w/500,000 mmf p/m 10%.	RE48A139 RE13A488		16-C-47302-6263	N16-C-11363	R16-C-11710-40	3DA500-190	CD	T-15005	CW		MK-3 MK-1 (2)
-481294-A	CAPACITOR, fixed: 4/29/44 paper dielectric; 500,000 mmf plus 10, minus 3%; 2000 vdcw; BS metal can; case 1 13/16" lg x 1 1/16" wd x 2 7/8" h; oil impr and filled; two por ins screw type term 7/8" h, located on top, spaced 13/16" c to c; no int gnd connections; strap mtg not supplied.	RE13A488 RE48A139		16-C-47283-2879								AN/SPA-1
-481294-A10	CAPACITOR, fixed: 4/29/44 NT-481294-A w/500,000 mmf p/m 10%. NOTE: AN/SPA-6A (2).	RE13A488 RE48A139		16-C-47304-2874	N16-C-11365-200		3DA500-247	CIE CIE	SAK 208AR50	CGG	8B52262rev0	AN/ APA-6(2) SEE NOTE

SHEET 48-455

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

RESTRICTED

RESTRICTED

SHEET 48 - 456

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481295	CAPACITOR, fixed: mica; 5000 mmf; 250 vacw; case 2" lg x 1" wd x 3/8" h; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom, ea w/0.10" mtg holes 1 1/4" mtg/c.	6/16/41 RE48A106 16C40										
-481295-B3	CAPACITOR, fixed: mica; 5000 mmf; 250 vacw; case 2" lg x 1" wd x 3/8" h; potted in sheet metal case; two axial wire leads rubber covered; two mtg tabs on bottom, ea w/0.10" mtg holes 1 1/4" mtg/c.	6/16/41 RE48A106 16C40		16-C-32693-5473				CRV	UC-2909A	CRV	DL-UC-2909A-501	
-481296	CAPACITOR, fixed: mica; 25,000 mmf; 1500 max vacw, 15 amp at 3000 kc, 15 amp at 1000 kc, 12 amp at 300 kc, 5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	6/27/41 RE48A131 16C40										
-481296-B2	CAPACITOR, fixed: mica; 25,000 mmf; 1500 max vacw, 15 amp at 3000 kc, 15 amp at 1000 kc, 12 amp at 300 kc, 5 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	6/27/41 RE48A131 16C40		16-C-34536-5834	N16-C-10569			CRV	UC-3373 Case 351	CRV	K-856829-6 rev4	WEA
-481297	CAPACITOR, fixed: mica; 35,000 mmf; 1500 max vacw, 15 amp at 3000 kc, 17 amp at 1000 kc, 14 amp at 300 kc, 6 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	6/27/41 RE48A131 16C40										
-481297-B2	CAPACITOR, fixed: mica; 35,000 mmf; 1500 max vacw, 15 amp at 3000 kc, 17 amp at 1000 kc, 14 amp at 300 kc, 6 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	6/27/41 RE48A131 16C40		16-C-34853-1634				CRV	UC-3374 Case #351	CRV	K-856829-5 rev4	WEA
-481298	CAPACITOR, fixed: mica; 75,000 mmf; 1500 max vacw, 15 amp at 3000 kc, 15 amp at 1000 kc, 20 amp at 300 kc, 8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	6/27/41 RE48A131 16C40										
-481298-B2	CAPACITOR, fixed: mica; 75,000 mmf; 1500 max vacw, 15 amp at 3000 kc, 15 amp at 1000 kc, 20 amp at 300 kc, 8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	6/27/41 RE48A131 16C40		16-C-35723-5834	N16-C-10600			CRV	UC-3373 Case #351	CRV	K-856829-7 rev4	WEA WEA-1 (2)

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-456

RESTRICTED

RESTRICTED

SHEET 48 - 497

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481299	CAPACITOR, fixed: 6/27/41 mica; 50,000 mmf; 500 vdcw, 11 amp at 3000 kc, 10 amp at 1000 kc, 8 amp at 300 kc, 5 amp at 100 kc; case 2 1/16" lg x 61/64" wd x 1 17/32" h; molded bakelite case; two screw term 7/16" lg 1 1/2" c to c on top; two mtg feet on bottom, ea w/ hole 0.15" diam, holes 2 3/8" c to c.	RE48A222 16C40										
-481299-B5	CAPACITOR, fixed: 6/27/41 NT-481299 w/50,000 mmf p/m 5%; temp coef ltr B.	RE48A222 16C40		16-C-35226-7188				CRV	UC-2989	CRV	K-856829-10rev4	WEA
-481300	CAPACITOR, fixed: 6/27/41 mica; 250 vdcw max, 16 amp at 3000 kc, 20 amp at 1000 kc, 16 amp at 300 kc, 12 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481300-B5	CAPACITOR, fixed: 6/27/41 NT-481300 w/ 250,000 mmf p/m 5%; temp coef ltr B.	RE48A131 16C40		16-C-37072-8036	N16-C-10710			CRV	UC-2980 case #351	CRV	K-856829-8 rev4	WEA WEA-1 (2)
-481300-B20	CAPACITOR, fixed: 6/27/41 T-481300 w/250,000 mmf p/m 20%; temp coef ltr B.	RE48A131 16C40		16-C-37083-3096								
-481301	CAPACITOR, fixed 6/27/41 mica; 100,000 mmf; 750 vdcw max, 16 amp at 3000 kc, 20 amp at 1000 kc, 15 amp at 300 kc, 8 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" h on 1 5/8" ctr; two 3/16" mtg holes on bottom on 2 5/8" mtg/c.	RE48A131 16C40										
-481301-B5	CAPACITOR, fixed: 6/27/41 NT-481301 w/100,000 mmf p/m 5%; temp coef ltr B. NOTE: QCX(3); QCY(3); QCZ(3).	RE48A131 16C40		16-C-36150-2748	N16-C-10645			CRV	UC-2984 case #351	CRV	K-856829-9rev4	WEA QCW(3) SEE NOTE
-481302	CAPACITOR, fixed: 8/11/42 mica; 500 mmf; 500 vdcw; case 1 1/4" lg x 5/8" wd x 1/4" thk; molded bakelite case; two solder lug term on front sides ea w/one 5/32" hole on 1 3/4" ctr; two 9/64" diam mtg holes on back of case 1 1/4" c to c.	RE48A301 16C40										
-481302-A10	CAPACITOR, fixed: 8/11/42 NT-481302 w/ 500 mmf p/m 10%; temp coef ltr A.	RE48A301		16-C-30167-2555				CAW	1460			LF-2

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-497

RESTRICTED

RESTRICTED

SHEET 48 - 498

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481303	CAPACITOR, fixed: paper dielectric; 2 mf plus 10 minus 3%; 1000 vdcw; HS metal can; case 1 7/8" lg x 1" wd x 4" h; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 13/16" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 0.213" diam mtg holes 13/32" apart 2 3/8" c to c.	6/27/41 RE48A159 RE13A488		16-C-49179-7232	N16-C-11490-25			CG CG	25F342 23F11	CRV	M-418141-11rev0	WEA OT OT-1
-481304	CAPACITOR, fixed: paper dielectric; 8 mf plus 10 minus 3%; 1500 vdcw; HS metal can; case 3 7/8" lg x 2 9/16" wd x 4 3/4" h o/a; oil impr and filled; two ceramic ins screw type term 1 1/8" h located on top 2" c to c; no int gnd connections; two mtg fl on bottom of case ea w/two 9/32" diam mtg holes 1 1/4" apart 4 1/2" c to c.	6/27/41 RE48A159 RE13A488		16-C-51461-9119	N16-C-11647			CG	25F341	CRV	K-860217-13rev7	WEA
-481305	CAPACITOR, fixed: electrolytic; 75 mf; 25 vdcw, 40v DC surge; working temp range minus 20°C to plus 65°C; case 2 3/4" lg x 1 3/8" diam; HS metal case; two solder lug term 13/32" h on top; term ins from case; mtg neck 1/2" lg 7/8"-16 thd w/lockwasher and nut.	7/3/41 RE13A549 RE48A345		16-C-20081-7161	N16-C-9693					CRV	K-90556-1	TBF TDQ
-481306	CAPACITOR, fixed: paper dielectric; 8 mf plus 10 minus 3%; 1000 vdcw; HS metal can; case 3 3/4" lg x 1 1/4" wd x 4 3/4" h o/a; dykanol "A" impr and filled; two por ins screw type term 7/8" h located on top, spaced 2" c to c; no int gnd connections; strap mtg not supplied.	7/14/41 RE48A139 RE13A488		16-C-51460-2437				CD	T-10060	CRP	L-74955-3revJ	MK-4
-481306-10	CAPACITOR, FIXED: Navy Type 481306 w/8 mfd p/a 10%.	12/2/48		16-C-51481-2452				CD	T-10080	CRP	L-74955-3	AN/MPN-1A
-481306-20	CAPACITOR, FIXED: Navy Type 481306 w/8 mfd p/m 20%.	5/7/49		16-C-51509-9200				CD	TWH10060			
-481307	CAPACITOR, fixed: electrolytic; 500 mf; 6 vdcw, 9v peak; working temp range minus 20°C to plus 65°C; case 2 1/2" lg x 1 3/8" diam; tubr metal case; four bayonet term 0.355" min lg x 0.093" diam; term #7 pos, #1 neg, #3, 5 no connection; plug-in mtg using octal tube socket.	7/23/41 RE48A294 RE13A549		16-C-20653-3051	N16-C-9699			CAW	AEP	CG CHE	K-7881182-2rev2 CO-838	TBX-2 TBX-4 TBX-4a
-481308	CAPACITOR, fixed: electrolytic; 30 mf; 150 vdcw, 200v DC peak; working temp range minus 20°C to plus 65°C; case 2 1/2" lg x 1 3/8" diam; tubr metal case; four bayonet term 0.355" min lg x 0.093" diam; term #5 pos, #3 neg, #1, 7 no connection; plug-in mtg using octal tube socket.	7/23/41 RE48A294 RE13A549		16-C-19864-1041	N16-C-9684			CAW	APP	CG CHE	K-7881182rev2 CO-836	TBX-2 TBX-4 TBX-4a

SHEET 48-498

RESTRICTED

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

RESTRICTED

SHEET 48 - 459

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481309	CAPACITOR, fixed: 7/23/41 paper dielectric; two sect; 1 mf/1 mf plus 10 minus 3%; 250/250 vdcw, 150v AC; ES metal can; case 4 1/2" lg x 3 1/4" wd x 1 7/8" thk; wax impr and filled; two stud and nut term 1 1/2" c to c at ea end; no int gnd connections; bent mtg bkt welded to can w/two 5/16" mtg holes 5 7/8" c to c on bottom.	RE13A488		16-C-53803-9010								
-481309-10	CAPACITOR, fixed: 7/23/41 NT-481309 w/1 mf/1 mf p/m 10%.	RE13A488		16-C-53847-6700				CR	UC-2323	CG CR	K-5825565 231B-21	
-481309-15	CAPACITOR, fixed: 7/23/41 NT-481309 w/1 mf/1 mf p/m 15%.	RE48A232 RE13A488		16-C-53886-8105	N16-C-11436							
-481310	CAPACITOR, fixed: 7/28/41 mica; 15000 mmf; 2000 max vdcw, 12 amp at 3000 kc, 12 amp at 1000 kc, 8 amp at 300 kc, 4 amp at 100 kc; case 2 5/16" lg x 1 1/4" wd x 1 27/32" h; molded bakelite case; two stud term on top 7/16" lg 1 5/8" c to c; two mtg feet w/ two 3/16" diam mtg holes 2 5/8" c to c.	RE48A131 16C40										
-481310-E2	CAPACITOR, fixed: 7/28/41 NT-481310 w/15,000 mmf p/m 2%; temp coef 1tr E.	RE48A131 16C40		16-C-34035-5621	N16-C-10540			CD	PL-784-6R	CW		ME-3 ME-4
-481310-E5	CAPACITOR, fixed: 7/28/41 NT-481310 w/15,000 mmf p/m 5%; temp coef 1tr E.	RE48A131 16C40		16-C-34040-7101	N16-C-10540-4			CD	PL-784-6R			
-481311	CAPACITOR, fixed: 7/29/41 paper dielectric; 50,000 mmf plus 10 minus 3%; 600 vdcw; ES metal can; case 1 13/16" lg x 1" wd x 3/4" h o/a; oil impr and filled; two solder lug term 3/8" h on side, spaced 1" c to c; no int gnd connections; two mtg ft 3/8" wd flush w/bottom, w/3/16" diam mtg holes spaced 2 1/8" c to c; for replacement use NT-481203.	RE13A488 RE48A129		16-C-44236-3119	N16-C-11165		3DA500-97.5 3DA500-97.20 3DA500-263	CD CIE CSL CQU CGF	DYR-6005 7002 XIRCW6-.05 AM126 N-7002	CW CZC	ES-682028-31ee4 70021ee3	Con't

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL

NAVSHIPS 900,109(A)
SUPPLEMENT # 1

SHEET 48-459

RESTRICTED

RESTRICTED

SHEET 48 - 460

NAVY TYPE DESIGNATION	NAME AND DESCRIPTION	NAVY DWG OR SPEC NO	JAN NO	STANDARD NAVY STOCK NO	E S O STOCK NO	A S O STOCK NO	SIGNAL CORPS STOCK NO	MFGR	MANUFACTURER'S PART NUMBER	CONTRACTOR	CONTRACTOR'S DWG OR PART NO	EQUIPMENT USED IN
-481311-10	CAPACITOR, fixed: NT-481311 w/50,000 mmf p/m 10%.	7/29/41 RE13A488 RE48A129		16-C-44257-3129	N16-C-11165		3DA500-45 3DA500-97.10 3DEA500-121	CSL CSF CGF CQU CBV CIE CD CAW CTD	XIRCW6-.05-10 FBTS-396A N-7002 AHL26 12M-1-20 7002 DYR-6005 630-.05 RLO-6005	CIP COL CW	ES-13105 956 2184 20 ES-682063-51	ST TCB-1 TCB-2 MK-9 MK-18
-481311-20	CAPACITOR, fixed: NT-481311 w/50,000 mmf p/m 20%.	7/29/41 RE13A488 RE48A129		16-C-44287-7453			3DA500-68 3DA500-237	CD CIE CSL CQU CGF	DYR-6005 7002 XIRCW6-.05-20 AHL26 N-7002	CFT COL	RF-2619-1-4 956 2184 40	DAU DAU-1
-481312	CAPACITOR, fixed: electrolytic; three sect; 40/40/40 mf; 450/450/450 vdcw; working temp range minus 20°C to plus 65°C; case 3" lg x 1 1/8" diam; tubr aluminum can; three lug term on bottom spaced 120 deg on 0.3125" rad; mtg ring is neg term; three mtg ears spaced 120 deg on 0.368" rad.	9/20/41 RE48A310 RE13A549		16-C-22740-8506				CMA	FP-TS7966			
-481313	CAPACITOR, fixed: paper dielectric; three sect; 4/8/8 mfd plus 10 minus 3%; 650 vdcw ea sect; RS metal can 4 1/4" lg x 2 1/8" wd x 5 7/16" h; four thd studs 3/8" h w/ solder lugs and nuts, located on bottom in two pr on 7/8" x 1" ctr, terms off set from ctr of case; no int gnd connections; two fl ea w/ two #12 drill holes on 2" x 4 3/4" mtg/c.	8/11/41 RE13A488		16-C-54733 7685				CSF CIE	F8734 7392F	CEL CEL	1170 rev A 42043	RBK RBK-12 RBK-13 RBK-14 RDC-1
-481313-20	CAPACITOR, fixed: NT-481313 w/4/8/8 mf p/m 20%.	8/11/41 RE48A304 RE13A488		16-C-54735-4051	N16-C-12716-12			CSF CIE	F-8734 7392F			
-481314	CAPACITOR, fixed: mica; 50 mmf; 500 vdcw, 1000 vdcw; case 1 1/16" lg x 15/32" wd max x 7/32" thk max; molded bakelite case; two axial wire leads.	8/11/41 RE48A233 JAN-C-5										
-481314-D1	CAPACITOR, FIXED: Navy Type 481314 w/50 mmf p/m 1%; temp coef letter D.	1/16/48 RE48A233 RE48A154		16-C-27623-8810				CER CD	MIJ 2R	CRR CZR	A18253-1 220751	SCR 624A SCR 624B
-481314-D2	CAPACITOR, fixed: NT-481314 w/50 mmf p/m 2%; temp coef 1tr D.	8/11/41 RE48A233 JAN-C-5	CM25D500C	16-C-27624-7019	N16-C-9843-99 N16-C-9843-98			CD CAW CFW	2R 1479 BSC	CRR	35-5019	SG-1(2) SG-28(2) SM-1 Con't

SHEET 48-460

RESTRICTED

NAVSHIPS 900.109(A)
SUPPLEMENT # 1

CATALOG OF NAVY TYPE ELECTRONIC MATERIAL