

2. MULTIPLE WIRE DETECTOR

2.1. INTRODUCTION

2.1.1. Visual Inspection

CHECK THE WIREWORK AND JUNCTION

WARNING

Do not touch any electrical wires unless you are qualified to do so. Always use proper safety procedures when working with electrical systems.

To do:

Check the wiring harness for any damage or loose connections. Repair or replace any damaged wires or loose connections.

Note:

Do not touch any electrical wires unless you are qualified to do so. Always use proper safety procedures when working with electrical systems.



2.1.2. Visual Inspection

2.1.2.1. Visual Inspection

CHECK THE WIREWORK

WARNING

Do not touch any electrical wires unless you are qualified to do so. Always use proper safety procedures when working with electrical systems.

To do:

Check the wiring harness for any damage or loose connections. Repair or replace any damaged wires or loose connections.



2.1.3. Visual Inspection

WARNING

Do not touch any electrical wires unless you are qualified to do so. Always use proper safety procedures when working with electrical systems.

To do:

Check the wiring harness for any damage or loose connections. Repair or replace any damaged wires or loose connections.

Note:

Do not touch any electrical wires unless you are qualified to do so. Always use proper safety procedures when working with electrical systems.



1.00 SECTION SUMMARY

1.0100 CASING

1.0110 Summary

1.0110.01 CASING, STEEL, SCHEDULE 40, 4" DIA.
 1.0110.02 CASING, STEEL, SCHEDULE 40, 6" DIA.

1.0120 Notes

1.0120.01 CASING SHALL BE PROVIDED WITH INSULATION
 AS SHOWN ON THE DRAWINGS AND SHALL BE
 INSTALLED WITH THE INSULATION FIRST.

1.0120.02 THE CASING SHALL BE PROVIDED WITH
 INSULATION AND SHALL BE INSTALLED WITH THE
 INSULATION FIRST.

CASING WITH INSULATION FIRST



1.02100 CASING

1.02100 Summary

1.02100.01 CASING, STEEL, SCHEDULE 40, 4" DIA.
 1.02100.02 CASING, STEEL, SCHEDULE 40, 6" DIA.
 1.02100.03 CASING, STEEL, SCHEDULE 40, 8" DIA.

1.02100 Notes

1.02100.01 CASING SHALL BE PROVIDED WITH INSULATION
 AS SHOWN ON THE DRAWINGS AND SHALL BE
 INSTALLED WITH THE INSULATION FIRST.

1.02100.02 THE CASING SHALL BE PROVIDED WITH
 INSULATION AND SHALL BE INSTALLED WITH THE
 INSULATION FIRST.



INSULATION FIRST

CASING



1.03100 CASING

1.03100 Summary

1.03100.01 CASING, STEEL, SCHEDULE 40, 4" DIA.
 1.03100.02 CASING, STEEL, SCHEDULE 40, 6" DIA.
 1.03100.03 CASING, STEEL, SCHEDULE 40, 8" DIA.

1.03100 Notes

1.03100.01 THE CASING SHALL BE PROVIDED WITH
 INSULATION AS SHOWN ON THE DRAWINGS AND
 SHALL BE INSTALLED WITH THE INSULATION
 FIRST.

100. **Section: Endometriosis**

ENDOMETRIAL BIOPSY ASSEMBLY



ENDOMETRIAL BIOPSY

ENDOMETRIAL BIOPSY HANDLE

- DESCRIPTION:**
 This handle may contain a spring and/or a stop and may be attached to the biopsy layer.
- IN USE:**
 The endometrial biopsy handle is used to insert the biopsy layer into the uterus.

ENDOMETRIAL BIOPSY LAYER

- DESCRIPTION:**
 The endometrial biopsy layer is used to collect the biopsy sample.
- IN USE:**
 The endometrial biopsy layer is inserted into the uterus and used to collect the biopsy sample.
- NOTE:** The endometrial biopsy layer is used to collect the biopsy sample.



5200 - Gas Valve Assembly (continued)

NOTE

**ALL PARTS MUST BE USED FROM THE ORIGINAL
MANUFACTURER OR AN EQUIVALENT. ALWAYS USE THE
LATEST REVISION OF THIS INSTRUCTIONS.**



CLIMATE AND ALTITUDE


WARNING
 The gas valve is designed to operate at sea level. Do not use at altitudes above 5000 feet (1524 m) unless approved by the manufacturer.

VENTILATION AND EXHAUSTION

WARNING
 Always use proper ventilation and exhaust systems. Do not use in enclosed spaces.



2.01. THEORETICAL WORK KNOWLEDGE (WORK)



2.00 - Cast In-Place Concrete Slab

2.01 - Cast In-Place Concrete Slab

Notes:
 1. Slab shall be cast in place and
 finished to a smooth surface.
 2. Slab shall be cast in place and
 finished to a smooth surface.



2.02 - Cast In-Place Concrete Slab

Notes:
 1. Slab shall be cast in place and
 finished to a smooth surface.
 2. Slab shall be cast in place and
 finished to a smooth surface.



2.03 - Cast In-Place Concrete Slab

Notes:
 1. Slab shall be cast in place and
 finished to a smooth surface.
 2. Slab shall be cast in place and
 finished to a smooth surface.



2.03 - Cast In-Place Concrete Slab

6.27 **Typical Reinforcement Arrangement (BS 5400-6:1991)**

